Multifuser Wood 36 White





Main Office, R&D and Logistics

Avenida do Polo 3, nº159, 4590-137 Carvalhosa Paços de Ferreira - Portugal Tlm . +351 917 851 019

Rua Quinta do Bom Retiro nº16, Armazém 9 2820-690 Charneca da Caparica - Portugal Tel . +351 212 964 100 Fax . +351 212 964 101

Vicoustic USA

5701 Sixth Avenue South, Suite 229 Seattle, WA 98108 Tel . (206) 767-2020 E-mail . info@vicousticusa.com

www.vicousticusa.com

Made from solid wood, the new diffuser is perfect for use in venues such as concert halls, hi-fi rooms and recording studios, where effective diffusion is often required, without too much absorption occurring at the same time. With its striking angled surface, the two-dimensional diffuser is based on a QRD sequence combined with changing reflection techniques (a result of the angled surface).

The panel itself is made in two parts. Each part can be rotated in different directions so that a uniform, omni-directional scattering of sound is achieved, with particularly effective diffusion of mid and low frequencies. Multifuser Wood 36 works between 470Hz and 10kHz. As well as its acoustic efficiency, the panel's attractive appearance makes it suitable for use in a range of settings. Available in Light Brown, Black and White finishes.

Applications:

Conference Rooms, Classrooms, Auditoriums, Hi-Fi and Home Cinema

Ref: U00003 Main Info

> EAN13: 5600301843037 HS-Code: 44101110

Dimensions: 595.0 x 595.0 x 75.0 mm

Scratch Resistance: No

Washable: No

Performance

Functionality: Diffusion

Absorption Frequency: Medium

NRC: 0.350

Fire Class European (EN): Euroclass E

Shipping

Units Per Box: 1 box

Box Dimensions: 605.0 x 309.0 x 118.0 mm

Box Weight: 13.2 kg

Row Materials | Material: Wood

Wood Type: Mdf Painted

Technical File

Multifuser Wood 36 White



Design Wood Color: White

Edges: Angled

Installation Place: Wall

Fixing Type: Screwed, Glued

Technical File