



Main Office, R&D and Logistics

Avenida do Polo 3, nº159,
4590-137 Carvalhosa
Paços de Ferreira - Portugal
Tlm . +351 917 851 019

Office 2

Rua Quinta do Bom Retiro nº16, Armazém 9
2820-690 Charneca da Caparica - Portugal
Tel . +351 212 964 100
Fax . +351 212 964 101
E-mail . info@vicoustic.com

Vicoustic USA

5701 Sixth Avenue South, Suite 229
Seattle, WA 98108
Tel . (206) 767-2020
E-mail . info@vicousticusa.com

www.vicousticusa.com

Flexi Wood A50 is a panel dedicated to the control of medium and medium-low frequencies. It acts simultaneously as an absorber and a reflector, controlling excess energy in a room without compromising its ambience. This helps to create listening spaces with a natural, bright sound.

The panel's revolutionary design is further enhanced by the addition of a wood surface. Long known for its excellent acoustic properties, the wood also adds elegance and modernity to the panel, making it suitable for use in any type of space.

The Flexi Wood panel is available in two different thicknesses for use in different frequency ranges. Flexi Wood A50 is designed to perform to maximum effect between 400 and 1250 Hz.

Applications:

Listening Rooms, Home Theatres, Recording and Broadcast Studios, Post Production Studios, Performance Spaces, Rehearsal Rooms, Conference and Teleconference Rooms, Public Spaces, Auditoriums, etc.

Main Info

Ref: B00048
EAN13: 5600301846724
HS-Code: 39211310
Dimensions: 600.0 x 600.0 x 54.0 mm
Scratch Resistance: No
Washable: No

Performance

Functionality: Absorption
Absorption Frequency: Medium
alpha with Shape Indicators: 0.45 (M)
NRC: 0.550
Fire Class European (EN): Euroclass E
Fire Class France (NF P): M1

Shipping

Units Per Box: 8 boxes
Box Dimensions: 620.0 x 620.0 x 495.0 mm
Box Weight: 15.3 kg

Technical File

Flexi Wood A50 Wenge



Row Materials	Material: Wood, Foam Wood Type: Mdf Painted Foam Type: M1
----------------------	---

Design	Wood Color: Black Edges: Angled
---------------	------------------------------------

Installation	Place: Wall, Ceiling Fixing Type: Glued
---------------------	--

Technical File