Super Fuser Spyke 2





Main Office, R&D and Logistics

Avenida do Polo 3, nº159, 4590-137 Carvalhosa Paços de Ferreira - Portugal Tlm . +351 917 851 019

Office 2

Rua Quinta do Bom Retiro nº16, Armazém 9 2820-690 Charneca da Caparica - Portugal Tel . +351 212 964 100 Fax . +351 212 964 101

Vicoustic USA

5701 Sixth Avenue South, Suite 229 Seattle, WA 98108 Tel . (206) 767-2020 E-mail . info@vicousticusa.com

www.vicousticusa.com

Manufactured in high quality EPS (Expanded Polystyrene), the Super Fusor Spyke 2 works as a sound energy redirector, fixing frequent room problems such as speech intelligibility and musical imprecision. Applied on ceilings to treat medium and high frequencies, our Super Fuser Spyke 2 redistributes sound across the room, generating a more uniform listening ambience.

Thanks to its mathematical geometry, Super Fuser Spyke 2 works in a more moderate way, compared with common diffusion products, avoiding excessive flutter. Its effective performance, aesthetic design, ease of installation and attractive price make Super Fuser Spyke 2 a top seller.

- Highly efficient diffusion
- Exceptional design
- Ease of installation
- Can be painted with water-based paints

Applications:

Recording and Broadcast Studios, Post Production Studios, Listening Rooms, Conference and Teleconference Rooms, Lecture Halls, Distance Learning Rooms, Public spaces, Auditoriums, Performance spaces, etc.

Main Info

Ref: B00002

EAN13: 5600217588893 HS-Code: 39031100

Dimensions: 600.0 x 600.0 x 125.0 mm

Scratch Resistance: No

Washable: No

Performance

Functionality: Diffusion

Absorption Frequency: Medium

NRC: 0.000

Fire Class European (EN): Euroclass E

Fire Class France (NF P): M1

Technical File

Super Fuser Spyke 2



Shipping Units Per Box: 6 boxes

Box Dimensions: 630.0 x 630.0 x 620.0 mm

Box Weight: 7.4 kg

Row Materials | Material: Polystyrene

Polystyrene Density: 60.0

Design Polystyrene Color: White

Edges: Angled

Installation Place: Wall

Fixing Type: Glued

Technical File