



Main Office, R&D and Logistics

Avenida do Polo 3, nº159,
4590-137 Carvalhosa
Paços de Ferreira - Portugal
Tlm . +351 917 851 019

Office 2

Rua Quinta do Bom Retiro nº16, Armazém 9
2820-690 Charneca da Caparica - Portugal
Tel . +351 212 964 100
Fax . +351 212 964 101
E-mail . info@vicoustic.com

Vicoustic USA

5701 Sixth Avenue South, Suite 229
Seattle, WA 98108
Tel . (206) 767-2020
E-mail . info@vicousticusa.com

www.vicousticusa.com

Anti-vibration wall mountings for partition walls. Designed to prevent structural transmission and provide maximum structural stability. Highly recommended for absorption of vibrations produced by airborne and impact noise. These units are a must in walls with sizable dimension.

Advantages The system combines specially designed materials and techniques allowing vibration reduction in both directions. It has a security system to prevent the complete collapse of the treatment in case of fire. **Characteristics** Suited for steel studs with dimensions: 48mm, 70mm, 90mm. **Installation** The first unit should be applied 1,50m from the floor. The second unit should be applied 3,00m from the floor. So on and so forth. The last unit should be applied between 10-30cm from the acoustic ceiling. Remember that the installation of the wall mountings should be in a criss-cross sequence (please see the installation procedure sheets).

Main Info

Ref: B00482
EAN13: 5600301841965
HS-Code: 68069000

Performance

Mounting Width: 48, 70 and 90mm
Load Weight Range: 10.00 to 70.00 Kg

Installation

Place: Wall
Steel: Yes
Fire Security Devices: Yes
Plate Thickness: 1.5 mm

Shipping

Units Per Box: 50 boxes
Box Dimensions: 625.0 x 329.0 x 188.0 mm
Box Weight: 14.1 kg

Technical File