



Main Office, R&D and Logistics

Avenida do Polo 3, nº159,
4590-137 Carvalhosa
Paços de Ferreira - Portugal
Tlm . +351 917 851 019

Office 2

Rua Quinta do Bom Retiro nº16, Armazém 9
2820-690 Charneca da Caparica - Portugal
Tel . +351 212 964 100
Fax . +351 212 964 101
E-mail . info@vicoustic.com

Vicoustic USA

5701 Sixth Avenue South, Suite 229
Seattle, WA 98108
Tel . (206) 767-2020
E-mail . info@vicousticusa.com

www.vicousticusa.com

Advanced anti-vibration system for ceiling suspension. Consists of a steel spring and rubber to achieve maximum isolation performance on low + medium + high frequencies. Now comes with a new security system to guarantee better resistance and higher security.

Advantages The steel spring provides an excellent degree of vibration insulation in the low/medium frequencies. - The rubber provides an important vibration isolation of the medium/high frequencies. - The combination of these 2 components make the best anti-vibration system for ceiling suspension.

Main Info

Ref: B00473
EAN13: 5600301841859
HS-Code: 68069000

Performance

Mounting Width: 60 mm
Rupture Point: 350.00 Kg
Load Weight Range: 11.00 to 36.00 Kg

Installation

Place: Ceiling
Steel: Yes
Rubber Color: Green
Security Devices: 1
Fire Security Devices: No

Shipping

Units Per Box: 50 boxes
Box Dimensions: 0.0 x 0.0 x 0.0 mm
Box Weight: 0.0 kg

Technical File