

Main Office, R&D and Logistics

Avenida do Polo 3, nº159,
4590-137 Carvalhosa
Paços de Ferreira - Portugal
Tlm . +351 917 851 019

Office 2

Rua Quinta do Bom Retiro nº16, Armazém 9
2820-690 Charneca da Caparica - Portugal
Tel . +351 212 964 100
Fax . +351 212 964 101
E-mail . info@vicoustic.com

Vicoustic USA

5701 Sixth Avenue South, Suite 229
Seattle, WA 98108
Tel . (206) 767-2020
E-mail . info@vicousticusa.com

www.vicousticusa.com

This acoustic panel consists of advanced acoustic foam technology allowing the highest absorption properties and an excellent fire rating standard. The Visquare Tech can also have a white or black finish and also has a Premium version where the panel is covered in a colored fabric, available in 8 colors. The combination of the acoustic foam and the cover gives the Visquare Tech a fire rating Euro Class B.

Visquare is designed to perform on medium and high frequencies giving an absorption effect. The effect occurs when sound energy passes through the perforated foam.

Vicoustic's research has revealed that perforated foam performs better compared with standard cut foam. A perforated, 40mm thick panel gives the same results as a 70 mm thick standard panel. This is because in addition to increasing the surface absorption, it also works as a sound trap. Visquare's holes are specifically designed to line-arise the absorption coefficient spectrum.

It is well known that foam absorption is not linear and the higher the frequency, the greater the efficiency. Vicoustic's research has shown that there is a particular way to create a flat absorption response with the foam, as seen with Cinema Round Premium and now with Visquare, where the foam is non linear.

Visquare is designed for spaces with a demanding acoustic environment. The high acoustic performance of the Visquare Tech acoustic panel is due to its open-cell, fine foam structure and perforated surface. This acoustic panel is excellent for absorbing reverberations caused by multiple sound reflections on surfaces. Such reverberations can increase loudness, making music or speech less perceptible, and thus obtrusive to a theatre audience for example.

Features:

- Low weight,
- Low temperature flexibility,
- High sound absorption capacity,
- Good thermal insulation properties,
- Constant physical properties over a wide temperature range, application temperature up to 240 °C [465 °F],
- Flame resistant - Euro Class B
- No fibre shedding (giving an advantage over mineral fibre), making it highly suitable for use in public spaces such as restaurants etc.
- highly suitable, cost-effective solution for large spaces.
- Available in two thicknesses: 40 mm and 60 mm


Applications:

Recording and Broadcast Studios, Post Production Studios, Conference and Teleconference Rooms, Public Spaces, Auditoriums, Restaurants, etc.

Technical File

Please notice that the dimensions of this panel have a tolerance margin of ± 3 mm

Graph



Main Info

Ref: B00646
EAN13: 5600301843891
HS-Code: 39211310
Dimensions: 595.0 x 595.0 x 40.0 mm
Scratch Resistance: No
Washable: No

Performance

Functionality: Absorption
Absorption Frequency: Medium
alpha with Shape Indicators: 0.65 (MH)
NRC: 0.750
Fire Class European (EN): Euroclass E

Shipping

Units Per Box: 12 boxes
Box Dimensions: 620.0 x 620.0 x 495.0 mm
Box Weight: 5.4 kg

Row Materials

Material: Fabric, Foam
Foam Type: Tech

Design

Fabric Color: Bordeaux
Edges: Angled

Installation

Place: Wall, Ceiling
Fixing Type: Glued