



Main Office, R&D and Logistics

Avenida do Polo 3, nº159,
4590-137 Carvalhosa
Paços de Ferreira - Portugal
Tlm. : +351 917 851 019

Office 2

Rua Quinta do Bom Retiro nº16, Armazém 9
2820-690 Charneca da Caparica - Portugal
Tel. : +351 212 964 100
Fax : +351 212 964 101
E-mail : info@vicoustic.com

Vicoustic USA

5701 Sixth Avenue South, Suite 229
Seattle, WA 98108
Tel. (206) 767-2020
E-mail : info@vicousticusa.com

www.vicousticusa.com

The Flat Panel consists of acoustic foam with high resistance fire rating, providing a wide range of applications in the aesthetic point of view. The Flat Panel has been specially developed to be used in restaurants, offices and meeting rooms, combining acoustic efficiency and an elegant appearance, now in rectangular (120 x 60 cm) and square panels (60 x 60 cm).

Available in two different foams (Vicoustic Foam and Vicoustic Tech Foam), two distinct thicknesses (2 cm and 4 cm) and also available in a Premium version where the panel is covered in 8 different colored fabrics, the variations are many. It is designed to perform mainly on medium and high frequencies, providing a cost-effective solution for ceilings and walls.

Flat Panel Premium - (Vicoustic Foam):


Polyurethane foam with extraordinary acoustic properties and classified in M1 class of fire reaction. Known for its flexibility and versatile applicability, this durable material is ideal for installations that require endurance.

Features:

- Low weight,
- Low temperature flexibility,
- Good sound absorption capacity,
- Good thermal insulation properties,
- Constant physical properties over a wide temperature range, application temperature up to 240 °C [465 °F],
- Flame resistant.

Please notice that the dimensions of this panel have a tolerance margin of +/-3 mm

Graph



Main Info

Ref: B00703

Technical File

EAN13: 5600301844836
HS-Code: 39211310
Dimensions: 1195.0 x 595.0 x 20.0 mm
Scratch Resistance: No
Washable: No

Performance | Functionality: Absorption
Absorption Frequency: Medium
alpha with Shape Indicators: 0.7
NRC: 0.650
Fire Class European (EN): Euroclass F

Shipping | Units Per Box: 16 boxes
Box Dimensions: 1230.0 x 630.0 x 340.0 mm
Box Weight: 11.4 kg

Raw Materials | Material: Fabric, Foam
Foam Type: M1

Design | Fabric Color: Black
Edges: Angled

Installation | Place: Wall, Ceiling
Fixing Type: Glued

Technical File