



Main Office, R&D and Logistics

Avenida do Polo 3, nº159,
4590-137 Carvalhosa
Paços de Ferreira - Portugal
Tlm . +351 917 851 019

Office 2

Rua Quinta do Bom Retiro nº16, Armazém 9
2820-690 Charneca da Caparica - Portugal
Tel . +351 212 964 100
Fax . +351 212 964 101
E-mail . info@vicoustic.com







Vicoustic USA

5701 Sixth Avenue South, Suite 229
Seattle, WA 98108
Tel . (206) 767-2020
E-mail . info@vicousticusa.com

www.vicousticusa.com

This sound proof door has 44mm of thickness, and includes a rim all along its periphery except on the bottom, with a seal in a special profile all around, and close to the pavement with a mechanical system moveable threshold.

The door is composed with steel sheets 1,5 mm thick, and also consists of a core completely filled with absorbent and damping material. It includes an asymmetric European lock with a Yale-type key and special hinges in the model with three-rod adjustment.

Finish	 Includes Grey Enamel Primer	  Options Keylock Without Floor Frame	   Anti-Panic Bar Circular Double Window Auto-Close System
---------------	--	---	--

Main Info

Ref: U00072
 EAN13: 5600301842672
 HS-Code: 73083000
 Dimensions: 850 x 2000 mm
 Number of Doors: 1 door
 Gross Weight: 63.00 kg

Performance

Fire Resistance: 30 minutes
 RW Reduction: 37 dB

Installation

Outer Measurements: 975 x 2063 mm
 Recommended Measurements for the construction span: 985 x 2073 mm

Shipping Info

Units Per Pallet: 1 door
 Pallet Dimensions: 2120 x 1040 x 460 mm
 Pallet Volume: 1.01 m3
 Pallet Weight: 130.80 kg

Technical File