



Main Office, R&D and Logistics

Avenida do Polo 3, nº159,
4590-137 Carvalhosa
Paços de Ferreira - Portugal
Tlm . +351 917 851 019

Office 2

Rua Quinta do Bom Retiro nº16, Armazém 9
2820-690 Charneca da Caparica - Portugal
Tel . +351 212 964 100
Fax . +351 212 964 101
E-mail . info@vicoustic.com

Vicoustic USA

5701 Sixth Avenue South, Suite 229
Seattle, WA 98108
Tel . (206) 767-2020
E-mail . info@vicousticusa.com

www.vicousticusa.com

The Flat Panel consists of acoustic foam with high resistance fire rating, providing a wide range of applications in the aesthetic point of view. The Flat Panel has been specially developed to be used in restaurants, offices and meeting rooms, combining acoustic efficiency and an elegant appearance, now in rectangular (120 x 60 cm) and square panels (60 x 60 cm).

It is designed to perform mainly on medium and high frequencies, providing a cost-effective solution for ceilings and walls.

Flat Panel Tech - (Vicoustic Foam Tech):

Made of Basotect® foam, it's long-term resistance to high temperatures and excellent fire characteristics are based on the use of melamine resin. The high nitrogen content of the resin is responsible for the extremely flame-resistant property of the foam without the need for fire retardants, making it particularly suitable for applications with high fire safety requirements. Features:

- Low weight,
- Low temperature flexibility,
- Good sound absorption capacity,
- Good thermal insulation properties,
- Constant physical properties over a wide temperature range, application temperature up to 240 °C [465 °F],
- Flame resistant.

Main Info

Ref: B00280

EAN13: 5600301845154

HS-Code: 39211310

Dimensions: 1200.0 x 600.0 x 20.0 mm

Scratch Resistance: No

Washable: No

Technical File

Flat Panel 120.2 Tech Black



Performance	Functionality: Absorption
	Absorption Frequency: Medium
	Absorption Class: C
	alpha with Shape Indicators: 0.70 (H)
	NRC: 0.650
	Fire Class European (EN): Euroclass B
	Fire Class Germany (DIN): B1
Shipping	Fire Class France (NF P): M1
Shipping	Units Per Box: 16 boxes
	Box Dimensions: 1230.0 x 630.0 x 340.0 mm
Row Materials	
Design	Material: Fabric, Foam
	Foam Type: Tech
Design	
Installation	Fabric Color: Black
	Edges: Angled
Installation	
Installation	Place: Wall, Ceiling
	Fixing Type: Glued

Technical File