



Anti-vibration wall mountings for partition walls. Designed to prevent structural transmission and provide maximum structural stability. Highly recommended for absorption of vibrations produced by airborne and impact noise. These units are a must in walls with sizable dimension.

Advantages The system combines specially designed materials and techniques allowing vibration reduction in both directions. It has a security system to prevent the complete collapse of the treatment in case of fire. **Characteristics** Suited for steel studs with dimensions: 48mm, 70mm, 90mm. **Installation** The first unit should be applied 1,50m from the floor. The second unit should be applied 3,00m from the floor. So on and so forth. The last unit should be applied between 10-30cm from the acoustic ceiling. Remember that the installation of the wall mountings should be in a criss-cross sequence (please see the installation procedure sheets).

Main Info	Ref: B00485
	EAN13: 5600301841996
	HS-Code: 68069000
	Dimensions: x x mm
	COM_ANTIVIBRATICS_FORM_LBL_ANTIVIBRATIC_WEIGHT: kg
Performance	Recycle Coefficient: 0.0 %
	COM_ANTIVIBRATICS_FORM_LBL_ANTIVIBRATIC_ROLE:
	COM_ANTIVIBRATICS_FORM_LBL_ANTIVIBRATIC_ABSORPTION_FREQUENCY:
	COM_ANTIVIBRATICS_FORM_LBL_ANTIVIBRATIC_ABSORPTION_CLASS:
	COM_ANTIVIBRATICS_FORM_LBL_ANTIVIBRATIC_AW:
Shipping	COM_ANTIVIBRATICS_FORM_LBL_ANTIVIBRATIC_NRC:
	Units Per Box: 50 boxes
	Box Dimensions: 0.0 x 0.0 x 0.0 mm
	Box Weight: 0.0 kg
	Box MSRP: 237.3 €
Installation	MasterCarton Box Dimensions: 0.0 x 0.0 x 0.0 mm
	MasterCarton Box MSRP: 0.0 €
	Place: Wall
	Load Weight Range: kg