



#### Main Office, R&D and Logistics

Avenida do Polo 3, nº159,  
4590-137 Carvalhosa  
Paços de Ferreira - Portugal  
Tlm . +351 917 851 019

#### Office 2

Rua Quinta do Bom Retiro nº16, Armazém 9  
2820-690 Charneca da Caparica - Portugal  
Tel . +351 212 964 100  
Fax . +351 212 964 101  
E-mail . info@vicoustic.com

#### Vicoustic USA

5701 Sixth Avenue South, Suite 229  
Seattle, WA 98108  
Tel . (206) 767-2020  
E-mail . info@vicousticusa.com

www.vicousticusa.com

Anti-vibration wall mountings designed to prevent structural transmission and provide maximum structural stability. Highly recommended for absorption of vibrations produced by airborne and impact noise. The lowest frequencies of airborne noise tend to be in the range of 28-30Hz. Impact noise tends to be even lower.

The steel spring system and EPDM rubber is specially designed to prevent sound amplifications through the wall structures, where the sound pressure level is between 100dB-105dB (medium/ low frequencies). These units are a must in walls with sizable dimension. Advantages Extremely efficient on the low frequency range. The system combines specially designed materials and techniques to achieve better results, and allowing vibration reduction in both directions. It has a security system to prevent the complete collapse of the treatment in case of fire. Extremely efficient in industrial zones. Characteristics Suited for steel studs with dimensions: 48mm, 70mm, 90mm. May adapt to other dimensions. Installation The first unit should be applied 1,50m from the floor. The second unit should be applied 3,00m from the floor. So on and so forth. The last unit should be applied between 10-30cm from the acoustic ceiling. Remember that the installation of the wall mountings should be in a criss-cross sequence (please see the installation procedure sheets).

## Main Info

Ref: B00486  
EAN13: 5600301841941  
HS-Code: 68069000

## Performance

Mounting Width: 48, 70 and 90mm  
Load Weight Range: 10.00 to 70.00 Kg

## Installation

Place: Division Wall  
Steel: Yes  
Fire Security Devices: Yes  
Plate Thickness: 1.5 mm

## Shipping

Units Per Box: 50 boxes  
Box Dimensions: 323.0 x 238.0 x 143.0 mm  
Box Weight: 11.6 kg

# Technical File