



#### Main Office, R&D and Logistics

Avenida do Polo 3, nº159,  
4590-137 Carvalhosa  
Paços de Ferreira - Portugal  
Tlm. : +351 917 851 019

#### Office 2

Rua Quinta do Bom Retiro nº16, Armazém 9  
2820-690 Charneca da Caparica - Portugal  
Tel. : +351 212 964 100  
Fax : +351 212 964 101  
E-mail : [info@vicoustic.com](mailto:info@vicoustic.com)

#### Vicoustic USA

5701 Sixth Avenue South, Suite 229  
Seattle, WA 98108  
Tel. : (206) 767-2020  
E-mail : [info@vicousticusa.com](mailto:info@vicousticusa.com)

[www.vicousticusa.com](http://www.vicousticusa.com)

This acoustic panel consists of advanced acoustic foam technology allowing the highest absorption properties and an excellent fire rating standard. The Visquare Tech can also have a white or black finish and also has a Premium version where the panel is covered in a colored fabric, available in 8 colors. The combination of the acoustic foam and the cover gives the Visquare Tech a fire rating Euro Class B.

Visquare is designed to perform on medium and high frequencies giving an absorption effect. The effect occurs when sound energy passes through the perforated foam.

Vicoustic's research has revealed that perforated foam performs better compared with standard cut foam. A perforated, 40mm thick panel gives the same results as a 70 mm thick standard panel. This is because in addition to increasing the surface absorption, it also works as a sound trap. Visquare's holes are specifically designed to line-arise the absorption coefficient spectrum.

It is well known that foam absorption is not linear and the higher the frequency, the greater the efficiency. Vicoustic's research has shown that there is a particular way to create a flat absorption response with the foam, as seen with Cinema Round Premium and now with Visquare, where the foam is non linear. Visquare is designed for spaces with a demanding acoustic environment. The high acoustic performance of the Visquare Tech acoustic panel is due to its open-cell, fine foam structure and perforated surface. This acoustic panel is excellent for absorbing reverberations caused by multiple sound reflections on surfaces. Such reverberations can increase loudness, making music or speech less perceptible, and thus obtrusive to a theatre audience for example.

#### Features:

- Low weight,
  - Low temperature flexibility,
  - High sound absorption capacity,
  - Good thermal insulation properties,
  - Constant physical properties over a wide temperature range, application temperature up to 240 &deg;C [465 &deg;F],
  - Flame resistant - Euro Class B
  - No fibre shedding (giving an advantage over mineral fibre), making it highly suitable for use in public spaces such as restaurants etc.
- highly suitable, cost-effective solution for large spaces.
- Available in two thicknesses: 40 mm and 60 mm

#### Applications:

Recording and Broadcast Studios, Post Production Studios, Conference and Teleconference Rooms, Public Spaces, Auditoriums, Restaurants, etc.

#### Main Info

Ref: B00211

EAN13: 5600301844034

HS-Code: 39211310

Dimensions: 600.0 x 600.0 x 60.0 mm

Scratch Resistance: No

## Technical File

<b>Performance</b>	Functionality: Absorption
	Absorption Frequency: Medium
	Absorption Class: B
	alpha with Shape Indicators: 0.85
	NRC: 0.850
	Fire Class European (EN): Euroclass B
	Fire Class Germany (DIN): B1
<b>Shipping</b>	Fire Class France (NF P): M1
<b>Shipping</b>	Units Per Box: 8 boxes
	Box Dimensions: 620.0 x 620.0 x 495.0 mm
<b>Row Materials</b>	
<b>Design</b>	Material: Fabric, Foam
	Foam Type: Tech
<b>Design</b>	
<b>Installation</b>	Place: Wall, Ceiling
	Fixing Type: Glued