



Main Office, R&D and Logistics

Avenida do Polo 3, nº159,
4590-137 Carvalhosa
Paços de Ferreira - Portugal
Tlm . +351 917 851 019

Office 2

Rua Quinta do Bom Retiro nº16, Armazém 9
2820-690 Charneca da Caparica - Portugal
Tel . +351 212 964 100
Fax . +351 212 964 101
E-mail . info@vicoustic.com

Vicoustic USA

5701 Sixth Avenue South, Suite 229
Seattle, WA 98108
Tel . (206) 767-2020
E-mail . info@vicousticusa.com

www.vicousticusa.com

Cinema Square is the latest addition to Vicoustic's Premium Line. The panel has been specially developed for use in large areas such as classrooms, performance spaces, offices and meeting rooms, where suspended ceilings can often be a limiting factor in the choice of acoustic treatment.

Cinema Square combines acoustic efficiency with elegant appearance. The panel's wood frame is packed with optimum density acoustic foam and covered in fabric. A choice of colours is available to match room interiors. Designed to perform mainly on medium and high frequencies, Cinema Square is a cost-effective solution for both ceilings and walls (where it can also be used to good effect in improving low frequencies). It's M1 (European) fire rating makes it highly suitable for use in a variety of public spaces.

Cinema Square Premium - (Vicoustic Foam) : A polyurethane foam with extraordinary acoustic properties and classified in M1 class of fire reaction. Known for it's flexibility and versatile applicability, this durable material is ideal for rigid foam insulation panels.

- Efficient absorption
- Easy to install
- Excellent value for money
- Fabrics can be removed and washed.

Applications:

Listening Rooms, Home Theatres, Recording and Broadcast Studios, Post Production Studios, Performance Spaces, Rehearsal Rooms, Conference and Teleconference Rooms, Public Spaces, Auditoriums, etc.

Please notice that the dimensions of this panel have a tolerance margin of +/-3 mm

Main Info

Ref: B00794
EAN13: 5600217588831
HS-Code: 39211310
Dimensions: 595.0 x 595.0 x 40.0 mm
Scratch Resistance: No
Washable: Yes

Performance

Functionality: Absorption
Absorption Frequency: High

Technical File

alpha with Shape Indicators: 0.70
NRC: 0.750
Fire Class European (EN): Euroclass F

Shipping

Units Per Box: 6 boxes
Box Dimensions: 620.0 x 620.0 x 335.0 mm
Box Weight: 7.0 kg

Row Materials

Material: Fabric, Foam
Foam Type: M1

Design

Fabric Color: Beige
Edges: Angled

Installation

Place: Wall, Ceiling
Fixing Type: Glued

Technical File