



Main Office, R&D and Logistics

Avenida do Polo 3, nº159,
4590-137 Carvalhosa
Paços de Ferreira - Portugal
Tlm . +351 917 851 019

Office 2

Rua Quinta do Bom Retiro nº16, Armazém 9
2820-690 Charneca da Caparica - Portugal
Tel . +351 212 964 100
Fax . +351 212 964 101
E-mail . info@vicoustic.com

Vicoustic USA

5701 Sixth Avenue South, Suite 229
Seattle, WA 98108
Tel . (206) 767-2020
E-mail . info@vicousticusa.com

www.vicousticusa.com

Made from solid wood, the new diffuser is perfect for use in venues such as concert halls, hi-fi rooms and recording studios, where effective diffusion is often required, without too much absorption occurring at the same time. With its striking angled surface, the two-dimensional diffuser is based on a QRD sequence combined with changing reflection techniques (a result of the angled surface).

The panel itself is made in two parts. Each part can be rotated in different directions so that a uniform, omni-directional scattering of sound is achieved, with particularly effective diffusion of mid and low frequencies. Multifuser Wood 64 works between 310Hz and 8kHz. As well as its acoustic efficiency, the panel's attractive appearance makes it suitable for use in a range of settings. Available in Light Brown, Black and White finishes.

Applications:

Conference Rooms, Classrooms, Auditoriums, Hi-Fi and Home Cinema.

Main Info

Ref: U00006
EAN13: 5600301843006
HS-Code: 44101110
Dimensions: 595.0 x 595.0 x 135.0 mm
Scratch Resistance: No
Washable: No

Performance

Functionality: Diffusion
Absorption Frequency: Medium
NRC: 0.350
Fire Class European (EN): Euroclass E

Shipping

Units Per Box: 1 box
Box Dimensions: 605.0 x 309.0 x 168.0 mm
Box Weight: 18.2 kg

Row Materials

Material: Wood
Wood Type: Mdf Painted

Technical File

Multifuser Wood 64 White



Design

Wood Color: White
Edges: Angled

Installation

Place: Wall
Fixing Type: Screwed, Glued

Technical File