



#### Main Office, R&D and Logistics

Avenida do Polo 3, nº159,  
4590-137 Carvalhosa  
Paços de Ferreira - Portugal  
Tlm . +351 917 851 019

#### Office 2

Rua Quinta do Bom Retiro nº16, Armazém 9  
2820-690 Charneca da Caparica - Portugal  
Tel . +351 212 964 100  
Fax . +351 212 964 101  
E-mail . info@vicoustic.com

#### Vicoustic USA

5701 Sixth Avenue South, Suite 229  
Seattle, WA 98108  
Tel . (206) 767-2020  
E-mail . info@vicousticusa.com

www.vicousticusa.com

Flexi Wood A75 is a panel dedicated to the control of medium and medium-low frequencies. It acts simultaneously as an absorber and a reflector, controlling excess energy in a room without compromising its ambience. This helps to create listening spaces with a natural, bright sound.

The panel's revolutionary design is further enhanced by the addition of a wood surface. Long known for its excellent acoustic properties, the wood also adds elegance and modernity to the panel, making it suitable for use in any type of space.

The Flexi Wood panel is available in two different thicknesses for use in different frequency ranges. Flexi Wood A75 acts as a Helmholtz resonator performing between 200Hz and 2000Hz.

## Main Info

Ref: B00052  
EAN13: 5600217588961  
HS-Code: 39211310  
Dimensions: 600.0 x 600.0 x 77.0 mm  
Scratch Resistance: No  
Washable: No

## Performance

Functionality: Absorption  
Absorption Frequency: Medium  
Absorption Class: C  
alpha with Shape Indicators: 0.6  
NRC: 0.650  
Fire Class European (EN): Euroclass F  
Fire Class France (NF P): M1

## Shipping

Units Per Box: 6 boxes  
Box Dimensions: 620.0 x 620.0 x 495.0 mm  
Box Weight: 9.4 kg

## Raw Materials

Material: Wood, Foam  
Wood Type: Mdf Painted

# Technical File

Foam Type: M1

## Design

Wood Color: Nordik  
Edges: Angled

## Installation

Place: Wall, Ceiling  
Fixing Type: Glued

*Technical File*