



#### Main Office, R&D and Logistics

Avenida do Polo 3, nº159,  
4590-137 Carvalhosa  
Paços de Ferreira - Portugal  
Tlm . +351 917 851 019

#### Office 2

Rua Quinta do Bom Retiro nº16, Armazém 9  
2820-690 Charneca da Caparica - Portugal  
Tel . +351 212 964 100  
Fax . +351 212 964 101  
E-mail . info@vicoustic.com

#### Vicoustic USA

5701 Sixth Avenue South, Suite 229  
Seattle, WA 98108  
Tel . (206) 767-2020  
E-mail . info@vicousticusa.com

www.vicousticusa.com

Advanced anti-vibration system for ceiling suspension. Consists of a steel spring and rubber to achieve maximum isolation performance on low + medium + high frequencies. Now comes with a new security system to guarantee better resistance and higher security.

**Advantages** The steel spring provides an excellent degree of vibration insulation in the low/medium frequencies. - The rubber provides an important vibration isolation of the medium/high frequencies. - The combination of these 2 components make the best anti-vibration system for ceiling suspension.

## Main Info

Ref: B00472  
EAN13: 5600301841842  
HS-Code: 68069000

## Performance

Mounting Width: 60 mm  
Rupture Point: 350.00 Kg  
Load Weight Range: 11.00 to 36.00 Kg

## Installation

Place: Ceiling  
Steel: Yes  
Rubber Color: Green  
Security Devices: 1  
Fire Security Devices: No

## Shipping

Units Per Box: 40 boxes  
Box Dimensions: 625.0 x 329.0 x 188.0 mm  
Box Weight: 8.7 kg

# Technical File