



#### Main Office, R&D and Logistics

Avenida do Polo 3, nº159,  
4590-137 Carvalhosa  
Paços de Ferreira - Portugal  
Tlm . +351 917 851 019

#### Office 2

Rua Quinta do Bom Retiro nº16, Armazém 9  
2820-690 Charneca da Caparica - Portugal  
Tel . +351 212 964 100  
Fax . +351 212 964 101  
E-mail . info@vicoustic.com







#### Vicoustic USA

5701 Sixth Avenue South, Suite 229  
Seattle, WA 98108  
Tel . (206) 767-2020  
E-mail . info@vicousticusa.com

www.vicousticusa.com

This sound proof door has 44mm of thickness, and includes a rim all along its periphery except on the bottom, with a seal in a special profile all around, and close to the pavement with a mechanical system moveable threshold.

The door is composed with steel sheets 1,5 mm thick, and also consists of a core completely filled with absorbent and damping material. It includes an asymmetric European lock with a Yale-type key and special hinges in the model with three-rod adjustment.

<b>Finish</b>	 <b>Includes</b> Grey Enamel Primer	  <b>Options</b> Keylock Without Floor Frame	   Anti-Panic Bar Circular Double Window Auto-Close System
---------------	---	---	---

## Main Info

Ref: U00073  
EAN13: 5600301842689  
HS-Code: 73083000  
Dimensions: 900 x 2000 mm  
Number of Doors: 1 door  
Gross Weight: 66.00 kg

## Performance

Fire Resistance: 30 minutes  
RW Reduction: 37 dB

## Installation

Outer Measurements: 1025 x 2063 mm  
Recommended Measurements for the construction span: 1035 x 2073 mm

## Shipping Info

Units Per Pallet: 1 door  
Pallet Dimensions: 2120 x 1090 x 460 mm  
Pallet Volume: 1.06 m3  
Pallet Weight: 135.10 kg

# Technical File