



Main Office, R&D and Logistics

Avenida do Polo 3, nº159,
4590-137 Carvalhosa
Paços de Ferreira - Portugal
Tlm . +351 917 851 019

Office 2

Rua Quinta do Bom Retiro nº16, Armazém 9
2820-690 Charneca da Caparica - Portugal
Tel . +351 212 964 100
Fax . +351 212 964 101
E-mail . info@vicoustic.com

Vicoustic USA

5701 Sixth Avenue South, Suite 229
Seattle, WA 98108
Tel . (206) 767-2020
E-mail . info@vicousticusa.com

www.vicousticusa.com

The VicVibro FS is a specially designed homogeneous elastomeric support system for floating floors, aimed to reduce impact noise in wooden floors. The semi-cylindrical modulation at its base increases the deflection, thus improving the vibration absorption

Installation Inside the specially modulated receptor U can be fixed a wooden batten with expansion bolts or stainless steel nails. You should use metal washers in every fix point. Attention: In every fix points must be used also metal washers.

Main Info

Ref: B00451
EAN13: 5600301841576
HS-Code: 68069000

Performance

Mounting Width: 50 mm
Load Weight Range: 80.00 Kg

Installation

Place: Floor
Steel: Yes
Fire Security Devices: No

Shipping

Units Per Box: 200 boxes
Box Dimensions: 625.0 x 329.0 x 188.0 mm
Box Weight: 15.9 kg

Technical File