



Main Office, R&D and Logistics

Avenida do Polo 3, nº159,
4590-137 Carvalhosa
Paços de Ferreira - Portugal
Tlm . +351 917 851 019

Office 2

Rua Quinta do Bom Retiro nº16, Armazém 9
2820-690 Charneca da Caparica - Portugal
Tel . +351 212 964 100
Fax . +351 212 964 101
E-mail . info@vicoustic.com







Vicoustic USA

5701 Sixth Avenue South, Suite 229
Seattle, WA 98108
Tel . (206) 767-2020
E-mail . info@vicousticusa.com

www.vicousticusa.com

This sound proof door has 44mm of thickness, and includes a rim all along its periphery except on the bottom, with a seal in a special profile all around, and close to the pavement with a mechanical system moveable threshold.

The door is composed with steel sheets 1,5 mm thick, and also consists of a core completely filled with absorbent and damping material. It includes an asymmetric European lock with a Yale-type key and special hinges in the model with three-rod adjustment.

Finish		Includes			Options			
	Grey Enamel Primer		Keylock	Without Floor Frame		Anti-Panic Bar	Circular Double Window	Auto-Close System

Main Info

Ref: U00071
EAN13: 5600301842665
HS-Code: 73083000
Dimensions: 800 x 2000 mm
Number of Doors: 1 door
Gross Weight: 60.00 kg

Performance

Fire Resistance: 30 minutes
RW Reduction: 37 dB

Installation

Outer Measurements: 925 x 2063 mm
Recommended Measurements for the construction span: 935 x 2073 mm

Shipping Info

Units Per Pallet: 1 door
Pallet Dimensions: 2120 x 990 x 460 mm
Pallet Volume: 0.97 m³
Pallet Weight: 126.40 kg

Technical File