https://github.com/andreea-buiga/flcd/tree/main/lab8

```
%{
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
int numberOfLine = 0;
%}
%option noyywrap
IDENTIFIER [a-zA-Z_][a-zA-Z0-9_]*
INTEGER 0|[+|-]?[1-9][0-9]*([.][0-9]*)?|[+|-]?0[.][0-9]*
STRING [\"][a-zA-Z0-9]+[\"]
CHAR [\'][a-zA-Z0-9][\']
%%
"HELLO"|"BYE"|"func"|"read"|"write"|"if"|"elif"|"else"|"loop"|"while"|"int"|"string"|"char"|"boo
I" {printf("Reserved word: %s\n", yytext);}
"+"|"-"|"*"|"/"|"%"|"<="|">="|"="|"!="|"<"|">"|"&&"|"||" {printf("Operator: %s\n", yytext);}
"{"|"}"|"["|"]"|"("|")"|"["|"]"|":"|";"|"""|"#"|"\"" {printf("Separator: %s\n", yytext);}
{IDENTIFIER} {printf("Identifier: %s\n", yytext);}
{INTEGER} {printf("Integer: %s\n", yytext);}
{STRING} {printf("String: %s\n", yytext);}
{CHAR} {printf("Char: %s\n", yytext);}
[\t]+ {}
[\n]+ {numberOfLine++;}
[0-9][a-zA-Z0-9_]* {printf("Invalid identifier at line %d\n", numberOfLine);}
[+|-]0 {printf("Invalid integer at line %d\n", numberOfLine);}
[+|-]?[0][0-9]*([.][0-9]*)?
                            {printf("Invalid integer at line %d\n", numberOfLine);}
['][a-zA-ZO-9][2,]['][['][a-zA-ZO-9][a-zA-ZO-9]['] {printf("Invalid char at line %d\n",
numberOfLine);}
['][a-zA-ZO-9]+[a-zA-ZO-9]+['] {printf("Invalid string at line %d\n", numberOfLine);}
. {printf("ERROR! Invalid symbol: %s at line: %d\n", yytext, numberOfLine+1);}
%%
int main( argc, argv )
int argc;
char **argv;
 ++argv, --argc; /* skip over program name */
 if ( argc > 0 )
```

```
yyin = fopen( argv[0], "r" );
else
  yyin = stdin;
yylex();
}
```

DEMO

Run these commands first.

```
C:\Users\andre\Documents\GitHub\flcd\lab8>flex lang.lxi
C:\Users\andre\Documents\GitHub\flcd\lab8>gcc lex.yy.c
```

Run the executable with the filename you want to test. This is a successful case:

```
C:\Users\andre\Documents\GitHub\flcd\lab8>a.exe p1.txt
Reserved word: HELLO
Identifier: var
Identifier: a
Separator: #
Reserved word: int
Separator: ;
Identifier: var
Identifier: b
Separator: #
Reserved word: int
Separator: ;
Identifier: var
Identifier: c
Separator: #
 .
Reserved word: int
Separator: ;
Reserved word: if
Identifier: a
Identifier: b
Operator: &&
Identifier: a
Operator: >=
Identifier: c
Separator: :
Reserved word: write
Identifier: a
Separator: )
Separator: ;
Reserved word: if
Identifier: b
Operator: >=
Identifier: a
Operator: &&
Identifier: b
Operator: >=
Identifier: c
Separator: :
Reserved word: write
Separator: (
Identifier: b
Separator: )
Separator:
Reserved word: if
```

This is an error case:

```
C:\Users\andre\Documents\GitHub\flcd\lab8>a.exe p1_err.txt
Reserved word: HELLO
Identifier: var
Identifier: a
Separator: #
Reserved word: int
Separator: ;
Identifier: var
Identifier: b
Separator: #
Reserved word: int
Separator: ;
Identifier: var
Identifier: c
Separator: #
Reserved word: int
Separator: ;
Identifier: var
Invalid identifier at line 4
```