



# **Methodologies for Software Processes**

## **Lecture 4**

# Tentative course outline



What next?




# Outline

1. The Verification Toolchain
2. Efficient weakest preconditions
3. Error localization

# The toolchain so far

- “Verification as compilation”
- Translate verification problems into simpler ones until the answer is trivial
- Wishlist for each translation **A**  $\rightarrow$  **B**
  - **Soundness**: If **B** is valid, then **A** is valid




# The toolchain so far

- “Verification as compilation”
- Translate verification problems into simpler ones until the answer is trivial
- Wishlist for each translation  $A \rightarrow B$ 
  - **Soundness:** If **B** is valid, then **A** is valid
  - **Completeness:** If **A** is valid, then **B** is valid


Soundness is *necessary*.

Completeness is *desirable*.



# The toolchain so far

- “Verification as compilation”
- Translate verification problems into simpler ones until the answer is trivial
- Wishlist for each translation  $A \rightarrow B$ 
  - **Soundness:** If **B** is valid, then **A** is valid
  - **Completeness:** If **A** is valid, then **B** is valid
  - **Efficiency:** **B**’s size is reasonable wrt. **A**
  - **Explainability:** We can reconstruct errors in **A** from errors in **B**



# Splitting the PL0 Language

## Programming Language **XPL**

- Statements are e**X**ecutable
- Deterministic conditionals
- Specifications via **triples**

### **XPL Statements**

```
S ::= var x | x := a | S;S
      | if (b) { S } else { S }
      | assert b
```

### **Verification condition**

$\{ P \} S \{ Q \}$  valid

## Verification Language **PL0**

- Statements model verification problems
- Nondeterministic choice
- **Verification-specific statements**

### **PL0 Statements**

```
S ::= var x | x := a | S;S
      | S [] S
      | assert P | assume P
```

What is our verification condition for PL0 programs if we have only a statement S (no pre- or postcondition)?



# Splitting the PL0 Language

## Programming Language **XPL**

- Statements are e**X**ecutable
- Deterministic conditionals
- Specifications via **triples**

### **XPL Statements**

```
S ::= var x | x := a | S;S
      | if (b) { S } else { S }
      | assert b
```

### **Verification condition**

**$\{ P \} S \{ Q \}$  valid**

## Verification Language **PL0**

- Statements model verification problems
- Nondeterministic choice
- **Verification-specific statements**

### **PL0 Statements**

```
S ::= var x | x := a | S;S
      | S [] S
      | assert P | assume P
```

### **Verification condition**

**$WP(S, \text{true})$  valid**

## Running example: triple\_min

```
method triple_min(x: Int, y: Int) returns (z: Int)
requires x >= 0 && y >= 0
ensures z <= 3 * x && z <= 3 * y && (z == 3 * x || z == 3 * y)
{
    z := x - y
    if (z < 0) {
        z := z + y
        z := z + 2 * x
    } else {
        z := z - x
        z := z + 4 * y
    }
}
```

The code examples contain every translation step applied to this program

```

// Step one: Encode the triple { A } S { B } using assume and assert.
// A few steps are needed to get a well-formed Viper program:
// We declare all variables upfront in a preamble
// We put everything in a method without parameters
method main()
{
    // preamble
    var x: Int
    var y: Int
    var z: Int

    // assume precondition
    assume x >= 0 && y >= 0

    // program statement still needs encoding
    z := x - y
    if (z < 0) {
        z := z + y
        z := z + 2 * x
    } else {
        z := z - x
        z := z + 4 * y
    }

    // assert postcondition
    assert z <= 3 * x && z <= 3 * y && (z == 3 * x || z == 3 * y)
}

```

*// Step two: Encode S in the next language layer (PL0)*  
*// Here, we need to encode the conditional if-then-else using assume and*  
*nondeterministic choice*  
*// To illustrate this in Viper, we need to declare a Boolean variable star.*


```
method main()  
{  
    // preamble  
    var x: Int  
    var y: Int  
    var z: Int  
    var star: Bool // needed to represent nondeterminism  
  
    assume x >= 0 && y >= 0  
  
    z := x - y  
    if (star) { // nondeterministic choice S1 [] S2  
        assume z < 0  
        z := z + y  
        z := z + 2 * x  
    } else {  
        assume !(z < 0)  
        z := z - x  
        z := z + 4 * y  
    }  
  
    assert z <= 3 * x && z <= 3 * y && (z == 3 * x || z == 3 * y)  
}
```

*// Step three: Encode S in the next language layer*  
*// by transforming the program into*  
*// dynamic single assignment form (DSA)*


```
method main()  
{  
    // preamble  
    var x0: Int  
    var y0: Int  
    var z0: Int  
    var z1: Int  
    var z2: Int  
    var star: Bool  
  
    assume x0 >= 0 && y0 >= 0  
  
    z0 := x0 - y0  
    if (star) {  
        assume z0 < 0  
        z1 := z0 + y0  
        z2 := z1 + 2 * x0  
    } else {  
        assume !(z0 < 0)  
        z1 := z0 - x0  
        z2 := z1 + 4 * y0  
    }  
  
    assert z2 <= 3 * x0 && z2 <= 3 * y0 && (z2 == 3 * x0 || z2 == 3 * y0)  
}
```

## The toolchain so far

- “Verification as compilation”
- Translate verification problems into simpler ones until the answer is trivial
- Wishlist for each translation **A**  $\rightarrow$  **B**
  - **Soundness:** If **B** is valid, then **A** is valid
  - **Completeness:** If **A** is valid, then **B** is valid
  - **Efficiency:** **B**’s size is reasonable wrt. **A**
  - **Explainability:** We can reconstruct errors in **A** from errors in **B**



## Soundness across the toolchain




previous exercise

$\{ P \} S_0 \{ Q \}$  valid  
iff  
 $P \implies WP(S_0, Q)$  (aka  $F$ ) valid

$F$  valid iff  $\neg F$  unsatisfiable

Sound for formally verified SMT solver (not Z3)

## Completeness across the toolchain



previous exercise

$\{ P \} S_0 \{ Q \}$  valid  
iff  
 $P \implies WP(S_0, Q)$  (aka  $F$ ) valid

$F$  valid iff  $\neg F$  unsatisfiable

Solver can only be complete for decidable theories


- unknown or non-termination  $\rightarrow$  false negatives



# Outline


1. The Verification Toolchain
2. Efficient weakest preconditions
3. Error localization

# Roadmap



# Verifier Performance

- The time consumed by an automated verifier is typically dominated by the SMT solver
- Factors influencing SMT performance
  - Size of verification conditions
  - Theories in the background predicate
  - Effectiveness of heuristics for undecidable theories, particularly quantifier instantiation
- Verification times are flaky
  - Minor changes in VCs can have major impact
  - Verification is often much faster than refutation



```
performance.vpr - examples - Visual Studio Code
performance.vpr U x
1  define INT_MIN (-2147483648)
2  define INT_MAX (2147483647)
3
4  method main()
5  {
6      var i: Int
7      var res: Int
8
9      assume INT_MIN <= i && i <= INT_MAX
10
11      if (i < 0) {
12          res := i / 2
13          assert INT_MIN <= res && res <= INT_MAX
14      } else {
15          res := i
16      }
17  }
18

main* 0 0 cat Verification of performance.vpr 99% IF-8 ORF Viper
```

## Size of Verification Conditions

Compute  $WP(S, Q)$  for the programs below; do you notice a pattern?

```
{ TODO }  
res := (start + end)/2  
{ res * res * res == x }
```

```
{ TODO }  
{  
    x := (y+z)*(y+z)  
}  
[ ] {  
    x := 12  
}  
{ 0 <= x }
```

# Size of Verification Conditions

Expression  $a$  is duplicated for each occurrence of variable  $x$

$S$	$WP(S, Q)$
<b>var</b> $x$	<b>forall</b> $x :: Q$
$x := a$	$Q[x / a]$ ←
<b>assert</b> $R$	$R \ \&\& \ Q$
<b>assume</b> $R$	$R \implies Q$
$S1; S2$	$WP(S1, WP(S2, Q))$
$S1 \ [ ] \ S2$	$WP(S1, Q) \ \&\& \ WP(S2, Q)$

Postcondition  $Q$  is duplicated for each nondeterministic choice

```
{ (start + end)/2 * (start + end)/2 *
  (start + end)/2 == x }
res := (start + end)/2
{ res * res * res == x }
```

```
{ 0 <= (y+z)*(y+z) ^ 0 <= 12 }
{
  { 0 <= (y+z)(y+z) }
  x := (y+z)*(y+z)
  { 0 <= x }
} [ ] {
  { 0 <= 12 }
  x := 12
  { 0 <= x }
}
{ 0 <= x }
```

**Worst case:** VC grows **exponentially** in the program size

## Eliminating duplication from assignments

Idea: add knowledge  $x == a$  once and for all instead of substituting every  $x$  by  $a$

$$WP(x := a, Q) ::= (x == a) ==> Q$$

Example with current **WP**

```
{ (start + end)/2 * (start + end)/2 *  
  (start + end)/2 == x }  
res := (start + end)/2  
{ res * res * res == x }
```

Example with proposed **WP**

```
{ res == (start + end)/2 ==>  
  res * res * res == x }  
res := (start + end)/2  
{ res * res * res == x }
```

Is the proposed change of **WP** sound?

## Soundness of alternative assignment rule

```
{ true }  
// ==>  
{ (0 == 1 ==> false) }  
// ==>  
{ x == 0 ==> (x == 1 ==> false) }  
x := 0  
{ x == 1 ==> false }  
x := 1  
{ false }  
assert false  
{ true }
```



**Unsound:** program verifies  
even though an assertion fails!

### Proposed change


$$WP(x := a, Q) ::= (x == a) ==> Q$$

- Issue: the new rule might contradict prior information about  $x$
- Solution: introduce a *fresh* variable

## Preliminary sound assignment rule

$$WP(x := a, Q) ::= (y == a) ==> Q[x / y]$$

where  $y$  is a fresh variable

```
{ true }  ==>
{ z == 0 ==> (y == 1 ==> false) }
x := 0;
{ y == 1 ==> false }
x := 1;
{ false }
assert false
{ true }
```

Fixes unsoundness

```
{ y == (start + end)/2 ==>
  y * y * y == x }
res := (start + end)/2
{ res * res * res == x }
```

still avoids duplication



# Eliminating redundancy from choice-statements

Similar idea: factor out postcondition using a fresh variable

$WP(S1 \text{ [] } S2, Q) ::= (B == Q) ==> WP(S1, B) \ \&\& \ WP(S2, B)$   
where  $B$  is a fresh Boolean variable

```
{ (x == 5 ==> 0 <= x) ^ 0 <= x }  
{  
  { x == 5 ==> 0 <= x }  
  assume x == 5  
  { 0 <= x }  
} [] {  
  { 0 <= x }  
  assert true  
  { 0 <= x }  
}  
{ 0 <= x }
```

```
{ b == (0 <= x) ==> (x == 5 ==> b) ^ b }  
{  
  { x == 5 ==> b }  
  assume x == 5  
  { b }  
} [] {  
  { b }  
  assert true  
  { b }  
}  
{ 0 <= x }
```

## Soundness of alternative rule for choices

$$WP(S1 [] S2, Q) ::= (B == Q) ==> WP(S1, B) \&\& WP(S2, B)$$

where  $B$  is a fresh Boolean variable

Is the proposed change of **WP** sound?

- **No**, not in general
- Issue: assignments in  $S1, S2$ 
  - substitutions  $[x / a]$  have no effect on fresh  $B$
  - but: may change postcondition  $Q$
- **Yes**, if  $S1, S2$  contain *no assignments*

```
{ B == (0 <= x) ==> B }  
{  
  { B }  
  x := (y+z)*(y+z)  
  { B }  
} [] {  
  { B }  
  x := -12  
  { B }  
}  
{ 0 <= x } // unsound!
```



## Towards efficient verification conditions

- **Choices:** sound and efficient rule for programs without assignments

$$WP(S1 [] S2, Q) ::= (B == Q) ==> WP(S1, B) \&\& WP(S2, B) \quad \text{where } B \text{ is fresh}$$

- **Assignments:** sound and efficient rule

$$WP(x := a, Q) ::= (y == a) ==> Q[x / y] \quad \text{where } y \text{ is fresh}$$

- **Observation:** if  $x$  does not appear in  $a$  ( $x \notin FV(a)$ ), then


$$WP(\text{assume } x == a, Q) \text{ valid} \quad \text{iff} \quad WP(x := a, Q) \text{ valid}$$

→ Can we translate PL0 into a **reduced verification language** without assignments?


# The minimal verification language MVL

## MVL Statements

```
S ::= assert R
    | assume R
    | S; S
    | S [] S
```



S	$EWP(S, Q)$
assert R	$R \ \&\& \ Q$
assume R	$R \implies Q$
$S1; S2$	$EWP(S1, EWP(S2, Q))$
$S1 [] S2$	$(B == Q) \implies EWP(S1, B) \ \&\& \ EWP(S2, B)$ where B is fresh




sound without assignments

- PL0:  $WP(S, Q)$  is exponential in the size of S and Q
  - MVL:  $EWP(S, Q)$  is linear in the size of S and Q
- Is there a sound & complete encoding from PL0 to MVL?


# From PL0 to MVL

- Main idea:
  1. Eliminate variable declarations (exercise, later)
  2. Make all assignments assign to fresh variables → single static assignment form (SSA)
  3. Replace every assignment  $x := a$  by assume  $x == a$  → passification
- Observation: all paths through a PL0 program are finite (no loops / recursion)
- A program is in **dynamic single assignment form (DSA)**  
iff every assignment on **a path** assigns to a fresh variable



```
x := 0
x := 1
y := x
```

```
x1 := 0
x2 := 1
y1 := x2
```



```
x := 0
{
  x := (y+z)*(y+z)
} [] {
  x := -12
}
```

```
x1 := 0
{
  x2 := (y1+z1)*(y1+z1)
} [] {
  x2 := -12
}
```

# DSA Construction

- Main idea
  - Introduce multiple versions of each variable
  - Always use the latest version
- Assignment
  - Assign to a new version
- Choice-statements
  - convert both branches individually
  - **synchronize** the last version of each variable

```
x := 0
x := 1
y := x
```

```
x1 := 0
x2 := 1
y1 := x2
```

```
x := 0
{
  x := (y+z)*(y+z)
  x := 7
} [] {
  x := -12
}
y := x
```

```
x1 := 0
{
  x2 := (y1+z1)*(y1+z1)
  x3 := 7
} [] {
  x2 := -12
  x3 := x2
}
y := x3
```

# How do we encode variable declarations in MVL?

*Hint:* try to encode `var x` as a PL0 program first

<code>S</code>	$WP(S, Q)$
<code>var x</code>	<code>forall x :: Q</code>
<code>x := a</code>	$Q[x / a]$
<code>assert R</code>	$R \ \&\& \ Q$
<code>assume R</code>	$R \implies Q$
<code>S1; S2</code>	$WP(S1, WP(S2, Q))$
<code>S1 [] S2</code>	$WP(S1, Q) \ \&\& \ WP(S2, Q)$

## Solution: How do we encode variable declarations in MVL?

Main Idea:

- Declaration “forgets” previous values
- Same effect: Assigning to a fresh variable

$WP(\text{var } x, Q) = WP(x := y, Q) ::= Q[x / y]$   
where  $y$  is fresh

$S$	$WP(S, Q)$
<b>var</b> $x$	<b>forall</b> $x :: Q$
$x := a$	$Q[x / a]$
<b>assert</b> $R$	$R \ \&\& \ Q$
<b>assume</b> $R$	$R \implies Q$
$S1; S2$	$WP(S1, WP(S2, Q))$
$S1 \ [\ ] \ S2$	$WP(S1, Q) \ \&\& \ WP(S2, Q)$

*(wlog. assume VC is in prenex normal form)*

valid: forall  $x :: Q$

iff ( $y$  fresh)

valid: forall  $y :: Q[x/y]$

iff ( $y$  is free, validity implicitly quantifies universally over all free variables)

valid:  $Q[x / y]$



# The toolchain so far


## Encode

- Pre- and postconditions
- If-statements
- Variable declarations
- DSA transformation
- Passification

Efficient *WP*

All *encodings* are **sound** and **complete**  
(not necessarily true for *solvers*)


Size of VCs: **linear** in the original triple



# Outline




1. The Verification Toolchain
2. Efficient weakest preconditions
3. Error localization

# Roadmap




# Verification Debugging with Counterexamples

Verification condition :  $\neg(\exists)WP(S, \text{true})$  satisfiable?

- unsat: 
- sat:  + model with initial values invalidating VC  $\rightarrow$  counterexample
- unknown:  + we can often still get a partial model
- Viper command line option  
--counterexample variables

**assert**  $x * x > 0$



  $\wedge$  Assert might fail. Assertion  $x * x > 0$  might not hold.  
counterexample:  
 $x \rightarrow 0$  [2, 10]

# Causes for verification failures

- Errors in the implementation
- Errors in the specification
  - Pre- and postconditions
  - Assumptions and assertions
- Incompleteness of the verifier
- Unsoundness of the SMT solver
  - Possible but unlikely for unverified solvers

```
{ 0 ≤ b*b - 4*c }  
discriminant := b*b - 4*a*c;  
x := (-b + √discriminant) / 2  
{ a*x2 + b*x + c = 0 }
```



```
// Fermat's Last theorem  
assert 0 < x && 0 < y && 0 < z ==>  
        x*x*x + y*y*y != z*z*z
```



→ Verifiers should help users to localize and fix verification failures

## How does verification fail?

Verification condition:  $(E)WP(S, \text{true})$  valid



If  $S$  contains **no assertions**, then  $(E)WP(S, \text{true})$  is valid.

How many assertions could fail? Which ones should we report?

```
{ (x < 17 ==> x < 26)
  && (x >= 17 ==> x > 42 && x > 17 && x != 16) }
{
  { x < 17 ==> x < 26 }
  assume x < 17;
  { x < 26 }
  assert x < 26
  { true }
} [] {
  { x >= 17 ==> x > 42 && x > 17 && x != 16 }
  assume x >= 17;
  { x > 42 && x > 17 && x != 16 }
  assert x > 42;
  { x > 17 && x != 16 }
  assert x > 17;
  { x != 16 }
  assert x != 16
  { true }
} { true }
```

# Solution

```
{ (x < 17 ==> x < 26)
  && (x >= 17 ==> x > 42 && x > 17 && x != 16) }
{
  { x < 17 ==> x < 26 }
  assume x < 17;
  { x < 26 }
  assert x < 26 // never fails
  { true }
} [] {
  { x >= 17 ==> x > 42 && x > 17 && x != 16 }
  assume x >= 17;
  { x > 42 && x > 17 && x != 16 }
  assert x > 42; // can fail → report!
  { x > 17 && x != 16 }
  assert x > 17; // can fail → report?
  { x != 16 }
  assert x != 16 // can fail → report?
  { true }
} { true }
```



## Error localization

If  $S$  contains **no assertions**, then  $(E)WP(S, \text{true})$  is valid.

- Goal: report assertions that fail verification
- How to **identify** failing assertions?
- **How many** failing assertions should we report?
- How do we deal with **dependencies** between failures?

```
assert MIN_INT <= x + y
assert x + y <= MAX_INT
res := x + y
```

```
assert MIN_INT <= x - y
assert x - y <= MAX_INT
d := x - y
```

```
assert d != 0
res := res / d
```

→ A single VC  $WP(S, \text{true})$  cannot report which parts of a proof fail


Idea: Split VC at assertions into *multiple* proof obligations

sets of predicates

S	$MWP(S, M)$
assert R	$M \cup \{R\}$
assume P	$\{P \implies Q \mid Q \in M\}$
S1; S2	$MWP(S1, MWP(S2, M))$
S1 [] S2	$MWP(S1, M) \cup MWP(S2, M)$

- New verification condition:  
Every P in  $MWP(S, \{\})$  is valid
- All predicates are implication chains  

$$P \implies Q \implies R$$
 not valid  $\rightarrow$  assert R failed



## Exercise: error localization

- Compute  $MWP(S, \{\})$  for the statement on the right.
- Which of the proof obligations are valid?
- For each *invalid* proof obligation, determine an initial state such that the corresponding assertion fails
- Verify the example on the right in Viper using the Carbon verifier. How many error messages do you get?

```
{  
  assert x == 7  
} [ ] {  
  assert x == 2  
  assert x > 0  
}
```

```
method foo(x: Int, b: Bool) {  
  if(b) {  
    assert x == 7  
  } else {  
    assert x == 2  
    assert x > 0  
  }  
}
```

## Solution: error localization

- $MWP(S, \{\}) = \{ x == 7, x == 2, x > 0 \}$
- Since  $x$  has an arbitrary value, none of the three proof obligations are valid
- Initial states
  - $x == 7$  may fail for initial state  $x == 0$
  - $x == 2$  may fail for initial state  $x == 0$
  - There is no execution in which  $x > 0$  fails because each execution where  $x$  is non-positive fails already at the previous assertion
- Viper reports only the first two assertions

```
{  
  assert x == 7  
} [ ] {  
  assert x == 2  
  assert x > 0  
}
```

```
method foo(x: Int, b: Bool) {  
  if(b) {  
    assert x == 7  
  } else {  
    assert x == 2  
    assert x > 0  
  }  
}
```

## Avoiding masked verification errors

- **WP** and **MWP** ignore the order of assertions

$WP(\text{assert } P; \text{assert } R, Q) = P \ \&\& \ R \ \&\& \ Q$

$MWP(\text{assert } P; \text{assert } R, M) = M \cup \{ P \} \cup \{ R \}$

`assert x == 2`  
`assert x > 0`

`assert x > 0`  
`assert x == 2`

- Issue: second assertion should only be checked if it passed the first assertion
- Solution: add an assumption after each assertion

`assert R`



`assert R`  
`assume R`

## Avoiding masked verification errors



```
{ x == 2 ==> x > 0, x == 2 }  
assert x == 2  
{ x == 2 ==> x > 0 }  
assume x == 2  
{ x > 0 }  
assert x > 0  
{ }  
assume x > 0  
{ }
```

Case 1: one assertion fails



```
{ x > 0 ==> x == 2, x > 0 }  
assert x > 0  
{ x > 0 ==> x == 2 }  
assume x > 0  
{ x == 2 }  
assert x == 2  
{ }  
assume x == 2  
{ }
```




Case 2: both assertions fails

# The toolchain so far

## Encode

- Pre- and postconditions
- If-statements
- Variable declarations
- DSA transformation
- Passification
- Avoid masked errors

Efficient *MWP*




All *encodings* are sound and complete

# The Error Propagation Toolchain

Keep **back-translation map** from encoding to original  $\rightarrow$  report errors for original problem


- Assertions  $\rightarrow$  postconditions, assertions
- Assume/Choice statements  $\rightarrow$  if-statements
- Versioned variables (DSA)  $\rightarrow$  original variables
- Assumptions  $\rightarrow$  assignments, masked errors
- Proof obligations  $\rightarrow$  assertions
- Solver results  $\rightarrow$  proof obligations





## Wrap-up

- “Verification as compilation”
- Wishlist for each translation **A**  $\rightarrow$  **B**
  - Sound **encodings**
  - Complete **encodings**
  - Linear-size verification conditions
  - Localize and **back-translate** errors



## Error reporting in Viper

- Viper has two verification backends
  - Counterexamples can be enabled via command line option
- Carbon
  - Uses weakest preconditions, similarly to the technique taught in this course, but uses [a more efficient approach](#)
  - Reports multiple verification failures
- Silicon
  - Uses symbolic execution (similar to **SP**)
  - Reports one verification error per method
  - Default verifier in the IDE