

UNIVERSITY OF REGINA

DISCRETE BAYESIAN NETWORKS INFERENCE WITH SIMPLE PROPAGATION

ANDRÉ E. DOS SANTOS

cs.uregina.ca/~evarista

dossantos@cs.uregina.ca


CS900



OUTLINE



INTRODUCTION



BAYESIAN NETWORKS (BNs)



DARWINIAN NETWORKS (DNs)



JOIN TREE PROPAGATION

(JTP)

OUTLINE









SIMPLE PROPAGATION

(SP)


EXPERIMENTAL RESULTS

CONCLUSIONS

QUESTIONS

BAYESIAN NETWORKS

PROBABILISTIC GRAPHICAL MODEL





CONDITIONAL PROBABILISTIC DISTRIBUTIONS

CPD

Pearl

1988














The Π of the CPTs is a **joint probability distribution** $\rho(U)$



 $\rho(\mathbf{U}) = \rho(\mathbf{fire}) \cdot \rho(\mathbf{burglar}) \cdot \rho(\mathbf{smoke} \mid \mathbf{fire}) \cdot \rho(\mathbf{cellphone} \mid \mathbf{fire}, \mathbf{burglar})$

DARWINIAN NETWORKS

SIMPLE PROPAGATION AROSE FROM DARWINIAN NETWORKS

(CAI 2015, CI 2016)



CLEVER WAY TO VIEW
CPTS






P(g|e,f)

DARWINIAN NETWORKS

POPULATION OF MICROORGANISMS








MULTIPLICATION IS


MERGE



$$\bullet$$
 black + \bullet white = \bullet white

$$\bullet$$
 black + \bullet black = \bullet black

$$\circ$$
 white $+ \circ$ white $= \bullet$ black







$$P(c|h) \cdot P(e|c,d) = P(c,e|d,h)$$

MARGINALIZATION IS REPLICATION AND NATURAL SELECTION


$$\sum P(c, e|d, h) = P(e|d, h)$$
















SIMPLE PROPAGATION


SP ONLY USES THE "ONE IN, ONE OUT" PROPERTY FOR JOIN TREE PROPAGATION





JOIN TREE PROPAGATION


JTP IS CENTRAL TO THE THEORY AND PRACTICE OF PROBABILISTIC EXPERT SYSTEMS
(Shafer 1996)















SIMPLE PROPAGATION


SP ONLY USES THE "ONE IN, ONE OUT" PROPERTY FOR JOIN TREE PROPAGATION





SIMPLE PROPAGATION

SP ONLY USES THE "ONE IN, ONE OUT" PROPERTY FOR JOIN TREE PROPAGATION










$$P(j|i) \cdot P(i, m|d = 0, l)$$

populations **p(i, m|d = 0, l)** and **p(j|i)** are then sent to the next node





$$S - E$$

☐ irrelevant potentials

ob



relevant potentials

BN	Vars	LP	SP	Savin
Water	32	0.06	0.05	17%
Oow	33	0.07	0.06	14%
Oow_Bas	33	0.04	0.03	25%
Mildew	35	0.05	0.04	20%
Oow_Solo	40	0.07	0.06	14%
Hkv2005	44	0.23	0.27	-17%
Barley	48	0.09	0.1	-11%
Kk	50	0.09	0.09	0%
Ship	50	0.16	0.17	-6%
Hailfinder	56	0.02	0.02	0%
Medianus	56	0.04	0.03	25%
3Nt	58	0.02	0.01	50%
Hepar_Ii	70	0.03	0.03	0%
Win95Pts	76	0.03	0.03	0%
System_V57	85	0.06	0.05	17%
Fwe_Model8	109	0.14	0.15	-7%
Pathfinder	109	0.12	0.11	8%
Adapt_T1	133	0.04	0.04	0%
Cc145	145	0.1	0.08	20%
Munin1	189	0.54	0.75	-39%
Andes	223	0.15	0.13	13%
Cc245	245	0.2	0.18	10%
Diabetes	413	0.34	0.31	9%
Adapt_T2	671	0.24	0.22	8%
Amirali	681	0.45	0.41	9%
Munin2	1003	0.49	0.45	8%
Munin4	1041	0.61	0.57	7%
Munin3	1044	0.66	0.64	3%

OPTIMAL JTs BUILT FROM 28 REAL-WORLD AND BENCHMARK BNs

- **SP** was **faster** in **18**
- SP tied LP in 5
- LP was faster in 5

CONCLUSION

SP IS A NEW BN INFERENCE ALGORITHM



NO TESTING OF INDEPENDENCIES

"ONE IN, ONE OUT"
PROPERTY



NO ELIMINATION ORDERINGS

SP IS FASTER THAN LP
IN 18/28 REAL-WORLD BNs





SP PERFORMS POORLY IN NON-OPTIMAL JOIN TREES



UNIVERSITY OF REGINA

DISCRETE BAYESIAN NETWORKS INFERENCE WITH SIMPLE PROPAGATION

ANDRÉ E. DOS SANTOS

cs.uregina.ca/~evarista

dossantos@cs.uregina.ca

CS900

