

```
--- djangoapi\core\myLib\baseDjangoView.py ---
```

```
from django.http import JsonResponse
from django.views import View
```

```
class BaseDjangoView(View):
```

```
    """
```

```
    DJANGO CLASS BASED VIEW
```

```
    This class is a class based view that will handle the insert,
    update, delete and select operations over the Buildings model.
```

```
    The class has the following methods:
```

- get() -> Handles the select operation. It will return the record with the id.
- post() -> Handles the insert, update, and delete operations.

```
    To use this view:
```

1. Inherit from this class.
2. Implement the methods selectone, selectall, insert, update, and delete.
3. Register the view in the urls.py file. For example for the building model:

```
    [...
```

```
        path('buildings_view/<str:action>/', views.BuildigsView.as_view(),
```

```
name='buildings_views'), # POST requests
```

```
        path('buildings_view/<str:action>/<int:id>/',
```

```
views.BuildigsView.as_view(), name='buildings_views'), # POST requests
```

```
    ...
```

```
    ]
```

4. To use the view, the URL must be like:

```
    To get a record, the URL must be like:
```

```
        GET /buildings_view/selectone/<id>/
```

```
    To get all the records, the URL must be like:
```

```
        GET /buildings_view/selectall/
```

```
    To insert a record, the URL must be like:
```

```
        POST /buildings_view/insert/ --> The data must be sent in the body of
```

```
the request.
```

```
    To update a record, the URL must be like:
```

```
        POST /buildings_view/update/<id>/ --> The data must be sent in the body
```

```
of the request.
```

```
    To delete a record, the URL must be like:
```

```
        POST /buildings_view/delete/<id>/
```

```
    You can add more methods to this class by redefining the get and post methods.
```

```
    To add
```

```
the newgetmethod and newpostmethod methods, you can do the following:
```

```
def get(self, request, *args, **kwargs):
```

```
    action=kwargs.get('action')
```

```
    if action == 'newgetmethod':
```

```
        return self.newgetmethod()
```

```
    else:
```

```
        return super().get(request, *args, **kwargs)
```

```

def post(self, request, *args, **kwargs):
    action = kwargs.get('action')
    if action == 'newpostmethod':
        return self.newpostmethod()
    else:
        return super().get(request, *args, **kwargs)

```

To call them, the URL must be like:

```

GET /buildings_view/newgetmethod/
POST /buildings_view/newpostmethod/

```

"""

```

def get(self, request, *args, **kwargs):
    """Handles the 'select' method with a GET request."""

    action=kwargs.get('action')
    if action == 'selectone':
        id = kwargs.get('id')
        return self.selectone(id)
    elif action == 'selectall':
        return self.selectall()
    else:
        return JsonResponse({"message": "Invalid operation option"}, status=400)

```

```

def post(self, request, *args, **kwargs):
    """Handles insert, update, and delete depending on the URL parameter."""

```

```

    action = kwargs.get('action')
    print(f"action father: {action}")
    if action == 'insert':
        return self.insert(request)
    elif action == 'update':
        id = kwargs.get('id')
        return self.update(request, id)
    elif action == 'delete':
        id = kwargs.get('id')
        return self.delete(id)
    else:
        JsonResponse({"message": "Invalid operation option"}, status=400)

```

#GET OPERATIONS

```

def selectone(self, id):
    return JsonResponse({'ok':True, 'message': 'Method selectone called: GET',
'data': []}, status=200)

```

```

def selectall(self):
    return JsonResponse({'ok':True, 'message': 'Method selectall called: GET',
'data': []}, status=200)

```

#POST OPERATIONS

```

def insert(self, request):
    return JsonResponse({'ok':True, 'message': 'Method insert called: POST', 'data':
[]}, status=200)
def update(self, request, id):

```

```
        return JsonResponse({'ok':True, 'message': 'Method update called: POST', 'data':  
[], status=200)  
    def delete(self, id):  
        return JsonResponse({'ok':True, 'message': 'Method delete called: POST', 'data':  
[], status=200)
```