

```
--- djangoapi\core\views.py ---
```

```
#Django imports
from django.http import JsonResponse
from django.views import View
from django.contrib.auth import authenticate, login, logout
from django.contrib.auth.mixins import LoginRequiredMixin
from django.shortcuts import redirect
import random, time

"""
Código Nombre Uso típico
200 OK Petición exitosa (valor por defecto).
201 Created Se ha creado un recurso (ej. un nuevo usuario).
400 Bad Request Datos enviados inválidos o mal formateados.
401 Unauthorized El usuario no está autenticado.
403 Forbidden Autenticado, pero sin permisos para esa acción.
404 Not Found El recurso solicitado no existe.
500 Internal Server Error Error inesperado en tu código Python.
"""

def custom_logout_view(request):
    logout(request)
    return redirect("/accounts/login/") # 0 a donde deseas redirigir después del logout

def notLoggedIn(request):
    return JsonResponse({"ok":False,"message": "You are not logged in",
"data":[]},status=400)

class HelloWorld(View):
    def get(self, request):
        return JsonResponse({"ok":True,"message": "Core. Hello world",
"data":[]},status=200)

class LoginView(View):
    def post(self, request, *args, **kwargs):
        if request.user.is_authenticated:
            username=request.user.username
            return JsonResponse({"ok":True,"message": "The user {0} already is
authenticated".format(username),
"data":[{"username":request.user.username}]},
status=200)

        username=request.POST.get('username')
        password=request.POST.get('password')
        user = authenticate(username=username, password=password)
        if user:
            login(request,user)#introduce into the request cookies the session_id,
# and in the auth_sessions the session data. This way,
# in following requests, know who is the user and if
# he is already authenticated.
# The cookies are sent in the response header on POST requests
            return JsonResponse({"ok":True,"message": "User {0} logged
```

```

in".format(username), "data":[{"username": username}]], status=200)
    else:
        # To make thinks difficult to hackers, you make a random delay,
        # between 0 and 1 second
        seconds=random.uniform(0, 1)
        time.sleep(seconds)
        return JsonResponse({"ok":False,"message": "Wrong user or password",
"data":[]},status=400)

class LogoutView(LoginRequiredMixin, View):
    def post(self, request, *args, **kwargs):
        username=request.user.username
        logout(request) #removes from the header of the request
                        #the the session_id, stored in a cookie
        return JsonResponse({"ok":True,"message": "The user {0} is now logged
out".format(username), "data":[]}, status=200)

class IsLoggedIn(View):
    def post(self, request, *args, **kwargs):
        print(request.user.username)
        print(request.user.is_authenticated)
        if request.user.is_authenticated:
            return JsonResponse({"ok":True,"message": "You are authenticated",
"data":[{"username':request.user.username}]], status=200)
        else:
            return JsonResponse({"ok":False,"message": "You are not authenticated",
"data":[]}, status=400)

```