

```
--- postgis\init-db.sh ---
```

```
#!/bin/bash
```

```
set -e
```

```
# Wait for PostgreSQL to be ready
```

```
until pg_isready; do
```

```
    echo ${POSTGRES_USER}
```

```
    echo "Waiting for PostgreSQL to start..."
```

```
    sleep 2
```

```
done
```

```
echo "PostgreSQL is ready. Starting restore."
```

```
#psql -U ${POSTGRES_USER} -d ${POSTGRES_DB} -c "create extension if not exists postgis"
```

```
### RESTORE THE DATABASE
```

```
#To restore a database follow the following steps.
```

```
#If no database restore, the database will be empty
```

```
### ADDITIONAL USERS CREATION
```

```
#To restore a database firsts you have to create the users that own the objects.
```

```
# - Put, in the file init-users.sql, the necessary sql sentences to create the users.
```

```
# - Uncomment the followign two lines.
```

```
#echo "Creating the user vagrant."
```

```
#psql -U ${POSTGRES_USER} -d ${POSTGRES_DB} < /usr/local/app/init-users.sql
```

```
### RESTORE THE DATABASE
```

```
#Create a custom backup file and put it here.
```

```
#Uncomment the following line and change the filename to restore
```

```
#pg_restore -v -U ${POSTGRES_USER} -d ${POSTGRES_DB} /usr/local/app/disati.backup
```

```
#echo "Database restore completed."
```

```
echo "Database cluster created."
```