

```
import math
def andrea_al_cuadrado(x):
    y=x**2
    return y
```

```
andrea_al_cuadrado(1)
```

```
1
```

```
def andrea2(x):
    y=math.pi*x+1
    return y
andrea2(2)
```

```
7.283185307179586
```

```
def andrea3(x):
    y=(x+3)/(x**2+1)
    return y
andrea3(5)
```

```
0.3076923076923077
```

```
def andrea4(x):
    y=math.log10((x+3*x**2)/(2+5*math.pi))
    return y
andrea4(2)
```

```
-0.10204057676209283
```

```
def andrea5(x):
    num=5*x+4
    den=math.pi+7*x
    y=math.exp(num/den)
    return y
andrea5(2)
```

```
2.263080435968593
```

```
x1=[10,2,3,40,5,-30]
print(x1)
print(x1[0])
print(x1[1])
```

```
[10, 2, 3, 40, 5, -30]
10
2
```

```
for x in x1:
    # Bloque de código a repetir
    print(x)
```

```
10
2
3
40
5
-30
```

```
for x in x1:
    print(andrea4(x))
```

```
1.2431930813939418
-0.10204057676209283
0.2289526422793316
2.4366767492040817
```

```
0.6549213745516128
2.1783426489242443
```

```
for x in range(5):
    print(x)
```

```
0
1
2
3
4
```

```
for x in range(5):
    print(Andrea3(x))
```

```
3.0
2.0
1.0
0.6
0.4117647058823529
```

```
for x in range(-5,5):
    print(Andrea2(x))
```

```
-14.707963267948966
-11.566370614359172
-8.42477796076938
-5.283185307179586
-2.141592653589793
1.0
4.141592653589793
7.283185307179586
10.42477796076938
13.566370614359172
```

```
abs(-1)
```

```
1
```

```
def Andrea_valor_absoluto(x):
    if x>0:
        y=x
    elif x<0:
        y=-x
    else:
        y=0
    return y
```

```
Andrea_valor_absoluto(-1)
```

```
for x in range (-5,5):
    print(Andrea_valor_absoluto(x))
```

```
None
None
None
None
None
0
None
None
None
None
```

```
#el mayor numero entre 3
def numero_mayor(a,b,c):
    if a > b:
        y = a
    if b > c:
        y = b
    else:
        y = c
    if a > b and a > c:
        y = a
    elif b > a and b > c:
        y = b
    else:
```

```
    y = c  
    return y
```

```
print(numero_mayor(-1,-3, 5))  
print(numero_mayor(10, 5, 3))  
print(numero_mayor(5, 10, 3))
```

```
5  
10  
10
```