

Data Model

General Conventions

- Primary IDs: UUID.
- Shared `BaseEntity` adds `id` , `createdAt` , and `updatedAt` .
- The DB naming strategy converts fields to snake_case.
- Migrations are located in `shared/migrations` .

users

System user.

Key fields:

Field	Type	Notes
id	UUID	primary key
email	string	login identifier
username	string	display/user name
password	string	hashed password
createdAt	timestampz	from base entity
updatedAt	timestampz	from base entity

tournaments

Main tournament entity.

Field	Type	Notes
id	UUID	primary key
title	varchar	required
description	varchar nullable	optional
visibility	enum	PUBLIC , PRIVATE
roundsCount	int	1..4
submissionDurationSeconds	int	15, 30, or 45
voteDurationSeconds	int	15, 30, or 45
status	enum	DRAFT , ACTIVE , COMPLETED , CANCELLED
inviteToken	UUID nullable	only for private tournaments
ownerId	UUID	owner user id
winnerId	UUID nullable	set on completion

tournament_participants

Tournament-user relation and accumulated score.

Composite primary key:

- tournamentId ;
- userId .

Field	Type	Notes

tournamentId	UUID	primary key part
userId	UUID	primary key part
cumulativeScore	int	default 0
createdAt	timestampz	used as a tie-break
updatedAt	timestampz	technical timestamp

`createdAt` is used for deterministic leaderboard tie-breaks when scores are equal.

tournament_rounds

Tournament round.

Unique index:

- `tournamentId` ;
- `number` .

Field	Type	Notes
id	UUID	primary key
tournamentId	UUID	owner tournament
number	int	round number
phase	enum	<code>SUBMISSION</code> , <code>VOTING</code>
promptKey	varchar	stable prompt key
promptType	enum	currently <code>TEXT</code>

promptContentEn	text	English prompt
promptContentRu	text	Russian prompt
submissionDeadline	timestamptz	close time for submission phase
submissionClosedAt	timestamptz nullable	actual close time
currentVotingSubmissionId	UUID nullable	current revealed submission
currentRevealIndex	int nullable	index in sequential voting
votingDeadline	timestamptz nullable	current voting window deadline
votingStepStatus	enum	IDLE , OPEN , FINALIZING , FINISHED
votingCompletedAt	timestamptz nullable	voting phase completion time
completedAt	timestamptz nullable	round completion time

The prompt is stored in the round row, so the client receives the same prompt during recovery.

tournament_round_submissions

Participant's text answer in a round.

Unique index:

- roundId ;
- authorId .

Field	Type	Notes
id	UUID	primary key

roundId	UUID	target round
authorId	UUID	participant user id
content	text	1..4000 chars
submittedAt	timestampz	create/update timestamp
likeCount	int	calculated after voting
dislikeCount	int	calculated after voting
roundScore	int	equals likeCount

Submitting again updates the existing row.

tournament_round_votes

Participant vote for a submission.

Unique index:

- roundId ;
- submissionId ;
- voterId .

Field	Type	Notes
id	UUID	primary key
roundId	UUID	target round
submissionId	UUID	current revealed submission
voterId	UUID	participant user id

value	enum	LIKE , DISLIKE
source	enum	MANUAL , AUTO_TIMEOUT
votedAt	timestampz	create/update timestamp

A manual vote upsert can overwrite the value until the voting window closes.

Redis Keys

Key	Used by	Purpose
{userId}:{fingerprint}	TokenService	refresh token storage
presence:{tournamentId}:sockets:{userId}	TournamentPresenceService	socket IDs per user per tournament
presence:{tournamentId}:users	TournamentPresenceService	unique online users per tournament
BullMQ queue keys	BullMQ	tournament realtime jobs

Enums

Tournament

TournamentStatus: DRAFT, ACTIVE, COMPLETED, CANCELLED
TournamentVisibility: PUBLIC, PRIVATE

Round

TournamentRoundPhase: SUBMISSION, VOTING
TournamentRoundPromptType: TEXT

TournamentRoundVotingStepStatus: IDLE, OPEN, FINALIZING, FINISHED

Vote

TournamentVoteValue: LIKE, DISLIKE

TournamentVoteSource: MANUAL, AUTO_TIMEOUT