


































Index of


























/opengl/docs/man_pages/hardcopy/GL/html/gl/

Name	Last modified	Size	Description
 Parent Directory			
 accum.html	09-Sep-97 16:16	5K	
 alphafunc.html	09-Sep-97 16:16	3K	
 aretexturesresident.h+	09-Sep-97 16:17	3K	
 arrayelement.html	09-Sep-97 16:17	2K	
 begin.html	09-Sep-97 16:17	8K	
 bindtexture.html	09-Sep-97 16:18	4K	
 bitmap.html	09-Sep-97 16:17	4K	
 blendcolorext.html	09-Sep-97 16:16	1K	
 blendfunc.html	09-Sep-97 16:17	8K	
 calllist.html	09-Sep-97 16:17	2K	
 calllists.html	09-Sep-97 16:17	6K	
 clear.html	09-Sep-97 16:16	3K	
 clearaccum.html	09-Sep-97 16:17	1K	
 clearcolor.html	09-Sep-97 16:17	1K	
 cleardepth.html	09-Sep-97 16:18	1K	
 clearindex.html	09-Sep-97 16:17	1K	
 clearstencil.html	09-Sep-97 16:16	1K	
 clipplane.html	09-Sep-97 16:17	3K	
 color.html	09-Sep-97 16:16	7K	
 colormask.html	09-Sep-97 16:17	1K	
 colormaterial.html	09-Sep-97 16:17	3K	
 colorpointer.html	09-Sep-97 16:17	4K	
 copypixels.html	09-Sep-97 16:17	9K	

 copyteximage1d.html	09-Sep-97 16:17	5K
 copyteximage2d.html	09-Sep-97 16:17	5K
 copytexsubimage1d.htm+	09-Sep-97 16:18	4K
 copytexsubimage2d.htm+	09-Sep-97 16:18	5K
 cullface.html	09-Sep-97 16:17	2K
 deletelists.html	09-Sep-97 16:18	1K
 deletetextures.html	09-Sep-97 16:17	1K
 depthfunc.html	09-Sep-97 16:17	2K
 depthmask.html	09-Sep-97 16:17	1K
 depthrange.html	09-Sep-97 16:17	2K
 drawarrays.html	09-Sep-97 16:16	3K
 drawbuffer.html	09-Sep-97 16:17	4K
 drawelements.html	09-Sep-97 16:17	3K
 drawpixels.html	09-Sep-97 16:17	17K
 edgeflag.html	09-Sep-97 16:16	2K
 edgeflagpointer.html	09-Sep-97 16:17	3K
 enable.html	09-Sep-97 16:17	13K
 enableclientstate.htm+	09-Sep-97 16:18	3K
 evalcoord.html	09-Sep-97 16:17	7K
 evalmesh.html	09-Sep-97 16:17	5K
 evalpoint.html	09-Sep-97 16:17	2K
 feedbackbuffer.html	09-Sep-97 16:17	8K
 finish.html	09-Sep-97 16:16	1K
 flush.html	09-Sep-97 16:17	1K
 fog.html	09-Sep-97 16:18	6K
 frontface.html	09-Sep-97 16:17	2K
 frustum.html	09-Sep-97 16:17	3K
 genlists.html	09-Sep-97 16:17	1K
 gentextures.html	09-Sep-97 16:18	2K

	get.html	09-Sep-97 16:18	61K
	getclipplane.html	09-Sep-97 16:17	1K
	geterror.html	09-Sep-97 16:17	3K
	getlight.html	09-Sep-97 16:17	7K
	getmap.html	09-Sep-97 16:17	4K
	getmaterial.html	09-Sep-97 16:17	4K
	getpixelmap.html	09-Sep-97 16:17	3K
	getpointerv.html	09-Sep-97 16:17	1K
	getpolygonstipple.htm+	09-Sep-97 16:17	1K
	getstring.html	09-Sep-97 16:17	3K
	gettexenv.html	09-Sep-97 16:17	2K
	gettexgen.html	09-Sep-97 16:17	3K
	getteximage.html	09-Sep-97 16:17	5K
	gettexlevelparameter.+	09-Sep-97 16:17	5K
	gettexp parameter.html	09-Sep-97 16:18	4K
	hint.html	09-Sep-97 16:17	3K
	index .html	09-Sep-97 16:17	2K
	indexmask.html	09-Sep-97 16:17	1K
	indexpointer.html	09-Sep-97 16:17	4K
	initnames.html	09-Sep-97 16:17	1K
	interleavedarrays.htm+	09-Sep-97 16:17	3K
	isenabled.html	09-Sep-97 16:17	4K
	islist.html	09-Sep-97 16:16	1K
	istexture.html	09-Sep-97 16:17	1K
	light.html	09-Sep-97 16:17	10K
	lightmodel.html	09-Sep-97 16:17	6K
	linestipple.html	09-Sep-97 16:17	3K
	linewidth.html	09-Sep-97 16:17	3K
	listbase.html	09-Sep-97 16:17	1K

 loadidentity.html	09-Sep-97 16:17	1K
 loadmatrix.html	09-Sep-97 16:17	2K
 loadname.html	09-Sep-97 16:17	1K
 logicop.html	09-Sep-97 16:16	4K
 map1.html	09-Sep-97 16:17	9K
 map2.html	09-Sep-97 16:17	12K
 mapgrid.html	09-Sep-97 16:17	3K
 material.html	09-Sep-97 16:17	7K
 matrixmode.html	09-Sep-97 16:17	1K
 multmatrix.html	09-Sep-97 16:17	3K
 newlist.html	09-Sep-97 16:16	5K
 normal.html	09-Sep-97 16:17	3K
 normalpointer.html	09-Sep-97 16:17	4K
 ortho.html	09-Sep-97 16:17	3K
 passthrough.html	09-Sep-97 16:17	1K
 pixelmap.html	09-Sep-97 16:16	8K
 pixelstore.html	09-Sep-97 16:17	14K
 pixeltransfer.html	09-Sep-97 16:17	13K
 pixelzoom.html	09-Sep-97 16:17	1K
 pointsize.html	09-Sep-97 16:17	4K
 polygonmode.html	09-Sep-97 16:18	3K
 polygonoffset.html	09-Sep-97 16:17	2K
 polygonstipple.html	09-Sep-97 16:17	2K
 prioritizetextures.ht+	09-Sep-97 16:17	3K
 pushattrib.html	09-Sep-97 16:17	10K
 pushclientattrib.html	09-Sep-97 16:17	3K
 pushmatrix.html	09-Sep-97 16:17	3K
 pushname.html	09-Sep-97 16:17	2K
 rasterpos.html	09-Sep-97 16:17	8K

 readbuffer.html	09-Sep-97 16:17	2K
 readpixels.html	09-Sep-97 16:17	11K
 rect.html	09-Sep-97 16:17	2K
 rendermode.html	09-Sep-97 16:17	3K
 rotate.html	09-Sep-97 16:17	2K
 scale.html	09-Sep-97 16:16	2K
 scissor.html	09-Sep-97 16:17	2K
 selectbuffer.html	09-Sep-97 16:17	4K
 shademodel.html	09-Sep-97 16:17	3K
 stencilfunc.html	09-Sep-97 16:17	5K
 stencilmask.html	09-Sep-97 16:17	1K
 stencilop.html	09-Sep-97 16:17	5K
 texcoord.html	09-Sep-97 16:16	5K
 texcoordpointer.html	09-Sep-97 16:18	4K
 texenv.html	09-Sep-97 16:17	8K
 texgen.html	09-Sep-97 16:17	8K
 teximage1d.html	09-Sep-97 16:17	14K
 teximage2d.html	09-Sep-97 16:17	14K
 texparameter.html	09-Sep-97 16:17	11K
 texsubimage1d.html	09-Sep-97 16:17	5K
 texsubimage2d.html	09-Sep-97 16:17	5K
 translate.html	09-Sep-97 16:17	2K
 vertex.html	09-Sep-97 16:17	4K
 vertexpointer.html	09-Sep-97 16:17	4K
 viewport.html	09-Sep-97 16:17	2K

NAME

glAccum - operate on the accumulation buffer

C SPECIFICATION

```
void glAccum( GLenum op,  
              GLfloat value )
```

PARAMETERS

op Specifies the accumulation buffer operation. Symbolic constants **GL_ACCUM**, **GL_LOAD**, **GL_ADD**, **GL_MULT**, and **GL_RETURN** are accepted.

value Specifies a floating-point value used in the accumulation buffer operation. *op* determines how *value* is used.

DESCRIPTION

The accumulation buffer is an extended-range color buffer. Images are not rendered into it. Rather, images rendered into one of the color buffers are added to the contents of the accumulation buffer after rendering. Effects such as antialiasing (of points, lines, and polygons), motion blur, and depth of field can be created by accumulating images generated with different transformation matrices.

Each pixel in the accumulation buffer consists of red, green, blue, and alpha values. The number of bits per component in the accumulation buffer depends on the implementation. You can examine this number by calling **glGetIntegerv** four times, with arguments **GL_ACCUM_RED_BITS**, **GL_ACCUM_GREEN_BITS**, **GL_ACCUM_BLUE_BITS**, and **GL_ACCUM_ALPHA_BITS**. Regardless of the number of bits per component, the range of values stored by each component is $[-1, 1]$. The accumulation buffer pixels are mapped one-to-one with frame buffer pixels.

glAccum operates on the accumulation buffer. The first argument, *op*, is a symbolic constant that selects an accumulation buffer operation. The second argument, *value*, is a floating-point value to be used in that operation. Five operations are specified: **GL_ACCUM**, **GL_LOAD**, **GL_ADD**, **GL_MULT**, and **GL_RETURN**.

All accumulation buffer operations are limited to the area of the current scissor box and applied identically to the red, green, blue, and alpha components of each pixel. If a **glAccum** operation results in a value outside the range $[-1, 1]$, the contents of an accumulation buffer pixel component are undefined.

The operations are as follows:

- GL_ACCUM** Obtains R, G, B, and A values from the buffer currently selected for reading (see **glReadBuffer**). Each component value is divided by $2^n - 1$, where n is the number of bits allocated to each color component in the currently selected buffer. The result is a floating-point value in the range $[0, 1]$, which is multiplied by *value* and added to the corresponding pixel component in the accumulation buffer, thereby updating the accumulation buffer.
- GL_LOAD** Similar to **GL_ACCUM**, except that the current value in the accumulation buffer is not used in the calculation of the new value. That is, the R, G, B, and A values from the currently selected buffer are divided by $2^n - 1$, multiplied by *value*, and then stored in the corresponding accumulation buffer cell, overwriting the current value.
- GL_ADD** Adds *value* to each R, G, B, and A in the accumulation buffer.
- GL_MULT** Multiplies each R, G, B, and A in the accumulation buffer by *value* and returns the scaled component to its corresponding accumulation buffer location.
- GL_RETURN** Transfers accumulation buffer values to the color buffer or buffers currently selected for writing. Each R, G, B, and A component is multiplied by *value*, then multiplied by $2^n - 1$, clamped to the range $[0, 2^n - 1]$, and stored in the corresponding display buffer cell. The only fragment operations that are applied to this transfer are pixel ownership, scissor,

dithering, and color writemasks.

To clear the accumulation buffer, call **glClearAccum** with R, G, B, and A values to set it to, then call **glClear** with the accumulation buffer enabled.

NOTES

Only pixels within the current scissor box are updated by a **glAccum** operation.

ERRORS

GL_INVALID_ENUM is generated if *op* is not an accepted value.

GL_INVALID_OPERATION is generated if there is no accumulation buffer.

GL_INVALID_OPERATION is generated if **glAccum** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_ACCUM_RED_BITS**

glGet with argument **GL_ACCUM_GREEN_BITS**

glGet with argument **GL_ACCUM_BLUE_BITS**

glGet with argument **GL_ACCUM_ALPHA_BITS**

SEE ALSO

glBlendFunc, **glClear**, **glClearAccum**, **glCopyPixels**, **glGet**, **glLogicOp**, **glPixelStore**, **glPixelTransfer**, **glReadBuffer**, **glReadPixels**, **glScissor**, **glStencilOp**

NAME

glAlphaFunc - specify the alpha test function

C SPECIFICATION

```
void glAlphaFunc( GLenum func,  
                  GLclampf ref )
```

PARAMETERS

func Specifies the alpha comparison function. Symbolic constants **GL_NEVER**, **GL_LESS**, **GL_EQUAL**, **GL_LEQUAL**, **GL_GREATER**, **GL_NOTEQUAL**, **GL_GEQUAL**, and **GL_ALWAYS** are accepted. The initial value is **GL_ALWAYS**.

ref Specifies the reference value that incoming alpha values are compared to. This value is clamped to the range 0 through 1, where 0 represents the lowest possible alpha value and 1 the highest possible value. The initial reference value is 0.

DESCRIPTION

The alpha test discards fragments depending on the outcome of a comparison between an incoming fragment's alpha value and a constant reference value. **glAlphaFunc** specifies the reference value and the comparison function. The comparison is performed only if alpha testing is enabled. By default, it is not enabled. (See **glEnable** and **glDisable** of **GL_ALPHA_TEST**.)

func and *ref* specify the conditions under which the pixel is drawn. The incoming alpha value is compared to *ref* using the function specified by *func*. If the value passes the comparison, the incoming fragment is drawn if it also passes subsequent stencil and depth buffer tests. If the value fails the comparison, no change is made to the frame buffer at that pixel location. The comparison functions are as follows:

GL_NEVER	Never passes.
GL_LESS	Passes if the incoming alpha value is less than the reference value.
GL_EQUAL	Passes if the incoming alpha value is

equal to the reference value.

GL_LEQUAL Passes if the incoming alpha value is less than or equal to the reference value.

GL_GREATER Passes if the incoming alpha value is greater than the reference value.

GL_NOTEQUAL Passes if the incoming alpha value is not equal to the reference value.

GL_GEQUAL Passes if the incoming alpha value is greater than or equal to the reference value.

GL_ALWAYS Always passes (initial value).

glAlphaFunc operates on all pixel write operations, including those resulting from the scan conversion of points, lines, polygons, and bitmaps, and from pixel draw and copy operations. **glAlphaFunc** does not affect screen clear operations.

NOTES

Alpha testing is performed only in RGBA mode.

ERRORS

GL_INVALID_ENUM is generated if *func* is not an accepted value.

GL_INVALID_OPERATION is generated if **glAlphaFunc** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_ALPHA_TEST_FUNC**

glGet with argument **GL_ALPHA_TEST_REF**

glIsEnabled with argument **GL_ALPHA_TEST**

SEE ALSO

glBlendFunc, **glClear**, **glDepthFunc**, **glEnable**, **glStencilFunc**

NAME

glAreTexturesResident - determine if textures are loaded in texture memory

C SPECIFICATION

```
GLboolean glAreTexturesResident( GLsizei n,  
                                  const GLuint *textures,  
                                  GLboolean *residences )
```

PARAMETERS

<i>n</i>	Specifies the number of textures to be queried.
<i>textures</i>	Specifies an array containing the names of the textures to be queried.
<i>residences</i>	Specifies an array in which the texture residence status is returned. The residence status of a texture named by an element of <i>textures</i> is returned in the corresponding element of <i>residences</i> .

DESCRIPTION

GL establishes a ``working set'' of textures that are resident in texture memory. These textures can be bound to a texture target much more efficiently than textures that are not resident.

glAreTexturesResident queries the texture residence status of the *n* textures named by the elements of *textures*. If all the named textures are resident, **glAreTexturesResident** returns **GL_TRUE**, and the contents of *residences* are undisturbed. If not all the named textures are resident, **glAreTexturesResident** returns **GL_FALSE**, and detailed status is returned in the *n* elements of *residences*. If an element of *residences* is **GL_TRUE**, then the texture named by the corresponding element of *textures* is resident.

The residence status of a single bound texture may also be queried by calling **glGetTexParameter** with the *target* argument set to the target to which the texture is bound, and the *p_name* argument set to **GL_TEXTURE_RESIDENT**. This is the only way that the residence status of a default texture can be queried.

NOTES

glAreTexturesResident is available only if the GL version is 1.1 or greater.

glAreTexturesResident returns the residency status of the textures at the time of invocation. It does not guarantee that the textures will remain resident at any other time.

If textures reside in virtual memory (there is no texture memory), they are considered always resident.

Some implementations may not load a texture until the first use of that texture.

ERRORS

GL_INVALID_VALUE is generated if *n* is negative.

GL_INVALID_VALUE is generated if any element in *textures* is 0 or does not name a texture. In that case, the function returns **GL_FALSE** and the contents of *residences* is indeterminate.

GL_INVALID_OPERATION is generated if **glAreTexturesResident** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGetTexParameter with parameter name **GL_TEXTURE_RESIDENT** retrieves the residence status of a currently bound texture.

SEE ALSO

glBindTexture, **glGetTexParameter**, **glPrioritizeTextures**, **glTexImage1D**, **glTexImage2D**, **glTexParameter**

NAME

glArrayElement - render a vertex using the specified vertex array element

C SPECIFICATION

```
void glArrayElement( GLint i )
```

PARAMETERS

i Specifies an index into the enabled vertex data arrays.

DESCRIPTION

glArrayElement commands are used within **glBegin/glEnd** pairs to specify vertex and attribute data for point, line, and polygon primitives. If **GL_VERTEX_ARRAY** is enabled when **glArrayElement** is called, a single vertex is drawn, using vertex and attribute data taken from location *i* of the enabled arrays. If **GL_VERTEX_ARRAY** is not enabled, no drawing occurs but the attributes corresponding to the enabled arrays are modified.

Use **glArrayElement** to construct primitives by indexing vertex data, rather than by streaming through arrays of data in first-to-last order. Because each call specifies only a single vertex, it is possible to explicitly specify per-primitive attributes such as a single normal per individual triangle.

Changes made to array data between the execution of **glBegin** and the corresponding execution of **glEnd** may affect calls to **glArrayElement** that are made within the same **glBegin/glEnd** period in non-sequential ways. That is, a call to **glArrayElement** that precedes a change to array data may access the changed data, and a call that follows a change to array data may access original data.

NOTES

glArrayElement is available only if the GL version is 1.1 or greater.

glArrayElement is included in display lists. If **glArrayElement** is entered into a display list, the necessary array data (determined by the array pointers and enables) is also entered into the display list. Because the array

pointers and enables are client-side state, their values affect display lists when the lists are created, not when the lists are executed.

SEE ALSO

`glColorPointer`, `glDrawArrays`, `glEdgeFlagPointer`,
`glGetPointerv`,
`glIndexPointer`, `glInterleavedArrays`, `glNormalPointer`,
`glTexCoordPointer`, `glVertexPointer`

NAME

glBegin, **glEnd** - delimit the vertices of a primitive or a group of like primitives

C SPECIFICATION

```
void glBegin( GLenum mode )
```

PARAMETERS

mode Specifies the primitive or primitives that will be created from vertices presented between **glBegin** and the subsequent **glEnd**. Ten symbolic constants are accepted: **GL_POINTS**, **GL_LINES**, **GL_LINE_STRIP**, **GL_LINE_LOOP**, **GL_TRIANGLES**, **GL_TRIANGLE_STRIP**, **GL_TRIANGLE_FAN**, **GL_QUADS**, **GL_QUAD_STRIP**, and **GL_POLYGON**.

C SPECIFICATION

```
void glEnd( void )
```

DESCRIPTION

glBegin and **glEnd** delimit the vertices that define a primitive or a group of like primitives. **glBegin** accepts a single argument that specifies in which of ten ways the vertices are interpreted. Taking n as an integer count starting at one, and N as the total number of vertices specified, the interpretations are as follows:

GL_POINTS	Treats each vertex as a single point. Vertex n defines point n . N points are drawn.
GL_LINES	Treats each pair of vertices as an independent line segment. Vertices $2n-1$ and $2n$ define line n . $N/2$ lines are drawn.
GL_LINE_STRIP	Draws a connected group of line segments from the first vertex to the last. Vertices n and $n+1$ define line n . $N-1$ lines are drawn.
GL_LINE_LOOP	Draws a connected group of line

segments from the first vertex to the last, then back to the first. Vertices n and $n+1$ define line n . The last line, however, is defined by vertices N and 1 . N lines are drawn.

GL_TRIANGLES

Treats each triplet of vertices as an independent triangle. Vertices $3n-2$, $3n-1$, and $3n$ define triangle n . $N/3$ triangles are drawn.

GL_TRIANGLE_STRIP

Draws a connected group of triangles. One triangle is defined for each vertex presented after the first two vertices. For odd n , vertices n , $n+1$, and $n+2$ define triangle n . For even n , vertices $n+1$, n , and $n+2$ define triangle n . $N-2$ triangles are drawn.

GL_TRIANGLE_FAN

Draws a connected group of triangles. One triangle is defined for each vertex presented after the first two vertices. Vertices 1 , $n+1$, and $n+2$ define triangle n . $N-2$ triangles are drawn.

GL_QUADS

Treats each group of four vertices as an independent quadrilateral. Vertices $4n-3$, $4n-2$, $4n-1$, and $4n$ define quadrilateral n . $N/4$ quadrilaterals are drawn.

GL_QUAD_STRIP

Draws a connected group of quadrilaterals. One quadrilateral is defined for each pair of vertices presented after the first pair. Vertices $2n-1$, $2n$, $2n+2$, and $2n+1$ define quadrilateral n . $N/2-1$ quadrilaterals are drawn. Note that the order in which vertices are used to construct a quadrilateral from strip data is different from that used with independent data.

GL_POLYGON

Draws a single, convex polygon. Vertices 1 through N define this polygon.

Only a subset of GL commands can be used between **glBegin** and **glEnd**. The commands are **glVertex**, **glColor**, **glIndex**, **glNormal**, **glTexCoord**, **glEvalCoord**, **glEvalPoint**, **glArrayElement**, **glMaterial**, and **glEdgeFlag**. Also, it is acceptable to use **glCallList** or **glCallLists** to execute display lists that include only the preceding commands. If any other GL command is executed between **glBegin** and **glEnd**, the error flag is set and the command is ignored.

Regardless of the value chosen for *mode*, there is no limit to the number of vertices that can be defined between **glBegin** and **glEnd**. Lines, triangles, quadrilaterals, and polygons that are incompletely specified are not drawn. Incomplete specification results when either too few vertices are provided to specify even a single primitive or when an incorrect multiple of vertices is specified. The incomplete primitive is ignored; the rest are drawn.

The minimum specification of vertices for each primitive is as follows: 1 for a point, 2 for a line, 3 for a triangle, 4 for a quadrilateral, and 3 for a polygon. Modes that require a certain multiple of vertices are **GL_LINES** (2), **GL_TRIANGLES** (3), **GL_QUADS** (4), and **GL_QUAD_STRIP** (2).

ERRORS

GL_INVALID_ENUM is generated if *mode* is set to an unaccepted value.

GL_INVALID_OPERATION is generated if **glBegin** is executed between a **glBegin** and the corresponding execution of **glEnd**.

GL_INVALID_OPERATION is generated if **glEnd** is executed without being preceded by a **glBegin**.

GL_INVALID_OPERATION is generated if a command other than **glVertex**, **glColor**, **glIndex**, **glNormal**, **glTexCoord**, **glEvalCoord**, **glEvalPoint**, **glArrayElement**, **glMaterial**, **glEdgeFlag**, **glCallList**, or **glCallLists** is executed between the execution of **glBegin** and the corresponding execution **glEnd**.

Execution of **glEnableClientState**, **glDisableClientState**, **glEdgeFlagPointer**, **glTexCoordPointer**, **glColorPointer**, **glIndexPointer**, **glNormalPointer**, **glVertexPointer**, **glInterleavedArrays**, or **glPixelStore** is not

allowed after a call to **glBegin** and before the corresponding call to **glEnd**, but an error may or may not be generated.

SEE ALSO

glArrayElement, glCallList, glCallLists, glColor, glEdgeFlag, glEvalCoord, glEvalPoint, glIndex, glMaterial, glNormal, glTexCoord, glVertex

NAME

glBindTexture - bind a named texture to a texturing target

C SPECIFICATION

```
void glBindTexture( GLenum target,  
                   GLuint texture )
```

PARAMETERS

target Specifies the target to which the texture is bound.
Must be either **GL_TEXTURE_1D** or **GL_TEXTURE_2D**.

texture Specifies the name of a texture.

DESCRIPTION

glBindTexture lets you create or use a named texture. Calling **glBindTexture** with *target* set to **GL_TEXTURE_1D** or **GL_TEXTURE_2D** and *texture* set to the name of the new texture binds the texture name to the target. When a texture is bound to a target, the previous binding for that target is automatically broken.

Texture names are unsigned integers. The value zero is reserved to represent the default texture for each texture target. Texture names and the corresponding texture contents are local to the shared display-list space (see **glXCreateContext**) of the current GL rendering context; two rendering contexts share texture names only if they also share display lists.

You may use **glGenTextures** to generate a set of new texture names.

When a texture is first bound, it assumes the dimensionality of its target: A texture first bound to **GL_TEXTURE_1D** becomes 1-dimensional and a texture first bound to **GL_TEXTURE_2D** becomes 2-dimensional. The state of a 1-dimensional texture immediately after it is first bound is equivalent to the state of the default **GL_TEXTURE_1D** at GL initialization, and similarly for 2-dimensional textures.

While a texture is bound, GL operations on the target to which it is bound affect the bound texture, and queries of the target to which it is bound return state from the bound

texture. If texture mapping of the dimensionality of the target to which a texture is bound is active, the bound texture is used. In effect, the texture targets become aliases for the textures currently bound to them, and the texture name zero refers to the default textures that were bound to them at initialization.

A texture binding created with **glBindTexture** remains active until a different texture is bound to the same target, or until the bound texture is deleted with **glDeleteTextures**.

Once created, a named texture may be re-bound to the target of the matching dimensionality as often as needed. It is usually much faster to use **glBindTexture** to bind an existing named texture to one of the texture targets than it is to reload the texture image using **glTexImage1D** or **glTexImage2D**. For additional control over performance, use **glPrioritizeTextures**.

glBindTexture is included in display lists.

NOTES

glBindTexture is available only if the GL version is 1.1 or greater.

ERRORS

GL_INVALID_ENUM is generated if *target* is not one of the allowable values.

GL_INVALID_OPERATION is generated if *texture* has a dimensionality which doesn't match that of *target*.

GL_INVALID_OPERATION is generated if **glBindTexture** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_TEXTURE_1D_BINDING**

glGet with argument **GL_TEXTURE_2D_BINDING**

SEE ALSO

glAreTexturesResident, **glDeleteTextures**, **glGenTextures**,
glGet,
glGetTexParameter, **glIsTexture**, **glPrioritizeTextures**,
glTexImage1D, **glTexImage2D**, **glTexParameter**

NAME

glBitmap - draw a bitmap

C SPECIFICATION

```
void glBitmap( GLsizei width,  
               GLsizei height,  
               GLfloat xorig,  
               GLfloat yorig,  
               GLfloat xmove,  
               GLfloat ymove,  
               const GLubyte *bitmap )
```

PARAMETERS

width, *height* Specify the pixel width and height of the bitmap image.

xorig, *yorig* Specify the location of the origin in the bitmap image. The origin is measured from the lower left corner of the bitmap, with right and up being the positive axes.

xmove, *ymove* Specify the x and y offsets to be added to the current raster position after the bitmap is drawn.

bitmap Specifies the address of the bitmap image.

DESCRIPTION

A bitmap is a binary image. When drawn, the bitmap is positioned relative to the current raster position, and frame buffer pixels corresponding to 1's in the bitmap are written using the current raster color or index. Frame buffer pixels corresponding to 0's in the bitmap are not modified.

glBitmap takes seven arguments. The first pair specifies the width and height of the bitmap image. The second pair specifies the location of the bitmap origin relative to the lower left corner of the bitmap image. The third pair of arguments specifies x and y offsets to be added to the current raster position after the bitmap has been drawn. The final argument is a pointer to the bitmap image itself.

The bitmap image is interpreted like image data for the **glDrawPixels** command, with *width* and *height* corresponding to the width and height arguments of that command, and with *type* set to **GL_BITMAP** and *format* set to **GL_COLOR_INDEX**. Modes specified using **glPixelStore** affect the interpretation of bitmap image data; modes specified using **glPixelTransfer** do not.

If the current raster position is invalid, **glBitmap** is ignored. Otherwise, the lower left corner of the bitmap image is positioned at the window coordinates

$$\begin{array}{rcl} x & = & | \ x \ - \ x \ | \\ w & & r \ \ o \\ y & = & | \ y \ - \ y \ | \\ w & & r \ \ o \end{array}$$

where (x ,y) is the raster position and (x ,y) is the bitmap origin. Fragments are then generated for each pixel corresponding to a 1 (one) in the bitmap image. These fragments are generated using the current raster z coordinate, color or color index, and current raster texture coordinates. They are then treated just as if they had been generated by a point, line, or polygon, including texture mapping, fogging, and all per-fragment operations such as alpha and depth testing.

After the bitmap has been drawn, the x and y coordinates of the current raster position are offset by *xmove* and *ymove*. No change is made to the z coordinate of the current raster position, or to the current raster color, texture coordinates, or index.

NOTES

To set a valid raster position outside the viewport, first set a valid raster position inside the viewport, then call **glBitmap** with NULL as the *bitmap* parameter and with *xmove* and *ymove* set to the offsets of the new raster position. This technique is useful when panning an image around the viewport.

ERRORS

GL_INVALID_VALUE is generated if *width* or *height* is negative.

GL_INVALID_OPERATION is generated if **glBitmap** is executed between the execution of **glBegin** and the corresponding

execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_CURRENT_RASTER_POSITION**
glGet with argument **GL_CURRENT_RASTER_COLOR**
glGet with argument **GL_CURRENT_RASTER_INDEX**
glGet with argument **GL_CURRENT_RASTER_TEXTURE_COORDS**
glGet with argument **GL_CURRENT_RASTER_POSITION_VALID**

SEE ALSO

glDrawPixels, **glPixelStore**, **glPixelTransfer**, **glRasterPos**

NAME

glBlendColorEXT - set the blend color

C SPECIFICATION

```
void glBlendColorEXT( GLclampf red,  
                     GLclampf green,  
                     GLclampf blue,  
                     GLclampf alpha )
```

PARAMETERS

GL_BLEND_COLOR_EXT

red, green, blue, alpha specify the components of

DESCRIPTION

The **GL_BLEND_COLOR_EXT** may be used to calculate the source and destination blending factors. See **glBlendFunc** for a complete description of the blending operations. Initially the **GL_BLEND_COLOR_EXT** is set to (0,0,0,0).

NOTES

glBlendColorEXT is part of the **EXT_blend_color** extension, not part of the core GL command set. If **GL_EXT_blend_color** is included in the string returned by **glGetString**, when called with argument **GL_EXTENSIONS**, extension **EXT_blend_color** is supported by the connection.

ERRORS

GL_INVALID_OPERATION is generated if **glBlendColorEXT** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with an argument of **GL_BLEND_COLOR_EXT**.

SEE ALSO

glBlendFunc, **glGetString**.

NAME

glBlendFunc - specify pixel arithmetic

C SPECIFICATION

```
void glBlendFunc( GLenum sfactor,
                  GLenum dfactor )
```

PARAMETERS

sfactor Specifies how the red, green, blue, and alpha source blending factors are computed. Nine symbolic constants are accepted: **GL_ZERO**, **GL_ONE**, **GL_DST_COLOR**, **GL_ONE_MINUS_DST_COLOR**, **GL_SRC_ALPHA**, **GL_ONE_MINUS_SRC_ALPHA**, **GL_DST_ALPHA**, **GL_ONE_MINUS_DST_ALPHA**, and **GL_SRC_ALPHA_SATURATE**. The initial value is **GL_ONE**.

dfactor Specifies how the red, green, blue, and alpha destination blending factors are computed. Eight symbolic constants are accepted: **GL_ZERO**, **GL_ONE**, **GL_SRC_COLOR**, **GL_ONE_MINUS_SRC_COLOR**, **GL_SRC_ALPHA**, **GL_ONE_MINUS_SRC_ALPHA**, **GL_DST_ALPHA**, and **GL_ONE_MINUS_DST_ALPHA**. The initial value is **GL_ZERO**.

DESCRIPTION

In RGBA mode, pixels can be drawn using a function that blends the incoming (source) RGBA values with the RGBA values that are already in the frame buffer (the destination values). Blending is initially disabled. Use **glEnable** and **glDisable** with argument **GL_BLEND** to enable and disable blending.

glBlendFunc defines the operation of blending when it is enabled. *sfactor* specifies which of nine methods is used to scale the source color components. *dfactor* specifies which of eight methods is used to scale the destination color components. The eleven possible methods are described in the following table. Each method defines four scale factors, one each for red, green, blue, and alpha.

In the table and in subsequent equations, source and destination color components are referred to as (R ,G ,B ,A) and (R ,G ,B ,A). They are understood to have **integer** values **between** 0 and (k ,k ,k ,k), where

R G B A
mc

$$k_c = 2^{-1}$$

and (mR,mG,mB,mA) is the number of red, green, blue, and alpha bitplanes.

Source and destination scale factors are referred to as (s_r,s_g,s_b,s_a) and (d_r,d_g,d_b,d_a). The scale factors described in the table, Gdenoted (f_r,f_g,f_b,f_a), represent either source or destination factors. All scale factors have range [0,1].

parameter	(f _r , f _g , f _b , f _a)
GL_ZERO	(0, 0, 0, 0)
GL_ONE	(1, 1, 1, 1)
GL_SRC_COLOR	(R /k _r , G /k _g , B /k _b , A /k _a)
GL_ONE_MINUS_SRC_COLOR	(1, 1, 1,s ₁)R- (R /k _r , G /k _g , B /k _b , A /k _a)
GL_DST_COLOR	(R /k _r , G /k _g , B /k _b , A /k _a) s _a A
GL_ONE_MINUS_DST_COLOR	(1, 1, 1,d ₁)R- (R /k _r , G /k _g , B /k _b , A /k _a)
GL_SRC_ALPHA	(A /k _a , A /k _a , A /k _a , A /k _a) d _a A
GL_ONE_MINUS_SRC_ALPHA	(1, 1, 1,s ₁)A- (A /k _a , A /k _a , A /k _a , A /k _a)
GL_DST_ALPHA	(A /k _a , A /k _a , A /k _a , A /k _a) s _a A
GL_ONE_MINUS_DST_ALPHA	(1, 1, 1,d ₁)A- (A /k _a , A /k _a , A /k _a , A /k _a)
GL_SRC_ALPHA_SATURATE	(i, i, i,d ₁)A d _a A d _a A

In the table,

$$i = \min(A, k - A) / k$$

$$s = A \quad d = A$$

To determine the blended RGBA values of a pixel when drawing in RGBA mode, the system uses the following equations:

$$R = \min(k, R_s + R_d)$$

$$G_d = \min(kR, G_{ss}R + G_{dd}R)$$

$$B_d = \min(kG, B_{ss}G + B_{dd}G)$$

$$A_d = \min(kB, A_{ss}B + A_{dd}B)$$

$$d = A \quad s = A \quad d = A$$

Despite the apparent precision of the above equations, blending arithmetic is not exactly specified, because blending operates with imprecise integer color values. However, a blend factor that should be equal to 1 is guaranteed not to modify its multiplicand, and a blend factor equal to 0 reduces its multiplicand to 0. For example, when *sfactor* is **GL_SRC_ALPHA**, *dfactor* is **GL_ONE_MINUS_SRC_ALPHA**, and A is equal to k, the equations reduce to simple replacement: A

$$R = R$$

Gd = Gs
Bd = Bs
Ad = As
d s

EXAMPLES

Transparency is best implemented using blend function (**GL_SRC_ALPHA**, **GL_ONE_MINUS_SRC_ALPHA**) with primitives sorted from farthest to nearest. Note that this transparency calculation does not require the presence of alpha bitplanes in the frame buffer.

Blend function (**GL_SRC_ALPHA**, **GL_ONE_MINUS_SRC_ALPHA**) is also useful for rendering antialiased points and lines in arbitrary order.

Polygon antialiasing is optimized using blend function (**GL_SRC_ALPHA_SATURATE**, **GL_ONE**) with polygons sorted from nearest to farthest. (See the **glEnable**, **glDisable** reference page and the **GL_POLYGON_SMOOTH** argument for information on polygon antialiasing.) Destination alpha bitplanes, which must be present for this blend function to operate correctly, store the accumulated coverage.

NOTES

Incoming (source) alpha is correctly thought of as a material opacity, ranging from 1.0 (K), representing complete opacity, to 0.0 (0), representing complete transparency.

When more than one color buffer is enabled for drawing, the GL performs blending separately for each enabled buffer, using the contents of that buffer for destination color. (See **glDrawBuffer**.)

Blending affects only RGBA rendering. It is ignored by color index renderers.

ERRORS

GL_INVALID_ENUM is generated if either *sfactor* or *dfactor* is not an accepted value.

GL_INVALID_OPERATION is generated if **glBlendFunc** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_BLEND_SRC**
glGet with argument **GL_BLEND_DST**
glIsEnabled with argument **GL_BLEND**

SEE ALSO

`glAlphaFunc`, `glClear`, `glDrawBuffer`, `glEnable`, `glLogicOp`,
`glStencilFunc`

NAME

glCallList - execute a display list

C SPECIFICATION

```
void glCallList( GLuint list )
```

PARAMETERS

list Specifies the integer name of the display list to be executed.

DESCRIPTION

glCallList causes the named display list to be executed. The commands saved in the display list are executed in order, just as if they were called without using a display list. If *list* has not been defined as a display list, **glCallList** is ignored.

glCallList can appear inside a display list. To avoid the possibility of infinite recursion resulting from display lists calling one another, a limit is placed on the nesting level of display lists during display-list execution. This limit is at least 64, and it depends on the implementation.

GL state is not saved and restored across a call to **glCallList**. Thus, changes made to GL state during the execution of a display list remain after execution of the display list is completed. Use **glPushAttrib**, **glPopAttrib**, **glPushMatrix**, and **glPopMatrix** to preserve GL state across **glCallList** calls.

NOTES

Display lists can be executed between a call to **glBegin** and the corresponding call to **glEnd**, as long as the display list includes only commands that are allowed in this interval.

ASSOCIATED GETS

glGet with argument **GL_MAX_LIST_NESTING**
glIsList

SEE ALSO

glCallLists, **glDeleteLists**, **glGenLists**, **glNewList**,
glPushAttrib, **glPushMatrix**

NAME

glCallLists - execute a list of display lists

C SPECIFICATION

```
void glCallLists( GLsizei n,  
                 GLenum type,  
                 const GLvoid *lists )
```

PARAMETERS

- n* Specifies the number of display lists to be executed.
- type* Specifies the type of values in *lists*. Symbolic constants **GL_BYTE**, **GL_UNSIGNED_BYTE**, **GL_SHORT**, **GL_UNSIGNED_SHORT**, **GL_INT**, **GL_UNSIGNED_INT**, **GL_FLOAT**, **GL_2_BYTES**, **GL_3_BYTES**, and **GL_4_BYTES** are accepted.
- lists* Specifies the address of an array of name offsets in the display list. The pointer type is void because the offsets can be bytes, shorts, ints, or floats, depending on the value of *type*.

DESCRIPTION

glCallLists causes each display list in the list of names passed as *lists* to be executed. As a result, the commands saved in each display list are executed in order, just as if they were called without using a display list. Names of display lists that have not been defined are ignored.

glCallLists provides an efficient means for executing more than one display list. *type* allows lists with various name formats to be accepted. The formats are as follows:

- | | |
|-------------------------|----------------------------------------------------------------------------------------------------------|
| GL_BYTE | <i>lists</i> is treated as an array of signed bytes, each in the range -128 through 127. |
| GL_UNSIGNED_BYTE | <i>lists</i> is treated as an array of unsigned bytes, each in the range 0 through 255. |
| GL_SHORT | <i>lists</i> is treated as an array of signed two-byte integers, each in the range -32768 through 32767. |

GL_UNSIGNED_SHORT	<i>lists</i> is treated as an array of unsigned two-byte integers, each in the range 0 through 65535.
GL_INT	<i>lists</i> is treated as an array of signed four-byte integers.
GL_UNSIGNED_INT	<i>lists</i> is treated as an array of unsigned four-byte integers.
GL_FLOAT	<i>lists</i> is treated as an array of four-byte floating-point values.
GL_2_BYTES	<i>lists</i> is treated as an array of unsigned bytes. Each pair of bytes specifies a single display-list name. The value of the pair is computed as 256 times the unsigned value of the first byte plus the unsigned value of the second byte.
GL_3_BYTES	<i>lists</i> is treated as an array of unsigned bytes. Each triplet of bytes specifies a single display-list name. The value of the triplet is computed as 65536 times the unsigned value of the first byte, plus 256 times the unsigned value of the second byte, plus the unsigned value of the third byte.
GL_4_BYTES	<i>lists</i> is treated as an array of unsigned bytes. Each quadruplet of bytes specifies a single display-list name. The value of the quadruplet is computed as 16777216 times the unsigned value of the first byte, plus 65536 times the unsigned value of the second byte, plus 256 times the unsigned value of the third byte, plus the unsigned value of the fourth byte.

The list of display-list names is not null-terminated. Rather, *n* specifies how many names are to be taken from

lists.

An additional level of indirection is made available with the **glListBase** command, which specifies an unsigned offset that is added to each display-list name specified in *lists* before that display list is executed.

glCallLists can appear inside a display list. To avoid the possibility of infinite recursion resulting from display lists calling one another, a limit is placed on the nesting level of display lists during display-list execution. This limit must be at least 64, and it depends on the implementation.

GL state is not saved and restored across a call to **glCallLists**. Thus, changes made to GL state during the execution of the display lists remain after execution is completed. Use **glPushAttrib**, **glPopAttrib**, **glPushMatrix**, and **glPopMatrix** to preserve GL state across **glCallLists** calls.

NOTES

Display lists can be executed between a call to **glBegin** and the corresponding call to **glEnd**, as long as the display list includes only commands that are allowed in this interval.

ERRORS

GL_INVALID_VALUE is generated if *n* is negative.

GL_INVALID_ENUM is generated if *type* is not one of **GL_BYTE**, **GL_UNSIGNED_BYTE**, **GL_SHORT**, **GL_UNSIGNED_SHORT**, **GL_INT**, **GL_UNSIGNED_INT**, **GL_FLOAT**, **GL_2_BYTES**, **GL_3_BYTES**, **GL_4_BYTES**.

ASSOCIATED GETS

glGet with argument **GL_LIST_BASE**
glGet with argument **GL_MAX_LIST_NESTING**
glIsList

SEE ALSO

glCallList, **glDeleteLists**, **glGenLists**, **glListBase**,
glNewList, **glPushAttrib**,
glPushMatrix

NAME

glClear - clear buffers to preset values

C SPECIFICATION

```
void glClear( GLbitfield mask )
```

PARAMETERS

mask Bitwise OR of masks that indicate the buffers to be cleared. The four masks are **GL_COLOR_BUFFER_BIT**, **GL_DEPTH_BUFFER_BIT**, **GL_ACCUM_BUFFER_BIT**, and **GL_STENCIL_BUFFER_BIT**.

DESCRIPTION

glClear sets the bitplane area of the window to values previously selected by **glClearColor**, **glClearIndex**, **glClearDepth**, **glClearStencil**, and **glClearAccum**. Multiple color buffers can be cleared simultaneously by selecting more than one buffer at a time using **glDrawBuffer**.

The pixel ownership test, the scissor test, dithering, and the buffer writemasks affect the operation of **glClear**. The scissor box bounds the cleared region. Alpha function, blend function, logical operation, stenciling, texture mapping, and depth-buffering are ignored by **glClear**.

glClear takes a single argument that is the bitwise OR of several values indicating which buffer is to be cleared.

The values are as follows:

GL_COLOR_BUFFER_BIT	Indicates the buffers currently enabled for color writing.
GL_DEPTH_BUFFER_BIT	Indicates the depth buffer.
GL_ACCUM_BUFFER_BIT	Indicates the accumulation buffer.
GL_STENCIL_BUFFER_BIT	Indicates the stencil buffer.

The value to which each buffer is cleared depends on the setting of the clear value for that buffer.

NOTES

If a buffer is not present, then a **glClear** directed at that buffer has no effect.

ERRORS

GL_INVALID_VALUE is generated if any bit other than the four defined bits is set in *mask*.

GL_INVALID_OPERATION is generated if **glClear** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_ACCUM_CLEAR_VALUE**

glGet with argument **GL_DEPTH_CLEAR_VALUE**

glGet with argument **GL_INDEX_CLEAR_VALUE**

glGet with argument **GL_COLOR_CLEAR_VALUE**

glGet with argument **GL_STENCIL_CLEAR_VALUE**

SEE ALSO

glClearAccum, **glClearColor**, **glClearDepth**, **glClearIndex**,
glClearStencil, **glDrawBuffer**, **glScissor**

NAME

glClearAccum - specify clear values for the accumulation buffer

C SPECIFICATION

```
void glClearAccum( GLfloat red,  
                  GLfloat green,  
                  GLfloat blue,  
                  GLfloat alpha )
```

PARAMETERS

red, *green*, *blue*, *alpha*

Specify the red, green, blue, and alpha values used when the accumulation buffer is cleared. The initial values are all 0.

DESCRIPTION

glClearAccum specifies the red, green, blue, and alpha values used by **glClear** to clear the accumulation buffer.

Values specified by **glClearAccum** are clamped to the range $[-1,1]$.

ERRORS

GL_INVALID_OPERATION is generated if **glClearAccum** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_ACCUM_CLEAR_VALUE**

SEE ALSO

glClear

NAME

glClearColor - specify clear values for the color buffers

C SPECIFICATION

```
void glClearColor( GLclampf red,  
                  GLclampf green,  
                  GLclampf blue,  
                  GLclampf alpha )
```

PARAMETERS

red, *green*, *blue*, *alpha*

Specify the red, green, blue, and alpha values used when the color buffers are cleared. The initial values are all 0.

DESCRIPTION

glClearColor specifies the red, green, blue, and alpha values used by **glClear** to clear the color buffers. Values specified by **glClearColor** are clamped to the range [0,1].

ERRORS

GL_INVALID_OPERATION is generated if **glClearColor** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_COLOR_CLEAR_VALUE**

SEE ALSO

glClear

NAME

glClearDepth - specify the clear value for the depth buffer

C SPECIFICATION

```
void glClearDepth( GLclampd depth )
```

PARAMETERS

depth Specifies the depth value used when the depth buffer is cleared. The initial value is 1.

DESCRIPTION

glClearDepth specifies the depth value used by **glClear** to clear the depth buffer. Values specified by **glClearDepth** are clamped to the range [0,1].

ERRORS

GL_INVALID_OPERATION is generated if **glClearDepth** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_DEPTH_CLEAR_VALUE**

SEE ALSO

glClear

NAME

glClearIndex - specify the clear value for the color index buffers

C SPECIFICATION

```
void glClearIndex( GLfloat c )
```

PARAMETERS

c Specifies the index used when the color index buffers are cleared. The initial value is 0.

DESCRIPTION

glClearIndex specifies the index used by **glClear** to clear the color index buffers. *c* is not clamped. Rather, *c* is converted to a fixed-point value with unspecified precision to the right of the binary point. The integer part of this value is then masked with $2^m - 1$, where *m* is the number of bits in a color index stored in the frame buffer.

ERRORS

GL_INVALID_OPERATION is generated if **glClearIndex** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_INDEX_CLEAR_VALUE**

glGet with argument **GL_INDEX_BITS**

SEE ALSO

glClear

NAME

glClearStencil - specify the clear value for the stencil buffer

C SPECIFICATION

```
void glClearStencil( GLint s )
```

PARAMETERS

s Specifies the index used when the stencil buffer is cleared. The initial value is 0.

DESCRIPTION

glClearStencil specifies the index used by **glClear** to clear the stencil buffer. *s* is masked with 2^m-1 , where *m* is the number of bits in the stencil buffer.

ERRORS

GL_INVALID_OPERATION is generated if **glClearStencil** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_STENCIL_CLEAR_VALUE**

glGet with argument **GL_STENCIL_BITS**

SEE ALSO

glClear

NAME

glClipPlane - specify a plane against which all geometry is clipped

C SPECIFICATION

```
void glClipPlane( GLenum plane,  
                  const GLdouble *equation )
```

PARAMETERS

plane Specifies which clipping plane is being positioned. Symbolic names of the form **GL_CLIP_PLANE i** , where i is an integer between 0 and **GL_MAX_CLIP_PLANES** -1, are accepted.

equation Specifies the address of an array of four double-precision floating-point values. These values are interpreted as a plane equation.

DESCRIPTION

Geometry is always clipped against the boundaries of a six-plane frustum in x , y , and z . **glClipPlane** allows the specification of additional planes, not necessarily perpendicular to the x , y , or z axis, against which all geometry is clipped. To determine the maximum number of additional clipping planes, call **glGetIntegerv** with argument **GL_MAX_CLIP_PLANES**. All implementations support at least six such clipping planes. Because the resulting clipping region is the intersection of the defined half-spaces, it is always convex.

glClipPlane specifies a half-space using a four-component plane equation. When **glClipPlane** is called, *equation* is transformed by the inverse of the modelview matrix and stored in the resulting eye coordinates. Subsequent changes to the modelview matrix have no effect on the stored plane-equation components. If the dot product of the eye coordinates of a vertex with the stored plane equation components is positive or zero, the vertex is *in* with respect to that clipping plane. Otherwise, it is *out*.

To enable and disable clipping planes, call **glEnable** and **glDisable** with the argument **GL_CLIP_PLANE i** , where i is the plane number.

All clipping planes are initially defined as (0, 0, 0, 0) in eye coordinates and are disabled.

NOTES

It is always the case that **GL_CLIP_PLANE_i** = **GL_CLIP_PLANE0** + _i.

ERRORS

GL_INVALID_ENUM is generated if *plane* is not an accepted value.

GL_INVALID_OPERATION is generated if **glClipPlane** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGetClipPlane

glIsEnabled with argument **GL_CLIP_PLANE_i**

SEE ALSO

glEnable

NAME

`glColor3b`, `glColor3d`, `glColor3f`, `glColor3i`, `glColor3s`,
`glColor3ub`, `glColor3ui`, `glColor3us`, `glColor4b`, `glColor4d`,
`glColor4f`, `glColor4i`, `glColor4s`, `glColor4ub`, `glColor4ui`,
`glColor4us`, `glColor3bv`, `glColor3dv`, `glColor3fv`, `glColor3iv`,
`glColor3sv`, `glColor3ubv`, `glColor3uiv`, `glColor3usv`,
`glColor4bv`, `glColor4dv`, `glColor4fv`, `glColor4iv`, `glColor4sv`,
`glColor4ubv`, `glColor4uiv`, `glColor4usv` - set the current
color

C SPECIFICATION

```
void glColor3b( GLbyte red,  
                GLbyte green,  
                GLbyte blue )  
void glColor3d( GLdouble red,  
                GLdouble green,  
                GLdouble blue )  
void glColor3f( GLfloat red,  
                GLfloat green,  
                GLfloat blue )  
void glColor3i( GLint red,  
                GLint green,  
                GLint blue )  
void glColor3s( GLshort red,  
                GLshort green,  
                GLshort blue )  
void glColor3ub( GLubyte red,  
                 GLubyte green,  
                 GLubyte blue )  
void glColor3ui( GLuint red,  
                 GLuint green,  
                 GLuint blue )  
void glColor3us( GLushort red,  
                 GLushort green,  
                 GLushort blue )  
void glColor4b( GLbyte red,  
                GLbyte green,  
                GLbyte blue,  
                GLbyte alpha )  
void glColor4d( GLdouble red,  
                GLdouble green,  
                GLdouble blue,  
                GLdouble alpha )  
void glColor4f( GLfloat red,
```

```

        GLfloat green,
        GLfloat blue,
        GLfloat alpha )
void glColor4i( GLint red,
        GLint green,
        GLint blue,
        GLint alpha )

void glColor4s( GLshort red,
        GLshort green,
        GLshort blue,
        GLshort alpha )
void glColor4ub( GLubyte red,
        GLubyte green,
        GLubyte blue,
        GLubyte alpha )
void glColor4ui( GLuint red,
        GLuint green,
        GLuint blue,
        GLuint alpha )
void glColor4us( GLushort red,
        GLushort green,
        GLushort blue,
        GLushort alpha )

```

PARAMETERS

red, green, blue

Specify new red, green, and blue values for the current color.

alpha

Specifies a new alpha value for the current color. Included only in the four-argument **glColor4** commands.

C SPECIFICATION

```

void glColor3bv( const GLbyte *v )
void glColor3dv( const GLdouble *v )
void glColor3fv( const GLfloat *v )
void glColor3iv( const GLint *v )
void glColor3sv( const GLshort *v )
void glColor3ubv( const GLubyte *v )
void glColor3uiv( const GLuint *v )
void glColor3usv( const GLushort *v )
void glColor4bv( const GLbyte *v )
void glColor4dv( const GLdouble *v )

```

```

void glColor4fv( const GLfloat *v )
void glColor4iv( const GLint *v )
void glColor4sv( const GLshort *v )
void glColor4ubv( const GLubyte *v )
void glColor4uiv( const GLuint *v )
void glColor4usv( const GLushort *v )

```

PARAMETERS

v Specifies a pointer to an array that contains red, green, blue, and (sometimes) alpha values.

DESCRIPTION

The GL stores both a current single-valued color index and a current four-valued RGBA color. **glColor** sets a new four-valued RGBA color. **glColor** has two major variants: **glColor3** and **glColor4**. **glColor3** variants specify new red, green, and blue values explicitly and set the current alpha value to 1.0 (full intensity) implicitly. **glColor4** variants specify all four color components explicitly.

glColor3b, **glColor4b**, **glColor3s**, **glColor4s**, **glColor3i**, and **glColor4i** take three or four signed byte, short, or long integers as arguments. When **v** is appended to the name, the color commands can take a pointer to an array of such values.

Current color values are stored in floating-point format, with unspecified mantissa and exponent sizes. Unsigned integer color components, when specified, are linearly mapped to floating-point values such that the largest representable value maps to 1.0 (full intensity), and 0 maps to 0.0 (zero intensity). Signed integer color components, when specified, are linearly mapped to floating-point values such that the most positive representable value maps to 1.0, and the most negative representable value maps to -1.0. (Note that this mapping does not convert 0 precisely to 0.0.) Floating-point values are mapped directly.

Neither floating-point nor signed integer values are clamped to the range [0,1] before the current color is updated. However, color components are clamped to this range before they are interpolated or written into a color buffer.

NOTES

The initial value for the current color is (1, 1, 1, 1).

The current color can be updated at any time. In particular, **glColor** can be called between a call to **glBegin** and the corresponding call to **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_CURRENT_COLOR**

glGet with argument **GL_RGBA_MODE**

SEE ALSO

glIndex

NAME

glColorMask - enable and disable writing of frame buffer color components

C SPECIFICATION

```
void glColorMask( GLboolean red,  
                  GLboolean green,  
                  GLboolean blue,  
                  GLboolean alpha )
```

PARAMETERS

red, green, blue, alpha

Specify whether red, green, blue, and alpha can or cannot be written into the frame buffer. The initial values are all **GL_TRUE**, indicating that the color components can be written.

DESCRIPTION

glColorMask specifies whether the individual color components in the frame buffer can or cannot be written. If *red* is **GL_FALSE**, for example, no change is made to the red component of any pixel in any of the color buffers, regardless of the drawing operation attempted.

Changes to individual bits of components cannot be controlled. Rather, changes are either enabled or disabled for entire color components.

ERRORS

GL_INVALID_OPERATION is generated if **glColorMask** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_COLOR_WRITEMASK**
glGet with argument **GL_RGBA_MODE**

SEE ALSO

glColor, glColorPointer, glDepthMask, glIndex, glIndexPointer, glIndexMask, glStencilMask

NAME

glColorMaterial - cause a material color to track the current color

C SPECIFICATION

```
void glColorMaterial( GLenum face,  
                     GLenum mode )
```

PARAMETERS

face Specifies whether front, back, or both front and back material parameters should track the current color. Accepted values are **GL_FRONT**, **GL_BACK**, and **GL_FRONT_AND_BACK**. The initial value is **GL_FRONT_AND_BACK**.

mode Specifies which of several material parameters track the current color. Accepted values are **GL_EMISSION**, **GL_AMBIENT**, **GL_DIFFUSE**, **GL_SPECULAR**, and **GL_AMBIENT_AND_DIFFUSE**. The initial value is **GL_AMBIENT_AND_DIFFUSE**.

DESCRIPTION

glColorMaterial specifies which material parameters track the current color. When **GL_COLOR_MATERIAL** is enabled, the material parameter or parameters specified by *mode*, of the material or materials specified by *face*, track the current color at all times.

To enable and disable **GL_COLOR_MATERIAL**, call **glEnable** and **glDisable** with argument **GL_COLOR_MATERIAL**. **GL_COLOR_MATERIAL** is initially disabled.

NOTES

glColorMaterial makes it possible to change a subset of material parameters for each vertex using only the **glColor** command, without calling **glMaterial**. If only such a subset of parameters is to be specified for each vertex, calling **glColorMaterial** is preferable to calling **glMaterial**.

Call **glColorMaterial** before enabling **GL_COLOR_MATERIAL**.

Calling **glDrawElements** may leave the current color indeterminate. If **glColorMaterial** is enabled while the

current color is indeterminate, the lighting material state specified by *face* and *mode* is also indeterminate.

If the GL version is 1.1 or greater, and **GL_COLOR_MATERIAL** is enabled, evaluated color values affect the results of the lighting equation as if the current color were being modified, but no change is made to the tracking lighting parameter of the current color.

ERRORS

GL_INVALID_ENUM is generated if *face* or *mode* is not an accepted value.

GL_INVALID_OPERATION is generated if **glColorMaterial** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glIsEnabled with argument **GL_COLOR_MATERIAL**

glGet with argument **GL_COLOR_MATERIAL_PARAMETER**

glGet with argument **GL_COLOR_MATERIAL_FACE**

SEE ALSO

glColor, **glColorPointer**, **glDrawElements**, **glEnable**, **glLight**, **glLightModel**, **glMaterial**

NAME

glColorPointer - define an array of colors

C SPECIFICATION

```
void glColorPointer( GLint size,  
                    GLenum type,  
                    GLsizei stride,  
                    const GLvoid *pointer )
```

PARAMETERS

<i>size</i>	Specifies the number of components per color. Must be 3 or 4.
<i>type</i>	Specifies the data type of each color component in the array. Symbolic constants GL_BYTE , GL_UNSIGNED_BYTE , GL_SHORT , GL_UNSIGNED_SHORT , GL_INT , GL_UNSIGNED_INT , GL_FLOAT , and GL_DOUBLE are accepted.
<i>stride</i>	Specifies the byte offset between consecutive colors. If <i>stride</i> is 0, (the initial value), the colors are understood to be tightly packed in the array.
<i>pointer</i>	Specifies a pointer to the first component of the first color element in the array.

DESCRIPTION

glColorPointer specifies the location and data format of an array of color components to use when rendering. *size* specifies the number of components per color, and must be 3 or 4. *type* specifies the data type of each color component, and *stride* specifies the byte stride from one color to the next allowing vertexes and attributes to be packed into a single array or stored in separate arrays. (Single-array storage may be more efficient on some implementations; see **glInterleavedArrays**.)

When a color array is specified, *size*, *type*, *stride*, and *pointer* are saved as client-side state.

To enable and disable the color array, call **glEnableClientState** and

glDisableClientState with the argument **GL_COLOR_ARRAY**. If enabled, the color array is used when **glDrawArrays**, **glDrawElements**, or **glArrayElement** is called.

NOTES

glColorPointer is available only if the GL version is 1.1 or greater.

The color array is initially disabled and isn't accessed when **glArrayElement**, **glDrawArrays**, or **glDrawElements** is called.

Execution of **glColorPointer** is not allowed between the execution of **glBegin** and the corresponding execution of **glEnd**, but an error may or may not be generated. If no error is generated, the operation is undefined.

glColorPointer is typically implemented on the client side.

Color array parameters are client-side state and are therefore not saved or restored by **glPushAttrib** and **glPopAttrib**. Use **glPushClientAttrib** and **glPopClientAttrib** instead.

ERRORS

GL_INVALID_VALUE is generated if *size* is not 3 or 4.

GL_INVALID_ENUM is generated if *type* is not an accepted value.

GL_INVALID_VALUE is generated if *stride* is negative.

ASSOCIATED GETS

glIsEnabled with argument **GL_COLOR_ARRAY**

glGet with argument **GL_COLOR_ARRAY_SIZE**

glGet with argument **GL_COLOR_ARRAY_TYPE**

glGet with argument **GL_COLOR_ARRAY_STRIDE**

glGetPointerv with argument **GL_COLOR_ARRAY_POINTER**

SEE ALSO

glArrayElement, **glDrawArrays**, **glDrawElements**,
glEdgeFlagPointer,
glEnable, **glGetPointerv**, **glIndexPointer**,
glInterleavedArrays, **glNormalPointer**, **glPopClientAttrib**,
glPushClientAttrib, **glTexCoordPointer**, **glVertexPointer**

NAME

glCopyPixels - copy pixels in the frame buffer

C SPECIFICATION

```
void glCopyPixels( GLint x,  
                  GLint y,  
                  GLsizei width,  
                  GLsizei height,  
                  GLenum type )
```

PARAMETERS

x, *y* Specify the window coordinates of the lower left corner of the rectangular region of pixels to be copied.

width, *height*

Specify the dimensions of the rectangular region of pixels to be copied. Both must be nonnegative.

type Specifies whether color values, depth values, or stencil values are to be copied. Symbolic constants **GL_COLOR**, **GL_DEPTH**, and **GL_STENCIL** are accepted.

DESCRIPTION

glCopyPixels copies a screen-aligned rectangle of pixels from the specified frame buffer location to a region relative to the current raster position. Its operation is well defined only if the entire pixel source region is within the exposed portion of the window. Results of copies from outside the window, or from regions of the window that are not exposed, are hardware dependent and undefined.

x and *y* specify the window coordinates of the lower left corner of the rectangular region to be copied. *width* and *height* specify the dimensions of the rectangular region to be copied. Both *width* and *height* must not be negative.

Several parameters control the processing of the pixel data while it is being copied. These parameters are set with three commands: **glPixelTransfer**, **glPixelMap**, and **glPixelZoom**. This reference page describes the effects on **glCopyPixels** of most, but not all, of the parameters specified by these three commands.

glCopyPixels copies values from each pixel with the lower left-hand corner at $(x + i, y + j)$ for $0 < i < \text{width}$ and $0 < j < \text{height}$. This pixel is said to be the i th pixel in the j th row. Pixels are copied in row order from the lowest to the highest row, left to right in each row.

type specifies whether color, depth, or stencil data is to be copied. The details of the transfer for each data type are as follows:

GL_COLOR Indices or RGBA colors are read from the buffer currently specified as the read source buffer (see **glReadBuffer**). If the GL is in color index mode, each index that is read from this buffer is converted to a fixed-point format with an unspecified number of bits to the right of the binary point. Each index is then shifted left by **GL_INDEX_SHIFT** bits, and added to **GL_INDEX_OFFSET**. If **GL_INDEX_SHIFT** is negative, the shift is to the right. In either case, zero bits fill otherwise unspecified bit locations in the result. If **GL_MAP_COLOR** is true, the index is replaced with the value that it references in lookup table **GL_PIXEL_MAP_I_TO_I**. Whether the lookup replacement of the index is done or not, the integer part of the index is then ANDed with $2^b - 1$, where b is the number of bits in a color index buffer.

If the GL is in RGBA mode, the red, green, blue, and alpha components of each pixel that is read are converted to an internal floating-point format with unspecified precision. The conversion maps the largest representable component value to 1.0, and component value 0 to 0.0. The resulting floating-point color values are then multiplied by **GL_c_SCALE** and added to **GL_c_BIAS**, where c is RED, GREEN, BLUE, and ALPHA for the respective color components. The results are clamped to the range $[0, 1]$. If **GL_MAP_COLOR** is true, each color component is scaled by the size of lookup table **GL_PIXEL_MAP_c_TO_c**, then replaced by the value that it references in that table. c is

R, G, B, or A.

The GL then converts the resulting indices or RGBA colors to fragments by attaching the current raster position z coordinate and texture coordinates to each pixel, then assigning window coordinates $(x + i, y + j)$, where (x, y) is the current raster position, and the pixel was the i th pixel in the j th row. These pixel fragments are then treated just like the fragments generated by rasterizing points, lines, or polygons. Texture mapping, fog, and all the fragment operations are applied before the fragments are written to the frame buffer.

GL_DEPTH

Depth values are read from the depth buffer and converted directly to an internal floating-point format with unspecified precision. The resulting floating-point depth value is then multiplied by **GL_DEPTH_SCALE** and added to **GL_DEPTH_BIAS**. The result is clamped to the range $[0,1]$.

The GL then converts the resulting depth components to fragments by attaching the current raster position color or color index and texture coordinates to each pixel, then assigning window coordinates $(x + i, y + j)$, where (x, y) is the current raster position, and the pixel was the i th pixel in the j th row. These pixel fragments are then treated just like the fragments generated by rasterizing points, lines, or polygons. Texture mapping, fog, and all the fragment operations are applied before the fragments are written to the frame buffer.

GL_STENCIL

Stencil indices are read from the stencil buffer and converted to an internal fixed-point format with an unspecified number of bits to the right of the binary point. Each fixed-point index is then shifted left by **GL_INDEX_SHIFT** bits, and added to **GL_INDEX_OFFSET**. If **GL_INDEX_SHIFT** is negative, the shift is to the right. In

either case, zero bits fill otherwise unspecified bit locations in the result. If **GL_MAP_STENCIL** is true, the index is replaced with the value that it references in lookup table **GL_PIXEL_MAP_S_TO_S**. Whether the lookup replacement of the index is done or not, the integer part of the index is then ANDed with 2^b-1 , where b is the number of bits in the stencil buffer. The resulting stencil indices are then written to the stencil buffer such that the index read from the i th location of the j th row is written to location $(x+i, y+j)$, where (x, y) is the current raster position. Only the pixel ownership test, the scissor test, and the stencil writemask affect these write operations.

The rasterization described thus far assumes pixel zoom factors of 1.0. If **glPixelZoom** is used to change the x and y pixel zoom factors, pixels are converted to fragments as follows. If (x, y) is the current raster position, and a given pixel is in the i th location in the j th row of the source pixel rectangle, then fragments are generated for pixels whose centers are in the rectangle with corners at

$$\begin{array}{cc} (x + \text{zoom}_x i, y + \text{zoom}_y j) \\ \text{r} \quad \quad \text{x} \quad \quad \text{r} \quad \quad \text{y} \\ \text{and} \\ (x + \text{zoom}_x (i+1), y + \text{zoom}_y (j+1)) \\ \text{r} \quad \quad \text{x} \quad \quad \text{r} \quad \quad \text{y} \end{array}$$

where zoom_x is the value of **GL_ZOOM_X** and zoom_y is the value of **GL_ZOOM_Y**.

EXAMPLES

To copy the color pixel in the lower left corner of the window to the current raster position, use `glCopyPixels(0, 0, 1, 1, GL_COLOR);`

NOTES

Modes specified by **glPixelStore** have no effect on the operation of **glCopyPixels**.

ERRORS

GL_INVALID_ENUM is generated if *type* is not an accepted

value.

GL_INVALID_VALUE is generated if either *width* or *height* is negative.

GL_INVALID_OPERATION is generated if *type* is **GL_DEPTH** and there is no depth buffer.

GL_INVALID_OPERATION is generated if *type* is **GL_STENCIL** and there is no stencil buffer.

GL_INVALID_OPERATION is generated if **glCopyPixels** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_CURRENT_RASTER_POSITION**

glGet with argument **GL_CURRENT_RASTER_POSITION_VALID**

SEE ALSO

glDepthFunc, **glDrawBuffer**, **glDrawPixels**, **glPixelMap**,
glPixelTransfer, **glPixelZoom**, **glRasterPos**, **glReadBuffer**,
glReadPixels, **glStencilFunc**

NAME

glCopyTexImage1D - copy pixels into a 1D texture image

C SPECIFICATION

```
void glCopyTexImage1D( GLenum target,  
                        GLint level,  
                        GLenum internalFormat,  
                        GLint x,  
                        GLint y,  
                        GLsizei width,  
                        GLint border )
```

PARAMETERS

<i>target</i>	Specifies the target texture. Must be GL_TEXTURE_1D .
<i>level</i>	Specifies the level-of-detail number. Level 0 is the base image level. Level <i>n</i> is the <i>n</i> th mipmap reduction image.
<i>internalFormat</i>	Specifies the internal format of the texture. Must be one of the following symbolic constants: GL_ALPHA , GL_ALPHA4 , GL_ALPHA8 , GL_ALPHA12 , GL_ALPHA16 , GL_LUMINANCE , GL_LUMINANCE4 , GL_LUMINANCE8 , GL_LUMINANCE12 , GL_LUMINANCE16 , GL_LUMINANCE_ALPHA , GL_LUMINANCE4_ALPHA4 , GL_LUMINANCE6_ALPHA2 , GL_LUMINANCE8_ALPHA8 , GL_LUMINANCE12_ALPHA4 , GL_LUMINANCE12_ALPHA12 , GL_LUMINANCE16_ALPHA16 , GL_INTENSITY , GL_INTENSITY4 , GL_INTENSITY8 , GL_INTENSITY12 , GL_INTENSITY16 , GL_RGB , GL_R3_G3_B2 , GL_RGB4 , GL_RGB5 , GL_RGB8 , GL_RGB10 , GL_RGB12 , GL_RGB16 , GL_RGBA , GL_RGBA2 , GL_RGBA4 , GL_RGB5_A1 , GL_RGBA8 , GL_RGB10_A2 , GL_RGBA12 , or GL_RGBA16 .
<i>x, y</i>	Specify the window coordinates of the left corner of the row of pixels to be copied.
<i>width</i>	Specifies the width of the texture image. Must be 0 or $2*n + 2*border$ for some

integer *n*. The height of the texture image is 1.

border Specifies the width of the border. Must be either 0 or 1.

DESCRIPTION

glCopyTexImage1D defines a one-dimensional texture image with pixels from the current **GL_READ_BUFFER**.

The screen-aligned pixel row with left corner at (*x*,*y*) and with a length of *width* + 2 * *border* defines the texture array at the mipmap level specified by *level*.

internalFormat specifies the internal format of the texture array.

The pixels in the row are processed exactly as if **glCopyPixels** had been called, but the process stops just before final conversion. At this point all pixel component values are clamped to the range [0, 1] and then converted to the texture's internal format for storage in the texel array.

Pixel ordering is such that lower *x* screen coordinates correspond to lower texture coordinates.

If any of the pixels within the specified row of the current **GL_READ_BUFFER** are outside the window associated with the current rendering context, then the values obtained for those pixels are undefined.

NOTES

glCopyTexImage1D is available only if the GL version is 1.1 or greater.

Texturing has no effect in color index mode.

1, 2, 3, and 4 are not accepted values for *internalFormat*.

An image with 0 width indicates a NULL texture.

ERRORS

GL_INVALID_ENUM is generated if *target* is not one of the allowable values.

GL_INVALID_VALUE is generated if *level* is less than 0.

GL_INVALID_VALUE may be generated if *level* is greater than $\log \max$, where \max is the returned value of **GL_MAX_TEXTURE_SIZE**.

GL_INVALID_VALUE is generated if *internalFormat* is not an allowable value.

GL_INVALID_VALUE is generated if *width* is less than 0 or greater than $2 + \text{GL_MAX_TEXTURE_SIZE}$, or if it cannot be represented as $2^n + 2 * (\text{border})$ for some integer value of *n*.

GL_INVALID_VALUE is generated if *border* is not 0 or 1.

GL_INVALID_OPERATION is generated if **glCopyTexImage1D** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGetTexImage

glIsEnabled with argument **GL_TEXTURE_1D**

SEE ALSO

glCopyPixels, **glCopyTexImage2D**, **glCopyTexSubImage1D**,
glCopyTexSubImage2D, **glPixelStore**, **glPixelTransfer**,
glTexEnv, **glTexGen**, **glTexImage1D**, **glTexImage2D**,
glTexSubImage1D, **glTexSubImage2D**,
glTexParameter

NAME

glCopyTexImage2D - copy pixels into a 2D texture image

C SPECIFICATION

```
void glCopyTexImage2D( GLenum target,  
                        GLint level,  
                        GLenum internalFormat,  
                        GLint x,  
                        GLint y,  
                        GLsizei width,  
                        GLsizei height,  
                        GLint border )
```

PARAMETERS

<i>target</i>	Specifies the target texture. Must be GL_TEXTURE_2D .
<i>level</i>	Specifies the level-of-detail number. Level 0 is the base image level. Level <i>n</i> is the <i>n</i> th mipmap reduction image.
<i>internalFormat</i>	Specifies the internal format of the texture. Must be one of the following symbolic constants: GL_ALPHA , GL_ALPHA4 , GL_ALPHA8 , GL_ALPHA12 , GL_ALPHA16 , GL_LUMINANCE , GL_LUMINANCE4 , GL_LUMINANCE8 , GL_LUMINANCE12 , GL_LUMINANCE16 , GL_LUMINANCE_ALPHA , GL_LUMINANCE4_ALPHA4 , GL_LUMINANCE6_ALPHA2 , GL_LUMINANCE8_ALPHA8 , GL_LUMINANCE12_ALPHA4 , GL_LUMINANCE12_ALPHA12 , GL_LUMINANCE16_ALPHA16 , GL_INTENSITY , GL_INTENSITY4 , GL_INTENSITY8 , GL_INTENSITY12 , GL_INTENSITY16 , GL_RGB , GL_R3_G3_B2 , GL_RGB4 , GL_RGB5 , GL_RGB8 , GL_RGB10 , GL_RGB12 , GL_RGB16 , GL_RGBA , GL_RGBA2 , GL_RGBA4 , GL_RGB5_A1 , GL_RGBA8 , GL_RGB10_A2 , GL_RGBA12 , or GL_RGBA16 .
<i>x, y</i>	Specify the window coordinates of the lower left corner of the rectangular region of pixels to be copied.

<i>width</i>	Specifies the width of the texture image. Must be 0 or $2*n + 2*border$ for some integer <i>n</i> .
<i>height</i>	Specifies the height of the texture image. Must be 0 or $2*m + 2*border$ for some integer <i>m</i> .
<i>border</i>	Specifies the width of the border. Must be either 0 or 1.

DESCRIPTION

glCopyTexImage2D defines a two-dimensional texture image with pixels from the current **GL_READ_BUFFER**.

The screen-aligned pixel rectangle with lower left corner at (*x*, *y*) and with a width of $width + 2 * border$ and a height of $height + 2 * border$ defines the texture array at the mipmap level specified by *level*. *internalFormat* specifies the internal format of the texture array.

The pixels in the rectangle are processed exactly as if **glCopyPixels** had been called, but the process stops just before final conversion. At this point all pixel component values are clamped to the range [0,1] and then converted to the texture's internal format for storage in the texel array.

Pixel ordering is such that lower *x* and *y* screen coordinates correspond to lower *s* and *t* texture coordinates.

If any of the pixels within the specified rectangle of the current **GL_READ_BUFFER** are outside the window associated with the current rendering context, then the values obtained for those pixels are undefined.

NOTES

glCopyTexImage2D is available only if the GL version is 1.1 or greater.

Texturing has no effect in color index mode.

1, 2, 3, and 4 are not accepted values for *internalFormat*.

An image with height or width of 0 indicates a NULL texture.

ERRORS

GL_INVALID_ENUM is generated if *target* is not **GL_TEXTURE_2D**.

GL_INVALID_VALUE is generated if *level* is less than 0.

GL_INVALID_VALUE may be generated if *level* is greater than $\log \text{max}$, where *max* is the returned value of **GL_MAX_TEXTURE_SIZE**.

GL_INVALID_VALUE is generated if *width* or *height* is less than 0, greater than $2 + \text{GL_MAX_TEXTURE_SIZE}$, or if *width* or *height* cannot be represented as $2^k + 2 * \text{border}$ for some integer *k*.

GL_INVALID_VALUE is generated if *border* is not 0 or 1.

GL_INVALID_VALUE is generated if *internalFormat* is not one of the allowable values.

GL_INVALID_OPERATION is generated if **glCopyTexImage2D** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGetTexImage

glIsEnabled with argument **GL_TEXTURE_2D**

SEE ALSO

glCopyPixels, **glCopyTexImage1D**, **glCopyTexSubImage1D**,
glCopyTexSubImage2D, **glPixelStore**, **glPixelTransfer**,
glTexEnv, **glTexGen**, **glTexImage1D**, **glTexImage2D**,
glTexSubImage1D, **glTexSubImage2D**,
glTexParameter

NAME

glCopyTexSubImage1D - copy a one-dimensional texture subimage

C SPECIFICATION

```
void glCopyTexSubImage1D( GLenum target,  
                           GLint level,  
                           GLint xoffset,  
                           GLint x,  
                           GLint y,  
                           GLsizei width )
```

PARAMETERS

<i>target</i>	Specifies the target texture. Must be GL_TEXTURE_1D .
<i>level</i>	Specifies the level-of-detail number. Level 0 is the base image level. Level <i>n</i> is the <i>n</i> th mipmap reduction image.
<i>xoffset</i>	Specifies the texel offset within the texture array.
<i>x</i> , <i>y</i>	Specify the window coordinates of the left corner of the row of pixels to be copied.
<i>width</i>	Specifies the width of the texture subimage.

DESCRIPTION

glCopyTexSubImage1D replaces a portion of a one-dimensional texture image with pixels from the current **GL_READ_BUFFER** (rather than from main memory, as is the case for **glTexSubImage1D**).

The screen-aligned pixel row with left corner at (*x*, *y*), and with length *width* replaces the portion of the texture array with *x* indices *xoffset* through *xoffset* + *width* - 1, inclusive. The destination in the texture array may not include any texels outside the texture array as it was originally specified.

The pixels in the row are processed exactly as if **glCopyPixels** had been called, but the process stops just

before final conversion. At this point all pixel component values are clamped to the range [0, 1] and then converted to the texture's internal format for storage in the texel array.

It is not an error to specify a subtexture with zero width, but such a specification has no effect. If any of the pixels within the specified row of the current **GL_READ_BUFFER** are outside the read window associated with the current rendering context, then the values obtained for those pixels are undefined.

No change is made to the *internalformat*, *width*, or *border* parameters of the specified texture array or to texel values outside the specified subregion.

NOTES

glCopyTexSubImage1D is available only if the GL version is 1.1 or greater.

Texturing has no effect in color index mode.

glPixelStore and **glPixelTransfer** modes affect texture images in exactly the way they affect **glDrawPixels**.

ERRORS

GL_INVALID_ENUM is generated if *target* is not **GL_TEXTURE_1D**.

GL_INVALID_OPERATION is generated if the texture array has not been defined by a previous **glTexImage1D** or **glCopyTexImage1D** operation.

GL_INVALID_VALUE is generated if *level* is less than 0.

GL_INVALID_VALUE may be generated if $level > \log_{max}$, where *max* is the returned value of **GL_MAX_TEXTURE_SIZE**.

GL_INVALID_VALUE is generated if $y < -b$ or if $width < -b$, where *b* is the border width of the texture array.

GL_INVALID_VALUE is generated if $xoffset < -b$, or $(xoffset + width) > (w-b)$, where *w* is the **GL_TEXTURE_WIDTH**, and *b* is the **GL_TEXTURE_BORDER** of the texture image being modified. Note that *w* includes twice the border width.

ASSOCIATED GETS

`glGetTexImage`

`glIsEnabled` with argument `GL_TEXTURE_1D`

SEE ALSO

`glCopyPixels`, `glCopyTexImage1D`, `glCopyTexImage2D`,
`glCopyTexSubImage2D`, `glPixelStore`, `glPixelTransfer`,
`glTexEnv`, `glTexGen`, `glTexImage1D`, `glTexImage2D`,
`glTexParameter`, `glTexSubImage1D`, `glTexSubImage2D`

NAME

glCopyTexSubImage2D - copy a two-dimensional texture subimage

C SPECIFICATION

```
void glCopyTexSubImage2D( GLenum target,
                           GLint level,
                           GLint xoffset,
                           GLint yoffset,
                           GLint x,
                           GLint y,
                           GLsizei width,
                           GLsizei height )
```

PARAMETERS

<i>target</i>	Specifies the target texture. Must be GL_TEXTURE_2D
<i>level</i>	Specifies the level-of-detail number. Level 0 is the base image level. Level <i>n</i> is the <i>n</i> th mipmap reduction image.
<i>xoffset</i>	Specifies a texel offset in the x direction within the texture array.
<i>yoffset</i>	Specifies a texel offset in the y direction within the texture array.
<i>x, y</i>	Specify the window coordinates of the lower left corner of the rectangular region of pixels to be copied.
<i>width</i>	Specifies the width of the texture subimage.
<i>height</i>	Specifies the height of the texture subimage.

DESCRIPTION

glCopyTexSubImage2D replaces a rectangular portion of a two-dimensional texture image with pixels from the current **GL_READ_BUFFER** (rather than from main memory, as is the case for **glTexSubImage2D**).

The screen-aligned pixel rectangle with lower left corner at

(*x*, *y*) and with width *width* and height *height* replaces the portion of the texture array with *x* indices *xoffset* through *xoffset* + *width* - 1, inclusive, and *y* indices *yoffset* through *yoffset* + *height* - 1, inclusive, at the mipmap level specified by *level*.

The pixels in the rectangle are processed exactly as if **glCopyPixels** had been called, but the process stops just before final conversion. At this point, all pixel component values are clamped to the range [0, 1] and then converted to the texture's internal format for storage in the texel array.

The destination rectangle in the texture array may not include any texels outside the texture array as it was originally specified. It is not an error to specify a subtexture with zero width or height, but such a specification has no effect.

If any of the pixels within the specified rectangle of the current **GL_READ_BUFFER** are outside the read window associated with the current rendering context, then the values obtained for those pixels are undefined.

No change is made to the *internalformat*, *width*, *height*, or *border* parameters of the specified texture array or to texel values outside the specified subregion.

NOTES

glCopyTexSubImage2D is available only if the GL version is 1.1 or greater.

Texturing has no effect in color index mode.

glPixelStore and **glPixelTransfer** modes affect texture images in exactly the way they affect **glDrawPixels**.

ERRORS

GL_INVALID_ENUM is generated if *target* is not **GL_TEXTURE_2D**.

GL_INVALID_OPERATION is generated if the texture array has not been defined by a previous **glTexImage2D** or **glCopyTexImage2D** operation.

GL_INVALID_VALUE is generated if *level* is less than 0.

GL_INVALID_VALUE may be generated if *level* is greater than *log max*, where *max* is the returned value of **GL_MAX_TEXTURE_SIZE**.

GL_INVALID_VALUE is generated if $x < -b$ or if $y < -b$, where *b* is the border width of the texture array.

GL_INVALID_VALUE is generated if $xoffset < -b$, $(xoffset + width) > (w - b)$, $yoffset < -b$, or $(yoffset + height) > (h - b)$, where *w* is the **GL_TEXTURE_WIDTH**, *h* is the **GL_TEXTURE_HEIGHT**, and *b* is the **GL_TEXTURE_BORDER** of the texture image being modified. Note that *w* and *h* include twice the border width.

GL_INVALID_OPERATION is generated if **glCopyTexSubImage2D** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGetTexImage

glIsEnabled with argument **GL_TEXTURE_2D**

SEE ALSO

glCopyPixels, **glCopyTexImage1D**, **glCopyTexImage2D**,
glCopyTexSubImage1D, **glPixelStore**, **glPixelTransfer**,
glTexEnv, **glTexGen**, **glTexImage1D**, **glTexImage2D**,
glTexParameter, **glTexSubImage1D**, **glTexSubImage2D**

NAME

glCullFace - specify whether front- or back-facing facets can be culled

C SPECIFICATION

```
void glCullFace( GLenum mode )
```

PARAMETERS

mode Specifies whether front- or back-facing facets are candidates for culling. Symbolic constants **GL_FRONT**, **GL_BACK**, and **GL_FRONT_AND_BACK** are accepted. The initial value is **GL_BACK**.

DESCRIPTION

glCullFace specifies whether front- or back-facing facets are culled (as specified by *mode*) when facet culling is enabled. Facet culling is initially disabled. To enable and disable facet culling, call the **glEnable** and **glDisable** commands with the argument **GL_CULL_FACE**. Facets include triangles, quadrilaterals, polygons, and rectangles.

glFrontFace specifies which of the clockwise and counterclockwise facets are front-facing and back-facing. See **glFrontFace**.

NOTES

If *mode* is **GL_FRONT_AND_BACK**, no facets are drawn, but other primitives such as points and lines are drawn.

ERRORS

GL_INVALID_ENUM is generated if *mode* is not an accepted value.

GL_INVALID_OPERATION is generated if **glCullFace** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glIsEnabled with argument **GL_CULL_FACE**
glGet with argument **GL_CULL_FACE_MODE**

SEE ALSO

glEnable, **glFrontFace**

NAME

glDeleteLists - delete a contiguous group of display lists

C SPECIFICATION

```
void glDeleteLists( GLuint list,  
                    GLsizei range )
```

PARAMETERS

list Specifies the integer name of the first display list to delete.

range Specifies the number of display lists to delete.

DESCRIPTION

glDeleteLists causes a contiguous group of display lists to be deleted. *list* is the name of the first display list to be deleted, and *range* is the number of display lists to delete. All display lists *d* with $list < d < list + range - 1$ are deleted.

All storage locations allocated to the specified display lists are freed, and the names are available for reuse at a later time. Names within the range that do not have an associated display list are ignored. If *range* is 0, nothing happens.

ERRORS

GL_INVALID_VALUE is generated if *range* is negative.

GL_INVALID_OPERATION is generated if **glDeleteLists** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

SEE ALSO

glCallList, **glCallLists**, **glGenLists**, **glIsList**, **glNewList**

NAME

glDeleteTextures - delete named textures

C SPECIFICATION

```
void glDeleteTextures( GLsizei n,  
                      const GLuint *textures )
```

PARAMETERS

n Specifies the number of textures to be deleted.

textures Specifies an array of textures to be deleted.

DESCRIPTION

glDeleteTextures deletes *n* textures named by the elements of the array *textures*. After a texture is deleted, it has no contents or dimensionality, and its name is free for reuse (for example by **glGenTextures**). If a texture that is currently bound is deleted, the binding reverts to 0 (the default texture).

glDeleteTextures silently ignores 0's and names that do not correspond to existing textures.

NOTES

glDeleteTextures is available only if the GL version is 1.1 or greater.

ERRORS

GL_INVALID_VALUE is generated if *n* is negative.

GL_INVALID_OPERATION is generated if **glDeleteTextures** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glIsTexture

SEE ALSO

glAreTexturesResident, **glBindTexture**, **glCopyTexImage1D**, **glCopyTexImage2D**, **glGenTextures**, **glGet**, **glGetTexParameter**, **glPrioritizeTextures**, **glTexImage1D**, **glTexImage2D**, **glTexParameter**

NAME

glDepthFunc - specify the value used for depth buffer comparisons

C SPECIFICATION

```
void glDepthFunc( GLenum func )
```

PARAMETERS

func Specifies the depth comparison function. Symbolic constants **GL_NEVER**, **GL_LESS**, **GL_EQUAL**, **GL_LEQUAL**, **GL_GREATER**, **GL_NOTEQUAL**, **GL_GEQUAL**, and **GL_ALWAYS** are accepted. The initial value is **GL_LESS**.

DESCRIPTION

glDepthFunc specifies the function used to compare each incoming pixel depth value with the depth value present in the depth buffer. The comparison is performed only if depth testing is enabled. (See **glEnable** and **glDisable** of **GL_DEPTH_TEST**.)

func specifies the conditions under which the pixel will be drawn. The comparison functions are as follows:

GL_NEVER	Never passes.
GL_LESS	Passes if the incoming depth value is less than the stored depth value.
GL_EQUAL	Passes if the incoming depth value is equal to the stored depth value.
GL_LEQUAL	Passes if the incoming depth value is less than or equal to the stored depth value.
GL_GREATER	Passes if the incoming depth value is greater than the stored depth value.
GL_NOTEQUAL	Passes if the incoming depth value is not equal to the stored depth value.
GL_GEQUAL	Passes if the incoming depth value is greater than or equal to the stored depth value.

GL_ALWAYS Always passes.

The initial value of *func* is **GL_LESS**. Initially, depth testing is disabled. Even if the depth buffer exists and the depth mask is non-zero, the depth buffer is not updated if the depth test is disabled.

ERRORS

GL_INVALID_ENUM is generated if *func* is not an accepted value.

GL_INVALID_OPERATION is generated if **glDepthFunc** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_DEPTH_FUNC**
glIsEnabled with argument **GL_DEPTH_TEST**

SEE ALSO

glDepthRange, glEnable, glPolygonOffset

NAME

glDepthMask - enable or disable writing into the depth buffer

C SPECIFICATION

```
void glDepthMask( GLboolean flag )
```

PARAMETERS

flag Specifies whether the depth buffer is enabled for writing. If *flag* is **GL_FALSE**, depth buffer writing is disabled. Otherwise, it is enabled. Initially, depth buffer writing is enabled.

DESCRIPTION

glDepthMask specifies whether the depth buffer is enabled for writing. If *flag* is **GL_FALSE**, depth buffer writing is disabled. Otherwise, it is enabled. Initially, depth buffer writing is enabled.

ERRORS

GL_INVALID_OPERATION is generated if **glDepthMask** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_DEPTH_WRITEMASK**

SEE ALSO

glColorMask, **glDepthFunc**, **glDepthRange**, **glIndexMask**, **glStencilMask**

NAME

glDepthRange - specify mapping of depth values from normalized device coordinates to window coordinates

C SPECIFICATION

```
void glDepthRange( GLclampd zNear,  
                  GLclampd zFar )
```

PARAMETERS

zNear Specifies the mapping of the near clipping plane to window coordinates. The initial value is 0.

zFar Specifies the mapping of the far clipping plane to window coordinates. The initial value is 1.

DESCRIPTION

After clipping and division by *w*, depth coordinates range from -1 to 1, corresponding to the near and far clipping planes. **glDepthRange** specifies a linear mapping of the normalized depth coordinates in this range to window depth coordinates. Regardless of the actual depth buffer implementation, window coordinate depth values are treated as though they range from 0 through 1 (like color components). Thus, the values accepted by **glDepthRange** are both clamped to this range before they are accepted.

The setting of (0,1) maps the near plane to 0 and the far plane to 1. With this mapping, the depth buffer range is fully utilized.

NOTES

It is not necessary that *zNear* be less than *zFar*. Reverse mappings such as *zNear*=1, and *zFar*=0 are acceptable.

ERRORS

GL_INVALID_OPERATION is generated if **glDepthRange** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_DEPTH_RANGE**

SEE ALSO

`glDepthFunc, glPolygonOffset, glViewport`

NAME

glDrawArrays - render primitives from array data

C SPECIFICATION

```
void glDrawArrays( GLenum mode,  
                  GLint first,  
                  GLsizei count )
```

PARAMETERS

mode Specifies what kind of primitives to render. Symbolic constants **GL_POINTS**, **GL_LINE_STRIP**, **GL_LINE_LOOP**, **GL_LINES**, **GL_TRIANGLE_STRIP**, **GL_TRIANGLE_FAN**, **GL_TRIANGLES**, **GL_QUAD_STRIP**, **GL_QUADS**, and **GL_POLYGON** are accepted.

first Specifies the starting index in the enabled arrays.

count Specifies the number of indices to be rendered.

DESCRIPTION

glDrawArrays specifies multiple geometric primitives with very few subroutine calls. Instead of calling a GL procedure to pass each individual vertex, normal, texture coordinate, edge flag, or color, you can prespecify separate arrays of vertexes, normals, and colors and use them to construct a sequence of primitives with a single call to **glDrawArrays**.

When **glDrawArrays** is called, it uses *count* sequential elements from each enabled array to construct a sequence of geometric primitives, beginning with element *first*. *mode* specifies what kind of primitives are constructed, and how the array elements construct those primitives. If **GL_VERTEX_ARRAY** is not enabled, no geometric primitives are generated.

Vertex attributes that are modified by **glDrawArrays** have an unspecified value after **glDrawArrays** returns. For example, if **GL_COLOR_ARRAY** is enabled, the value of the current color is undefined after **glDrawArrays** executes. Attributes that aren't modified remain well defined.

NOTES

glDrawArrays is available only if the GL version is 1.1 or

greater.

glDrawArrays is included in display lists. If **glDrawArrays** is entered into a display list, the necessary array data (determined by the array pointers and enables) is also entered into the display list. Because the array pointers and enables are client-side state, their values affect display lists when the lists are created, not when the lists are executed.

ERRORS

GL_INVALID_ENUM is generated if *mode* is not an accepted value.

GL_INVALID_VALUE is generated if *count* is negative.

GL_INVALID_OPERATION is generated if **glDrawArrays** is executed between the execution of **glBegin** and the corresponding **glEnd**.

SEE ALSO

glArrayElement, **glColorPointer**, **glDrawElements**,
glEdgeFlagPointer,
glGetPointerv, **glIndexPointer**, **glInterleavedArrays**,
glNormalPointer,
glTexCoordPointer, **glVertexPointer**

NAME

glDrawBuffer - specify which color buffers are to be drawn into

C SPECIFICATION

```
void glDrawBuffer( GLenum mode )
```

PARAMETERS

mode Specifies up to four color buffers to be drawn into. Symbolic constants **GL_NONE**, **GL_FRONT_LEFT**, **GL_FRONT_RIGHT**, **GL_BACK_LEFT**, **GL_BACK_RIGHT**, **GL_FRONT**, **GL_BACK**, **GL_LEFT**, **GL_RIGHT**, **GL_FRONT_AND_BACK**, and **GL_AUX*i***, where *i* is between 0 and ``**GL_AUX_BUFFERS**'' -1, are accepted (**GL_AUX_BUFFERS** is not the upper limit; use **glGet** to query the number of available aux buffers.) The initial value is **GL_FRONT** for single-buffered contexts, and **GL_BACK** for double-buffered contexts.

DESCRIPTION

When colors are written to the frame buffer, they are written into the color buffers specified by **glDrawBuffer**. The specifications are as follows:

GL_NONE	No color buffers are written.
GL_FRONT_LEFT	Only the front left color buffer is written.
GL_FRONT_RIGHT	Only the front right color buffer is written.
GL_BACK_LEFT	Only the back left color buffer is written.
GL_BACK_RIGHT	Only the back right color buffer is written.
GL_FRONT	Only the front left and front right color buffers are written. If there is no front right color buffer, only the front left color buffer is written.

GL_BACK	Only the back left and back right color buffers are written. If there is no back right color buffer, only the back left color buffer is written.
GL_LEFT	Only the front left and back left color buffers are written. If there is no back left color buffer, only the front left color buffer is written.
GL_RIGHT	Only the front right and back right color buffers are written. If there is no back right color buffer, only the front right color buffer is written.
GL_FRONT_AND_BACK	All the front and back color buffers (front left, front right, back left, back right) are written. If there are no back color buffers, only the front left and front right color buffers are written. If there are no right color buffers, only the front left and back left color buffers are written. If there are no right or back color buffers, only the front left color buffer is written.
GL_AUX<i>i</i>	Only auxiliary color buffer <i>i</i> is written.

If more than one color buffer is selected for drawing, then blending or logical operations are computed and applied independently for each color buffer and can produce different results in each buffer.

Monoscopic contexts include only *left* buffers, and stereoscopic contexts include both *left* and *right* buffers. Likewise, single-buffered contexts include only *front* buffers, and double-buffered contexts include both *front* and *back* buffers. The context is selected at GL initialization.

NOTES

It is always the case that `GL_AUXi = GL_AUX0 + i`.

ERRORS

`GL_INVALID_ENUM` is generated if *mode* is not an accepted value.

`GL_INVALID_OPERATION` is generated if none of the buffers indicated by *mode* exists.

`GL_INVALID_OPERATION` is generated if `glDrawBuffer` is executed between the execution of `glBegin` and the corresponding execution of `glEnd`.

ASSOCIATED GETS

`glGet` with argument `GL_DRAW_BUFFER`

`glGet` with argument `GL_AUX_BUFFERS`

SEE ALSO

`glBlendFunc`, `glColorMask`, `glIndexMask`, `glLogicOp`,
`glReadBuffer`

NAME

glDrawElements - render primitives from array data

C SPECIFICATION

```
void glDrawElements( GLenum mode,  
                    GLsizei count,  
                    GLenum type,  
                    const GLvoid *indices )
```

PARAMETERS

mode Specifies what kind of primitives to render. Symbolic constants **GL_POINTS**, **GL_LINE_STRIP**, **GL_LINE_LOOP**, **GL_LINES**, **GL_TRIANGLE_STRIP**, **GL_TRIANGLE_FAN**, **GL_TRIANGLES**, **GL_QUAD_STRIP**, **GL_QUADS**, and **GL_POLYGON** are accepted.

count Specifies the number of elements to be rendered.

type Specifies the type of the values in *indices*. Must be one of **GL_UNSIGNED_BYTE**, **GL_UNSIGNED_SHORT**, or **GL_UNSIGNED_INT**.

indices Specifies a pointer to the location where the indices are stored.

DESCRIPTION

glDrawElements specifies multiple geometric primitives with very few subroutine calls. Instead of calling a GL function to pass each individual vertex, normal, texture coordinate, edge flag, or color, you can prespecify separate arrays of vertexes, normals, and so on and use them to construct a sequence of primitives with a single call to **glDrawElements**.

When **glDrawElements** is called, it uses *count* sequential elements from an enabled array, starting at *indices* to construct a sequence of geometric primitives. *mode* specifies what kind of primitives are constructed, and how the array elements construct these primitives. If more than one array is enabled, each is used. If **GL_VERTEX_ARRAY** is not enabled, no geometric primitives are constructed.

Vertex attributes that are modified by **glDrawElements** have an unspecified value after **glDrawElements** returns. For

example, if **GL_COLOR_ARRAY** is enabled, the value of the current color is undefined after **glDrawElements** executes. Attributes that aren't modified remain well defined.

NOTES

glDrawElements is available only if the GL version is 1.1 or greater.

glDrawElements is included in display lists. If **glDrawElements** is entered into a display list, the necessary array data (determined by the array pointers and enables) is also entered into the display list. Because the array pointers and enables are client-side state, their values affect display lists when the lists are created, not when the lists are executed.

ERRORS

GL_INVALID_ENUM is generated if *mode* is not an accepted value.

GL_INVALID_VALUE is generated if *count* is negative.

GL_INVALID_OPERATION is generated if **glDrawElements** is executed between the execution of **glBegin** and the corresponding **glEnd**.

SEE ALSO

glArrayElement, **glColorPointer**, **glDrawArrays**,
glEdgeFlagPointer,
glGetPointerv, **glIndexPointer**, **glInterleavedArrays**,
glNormalPointer,
glTexCoordPointer, **glVertexPointer**

NAME

glDrawPixels - write a block of pixels to the frame buffer

C SPECIFICATION

```
void glDrawPixels( GLsizei width,
                  GLsizei height,
                  GLenum format,
                  GLenum type,
                  const GLvoid *pixels )
```

PARAMETERS

width, height Specify the dimensions of the pixel rectangle to be written into the frame buffer.

format Specifies the format of the pixel data. Symbolic constants **GL_COLOR_INDEX**, **GL_STENCIL_INDEX**, **GL_DEPTH_COMPONENT**, **GL_RGBA**, **GL_RED**, **GL_GREEN**, **GL_BLUE**, **GL_ALPHA**, **GL_RGB**, **GL_LUMINANCE**, and **GL_LUMINANCE_ALPHA** are accepted.

type Specifies the data type for *pixels*. Symbolic constants **GL_UNSIGNED_BYTE**, **GL_BYTE**, **GL_BITMAP**, **GL_UNSIGNED_SHORT**, **GL_SHORT**, **GL_UNSIGNED_INT**, **GL_INT**, and **GL_FLOAT** are accepted.

pixels Specifies a pointer to the pixel data.

DESCRIPTION

glDrawPixels reads pixel data from memory and writes it into the frame buffer relative to the current raster position. Use **glRasterPos** to set the current raster position; use **glGet** with argument **GL_CURRENT_RASTER_POSITION** to query the raster position.

Several parameters define the encoding of pixel data in memory and control the processing of the pixel data before it is placed in the frame buffer. These parameters are set with four commands: **glPixelStore**, **glPixelTransfer**, **glPixelMap**, and **glPixelZoom**. This reference page describes the effects on **glDrawPixels** of many, but not all, of the parameters specified by these four commands.

Data is read from *pixels* as a sequence of signed or unsigned bytes, signed or unsigned shorts, signed or unsigned integers, or single-precision floating-point values, depending on *type*. Each of these bytes, shorts, integers, or floating-point values is interpreted as one color or depth component, or one index, depending on *format*. Indices are always treated individually. Color components are treated as groups of one, two, three, or four values, again based on *format*. Both individual indices and groups of components are referred to as pixels. If *type* is **GL_BITMAP**, the data must be unsigned bytes, and *format* must be either **GL_COLOR_INDEX** or **GL_STENCIL_INDEX**. Each unsigned byte is treated as eight 1-bit pixels, with bit ordering determined by **GL_UNPACK_LSB_FIRST** (see **glPixelStore**).

widthxheight pixels are read from memory, starting at location *pixels*. By default, these pixels are taken from adjacent memory locations, except that after all *width* pixels are read, the read pointer is advanced to the next four-byte boundary. The four-byte row alignment is specified by **glPixelStore** with argument **GL_UNPACK_ALIGNMENT**, and it can be set to one, two, four, or eight bytes. Other pixel store parameters specify different read pointer advancements, both before the first pixel is read and after all *width* pixels are read. See the **glPixelStore** reference page for details on these options.

The *widthxheight* pixels that are read from memory are each operated on in the same way, based on the values of several parameters specified by **glPixelTransfer** and **glPixelMap**. The details of these operations, as well as the target buffer into which the pixels are drawn, are specific to the format of the pixels, as specified by *format*. *format* can assume one of eleven symbolic values:

GL_COLOR_INDEX

Each pixel is a single value, a color index. It is converted to fixed-point format, with an unspecified number of bits to the right of the binary point, regardless of the memory data type. Floating-point values convert to true fixed-point values. Signed and unsigned integer data is converted with all fraction bits set to 0. Bitmap data convert to either 0 or 1.

Each fixed-point index is then shifted left by **GL_INDEX_SHIFT** bits and added to **GL_INDEX_OFFSET**. If **GL_INDEX_SHIFT** is negative, the shift is to the right. In either case, zero bits fill otherwise unspecified bit locations in the result.

If the GL is in RGBA mode, the resulting index is converted to an RGBA pixel with the help of the **GL_PIXEL_MAP_I_TO_R**, **GL_PIXEL_MAP_I_TO_G**, **GL_PIXEL_MAP_I_TO_B**, and **GL_PIXEL_MAP_I_TO_A** tables. If the GL is in color index mode, and if **GL_MAP_COLOR** is true, the index is replaced with the value that it references in lookup table **GL_PIXEL_MAP_I_TO_I**. Whether the lookup replacement of the index is done or not, the integer part of the index is then ANDed with $2^b - 1$, where b is the number of bits in a color index buffer.

The GL then converts the resulting indices or RGBA colors to fragments by attaching the current raster position z coordinate and texture coordinates to each pixel, then assigning x and y window coordinates to the n th fragment such that

$$\begin{aligned}x_n &= x_r + n \bmod \text{width} \\y_n &= y_r + \lfloor n / \text{width} \rfloor\end{aligned}$$

where (x_r, y_r) is the current raster position. These pixelrfragments are then treated just like the fragments generated by rasterizing points, lines, or polygons. Texture mapping, fog, and all the fragment operations are applied before the fragments are written to the frame buffer.

GL_STENCIL_INDEX

Each pixel is a single value, a stencil index. It is converted to fixed-point format, with an unspecified number of bits to the right of the binary point, regardless of the memory data type. Floating-point values convert to true fixed-point values. Signed and unsigned integer data is converted with all fraction bits set to 0. Bitmap data convert to either 0 or 1.

Each fixed-point index is then shifted left by **GL_INDEX_SHIFT** bits, and added to **GL_INDEX_OFFSET**. If **GL_INDEX_SHIFT** is negative, the shift is to the right. In either case, zero bits fill otherwise unspecified bit locations in the result. If **GL_MAP_STENCIL** is true, the index is replaced with the value that it references in lookup table **GL_PIXEL_MAP_S_TO_S**. Whether the lookup replacement of the index is done or not, the integer part of the index is then ANDed with $2^b - 1$, where b is the number of bits in the stencil buffer. The resulting stencil indices are then written to the stencil buffer such that the n th index is written to location

$$x_n = x_r + n \bmod \text{width}$$

$$y = y_r + \lfloor n / \text{width} \rfloor$$

where (x_r, y_r) is the current raster position. Only the pixel ownership test, the scissor test, and the stencil writemask affect these write operations.

GL_DEPTH_COMPONENT

Each pixel is a single-depth component. Floating-point data is converted directly to an internal floating-point format with unspecified precision. Signed integer data is mapped linearly to the internal floating-point format such that the most positive representable integer value maps to 1.0, and the most negative representable value maps to -1.0. Unsigned integer data is mapped similarly: the largest integer value maps to 1.0, and 0 maps to 0.0. The resulting floating-point depth value is then multiplied by **GL_DEPTH_SCALE** and added to **GL_DEPTH_BIAS**. The result is clamped to the range $[0, 1]$.

The GL then converts the resulting depth components to fragments by attaching the current raster position color or color index and texture coordinates to each pixel, then assigning x and y window coordinates to the n th fragment such that

$$x_n = x_r + n \bmod \text{width}$$

$$y = y_r + \lfloor n / \text{width} \rfloor$$

n r

where (x ,y) is the current raster position. These pixel fragments are then treated just like the fragments generated by rasterizing points, lines, or polygons. Texture mapping, fog, and all the fragment operations are applied before the fragments are written to the frame buffer.

GL_RGBA

Each pixel is a four-component group: for **GL_RGBA**, the red component is first, followed by green, followed by blue, followed by alpha. Floating-point values are converted directly to an internal floating-point format with unspecified precision. Signed integer values are mapped linearly to the internal floating-point format such that the most positive representable integer value maps to 1.0, and the most negative representable value maps to -1.0. (Note that this mapping does not convert 0 precisely to 0.0.) Unsigned integer data is mapped similarly: the largest integer value maps to 1.0, and 0 maps to 0.0. The resulting floating-point color values are then multiplied by **GL_c_SCALE** and added to **GL_c_BIAS**, where *c* is RED, GREEN, BLUE, and ALPHA for the respective color components. The results are clamped to the range [0,1].

If **GL_MAP_COLOR** is true, each color component is scaled by the size of lookup table **GL_PIXEL_MAP_c_TO_c**, then replaced by the value that it references in that table. *c* is R, G, B, or A respectively.

The GL then converts the resulting RGBA colors to fragments by attaching the current raster position *z* coordinate and texture coordinates to each pixel, then assigning *x* and *y* window coordinates to the *n*th fragment such that

$$\begin{aligned}x_n &= x_r + n \bmod \text{width} \\y_n &= y_r + \lfloor n/\text{width} \rfloor\end{aligned}$$

where (x ,y) is the current raster position. These pixel fragments are then treated just like the fragments generated by rasterizing points, lines, or

polygons. Texture mapping, fog, and all the fragment operations are applied before the fragments are written to the frame buffer.

GL_RED

Each pixel is a single red component. This component is converted to the internal floating-point format in the same way the red component of an RGBA pixel is. It is then converted to an RGBA pixel with green and blue set to 0, and alpha set to 1. After this conversion, the pixel is treated as if it had been read as an RGBA pixel.

GL_GREEN

Each pixel is a single green component. This component is converted to the internal floating-point format in the same way the green component of an RGBA pixel is. It is then converted to an RGBA pixel with red and blue set to 0, and alpha set to 1. After this conversion, the pixel is treated as if it had been read as an RGBA pixel.

GL_BLUE

Each pixel is a single blue component. This component is converted to the internal floating-point format in the same way the blue component of an RGBA pixel is. It is then converted to an RGBA pixel with red and green set to 0, and alpha set to 1. After this conversion, the pixel is treated as if it had been read as an RGBA pixel.

GL_ALPHA

Each pixel is a single alpha component. This component is converted to the internal floating-point format in the same way the alpha component of an RGBA pixel is. It is then converted to an RGBA pixel with red, green, and blue set to 0. After this conversion, the pixel is treated as if it had been read as an RGBA pixel.

GL_RGB

Each pixel is a three-component group: red first, followed by green, followed by blue. Each component is converted to the internal floating-point format in the same way the red, green, and blue components of an RGBA pixel are. The color triple is converted to an RGBA pixel with alpha set to 1. After this conversion, the

pixel is treated as if it had been read as an RGBA pixel.

GL_LUMINANCE

Each pixel is a single luminance component. This component is converted to the internal floating-point format in the same way the red component of an RGBA pixel is. It is then converted to an RGBA pixel with red, green, and blue set to the converted luminance value, and alpha set to 1. After this conversion, the pixel is treated as if it had been read as an RGBA pixel.

GL_LUMINANCE_ALPHA

Each pixel is a two-component group: luminance first, followed by alpha. The two components are converted to the internal floating-point format in the same way the red component of an RGBA pixel is. They are then converted to an RGBA pixel with red, green, and blue set to the converted luminance value, and alpha set to the converted alpha value. After this conversion, the pixel is treated as if it had been read as an RGBA pixel.

The following table summarizes the meaning of the valid constants for the *type* parameter:

<i>type</i>	<i>corresponding type</i>
GL_UNSIGNED_BYTE	unsigned 8-bit integer
GL_BYTE	signed 8-bit integer
GL_BITMAP	single bits in unsigned 8-bit integers
GL_UNSIGNED_SHORT	unsigned 16-bit integer
GL_SHORT	signed 16-bit integer
GL_UNSIGNED_INT	unsigned 32-bit integer

GL_INT	32-bit integer
GL_FLOAT	single-precision floating-point

The rasterization described so far assumes pixel zoom factors of 1. If

glPixelZoom is used to change the x and y pixel zoom factors, pixels are converted to fragments as follows. If (x , y) is the current raster position, and a given pixel is in the nth column and mth row of the pixel rectangle, then fragments are generated for pixels whose centers are in the rectangle with corners at

$$\begin{array}{cccc} & & (x + \text{zoom } n, & y + \text{zoom } m) \\ & r & x & r & y \\ (x + \text{zoom } (n+1), & y + \text{zoom } (m+1)) \\ & r & x & r & y \end{array}$$

where zoom_x is the value of **GL_ZOOM_X** and zoom_y is the value of **GL_ZOOM_Y**.

ERRORS

GL_INVALID_VALUE is generated if either *width* or *height* is negative.

GL_INVALID_ENUM is generated if *format* or *type* is not one of the accepted values.

GL_INVALID_OPERATION is generated if *format* is **GL_RED**, **GL_GREEN**, **GL_BLUE**, **GL_ALPHA**, **GL_RGB**, **GL_RGBA**, **GL_LUMINANCE**, or **GL_LUMINANCE_ALPHA**, and the GL is in color index mode.

GL_INVALID_ENUM is generated if *type* is **GL_BITMAP** and *format* is not either **GL_COLOR_INDEX** or **GL_STENCIL_INDEX**.

GL_INVALID_OPERATION is generated if *format* is **GL_STENCIL_INDEX** and there is no stencil buffer.

GL_INVALID_OPERATION is generated if **glDrawPixels** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_CURRENT_RASTER_POSITION**

glGet with argument **GL_CURRENT_RASTER_POSITION_VALID**

SEE ALSO

`glAlphaFunc`, `glBlendFunc`, `glCopyPixels`, `glDepthFunc`,
`glLogicOp`, `glPixelMap`, `glPixelStore`, `glPixelTransfer`,
`glPixelZoom`, `glRasterPos`, `glReadPixels`, `glScissor`,
`glStencilFunc`

NAME

glEdgeFlag, **glEdgeFlagv** - flag edges as either boundary or nonboundary

C SPECIFICATION

```
void glEdgeFlag( GLboolean flag )
```

PARAMETERS

flag Specifies the current edge flag value, either **GL_TRUE** or **GL_FALSE**. The initial value is **GL_TRUE**.

C SPECIFICATION

```
void glEdgeFlagv( const GLboolean *flag )
```

PARAMETERS

flag Specifies a pointer to an array that contains a single boolean element, which replaces the current edge flag value.

DESCRIPTION

Each vertex of a polygon, separate triangle, or separate quadrilateral specified between a **glBegin**/**glEnd** pair is marked as the start of either a boundary or nonboundary edge. If the current edge flag is true when the vertex is specified, the vertex is marked as the start of a boundary edge. Otherwise, the vertex is marked as the start of a nonboundary edge. **glEdgeFlag** sets the edge flag bit to **GL_TRUE** if *flag* is **GL_TRUE**, and to **GL_FALSE** otherwise.

The vertices of connected triangles and connected quadrilaterals are always marked as boundary, regardless of the value of the edge flag.

Boundary and nonboundary edge flags on vertices are significant only if **GL_POLYGON_MODE** is set to **GL_POINT** or **GL_LINE**. See **glPolygonMode**.

NOTES

The current edge flag can be updated at any time. In particular, **glEdgeFlag** can be called between a call to **glBegin** and the corresponding call to **glEnd**.

ASSOCIATED GETS

`glGet` with argument `GL_EDGE_FLAG`

SEE ALSO

`glBegin`, `glEdgeFlagPointer`, `glPolygonMode`

NAME

glEdgeFlagPointer - define an array of edge flags

C SPECIFICATION

```
void glEdgeFlagPointer( GLsizei stride,  
                        const GLvoid *pointer )
```

PARAMETERS

stride Specifies the byte offset between consecutive edge flags. If *stride* is 0 (the initial value), the edge flags are understood to be tightly packed in the array.

pointer Specifies a pointer to the first edge flag in the array.

DESCRIPTION

glEdgeFlagPointer specifies the location and data format of an array of boolean edge flags to use when rendering. *stride* specifies the byte stride from one edge flag to the next allowing vertexes and attributes to be packed into a single array or stored in separate arrays. (Single-array storage may be more efficient on some implementations; see **glInterleavedArrays**.)

When an edge flag array is specified, *stride* and *pointer* are saved as client-side state.

To enable and disable the edge flag array, call **glEnableClientState** and **glDisableClientState** with the argument **GL_EDGE_FLAG_ARRAY**. If enabled, the edge flag array is used when **glDrawArrays**, **glDrawElements**, or **glArrayElement** is called.

Use **glDrawArrays** to construct a sequence of primitives (all of the same type) from prespecified vertex and vertex attribute arrays. Use **glArrayElement** to specify primitives by indexing vertexes and vertex attributes and **glDrawElements** to construct a sequence of primitives by indexing vertexes and vertex attributes.

NOTES

glEdgeFlagPointer is available only if the GL version is 1.1

or greater.

The edge flag array is initially disabled and it won't be accessed when

glArrayElement, **glDrawElements** or **glDrawArrays** is called.

Execution of **glEdgeFlagPointer** is not allowed between the execution of **glBegin** and the corresponding execution of **glEnd**, but an error may or may not be generated. If no error is generated, the operation is undefined.

glEdgeFlagPointer is typically implemented on the client side.

Edge flag array parameters are client-side state and are therefore not saved or restored by **glPushAttrib** and **glPopAttrib**. Use **glPushClientAttrib** and **glPopClientAttrib** instead.

ERRORS

GL_INVALID_ENUM is generated if *stride* is negative.

ASSOCIATED GETS

glIsEnabled with argument **GL_EDGE_FLAG_ARRAY**

glGet with argument **GL_EDGE_FLAG_ARRAY_STRIDE**

glGetPointerv with argument **GL_EDGE_FLAG_ARRAY_POINTER**

SEE ALSO

glArrayElement, **glColorPointer**, **glDrawArrays**,
glDrawElements, **glEnable**, **glGetPointerv**, **glIndexPointer**,
glNormalPointer, **glPopClientAttrib**,
glPushClientAttrib, **glTexCoordPointer**, **glVertexPointer**

NAME

glEnable, **glDisable** - enable or disable server-side GL capabilities

C SPECIFICATION

```
void glEnable( GLenum cap )
```

PARAMETERS

cap Specifies a symbolic constant indicating a GL capability.

C SPECIFICATION

```
void glDisable( GLenum cap )
```

PARAMETERS

cap Specifies a symbolic constant indicating a GL capability.

DESCRIPTION

glEnable and **glDisable** enable and disable various capabilities. Use **glIsEnabled** or **glGet** to determine the current setting of any capability. The initial value for each capability with the exception of **GL_DITHER** is **GL_FALSE**. The initial value for **GL_DITHER** is **GL_TRUE**.

Both **glEnable** and **glDisable** take a single argument, *cap*, which can assume one of the following values:

GL_ALPHA_TEST	If enabled, do alpha testing. See glAlphaFunc .
GL_AUTO_NORMAL	If enabled, generate normal vectors when either GL_MAP2_VERTEX_3 or GL_MAP2_VERTEX_4 is used to generate vertices. See glMap2 .
GL_BLEND	If enabled, blend the incoming RGBA color values with the values in the color buffers. See glBlendFunc .
GL_CLIP_PLANE<i>i</i>	If enabled, clip geometry against user-defined clipping plane <i>i</i> . See

	glClipPlane.
GL_COLOR_LOGIC_OP	If enabled, apply the currently selected logical operation to the incoming RGBA color and color buffer values. See glLogicOp .
GL_COLOR_MATERIAL	If enabled, have one or more material parameters track the current color. See glColorMaterial .
GL_CULL_FACE	If enabled, cull polygons based on their winding in window coordinates. See glCullFace .
GL_DEPTH_TEST	If enabled, do depth comparisons and update the depth buffer. Note that even if the depth buffer exists and the depth mask is non-zero, the depth buffer is not updated if the depth test is disabled. See glDepthFunc and glDepthRange .
GL_DITHER	If enabled, dither color components or indices before they are written to the color buffer.
GL_FOG	If enabled, blend a fog color into the posttexturing color. See glFog .
GL_INDEX_LOGIC_OP	If enabled, apply the currently selected logical operation to the incoming index and color buffer indices. See glLogicOp .
GL_LIGHT<i>i</i>	If enabled, include light <i>i</i> in the evaluation of the lighting equation. See glLightModel and glLight .
GL_LIGHTING	If enabled, use the current lighting parameters to compute the

	vertex color or index. Otherwise, simply associate the current color or index with each vertex. See glMaterial , glLightModel , and glLight .
GL_LINE_SMOOTH	If enabled, draw lines with correct filtering. Otherwise, draw aliased lines. See glLineWidth .
GL_LINE_STIPPLE	If enabled, use the current line stipple pattern when drawing lines. See glLineStipple .
GL_MAP1_COLOR_4	If enabled, calls to glEvalCoord1 , glEvalMesh1 , and glEvalPoint1 generate RGBA values. See glMap1 .
GL_MAP1_INDEX	If enabled, calls to glEvalCoord1 , glEvalMesh1 , and glEvalPoint1 generate color indices. See glMap1 .
GL_MAP1_NORMAL	If enabled, calls to glEvalCoord1 , glEvalMesh1 , and glEvalPoint1 generate normals. See glMap1 .
GL_MAP1_TEXTURE_COORD_1	If enabled, calls to glEvalCoord1 , glEvalMesh1 , and glEvalPoint1 generate <i>s</i> texture coordinates. See glMap1 .
GL_MAP1_TEXTURE_COORD_2	If enabled, calls to glEvalCoord1 , glEvalMesh1 , and glEvalPoint1 generate <i>s</i> and <i>t</i> texture coordinates. See glMap1 .
GL_MAP1_TEXTURE_COORD_3	If enabled, calls to glEvalCoord1 , glEvalMesh1 , and glEvalPoint1 generate <i>s</i> , <i>t</i> , and <i>r</i> texture coordinates. See glMap1 .
GL_MAP1_TEXTURE_COORD_4	If enabled, calls to glEvalCoord1 , glEvalMesh1 , and glEvalPoint1 generate <i>s</i> , <i>t</i> , <i>r</i> , and <i>q</i> texture coordinates. See glMap1 .

GL_MAP1_VERTEX_3	If enabled, calls to glEvalCoord1 , glEvalMesh1 , and glEvalPoint1 generate <i>x</i> , <i>y</i> , and <i>z</i> vertex coordinates. See glMap1 .
GL_MAP1_VERTEX_4	If enabled, calls to glEvalCoord1 , glEvalMesh1 , and glEvalPoint1 generate homogeneous <i>x</i> , <i>y</i> , <i>z</i> , and <i>w</i> vertex coordinates. See glMap1 .
GL_MAP2_COLOR_4	If enabled, calls to glEvalCoord2 , glEvalMesh2 , and glEvalPoint2 generate RGBA values. See glMap2 .
GL_MAP2_INDEX	If enabled, calls to glEvalCoord2 , glEvalMesh2 , and glEvalPoint2 generate color indices. See glMap2 .
GL_MAP2_NORMAL	If enabled, calls to glEvalCoord2 , glEvalMesh2 , and glEvalPoint2 generate normals. See glMap2 .
GL_MAP2_TEXTURE_COORD_1	If enabled, calls to glEvalCoord2 , glEvalMesh2 , and glEvalPoint2 generate <i>s</i> texture coordinates. See glMap2 .
GL_MAP2_TEXTURE_COORD_2	If enabled, calls to glEvalCoord2 , glEvalMesh2 , and glEvalPoint2 generate <i>s</i> and <i>t</i> texture coordinates. See glMap2 .
GL_MAP2_TEXTURE_COORD_3	If enabled, calls to glEvalCoord2 , glEvalMesh2 , and glEvalPoint2 generate <i>s</i> , <i>t</i> , and <i>r</i> texture coordinates. See glMap2 .
GL_MAP2_TEXTURE_COORD_4	If enabled, calls to glEvalCoord2 , glEvalMesh2 , and glEvalPoint2 generate <i>s</i> , <i>t</i> , <i>r</i> , and <i>q</i> texture coordinates. See glMap2 .
GL_MAP2_VERTEX_3	If enabled, calls to glEvalCoord2 , glEvalMesh2 , and glEvalPoint2

	generate x, y, and z vertex coordinates. See glMap2 .
GL_MAP2_VERTEX_4	If enabled, calls to glEvalCoord2 , glEvalMesh2 , and glEvalPoint2 generate homogeneous x, y, z, and w vertex coordinates. See glMap2 .
GL_NORMALIZE	If enabled, normal vectors specified with glNormal are scaled to unit length after transformation. See glNormal .
GL_POINT_SMOOTH	If enabled, draw points with proper filtering. Otherwise, draw aliased points. See glPointSize .
GL_POLYGON_OFFSET_FILL	If enabled, and if the polygon is rendered in GL_FILL mode, an offset is added to depth values of a polygon's fragments before the depth comparison is performed. See glPolygonOffset .
GL_POLYGON_OFFSET_LINE	If enabled, and if the polygon is rendered in GL_LINE mode, an offset is added to depth values of a polygon's fragments before the depth comparison is performed. See glPolygonOffset .
GL_POLYGON_OFFSET_POINT	If enabled, an offset is added to depth values of a polygon's fragments before the depth comparison is performed, if the polygon is rendered in GL_POINT mode. See glPolygonOffset .
GL_POLYGON_SMOOTH	If enabled, draw polygons with proper filtering. Otherwise, draw aliased polygons. For correct anti-aliased polygons, an alpha buffer is needed and the polygons must be sorted front to back.

GL_POLYGON_STIPPLE	If enabled, use the current polygon stipple pattern when rendering polygons. See glPolygonStipple .
GL_SCISSOR_TEST	If enabled, discard fragments that are outside the scissor rectangle. See glScissor .
GL_STENCIL_TEST	If enabled, do stencil testing and update the stencil buffer. See glStencilFunc and glStencilOp .
GL_TEXTURE_1D	If enabled, one-dimensional texturing is performed (unless two-dimensional texturing is also enabled). See glTexImage1D .
GL_TEXTURE_2D	If enabled, two-dimensional texturing is performed. See glTexImage2D .
GL_TEXTURE_GEN_Q	If enabled, the <i>q</i> texture coordinate is computed using the texture generation function defined with glTexGen . Otherwise, the current <i>q</i> texture coordinate is used. See glTexGen .
GL_TEXTURE_GEN_R	If enabled, the <i>r</i> texture coordinate is computed using the texture generation function defined with glTexGen . Otherwise, the current <i>r</i> texture coordinate is used. See glTexGen .
GL_TEXTURE_GEN_S	If enabled, the <i>s</i> texture coordinate is computed using the texture generation function defined with glTexGen . Otherwise, the current <i>s</i> texture coordinate is used. See glTexGen .
GL_TEXTURE_GEN_T	If enabled, the <i>t</i> texture coordinate is computed using the texture generation function defined with glTexGen . Otherwise, the

current *t* texture coordinate is used. See **glTexGen**.

NOTES

GL_POLYGON_OFFSET_FILL, **GL_POLYGON_OFFSET_LINE**, **GL_POLYGON_OFFSET_POINT**, **GL_COLOR_LOGIC_OP**, and **GL_INDEX_LOGIC_OP** are only available if the GL version is 1.1 or greater.

ERRORS

GL_INVALID_ENUM is generated if *cap* is not one of the values listed previously.

GL_INVALID_OPERATION is generated if **glEnable** or **glDisable** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

SEE ALSO

glAlphaFunc, **glBlendFunc**, **glClipPlane**, **glColorMaterial**, **glCullFace**, **glDepthFunc**, **glDepthRange**, **glEnableClientState**, **glFog**, **glGet**, **glIsEnabled**, **glLight**, **glLightModel**, **glLineWidth**, **glLineStipple**, **glLogicOp**, **glMap1**, **glMap2**, **glMaterial**, **glNormal**, **glPointSize**, **glPolygonMode**, **glPolygonOffset**, **glPolygonStipple**, **glScissor**, **glStencilFunc**, **glStencilOp**, **glTexGen**, **glTexImage1D**, **glTexImage2D**

NAME

glEnableClientState, **glDisableClientState** - enable or disable client-side capability

C SPECIFICATION

```
void glEnableClientState( GLenum cap )
```

PARAMETERS

cap Specifies the capability to enable. Symbolic constants **GL_COLOR_ARRAY**, **GL_EDGE_FLAG_ARRAY**, **GL_INDEX_ARRAY**, **GL_NORMAL_ARRAY**, **GL_TEXTURE_COORD_ARRAY**, and **GL_VERTEX_ARRAY** are accepted.

C SPECIFICATION

```
void glDisableClientState( GLenum cap )
```

PARAMETERS

cap Specifies the capability to disable.

DESCRIPTION

glEnableClientState and **glDisableClientState** enable or disable individual client-side capabilities. By default, all client-side capabilities are disabled. Both **glEnableClientState** and **glDisableClientState** take a single argument, *cap*, which can assume one of the following values:

GL_COLOR_ARRAY	If enabled, the color array is enabled for writing and used during rendering when glDrawArrays or glDrawElement is called. See glColorPointer .
GL_EDGE_FLAG_ARRAY	If enabled, the edge flag array is enabled for writing and used during rendering when glDrawArrays or glDrawElements is called. See glEdgeFlagPointer .
GL_INDEX_ARRAY	If enabled, the index array is enabled for writing and used during rendering when glDrawArrays or glDrawElements is called. See

glIndexPointer.

GL_NORMAL_ARRAY

If enabled, the normal array is enabled for writing and used during rendering when **glDrawArrays** or **glDrawElements** is called. See **glNormalPointer.**

GL_TEXTURE_COORD_ARRAY

If enabled, the texture coordinate array is enabled for writing and used for rendering when **glDrawArrays** or **glDrawElements** is called. See **glTexCoordPointer.**

GL_VERTEX_ARRAY

If enabled, the vertex array is enabled for writing and used during rendering when **glDrawArrays** or **glDrawElements** is called. See **glVertexPointer.**

NOTES

glEnableClientState is available only if the GL version is 1.1 or greater.

ERRORS

GL_INVALID_ENUM is generated if *cap* is not an accepted value.

glEnableClientState is not allowed between the execution of **glBegin** and the corresponding **glEnd**, but an error may or may not be generated. If no error is generated, the behavior is undefined.

SEE ALSO

glArrayElement, glColorPointer, glDrawArrays, glDrawElements, glEdgeFlagPointer, glEnable, glGetPointerv, glIndexPointer, glInterleavedArrays, glNormalPointer, glTexCoordPointer, glVertexPointer

NAME

glEvalCoord1d, **glEvalCoord1f**, **glEvalCoord2d**, **glEvalCoord2f**,
glEvalCoord1dv, **glEvalCoord1fv**, **glEvalCoord2dv**,
glEvalCoord2fv - evaluate enabled one- and two-dimensional
maps

C SPECIFICATION

```
void glEvalCoord1d( GLdouble u )  
void glEvalCoord1f( GLfloat u )  
void glEvalCoord2d( GLdouble u,  
                    GLdouble v )  
void glEvalCoord2f( GLfloat u,  
                    GLfloat v )
```

PARAMETERS

- u* Specifies a value that is the domain coordinate *u* to the basis function defined in a previous **glMap1** or **glMap2** command.
- v* Specifies a value that is the domain coordinate *v* to the basis function defined in a previous **glMap2** command.
This argument is not present in a **glEvalCoord1** command.

C SPECIFICATION

```
void glEvalCoord1dv( const GLdouble *u )  
void glEvalCoord1fv( const GLfloat *u )  
void glEvalCoord2dv( const GLdouble *u )  
void glEvalCoord2fv( const GLfloat *u )
```

PARAMETERS

- u* Specifies a pointer to an array containing either one or two domain coordinates. The first coordinate is *u*. The second coordinate is *v*, which is present only in **glEvalCoord2** versions.

DESCRIPTION

glEvalCoord1 evaluates enabled one-dimensional maps at argument *u*. **glEvalCoord2** does the same for two-dimensional maps using two domain values, *u* and *v*. To define a map, call **glMap1** and **glMap2**; to enable and disable it, call **glEnable** and **glDisable**.

When one of the **glEvalCoord** commands is issued, all currently enabled maps of the indicated dimension are evaluated. Then, for each enabled map, it is as if the corresponding GL command had been issued with the computed value. That is, if **GL_MAP1_INDEX** or **GL_MAP2_INDEX** is enabled, a **glIndex** command is simulated. If **GL_MAP1_COLOR_4** or **GL_MAP2_COLOR_4** is enabled, a **glColor** command is simulated. If **GL_MAP1_NORMAL** or **GL_MAP2_NORMAL** is enabled, a normal vector is produced, and if any of **GL_MAP1_TEXTURE_COORD_1**, **GL_MAP1_TEXTURE_COORD_2**, **GL_MAP1_TEXTURE_COORD_3**, **GL_MAP1_TEXTURE_COORD_4**, **GL_MAP2_TEXTURE_COORD_1**, **GL_MAP2_TEXTURE_COORD_2**, **GL_MAP2_TEXTURE_COORD_3**, or **GL_MAP2_TEXTURE_COORD_4** is enabled, then an appropriate **glTexCoord** command is simulated.

For color, color index, normal, and texture coordinates the GL uses evaluated values instead of current values for those evaluations that are enabled, and current values otherwise. However, the evaluated values do not update the current values. Thus, if **glVertex** commands are interspersed with **glEvalCoord** commands, the color, normal, and texture coordinates associated with the **glVertex** commands are not affected by the values generated by the **glEvalCoord** commands, but only by the most recent **glColor**, **glIndex**, **glNormal**, and **glTexCoord** commands.

No commands are issued for maps that are not enabled. If more than one texture evaluation is enabled for a particular dimension (for example, **GL_MAP2_TEXTURE_COORD_1** and **GL_MAP2_TEXTURE_COORD_2**), then only the evaluation of the map that produces the larger number of coordinates (in this case, **GL_MAP2_TEXTURE_COORD_2**) is carried out. **GL_MAP1_VERTEX_4** overrides **GL_MAP1_VERTEX_3**, and **GL_MAP2_VERTEX_4** overrides **GL_MAP2_VERTEX_3**, in the same manner. If neither a three- nor a four-component vertex map is enabled for the specified dimension, the **glEvalCoord** command is ignored.

If you have enabled automatic normal generation, by calling **glEnable** with argument **GL_AUTO_NORMAL**, **glEvalCoord2** generates surface normals analytically, regardless of the contents or enabling of the **GL_MAP2_NORMAL** map. Let

$$\begin{matrix} & P_p & P_p \\ m = & -- & X & -- \end{matrix}$$

Then the generated normal n is

$$n = \frac{-}{||m||}$$

If automatic normal generation is disabled, the corresponding normal map **GL_MAP2_NORMAL**, if enabled, is used to produce a normal. If neither automatic normal generation nor a normal map is enabled, no normal is generated for **glEvalCoord2** commands.

ASSOCIATED GETS

glIsEnabled with argument **GL_MAP1_VERTEX_3**
glIsEnabled with argument **GL_MAP1_VERTEX_4**
glIsEnabled with argument **GL_MAP1_INDEX**
glIsEnabled with argument **GL_MAP1_COLOR_4**
glIsEnabled with argument **GL_MAP1_NORMAL**
glIsEnabled with argument **GL_MAP1_TEXTURE_COORD_1**
glIsEnabled with argument **GL_MAP1_TEXTURE_COORD_2**
glIsEnabled with argument **GL_MAP1_TEXTURE_COORD_3**
glIsEnabled with argument **GL_MAP1_TEXTURE_COORD_4**
glIsEnabled with argument **GL_MAP2_VERTEX_3**
glIsEnabled with argument **GL_MAP2_VERTEX_4**
glIsEnabled with argument **GL_MAP2_INDEX**
glIsEnabled with argument **GL_MAP2_COLOR_4**
glIsEnabled with argument **GL_MAP2_NORMAL**
glIsEnabled with argument **GL_MAP2_TEXTURE_COORD_1**
glIsEnabled with argument **GL_MAP2_TEXTURE_COORD_2**
glIsEnabled with argument **GL_MAP2_TEXTURE_COORD_3**
glIsEnabled with argument **GL_MAP2_TEXTURE_COORD_4**
glIsEnabled with argument **GL_AUTO_NORMAL**
glGetMap

SEE ALSO

glBegin, **glColor**, **glEnable**, **glEvalMesh**, **glEvalPoint**,
glIndex, **glMap1**, **glMap2**, **glMapGrid**, **glNormal**, **glTexCoord**,
glVertex

NAME

glEvalMesh1, **glEvalMesh2** - compute a one- or two-dimensional grid of points or lines

C SPECIFICATION

```
void glEvalMesh1( GLenum mode,  
                  GLint i1,  
                  GLint i2 )
```

PARAMETERS

mode In **glEvalMesh1**, specifies whether to compute a one-dimensional mesh of points or lines. Symbolic constants **GL_POINT** and **GL_LINE** are accepted.

i1, *i2*

Specify the first and last integer values for grid domain variable *i*.

C SPECIFICATION

```
void glEvalMesh2( GLenum mode,  
                  GLint i1,  
                  GLint i2,  
                  GLint j1,  
                  GLint j2 )
```

PARAMETERS

mode In **glEvalMesh2**, specifies whether to compute a two-dimensional mesh of points, lines, or polygons. Symbolic constants **GL_POINT**, **GL_LINE**, and **GL_FILL** are accepted.

i1, *i2*

Specify the first and last integer values for grid domain variable *i*.

j1, *j2*

Specify the first and last integer values for grid domain variable *j*.

DESCRIPTION

glMapGrid and **glEvalMesh** are used in tandem to efficiently generate and evaluate a series of evenly-spaced map domain

values. **glEvalMesh** steps through the integer domain of a one- or two-dimensional grid, whose range is the domain of the evaluation maps specified by **glMap1** and **glMap2**. *mode* determines whether the resulting vertices are connected as points, lines, or filled polygons.

In the one-dimensional case, **glEvalMesh1**, the mesh is generated as if the following code fragment were executed:

```
glBegin (type);
for (i = i1; i <= i2; i += 1)
    glEvalCoord1(i . DELTA u + u sub 1)
glEnd();
```

where

$$\text{DELTA } u = (u_2 - u_1) / 1$$

and n , u_1 , and u_2 are the arguments to the most recent

glMapGrid1 command. *type* is **GL_POINTS** if *mode* is **GL_POINT**, or **GL_LINES** if *mode* is **GL_LINE**.

The one absolute numeric requirement is that if $i = n$, then the value computed from

$$i . \text{DELTA } u + u$$

is exactly u .

In the two-dimensional case, **glEvalMesh2**, let

$$\text{DELTA } u = (u_2 - u_1) / n$$

$$\text{DELTA } v = (v_2 - v_1) / m,$$

where n , u_1 , u_2 , m , v_1 , and v_2

are the arguments to the most recent **glMapGrid2** command. Then, if *mode* is **GL_FILL**, the **glEvalMesh2** command is equivalent to:

```
for (j = j1; j < j2; j += 1) {
```

```

glBegin (GL_QUAD_STRIP);
for (i = i1; i <= i2; i += 1) {
    glEvalCoord2(i . DELTA u + u , j . DELTA v + v );
                                1                                1
    glEvalCoord2(i . DELTA u + u , (j+1) . DELTA v + v );
                                1                                1
}
glEnd();
}

```

If *mode* is **GL_LINE**, then a call to **glEvalMesh2** is equivalent to:

```

for (j = j1; j <= j2; j += 1) {
    glBegin(GL_LINE_STRIP);
    for (i = i1; i <= i2; i += 1)
        glEvalCoord2(i . DELTA u + u , j . DELTA v + v );
                                1                                1
    glEnd();
}
for (i = i1; i <= i2; i += 1) {
    glBegin(GL_LINE_STRIP);
    for (j = j1; j <= j2; j += 1)
        glEvalCoord2(i . DELTA u + u , j . DELTA v + v );
                                1                                1
    glEnd();
}

```

And finally, if *mode* is **GL_POINT**, then a call to **glEvalMesh2** is equivalent to:

```

glBegin (GL_POINTS);
for (j = j1; j <= j2; j += 1) {
    for (i = i1; i <= i2; i += 1) {
        glEvalCoord2(i . DELTA u + u , j . DELTA v + v );
                                1                                1
    }
}
glEnd();

```

In all three cases, the only absolute numeric requirements are that if $i = n$, then the value computed from $i . \text{DELTA } u + u$ is exactly u ,
 $\qquad\qquad\qquad 1 \qquad\qquad\qquad 2$
and if $j = m$,

then the value computed from
$$j \cdot \text{DELTA } v_1 + v_2 \text{ is exactly } v.$$

ERRORS

GL_INVALID_ENUM is generated if *mode* is not an accepted value.

GL_INVALID_OPERATION is generated if **glEvalMesh** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_MAP1_GRID_DOMAIN**

glGet with argument **GL_MAP2_GRID_DOMAIN**

glGet with argument **GL_MAP1_GRID_SEGMENTS**

glGet with argument **GL_MAP2_GRID_SEGMENTS**

SEE ALSO

glBegin, **glEvalCoord**, **glEvalPoint**, **glMap1**, **glMap2**, **glMapGrid**

NAME

glEvalPoint1, **glEvalPoint2** - generate and evaluate a single point in a mesh

C SPECIFICATION

```
void glEvalPoint1( GLint i )
void glEvalPoint2( GLint i,
                  GLint j )
```

PARAMETERS

i Specifies the integer value for grid domain variable *i*.

j Specifies the integer value for grid domain variable *j* (**glEvalPoint2** only).

DESCRIPTION

glMapGrid and **glEvalMesh** are used in tandem to efficiently generate and evaluate a series of evenly spaced map domain values. **glEvalPoint** can be used to evaluate a single grid point in the same gridspace that is traversed by **glEvalMesh**. Calling **glEvalPoint1** is equivalent to calling

```
glEvalCoord1(i . DELTA u + u );
              1
```

where

$$\text{DELTA } u = (u_2 - u_1) / n$$

and n , u_1 , and u_2

are the arguments to the most recent **glMapGrid1** command. The one absolute numeric requirement is that if $i = n$, then the value computed from $i \cdot \text{DELTA } u + u_1$ is exactly u_2 .

In the two-dimensional case, **glEvalPoint2**, let $\text{DELTA } u = (u_2 - u_1) / n$

$$\text{DELTA } v = (v_2 - v_1) / m$$

where n , u_1 , u_2 , m , v_1 , and v_2

are the arguments to the most recent **glMapGrid2** command. Then the **glEvalPoint2** command is equivalent to calling

```
glEvalCoord2(i . DELTA u + u_1 , j . DELTA v + v_1 );
```

The only absolute numeric requirements are that if $i = n$, then the value computed from

$i . \text{DELTA } u + u_1$ is exactly u_2 ,

and if $j = m$, then the value computed from

$j \text{ cdot } \text{DELTA } v + v_1$ is exactly v_2 .

ASSOCIATED GETS

glGet with argument **GL_MAP1_GRID_DOMAIN**

glGet with argument **GL_MAP2_GRID_DOMAIN**

glGet with argument **GL_MAP1_GRID_SEGMENTS**

glGet with argument **GL_MAP2_GRID_SEGMENTS**

SEE ALSO

glEvalCoord, **glEvalMesh**, **glMap1**, **glMap2**, **glMapGrid**

NAME

glFeedbackBuffer - controls feedback mode

C SPECIFICATION

```
void glFeedbackBuffer( GLsizei size,  
                      GLenum type,  
                      GLfloat *buffer )
```

PARAMETERS

size Specifies the maximum number of values that can be written into *buffer*.

type Specifies a symbolic constant that describes the information that will be returned for each vertex. **GL_2D**, **GL_3D**, **GL_3D_COLOR**, **GL_3D_COLOR_TEXTURE**, and **GL_4D_COLOR_TEXTURE** are accepted.

buffer Returns the feedback data.

DESCRIPTION

The **glFeedbackBuffer** function controls feedback. Feedback, like selection, is a GL mode. The mode is selected by calling **glRenderMode** with **GL_FEEDBACK**. When the GL is in feedback mode, no pixels are produced by rasterization. Instead, information about primitives that would have been rasterized is fed back to the application using the GL.

glFeedbackBuffer has three arguments: *buffer* is a pointer to an array of floating-point values into which feedback information is placed. *size* indicates the size of the array. *type* is a symbolic constant describing the information that is fed back for each vertex. **glFeedbackBuffer** must be issued before feedback mode is enabled (by calling **glRenderMode** with argument **GL_FEEDBACK**). Setting **GL_FEEDBACK** without establishing the feedback buffer, or calling **glFeedbackBuffer** while the GL is in feedback mode, is an error.

When **glRenderMode** is called while in feedback mode, it returns the number of entries placed in the feedback array, and resets the feedback array pointer to the base of the feedback buffer. The returned value never exceeds *size*. If the feedback data required more room than was available in *buffer*, **glRenderMode** returns a negative value. To take the GL out of feedback mode, call **glRenderMode** with a parameter value other than **GL_FEEDBACK**.

While in feedback mode, each primitive, bitmap, or pixel rectangle that would be rasterized generates a block of values that are copied into the feedback array. If doing so would cause the number of entries to exceed the maximum, the

block is partially written so as to fill the array (if there is any room left at all), and an overflow flag is set. Each block begins with a code indicating the primitive type, followed by values that describe the primitive's vertices and associated data. Entries are also written for bitmaps and pixel rectangles. Feedback occurs after polygon culling and **glPolygonMode** interpretation of polygons has taken place, so polygons that are culled are not returned in the feedback buffer. It can also occur after polygons with more than three edges are broken up into triangles, if the GL implementation renders polygons by performing this decomposition.

The **glPassThrough** command can be used to insert a marker into the feedback buffer. See **glPassThrough**.

Following is the grammar for the blocks of values written into the feedback buffer. Each primitive is indicated with a unique identifying value followed by some number of vertices. Polygon entries include an integer value indicating how many vertices follow. A vertex is fed back as some number of floating-point values, as determined by *type*. Colors are fed back as four values in RGBA mode and one value in color index mode.

```
feedbackList <- feedbackItem feedbackList |
feedbackItem

feedbackItem <- point | lineSegment | polygon | bitmap
| pixelRectangle | passThru

point <- GL_POINT_TOKEN vertex

lineSegment <- GL_LINE_TOKEN vertex vertex |
GL_LINE_RESET_TOKEN vertex vertex

polygon <- GL_POLYGON_TOKEN n polySpec

polySpec <- polySpec vertex | vertex vertex vertex

bitmap <- GL_BITMAP_TOKEN vertex

pixelRectangle <- GL_DRAW_PIXEL_TOKEN vertex |
GL_COPY_PIXEL_TOKEN vertex

passThru <- GL_PASS_THROUGH_TOKEN value

vertex <- 2d | 3d | 3dColor | 3dColorTexture |
4dColorTexture

2d <- value value
3d <- value value value

3dColor <- value value value color
```

```

3dColorTexture <- value value value color tex

4dColorTexture <- value value value value color tex

color <- rgba | index

rgba <- value value value value

index <- value

tex <- value value value value

```

value is a floating-point number, and *n* is a floating-point integer giving the number of vertices in the polygon.

GL_POINT_TOKEN, **GL_LINE_TOKEN**, **GL_LINE_RESET_TOKEN**, **GL_POLYGON_TOKEN**, **GL_BITMAP_TOKEN**, **GL_DRAW_PIXEL_TOKEN**, **GL_COPY_PIXEL_TOKEN** and **GL_PASS_THROUGH_TOKEN** are symbolic floating-point constants. **GL_LINE_RESET_TOKEN** is returned whenever the line stipple pattern is reset. The data returned as a vertex depends on the feedback type.

The following table gives the correspondence between *type* and the number of values per vertex. *k* is 1 in color index mode and 4 in RGBA mode.

<i>type</i>	<i>coordinates</i>	<i>color</i>	<i>texture</i>	<i>total number of values</i>
GL_2D	<i>x, y</i>			2
GL_3D	<i>x, y, z</i>			3
GL_3D_COLOR	<i>x, y, z</i>	<i>k</i>		3+ <i>k</i>
GL_3D_COLOR_TEXTURE	<i>x, y, z,</i>	<i>k</i>	4	7+ <i>k</i>
GL_4D_COLOR_TEXTURE	<i>x, y, z, w</i>	<i>k</i>	4	8+ <i>k</i>

Feedback vertex coordinates are in window coordinates, except *w*, which is in clip coordinates. Feedback colors are lighted, if lighting is enabled. Feedback texture coordinates are generated, if texture coordinate generation is enabled. They are always transformed by the texture matrix.

NOTES

glFeedbackBuffer, when used in a display list, is not compiled into the display list but is executed immediately.

ERRORS

GL_INVALID_ENUM is generated if *type* is not an accepted value.

GL_INVALID_VALUE is generated if *size* is negative.

GL_INVALID_OPERATION is generated if **glFeedbackBuffer** is called while the render mode is **GL_FEEDBACK**, or if **glRenderMode** is called with argument **GL_FEEDBACK** before **glFeedbackBuffer** is called at least once.

GL_INVALID_OPERATION is generated if **glFeedbackBuffer** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_RENDER_MODE**

SEE ALSO

glBegin, **glLineStipple**, **glPassThrough**, **glPolygonMode**,
glRenderMode, **glSelectBuffer**

NAME

glFinish - block until all GL execution is complete

C SPECIFICATION

```
void glFinish( void )
```

DESCRIPTION

glFinish does not return until the effects of all previously called GL commands are complete. Such effects include all changes to GL state, all changes to connection state, and all changes to the frame buffer contents.

NOTES

glFinish requires a round trip to the server.

ERRORS

GL_INVALID_OPERATION is generated if **glFinish** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

SEE ALSO

glFlush

NAME

glFlush - force execution of GL commands in finite time

C SPECIFICATION

```
void glFlush( void )
```

DESCRIPTION

Different GL implementations buffer commands in several different locations, including network buffers and the graphics accelerator itself. **glFlush** empties all of these buffers, causing all issued commands to be executed as quickly as they are accepted by the actual rendering engine. Though this execution may not be completed in any particular time period, it does complete in finite time.

Because any GL program might be executed over a network, or on an accelerator that buffers commands, all programs should call **glFlush** whenever they count on having all of their previously issued commands completed. For example, call **glFlush** before waiting for user input that depends on the generated image.

NOTES

glFlush can return at any time. It does not wait until the execution of all previously issued GL commands is complete.

ERRORS

GL_INVALID_OPERATION is generated if **glFlush** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

SEE ALSO

glFinish

NAME

glFogf, glFogi, glFogfv, glFogiv - specify fog parameters

C SPECIFICATION

```
void glFogf( GLenum pname,
             GLfloat param )
void glFogi( GLenum pname,
             GLint param )
```

PARAMETERS

pname Specifies a single-valued fog parameter. **GL_FOG_MODE**, **GL_FOG_DENSITY**, **GL_FOG_START**, **GL_FOG_END**, and **GL_FOG_INDEX** are accepted.

param Specifies the value that *pname* will be set to.

C SPECIFICATION

```
void glFogfv( GLenum pname,
              const GLfloat *params )
void glFogiv( GLenum pname,
              const GLint *params )
```

PARAMETERS

pname Specifies a fog parameter. **GL_FOG_MODE**, **GL_FOG_DENSITY**, **GL_FOG_START**, **GL_FOG_END**, **GL_FOG_INDEX**, and **GL_FOG_COLOR** are accepted.

params Specifies the value or values to be assigned to *pname*. **GL_FOG_COLOR** requires an array of four values. All other parameters accept an array containing only a single value.

DESCRIPTION

Fog is initially disabled. While enabled, fog affects rasterized geometry, bitmaps, and pixel blocks, but not buffer clear operations. To enable and disable fog, call **glEnable** and **glDisable** with argument **GL_FOG**.

glFog assigns the value or values in *params* to the fog parameter specified by *pname*. The following values are

accepted for *pname*:

GL_FOG_MODE	<i>params</i> is a single integer or floating-point value that specifies the equation to be used to compute the fog blend factor, <i>f</i> . Three symbolic constants are accepted: GL_LINEAR , GL_EXP , and GL_EXP2 . The equations corresponding to these symbolic constants are defined below. The initial fog mode is GL_EXP .
GL_FOG_DENSITY	<i>params</i> is a single integer or floating-point value that specifies density, the fog density used in both exponential fog equations. Only nonnegative densities are accepted. The initial fog density is 1.
GL_FOG_START	<i>params</i> is a single integer or floating-point value that specifies start, the near distance used in the linear fog equation. The initial near distance is 0.
GL_FOG_END	<i>params</i> is a single integer or floating-point value that specifies end, the far distance used in the linear fog equation. The initial far distance is 1.
GL_FOG_INDEX	<i>params</i> is a single integer or floating-point value that specifies <i>i</i> , the fog color index. The initial fog index is 0.
GL_FOG_COLOR	<i>params</i> contains four integer or floating-point values that specify <i>C</i> , the fog color. Integer values are <i>f</i> mapped linearly such that the most positive representable value maps to 1.0, and the most negative representable value maps to -1.0. Floating-point values are mapped directly. After conversion, all color components are clamped to the range [0,1]. The initial fog color is (0, 0, 0, 0).

Fog blends a fog color with each rasterized pixel fragment's posttexturing color using a blending factor *f*. Factor *f* is computed in one of three ways, depending on the fog mode. Let *z* be the distance in eye coordinates from the origin to the fragment being fogged. The equation for **GL_LINEAR** fog is

$$f = \frac{\text{end} - \text{start}}{\text{end} - \text{start}}$$

The equation for **GL_EXP** fog is

$$f = e^{-(\text{density} \cdot z)}$$

The equation for **GL_EXP2** fog is

$$f = e^{-(\text{density} \cdot z)^2}$$

Regardless of the fog mode, *f* is clamped to the range [0,1] after it is computed. Then, if the GL is in RGBA color mode, the fragment's color *C* is replaced by

$$C_r' = fC_r + (1-f)C_r$$

In color index mode, the fragment's color index *i* is replaced by

$$i_r' = i_r + (1-f)i_r$$

ERRORS

GL_INVALID_ENUM is generated if *pname* is not an accepted value, or if *pname* is **GL_FOG_MODE** and *params* is not an accepted value.

GL_INVALID_VALUE is generated if *pname* is **GL_FOG_DENSITY**, and *params* is negative.

GL_INVALID_OPERATION is generated if **glFog** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glIsEnabled with argument **GL_FOG**

glGet with argument **GL_FOG_COLOR**
glGet with argument **GL_FOG_INDEX**
glGet with argument **GL_FOG_DENSITY**
glGet with argument **GL_FOG_START**
glGet with argument **GL_FOG_END**
glGet with argument **GL_FOG_MODE**

SEE ALSO

glEnable

NAME

glFrontFace - define front- and back-facing polygons

C SPECIFICATION

```
void glFrontFace( GLenum mode )
```

PARAMETERS

mode Specifies the orientation of front-facing polygons. **GL_CW** and **GL_CCW** are accepted. The initial value is **GL_CCW**.

DESCRIPTION

In a scene composed entirely of opaque closed surfaces, back-facing polygons are never visible. Eliminating these invisible polygons has the obvious benefit of speeding up the rendering of the image. To enable and disable elimination of back-facing polygons, call **glEnable** and **glDisable** with argument **GL_CULL_FACE**.

The projection of a polygon to window coordinates is said to have clockwise winding if an imaginary object following the path from its first vertex, its second vertex, and so on, to its last vertex, and finally back to its first vertex, moves in a clockwise direction about the interior of the polygon. The polygon's winding is said to be counterclockwise if the imaginary object following the same path moves in a counterclockwise direction about the interior of the polygon. **glFrontFace** specifies whether polygons with clockwise winding in window coordinates, or counterclockwise winding in window coordinates, are taken to be front-facing. Passing **GL_CCW** to *mode* selects counterclockwise polygons as front-facing; **GL_CW** selects clockwise polygons as front-facing. By default, counterclockwise polygons are taken to be front-facing.

ERRORS

GL_INVALID_ENUM is generated if *mode* is not an accepted value.

GL_INVALID_OPERATION is generated if **glFrontFace** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

`glGet` with argument `GL_FRONT_FACE`

SEE ALSO

`glCullFace`, `glLightModel`

NAME

glFrustum - multiply the current matrix by a perspective matrix

C SPECIFICATION

```
void glFrustum( GLdouble left,
                GLdouble right,
                GLdouble bottom,
                GLdouble top,
                GLdouble zNear,
                GLdouble zFar )
```

PARAMETERS

left, *right* Specify the coordinates for the left and right vertical clipping planes.

bottom, *top* Specify the coordinates for the bottom and top horizontal clipping planes.

zNear, *zFar* Specify the distances to the near and far depth clipping planes. Both distances must be positive.

DESCRIPTION

glFrustum describes a perspective matrix that produces a perspective projection. The current matrix (see **glMatrixMode**) is multiplied by this matrix and the result replaces the current matrix, as if **glMultMatrix** were called with the following matrix as its argument:

$$\begin{pmatrix} \frac{\text{right-left}}{zNear-zFar} & 0 & A & 0 \\ 0 & \frac{\text{top-bottom}}{zNear-zFar} & B & 0 \\ 0 & 0 & C & D \\ 0 & 0 & -1 & 0 \end{pmatrix}$$

$$A = \frac{\text{right} + \text{left}}{zNear-zFar}$$

$$B = \frac{\text{top} - \text{bottom}}{\text{zFar} - \text{zNear}}$$

$$C = \frac{-\text{zFar} - \text{zNear}}{\text{zFar} - \text{zNear}}$$

$$D = \frac{\text{right} - \text{left}}{\text{zFar} - \text{zNear}}$$

Typically, the matrix mode is **GL_PROJECTION**, and (*left*, *bottom*, *-zNear*) and (*right*, *top*, *-zNear*) specify the points on the near clipping plane that are mapped to the lower left and upper right corners of the window, assuming that the eye is located at (0, 0, 0). *-zFar* specifies the location of the far clipping plane. Both *zNear* and *zFar* must be positive.

Use **glPushMatrix** and **glPopMatrix** to save and restore the current matrix stack.

NOTES

Depth buffer precision is affected by the values specified for *zNear* and *zFar*. The greater the ratio of *zFar* to *zNear* is, the less effective the depth buffer will be at distinguishing between surfaces that are near each other. If

$$r = \frac{\text{zFar}}{\text{zNear}}$$

roughly $\log(r)$ bits of depth buffer precision are lost. Because *r* approaches infinity as *zNear* approaches 0, *zNear* must never be set to 0.

ERRORS

GL_INVALID_VALUE is generated if *zNear* or *zFar* is not positive.

GL_INVALID_OPERATION is generated if **glFrustum** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_MATRIX_MODE**
glGet with argument **GL_MODELVIEW_MATRIX**
glGet with argument **GL_PROJECTION_MATRIX**
glGet with argument **GL_TEXTURE_MATRIX**

SEE ALSO

glOrtho, **glMatrixMode**, **glMultMatrix**, **glPushMatrix**,

glViewport

NAME

glGenLists - generate a contiguous set of empty display lists

C SPECIFICATION

GLuint **glGenLists**(GLsizei *range*)

PARAMETERS

range Specifies the number of contiguous empty display lists to be generated.

DESCRIPTION

glGenLists has one argument, *range*. It returns an integer *n* such that *range* contiguous empty display lists, named *n*, *n*+1, ..., *n*+*range* -1, are created. If *range* is 0, if there is no group of *range* contiguous names available, or if any error is generated, no display lists are generated, and 0 is returned.

ERRORS

GL_INVALID_VALUE is generated if *range* is negative.

GL_INVALID_OPERATION is generated if **glGenLists** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glIsList

SEE ALSO

glCallList, **glCallLists**, **glDeleteLists**, **glNewList**

NAME

glGenTextures - generate texture names

C SPECIFICATION

```
void glGenTextures( GLsizei n,  
                    GLuint *textures )
```

PARAMETERS

n Specifies the number of texture names to be generated.

textures Specifies an array in which the generated texture names are stored.

DESCRIPTION

glGenTextures returns *n* texture names in *textures*. There is no guarantee that the names form a contiguous set of integers; however, it is guaranteed that none of the returned names was in use immediately before the call to **glGenTextures**.

The generated textures have no dimensionality; they assume the dimensionality of the texture target to which they are first bound (see **glBindTexture**).

Texture names returned by a call to **glGenTextures** are not returned by subsequent calls, unless they are first deleted with **glDeleteTextures**.

NOTES

glGenTextures is available only if the GL version is 1.1 or greater.

ERRORS

GL_INVALID_VALUE is generated if *n* is negative.

GL_INVALID_OPERATION is generated if **glGenTextures** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glIsTexture

SEE ALSO

`glBindTexture`, `glCopyTexImage1D`, `glCopyTexImage2D`,
`glDeleteTextures`, `glGet`, `glGetTexParameter`, `glTexImage1D`,
`glTexImage2D`, `glTexParameter`

NAME

glGetBooleanv, glGetDoublev, glGetFloatv, glGetIntegerv -
return the value or values of a selected parameter

C SPECIFICATION

```
void glGetBooleanv( GLenum pname,  
                    GLboolean *params )
```

C SPECIFICATION

```
void glGetDoublev( GLenum pname,  
                   GLdouble *params )
```

C SPECIFICATION

```
void glGetFloatv( GLenum pname,  
                  GLfloat *params )
```

C SPECIFICATION

```
void glGetIntegerv( GLenum pname,  
                    GLint *params )
```

PARAMETERS

pname Specifies the parameter value to be returned. The symbolic constants in the list below are accepted.

params Returns the value or values of the specified parameter.

DESCRIPTION

These four commands return values for simple state variables in GL. *pname* is a symbolic constant indicating the state variable to be returned, and *params* is a pointer to an array of the indicated type in which to place the returned data.

Type conversion is performed if *params* has a different type than the state variable value being requested. If **glGetBooleanv** is called, a floating-point (or integer) value is converted to **GL_FALSE** if and only if it is 0.0 (or 0). Otherwise, it is converted to **GL_TRUE**. If **glGetIntegerv** is called, boolean values are returned as **GL_TRUE** or **GL_FALSE**, and most floating-point values are rounded to the nearest

integer value. Floating-point colors and normals, however, are returned with a linear mapping that maps 1.0 to the most positive representable integer value, and -1.0 to the most negative representable integer value. If **glGetFloatv** or **glGetDoublev** is called, boolean values are returned as **GL_TRUE** or **GL_FALSE**, and integer values are converted to floating-point values.

The following symbolic constants are accepted by *pname*:

GL_ACCUM_ALPHA_BITS	<i>params</i> returns one value, the number of alpha bitplanes in the accumulation buffer.
GL_ACCUM_BLUE_BITS	<i>params</i> returns one value, the number of blue bitplanes in the accumulation buffer.
GL_ACCUM_CLEAR_VALUE	<i>params</i> returns four values: the red, green, blue, and alpha values used to clear the accumulation buffer. Integer values, if requested, are linearly mapped from the internal floating-point representation such that 1.0 returns the most positive representable integer value, and -1.0 returns the most negative representable integer value. The initial value is (0, 0, 0, 0). See glClearAccum .
GL_ACCUM_GREEN_BITS	<i>params</i> returns one value, the number of green bitplanes in the accumulation buffer.
GL_ACCUM_RED_BITS	<i>params</i> returns one value, the number of red bitplanes in the accumulation buffer.
GL_ALPHA_BIAS	<i>params</i> returns one value, the alpha bias factor used during pixel transfers. The initial value is 0. See glPixelTransfer .
GL_ALPHA_BITS	<i>params</i> returns one value, the number of alpha bitplanes in each

color buffer.

GL_ALPHA_SCALE

params returns one value, the alpha scale factor used during pixel transfers. The initial value is 1. See **glPixelTransfer**.

GL_ALPHA_TEST

params returns a single boolean value indicating whether alpha testing of fragments is enabled. The initial value is **GL_FALSE**. See **glAlphaFunc**.

GL_ALPHA_TEST_FUNC

params returns one value, the symbolic name of the alpha test function. The initial value is **GL_ALWAYS**. See **glAlphaFunc**.

GL_ALPHA_TEST_REF

params returns one value, the reference value for the alpha test. The initial value is 0. See **glAlphaFunc**. An integer value, if requested, is linearly mapped from the internal floating-point representation such that 1.0 returns the most positive representable integer value, and -1.0 returns the most negative representable integer value.

GL_ATTRIB_STACK_DEPTH

params returns one value, the depth of the attribute stack. If the stack is empty, 0 is returned. The initial value is 0. See **glPushAttrib**.

GL_AUTO_NORMAL

params returns a single boolean value indicating whether 2D map evaluation automatically generates surface normals. The initial value is **GL_FALSE**. See **glMap2**.

GL_AUX_BUFFERS

params returns one value, the number of auxiliary color buffers. The initial value is 0.

GL_BLEND	<i>params</i> returns a single boolean value indicating whether blending is enabled. The initial value is GL_FALSE . See glBlendFunc .
GL_BLEND_COLOR_EXT	<i>params</i> returns four values, the red, green, blue, and alpha values which are the components of the blend color. See glBlendColorEXT .
GL_BLEND_DST	<i>params</i> returns one value, the symbolic constant identifying the destination blend function. The initial value is GL_ZERO . See glBlendFunc .
GL_BLEND_EQUATION_EXT	<i>params</i> returns one value, a symbolic constant indicating whether the blend equation is GL_FUNC_ADD_EXT , GL_MIN_EXT or GL_MAX_EXT . See glBlendEquationEXT .
GL_BLEND_SRC	<i>params</i> returns one value, the symbolic constant identifying the source blend function. The initial value is GL_ONE . See glBlendFunc .
GL_BLUE_BIAS	<i>params</i> returns one value, the blue bias factor used during pixel transfers. The initial value is 0. See glPixelTransfer .
GL_BLUE_BITS	<i>params</i> returns one value, the number of blue bitplanes in each color buffer.
GL_BLUE_SCALE	<i>params</i> returns one value, the blue scale factor used during pixel transfers. The initial value is 1. See glPixelTransfer .
GL_CLIENT_ATTRIB_STACK_DEPTH	<i>params</i> returns one value indicating the depth of the attribute stack. The initial value is 0. See glPushClientAttrib .

GL_CLIP_PLANE<i>i</i>	<i>params</i> returns a single boolean value indicating whether the specified clipping plane is enabled. The initial value is GL_FALSE . See glClipPlane .
GL_COLOR_ARRAY	<i>params</i> returns a single boolean value indicating whether the color array is enabled. The initial value is GL_FALSE . See glColorPointer .
GL_COLOR_ARRAY_SIZE	<i>params</i> returns one value, the number of components per color in the color array. The initial value is 4. See glColorPointer .
GL_COLOR_ARRAY_STRIDE	<i>params</i> returns one value, the byte offset between consecutive colors in the color array. The initial value is 0. See glColorPointer .
GL_COLOR_ARRAY_TYPE	<i>params</i> returns one value, the data type of each component in the color array. The initial value is GL_FLOAT . See glColorPointer .
GL_COLOR_CLEAR_VALUE	<i>params</i> returns four values: the red, green, blue, and alpha values used to clear the color buffers. Integer values, if requested, are linearly mapped from the internal floating-point representation such that 1.0 returns the most positive representable integer value, and -1.0 returns the most negative representable integer value. The initial value is (0, 0, 0, 0). See glClearColor .
GL_COLOR_LOGIC_OP	<i>params</i> returns a single boolean value indicating whether a fragment's RGBA color values are merged into the framebuffer using a logical operation. The initial value is GL_FALSE . See glLogicOp .

GL_COLOR_MATERIAL	<i>params</i> returns a single boolean value indicating whether one or more material parameters are tracking the current color. The initial value is GL_FALSE . See glColorMaterial .
GL_COLOR_MATERIAL_FACE	<i>params</i> returns one value, a symbolic constant indicating which materials have a parameter that is tracking the current color. The initial value is GL_FRONT_AND_BACK . See glColorMaterial .
GL_COLOR_MATERIAL_PARAMETER	<i>params</i> returns one value, a symbolic constant indicating which material parameters are tracking the current color. The initial value is GL_AMBIENT_AND_DIFFUSE . See glColorMaterial .
GL_COLOR_WRITEMASK	<i>params</i> returns four boolean values: the red, green, blue, and alpha write enables for the color buffers. The initial value is (GL_TRUE , GL_TRUE , GL_TRUE , GL_TRUE). See glColorMask .
GL_CULL_FACE	<i>params</i> returns a single boolean value indicating whether polygon culling is enabled. The initial value is GL_FALSE . See glCullFace .
GL_CULL_FACE_MODE	<i>params</i> returns one value, a symbolic constant indicating which polygon faces are to be culled. The initial value is GL_BACK . See glCullFace .
GL_CURRENT_COLOR	<i>params</i> returns four values: the red, green, blue, and alpha values of the current color. Integer values, if requested, are linearly mapped from the internal floating-

point representation such that 1.0 returns the most positive representable integer value, and -1.0 returns the most negative representable integer value. See **glColor**. The initial value is (1, 1, 1).

GL_CURRENT_INDEX

params returns one value, the current color index. The initial value is 1. See **glIndex**.

GL_CURRENT_NORMAL

params returns three values: the *x*, *y*, and *z* values of the current normal. Integer values, if requested, are linearly mapped from the internal floating-point representation such that 1.0 returns the most positive representable integer value, and -1.0 returns the most negative representable integer value. The initial value is (0, 0, 1). See **glNormal**.

GL_CURRENT_RASTER_COLOR

params returns four values: the red, green, blue, and alpha values of the current raster position. Integer values, if requested, are linearly mapped from the internal floating-point representation such that 1.0 returns the most positive representable integer value, and -1.0 returns the most negative representable integer value. The initial value is (1, 1, 1, 1). See **glRasterPos**.

GL_CURRENT_RASTER_DISTANCE

params returns one value, the distance from the eye to the current raster position. The initial value is 0. See **glRasterPos**.

GL_CURRENT_RASTER_INDEX

params returns one value, the color

index of the current raster position. The initial value is 1. See **glRasterPos**.

GL_CURRENT_RASTER_POSITION

params returns four values: the *x*, *y*, *z*, and *w* components of the current raster position. *x*, *y*, and *z* are in window coordinates, and *w* is in clip coordinates. The initial value is (0, 0, 0, 1). See **glRasterPos**.

GL_CURRENT_RASTER_POSITION_VALID

params returns a single boolean value indicating whether the current raster position is valid. The initial value is **GL_TRUE**. See **glRasterPos**.

GL_CURRENT_RASTER_TEXTURE_COORDS

params returns four values: the *s*, *t*, *r*, and *q* current raster texture coordinates. The initial value is (0, 0, 0, 1). See **glRasterPos** and **glTexCoord**.

GL_CURRENT_TEXTURE_COORDS

params returns four values: the *s*, *t*, *r*, and *q* current texture coordinates. The initial value is (0, 0, 0, 1). See **glTexCoord**.

GL_DEPTH_BIAS

params returns one value, the depth bias factor used during pixel transfers. The initial value is 0. See **glPixelTransfer**.

GL_DEPTH_BITS

params returns one value, the number of bitplanes in the depth buffer.

GL_DEPTH_CLEAR_VALUE

params returns one value, the value that is used to clear the depth buffer. Integer values, if requested, are linearly mapped from

the internal floating-point representation such that 1.0 returns the most positive representable integer value, and -1.0 returns the most negative representable integer value. The initial value is 1. See **glClearDepth**.

GL_DEPTH_FUNC

params returns one value, the symbolic constant that indicates the depth comparison function. The initial value is **GL_LESS**. See **glDepthFunc**.

GL_DEPTH_RANGE

params returns two values: the near and far mapping limits for the depth buffer. Integer values, if requested, are linearly mapped from the internal floating-point representation such that 1.0 returns the most positive representable integer value, and -1.0 returns the most negative representable integer value. The initial value is (0, 1). See **glDepthRange**.

GL_DEPTH_SCALE

params returns one value, the depth scale factor used during pixel transfers. The initial value is 1. See **glPixelTransfer**.

GL_DEPTH_TEST

params returns a single boolean value indicating whether depth testing of fragments is enabled. The initial value is **GL_FALSE**. See **glDepthFunc** and **glDepthRange**.

GL_DEPTH_WRITEMASK

params returns a single boolean value indicating if the depth buffer is enabled for writing. The initial value is **GL_TRUE**. See **glDepthMask**.

GL_DITHER

params returns a single boolean

	value indicating whether dithering of fragment colors and indices is enabled. The initial value is GL_TRUE .
GL_DOUBLEBUFFER	<i>params</i> returns a single boolean value indicating whether double buffering is supported.
GL_DRAW_BUFFER	<i>params</i> returns one value, a symbolic constant indicating which buffers are being drawn to. See glDrawBuffer . The initial value is GL_BACK if there are back buffers, otherwise it is GL_FRONT .
GL_EDGE_FLAG	<i>params</i> returns a single boolean value indicating whether the current edge flag is GL_TRUE or GL_FALSE . The initial value is GL_TRUE . See glEdgeFlag .
GL_EDGE_FLAG_ARRAY	<i>params</i> returns a single boolean value indicating whether the edge flag array is enabled. The initial value is GL_FALSE . See glEdgeFlagPointer .
GL_EDGE_FLAG_ARRAY_STRIDE	<i>params</i> returns one value, the byte offset between consecutive edge flags in the edge flag array. The initial value is 0. See glEdgeFlagPointer .
GL_FOG	<i>params</i> returns a single boolean value indicating whether fogging is enabled. The initial value is GL_FALSE . See glFog .
GL_FOG_COLOR	<i>params</i> returns four values: the red, green, blue, and alpha components of the fog color. Integer values, if requested, are linearly mapped from the internal floating-point representation such

that 1.0 returns the most positive representable integer value, and -1.0 returns the most negative representable integer value. The initial value is (0, 0, 0, 0). See **glFog**.

GL_FOG_DENSITY

params returns one value, the fog density parameter. The initial value is 1. See **glFog**.

GL_FOG_END

params returns one value, the end factor for the linear fog equation. The initial value is 1. See **glFog**.

GL_FOG_HINT

params returns one value, a symbolic constant indicating the mode of the fog hint. The initial value is **GL_DONT_CARE**. See **glHint**.

GL_FOG_INDEX

params returns one value, the fog color index. The initial value is 0. See **glFog**.

GL_FOG_MODE

params returns one value, a symbolic constant indicating which fog equation is selected. The initial value is **GL_EXP**. See **glFog**.

GL_FOG_START

params returns one value, the start factor for the linear fog equation. The initial value is 0. See **glFog**.

GL_FRONT_FACE

params returns one value, a symbolic constant indicating whether clockwise or counterclockwise polygon winding is treated as front-facing. The initial value is **GL_CCW**. See **glFrontFace**.

GL_GREEN_BIAS

params returns one value, the green bias factor used during pixel transfers. The initial value is 0.

GL_GREEN_BITS

params returns one value, the

	number of green bitplanes in each color buffer.
GL_GREEN_SCALE	<i>params</i> returns one value, the green scale factor used during pixel transfers. The initial value is 1. See glPixelTransfer .
GL_INDEX_ARRAY	<i>params</i> returns a single boolean value indicating whether the color index array is enabled. The initial value is GL_FALSE . See glIndexPointer .
GL_INDEX_ARRAY_STRIDE	<i>params</i> returns one value, the byte offset between consecutive color indexes in the color index array. The initial value is 0. See glIndexPointer .
GL_INDEX_ARRAY_TYPE	<i>params</i> returns one value, the data type of indexes in the color index array. The initial value is GL_FLOAT . See glIndexPointer .
GL_INDEX_BITS	<i>params</i> returns one value, the number of bitplanes in each color index buffer.
GL_INDEX_CLEAR_VALUE	<i>params</i> returns one value, the color index used to clear the color index buffers. The initial value is 0. See glClearIndex .
GL_INDEX_LOGIC_OP	<i>params</i> returns a single boolean value indicating whether a fragment's index values are merged into the framebuffer using a logical operation. The initial value is GL_FALSE . See glLogicOp .
GL_INDEX_MODE	<i>params</i> returns a single boolean value indicating whether the GL is in color index mode (GL_TRUE) or RGBA mode (GL_FALSE).

GL_INDEX_OFFSET	<i>params</i> returns one value, the offset added to color and stencil indices during pixel transfers. The initial value is 0. See glPixelTransfer .
GL_INDEX_SHIFT	<i>params</i> returns one value, the amount that color and stencil indices are shifted during pixel transfers. The initial value is 0. See glPixelTransfer .
GL_INDEX_WRITEMASK	<i>params</i> returns one value, a mask indicating which bitplanes of each color index buffer can be written. The initial value is all 1's. See glIndexMask .
GL_LIGHT<i>i</i>	<i>params</i> returns a single boolean value indicating whether the specified light is enabled. The initial value is GL_FALSE . See glLight and glLightModel .
GL_LIGHTING	<i>params</i> returns a single boolean value indicating whether lighting is enabled. The initial value is GL_FALSE . See glLightModel .
GL_LIGHT_MODEL_AMBIENT	<i>params</i> returns four values: the red, green, blue, and alpha components of the ambient intensity of the entire scene. Integer values, if requested, are linearly mapped from the internal floating-point representation such that 1.0 returns the most positive representable integer value, and -1.0 returns the most negative representable integer value. The initial value is (0.2, 0.2, 0.2, 1.0). See glLightModel .
GL_LIGHT_MODEL_LOCAL_VIEWER	<i>params</i> returns a single boolean value indicating whether specular

reflection calculations treat the viewer as being local to the scene. The initial value is **GL_FALSE**. See **glLightModel**.

GL_LIGHT_MODEL_TWO_SIDE *params* returns a single boolean value indicating whether separate materials are used to compute lighting for front- and back-facing polygons. The initial value is **GL_FALSE**. See **glLightModel**.

GL_LINE_SMOOTH *params* returns a single boolean value indicating whether antialiasing of lines is enabled. The initial value is **GL_FALSE**. See **glLineWidth**.

GL_LINE_SMOOTH_HINT *params* returns one value, a symbolic constant indicating the mode of the line antialiasing hint. The initial value is **GL_DONT_CARE**. See **glHint**.

GL_LINE_STIPPLE *params* returns a single boolean value indicating whether stippling of lines is enabled. The initial value is **GL_FALSE**. See **glLineStipple**.

GL_LINE_STIPPLE_PATTERN *params* returns one value, the 16-bit line stipple pattern. The initial value is all 1's. See **glLineStipple**.

GL_LINE_STIPPLE_REPEAT *params* returns one value, the line stipple repeat factor. The initial value is 1. See **glLineStipple**.

GL_LINE_WIDTH *params* returns one value, the line width as specified with **glLineWidth**. The initial value is 1.

GL_LINE_WIDTH_GRANULARITY *params* returns one value, the width

difference between adjacent supported widths for antialiased lines. See **glLineWidth**.

GL_LINE_WIDTH_RANGE

params returns two values: the smallest and largest supported widths for antialiased lines. See **glLineWidth**.

GL_LIST_BASE

params returns one value, the base offset added to all names in arrays presented to **glCallLists**. The initial value is 0. See **glListBase**.

GL_LIST_INDEX

params returns one value, the name of the display list currently under construction. 0 is returned if no display list is currently under construction. The initial value is 0. See **glNewList**.

GL_LIST_MODE

params returns one value, a symbolic constant indicating the construction mode of the display list currently under construction. The initial value is 0. See **glNewList**.

GL_LOGIC_OP_MODE

params returns one value, a symbolic constant indicating the selected logic operation mode. The initial value is **GL_COPY**. See **glLogicOp**.

GL_MAP1_COLOR_4

params returns a single boolean value indicating whether 1D evaluation generates colors. The initial value is **GL_FALSE**. See **glMap1**.

GL_MAP1_GRID_DOMAIN

params returns two values: the endpoints of the 1D map's grid domain. The initial value is (0, 1). See **glMapGrid**.

GL_MAP1_GRID_SEGMENTS

params returns one value, the

number of partitions in the 1D map's grid domain. The initial value is 1. See **glMapGrid**.

GL_MAP1_INDEX

params returns a single boolean value indicating whether 1D evaluation generates color indices. The initial value is **GL_FALSE**. See **glMap1**.

GL_MAP1_NORMAL

params returns a single boolean value indicating whether 1D evaluation generates normals. The initial value is **GL_FALSE**. See **glMap1**.

GL_MAP1_TEXTURE_COORD_1

params returns a single boolean value indicating whether 1D evaluation generates 1D texture coordinates. The initial value is **GL_FALSE**. See **glMap1**.

GL_MAP1_TEXTURE_COORD_2

params returns a single boolean value indicating whether 1D evaluation generates 2D texture coordinates. The initial value is **GL_FALSE**. See **glMap1**.

GL_MAP1_TEXTURE_COORD_3

params returns a single boolean value indicating whether 1D evaluation generates 3D texture coordinates. The initial value is **GL_FALSE**. See **glMap1**.

GL_MAP1_TEXTURE_COORD_4

params returns a single boolean value indicating whether 1D evaluation generates 4D texture coordinates. The initial value is **GL_FALSE**. See **glMap1**.

GL_MAP1_VERTEX_3

params returns a single boolean value indicating whether 1D evaluation generates 3D vertex coordinates. The initial value is **GL_FALSE**. See **glMap1**.

GL_MAP1_VERTEX_4	<i>params</i> returns a single boolean value indicating whether 1D evaluation generates 4D vertex coordinates. The initial value is GL_FALSE . See glMap1 .
GL_MAP2_COLOR_4	<i>params</i> returns a single boolean value indicating whether 2D evaluation generates colors. The initial value is GL_FALSE . See glMap2 .
GL_MAP2_GRID_DOMAIN	<i>params</i> returns four values: the endpoints of the 2D map's i and j grid domains. The initial value is (0,1; 0,1). See glMapGrid .
GL_MAP2_GRID_SEGMENTS	<i>params</i> returns two values: the number of partitions in the 2D map's i and j grid domains. The initial value is (1,1). See glMapGrid .
GL_MAP2_INDEX	<i>params</i> returns a single boolean value indicating whether 2D evaluation generates color indices. The initial value is GL_FALSE . See glMap2 .
GL_MAP2_NORMAL	<i>params</i> returns a single boolean value indicating whether 2D evaluation generates normals. The initial value is GL_FALSE . See glMap2 .
GL_MAP2_TEXTURE_COORD_1	<i>params</i> returns a single boolean value indicating whether 2D evaluation generates 1D texture coordinates. The initial value is GL_FALSE . See glMap2 .
GL_MAP2_TEXTURE_COORD_2	<i>params</i> returns a single boolean value indicating whether 2D evaluation generates 2D texture coordinates. The initial value is GL_FALSE . See glMap2 .

GL_MAP2_TEXTURE_COORD_3	<i>params</i> returns a single boolean value indicating whether 2D evaluation generates 3D texture coordinates. The initial value is GL_FALSE . See glMap2 .
GL_MAP2_TEXTURE_COORD_4	<i>params</i> returns a single boolean value indicating whether 2D evaluation generates 4D texture coordinates. The initial value is GL_FALSE . See glMap2 .
GL_MAP2_VERTEX_3	<i>params</i> returns a single boolean value indicating whether 2D evaluation generates 3D vertex coordinates. The initial value is GL_FALSE . See glMap2 .
GL_MAP2_VERTEX_4	<i>params</i> returns a single boolean value indicating whether 2D evaluation generates 4D vertex coordinates. The initial value is GL_FALSE . See glMap2 .
GL_MAP_COLOR	<i>params</i> returns a single boolean value indicating if colors and color indices are to be replaced by table lookup during pixel transfers. The initial value is GL_FALSE . See glPixelTransfer .
GL_MAP_STENCIL	<i>params</i> returns a single boolean value indicating if stencil indices are to be replaced by table lookup during pixel transfers. The initial value is GL_FALSE . See glPixelTransfer .
GL_MATRIX_MODE	<i>params</i> returns one value, a symbolic constant indicating which matrix stack is currently the target of all matrix operations. The initial value is GL_MODELVIEW . See glMatrixMode .

GL_MAX_CLIENT_ATTRIB_STACK_DEPTH

params returns one value indicating the maximum supported depth of the client attribute stack. See **glPushClientAttrib**.

GL_MAX_ATTRIB_STACK_DEPTH

params returns one value, the maximum supported depth of the attribute stack. The value must be at least 16. See **glPushAttrib**.

GL_MAX_CLIP_PLANES

params returns one value, the maximum number of application-defined clipping planes. The value must be at least 6. See **glClipPlane**.

GL_MAX_EVAL_ORDER

params returns one value, the maximum equation order supported by 1D and 2D evaluators. The value must be at least 8. See **glMap1** and **glMap2**.

GL_MAX_LIGHTS

params returns one value, the maximum number of lights. The value must be at least 8. See **glLight**.

GL_MAX_LIST_NESTING

params returns one value, the maximum recursion depth allowed during display-list traversal. The value must be at least 64. See **glCallList**.

GL_MAX_MODELVIEW_STACK_DEPTH

params returns one value, the maximum supported depth of the modelview matrix stack. The value must be at least 32. See **glPushMatrix**.

GL_MAX_NAME_STACK_DEPTH

params returns one value, the maximum supported depth of the selection name stack. The value must be at least 64. See **glPushName**.

GL_MAX_PIXEL_MAP_TABLE	<i>params</i> returns one value, the maximum supported size of a glPixelMap lookup table. The value must be at least 32. See glPixelMap .
GL_MAX_PROJECTION_STACK_DEPTH	<i>params</i> returns one value, the maximum supported depth of the projection matrix stack. The value must be at least 2. See glPushMatrix .
GL_MAX_TEXTURE_SIZE	<i>params</i> returns one value. The value gives a rough estimate of the largest texture that the GL can handle. If the GL version is 1.1 or greater, use GL_PROXY_TEXTURE_1D or GL_PROXY_TEXTURE_2D to determine if a texture is too large. See glTexImage1D and glTexImage2D .
GL_MAX_TEXTURE_STACK_DEPTH	<i>params</i> returns one value, the maximum supported depth of the texture matrix stack. The value must be at least 2. See glPushMatrix .
GL_MAX_VIEWPORT_DIMS	<i>params</i> returns two values: the maximum supported width and height of the viewport. These must be at least as large as the visible dimensions of the display being rendered to. See glViewport .
GL_MODELVIEW_MATRIX	<i>params</i> returns sixteen values: the modelview matrix on the top of the modelview matrix stack. Initially this matrix is the identity matrix. See glPushMatrix .
GL_MODELVIEW_STACK_DEPTH	<i>params</i> returns one value, the number of matrices on the modelview matrix stack. The initial value is

1. See **glPushMatrix**.

GL_NAME_STACK_DEPTH

params returns one value, the number of names on the selection name stack. The initial value is 0. See **glPushName**.

GL_NORMAL_ARRAY

params returns a single boolean value, indicating whether the normal array is enabled. The initial value is **GL_FALSE**. See **glNormalPointer**.

GL_NORMAL_ARRAY_STRIDE

params returns one value, the byte offset between consecutive normals in the normal array. The initial value is 0. See **glNormalPointer**.

GL_NORMAL_ARRAY_TYPE

params returns one value, the data type of each coordinate in the normal array. The initial value is **GL_FLOAT**. See **glNormalPointer**.

GL_NORMALIZE

params returns a single boolean value indicating whether normals are automatically scaled to unit length after they have been transformed to eye coordinates. The initial value is **GL_FALSE**. See **glNormal**.

GL_PACK_ALIGNMENT

params returns one value, the byte alignment used for writing pixel data to memory. The initial value is 4. See **glPixelStore**.

GL_PACK_LSB_FIRST

params returns a single boolean value indicating whether single-bit pixels being written to memory are written first to the least significant bit of each unsigned byte. The initial value is **GL_FALSE**. See **glPixelStore**.

GL_PACK_ROW_LENGTH

params returns one value, the row length used for writing pixel data

to memory. The initial value is 0. See **glPixelStore**.

GL_PACK_SKIP_PIXELS

params returns one value, the number of pixel locations skipped before the first pixel is written into memory. The initial value is 0. See **glPixelStore**.

GL_PACK_SKIP_ROWS

params returns one value, the number of rows of pixel locations skipped before the first pixel is written into memory. The initial value is 0. See **glPixelStore**.

GL_PACK_SWAP_BYTES

params returns a single boolean value indicating whether the bytes of two-byte and four-byte pixel indices and components are swapped before being written to memory. The initial value is **GL_FALSE**. See **glPixelStore**.

GL_PERSPECTIVE_CORRECTION_HINT

params returns one value, a symbolic constant indicating the mode of the perspective correction hint. The initial value is **GL_DONT_CARE**. See **glHint**.

GL_PIXEL_MAP_A_TO_A_SIZE

params returns one value, the size of the alpha-to-alpha pixel translation table. The initial value is 1. See **glPixelMap**.

GL_PIXEL_MAP_B_TO_B_SIZE

params returns one value, the size of the blue-to-blue pixel translation table. The initial value is 1. See **glPixelMap**.

GL_PIXEL_MAP_G_TO_G_SIZE

params returns one value, the size of the green-to-green pixel translation table. The initial value is 1. See **glPixelMap**.

GL_PIXEL_MAP_I_TO_A_SIZE

params returns one value, the size

of the index-to-alpha pixel translation table. The initial value is 1. See **glPixelMap**.

GL_PIXEL_MAP_I_TO_B_SIZE *params* returns one value, the size of the index-to-blue pixel translation table. The initial value is 1. See **glPixelMap**.

GL_PIXEL_MAP_I_TO_G_SIZE *params* returns one value, the size of the index-to-green pixel translation table. The initial value is 1. See **glPixelMap**.

GL_PIXEL_MAP_I_TO_I_SIZE *params* returns one value, the size of the index-to-index pixel translation table. The initial value is 1. See **glPixelMap**.

GL_PIXEL_MAP_I_TO_R_SIZE *params* returns one value, the size of the index-to-red pixel translation table. The initial value is 1. See **glPixelMap**.

GL_PIXEL_MAP_R_TO_R_SIZE *params* returns one value, the size of the red-to-red pixel translation table. The initial value is 1. See **glPixelMap**.

GL_PIXEL_MAP_S_TO_S_SIZE *params* returns one value, the size of the stencil-to-stencil pixel translation table. The initial value is 1. See **glPixelMap**.

GL_POINT_SIZE *params* returns one value, the point size as specified by **glPointSize**. The initial value is 1.

GL_POINT_SIZE_GRANULARITY *params* returns one value, the size difference between adjacent supported sizes for antialiased points. See **glPointSize**.

GL_POINT_SIZE_RANGE *params* returns two values: the smallest and largest supported

sizes for antialiased points. The smallest size must be at most 1, and the largest size must be at least 1. See **glPointSize**.

GL_POINT_SMOOTH

params returns a single boolean value indicating whether antialiasing of points is enabled. The initial value is **GL_FALSE**. See **glPointSize**.

GL_POINT_SMOOTH_HINT

params returns one value, a symbolic constant indicating the mode of the point antialiasing hint. The initial value is **GL_DONT_CARE**. See **glHint**.

GL_POLYGON_MODE

params returns two values: symbolic constants indicating whether front-facing and back-facing polygons are rasterized as points, lines, or filled polygons. The initial value is **GL_FILL**. See **glPolygonMode**.

GL_POLYGON_OFFSET_FACTOR

params returns one value, the scaling factor used to determine the variable offset that is added to the depth value of each fragment generated when a polygon is rasterized. The initial value is 0. See **glPolygonOffset**.

GL_POLYGON_OFFSET_UNITS

params returns one value. This value is multiplied by an implementation-specific value and then added to the depth value of each fragment generated when a polygon is rasterized. The initial value is 0. See **glPolygonOffset**.

GL_POLYGON_OFFSET_FILL

params returns a single boolean value indicating whether polygon offset is enabled for polygons in fill mode. The initial value is **GL_FALSE**. See **glPolygonOffset**.

GL_POLYGON_OFFSET_LINE	<i>params</i> returns a single boolean value indicating whether polygon offset is enabled for polygons in line mode. The initial value is GL_FALSE . See glPolygonOffset .
GL_POLYGON_OFFSET_POINT	<i>params</i> returns a single boolean value indicating whether polygon offset is enabled for polygons in point mode. The initial value is GL_FALSE . See glPolygonOffset .
GL_POLYGON_SMOOTH	<i>params</i> returns a single boolean value indicating whether antialiasing of polygons is enabled. The initial value is GL_FALSE . See glPolygonMode .
GL_POLYGON_SMOOTH_HINT	<i>params</i> returns one value, a symbolic constant indicating the mode of the polygon antialiasing hint. The initial value is GL_DONT_CARE . See glHint .
GL_POLYGON_STIPPLE	<i>params</i> returns a single boolean value indicating whether polygon stippling is enabled. The initial value is GL_FALSE . See glPolygonStipple .
GL_PROJECTION_MATRIX	<i>params</i> returns sixteen values: the projection matrix on the top of the projection matrix stack. Initially this matrix is the identity matrix. See glPushMatrix .
GL_PROJECTION_STACK_DEPTH	<i>params</i> returns one value, the number of matrices on the projection matrix stack. The initial value is 1. See glPushMatrix .
GL_READ_BUFFER	<i>params</i> returns one value, a symbolic constant indicating which

	color buffer is selected for reading. The initial value is GL_BACK if there is a back buffer, otherwise it is GL_FRONT . See glReadPixels and glAccum .
GL_RED_BIAS	<i>params</i> returns one value, the red bias factor used during pixel transfers. The initial value is 0.
GL_RED_BITS	<i>params</i> returns one value, the number of red bitplanes in each color buffer.
GL_RED_SCALE	<i>params</i> returns one value, the red scale factor used during pixel transfers. The initial value is 1. See glPixelTransfer .
GL_RENDER_MODE	<i>params</i> returns one value, a symbolic constant indicating whether the GL is in render, select, or feedback mode. The initial value is GL_RENDER . See glRenderMode .
GL_RGBA_MODE	<i>params</i> returns a single boolean value indicating whether the GL is in RGBA mode (true) or color index mode (false). See glColor .
GL_SCISSOR_BOX	<i>params</i> returns four values: the x and y window coordinates of the scissor box, followed by its width and height. Initially the x and y window coordinates are both 0 and the width and height are set to the size of the window. See glScissor .
GL_SCISSOR_TEST	<i>params</i> returns a single boolean value indicating whether scissoring is enabled. The initial value is GL_FALSE . See glScissor .
GL_SHADE_MODEL	<i>params</i> returns one value, a symbolic constant indicating

	whether the shading mode is flat or smooth. The initial value is GL_SMOOTH . See glShadeModel .
GL_STENCIL_BITS	<i>params</i> returns one value, the number of bitplanes in the stencil buffer.
GL_STENCIL_CLEAR_VALUE	<i>params</i> returns one value, the index to which the stencil bitplanes are cleared. The initial value is 0. See glClearStencil .
GL_STENCIL_FAIL	<i>params</i> returns one value, a symbolic constant indicating what action is taken when the stencil test fails. The initial value is GL_KEEP . See glStencilOp .
GL_STENCIL_FUNC	<i>params</i> returns one value, a symbolic constant indicating what function is used to compare the stencil reference value with the stencil buffer value. The initial value is GL_ALWAYS . See glStencilFunc .
GL_STENCIL_PASS_DEPTH_FAIL	<i>params</i> returns one value, a symbolic constant indicating what action is taken when the stencil test passes, but the depth test fails. The initial value is GL_KEEP . See glStencilOp .
GL_STENCIL_PASS_DEPTH_PASS	<i>params</i> returns one value, a symbolic constant indicating what action is taken when the stencil test passes and the depth test passes. The initial value is GL_KEEP . See glStencilOp .
GL_STENCIL_REF	<i>params</i> returns one value, the reference value that is compared with the contents of the stencil

	buffer. The initial value is 0. See glStencilFunc .
GL_STENCIL_TEST	<i>params</i> returns a single boolean value indicating whether stencil testing of fragments is enabled. The initial value is GL_FALSE . See glStencilFunc and glStencilOp .
GL_STENCIL_VALUE_MASK	<i>params</i> returns one value, the mask that is used to mask both the stencil reference value and the stencil buffer value before they are compared. The initial value is all 1's. See glStencilFunc .
GL_STENCIL_WRITEMASK	<i>params</i> returns one value, the mask that controls writing of the stencil bitplanes. The initial value is all 1's. See glStencilMask .
GL_STEREO	<i>params</i> returns a single boolean value indicating whether stereo buffers (left and right) are supported.
GL_SUBPIXEL_BITS	<i>params</i> returns one value, an estimate of the number of bits of subpixel resolution that are used to position rasterized geometry in window coordinates. The initial value is 4.
GL_TEXTURE_1D	<i>params</i> returns a single boolean value indicating whether 1D texture mapping is enabled. The initial value is GL_FALSE . See glTexImage1D .
GL_TEXTURE_1D_BINDING	<i>params</i> returns a single value, the name of the texture currently bound to the target GL_TEXTURE_1D . The initial value is 0. See glBindTexture .

GL_TEXTURE_2D	<i>params</i> returns a single boolean value indicating whether 2D texture mapping is enabled. The initial value is GL_FALSE . See glTexImage2D .
GL_TEXTURE_2D_BINDING	<i>params</i> returns a single value, the name of the texture currently bound to the target GL_TEXTURE_2D . The initial value is 0. See glBindTexture .
GL_TEXTURE_COORD_ARRAY	<i>params</i> returns a single boolean value indicating whether the texture coordinate array is enabled. The initial value is GL_FALSE . See glTexCoordPointer .
GL_TEXTURE_COORD_ARRAY_SIZE	<i>params</i> returns one value, the number of coordinates per element in the texture coordinate array. The initial value is 4. See glTexCoordPointer .
GL_TEXTURE_COORD_ARRAY_STRIDE	<i>params</i> returns one value, the byte offset between consecutive elements in the texture coordinate array. The initial value is 0. See glTexCoordPointer .
GL_TEXTURE_COORD_ARRAY_TYPE	<i>params</i> returns one value, the data type of the coordinates in the texture coordinate array. The initial value is GL_FLOAT . See glTexCoordPointer .
GL_TEXTURE_GEN_Q	<i>params</i> returns a single boolean value indicating whether automatic generation of the <i>q</i> texture coordinate is enabled. The initial value is GL_FALSE . See glTexGen .
GL_TEXTURE_GEN_R	<i>params</i> returns a single boolean

	value indicating whether automatic generation of the <i>r</i> texture coordinate is enabled. The initial value is GL_FALSE . See glTexGen .
GL_TEXTURE_GEN_S	<i>params</i> returns a single boolean value indicating whether automatic generation of the <i>S</i> texture coordinate is enabled. The initial value is GL_FALSE . See glTexGen .
GL_TEXTURE_GEN_T	<i>params</i> returns a single boolean value indicating whether automatic generation of the <i>T</i> texture coordinate is enabled. The initial value is GL_FALSE . See glTexGen .
GL_TEXTURE_MATRIX	<i>params</i> returns sixteen values: the texture matrix on the top of the texture matrix stack. Initially this matrix is the identity matrix. See glPushMatrix .
GL_TEXTURE_STACK_DEPTH	<i>params</i> returns one value, the number of matrices on the texture matrix stack. The initial value is 1. See glPushMatrix .
GL_UNPACK_ALIGNMENT	<i>params</i> returns one value, the byte alignment used for reading pixel data from memory. The initial value is 4. See glPixelStore .
GL_UNPACK_LSB_FIRST	<i>params</i> returns a single boolean value indicating whether single-bit pixels being read from memory are read first from the least significant bit of each unsigned byte. The initial value is GL_FALSE . See glPixelStore .
GL_UNPACK_ROW_LENGTH	<i>params</i> returns one value, the row length used for reading pixel data from memory. The initial value is 0. See glPixelStore .

GL_UNPACK_SKIP_PIXELS	<i>params</i> returns one value, the number of pixel locations skipped before the first pixel is read from memory. The initial value is 0. See glPixelStore .
GL_UNPACK_SKIP_ROWS	<i>params</i> returns one value, the number of rows of pixel locations skipped before the first pixel is read from memory. The initial value is 0. See glPixelStore .
GL_UNPACK_SWAP_BYTES	<i>params</i> returns a single boolean value indicating whether the bytes of two-byte and four-byte pixel indices and components are swapped after being read from memory. The initial value is GL_FALSE . See glPixelStore .
GL_VERTEX_ARRAY	<i>params</i> returns a single boolean value indicating whether the vertex array is enabled. The initial value is GL_FALSE . See glVertexPointer .
GL_VERTEX_ARRAY_SIZE	<i>params</i> returns one value, the number of coordinates per vertex in the vertex array. The initial value is 4. See glVertexPointer .
GL_VERTEX_ARRAY_STRIDE	<i>params</i> returns one value, the byte offset between consecutive vertexes in the vertex array. The initial value is 0. See glVertexPointer .
GL_VERTEX_ARRAY_TYPE	<i>params</i> returns one value, the data type of each coordinate in the vertex array. The initial value is GL_FLOAT . See glVertexPointer .
GL_VIEWPORT	<i>params</i> returns four values: the x and y window coordinates of the viewport, followed by its width and height. Initially the x and y window coordinates are both set to 0, and the width and height are set

to the width and height of the window into which the GL will do its rendering. See **glViewport**.

GL_ZOOM_X *params* returns one value, the x pixel zoom factor. The initial value is 1. See **glPixelZoom**.

GL_ZOOM_Y *params* returns one value, the y pixel zoom factor. The initial value is 1. See **glPixelZoom**.

Many of the boolean parameters can also be queried more easily using **glIsEnabled**.

NOTES

GL_COLOR_LOGIC_OP, **GL_COLOR_ARRAY**, **GL_COLOR_ARRAY_SIZE**, **GL_COLOR_ARRAY_STRIDE**, **GL_COLOR_ARRAY_TYPE**, **GL_EDGE_FLAG_ARRAY**, **GL_EDGE_FLAG_ARRAY_STRIDE**, **GL_INDEX_ARRAY**, **GL_INDEX_ARRAY_STRIDE**, **GL_INDEX_ARRAY_TYPE**, **GL_INDEX_LOGIC_OP**, **GL_NORMAL_ARRAY**, **GL_NORMAL_ARRAY_STRIDE**, **GL_NORMAL_ARRAY_TYPE**, **GL_POLYGON_OFFSET_UNITS**, **GL_POLYGON_OFFSET_FACTOR**, **GL_POLYGON_OFFSET_FILL**, **GL_POLYGON_OFFSET_LINE**, **GL_POLYGON_OFFSET_POINT**, **GL_TEXTURE_COORD_ARRAY**, **GL_TEXTURE_COORD_ARRAY_SIZE**, **GL_TEXTURE_COORD_ARRAY_STRIDE**, **GL_TEXTURE_COORD_ARRAY_TYPE**, **GL_VERTEX_ARRAY**, **GL_VERTEX_ARRAY_SIZE**, **GL_VERTEX_ARRAY_STRIDE**, and **GL_VERTEX_ARRAY_TYPE** are available only if the GL version is 1.1 or greater.

ERRORS

GL_INVALID_ENUM is generated if *pname* is not an accepted value.

GL_INVALID_OPERATION is generated if **glGet** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

SEE ALSO

glGetClipPlane, **glGetError**, **glGetLight**, **glGetMap**, **glGetMaterial**, **glGetPixelMap**, **glGetPointerv**, **glGetPolygonStipple**, **glGetString**, **glGetTexEnv**, **glGetTexGen**, **glGetTexImage**, **glGetTexLevelParameter**, **glGetTexParameter**, **glIsEnabled**

NAME

glGetClipPlane - return the coefficients of the specified clipping plane

C SPECIFICATION

```
void glGetClipPlane( GLenum plane,  
                    GLdouble *equation )
```

PARAMETERS

plane Specifies a clipping plane. The number of clipping planes depends on the implementation, but at least six clipping planes are supported. They are identified by symbolic names of the form **GL_CLIP_PLANEi** where $0 < i < \text{GL_MAX_CLIP_PLANES}$.

equation Returns four double-precision values that are the coefficients of the plane equation of *plane* in eye coordinates. The initial value is (0, 0, 0, 0).

DESCRIPTION

glGetClipPlane returns in *equation* the four coefficients of the plane equation for *plane*.

NOTES

It is always the case that **GL_CLIP_PLANEi** = **GL_CLIP_PLANE0** + i.

If an error is generated, no change is made to the contents of *equation*.

ERRORS

GL_INVALID_ENUM is generated if *plane* is not an accepted value.

GL_INVALID_OPERATION is generated if **glGetClipPlane** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

SEE ALSO

glClipPlane

NAME

glGetError - return error information

C SPECIFICATION

GLenum **glGetError**(void)

DESCRIPTION

glGetError returns the value of the error flag. Each detectable error is assigned a numeric code and symbolic name. When an error occurs, the error flag is set to the appropriate error code value. No other errors are recorded until **glGetError** is called, the error code is returned, and the flag is reset to **GL_NO_ERROR**. If a call to **glGetError** returns **GL_NO_ERROR**, there has been no detectable error since the last call to **glGetError**, or since the GL was initialized.

To allow for distributed implementations, there may be several error flags. If any single error flag has recorded an error, the value of that flag is returned and that flag is reset to **GL_NO_ERROR** when **glGetError** is called. If more than one flag has recorded an error, **glGetError** returns and clears an arbitrary error flag value. Thus, **glGetError** should always be called in a loop, until it returns **GL_NO_ERROR**, if all error flags are to be reset.

Initially, all error flags are set to **GL_NO_ERROR**.

The following errors are currently defined:

GL_NO_ERROR	No error has been recorded. The value of this symbolic constant is guaranteed to be 0.
GL_INVALID_ENUM	An unacceptable value is specified for an enumerated argument. The offending command is ignored, and has no other side effect than to set the error flag.
GL_INVALID_VALUE	A numeric argument is out of

range. The offending command is ignored, and has no other side effect than to set the error flag.

GL_INVALID_OPERATION

The specified operation is not allowed in the current state. The offending command is ignored, and has no other side effect than to set the error flag.

GL_STACK_OVERFLOW

This command would cause a stack overflow. The offending command is ignored, and has no other side effect than to set the error flag.

GL_STACK_UNDERFLOW

This command would cause a stack underflow. The offending command is ignored, and has no other side effect than to set the error flag.

GL_OUT_OF_MEMORY

There is not enough memory left to execute the command. The state of the GL is undefined, except for the state of the error flags, after this error is recorded.

When an error flag is set, results of a GL operation are undefined only if **GL_OUT_OF_MEMORY** has occurred. In all other cases, the command generating the error is ignored and has no effect on the GL state or frame buffer contents. If the generating command returns a value, it returns 0. If **glGetError** itself generates an error, it returns 0.

ERRORS

GL_INVALID_OPERATION is generated if **glGetError** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**. In this case **glGetError** returns 0.

NAME

glGetLightfv, glGetLightiv - return light source parameter values

C SPECIFICATION

```
void glGetLightfv( GLenum light,
                  GLenum pname,
                  GLfloat *params )
void glGetLightiv( GLenum light,
                  GLenum pname,
                  GLint *params )
```

PARAMETERS

light Specifies a light source. The number of possible lights depends on the implementation, but at least eight lights are supported. They are identified by symbolic names of the form **GL_LIGHTi** where $0 < i < \text{GL_MAX_LIGHTS}$.

pname Specifies a light source parameter for *light*. Accepted symbolic names are **GL_AMBIENT**, **GL_DIFFUSE**, **GL_SPECULAR**, **GL_POSITION**, **GL_SPOT_DIRECTION**, **GL_SPOT_EXPONENT**, **GL_SPOT_CUTOFF**, **GL_CONSTANT_ATTENUATION**, **GL_LINEAR_ATTENUATION**, and **GL_QUADRATIC_ATTENUATION**.

params Returns the requested data.

DESCRIPTION

glGetLight returns in *params* the value or values of a light source parameter. *light* names the light and is a symbolic name of the form **GL_LIGHTi** for $0 < i < \text{GL_MAX_LIGHTS}$, where **GL_MAX_LIGHTS** is an implementation dependent constant that is greater than or equal to eight. *pname* specifies one of ten light source parameters, again by symbolic name.

The following parameters are defined:

GL_AMBIENT	<i>params</i> returns four integer or floating-point values representing the ambient intensity of the light source. Integer values, when requested, are linearly mapped from the internal
-------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

floating-point representation such that 1.0 maps to the most positive representable integer value, and -1.0 maps to the most negative representable integer value. If the internal value is outside the range $[-1, 1]$, the corresponding integer return value is undefined. The initial value is (0, 0, 0, 1).

GL_DIFFUSE

params returns four integer or floating-point values representing the diffuse intensity of the light source. Integer values, when requested, are linearly mapped from the internal floating-point representation such that 1.0 maps to the most positive representable integer value, and -1.0 maps to the most negative representable integer value. If the internal value is outside the range $[-1, 1]$, the corresponding integer return value is undefined. The initial value for **GL_LIGHT0** is (1, 1, 1, 1); for other lights, the initial value is (0, 0, 0, 0).

GL_SPECULAR

params returns four integer or floating-point values representing the specular intensity of the light source. Integer values, when requested, are linearly mapped from the internal floating-point representation such that 1.0 maps to the most positive representable integer value, and -1.0 maps to the most negative representable integer value. If the internal value is outside the range $[-1, 1]$, the corresponding integer return value is undefined. The initial value for **GL_LIGHT0** is (1, 1, 1, 1); for other lights, the initial value is (0, 0, 0, 0).

GL_POSITION

params returns four integer or floating-point values representing the

position of the light source. Integer values, when requested, are computed by rounding the internal floating-point values to the nearest integer value. The returned values are those maintained in eye coordinates. They will not be equal to the values specified using **glLight**, unless the modelview matrix was identity at the time **glLight** was called. The initial value is (0, 0, 1, 0).

GL_SPOT_DIRECTION

params returns three integer or floating-point values representing the direction of the light source. Integer values, when requested, are computed by rounding the internal floating-point values to the nearest integer value. The returned values are those maintained in eye coordinates. They will not be equal to the values specified using **glLight**, unless the modelview matrix was identity at the time **glLight** was called. Although spot direction is normalized before being used in the lighting equation, the returned values are the transformed versions of the specified values prior to normalization. The initial value is (0, 0, -1).

GL_SPOT_EXPONENT

params returns a single integer or floating-point value representing the spot exponent of the light. An integer value, when requested, is computed by rounding the internal floating-point representation to the nearest integer. The initial value is 0.

GL_SPOT_CUTOFF

params returns a single integer or floating-point value representing the spot cutoff angle of the light. An integer value, when requested, is computed by rounding the internal floating-point representation to the nearest integer. The initial value is 180.

GL_CONSTANT_ATTENUATION

params returns a single integer or floating-point value representing the constant (not distance-related) attenuation of the light. An integer value, when requested, is computed by rounding the internal floating-point representation to the nearest integer. The initial value is 1.

GL_LINEAR_ATTENUATION

params returns a single integer or floating-point value representing the linear attenuation of the light. An integer value, when requested, is computed by rounding the internal floating-point representation to the nearest integer. The initial value is 0.

GL_QUADRATIC_ATTENUATION

params returns a single integer or floating-point value representing the quadratic attenuation of the light. An integer value, when requested, is computed by rounding the internal floating-point representation to the nearest integer. The initial value is 0.

NOTES

It is always the case that **GL_LIGHT i** = **GL_LIGHT0** + i .

If an error is generated, no change is made to the contents of *params*.

ERRORS

GL_INVALID_ENUM is generated if *light* or *pname* is not an accepted value.

GL_INVALID_OPERATION is generated if **glGetLight** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

SEE ALSO

glLight

NAME

glGetMapdv, **glGetMapfv**, **glGetMapiv** - return evaluator parameters

C SPECIFICATION

```
void glGetMapdv( GLenum target,
                 GLenum query,
                 GLdouble *v )
void glGetMapfv( GLenum target,
                 GLenum query,
                 GLfloat *v )
void glGetMapiv( GLenum target,
                 GLenum query,
                 GLint *v )
```

PARAMETERS

target Specifies the symbolic name of a map. Accepted values are **GL_MAP1_COLOR_4**, **GL_MAP1_INDEX**, **GL_MAP1_NORMAL**, **GL_MAP1_TEXTURE_COORD_1**, **GL_MAP1_TEXTURE_COORD_2**, **GL_MAP1_TEXTURE_COORD_3**, **GL_MAP1_TEXTURE_COORD_4**, **GL_MAP1_VERTEX_3**, **GL_MAP1_VERTEX_4**, **GL_MAP2_COLOR_4**, **GL_MAP2_INDEX**, **GL_MAP2_NORMAL**, **GL_MAP2_TEXTURE_COORD_1**, **GL_MAP2_TEXTURE_COORD_2**, **GL_MAP2_TEXTURE_COORD_3**, **GL_MAP2_TEXTURE_COORD_4**, **GL_MAP2_VERTEX_3**, and **GL_MAP2_VERTEX_4**.

query Specifies which parameter to return. Symbolic names **GL_COEFF**, **GL_ORDER**, and **GL_DOMAIN** are accepted.

v Returns the requested data.

DESCRIPTION

glMap1 and **glMap2** define evaluators. **glGetMap** returns evaluator parameters. *target* chooses a map, *query* selects a specific parameter, and *v* points to storage where the values will be returned.

The acceptable values for the *target* parameter are described in the **glMap1** and **glMap2** reference pages.

query can assume the following values:

GL_COEFF	<code>v</code> returns the control points for the evaluator function. One-dimensional evaluators return order control points, and two-dimensional evaluators return <code>uorder</code> <code>xvorder</code> control points. Each control point consists of one, two, three, or four integer, single-precision floating-point, or double-precision floating-point values, depending on the type of the evaluator. The GL returns two-dimensional control points in row-major order, incrementing the <code>uorder</code> index quickly and the <code>vorder</code> index after each row. Integer values, when requested, are computed by rounding the internal floating-point values to the nearest integer values.
GL_ORDER	<code>v</code> returns the order of the evaluator function. One-dimensional evaluators return a single value, order. The initial value is 1. Two-dimensional evaluators return two values, <code>uorder</code> and <code>vorder</code> . The initial value is 1,1.
GL_DOMAIN	<code>v</code> returns the linear <code>u</code> and <code>v</code> mapping parameters. One-dimensional evaluators return two values, <code>u1</code> and <code>u2</code> , as specified by glMap1 . Two-dimensional evaluators return four values (<code>u1</code> , <code>u2</code> , <code>v1</code> , and <code>v2</code>) as specified by glMap2 . Integer values, when requested, are computed by rounding the internal floating-point values to the nearest integer values.

NOTES

If an error is generated, no change is made to the contents of `v`.

ERRORS

GL_INVALID_ENUM is generated if either *target* or *query* is not an accepted value.

GL_INVALID_OPERATION is generated if **glGetMap** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

SEE ALSO

`glEvalCoord, glMap1, glMap2`

NAME

glGetMaterialfv, **glGetMaterialiv** - return material parameters

C SPECIFICATION

```
void glGetMaterialfv( GLenum face,  
                     GLenum pname,  
                     GLfloat *params )  
  
void glGetMaterialiv( GLenum face,  
                     GLenum pname,  
                     GLint *params )
```

PARAMETERS

face Specifies which of the two materials is being queried. **GL_FRONT** or **GL_BACK** are accepted, representing the front and back materials, respectively.

pname Specifies the material parameter to return. **GL_AMBIENT**, **GL_DIFFUSE**, **GL_SPECULAR**, **GL_EMISSION**, **GL_SHININESS**, and **GL_COLOR_INDEXES** are accepted.

params Returns the requested data.

DESCRIPTION

glGetMaterial returns in *params* the value or values of parameter *pname* of material *face*. Six parameters are defined:

GL_AMBIENT *params* returns four integer or floating-point values representing the ambient reflectance of the material. Integer values, when requested, are linearly mapped from the internal floating-point representation such that 1.0 maps to the most positive representable integer value, and -1.0 maps to the most negative representable integer value. If the internal value is outside the range [-1, 1], the corresponding integer return value is undefined. The initial value is (0.2, 0.2, 0.2, 1.0)

GL_DIFFUSE

params returns four integer or floating-point values representing the diffuse reflectance of the material. Integer values, when requested, are linearly mapped from the internal floating-point representation such that 1.0 maps to the most positive representable integer value, and -1.0 maps to the most negative representable integer value. If the internal value is outside the range $[-1, 1]$, the corresponding integer return value is undefined. The initial value is (0.8, 0.8, 0.8, 1.0).

GL_SPECULAR

params returns four integer or floating-point values representing the specular reflectance of the material. Integer values, when requested, are linearly mapped from the internal floating-point representation such that 1.0 maps to the most positive representable integer value, and -1.0 maps to the most negative representable integer value. If the internal value is outside the range $[-1, 1]$, the corresponding integer return value is undefined. The initial value is (0, 0, 0, 1).

GL_EMISSION

params returns four integer or floating-point values representing the emitted light intensity of the material. Integer values, when requested, are linearly mapped from the internal floating-point representation such that 1.0 maps to the most positive representable integer value, and -1.0 maps to the most negative representable integer value. If the internal value is outside the range $[-1, 1.0]$, the corresponding integer return value is undefined. The initial value is (0, 0, 0, 1).

GL_SHININESS

params returns one integer or floating-point value representing the specular exponent of the material. Integer values, when requested, are computed by rounding the internal floating-point value to the nearest integer value. The initial value is 0.

GL_COLOR_INDEXES

params returns three integer or floating-point values representing the ambient, diffuse, and specular indices of the material. These indices are used only for color index lighting. (All the other parameters are used only for RGBA lighting.) Integer values, when requested, are computed by rounding the internal floating-point values to the nearest integer values.

NOTES

If an error is generated, no change is made to the contents of *params*.

ERRORS

GL_INVALID_ENUM is generated if *face* or *pname* is not an accepted value.

GL_INVALID_OPERATION is generated if **glGetMaterial** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

SEE ALSO

glMaterial

NAME

glGetPixelMapfv, **glGetPixelMapuiv**, **glGetPixelMapusv** - return the specified pixel map

C SPECIFICATION

```
void glGetPixelMapfv( GLenum map,  
                     GLfloat *values )  
void glGetPixelMapuiv( GLenum map,  
                      GLuint *values )  
void glGetPixelMapusv( GLenum map,  
                      GLushort *values )
```

PARAMETERS

map Specifies the name of the pixel map to return. Accepted values are **GL_PIXEL_MAP_I_TO_I**, **GL_PIXEL_MAP_S_TO_S**, **GL_PIXEL_MAP_I_TO_R**, **GL_PIXEL_MAP_I_TO_G**, **GL_PIXEL_MAP_I_TO_B**, **GL_PIXEL_MAP_I_TO_A**, **GL_PIXEL_MAP_R_TO_R**, **GL_PIXEL_MAP_G_TO_G**, **GL_PIXEL_MAP_B_TO_B**, and **GL_PIXEL_MAP_A_TO_A**.

values Returns the pixel map contents.

DESCRIPTION

See the **glPixelMap** reference page for a description of the acceptable values for the *map* parameter. **glGetPixelMap** returns in *values* the contents of the pixel map specified in *map*. Pixel maps are used during the execution of **glReadPixels**, **glDrawPixels**, **glCopyPixels**, **glTexImage1D**, and **glTexImage2D** to map color indices, stencil indices, color components, and depth components to other values.

Unsigned integer values, if requested, are linearly mapped from the internal fixed or floating-point representation such that 1.0 maps to the largest representable integer value, and 0.0 maps to 0. Return unsigned integer values are undefined if the map value was not in the range [0,1].

To determine the required size of *map*, call **glGet** with the appropriate symbolic constant.

NOTES

If an error is generated, no change is made to the contents

of values.

ERRORS

GL_INVALID_ENUM is generated if *map* is not an accepted value.

GL_INVALID_OPERATION is generated if **glGetPixelMap** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_PIXEL_MAP_I_TO_I_SIZE**
glGet with argument **GL_PIXEL_MAP_S_TO_S_SIZE**
glGet with argument **GL_PIXEL_MAP_I_TO_R_SIZE**
glGet with argument **GL_PIXEL_MAP_I_TO_G_SIZE**
glGet with argument **GL_PIXEL_MAP_I_TO_B_SIZE**
glGet with argument **GL_PIXEL_MAP_I_TO_A_SIZE**
glGet with argument **GL_PIXEL_MAP_R_TO_R_SIZE**
glGet with argument **GL_PIXEL_MAP_G_TO_G_SIZE**
glGet with argument **GL_PIXEL_MAP_B_TO_B_SIZE**
glGet with argument **GL_PIXEL_MAP_A_TO_A_SIZE**
glGet with argument **GL_MAX_PIXEL_MAP_TABLE**

SEE ALSO

glCopyPixels, **glDrawPixels**, **glPixelMap**, **glPixelTransfer**,
glReadPixels, **glTexImage1D**, **glTexImage2D**

NAME

glGetPointerv - return the address of the specified pointer

C SPECIFICATION

```
void glGetPointerv( GLenum pname,  
                   GLvoid* *params )
```

PARAMETERS

pname Specifies the array or buffer pointer to be returned. Symbolic constants **GL_COLOR_ARRAY_POINTER**, **GL_EDGE_FLAG_ARRAY_POINTER**, **GL_FEEDBACK_BUFFER_POINTER**, **GL_INDEX_ARRAY_POINTER**, **GL_NORMAL_ARRAY_POINTER**, **GL_TEXTURE_COORD_ARRAY_POINTER**, **GL_SELECTION_BUFFER_POINTER**, and **GL_VERTEX_ARRAY_POINTER** are accepted.

params Returns the pointer value specified by *pname*.

DESCRIPTION

glGetPointerv returns pointer information. *pname* is a symbolic constant indicating the pointer to be returned, and *params* is a pointer to a location in which to place the returned data.

NOTES

glGetPointerv is available only if the GL version is 1.1 or greater.

The pointers are all client-side state.

The initial value for each pointer is 0.

ERRORS

GL_INVALID_ENUM is generated if *pname* is not an accepted value.

SEE ALSO

glArrayElement, **glColorPointer**, **glDrawArrays**, **glEdgeFlagPointer**, **glFeedbackBuffer**, **glIndexPointer**, **glInterleavedArrays**, **glNormalPointer**, **glSelectBuffer**, **glTexCoordPointer**, **glVertexPointer**

NAME

glGetPolygonStipple - return the polygon stipple pattern

C SPECIFICATION

```
void glGetPolygonStipple( GLubyte *mask )
```

PARAMETERS

mask Returns the stipple pattern. The initial value is all 1's.

DESCRIPTION

glGetPolygonStipple returns to *mask* a 32x32 polygon stipple pattern. The pattern is packed into memory as if **glReadPixels** with both *height* and *width* of 32, *type* of **GL_BITMAP**, and *format* of **GL_COLOR_INDEX** were called, and the stipple pattern were stored in an internal 32x32 color index buffer. Unlike **glReadPixels**, however, pixel transfer operations (shift, offset, pixel map) are not applied to the returned stipple image.

NOTES

If an error is generated, no change is made to the contents of *mask*.

ERRORS

GL_INVALID_OPERATION is generated if **glGetPolygonStipple** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

SEE ALSO

glPixelStore, **glPixelTransfer**, **glPolygonStipple**,
glReadPixels

NAME

glGetString - return a string describing the current GL connection

C SPECIFICATION

```
const GLubyte * glGetString( GLenum name )
```

PARAMETERS

name Specifies a symbolic constant, one of **GL_VENDOR**, **GL_RENDERER**, **GL_VERSION**, or **GL_EXTENSIONS**.

DESCRIPTION

glGetString returns a pointer to a static string describing some aspect of the current GL connection. *name* can be one of the following:

GL_VENDOR	Returns the company responsible for this GL implementation. This name does not change from release to release.
GL_RENDERER	Returns the name of the renderer. This name is typically specific to a particular configuration of a hardware platform. It does not change from release to release.
GL_VERSION	Returns a version or release number.
GL_EXTENSIONS	Returns a space-separated list of supported extensions to GL.

Because the GL does not include queries for the performance characteristics of an implementation, some applications are written to recognize known platforms and modify their GL usage based on known performance characteristics of these platforms. Strings **GL_VENDOR** and **GL_RENDERER** together uniquely specify a platform. They do not change from release to release and should be used by platform-recognition algorithms.

Some applications want to make use of features that are not part of the standard GL. These features may be implemented as extensions to the standard GL. The **GL_EXTENSIONS** string

is a space-separated list of supported GL extensions.
(Extension names never contain a space character.)

The **GL_VERSION** string begins with a version number. The version number uses one of these forms:

major_number.minor_number
major_number.minor_number.release_number

Vendor-specific information may follow the version number. Its format depends on the implementation, but a space always separates the version number and the vendor-specific information.

All strings are null-terminated.

NOTES

If an error is generated, **glGetString** returns 0.

The client and server may support different versions or extensions. **glGetString** always returns a compatible version number or list of extensions. The release number always describes the server.

ERRORS

GL_INVALID_ENUM is generated if *name* is not an accepted value.

GL_INVALID_OPERATION is generated if **glGetString** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

NAME

glGetTexEnvfv, glGetTexEnviv - return texture environment parameters

C SPECIFICATION

```
void glGetTexEnvfv( GLenum target,  
                   GLenum pname,  
                   GLfloat *params )  
void glGetTexEnviv( GLenum target,  
                   GLenum pname,  
                   GLint *params )
```

PARAMETERS

target Specifies a texture environment. Must be **GL_TEXTURE_ENV**.

pname Specifies the symbolic name of a texture environment parameter. Accepted values are **GL_TEXTURE_ENV_MODE** and **GL_TEXTURE_ENV_COLOR**.

params Returns the requested data.

DESCRIPTION

glGetTexEnv returns in *params* selected values of a texture environment that was specified with **glTexEnv**. *target* specifies a texture environment. Currently, only one texture environment is defined and supported: **GL_TEXTURE_ENV**.

pname names a specific texture environment parameter, as follows:

GL_TEXTURE_ENV_MODE

params returns the single-valued texture environment mode, a symbolic constant. The initial value is **GL_MODULATE**.

GL_TEXTURE_ENV_COLOR

params returns four integer or floating-point values that are the texture environment color. Integer values, when requested, are linearly mapped from the internal floating-point representation such that 1.0 maps to the most

positive representable integer, and -1.0 maps to the most negative representable integer. The initial value is (0, 0, 0, 0).

NOTES

If an error is generated, no change is made to the contents of *params*.

ERRORS

GL_INVALID_ENUM is generated if *target* or *pname* is not an accepted value.

GL_INVALID_OPERATION is generated if **glGetTexEnv** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

SEE ALSO

glTexEnv

NAME

glGetTexGendv, glGetTexGenfv, glGetTexGeniv - return texture coordinate generation parameters

C SPECIFICATION

```
void glGetTexGendv( GLenum coord,
                   GLenum pname,
                   GLdouble *params )
void glGetTexGenfv( GLenum coord,
                   GLenum pname,
                   GLfloat *params )
void glGetTexGeniv( GLenum coord,
                   GLenum pname,
                   GLint *params )
```

PARAMETERS

coord Specifies a texture coordinate. Must be **GL_S**, **GL_T**, **GL_R**, or **GL_Q**.

pname Specifies the symbolic name of the value(s) to be returned. Must be either **GL_TEXTURE_GEN_MODE** or the name of one of the texture generation plane equations: **GL_OBJECT_PLANE** or **GL_EYE_PLANE**.

params Returns the requested data.

DESCRIPTION

glGetTexGen returns in *params* selected parameters of a texture coordinate generation function that was specified using **glTexGen**. *coord* names one of the (*s*, *t*, *r*, *q*) texture coordinates, using the symbolic constant **GL_S**, **GL_T**, **GL_R**, or **GL_Q**.

pname specifies one of three symbolic names:

GL_TEXTURE_GEN_MODE

params returns the single-valued texture generation function, a symbolic constant. The initial value is **GL_EYE_LINEAR**.

GL_OBJECT_PLANE

params returns the four plane equation coefficients that specify object linear-coordinate

generation. Integer values, when requested, are mapped directly from the internal floating-point representation.

GL_EYE_PLANE

params returns the four plane equation coefficients that specify eye linear-coordinate generation. Integer values, when requested, are mapped directly from the internal floating-point representation. The returned values are those maintained in eye coordinates. They are not equal to the values specified using **glTexGen**, unless the modelview matrix was identity when **glTexGen** was called.

NOTES

If an error is generated, no change is made to the contents of *params*.

ERRORS

GL_INVALID_ENUM is generated if *coord* or *pname* is not an accepted value.

GL_INVALID_OPERATION is generated if **glGetTexGen** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

SEE ALSO

glTexGen

NAME

glGetTexImage - return a texture image

C SPECIFICATION

```
void glGetTexImage( GLenum target,  
                   GLint level,  
                   GLenum format,  
                   GLenum type,  
                   GLvoid *pixels )
```

PARAMETERS

target Specifies which texture is to be obtained. **GL_TEXTURE_1D** and **GL_TEXTURE_2D** are accepted.

level Specifies the level-of-detail number of the desired image. Level 0 is the base image level. Level n is the nth mipmap reduction image.

format Specifies a pixel format for the returned data. The supported formats are **GL_RED**, **GL_GREEN**, **GL_BLUE**, **GL_ALPHA**, **GL_RGB**, **GL_RGBA**, **GL_LUMINANCE**, and **GL_LUMINANCE_ALPHA**.

type Specifies a pixel type for the returned data. The supported types are **GL_UNSIGNED_BYTE**, **GL_BYTE**, **GL_UNSIGNED_SHORT**, **GL_SHORT**, **GL_UNSIGNED_INT**, **GL_INT**, and **GL_FLOAT**.

pixels Returns the texture image. Should be a pointer to an array of the type specified by *type*.

DESCRIPTION

glGetTexImage returns a texture image into *pixels*. *target* specifies whether the desired texture image is one specified by **glTexImage1D** (**GL_TEXTURE_1D**) or by **glTexImage2D** (**GL_TEXTURE_2D**). *level* specifies the level-of-detail number of the desired image. *format* and *type* specify the format and type of the desired image array. See the reference pages **glTexImage1D** and **glDrawPixels** for a description of the acceptable values for the *format* and *type* parameters, respectively.

To understand the operation of **glGetTexImage**, consider the

selected internal four-component texture image to be an RGBA color buffer the size of the image. The semantics of **glGetTexImage** are then identical to those of **glReadPixels** called with the same *format* and *type*, with *x* and *y* set to 0, *width* set to the width of the texture image (including border if one was specified), and *height* set to 1 for 1D images, or to the height of the texture image (including border if one was specified) for 2D images. Because the internal texture image is an RGBA image, pixel formats **GL_COLOR_INDEX**, **GL_STENCIL_INDEX**, and **GL_DEPTH_COMPONENT** are not accepted, and pixel type **GL_BITMAP** is not accepted.

If the selected texture image does not contain four components, the following mappings are applied. Single-component textures are treated as RGBA buffers with red set to the single-component value, green set to 0, blue set to 0, and alpha set to 1. Two-component textures are treated as RGBA buffers with red set to the value of component zero, alpha set to the value of component one, and green and blue set to 0. Finally, three-component textures are treated as RGBA buffers with red set to component zero, green set to component one, blue set to component two, and alpha set to 1.

To determine the required size of *pixels*, use **glGetTexLevelParameter** to determine the dimensions of the internal texture image, then scale the required number of pixels by the storage required for each pixel, based on *format* and *type*. Be sure to take the pixel storage parameters into account, especially **GL_PACK_ALIGNMENT**.

NOTES

If an error is generated, no change is made to the contents of *pixels*.

ERRORS

GL_INVALID_ENUM is generated if *target*, *format*, or *type* is not an accepted value.

GL_INVALID_VALUE is generated if *level* is less than 0.

GL_INVALID_VALUE may be generated if *level* is greater than $\log \text{max}$, where max is the returned value of **GL_MAX_TEXTURE_SIZE**.

GL_INVALID_OPERATION is generated if **glGetTexImage** is

executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGetTexLevelParameter with argument **GL_TEXTURE_WIDTH**
glGetTexLevelParameter with argument **GL_TEXTURE_HEIGHT**
glGetTexLevelParameter with argument **GL_TEXTURE_BORDER**
glGetTexLevelParameter with argument **GL_TEXTURE_COMPONENTS**
glGet with arguments **GL_PACK_ALIGNMENT** and others

SEE ALSO

glDrawPixels, **glReadPixels**, **glTexEnv**, **glTexGen**,
glTexImage1D, **glTexImage2D**, **glTexSubImage1D**,
glTexSubImage2D, **glTexParameter**

NAME

glGetTexLevelParameterfv, glGetTexLevelParameteriv - return texture parameter values for a specific level of detail

C SPECIFICATION

```
void glGetTexLevelParameterfv( GLenum target,  
                                GLint level,  
                                GLenum pname,  
                                GLfloat *params )  
  
void glGetTexLevelParameteriv( GLenum target,  
                                GLint level,  
                                GLenum pname,  
                                GLint *params )
```

PARAMETERS

target Specifies the symbolic name of the target texture, either **GL_TEXTURE_1D**, **GL_TEXTURE_2D**, **GL_PROXY_TEXTURE_1D**, or **GL_PROXY_TEXTURE_2D**.

level Specifies the level-of-detail number of the desired image. Level 0 is the base image level. Level *n* is the *n*th mipmap reduction image.

pname Specifies the symbolic name of a texture parameter. **GL_TEXTURE_WIDTH**, **GL_TEXTURE_HEIGHT**, **GL_TEXTURE_INTERNAL_FORMAT**, **GL_TEXTURE_BORDER**, **GL_TEXTURE_RED_SIZE**, **GL_TEXTURE_GREEN_SIZE**, **GL_TEXTURE_BLUE_SIZE**, **GL_TEXTURE_ALPHA_SIZE**, **GL_TEXTURE_LUMINANCE_SIZE**, and **GL_TEXTURE_INTENSITY_SIZE** are accepted.

params Returns the requested data.

DESCRIPTION

glGetTexLevelParameter returns in *params* texture parameter values for a specific level-of-detail value, specified as *level*. *target* defines the target texture, either **GL_TEXTURE_1D**, **GL_TEXTURE_2D**, **GL_PROXY_TEXTURE_1D**, or **GL_PROXY_TEXTURE_2D**.

GL_MAX_TEXTURE_SIZE is not really descriptive enough. It has to report the largest square texture image that can be accommodated with mipmaps and borders, but a long skinny

texture, or a texture without mipmaps and borders, may easily fit in texture memory. The proxy targets allow the user to more accurately query whether the GL can accommodate a texture of a given configuration. If the texture cannot be accommodated, the texture state variables, which may be queried with **glGetTexLevelParameter**, are set to 0. If the texture can be accommodated, the texture state values will be set as they would be set for a non-proxy target.

pname specifies the texture parameter whose value or values will be returned.

The accepted parameter names are as follows:

GL_TEXTURE_WIDTH

params returns a single value, the width of the texture image. This value includes the border of the texture image. The initial value is 0.

GL_TEXTURE_HEIGHT

params returns a single value, the height of the texture image. This value includes the border of the texture image. The initial value is 0.

GL_TEXTURE_INTERNAL_FORMAT

params returns a single value, the internal format of the texture image.

GL_TEXTURE_BORDER

params returns a single value, the width in pixels of the border of the texture image. The initial value is 0.

GL_TEXTURE_RED_SIZE,

GL_TEXTURE_GREEN_SIZE,

GL_TEXTURE_BLUE_SIZE,

GL_TEXTURE_ALPHA_SIZE,

GL_TEXTURE_LUMINANCE_SIZE,

GL_TEXTURE_INTENSITY_SIZE

The internal storage resolution of an individual component. The resolution chosen by the GL will

be a close match for the resolution requested by the user with the component argument of **glTexImage1D** or **glTexImage2D**. The initial value is 0.

NOTES

If an error is generated, no change is made to the contents of *params*.

GL_TEXTURE_INTERNAL_FORMAT is only available if the GL version is 1.1 or greater. In version 1.0, use **GL_TEXTURE_COMPONENTS** instead.

GL_PROXY_TEXTURE_1D and **GL_PROXY_TEXTURE_2D** are only available if the GL version is 1.1 or greater.

ERRORS

GL_INVALID_ENUM is generated if *target* or *pname* is not an accepted value.

GL_INVALID_VALUE is generated if *level* is less than 0.

GL_INVALID_VALUE may be generated if *level* is greater than \log_{max} , where *max* is the returned value of **GL_MAX_TEXTURE_SIZE**.

GL_INVALID_OPERATION is generated if **glGetTexLevelParameter** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

SEE ALSO

glGetTexParameter, **glCopyTexImage1D**, **glCopyTexImage2D**, **glCopyTexSubImage1D**, **glCopyTexSubImage2D**, **glTexEnv**, **glTexGen**, **glTexImage1D**, **glTexImage2D**, **glTexSubImage1D**, **glTexSubImage2D**, **glTexParameter**

NAME

glGetTexParameterfv, glGetTexParameteriv - return texture parameter values

C SPECIFICATION

```
void glGetTexParameterfv( GLenum target,
                          GLenum pname,
                          GLfloat *params )
void glGetTexParameteriv( GLenum target,
                          GLenum pname,
                          GLint *params )
```

PARAMETERS

target Specifies the symbolic name of the target texture. **GL_TEXTURE_1D** and **GL_TEXTURE_2D** are accepted.

pname Specifies the symbolic name of a texture parameter. **GL_TEXTURE_MAG_FILTER**, **GL_TEXTURE_MIN_FILTER**, **GL_TEXTURE_WRAP_S**, **GL_TEXTURE_WRAP_T**, **GL_TEXTURE_BORDER_COLOR**, **GL_TEXTURE_PRIORITY**, and **GL_TEXTURE_RESIDENT** are accepted.

params Returns the texture parameters.

DESCRIPTION

glGetTexParameter returns in *params* the value or values of the texture parameter specified as *pname*. *target* defines the target texture, either **GL_TEXTURE_1D** or **GL_TEXTURE_2D**, to specify one- or two-dimensional texturing. *pname* accepts the same symbols as **glTexParameter**, with the same interpretations:

GL_TEXTURE_MAG_FILTER	Returns the single-valued texture magnification filter, a symbolic constant. The initial value is GL_LINEAR .
GL_TEXTURE_MIN_FILTER	Returns the single-valued texture minification filter, a symbolic constant. The initial value is

GL_NEAREST_MIPMAP_LINEAR.

GL_TEXTURE_WRAP_S

Returns the single-valued wrapping function for texture coordinate *s*, a symbolic constant. The initial value is **GL_REPEAT.**

GL_TEXTURE_WRAP_T

Returns the single-valued wrapping function for texture coordinate *t*, a symbolic constant. The initial value is **GL_REPEAT.**

GL_TEXTURE_BORDER_COLOR

Returns four integer or floating-point numbers that comprise the RGBA color of the texture border. Floating-point values are returned in the range [0, 1]. Integer values are returned as a linear mapping of the internal floating-point representation such that 1.0 maps to the most positive representable integer and -1.0 maps to the most negative representable integer. The initial value is (0, 0, 0, 0).

GL_TEXTURE_PRIORITY

Returns the residence priority of the target texture (or the named texture bound to it). The initial value is 1. See **glPrioritizeTextures.**

GL_TEXTURE_RESIDENT

Returns the residence status of the target texture. If the value

returned in *params* is **GL_TRUE**, the texture is resident in texture memory. See **glAreTexturesResident**.

NOTES

GL_TEXTURE_PRIORITY and **GL_TEXTURE_RESIDENT** are only available if the GL version is 1.1 or greater.

If an error is generated, no change is made to the contents of *params*.

ERRORS

GL_INVALID_ENUM is generated if *target* or *pname* is not an accepted value.

GL_INVALID_OPERATION is generated if **glGetTexParameter** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

SEE ALSO

glAreTexturesResident, **glPrioritizeTextures**, **glTexParameter**

NAME

glHint - specify implementation-specific hints

C SPECIFICATION

```
void glHint( GLenum target,  
             GLenum mode )
```

PARAMETERS

target Specifies a symbolic constant indicating the behavior to be controlled. **GL_FOG_HINT**, **GL_LINE_SMOOTH_HINT**, **GL_PERSPECTIVE_CORRECTION_HINT**, **GL_POINT_SMOOTH_HINT**, and **GL_POLYGON_SMOOTH_HINT** are accepted.

mode Specifies a symbolic constant indicating the desired behavior. **GL_FASTEST**, **GL_NICEST**, and **GL_DONT_CARE** are accepted.

DESCRIPTION

Certain aspects of GL behavior, when there is room for interpretation, can be controlled with hints. A hint is specified with two arguments. *target* is a symbolic constant indicating the behavior to be controlled, and *mode* is another symbolic constant indicating the desired behavior. The initial value for each *target* is **GL_DONT_CARE**. *mode* can be one of the following:

GL_FASTEST	The most efficient option should be chosen.
GL_NICEST	The most correct, or highest quality, option should be chosen.
GL_DONT_CARE	No preference.

Though the implementation aspects that can be hinted are well defined, the interpretation of the hints depends on the implementation. The hint aspects that can be specified with *target*, along with suggested semantics, are as follows:

GL_FOG_HINT	Indicates the accuracy of fog calculation. If per-pixel fog calculation is not efficiently supported
--------------------	------------------------------------------------------------------------------------------------------

by the GL implementation, hinting **GL_DONT_CARE** or **GL_FASTEST** can result in per-vertex calculation of fog effects.

GL_LINE_SMOOTH_HINT Indicates the sampling quality of antialiased lines. If a larger filter function is applied, hinting **GL_NICEST** can result in more pixel fragments being generated during rasterization,

GL_PERSPECTIVE_CORRECTION_HINT

Indicates the quality of color and texture coordinate interpolation. If perspective-corrected parameter interpolation is not efficiently supported by the GL implementation, hinting **GL_DONT_CARE** or **GL_FASTEST** can result in simple linear interpolation of colors and/or texture coordinates.

GL_POINT_SMOOTH_HINT

Indicates the sampling quality of antialiased points. If a larger filter function is applied, hinting **GL_NICEST** can result in more pixel fragments being generated during rasterization,

GL_POLYGON_SMOOTH_HINT

Indicates the sampling quality of antialiased polygons. Hinting **GL_NICEST** can result in more pixel fragments being generated during rasterization, if a larger filter function is applied.

NOTES

The interpretation of hints depends on the implementation. Some implementations ignore **glHint** settings.

ERRORS

GL_INVALID_ENUM is generated if either *target* or *mode* is not an accepted value.

GL_INVALID_OPERATION is generated if **glHint** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

NAME

glIndexd, glIndexf, glIndexi, glIndexs, glIndexub, glIndexdv, glIndexfv, glIndexiv, glIndexsv, glIndexubv - set the current color index

C SPECIFICATION

```
void glIndexd( GLdouble c )
void glIndexf( GLfloat c )
void glIndexi( GLint c )
void glIndexs( GLshort c )
void glIndexub( GLubyte c )
```

PARAMETERS

c Specifies the new value for the current color index.

C SPECIFICATION

```
void glIndexdv( const GLdouble *c )
void glIndexfv( const GLfloat *c )
void glIndexiv( const GLint *c )
void glIndexsv( const GLshort *c )
void glIndexubv( const GLubyte *c )
```

PARAMETERS

c Specifies a pointer to a one-element array that contains the new value for the current color index.

DESCRIPTION

glIndex updates the current (single-valued) color index. It takes one argument, the new value for the current color index.

The current index is stored as a floating-point value. Integer values are converted directly to floating-point values, with no special mapping. The initial value is 1.

Index values outside the representable range of the color index buffer are not clamped. However, before an index is dithered (if enabled) and written to the frame buffer, it is converted to fixed-point format. Any bits in the integer portion of the resulting fixed-point value that do not correspond to bits in the frame buffer are masked out.

NOTES

glIndexub and **glIndexubv** are available only if the GL version is 1.1 or greater.

The current index can be updated at any time. In particular, **glIndex** can be called between a call to **glBegin** and the corresponding call to **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_CURRENT_INDEX**

SEE ALSO

glColor, **glIndexPointer**

NAME

glIndexMask - control the writing of individual bits in the color index buffers

C SPECIFICATION

```
void glIndexMask( GLuint mask )
```

PARAMETERS

mask Specifies a bit mask to enable and disable the writing of individual bits in the color index buffers. Initially, the mask is all 1's.

DESCRIPTION

glIndexMask controls the writing of individual bits in the color index buffers. The least significant *n* bits of *mask*, where *n* is the number of bits in a color index buffer, specify a mask. Where a 1 (one) appears in the mask, it's possible to write to the corresponding bit in the color index buffer (or buffers). Where a 0 (zero) appears, the corresponding bit is write-protected.

This mask is used only in color index mode, and it affects only the buffers currently selected for writing (see **glDrawBuffer**). Initially, all bits are enabled for writing.

ERRORS

GL_INVALID_OPERATION is generated if **glIndexMask** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_INDEX_WRITEMASK**

SEE ALSO

glColorMask, **glDepthMask**, **glDrawBuffer**, **glIndex**, **glIndexPointer**, **glStencilMask**

NAME

glIndexPointer - define an array of color indexes

C SPECIFICATION

```
void glIndexPointer( GLenum type,
                    GLsizei stride,
                    const GLvoid *pointer )
```

PARAMETERS

type Specifies the data type of each color index in the array. Symbolic constants **GL_UNSIGNED_BYTE**, **GL_SHORT**, **GL_INT**, **GL_FLOAT**, and **GL_DOUBLE** are accepted.

stride Specifies the byte offset between consecutive color indexes. If *stride* is 0 (the initial value), the color indexes are understood to be tightly packed in the array.

pointer Specifies a pointer to the first index in the array.

DESCRIPTION

glIndexPointer specifies the location and data format of an array of color indexes to use when rendering. *type* specifies the data type of each color index and *stride* gives the byte stride from one color index to the next allowing vertexes and attributes to be packed into a single array or stored in separate arrays. (Single-array storage may be more efficient on some implementations; see **glInterleavedArrays**.)

type, *stride*, and *pointer* are saved as client-side state.

The color index array is initially disabled. To enable and disable the array, call **glEnableClientState** and **glDisableClientState** with the argument **GL_INDEX_ARRAY**. If enabled, the color index array is used when **glDrawArrays**, **glDrawElements** or **glArrayElement** is called.

Use **glDrawArrays** to construct a sequence of primitives (all of the same type) from prespecified vertex and vertex attribute arrays. Use **glArrayElement** to specify primitives

by indexing vertexes and vertex attributes and **glDrawElements** to construct a sequence of primitives by indexing vertexes and vertex attributes.

NOTES

glIndexPointer is available only if the GL version is 1.1 or greater.

The color index array is initially disabled, and it isn't accessed when **glArrayElement**, **glDrawElements** or **glDrawArrays** is called.

Execution of **glIndexPointer** is not allowed between **glBegin** and the corresponding **glEnd**, but an error may or may not be generated. If an error is not generated, the operation is undefined.

glIndexPointer is typically implemented on the client side.

Since the color index array parameters are client-side state, they are not saved or restored by **glPushAttrib** and **glPopAttrib**. Use **glPushClientAttrib** and **glPopClientAttrib** instead.

ERRORS

GL_INVALID_ENUM is generated if *type* is not an accepted value.

GL_INVALID_VALUE is generated if *stride* is negative.

ASSOCIATED GETS

glIsEnabled with argument **GL_INDEX_ARRAY**

glGet with argument **GL_INDEX_ARRAY_TYPE**

glGet with argument **GL_INDEX_ARRAY_STRIDE**

glGetPointerv with argument **GL_INDEX_ARRAY_POINTER**

SEE ALSO

glArrayElement, **glColorPointer**, **glDrawArrays**,
glDrawElements, **glEdgeFlagPointer**, **glEnable**, **glGetPointerv**,
glInterleavedArrays, **glNormalPointer**, **glPopClientAttrib**,
glPushClientAttrib, **glTexCoordPointer**, **glVertexPointer**

NAME

glInitNames - initialize the name stack

C SPECIFICATION

```
void glInitNames( void )
```

DESCRIPTION

The name stack is used during selection mode to allow sets of rendering commands to be uniquely identified. It consists of an ordered set of unsigned integers.

glInitNames causes the name stack to be initialized to its default empty state.

The name stack is always empty while the render mode is not **GL_SELECT**. Calls to **glInitNames** while the render mode is not **GL_SELECT** are ignored.

ERRORS

GL_INVALID_OPERATION is generated if **glInitNames** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_NAME_STACK_DEPTH**

glGet with argument **GL_MAX_NAME_STACK_DEPTH**

SEE ALSO

glLoadName, **glPushName**, **glRenderMode**, **glSelectBuffer**

NAME

glInterleavedArrays - simultaneously specify and enable several interleaved arrays

C SPECIFICATION

```
void glInterleavedArrays( GLenum format,
                          GLsizei stride,
                          const GLvoid *pointer )
```

PARAMETERS

format Specifies the type of array to enable. Symbolic constants **GL_V2F**, **GL_V3F**, **GL_C4UB_V2F**, **GL_C4UB_V3F**, **GL_C3F_V3F**, **GL_N3F_V3F**, **GL_C4F_N3F_V3F**, **GL_T2F_V3F**, **GL_T4F_V4F**, **GL_T2F_C4UB_V3F**, **GL_T2F_C3F_V3F**, **GL_T2F_N3F_V3F**, **GL_T2F_C4F_N3F_V3F**, and **GL_T4F_C4F_N3F_V4F** are accepted.

stride Specifies the offset in bytes between each aggregate array element.

DESCRIPTION

glInterleavedArrays lets you specify and enable individual color, normal, texture and vertex arrays whose elements are part of a larger aggregate array element. For some implementations, this is more efficient than specifying the arrays separately.

If *stride* is 0, the aggregate elements are stored consecutively. Otherwise, *stride* bytes occur between the beginning of one aggregate array element and the beginning of the next aggregate array element.

format serves as a 'key' describing the extraction of individual arrays from the aggregate array. If *format* contains a T, then texture coordinates are extracted from the interleaved array. If C is present, color values are extracted. If N is present, normal coordinates are extracted. Vertex coordinates are always extracted.

The digits 2, 3, and 4 denote how many values are extracted. F indicates that values are extracted as floating-point values. Colors may also be extracted as 4 unsigned bytes if 4UB follows the C. If a color is extracted as 4 unsigned

bytes, the vertex array element which follows is located at the first possible floating-point aligned address.

NOTES

glInterleavedArrays is available only if the GL version is 1.1 or greater.

If **glInterleavedArrays** is called while compiling a display list, it is not compiled into the list, and it is executed immediately.

Execution of **glInterleavedArrays** is not allowed between the execution of **glBegin** and the corresponding execution of **glEnd**, but an error may or may not be generated. If no error is generated, the operation is undefined.

glInterleavedArrays is typically implemented on the client side.

Vertex array parameters are client-side state and are therefore not saved or restored by **glPushAttrib** and **glPopAttrib**. Use **glPushClientAttrib** and **glPopClientAttrib** instead.

ERRORS

GL_INVALID_ENUM is generated if *format* is not an accepted value.

GL_INVALID_VALUE is generated if *stride* is negative.

SEE ALSO

glArrayElement, **glColorPointer**, **glDrawArrays**,
glDrawElements, **glEdgeFlagPointer**, **glEnableClientState**,
glGetPointer, **glIndexPointer**, **glNormalPointer**,
glTexCoordPointer, **glVertexPointer**

NAME

glIsEnabled - test whether a capability is enabled

C SPECIFICATION

GLboolean **glIsEnabled**(GLenum *cap*)

PARAMETERS

cap Specifies a symbolic constant indicating a GL capability.

DESCRIPTION

glIsEnabled returns **GL_TRUE** if *cap* is an enabled capability and returns **GL_FALSE** otherwise. Initially all capabilities except **GL_DITHER** are disabled; **GL_DITHER** is initially enabled.

The following capabilities are accepted for *cap*:

Constant	See
GL_ALPHA_TEST	glAlphaFunc
GL_AUTO_NORMAL	glEvalCoord
GL_BLEND	glBlendFunc, glLogicOp
GL_CLIP_PLANE <i>i</i>	glClipPlane
GL_COLOR_ARRAY	glColorPointer
GL_COLOR_LOGIC_OP	glLogicOp
GL_COLOR_MATERIAL	glColorMaterial
GL_CULL_FACE	glCullFace
GL_DEPTH_TEST	glDepthFunc, glDepthRange
GL_DITHER	glEnable
GL_EDGE_FLAG_ARRAY	glEdgeFlagPointer
GL_FOG	glFog
GL_INDEX_ARRAY	glIndexPointer
GL_INDEX_LOGIC_OP	glLogicOp
GL_LIGHT <i>i</i>	glLightModel, glLight
GL_LIGHTING	glMaterial, glLightModel, glLight
GL_LINE_SMOOTH	glLineWidth
GL_LINE_STIPPLE	glLineStipple
GL_MAP1_COLOR_4	glMap1, glMap2
GL_MAP2_TEXTURE_COORD_2	glMap2
GL_MAP2_TEXTURE_COORD_3	glMap2
GL_MAP2_TEXTURE_COORD_4	glMap2
GL_MAP2_VERTEX_3	glMap2

<code>GL_MAP2_VERTEX_4</code>	<code>glMap2</code>
<code>GL_NORMAL_ARRAY</code>	<code>glNormalPointer</code>
<code>GL_NORMALIZE</code>	<code>glNormal</code>
<code>GL_POINT_SMOOTH</code>	<code>glPointSize</code>
<code>GL_POLYGON_SMOOTH</code>	<code>glPolygonMode</code>
<code>GL_POLYGON_OFFSET_FILL</code>	<code>glPolygonOffset</code>
<code>GL_POLYGON_OFFSET_LINE</code>	<code>glPolygonOffset</code>
<code>GL_POLYGON_OFFSET_POINT</code>	<code>glPolygonOffset</code>
<code>GL_POLYGON_STIPPLE</code>	<code>glPolygonStipple</code>
<code>GL_SCISSOR_TEST</code>	<code>glScissor</code>
<code>GL_STENCIL_TEST</code>	<code>glStencilFunc, glStencilOp</code>
<code>GL_TEXTURE_1D</code>	<code>glTexImage1D</code>
<code>GL_TEXTURE_2D</code>	<code>glTexImage2D</code>
<code>GL_TEXTURE_COORD_ARRAY</code>	<code>glTexCoordPointer</code>
<code>GL_TEXTURE_GEN_Q</code>	<code>glTexGen</code>
<code>GL_TEXTURE_GEN_R</code>	<code>glTexGen</code>
<code>GL_TEXTURE_GEN_S</code>	<code>glTexGen</code>
<code>GL_TEXTURE_GEN_T</code>	<code>glTexGen</code>
<code>GL_VERTEX_ARRAY</code>	<code>glVertexPointer</code>

NOTES

If an error is generated, `glIsEnabled` returns 0.

`GL_COLOR_LOGIC_OP`, `GL_COLOR_ARRAY`, `GL_EDGE_FLAG_ARRAY`, `GL_INDEX_ARRAY`, `GL_INDEX_LOGIC_OP`, `GL_NORMAL_ARRAY`, `GL_POLYGON_OFFSET_FILL`, `GL_POLYGON_OFFSET_LINE`, `GL_POLYGON_OFFSET_POINT`, `GL_TEXTURE_COORD_ARRAY`, and `GL_VERTEX_ARRAY` are only available if the GL version is 1.1 or greater

ERRORS

`GL_INVALID_ENUM` is generated if *cap* is not an accepted value.

`GL_INVALID_OPERATION` is generated if `glIsEnabled` is executed between the execution of `glBegin` and the corresponding execution of `glEnd`.

SEE ALSO

`glEnable`, `glEnableClientState`

NAME

glIsList - determine if a name corresponds to a display-list

C SPECIFICATION

GLboolean **glIsList**(GLuint *list*)

PARAMETERS

list Specifies a potential display-list name.

DESCRIPTION

glIsList returns **GL_TRUE** if *list* is the name of a display list and returns **GL_FALSE** otherwise.

ERRORS

GL_INVALID_OPERATION is generated if **glIsList** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

SEE ALSO

glCallList, **glCallLists**, **glDeleteLists**, **glGenLists**,
glNewList

NAME

glIsTexture - determine if a name corresponds to a texture

C SPECIFICATION

GLboolean **glIsTexture**(GLuint *texture*)

PARAMETERS

texture Specifies a value that may be the name of a texture.

DESCRIPTION

glIsTexture returns **GL_TRUE** if *texture* is currently the name of a texture. If *texture* is zero, or is a non-zero value that is not currently the name of a texture, or if an error occurs, **glIsTexture** returns **GL_FALSE**.

NOTES

glIsTexture is available only if the GL version is 1.1 or greater.

ERRORS

GL_INVALID_OPERATION is generated if **glIsTexture** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

SEE ALSO

glBindTexture, **glCopyTexImage1D**, **glCopyTexImage2D**,
glDeleteTextures, **glGenTextures**, **glGet**, **glGetTexParameter**,
glTexImage1D, **glTexImage2D**,
glTexParameter

NAME

glLightf, glLighti, glLightfv, glLightiv - set light source parameters

C SPECIFICATION

```
void glLightf( GLenum light,
               GLenum pname,
               GLfloat param )
void glLighti( GLenum light,
               GLenum pname,
               GLint param )
```

PARAMETERS

light Specifies a light. The number of lights depends on the implementation, but at least eight lights are supported. They are identified by symbolic names of the form **GL_LIGHTi** where $0 < i < \mathbf{GL_MAX_LIGHTS}$.

pname Specifies a single-valued light source parameter for *light*. **GL_SPOT_EXPONENT**, **GL_SPOT_CUTOFF**, **GL_CONSTANT_ATTENUATION**, **GL_LINEAR_ATTENUATION**, and **GL_QUADRATIC_ATTENUATION** are accepted.

param Specifies the value that parameter *pname* of light source *light* will be set to.

C SPECIFICATION

```
void glLightfv( GLenum light,
                GLenum pname,
                const GLfloat *params )
void glLightiv( GLenum light,
                GLenum pname,
                const GLint *params )
```

PARAMETERS

light Specifies a light. The number of lights depends on the implementation, but at least eight lights are supported. They are identified by symbolic names of the form **GL_LIGHTi** where $0 < i < \mathbf{GL_MAX_LIGHTS}$.

pname

Specifies a light source parameter for *light*.
GL_AMBIENT, **GL_DIFFUSE**, **GL_SPECULAR**, **GL_POSITION**,
GL_SPOT_CUTOFF, **GL_SPOT_DIRECTION**, **GL_SPOT_EXPONENT**,
GL_CONSTANT_ATTENUATION, **GL_LINEAR_ATTENUATION**, and
GL_QUADRATIC_ATTENUATION are accepted.

params

Specifies a pointer to the value or values that
parameter *pname* of light source *light* will be set to.

DESCRIPTION

glLight sets the values of individual light source parameters. *light* names the light and is a symbolic name of the form **GL_LIGHTi**, where $0 < i < \text{GL_MAX_LIGHTS}$. *pname* specifies one of ten light source parameters, again by symbolic name. *params* is either a single value or a pointer to an array that contains the new values.

To enable and disable lighting calculation, call **glEnable** and **glDisable** with argument **GL_LIGHTING**. Lighting is initially disabled. When it is enabled, light sources that are enabled contribute to the lighting calculation. Light source *i* is enabled and disabled using **glEnable** and **glDisable** with argument **GL_LIGHTi**.

The ten light parameters are as follows:

GL_AMBIENT *params* contains four integer or floating-point values that specify the ambient RGBA intensity of the light. Integer values are mapped linearly such that the most positive representable value maps to 1.0, and the most negative representable value maps to -1.0. Floating-point values are mapped directly. Neither integer nor floating-point values are clamped. The initial ambient light intensity is (0, 0, 0, 1).

GL_DIFFUSE *params* contains four integer or floating-point values that specify the diffuse RGBA intensity of the light. Integer values are mapped linearly such that the most positive representable value maps to 1.0, and the most negative

representable value maps to -1.0. Floating-point values are mapped directly. Neither integer nor floating-point values are clamped. The initial value for **GL_LIGHT0** is (1, 1, 1, 1); for other lights, the initial value is (0, 0, 0, 0).

GL_SPECULAR

params contains four integer or floating-point values that specify the specular RGBA intensity of the light. Integer values are mapped linearly such that the most positive representable value maps to 1.0, and the most negative representable value maps to -1.0. Floating-point values are mapped directly. Neither integer nor floating-point values are clamped. The initial value for **GL_LIGHT0** is (1, 1, 1, 1); for other lights, the initial value is (0, 0, 0, 0).

GL_POSITION

params contains four integer or floating-point values that specify the position of the light in homogeneous object coordinates. Both integer and floating-point values are mapped directly. Neither integer nor floating-point values are clamped.

The position is transformed by the modelview matrix when **glLight** is called (just as if it were a point), and it is stored in eye coordinates. If the w component of the position is 0, the light is treated as a directional source. Diffuse and specular lighting calculations take the light's direction, but not its actual position, into account, and attenuation is disabled. Otherwise, diffuse and specular lighting calculations are based on the actual location of the light in eye coordinates, and attenuation is enabled. The initial position is (0, 0, 1, 0); thus, the initial light source is

directional, parallel to, and in the direction of the -z axis.

GL_SPOT_DIRECTION

params contains three integer or floating-point values that specify the direction of the light in homogeneous object coordinates. Both integer and floating-point values are mapped directly. Neither integer nor floating-point values are clamped.

The spot direction is transformed by the inverse of the modelview matrix when **glLight** is called (just as if it were a normal), and it is stored in eye coordinates. It is significant only when **GL_SPOT_CUTOFF** is not 180, which it is initially. The initial direction is (0, 0, -1).

GL_SPOT_EXPONENT

params is a single integer or floating-point value that specifies the intensity distribution of the light. Integer and floating-point values are mapped directly. Only values in the range [0,128] are accepted.

Effective light intensity is attenuated by the cosine of the angle between the direction of the light and the direction from the light to the vertex being lighted, raised to the power of the spot exponent. Thus, higher spot exponents result in a more focused light source, regardless of the spot cutoff angle (see **GL_SPOT_CUTOFF**, next paragraph). The initial spot exponent is 0, resulting in uniform light distribution.

GL_SPOT_CUTOFF

params is a single integer or floating-point value that specifies the maximum spread angle of a light source. Integer and floating-point values are mapped directly. Only values in the range [0,90] and the special value 180 are accepted. If the angle between the

direction of the light and the direction from the light to the vertex being lighted is greater than the spot cutoff angle, the light is completely masked. Otherwise, its intensity is controlled by the spot exponent and the attenuation factors. The initial spot cutoff is 180, resulting in uniform light distribution.

GL_CONSTANT_ATTENUATION

GL_LINEAR_ATTENUATION

GL_QUADRATIC_ATTENUATION

params is a single integer or floating-point value that specifies one of the three light attenuation factors. Integer and floating-point values are mapped directly. Only nonnegative values are accepted. If the light is positional, rather than directional, its intensity is attenuated by the reciprocal of the sum of the constant factor, the linear factor times the distance between the light and the vertex being lighted, and the quadratic factor times the square of the same distance. The initial attenuation factors are (1, 0, 0), resulting in no attenuation.

NOTES

It is always the case that **GL_LIGHT*i*** = **GL_LIGHT0** + *i*.

ERRORS

GL_INVALID_ENUM is generated if either *light* or *pname* is not an accepted value.

GL_INVALID_VALUE is generated if a spot exponent value is specified outside the range [0,128], or if spot cutoff is specified outside the range [0,90] (except for the special value 180), or if a negative attenuation factor is specified.

GL_INVALID_OPERATION is generated if **glLight** is executed

between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGetLight

glIsEnabled with argument **GL_LIGHTING**

SEE ALSO

glColorMaterial, **glLightModel**, **glMaterial**

NAME

glLightModelf, glLightModeli, glLightModelfv, glLightModeliv
- set the lighting model parameters

C SPECIFICATION

```
void glLightModelf( GLenum pname,  
                   GLfloat param )  
void glLightModeli( GLenum pname,  
                   GLint param )
```

PARAMETERS

pname Specifies a single-valued lighting model parameter.
GL_LIGHT_MODEL_LOCAL_VIEWER and
GL_LIGHT_MODEL_TWO_SIDE are accepted.

param Specifies the value that *param* will be set to.

C SPECIFICATION

```
void glLightModelfv( GLenum pname,  
                    const GLfloat *params )  
void glLightModeliv( GLenum pname,  
                    const GLint *params )
```

PARAMETERS

pname
Specifies a lighting model parameter.
GL_LIGHT_MODEL_AMBIENT, **GL_LIGHT_MODEL_LOCAL_VIEWER**,
and **GL_LIGHT_MODEL_TWO_SIDE** are accepted.

params
Specifies a pointer to the value or values that *params*
will be set to.

DESCRIPTION

glLightModel sets the lighting model parameter. *pname* names a parameter and *params* gives the new value. There are three lighting model parameters:

GL_LIGHT_MODEL_AMBIENT

params contains four integer or floating-point values that specify the ambient RGBA intensity of the entire scene. Integer values are mapped

linearly such that the most positive representable value maps to 1.0, and the most negative representable value maps to -1.0. Floating-point values are mapped directly. Neither integer nor floating-point values are clamped. The initial ambient scene intensity is (0.2, 0.2, 0.2, 1.0).

GL_LIGHT_MODEL_LOCAL_VIEWER

params is a single integer or floating-point value that specifies how specular reflection angles are computed. If *params* is 0 (or 0.0), specular reflection angles take the view direction to be parallel to and in the direction of the -z axis, regardless of the location of the vertex in eye coordinates. Otherwise, specular reflections are computed from the origin of the eye coordinate system. The initial value is 0.

GL_LIGHT_MODEL_TWO_SIDE

params is a single integer or floating-point value that specifies whether one- or two-sided lighting calculations are done for polygons. It has no effect on the lighting calculations for points, lines, or bitmaps. If *params* is 0 (or 0.0), one-sided lighting is specified, and only the *front* material parameters are used in the lighting equation. Otherwise, two-sided lighting is specified. In this case, vertices of back-facing polygons are lighted using the *back* material parameters, and have their normals reversed before the lighting equation is evaluated. Vertices of front-facing polygons are always lighted using the *front* material parameters, with no change to their normals. The initial value is 0.

In RGBA mode, the lighted color of a vertex is the sum of the material emission intensity, the product of the material ambient reflectance and the lighting model full-scene ambient intensity, and the contribution of each enabled light source. Each light source contributes the sum of three terms: ambient, diffuse, and specular. The ambient light source contribution is the product of the material ambient reflectance and the light's ambient intensity. The diffuse light source contribution is the product of the material diffuse reflectance, the light's diffuse intensity, and the dot product of the vertex's normal with the

normalized vector from the vertex to the light source. The specular light source contribution is the product of the material specular reflectance, the light's specular intensity, and the dot product of the normalized vertex-to-eye and vertex-to-light vectors, raised to the power of the shininess of the material. All three light source contributions are attenuated equally based on the distance from the vertex to the light source and on light source direction, spread exponent, and spread cutoff angle. All dot products are replaced with 0 if they evaluate to a negative value.

The alpha component of the resulting lighted color is set to the alpha value of the material diffuse reflectance.

In color index mode, the value of the lighted index of a vertex ranges from the ambient to the specular values passed to **glMaterial** using **GL_COLOR_INDEXES**. Diffuse and specular coefficients, computed with a (.30, .59, .11) weighting of the lights' colors, the shininess of the material, and the same reflection and attenuation equations as in the RGBA case, determine how much above ambient the resulting index is.

ERRORS

GL_INVALID_ENUM is generated if *pname* is not an accepted value.

GL_INVALID_OPERATION is generated if **glLightModel** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_LIGHT_MODEL_AMBIENT**
glGet with argument **GL_LIGHT_MODEL_LOCAL_VIEWER**
glGet with argument **GL_LIGHT_MODEL_TWO_SIDE**
glIsEnabled with argument **GL_LIGHTING**

SEE ALSO

glLight, **glMaterial**

NAME

glLineStipple - specify the line stipple pattern

C SPECIFICATION

```
void glLineStipple( GLint factor,  
                   GLushort pattern )
```

PARAMETERS

factor Specifies a multiplier for each bit in the line stipple pattern. If *factor* is 3, for example, each bit in the pattern is used three times before the next bit in the pattern is used. *factor* is clamped to the range [1, 256] and defaults to 1.

pattern Specifies a 16-bit integer whose bit pattern determines which fragments of a line will be drawn when the line is rasterized. Bit zero is used first; the default pattern is all 1's.

DESCRIPTION

Line stippling masks out certain fragments produced by rasterization; those fragments will not be drawn. The masking is achieved by using three parameters: the 16-bit line stipple pattern *pattern*, the repeat count *factor*, and an integer stipple counter *s*.

Counter *s* is reset to 0 whenever **glBegin** is called, and before each line segment of a **glBegin(GL_LINES)/glEnd** sequence is generated. It is incremented after each fragment of a unit width aliased line segment is generated, or after each *i* fragments of an *i* width line segment are generated. The *i* fragments associated with count *s* are masked out if

$$pattern \text{ bit } (s / factor) \bmod 16$$

is 0, otherwise these fragments are sent to the frame buffer. Bit zero of *pattern* is the least significant bit.

Antialiased lines are treated as a sequence of *1xwidth* rectangles for purposes of stippling. Whether rectangle *s* is rasterized or not depends on the fragment rule described for aliased lines, counting rectangles rather than groups of

fragments.

To enable and disable line stippling, call **glEnable** and **glDisable** with argument **GL_LINE_STIPPLE**. When enabled, the line stipple pattern is applied as described above. When disabled, it is as if the pattern were all 1's. Initially, line stippling is disabled.

ERRORS

GL_INVALID_OPERATION is generated if **glLineStipple** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_LINE_STIPPLE_PATTERN**

glGet with argument **GL_LINE_STIPPLE_REPEAT**

glIsEnabled with argument **GL_LINE_STIPPLE**

SEE ALSO

glLineWidth, **glPolygonStipple**

NAME

glLineWidth - specify the width of rasterized lines

C SPECIFICATION

```
void glLineWidth( GLfloat width )
```

PARAMETERS

width Specifies the width of rasterized lines. The initial value is 1.

DESCRIPTION

glLineWidth specifies the rasterized width of both aliased and antialiased lines. Using a line width other than 1 has different effects, depending on whether line antialiasing is enabled. To enable and disable line antialiasing, call **glEnable** and **glDisable** with argument **GL_LINE_SMOOTH**. Line antialiasing is initially disabled.

If line antialiasing is disabled, the actual width is determined by rounding the supplied width to the nearest integer. (If the rounding results in the value 0, it is as if the line width were 1.) If $| \Delta x | \geq | \Delta y |$, *i* pixels are filled in each column that is rasterized, where *i* is the rounded value of *width*. Otherwise, *i* pixels are filled in each row that is rasterized.

If antialiasing is enabled, line rasterization produces a fragment for each pixel square that intersects the region lying within the rectangle having width equal to the current line width, length equal to the actual length of the line, and centered on the mathematical line segment. The coverage value for each fragment is the window coordinate area of the intersection of the rectangular region with the corresponding pixel square. This value is saved and used in the final rasterization step.

Not all widths can be supported when line antialiasing is enabled. If an unsupported width is requested, the nearest supported width is used. Only width 1 is guaranteed to be supported; others depend on the implementation. To query the range of supported widths and the size difference between supported widths within the range, call **glGet** with

arguments **GL_LINE_WIDTH_RANGE** and **GL_LINE_WIDTH_GRANULARITY**.

NOTES

The line width specified by **glLineWidth** is always returned when **GL_LINE_WIDTH** is queried. Clamping and rounding for aliased and antialiased lines have no effect on the specified value.

Nonantialiased line width may be clamped to an implementation-dependent maximum. Although this maximum cannot be queried, it must be no less than the maximum value for antialiased lines, rounded to the nearest integer value.

ERRORS

GL_INVALID_VALUE is generated if *width* is less than or equal to 0.

GL_INVALID_OPERATION is generated if **glLineWidth** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_LINE_WIDTH**

glGet with argument **GL_LINE_WIDTH_RANGE**

glGet with argument **GL_LINE_WIDTH_GRANULARITY**

glIsEnabled with argument **GL_LINE_SMOOTH**

SEE ALSO

glEnable

NAME

glListBase - set the display-list base for **glCallLists**

C SPECIFICATION

```
void glListBase( GLuint base )
```

PARAMETERS

base Specifies an integer offset that will be added to **glCallLists** offsets to generate display-list names. The initial value is 0.

DESCRIPTION

glCallLists specifies an array of offsets. Display-list names are generated by adding *base* to each offset. Names that reference valid display lists are executed; the others are ignored.

ERRORS

GL_INVALID_OPERATION is generated if **glListBase** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_LIST_BASE**

SEE ALSO

glCallLists

NAME

glLoadIdentity - replace the current matrix with the identity matrix

C SPECIFICATION

```
void glLoadIdentity( void )
```

DESCRIPTION

glLoadIdentity replaces the current matrix with the identity matrix. It is semantically equivalent to calling **glLoadMatrix** with the identity matrix

$$\begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

but in some cases it is more efficient.

ERRORS

GL_INVALID_OPERATION is generated if **glLoadIdentity** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_MATRIX_MODE**
glGet with argument **GL_MODELVIEW_MATRIX**
glGet with argument **GL_PROJECTION_MATRIX**
glGet with argument **GL_TEXTURE_MATRIX**

SEE ALSO

glLoadMatrix, **glMatrixMode**, **glMultMatrix**, **glPushMatrix**

NAME

glLoadMatrixd, **glLoadMatrixf** - replace the current matrix with the specified matrix

C SPECIFICATION

```
void glLoadMatrixd( const GLdouble *m )
void glLoadMatrixf( const GLfloat *m )
```

PARAMETERS

m Specifies a pointer to 16 consecutive values, which are used as the elements of a 4x4 column-major matrix.

DESCRIPTION

glLoadMatrix replaces the current matrix with the one whose elements are specified by *m*. The current matrix is the projection matrix, modelview matrix, or texture matrix, depending on the current matrix mode (see **glMatrixMode**).

The current matrix, *M*, defines a transformation of coordinates. For instance, assume *M* refers to the modelview matrix. If *v* = (*v*[0],*v*[1],*v*[2],*v*[3]) is the set of object coordinates of a vertex, and *m* points to an array of 16 single- or double-precision floating-point values *m*[0],*m*[1],...,*m*[15], then the modelview transformation *M*(*v*) does the following:

$$M(v) = \begin{pmatrix} m[0] & m[4] & m[8] & m[12] \\ m[1] & m[5] & m[9] & m[13] \\ m[2] & m[6] & m[10] & m[14] \\ m[3] & m[7] & m[11] & m[15] \end{pmatrix} \times \begin{pmatrix} v[0] \\ v[1] \\ v[2] \\ v[3] \end{pmatrix}$$

Where 'x' denotes matrix multiplication.

Projection and texture transformations are similarly defined.

NOTES

While the elements of the matrix may be specified with single or double precision, the GL implementation may store or operate on these values in less than single precision.

ERRORS

GL_INVALID_OPERATION is generated if **glLoadMatrix** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_MATRIX_MODE**
glGet with argument **GL_MODELVIEW_MATRIX**
glGet with argument **GL_PROJECTION_MATRIX**
glGet with argument **GL_TEXTURE_MATRIX**

SEE ALSO

glLoadIdentity, glMatrixMode, glMultMatrix, glPushMatrix

NAME

glLoadName - load a name onto the name stack

C SPECIFICATION

```
void glLoadName( GLuint name )
```

PARAMETERS

name Specifies a name that will replace the top value on the name stack.

DESCRIPTION

The name stack is used during selection mode to allow sets of rendering commands to be uniquely identified. It consists of an ordered set of unsigned integers. **glLoadName** causes *name* to replace the value on the top of the name stack, which is initially empty.

The name stack is always empty while the render mode is not **GL_SELECT**. Calls to **glLoadName** while the render mode is not **GL_SELECT** are ignored.

ERRORS

GL_INVALID_OPERATION is generated if **glLoadName** is called while the name stack is empty.

GL_INVALID_OPERATION is generated if **glLoadName** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_NAME_STACK_DEPTH**

glGet with argument **GL_MAX_NAME_STACK_DEPTH**

SEE ALSO

glInitNames, **glPushName**, **glRenderMode**, **glSelectBuffer**

NAME

glLogicOp - specify a logical pixel operation for color index rendering

C SPECIFICATION

```
void glLogicOp( GLenum opcode )
```

PARAMETERS

opcode Specifies a symbolic constant that selects a logical operation. The following symbols are accepted:
GL_CLEAR, **GL_SET**, **GL_COPY**, **GL_COPY_INVERTED**,
GL_NOOP, **GL_INVERT**, **GL_AND**, **GL_NAND**, **GL_OR**, **GL_NOR**,
GL_XOR, **GL_EQUIV**, **GL_AND_REVERSE**, **GL_AND_INVERTED**,
GL_OR_REVERSE, and **GL_OR_INVERTED**. The initial value is **GL_COPY**.

DESCRIPTION

glLogicOp specifies a logical operation that, when enabled, is applied between the incoming color index or RGBA color and the color index or RGBA color at the corresponding location in the frame buffer. To enable or disable the logical operation, call **glEnable** and **glDisable** using the symbolic constant **GL_COLOR_LOGIC_OP** for RGBA mode or **GL_INDEX_LOGIC_OP** for color index mode. The initial value is disabled for both operations.

<i>opcode</i>	<i>resulting value</i>
GL_CLEAR	0
GL_SET	1
GL_COPY	s
GL_COPY_INVERTED	~s
GL_NOOP	d
GL_INVERT	~d
GL_AND	s & d
GL_NAND	~(s & d)
GL_OR	s d
GL_NOR	~(s d)
GL_XOR	s ^ d
GL_EQUIV	~(s ^ d)
GL_AND_REVERSE	s & ~d
GL_AND_INVERTED	~s & d

GL_OR_REVERSE	<i>s</i> <i>~d</i>
GL_OR_INVERTED	<i>~s</i> <i>d</i>

opcode is a symbolic constant chosen from the list above. In the explanation of the logical operations, *s* represents the incoming color index and *d* represents the index in the frame buffer. Standard C-language operators are used. As these bitwise operators suggest, the logical operation is applied independently to each bit pair of the source and destination indices or colors.

NOTES

Color index logical operations are always supported. RGBA logical operations are supported only if the GL version is 1.1 or greater.

When more than one RGBA color or index buffer is enabled for drawing, logical operations are performed separately for each enabled buffer, using for the destination value the contents of that buffer (see **glDrawBuffer**).

ERRORS

GL_INVALID_ENUM is generated if *opcode* is not an accepted value.

GL_INVALID_OPERATION is generated if **glLogicOp** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_LOGIC_OP_MODE**.

glIsEnabled with argument **GL_COLOR_LOGIC_OP** or **GL_INDEX_LOGIC_OP**.

SEE ALSO

glAlphaFunc, **glBlendFunc**, **glDrawBuffer**, **glEnable**, **glStencilOp**

NAME

glMap1d, glMap1f - define a one-dimensional evaluator

C SPECIFICATION

```
void glMap1d( GLenum target,
              GLdouble u1,
              GLdouble u2,
              GLint stride,
              GLint order,
              const GLdouble *points )

void glMap1f( GLenum target,
              GLfloat u1,
              GLfloat u2,
              GLint stride,
              GLint order,
              const GLfloat *points )
```

PARAMETERS

- target* Specifies the kind of values that are generated by the evaluator. Symbolic constants **GL_MAP1_VERTEX_3**, **GL_MAP1_VERTEX_4**, **GL_MAP1_INDEX**, **GL_MAP1_COLOR_4**, **GL_MAP1_NORMAL**, **GL_MAP1_TEXTURE_COORD_1**, **GL_MAP1_TEXTURE_COORD_2**, **GL_MAP1_TEXTURE_COORD_3**, and **GL_MAP1_TEXTURE_COORD_4** are accepted.
- u1, u2* Specify a linear mapping of *u*, as presented to **glEvalCoord1**, to u , the variable that is evaluated by the equations specified by this command.
- stride* Specifies the number of floats or doubles between the beginning of one control point and the beginning of the next one in the data structure referenced in *points*. This allows control points to be embedded in arbitrary data structures. The only constraint is that the values for a particular control point must occupy contiguous memory locations.
- order* Specifies the number of control points. Must be positive.
- points* Specifies a pointer to the array of control points.

DESCRIPTION

Evaluators provide a way to use polynomial or rational polynomial mapping to produce vertices, normals, texture coordinates, and colors. The values produced by an evaluator are sent to further stages of GL processing just as if they had been presented using **glVertex**, **glNormal**, **glTexCoord**, and **glColor** commands, except that the generated values do not update the current normal, texture coordinates, or color.

All polynomial or rational polynomial splines of any degree (up to the maximum degree supported by the GL implementation) can be described using evaluators. These include almost all splines used in computer graphics: B-splines, Bezier curves, Hermite splines, and so on.

Evaluators define curves based on Bernstein polynomials. Define $p(u)$ as

$$p(u) = \sum_{i=0}^n B_i(u) R_i$$

where R_i is a control point and $B_i(u)$ is the i th Bernstein polynomial of degree n ($order = n+1$):

$$B_i(u) = \frac{\binom{n}{i} u^i (1-u)^{n-i}}{\binom{n}{i}}$$

Recall that

$$\binom{n}{0} = 1 \text{ and } \frac{\binom{n}{0}}{\binom{n}{0}} = 1$$

glMap1 is used to define the basis and to specify what kind of values are produced. Once defined, a map can be enabled and disabled by calling **glEnable** and **glDisable** with the map name, one of the nine predefined values for *target* described below. **glEvalCoord1** evaluates the one-dimensional maps that are enabled. When **glEvalCoord1** presents a value u , the Bernstein functions are evaluated using u , where

$$u = \frac{u_2 - u_1}{u_2 - u_1}$$

target is a symbolic constant that indicates what kind of

control points are provided in *points*, and what output is generated when the map is evaluated. It can assume one of nine predefined values:

GL_MAP1_VERTEX_3	Each control point is three floating-point values representing <i>x</i> , <i>y</i> , and <i>z</i> . Internal glVertex3 commands are generated when the map is evaluated.
GL_MAP1_VERTEX_4	Each control point is four floating-point values representing <i>x</i> , <i>y</i> , <i>z</i> , and <i>w</i> . Internal glVertex4 commands are generated when the map is evaluated.
GL_MAP1_INDEX	Each control point is a single floating-point value representing a color index. Internal glIndex commands are generated when the map is evaluated but the current index is not updated with the value of these glIndex commands.
GL_MAP1_COLOR_4	Each control point is four floating-point values representing red, green, blue, and alpha. Internal glColor4 commands are generated when the map is evaluated but the current color is not updated with the value of these glColor4 commands.
GL_MAP1_NORMAL	Each control point is three floating-point values representing the <i>x</i> , <i>y</i> , and <i>z</i> components of a normal vector. Internal glNormal commands are generated when the map is evaluated but the current normal is not updated with the value of these glNormal commands.
GL_MAP1_TEXTURE_COORD_1	Each control point is a single floating-point value representing the <i>s</i> texture coordinate. Internal glTexCoord1 commands are generated

when the map is evaluated but the current texture coordinates are not updated with the value of these **glTexCoord** commands.

- GL_MAP1_TEXTURE_COORD_2** Each control point is two floating-point values representing the s and t texture coordinates. Internal **glTexCoord2** commands are generated when the map is evaluated but the current texture coordinates are not updated with the value of these **glTexCoord** commands.
- GL_MAP1_TEXTURE_COORD_3** Each control point is three floating-point values representing the s, t, and r texture coordinates. Internal **glTexCoord3** commands are generated when the map is evaluated but the current texture coordinates are not updated with the value of these **glTexCoord** commands.
- GL_MAP1_TEXTURE_COORD_4** Each control point is four floating-point values representing the s, t, r, and q texture coordinates. Internal **glTexCoord4** commands are generated when the map is evaluated but the current texture coordinates are not updated with the value of these **glTexCoord** commands.

stride, *order*, and *points* define the array addressing for accessing the control points. *points* is the location of the first control point, which occupies one, two, three, or four contiguous memory locations, depending on which map is being defined. *order* is the number of control points in the array. *stride* specifies how many float or double locations to advance the internal memory pointer to reach the next control point.

NOTES

As is the case with all GL commands that accept pointers to

data, it is as if the contents of *points* were copied by **glMap1** before **glMap1** returns. Changes to the contents of *points* have no effect after **glMap1** is called.

ERRORS

GL_INVALID_ENUM is generated if *target* is not an accepted value.

GL_INVALID_VALUE is generated if *u1* is equal to *u2*.

GL_INVALID_VALUE is generated if *stride* is less than the number of values in a control point.

GL_INVALID_VALUE is generated if *order* is less than 1 or greater than the return value of **GL_MAX_EVAL_ORDER**.

GL_INVALID_OPERATION is generated if **glMap1** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGetMap

glGet with argument **GL_MAX_EVAL_ORDER**

glIsEnabled with argument **GL_MAP1_VERTEX_3**

glIsEnabled with argument **GL_MAP1_VERTEX_4**

glIsEnabled with argument **GL_MAP1_INDEX**

glIsEnabled with argument **GL_MAP1_COLOR_4**

glIsEnabled with argument **GL_MAP1_NORMAL**

glIsEnabled with argument **GL_MAP1_TEXTURE_COORD_1**

glIsEnabled with argument **GL_MAP1_TEXTURE_COORD_2**

glIsEnabled with argument **GL_MAP1_TEXTURE_COORD_3**

glIsEnabled with argument **GL_MAP1_TEXTURE_COORD_4**

SEE ALSO

glBegin, **glColor**, **glEnable**, **glEvalCoord**, **glEvalMesh**,
glEvalPoint, **glMap2**, **glMapGrid**, **glNormal**, **glTexCoord**,
glVertex

NAME

glMap2d, glMap2f - define a two-dimensional evaluator

C SPECIFICATION

```
void glMap2d( GLenum target,
              GLdouble u1,
              GLdouble u2,
              GLint ustride,
              GLint uorder,
              GLdouble v1,
              GLdouble v2,
              GLint vstride,
              GLint vorder,
              const GLdouble *points )

void glMap2f( GLenum target,
              GLfloat u1,
              GLfloat u2,
              GLint ustride,
              GLint uorder,
              GLfloat v1,
              GLfloat v2,
              GLint vstride,
              GLint vorder,
              const GLfloat *points )
```

PARAMETERS

- target* Specifies the kind of values that are generated by the evaluator. Symbolic constants **GL_MAP2_VERTEX_3**, **GL_MAP2_VERTEX_4**, **GL_MAP2_INDEX**, **GL_MAP2_COLOR_4**, **GL_MAP2_NORMAL**, **GL_MAP2_TEXTURE_COORD_1**, **GL_MAP2_TEXTURE_COORD_2**, **GL_MAP2_TEXTURE_COORD_3**, and **GL_MAP2_TEXTURE_COORD_4** are accepted.
- u1, u2* Specify a linear mapping of *u*, as presented to **glEvalCoord2**, to \wedge , one of the two variables that are evaluated by the equations specified by this command. Initially, *u1* is 0 and *u2* is 1.
- ustride* Specifies the number of floats or doubles between the beginning of control point *R_{ij}* and the beginning of control point *R_{ij+1}*, where *i* and *j* are the *u* and *v* control point indices,

respectively. This allows control points to be embedded in arbitrary data structures. The only constraint is that the values for a particular control point must occupy contiguous memory locations. The initial value of *ustride* is 0.

- uorder* Specifies the dimension of the control point array in the u axis. Must be positive. The initial value is 1.
- v1*, *v2* Specify a linear mapping of *v*, as presented to **glEvalCoord2**, to u , one of the two variables that are evaluated by the equations specified by this command. Initially, *v1* is 0 and *v2* is 1.
- vstride* Specifies the number of floats or doubles between the beginning of control point *R* and the beginning of control point *R_{ij}*, where *i* and *j* are the u and v control point **(indices)**, respectively. This allows control points to be embedded in arbitrary data structures. The only constraint is that the values for a particular control point must occupy contiguous memory locations. The initial value of *vstride* is 0.
- vorder* Specifies the dimension of the control point array in the v axis. Must be positive. The initial value is 1.
- points* Specifies a pointer to the array of control points.

DESCRIPTION

Evaluators provide a way to use polynomial or rational polynomial mapping to produce vertices, normals, texture coordinates, and colors. The values produced by an evaluator are sent on to further stages of GL processing just as if they had been presented using **glVertex**, **glNormal**, **glTexCoord**, and **glColor** commands, except that the generated values do not update the current normal, texture coordinates, or color.

All polynomial or rational polynomial splines of any degree (up to the maximum degree supported by the GL implementation) can be described using evaluators. These include almost all surfaces used in computer graphics, including B-spline surfaces, NURBS surfaces, Bezier

surfaces, and so on.

Evaluators define surfaces based on bivariate Bernstein polynomials. Define $p(u, v)$ as

$$p(u, v) = \sum_{i=0}^n \sum_{j=0}^m R_{ij} B_i(u) B_j(v)$$

where R_{ij} is a control point, $B_i(u)$ is the i th Bernstein polynomial of degree n ($uorder = n+1$)

$$B_i(u) = \binom{n}{i} u^i (1-u)^{n-i}$$

and $B_j(v)$ is the j th Bernstein polynomial of degree m ($vorder = m+1$)

$$B_j(v) = \binom{m}{j} v^j (1-v)^{m-j}$$

Recall that

$$\binom{n}{0} = 1 \text{ and } \binom{n}{0} = 1$$

glMap2 is used to define the basis and to specify what kind of values are produced. Once defined, a map can be enabled and disabled by calling **glEnable** and **glDisable** with the map name, one of the nine predefined values for *target*, described below. When **glEvalCoord2** presents values u and v , the bivariate Bernstein polynomials are evaluated using u and v , where

$$u = \frac{u_2 - u_1}{v_2 - v_1}$$

target is a symbolic constant that indicates what kind of control points are provided in *points*, and what output is generated when the map is evaluated. It can assume one of nine predefined values:

GL_MAP2_VERTEX_3

Each control point is three floating-point values representing x , y , and z . Internal **glVertex3**

commands are generated when the map is evaluated.

GL_MAP2_VERTEX_4

Each control point is four floating-point values representing *x*, *y*, *z*, and *w*. Internal **glVertex4** commands are generated when the map is evaluated.

GL_MAP2_INDEX

Each control point is a single floating-point value representing a color index. Internal **glIndex** commands are generated when the map is evaluated but the current index is not updated with the value of these **glIndex** commands.

GL_MAP2_COLOR_4

Each control point is four floating-point values representing red, green, blue, and alpha. Internal **glColor4** commands are generated when the map is evaluated but the current color is not updated with the value of these **glColor4** commands.

GL_MAP2_NORMAL

Each control point is three floating-point values representing the *x*, *y*, and *z* components of a normal vector. Internal **glNormal** commands are generated when the map is evaluated but the current normal is not updated with the value of these **glNormal** commands.

GL_MAP2_TEXTURE_COORD_1

Each control point is a single floating-point value representing the *s* texture coordinate. Internal **glTexCoord1** commands are generated when the map is evaluated but the current texture coordinates are not updated with the value of these **glTexCoord** commands.

GL_MAP2_TEXTURE_COORD_2

Each control point is two floating-point values representing

the s and t texture coordinates.
Internal

glTexCoord2 commands are generated when the map is evaluated but the current texture coordinates are not updated with the value of these **glTexCoord** commands.

GL_MAP2_TEXTURE_COORD_3 Each control point is three floating-point values representing the s, t, and r texture coordinates. Internal **glTexCoord3** commands are generated when the map is evaluated but the current texture coordinates are not updated with the value of these **glTexCoord** commands.

GL_MAP2_TEXTURE_COORD_4 Each control point is four floating-point values representing the s, t, r, and q texture coordinates. Internal **glTexCoord4** commands are generated when the map is evaluated but the current texture coordinates are not updated with the value of these **glTexCoord** commands.

ustride, *uorder*, *vstride*, *vorder*, and *points* define the array addressing for accessing the control points. *points* is the location of the first control point, which occupies one, two, three, or four contiguous memory locations, depending on which map is being defined. There are *uorder**xvorder* control points in the array. *ustride* specifies how many float or double locations are skipped to advance the internal memory pointer from control point R to control point R . *vstride* specifies how many float or double locations **siarej** skipped to advance the internal memory pointer from control point R to control point R . *ij*
i(j+1)

NOTES

As is the case with all GL commands that accept pointers to data, it is as if the contents of *points* were copied by **glMap2** before **glMap2** returns. Changes to the contents of *points* have no effect after **glMap2** is called.

Initially, **GL_AUTO_NORMAL** is enabled. If **GL_AUTO_NORMAL** is enabled, normal vectors are generated when either **GL_MAP2_VERTEX_3** or **GL_MAP2_VERTEX_4** is used to generate vertices.

ERRORS

GL_INVALID_ENUM is generated if *target* is not an accepted value.

GL_INVALID_VALUE is generated if *u1* is equal to *u2*, or if *v1* is equal to *v2*.

GL_INVALID_VALUE is generated if either *ustride* or *vstride* is less than the number of values in a control point.

GL_INVALID_VALUE is generated if either *uorder* or *vorder* is less than 1 or greater than the return value of **GL_MAX_EVAL_ORDER**.

GL_INVALID_OPERATION is generated if **glMap2** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGetMap

glGet with argument **GL_MAX_EVAL_ORDER**

glIsEnabled with argument **GL_MAP2_VERTEX_3**

glIsEnabled with argument **GL_MAP2_VERTEX_4**

glIsEnabled with argument **GL_MAP2_INDEX**

glIsEnabled with argument **GL_MAP2_COLOR_4**

glIsEnabled with argument **GL_MAP2_NORMAL**

glIsEnabled with argument **GL_MAP2_TEXTURE_COORD_1**

glIsEnabled with argument **GL_MAP2_TEXTURE_COORD_2**

glIsEnabled with argument **GL_MAP2_TEXTURE_COORD_3**

glIsEnabled with argument **GL_MAP2_TEXTURE_COORD_4**

SEE ALSO

glBegin, **glColor**, **glEnable**, **glEvalCoord**, **glEvalMesh**, **glEvalPoint**, **glMap1**, **glMapGrid**, **glNormal**, **glTexCoord**, **glVertex**

NAME

glMapGrid1d, glMapGrid1f, glMapGrid2d, glMapGrid2f - define a one- or two-dimensional mesh

C SPECIFICATION

```
void glMapGrid1d( GLint un,
                  GLdouble u1,
                  GLdouble u2 )
void glMapGrid1f( GLint un,
                  GLfloat u1,
                  GLfloat u2 )
void glMapGrid2d( GLint un,
                  GLdouble u1,
                  GLdouble u2,
                  GLint vn,
                  GLdouble v1,
                  GLdouble v2 )
void glMapGrid2f( GLint un,
                  GLfloat u1,
                  GLfloat u2,
                  GLint vn,
                  GLfloat v1,
                  GLfloat v2 )
```

PARAMETERS

un Specifies the number of partitions in the grid range interval [*u1*, *u2*]. Must be positive.

u1, *u2*
Specify the mappings for integer grid domain values *i*=0 and *i*=*un*.

vn Specifies the number of partitions in the grid range interval [*v1*, *v2*]
(**glMapGrid2** only).

v1, *v2*
Specify the mappings for integer grid domain values *j*=0 and *j*=*vn*
(**glMapGrid2** only).

DESCRIPTION

glMapGrid and **glEvalMesh** are used together to efficiently

generate and evaluate a series of evenly-spaced map domain values. **glEvalMesh** steps through the integer domain of a one- or two-dimensional grid, whose range is the domain of the evaluation maps specified by **glMap1** and **glMap2**.

glMapGrid1 and **glMapGrid2** specify the linear grid mappings between the *i* (or *i* and *j*) integer grid coordinates, to the *u* (or *u* and *v*) floating-point evaluation map coordinates. See **glMap1** and **glMap2** for details of how *u* and *v* coordinates are evaluated.

glMapGrid1 specifies a single linear mapping such that integer grid coordinate 0 maps exactly to *u1*, and integer grid coordinate *un* maps exactly to *u2*. All other integer grid coordinates *i* are mapped so that

$$u = i(u2-u1)/un + u1$$

glMapGrid2 specifies two such linear mappings. One maps integer grid coordinate *i*=0 exactly to *u1*, and integer grid coordinate *i*=*un* exactly to *u2*. The other maps integer grid coordinate *j*=0 exactly to *v1*, and integer grid coordinate *j*=*vn* exactly to *v2*. Other integer grid coordinates *i* and *j* are mapped such that

$$u = i(u2-u1)/un + u1$$

$$v = j(v2-v1)/vn + v1$$

The mappings specified by **glMapGrid** are used identically by **glEvalMesh** and **glEvalPoint**.

ERRORS

GL_INVALID_VALUE is generated if either *un* or *vn* is not positive.

GL_INVALID_OPERATION is generated if **glMapGrid** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_MAP1_GRID_DOMAIN**

glGet with argument **GL_MAP2_GRID_DOMAIN**

glGet with argument **GL_MAP1_GRID_SEGMENTS**

glGet with argument **GL_MAP2_GRID_SEGMENTS**

SEE ALSO

glEvalCoord, glEvalMesh, glEvalPoint, glMap1, glMap2

NAME

glMaterialf, glMateriali, glMaterialfv, glMaterialiv -
specify material parameters for the lighting model

C SPECIFICATION

```
void glMaterialf( GLenum face,  
                  GLenum pname,  
                  GLfloat param )  
  
void glMateriali( GLenum face,  
                  GLenum pname,  
                  GLint param )
```

PARAMETERS

face Specifies which face or faces are being updated. Must be one of **GL_FRONT**, **GL_BACK**, or **GL_FRONT_AND_BACK**.

pname Specifies the single-valued material parameter of the face or faces that is being updated. Must be **GL_SHININESS**.

param Specifies the value that parameter **GL_SHININESS** will be set to.

C SPECIFICATION

```
void glMaterialfv( GLenum face,  
                   GLenum pname,  
                   const GLfloat *params )  
  
void glMaterialiv( GLenum face,  
                   GLenum pname,  
                   const GLint *params )
```

PARAMETERS

face Specifies which face or faces are being updated. Must be one of **GL_FRONT**, **GL_BACK**, or **GL_FRONT_AND_BACK**.

pname Specifies the material parameter of the face or faces that is being updated. Must be one of **GL_AMBIENT**, **GL_DIFFUSE**, **GL_SPECULAR**, **GL_EMISSION**, **GL_SHININESS**, **GL_AMBIENT_AND_DIFFUSE**, or **GL_COLOR_INDEXES**.

params

Specifies a pointer to the value or values that *pname* will be set to.

DESCRIPTION

glMaterial assigns values to material parameters. There are two matched sets of material parameters. One, the *front-facing* set, is used to shade points, lines, bitmaps, and all polygons (when two-sided lighting is disabled), or just front-facing polygons (when two-sided lighting is enabled). The other set, *back-facing*, is used to shade back-facing polygons only when two-sided lighting is enabled. Refer to the **glLightModel** reference page for details concerning one- and two-sided lighting calculations.

glMaterial takes three arguments. The first, *face*, specifies whether the **GL_FRONT** materials, the **GL_BACK** materials, or both **GL_FRONT_AND_BACK** materials will be modified. The second, *pname*, specifies which of several parameters in one or both sets will be modified. The third, *params*, specifies what value or values will be assigned to the specified parameter.

Material parameters are used in the lighting equation that is optionally applied to each vertex. The equation is discussed in the **glLightModel** reference page. The parameters that can be specified using **glMaterial**, and their interpretations by the lighting equation, are as follows:

GL_AMBIENT

params contains four integer or floating-point values that specify the ambient RGBA reflectance of the material. Integer values are mapped linearly such that the most positive representable value maps to 1.0, and the most negative representable value maps to -1.0. Floating-point values are mapped directly. Neither integer nor floating-point values are clamped. The initial ambient reflectance for both front- and back-facing materials is (0.2, 0.2, 0.2, 1.0).

GL_DIFFUSE

params contains four integer or floating-point values that specify the diffuse RGBA reflectance of the

material. Integer values are mapped linearly such that the most positive representable value maps to 1.0, and the most negative representable value maps to -1.0. Floating-point values are mapped directly. Neither integer nor floating-point values are clamped. The initial diffuse reflectance for both front- and back-facing materials is (0.8, 0.8, 0.8, 1.0).

GL_SPECULAR

params contains four integer or floating-point values that specify the specular RGBA reflectance of the material. Integer values are mapped linearly such that the most positive representable value maps to 1.0, and the most negative representable value maps to -1.0. Floating-point values are mapped directly. Neither integer nor floating-point values are clamped. The initial specular reflectance for both front- and back-facing materials is (0, 0, 0, 1).

GL_EMISSION

params contains four integer or floating-point values that specify the RGBA emitted light intensity of the material. Integer values are mapped linearly such that the most positive representable value maps to 1.0, and the most negative representable value maps to -1.0. Floating-point values are mapped directly. Neither integer nor floating-point values are clamped. The initial emission intensity for both front- and back-facing materials is (0, 0, 0, 1).

GL_SHININESS

params is a single integer or floating-point value that specifies the RGBA specular exponent of the material. Integer and floating-point values are mapped directly. Only values in the range [0,128] are accepted. The initial specular exponent for both front- and

back-facing materials is 0.

GL_AMBIENT_AND_DIFFUSE

Equivalent to calling **glMaterial** twice with the same parameter values, once with **GL_AMBIENT** and once with **GL_DIFFUSE**.

GL_COLOR_INDEXES

params contains three integer or floating-point values specifying the color indices for ambient, diffuse, and specular lighting. These three values, and **GL_SHININESS**, are the only material values used by the color index mode lighting equation. Refer to the **glLightModel** reference page for a discussion of color index lighting.

NOTES

The material parameters can be updated at any time. In particular, **glMaterial** can be called between a call to **glBegin** and the corresponding call to **glEnd**. If only a single material parameter is to be changed per vertex, however, **glColorMaterial** is preferred over **glMaterial** (see **glColorMaterial**).

ERRORS

GL_INVALID_ENUM is generated if either *face* or *pname* is not an accepted value.

GL_INVALID_VALUE is generated if a specular exponent outside the range [0,128] is specified.

ASSOCIATED GETS

glGetMaterial

SEE ALSO

glColorMaterial, **glLight**, **glLightModel**

NAME

glMatrixMode - specify which matrix is the current matrix

C SPECIFICATION

```
void glMatrixMode( GLenum mode )
```

PARAMETERS

mode Specifies which matrix stack is the target for subsequent matrix operations. Three values are accepted: **GL_MODELVIEW**, **GL_PROJECTION**, and **GL_TEXTURE**. The initial value is **GL_MODELVIEW**.

DESCRIPTION

glMatrixMode sets the current matrix mode. *mode* can assume one of three values:

GL_MODELVIEW	Applies subsequent matrix operations to the modelview matrix stack.
GL_PROJECTION	Applies subsequent matrix operations to the projection matrix stack.
GL_TEXTURE	Applies subsequent matrix operations to the texture matrix stack.

To find out which matrix stack is currently the target of all matrix operations, call **glGet** with argument **GL_MATRIX_MODE**. The initial value is **GL_MODELVIEW**.

ERRORS

GL_INVALID_ENUM is generated if *mode* is not an accepted value.

GL_INVALID_OPERATION is generated if **glMatrixMode** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_MATRIX_MODE**

SEE ALSO

`glLoadMatrix`, `glPushMatrix`

NAME

glMultMatrixd, **glMultMatrixf** - multiply the current matrix with the specified matrix

C SPECIFICATION

```
void glMultMatrixd( const GLdouble *m )
void glMultMatrixf( const GLfloat *m )
```

PARAMETERS

m Points to 16 consecutive values that are used as the elements of a 4x4 column-major matrix.

DESCRIPTION

glMultMatrix multiplies the current matrix with the one specified using *m*, and replaces the current matrix with the product.

The current matrix is determined by the current matrix mode (see **glMatrixMode**). It is either the projection matrix, modelview matrix, or the texture matrix.

EXAMPLES

If the current matrix is *C*, and the coordinates to be transformed are, *v*=(*v*[0],*v*[1],*v*[2],*v*[3]). Then the current transformation is *C* x *v*, or

$$\begin{pmatrix} c[0] & c[4] & c[8] & c[12] \\ c[1] & c[5] & c[9] & c[13] \\ c[2] & c[6] & c[10] & c[14] \\ c[3] & c[7] & c[11] & c[15] \end{pmatrix} \begin{pmatrix} v[0] \\ v[1] \\ v[2] \\ v[3] \end{pmatrix} = \begin{pmatrix} v[0] \\ v[1] \\ v[2] \\ v[3] \end{pmatrix}$$

Calling **glMultMatrix** with an argument of *m*=*m*[0],*m*[1],...,*m*[15] replaces the current transformation with (*C* x *M*) x *v*, or

$$\begin{pmatrix} c[0] & c[4] & c[8] & c[12] \\ c[1] & c[5] & c[9] & c[13] \\ c[2] & c[6] & c[10] & c[14] \\ c[3] & c[7] & c[11] & c[15] \end{pmatrix} \begin{pmatrix} m[0] & m[4] & m[8] & m[12] \\ m[1] & m[5] & m[9] & m[13] \\ m[2] & m[6] & m[10] & m[14] \\ m[3] & m[7] & m[11] & m[15] \end{pmatrix} \begin{pmatrix} v[0] \\ v[1] \\ v[2] \\ v[3] \end{pmatrix} = \begin{pmatrix} v[0] \\ v[1] \\ v[2] \\ v[3] \end{pmatrix}$$

Where 'x' denotes matrix multiplication, and *v* is represented as a 4 x 1 matrix.

NOTES

While the elements of the matrix may be specified with

single or double precision, the GL may store or operate on these values in less than single precision.

In many computer languages 4x4 arrays are represented in row-major order. The transformations just described represent these matrices in column-major order. The order of the multiplication is important. For example, if the current transformation is a rotation, and **glMultMatrix** is called with a translation matrix, the translation is done directly on the coordinates to be transformed, while the rotation is done on the results of that translation.

ERRORS

GL_INVALID_OPERATION is generated if **glMultMatrix** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_MATRIX_MODE**

glGet with argument **GL_MODELVIEW_MATRIX**

glGet with argument **GL_PROJECTION_MATRIX**

glGet with argument **GL_TEXTURE_MATRIX**

SEE ALSO

glLoadIdentity, glLoadMatrix, glMatrixMode, glPushMatrix

NAME

glNewList, glEndList - create or replace a display list

C SPECIFICATION

```
void glNewList( GLuint list,
                GLenum mode )
```

PARAMETERS

list Specifies the display-list name.

mode Specifies the compilation mode, which can be **GL_COMPILE** or **GL_COMPILE_AND_EXECUTE**.

C SPECIFICATION

```
void glEndList( void )
```

DESCRIPTION

Display lists are groups of GL commands that have been stored for subsequent execution. Display lists are created with **glNewList**. All subsequent commands are placed in the display list, in the order issued, until **glEndList** is called.

glNewList has two arguments. The first argument, *list*, is a positive integer that becomes the unique name for the display list. Names can be created and reserved with **glGenLists** and tested for uniqueness with **glIsList**. The second argument, *mode*, is a symbolic constant that can assume one of two values:

GL_COMPILE	Commands are merely compiled.
GL_COMPILE_AND_EXECUTE	Commands are executed as they are compiled into the display list.

Certain commands are not compiled into the display list but are executed immediately, regardless of the display-list mode. These commands are **glColorPointer**, **glDeleteLists**, **glDisableClientState**, **glEdgeFlagPointer**, **glEnableClientState**, **glFeedbackBuffer**, **glFinish**, **glFlush**, **glGenLists**, **glIndexPointer**, **glInterleavedArrays**,

glIsEnabled, **glIsList**, **glNormalPointer**, **glPopClientAttrib**, **glPixelStore**, **glPushClientAttrib**, **glReadPixels**, **glRenderMode**, **glSelectBuffer**, **glTexCoordPointer**, **glVertexPointer**, and all of the **glGet** commands.

Similarly, **glTexImage2D** and **glTexImage1D** are executed immediately and not compiled into the display list when their first argument is **GL_PROXY_TEXTURE_2D** or **GL_PROXY_TEXTURE_1D**, respectively.

When **glEndList** is encountered, the display-list definition is completed by associating the list with the unique name *list* (specified in the **glNewList** command). If a display list with name *list* already exists, it is replaced only when **glEndList** is called.

NOTES

glCallList and **glCallLists** can be entered into display lists. Commands in the display list or lists executed by **glCallList** or **glCallLists** are not included in the display list being created, even if the list creation mode is **GL_COMPILE_AND_EXECUTE**.

A display list is just a group of commands and arguments, so errors generated by commands in a display list must be generated when the list is executed. If the list is created in **GL_COMPILE** mode, errors are not generated until the list is executed.

ERRORS

GL_INVALID_VALUE is generated if *list* is 0.

GL_INVALID_ENUM is generated if *mode* is not an accepted value.

GL_INVALID_OPERATION is generated if **glEndList** is called without a preceding **glNewList**, or if **glNewList** is called while a display list is being defined.

GL_INVALID_OPERATION is generated if **glNewList** or **glEndList** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

GL_OUT_OF_MEMORY is generated if there is insufficient memory to compile the display list. If the GL version is 1.1 or greater, no change is made to the previous contents of

the display list, if any, and no other change is made to the GL state. (It is as if no attempt had been made to create the new display list.)

ASSOCIATED GETS

glIsList

glGet with argument **GL_LIST_INDEX**

glGet with argument **GL_LIST_MODE**

SEE ALSO

glCallList, glCallLists, glDeleteLists, glGenLists

NAME

glNormal3b, **glNormal3d**, **glNormal3f**, **glNormal3i**, **glNormal3s**,
glNormal3bv, **glNormal3dv**, **glNormal3fv**, **glNormal3iv**,
glNormal3sv - set the current normal vector

C SPECIFICATION

```
void glNormal3b( GLbyte nx,  
                 GLbyte ny,  
                 GLbyte nz )  
void glNormal3d( GLdouble nx,  
                 GLdouble ny,  
                 GLdouble nz )  
void glNormal3f( GLfloat nx,  
                 GLfloat ny,  
                 GLfloat nz )  
void glNormal3i( GLint nx,  
                 GLint ny,  
                 GLint nz )  
void glNormal3s( GLshort nx,  
                 GLshort ny,  
                 GLshort nz )
```

PARAMETERS

nx, ny, nz

Specify the x, y, and z coordinates of the new current normal. The initial value of the current normal is the unit vector, (0, 0, 1).

C SPECIFICATION

```
void glNormal3bv( const GLbyte *v )  
void glNormal3dv( const GLdouble *v )  
void glNormal3fv( const GLfloat *v )  
void glNormal3iv( const GLint *v )  
void glNormal3sv( const GLshort *v )
```

PARAMETERS

v Specifies a pointer to an array of three elements: the x, y, and z coordinates of the new current normal.

DESCRIPTION

The current normal is set to the given coordinates whenever **glNormal** is issued. Byte, short, or integer arguments are

converted to floating-point format with a linear mapping that maps the most positive representable integer value to 1.0, and the most negative representable integer value to -1.0.

Normals specified with **glNormal** need not have unit length. If normalization is enabled, then normals specified with **glNormal** are normalized after transformation. To enable and disable normalization, call **glEnable** and **glDisable** with the argument **GL_NORMALIZE**. Normalization is initially disabled.

NOTES

The current normal can be updated at any time. In particular, **glNormal** can be called between a call to **glBegin** and the corresponding call to **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_CURRENT_NORMAL**
glIsEnabled with argument **GL_NORMALIZE**

SEE ALSO

glBegin, **glColor**, **glIndex**, **glNormalPointer**, **glTexCoord**,
glVertex

NAME

glNormalPointer - define an array of normals

C SPECIFICATION

```
void glNormalPointer( GLenum type,  
                     GLsizei stride,  
                     const GLvoid *pointer )
```

PARAMETERS

type Specifies the data type of each coordinate in the array. Symbolic constants **GL_BYTE**, **GL_SHORT**, **GL_INT**, **GL_FLOAT**, and **GL_DOUBLE** are accepted. The initial value is **GL_FLOAT**.

stride Specifies the byte offset between consecutive normals. If *stride* is 0- the initial value-the normals are understood to be tightly packed in the array.

pointer Specifies a pointer to the first coordinate of the first normal in the array.

DESCRIPTION

glNormalPointer specifies the location and data format of an array of normals to use when rendering. *type* specifies the data type of the normal coordinates and *stride* gives the byte stride from one normal to the next, allowing vertexes and attributes to be packed into a single array or stored in separate arrays. (Single-array storage may be more efficient on some implementations; see **glInterleavedArrays**.) When a normal array is specified, *type*, *stride*, and *pointer* are saved as client-side state.

To enable and disable the normal array, call **glEnableClientState** and **glDisableClientState** with the argument **GL_NORMAL_ARRAY**. If enabled, the normal array is used when **glDrawArrays**, **glDrawElements**, or **glArrayElement** is called.

Use **glDrawArrays** to construct a sequence of primitives (all of the same type) from prespecified vertex and vertex attribute arrays. Use **glArrayElement** to specify primitives by indexing vertexes and vertex attributes and

glDrawElements to construct a sequence of primitives by indexing vertexes and vertex attributes.

NOTES

glNormalPointer is available only if the GL version is 1.1 or greater.

The normal array is initially disabled and isn't accessed when **glArrayElement**, **glDrawElements**, or **glDrawArrays** is called.

Execution of **glNormalPointer** is not allowed between **glBegin** and the corresponding **glEnd**, but an error may or may not be generated. If an error is not generated, the operation is undefined.

glNormalPointer is typically implemented on the client side.

Since the normal array parameters are client-side state, they are not saved or restored by **glPushAttrib** and **glPopAttrib**. Use **glPushClientAttrib** and **glPopClientAttrib** instead.

ERRORS

GL_INVALID_ENUM is generated if *type* is not an accepted value.

GL_INVALID_VALUE is generated if *stride* is negative.

ASSOCIATED GETS

glIsEnabled with argument **GL_NORMAL_ARRAY**

glGet with argument **GL_NORMAL_ARRAY_TYPE**

glGet with argument **GL_NORMAL_ARRAY_STRIDE**

glGetPointerv with argument **GL_NORMAL_ARRAY_POINTER**

SEE ALSO

glArrayElement, **glColorPointer**, **glDrawArrays**,
glDrawElements, **glEdgeFlagPointer**, **glEnable**, **glGetPointerv**,
glIndexPointer, **glInterleavedArrays**, **glPopClientAttrib**,
glPushClientAttrib, **glTexCoordPointer**, **glVertexPointer**

NAME

glOrtho - multiply the current matrix with an orthographic matrix

C SPECIFICATION

```
void glOrtho( GLdouble left,
               GLdouble right,
               GLdouble bottom,
               GLdouble top,
               GLdouble zNear,
               GLdouble zFar )
```

PARAMETERS

left, *right* Specify the coordinates for the left and right vertical clipping planes.

bottom, *top* Specify the coordinates for the bottom and top horizontal clipping planes.

zNear, *zFar* Specify the distances to the nearer and farther depth clipping planes. These values are negative if the plane is to be behind the viewer.

DESCRIPTION

glOrtho describes a transformation that produces a parallel projection. The current matrix (see **glMatrixMode**) is multiplied by this matrix and the result replaces the current matrix, as if **glMultMatrix** were called with the following matrix as its argument:

$$\begin{pmatrix} \frac{\text{right-left}}{t} & 0 & 0 & t \\ 0 & \frac{\text{top-bottom}}{ty} & 0 & ty \\ 0 & 0 & \frac{\text{zFar-zNear}}{z} & 1 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

where

$$t = -\frac{\text{zFar-zNear}}{\text{zNear}}$$

$$\begin{array}{rcl}
 x & & \text{right-left} \\
 t & = & -\frac{\quad}{\quad} \\
 y & & \text{top-bottom} \\
 t & = & -\frac{\quad}{\quad} \\
 z & & z\text{Far}-z\text{Near}
 \end{array}$$

Typically, the matrix mode is **GL_PROJECTION**, and (*left*, *bottom*, *-zNear*) and (*right*, *top*, *-zNear*) specify the points on the near clipping plane that are mapped to the lower left and upper right corners of the window, respectively, assuming that the eye is located at (0, 0, 0). *-zFar* specifies the location of the far clipping plane. Both *zNear* and *zFar* can be either positive or negative.

Use **glPushMatrix** and **glPopMatrix** to save and restore the current matrix stack.

ERRORS

GL_INVALID_OPERATION is generated if **glOrtho** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_MATRIX_MODE**
glGet with argument **GL_MODELVIEW_MATRIX**
glGet with argument **GL_PROJECTION_MATRIX**
glGet with argument **GL_TEXTURE_MATRIX**

SEE ALSO

glFrustum, **glMatrixMode**, **glMultMatrix**, **glPushMatrix**, **glViewport**

NAME

glPassThrough - place a marker in the feedback buffer

C SPECIFICATION

```
void glPassThrough( GLfloat token )
```

PARAMETERS

token Specifies a marker value to be placed in the feedback buffer following a **GL_PASS_THROUGH_TOKEN**.

DESCRIPTION

Feedback is a GL render mode. The mode is selected by calling **glRenderMode** with **GL_FEEDBACK**. When the GL is in feedback mode, no pixels are produced by rasterization. Instead, information about primitives that would have been rasterized is fed back to the application using the GL. See the **glFeedbackBuffer** reference page for a description of the feedback buffer and the values in it.

glPassThrough inserts a user-defined marker in the feedback buffer when it is executed in feedback mode. *token* is returned as if it were a primitive; it is indicated with its own unique identifying value: **GL_PASS_THROUGH_TOKEN**. The order of **glPassThrough** commands with respect to the specification of graphics primitives is maintained.

NOTES

glPassThrough is ignored if the GL is not in feedback mode.

ERRORS

GL_INVALID_OPERATION is generated if **glPassThrough** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_RENDER_MODE**

SEE ALSO

glFeedbackBuffer, **glRenderMode**

NAME

glPixelMapfv, glPixelMapuiv, glPixelMapusv - set up pixel transfer maps

C SPECIFICATION

```
void glPixelMapfv( GLenum map,
                   GLsizei mapsize,
                   const GLfloat *values )
void glPixelMapuiv( GLenum map,
                   GLsizei mapsize,
                   const GLuint *values )
void glPixelMapusv( GLenum map,
                   GLsizei mapsize,
                   const GLushort *values )
```

PARAMETERS

map Specifies a symbolic map name. Must be one of the following: **GL_PIXEL_MAP_I_TO_I**, **GL_PIXEL_MAP_S_TO_S**, **GL_PIXEL_MAP_I_TO_R**, **GL_PIXEL_MAP_I_TO_G**, **GL_PIXEL_MAP_I_TO_B**, **GL_PIXEL_MAP_I_TO_A**, **GL_PIXEL_MAP_R_TO_R**, **GL_PIXEL_MAP_G_TO_G**, **GL_PIXEL_MAP_B_TO_B**, or **GL_PIXEL_MAP_A_TO_A**.

mapsize Specifies the size of the map being defined.

values Specifies an array of *mapsize* values.

DESCRIPTION

glPixelMap sets up translation tables, or *maps*, used by **glCopyPixels**, **glCopyTexImage1D**, **glCopyTexImage2D**, **glCopyTexSubImage1D**, **glCopyTexSubImage2D**, **glDrawPixels**, **glReadPixels**, **glTexImage1D**, **glTexImage2D**, **glTexSubImage1D**, and **glTexSubImage2D**. Use of these maps is described completely in the **glPixelTransfer** reference page, and partly in the reference pages for the pixel and texture image commands. Only the specification of the maps is described in this reference page.

map is a symbolic map name, indicating one of ten maps to set. *mapsize* specifies the number of entries in the map, and *values* is a pointer to an array of *mapsize* map values.

The ten maps are as follows:

GL_PIXEL_MAP_I_TO_I	Maps color indices to color indices.
GL_PIXEL_MAP_S_TO_S	Maps stencil indices to stencil indices.
GL_PIXEL_MAP_I_TO_R	Maps color indices to red components.

GL_PIXEL_MAP_I_TO_G	Maps color indices to green components.
GL_PIXEL_MAP_I_TO_B	Maps color indices to blue components.
GL_PIXEL_MAP_I_TO_A	Maps color indices to alpha components.
GL_PIXEL_MAP_R_TO_R	Maps red components to red components.
GL_PIXEL_MAP_G_TO_G	Maps green components to green components.
GL_PIXEL_MAP_B_TO_B	Maps blue components to blue components.
GL_PIXEL_MAP_A_TO_A	Maps alpha components to alpha components.

The entries in a map can be specified as single-precision floating-point numbers, unsigned short integers, or unsigned long integers. Maps that store color component values (all but **GL_PIXEL_MAP_I_TO_I** and **GL_PIXEL_MAP_S_TO_S**) retain their values in floating-point format, with unspecified mantissa and exponent sizes. Floating-point values specified by **glPixelMapfv** are converted directly to the internal floating-point format of these maps, then clamped to the range [0,1]. Unsigned integer values specified by **glPixelMapusv** and **glPixelMapuiv** are converted linearly such that the largest representable integer maps to 1.0, and 0 maps to 0.0.

Maps that store indices, **GL_PIXEL_MAP_I_TO_I** and **GL_PIXEL_MAP_S_TO_S**, retain their values in fixed-point format, with an unspecified number of bits to the right of the binary point. Floating-point values specified by **glPixelMapfv** are converted directly to the internal fixed-point format of these maps. Unsigned integer values specified by **glPixelMapusv** and **glPixelMapuiv** specify integer values, with all 0's to the right of the binary point.

The following table shows the initial sizes and values for each of the maps. Maps that are indexed by either color or stencil indices must have *mapsize* = 2n for some n or the results are undefined. The maximum allowable size for each map depends on the implementation and can be determined by calling **glGet** with argument **GL_MAX_PIXEL_MAP_TABLE**. The single maximum applies to all maps; it is at least 32.

	<i>map</i>	<i>lookup index</i>	<i>lookup value</i>	<i>initial size</i>	<i>initial value</i>
--	------------	---------------------	---------------------	---------------------	----------------------

<code>GL_PIXEL_MAP_I_TO_I</code>	color index	color index	1	0
<code>GL_PIXEL_MAP_S_TO_S</code>	stencil index	stencil index	1	0
<code>GL_PIXEL_MAP_I_TO_R</code>	color index	R	1	0
<code>GL_PIXEL_MAP_I_TO_G</code>	color index	G	1	0
<code>GL_PIXEL_MAP_I_TO_B</code>	color index	B	1	0
<code>GL_PIXEL_MAP_I_TO_A</code>	color index	A	1	0
<code>GL_PIXEL_MAP_R_TO_R</code>	R	R	1	0
<code>GL_PIXEL_MAP_G_TO_G</code>	G	G	1	0
<code>GL_PIXEL_MAP_B_TO_B</code>	B	B	1	0
<code>GL_PIXEL_MAP_A_TO_A</code>	A	A	1	0

ERRORS

`GL_INVALID_ENUM` is generated if *map* is not an accepted value.

`GL_INVALID_VALUE` is generated if *mapsize* is less than one or larger than `GL_MAX_PIXEL_MAP_TABLE`.

`GL_INVALID_VALUE` is generated if *map* is `GL_PIXEL_MAP_I_TO_I`, `GL_PIXEL_MAP_S_TO_S`, `GL_PIXEL_MAP_I_TO_R`, `GL_PIXEL_MAP_I_TO_G`, `GL_PIXEL_MAP_I_TO_B`, or `GL_PIXEL_MAP_I_TO_A`, and *mapsize* is not a power of two.

`GL_INVALID_OPERATION` is generated if `glPixelMap` is executed between the execution of `glBegin` and the corresponding execution of `glEnd`.

ASSOCIATED GETS

`glGetPixelMap`

`glGet` with argument `GL_PIXEL_MAP_I_TO_I_SIZE`
`glGet` with argument `GL_PIXEL_MAP_S_TO_S_SIZE`
`glGet` with argument `GL_PIXEL_MAP_I_TO_R_SIZE`
`glGet` with argument `GL_PIXEL_MAP_I_TO_G_SIZE`
`glGet` with argument `GL_PIXEL_MAP_I_TO_B_SIZE`
`glGet` with argument `GL_PIXEL_MAP_I_TO_A_SIZE`
`glGet` with argument `GL_PIXEL_MAP_R_TO_R_SIZE`
`glGet` with argument `GL_PIXEL_MAP_G_TO_G_SIZE`
`glGet` with argument `GL_PIXEL_MAP_B_TO_B_SIZE`
`glGet` with argument `GL_PIXEL_MAP_A_TO_A_SIZE`
`glGet` with argument `GL_MAX_PIXEL_MAP_TABLE`

SEE ALSO

`glCopyPixels`, `glCopyTexImage1D`, `glCopyTexImage2D`,

glCopyTexSubImage1D, glCopyTexSubImage2D, glDrawPixels,
glPixelStore, glPixelTransfer, glReadPixels, glTexImage1D,
glTexImage2D, glTexSubImage1D, glTexSubImage2D

NAME

glPixelStoref, glPixelStorei - set pixel storage modes

C SPECIFICATION

```
void glPixelStoref( GLenum pname,  
                   GLfloat param )  
void glPixelStorei( GLenum pname,  
                   GLint param )
```

PARAMETERS

pname Specifies the symbolic name of the parameter to be set. Six values affect the packing of pixel data into memory: **GL_PACK_SWAP_BYTES**, **GL_PACK_LSB_FIRST**, **GL_PACK_ROW_LENGTH**, **GL_PACK_SKIP_PIXELS**, **GL_PACK_SKIP_ROWS**, and **GL_PACK_ALIGNMENT**. Six more affect the unpacking of pixel data from memory: **GL_UNPACK_SWAP_BYTES**, **GL_UNPACK_LSB_FIRST**, **GL_UNPACK_ROW_LENGTH**, **GL_UNPACK_SKIP_PIXELS**, **GL_UNPACK_SKIP_ROWS**, and **GL_UNPACK_ALIGNMENT**.

param Specifies the value that *pname* is set to.

DESCRIPTION

glPixelStore sets pixel storage modes that affect the operation of subsequent **glDrawPixels** and **glReadPixels** as well as the unpacking of polygon stipple patterns (see **glPolygonStipple**), bitmaps (see **glBitmap**), and texture patterns (see **glTexImage1D**, **glTexImage2D**, **glTexSubImage1D**, and **glTexSubImage2D**).

pname is a symbolic constant indicating the parameter to be set, and *param* is the new value. Six of the twelve storage parameters affect how pixel data is returned to client memory, and are therefore significant only for **glReadPixels** commands. They are as follows:

GL_PACK_SWAP_BYTES

If true, byte ordering for multibyte color components, depth components, color indices, or stencil indices is reversed. That is, if a four-byte component consists of bytes *b* , *b* , *b* , *b* , it is stored in memory as *b* , *b* , ***b*** , ***b*** if **GL_PACK_SWAP_BYTES** is true.³ **GL_PACK_SWAP_BYTES** has no effect on the memory order of components

within a pixel, only on the order of bytes within components or indices. For example, the three components of a **GL_RGB** format pixel are always stored with red first, green second, and blue third, regardless of the value of **GL_PACK_SWAP_BYTES**.

GL_PACK_LSB_FIRST

If true, bits are ordered within a byte from least significant to most significant; otherwise, the first bit in each byte is the most significant one. This parameter is significant for bitmap data only.

GL_PACK_ROW_LENGTH

If greater than 0, **GL_PACK_ROW_LENGTH** defines the number of pixels in a row. If the first pixel of a row is placed at location p in memory, then the location of the first pixel of the next row is obtained by skipping

$$k = \begin{pmatrix} nl & s > a \\ _ & s < a \\ s & a \end{pmatrix}$$

components or indices, where n is the number of components or indices in a pixel, l is the number of pixels in a row (**GL_PACK_ROW_LENGTH** if it is greater than 0, the width argument to the pixel routine otherwise), a is the value of **GL_PACK_ALIGNMENT**, and s is the size, in bytes, of a single component (if $a < s$, then it is as if $a = s$). In the case of 1-bit values, the location of the next row is obtained by skipping

$$k = \begin{pmatrix} 8a & _ \\ 8a \end{pmatrix}$$

components or indices.

The word *component* in this description refers to the nonindex values red, green, blue, alpha, and depth. Storage format **GL_RGB**, for example, has three components per pixel: first red, then green, and finally blue.

GL_PACK_SKIP_PIXELS and **GL_PACK_SKIP_ROWS**

These values are provided as a convenience to the programmer; they provide no functionality that cannot be duplicated simply by incrementing the pointer passed to **glReadPixels**. Setting **GL_PACK_SKIP_PIXELS** to *i* is equivalent to incrementing the pointer by *i* components or indices, where *n* is the number of components or indices in each pixel. Setting **GL_PACK_SKIP_ROWS** to *j* is equivalent to incrementing the pointer by *jk* components or indices, where *k* is the number of components or indices per row, as just computed in the **GL_PACK_ROW_LENGTH** section.

GL_PACK_ALIGNMENT

Specifies the alignment requirements for the start of each pixel row in memory. The allowable values are 1 (byte-alignment), 2 (rows aligned to even-numbered bytes), 4 (word-alignment), and 8 (rows start on double-word boundaries).

The other six of the twelve storage parameters affect how pixel data is read from client memory. These values are significant for **glDrawPixels**, **glTexImage1D**, **glTexImage2D**, **glTexSubImage1D**, **glTexSubImage2D**, **glBitmap**, and **glPolygonStipple**. They are as follows:

GL_UNPACK_SWAP_BYTES

If true, byte ordering for multibyte color components, depth components, color indices, or stencil indices is reversed. That is, if a four-byte component consists of bytes *b₀*, *b₁*, *b₂*, *b₃*, it is taken from memory as *b₃*, *b₂*, *b₁*, *b₀* if **GL_UNPACK_SWAP_BYTES** is true. 3

GL_UNPACK_SWAP_BYTES has no effect on the memory order of components within a pixel, only on the order of bytes within components or indices. For example, the three components of a **GL_RGB** format pixel are always stored with red first, green second, and blue third, regardless of the value of **GL_UNPACK_SWAP_BYTES**.

GL_UNPACK_LSB_FIRST

If true, bits are ordered within a byte from least significant to most significant; otherwise, the first bit in each byte is the most significant one. This is relevant only for bitmap data.

GL_UNPACK_ROW_LENGTH

If greater than 0, **GL_UNPACK_ROW_LENGTH** defines the

number of pixels in a row. If the first pixel of a row is placed at location p in memory, then the location of the first pixel of the next row is obtained by skipping

$$k = \begin{pmatrix} nl & s > a \\ _ & s < a \\ s & a \end{pmatrix}$$

components or indices, where n is the number of components or indices in a pixel, l is the number of pixels in a row (**GL_UNPACK_ROW_LENGTH** if it is greater than 0, the width argument to the pixel routine otherwise), a is the value of **GL_UNPACK_ALIGNMENT**, and s is the size, in bytes, of a single component (if $a < s$, then it is as if $a = s$). In the case of 1-bit values, the location of the next row is obtained by skipping

$$k = \begin{pmatrix} 8a & _ \\ 8a \end{pmatrix}$$

components or indices.

The word *component* in this description refers to the nonindex values red, green, blue, alpha, and depth. Storage format **GL_RGB**, for example, has three components per pixel: first red, then green, and finally blue.

GL_UNPACK_SKIP_PIXELS and GL_UNPACK_SKIP_ROWS

These values are provided as a convenience to the programmer; they provide no functionality that cannot be duplicated by incrementing the pointer passed to **glDrawPixels**, **glTexImage1D**, **glTexImage2D**, **glTexSubImage1D**, **glTexSubImage2D**, **glBitmap**, or **glPolygonStipple**. Setting **GL_UNPACK_SKIP_PIXELS** to i is equivalent to incrementing the pointer by in components or indices, where n is the number of components or indices in each pixel. Setting **GL_UNPACK_SKIP_ROWS** to j is equivalent to incrementing the pointer by jk components or indices, where k is the number of components or indices per row, as just computed in the **GL_UNPACK_ROW_LENGTH** section.

GL_UNPACK_ALIGNMENT

Specifies the alignment requirements for the start of each pixel row in memory. The allowable values are 1 (byte-alignment), 2 (rows aligned to even-numbered

bytes), 4 (word-alignment), and 8 (rows start on double-word boundaries).

The following table gives the type, initial value, and range of valid values for each storage parameter that can be set with **glPixelStore**.

<i>pname</i>	<i>type</i>	<i>initial value</i>	<i>valid range</i>
GL_PACK_SWAP_BYTES	boolean	false	true or false
GL_PACK_LSB_FIRST	boolean	false	true or false
GL_PACK_ROW_LENGTH	integer	0	[0,∞)
GL_PACK_SKIP_ROWS	integer	0	[0,∞)
GL_PACK_SKIP_PIXELS	integer	0	[0,∞)
GL_PACK_ALIGNMENT	integer	4	1, 2, 4, or 8
GL_UNPACK_SWAP_BYTES	boolean	false	true or false
GL_UNPACK_LSB_FIRST	boolean	false	true or false
GL_UNPACK_ROW_LENGTH	integer	0	[0,∞)
GL_UNPACK_SKIP_ROWS	integer	0	[0,∞)
GL_UNPACK_SKIP_PIXELS	integer	0	[0,∞)
GL_UNPACK_ALIGNMENT	integer	4	1, 2, 4, or 8

glPixelStoref can be used to set any pixel store parameter. If the parameter type is boolean, then if *param* is 0, the parameter is false; otherwise it is set to true. If *pname* is a integer type parameter, *param* is rounded to the nearest integer.

Likewise, **glPixelStorei** can also be used to set any of the pixel store parameters. Boolean parameters are set to false if *param* is 0 and true otherwise.

NOTES

The pixel storage modes in effect when **glDrawPixels**, **glReadPixels**, **glTexImage1D**, **glTexImage2D**, **glTexSubImage1D**, **glTexSubImage2D**, **glBitmap**, or **glPolygonStipple** is placed in a display list control the interpretation of memory data. The pixel storage modes in effect when a display list is executed are not significant.

Pixel storage modes are client state and must be pushed and restored using

glPushClientAttrib and **glPopClientAttrib**.

ERRORS

GL_INVALID_ENUM is generated if *pname* is not an accepted value.

GL_INVALID_VALUE is generated if a negative row length, pixel skip, or row skip value is specified, or if alignment is specified as other than 1, 2, 4, or 8.

GL_INVALID_OPERATION is generated if **glPixelStore** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_PACK_SWAP_BYTES**
glGet with argument **GL_PACK_LSB_FIRST**
glGet with argument **GL_PACK_ROW_LENGTH**
glGet with argument **GL_PACK_SKIP_ROWS**
glGet with argument **GL_PACK_SKIP_PIXELS**
glGet with argument **GL_PACK_ALIGNMENT**
glGet with argument **GL_UNPACK_SWAP_BYTES**
glGet with argument **GL_UNPACK_LSB_FIRST**
glGet with argument **GL_UNPACK_ROW_LENGTH**
glGet with argument **GL_UNPACK_SKIP_ROWS**
glGet with argument **GL_UNPACK_SKIP_PIXELS**
glGet with argument **GL_UNPACK_ALIGNMENT**

SEE ALSO

glBitmap, **glDrawPixels**, **glPixelMap**, **glPixelTransfer**,
glPixelZoom,
glPolygonStipple, **glPushClientAttrib**, **glReadPixels**,
glTexImage1D, **glTexImage2D**, **glTexSubImage1D**, **glTexSubImage2D**

NAME

glPixelTransferf, glPixelTransferi - set pixel transfer modes

C SPECIFICATION

```
void glPixelTransferf( GLenum pname,
                      GLfloat param )
void glPixelTransferi( GLenum pname,
                      GLint param )
```

PARAMETERS

pname Specifies the symbolic name of the pixel transfer parameter to be set. Must be one of the following: **GL_MAP_COLOR**, **GL_MAP_STENCIL**, **GL_INDEX_SHIFT**, **GL_INDEX_OFFSET**, **GL_RED_SCALE**, **GL_RED_BIAS**, **GL_GREEN_SCALE**, **GL_GREEN_BIAS**, **GL_BLUE_SCALE**, **GL_BLUE_BIAS**, **GL_ALPHA_SCALE**, **GL_ALPHA_BIAS**, **GL_DEPTH_SCALE**, or **GL_DEPTH_BIAS**.

param Specifies the value that *pname* is set to.

DESCRIPTION

glPixelTransfer sets pixel transfer modes that affect the operation of subsequent **glCopyPixels**, **glCopyTexImage1D**, **glCopyTexImage2D**, **glCopyTexSubImage1D**, **glCopyTexSubImage2D**, **glDrawPixels**, **glReadPixels**, **glTexImage1D**, **glTexImage2D**, **glTexSubImage1D**, and **glTexSubImage2D** commands. The algorithms that are specified by pixel transfer modes operate on pixels after they are read from the frame buffer (**glCopyPixels**, **glCopyTexImage1D**, **glCopyTexImage2D**, **glCopyTexSubImage1D**, **glCopyTexSubImage2D**, and **glReadPixels**), or unpacked from client memory (**glDrawPixels**, **glTexImage1D**, **glTexImage2D**, **glTexSubImage1D**, and **glTexSubImage2D**). Pixel transfer operations happen in the same order, and in the same manner, regardless of the command that resulted in the pixel operation. Pixel storage modes (see **glPixelStore**) control the unpacking of pixels being read from client memory, and the packing of pixels being written back into client memory.

Pixel transfer operations handle four fundamental pixel types: *color*, *color index*, *depth*, and *stencil*. *Color* pixels consist of four floating-point values with

unspecified mantissa and exponent sizes, scaled such that 0 represents zero intensity and 1 represents full intensity. *Color indices* comprise a single fixed-point value, with unspecified precision to the right of the binary point. *Depth* pixels comprise a single floating-point value, with unspecified mantissa and exponent sizes, scaled such that 0.0 represents the minimum depth buffer value, and 1.0 represents the maximum depth buffer value. Finally, *stencil* pixels comprise a single fixed-point value, with unspecified precision to the right of the binary point.

The pixel transfer operations performed on the four basic pixel types are as follows:

Color Each of the four color components is multiplied by a scale factor, then added to a bias factor. That is, the red component is multiplied by **GL_RED_SCALE**, then added to **GL_RED_BIAS**; the green component is multiplied by **GL_GREEN_SCALE**, then added to **GL_GREEN_BIAS**; the blue component is multiplied by **GL_BLUE_SCALE**, then added to **GL_BLUE_BIAS**; and the alpha component is multiplied by **GL_ALPHA_SCALE**, then added to **GL_ALPHA_BIAS**. After all four color components are scaled and biased, each is clamped to the range [0,1]. All color, scale, and bias values are specified with **glPixelTransfer**.

If **GL_MAP_COLOR** is true, each color component is scaled by the size of the corresponding color-to-color map, then replaced by the contents of that map indexed by the scaled component. That is, the red component is scaled by **GL_PIXEL_MAP_R_TO_R_SIZE**, then replaced by the contents of **GL_PIXEL_MAP_R_TO_R** indexed by itself. The green component is scaled by **GL_PIXEL_MAP_G_TO_G_SIZE**, then replaced by the contents of **GL_PIXEL_MAP_G_TO_G** indexed by itself. The blue component is scaled by **GL_PIXEL_MAP_B_TO_B_SIZE**, then replaced by the contents of **GL_PIXEL_MAP_B_TO_B** indexed by itself. And the alpha component is scaled by **GL_PIXEL_MAP_A_TO_A_SIZE**, then replaced by the contents of **GL_PIXEL_MAP_A_TO_A** indexed by itself. All components taken from the maps are then clamped to the range [0,1]. **GL_MAP_COLOR**

is specified with **glPixelTransfer**. The contents of the various maps are specified with **glPixelMap**.

Color index Each color index is shifted left by **GL_INDEX_SHIFT** bits; any bits beyond the number of fraction bits carried by the fixed-point index are filled with zeros. If **GL_INDEX_SHIFT** is negative, the shift is to the right, again zero filled. Then **GL_INDEX_OFFSET** is added to the index. **GL_INDEX_SHIFT** and **GL_INDEX_OFFSET** are specified with **glPixelTransfer**. From this point, operation diverges depending on the required format of the resulting pixels. If the resulting pixels are to be written to a color index buffer, or if they are being read back to client memory in **GL_COLOR_INDEX** format, the pixels continue to be treated as indices. If **GL_MAP_COLOR** is true, each index is masked by $2^n - 1$, where n is **GL_PIXEL_MAP_I_TO_I_SIZE**, then replaced by the contents of **GL_PIXEL_MAP_I_TO_I** indexed by the masked value. **GL_MAP_COLOR** is specified with **glPixelTransfer**. The contents of the index map is specified with **glPixelMap**.

If the resulting pixels are to be written to an RGBA color buffer, or if they are read back to client memory in a format other than **GL_COLOR_INDEX**, the pixels are converted from indices to colors by referencing the four maps **GL_PIXEL_MAP_I_TO_R**, **GL_PIXEL_MAP_I_TO_G**, **GL_PIXEL_MAP_I_TO_B**, and **GL_PIXEL_MAP_I_TO_A**. Before being dereferenced, the index is masked by $2^n - 1$, where n is **GL_PIXEL_MAP_I_TO_R_SIZE** for the red map, **GL_PIXEL_MAP_I_TO_G_SIZE** for the green map, **GL_PIXEL_MAP_I_TO_B_SIZE** for the blue map, and **GL_PIXEL_MAP_I_TO_A_SIZE** for the alpha map. All components taken from the maps are then clamped to the range $[0,1]$. The contents of the four maps is specified with **glPixelMap**.

Depth Each depth value is multiplied by **GL_DEPTH_SCALE**, added to **GL_DEPTH_BIAS**, then

clamped to the range [0,1].

Stencil Each index is shifted **GL_INDEX_SHIFT** bits just as a color index is, then added to **GL_INDEX_OFFSET**. If **GL_MAP_STENCIL** is true, each index is masked by $2^n - 1$, where n is **GL_PIXEL_MAP_S_TO_S_SIZE**, then replaced by the contents of **GL_PIXEL_MAP_S_TO_S** indexed by the masked value.

The following table gives the type, initial value, and range of valid values for each of the pixel transfer parameters that are set with **glPixelTransfer**.

<i>pname</i>	<i>type</i>	<i>initial value</i>	<i>valid range</i>
GL_MAP_COLOR	boolean	false	true/false
GL_MAP_STENCIL	boolean	false	true/false
GL_INDEX_SHIFT	integer	0	(-∞,∞)
GL_INDEX_OFFSET	integer	0	(-∞,∞)
GL_RED_SCALE	float	1	(-∞,∞)
GL_GREEN_SCALE	float	1	(-∞,∞)
GL_BLUE_SCALE	float	1	(-∞,∞)
GL_ALPHA_SCALE	float	1	(-∞,∞)
GL_DEPTH_SCALE	float	1	(-∞,∞)
GL_RED_BIAS	float	0	(-∞,∞)
GL_GREEN_BIAS	float	0	(-∞,∞)
GL_BLUE_BIAS	float	0	(-∞,∞)
GL_ALPHA_BIAS	float	0	(-∞,∞)
GL_DEPTH_BIAS	float	0	(-∞,∞)

glPixelTransferf can be used to set any pixel transfer parameter. If the parameter type is boolean, 0 implies false and any other value implies true. If *pname* is an integer parameter, *param* is rounded to the nearest integer.

Likewise, **glPixelTransferi** can be used to set any of the pixel transfer parameters. Boolean parameters are set to false if *param* is 0 and to true otherwise. *param* is

converted to floating point before being assigned to real-valued parameters.

NOTES

If a `glCopyPixels`, `glCopyTexImage1D`, `glCopyTexImage2D`, `glCopyTexSubImage1D`, `glCopyTexSubImage2D`, `glDrawPixels`, `glReadPixels`, `glTexImage1D`, `glTexImage2D`, `glTexSubImage1D`, or `glTexSubImage2D` command is placed in a display list (see `glNewList` and `glCallList`), the pixel transfer mode settings in effect when the display list is executed are the ones that are used. They may be different from the settings when the command was compiled into the display list.

ERRORS

`GL_INVALID_ENUM` is generated if *pname* is not an accepted value.

`GL_INVALID_OPERATION` is generated if `glPixelTransfer` is executed between the execution of `glBegin` and the corresponding execution of `glEnd`.

ASSOCIATED GETS

`glGet` with argument `GL_MAP_COLOR`
`glGet` with argument `GL_MAP_STENCIL`
`glGet` with argument `GL_INDEX_SHIFT`
`glGet` with argument `GL_INDEX_OFFSET`
`glGet` with argument `GL_RED_SCALE`
`glGet` with argument `GL_RED_BIAS`
`glGet` with argument `GL_GREEN_SCALE`
`glGet` with argument `GL_GREEN_BIAS`
`glGet` with argument `GL_BLUE_SCALE`
`glGet` with argument `GL_BLUE_BIAS`
`glGet` with argument `GL_ALPHA_SCALE`
`glGet` with argument `GL_ALPHA_BIAS`
`glGet` with argument `GL_DEPTH_SCALE`
`glGet` with argument `GL_DEPTH_BIAS`

SEE ALSO

`glCallList`, `glCopyPixels`, `glCopyTexImage1D`,
`glCopyTexImage2D`, `glCopyTexSubImage1D`, `glCopyTexSubImage2D`,
`glDrawPixels`, `glNewList`, `glPixelMap`, `glPixelStore`,
`glPixelZoom`, `glReadPixels`, `glTexImage1D`, `glTexImage2D`,
`glTexSubImage1D`, `glTexSubImage2D`

NAME

glPixelZoom - specify the pixel zoom factors

C SPECIFICATION

```
void glPixelZoom( GLfloat xfactor,  
                  GLfloat yfactor )
```

PARAMETERS

xfactor, *yfactor* Specify the x and y zoom factors for pixel write operations.

DESCRIPTION

glPixelZoom specifies values for the x and y zoom factors. During the execution of **glDrawPixels** or **glCopyPixels**, if (*xr*, *yr*) is the current raster position, and a given element is in the *m*th row and *n*th column of the pixel rectangle, then pixels whose centers are in the rectangle with corners at

$$(xr + n.xfactor, yr + m.yfactor)$$
$$(xr + (n+1).xfactor, yr + (m+1).yfactor)$$

are candidates for replacement. Any pixel whose center lies on the bottom or left edge of this rectangular region is also modified.

Pixel zoom factors are not limited to positive values. Negative zoom factors reflect the resulting image about the current raster position.

ERRORS

GL_INVALID_OPERATION is generated if **glPixelZoom** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_ZOOM_X**
glGet with argument **GL_ZOOM_Y**

SEE ALSO

glCopyPixels, **glDrawPixels**

NAME

glPointSize - specify the diameter of rasterized points

C SPECIFICATION

```
void glPointSize( GLfloat size )
```

PARAMETERS

size Specifies the diameter of rasterized points. The initial value is 1.

DESCRIPTION

glPointSize specifies the rasterized diameter of both aliased and antialiased points. Using a point size other than 1 has different effects, depending on whether point antialiasing is enabled. To enable and disable point antialiasing, call **glEnable** and **glDisable** with argument **GL_POINT_SMOOTH**. Point antialiasing is initially disabled.

If point antialiasing is disabled, the actual size is determined by rounding the supplied size to the nearest integer. (If the rounding results in the value 0, it is as if the point size were 1.) If the rounded size is odd, then the center point (x, y) of the pixel fragment that represents the point is computed as

$$\left(\left\lfloor x \right\rfloor + .5, \left\lfloor y \right\rfloor + .5 \right)$$

where *w* subscripts indicate window coordinates. All pixels that lie within the square grid of the rounded size centered at (x, y) make up the fragment. If the size is even, the center point is

$$\left(\left\lfloor x + .5 \right\rfloor, \left\lfloor y + .5 \right\rfloor \right)$$

and the rasterized fragment's centers are the half-integer window coordinates within the square of the rounded size centered at (x, y). All pixel fragments produced in rasterizing a nonantialiased point are assigned the same associated data, that of the vertex corresponding to the point.

If antialiasing is enabled, then point rasterization produces a fragment for each pixel square that intersects

the region lying within the circle having diameter equal to the current point size and centered at the point's (x , y). The coverage value for each fragment is the window w w coordinate area of the intersection of the circular region with the corresponding pixel square. This value is saved and used in the final rasterization step. The data associated with each fragment is the data associated with the point being rasterized.

Not all sizes are supported when point antialiasing is enabled. If an unsupported size is requested, the nearest supported size is used. Only size 1 is guaranteed to be supported; others depend on the implementation. To query the range of supported sizes and the size difference between supported sizes within the range, call **glGet** with arguments **GL_POINT_SIZE_RANGE** and **GL_POINT_SIZE_GRANULARITY**.

NOTES

The point size specified by **glPointSize** is always returned when **GL_POINT_SIZE** is queried. Clamping and rounding for aliased and antialiased points have no effect on the specified value.

A non-antialiased point size may be clamped to an implementation-dependent maximum. Although this maximum cannot be queried, it must be no less than the maximum value for antialiased points, rounded to the nearest integer value.

ERRORS

GL_INVALID_VALUE is generated if *size* is less than or equal to 0.

GL_INVALID_OPERATION is generated if **glPointSize** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_POINT_SIZE**
glGet with argument **GL_POINT_SIZE_RANGE**
glGet with argument **GL_POINT_SIZE_GRANULARITY**
glIsEnabled with argument **GL_POINT_SMOOTH**

SEE ALSO

glEnable

NAME

glPolygonMode - select a polygon rasterization mode

C SPECIFICATION

```
void glPolygonMode( GLenum face,  
                    GLenum mode )
```

PARAMETERS

face Specifies the polygons that *mode* applies to. Must be **GL_FRONT** for front-facing polygons, **GL_BACK** for back-facing polygons, or **GL_FRONT_AND_BACK** for front- and back-facing polygons.

mode Specifies how polygons will be rasterized. Accepted values are **GL_POINT**, **GL_LINE**, and **GL_FILL**. The initial value is **GL_FILL** for both front- and back-facing polygons.

DESCRIPTION

glPolygonMode controls the interpretation of polygons for rasterization. *face* describes which polygons *mode* applies to: front-facing polygons (**GL_FRONT**), back-facing polygons (**GL_BACK**), or both (**GL_FRONT_AND_BACK**). The polygon mode affects only the final rasterization of polygons. In particular, a polygon's vertices are lit and the polygon is clipped and possibly culled before these modes are applied.

Three modes are defined and can be specified in *mode*:

GL_POINT Polygon vertices that are marked as the start of a boundary edge are drawn as points. Point attributes such as **GL_POINT_SIZE** and **GL_POINT_SMOOTH** control the rasterization of the points. Polygon rasterization attributes other than **GL_POLYGON_MODE** have no effect.

GL_LINE Boundary edges of the polygon are drawn as line segments. They are treated as connected line segments for line stippling; the line stipple counter and pattern are not reset between segments (see **glLineStipple**). Line attributes such as **GL_LINE_WIDTH** and **GL_LINE_SMOOTH** control the rasterization of

the lines. Polygon rasterization attributes other than **GL_POLYGON_MODE** have no effect.

GL_FILL The interior of the polygon is filled. Polygon attributes such as **GL_POLYGON_STIPPLE** and **GL_POLYGON_SMOOTH** control the rasterization of the polygon.

EXAMPLES

To draw a surface with filled back-facing polygons and outlined front-facing polygons, call `glPolygonMode(GL_FRONT, GL_LINE)`;

NOTES

Vertices are marked as boundary or nonboundary with an edge flag. Edge flags are generated internally by the GL when it decomposes polygons; they can be set explicitly using **glEdgeFlag**.

ERRORS

GL_INVALID_ENUM is generated if either *face* or *mode* is not an accepted value.

GL_INVALID_OPERATION is generated if **glPolygonMode** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_POLYGON_MODE**

SEE ALSO

glBegin, **glEdgeFlag**, **glLineStipple**, **glLineWidth**, **glPointSize**, **glPolygonStipple**

NAME

glPolygonOffset - set the scale and units used to calculate depth values

C SPECIFICATION

```
void glPolygonOffset( GLfloat factor,  
                      GLfloat units )
```

PARAMETERS

factor Specifies a scale factor that is used to create a variable depth offset for each polygon. The initial value is 0.

units Is multiplied by an implementation-specific value to create a constant depth offset. The initial value is 0.

DESCRIPTION

When **GL_POLYGON_OFFSET** is enabled, each fragment's *depth* value will be offset after it is interpolated from the *depth* values of the appropriate vertices. The value of the offset is $\text{factor} * \text{DZ} + r * \text{units}$, where *DZ* is a measurement of the change in depth relative to the screen area of the polygon, and *r* is the smallest value that is guaranteed to produce a resolvable offset for a given implementation. The offset is added before the depth test is performed and before the value is written into the depth buffer.

glPolygonOffset is useful for rendering hidden-line images, for applying decals to surfaces, and for rendering solids with highlighted edges.

NOTES

glPolygonOffset is available only if the GL version is 1.1 or greater.

glPolygonOffset has no effect on depth coordinates placed in the feedback buffer.

glPolygonOffset has no effect on selection.

ERRORS

GL_INVALID_OPERATION is generated if **glPolygonOffset** is

executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glIsEnabled with argument **GL_POLYGON_OFFSET_FILL**, **GL_POLYGON_OFFSET_LINE**, or **GL_POLYGON_OFFSET_POINT**.

glGet with argument **GL_POLYGON_OFFSET_FACTOR** or **GL_POLYGON_OFFSET_UNITS**.

SEE ALSO

glDepthFunc, **glDisable**, **glEnable**, **glGet**, **glIsEnabled**, **glLineWidth**, **glStencilOp**, **glTexEnv**

NAME

glPolygonStipple - set the polygon stippling pattern

C SPECIFICATION

```
void glPolygonStipple( const GLubyte *mask )
```

PARAMETERS

mask Specifies a pointer to a 32x32 stipple pattern that will be unpacked from memory in the same way that **glDrawPixels** unpacks pixels.

DESCRIPTION

Polygon stippling, like line stippling (see **glLineStipple**), masks out certain fragments produced by rasterization, creating a pattern. Stippling is independent of polygon antialiasing.

mask is a pointer to a 32x32 stipple pattern that is stored in memory just like the pixel data supplied to a **glDrawPixels** call with *height* and *width* both equal to 32, a pixel format of **GL_COLOR_INDEX**, and data type of **GL_BITMAP**. That is, the stipple pattern is represented as a 32x32 array of 1-bit color indices packed in unsigned bytes. **glPixelStore** parameters like **GL_UNPACK_SWAP_BYTES** and **GL_UNPACK_LSB_FIRST** affect the assembling of the bits into a stipple pattern. Pixel transfer operations (shift, offset, pixel map) are not applied to the stipple image, however.

To enable and disable polygon stippling, call **glEnable** and **glDisable** with argument **GL_POLYGON_STIPPLE**. Polygon stippling is initially disabled. If it's enabled, a rasterized polygon fragment with window coordinates *x* and *y* is sent to the next stage of the GL if and only if the (*x* mod 32)th bit in the (*y* mod 32)th row of the stipple pattern is 1 (one). When polygon stippling is disabled, it is as if the stipple pattern consists of all 1's.

ERRORS

GL_INVALID_OPERATION is generated if **glPolygonStipple** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGetPolygonStipple

glIsEnabled with argument **GL_POLYGON_STIPPLE**

SEE ALSO

glDrawPixels, glLineStipple, glPixelStore, glPixelTransfer

NAME

glPrioritizeTextures - set texture residence priority

C SPECIFICATION

```
void glPrioritizeTextures( GLsizei n,  
                           const GLuint *textures,  
                           const GLclampf *priorities )
```

PARAMETERS

<i>n</i>	Specifies the number of textures to be prioritized.
<i>textures</i>	Specifies an array containing the names of the textures to be prioritized.
<i>priorities</i>	Specifies an array containing the texture priorities. A priority given in an element of <i>priorities</i> applies to the texture named by the corresponding element of <i>textures</i> .

DESCRIPTION

glPrioritizeTextures assigns the *n* texture priorities given in *priorities* to the *n* textures named in *textures*.

The GL establishes a ``working set'' of textures that are resident in texture memory. These textures may be bound to a texture target much more efficiently than textures that are not resident. By specifying a priority for each texture, **glPrioritizeTextures** allows applications to guide the GL implementation in determining which textures should be resident.

The priorities given in *priorities* are clamped to the range [0,1] before they are assigned. 0 indicates the lowest priority; textures with priority 0 are least likely to be resident. 1 indicates the highest priority; textures with priority 1 are most likely to be resident. However, textures are not guaranteed to be resident until they are used.

glPrioritizeTextures silently ignores attempts to prioritize texture 0, or any texture name that does not correspond to an existing texture.

glPrioritizeTextures does not require that any of the textures named by *textures* be bound to a texture target. **glTexParameter** may also be used to set a texture's priority, but only if the texture is currently bound. This is the only way to set the priority of a default texture.

NOTES

glPrioritizeTextures is available only if the GL version is 1.1 or greater.

ERRORS

GL_INVALID_VALUE is generated if *n* is negative.

GL_INVALID_OPERATION is generated if **glPrioritizeTextures** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGetTexParameter with parameter name **GL_TEXTURE_PRIORITY** retrieves the priority of a currently bound texture.

SEE ALSO

glAreTexturesResident, **glBindTexture**, **glCopyTexImage1D**, **glCopyTexImage2D**, **glTexImage1D**, **glTexImage2D**, **glTexParameter**

NAME

glPushAttrib, glPopAttrib - push and pop the server attribute stack

C SPECIFICATION

```
void glPushAttrib( GLbitfield mask )
```

PARAMETERS

mask Specifies a mask that indicates which attributes to save. Values for *mask* are listed below.

C SPECIFICATION

```
void glPopAttrib( void )
```

DESCRIPTION

glPushAttrib takes one argument, a mask that indicates which groups of state variables to save on the attribute stack. Symbolic constants are used to set bits in the mask. *mask* is typically constructed by ORing several of these constants together. The special mask **GL_ALL_ATTRIB_BITS** can be used to save all stackable states.

The symbolic mask constants and their associated GL state are as follows (the second column lists which attributes are saved):

GL_ACCUM_BUFFER_BIT	Accumulation buffer clear value
GL_COLOR_BUFFER_BIT	GL_ALPHA_TEST enable bit Alpha test function and reference value GL_BLEND enable bit Blending source and destination functions Constant blend color Blending equation GL_DITHER enable bit GL_DRAW_BUFFER setting GL_COLOR_LOGIC_OP enable bit GL_INDEX_LOGIC_OP enable bit Logic op function Color mode and index mode clear values Color mode and index mode writemasks
GL_CURRENT_BIT	Current RGBA color Current color index Current normal vector Current texture coordinates Current raster position
	GL_CURRENT_RASTER_POSITION_VALID flag RGBA color associated with current raster position

position	Color index associated with current raster
position	Texture coordinates associated with current raster
	GL_EDGE_FLAG flag
GL_DEPTH_BUFFER_BIT	GL_DEPTH_TEST enable bit Depth buffer test function Depth buffer clear value GL_DEPTH_WRITEMASK enable bit
GL_ENABLE_BIT	GL_ALPHA_TEST flag GL_AUTO_NORMAL flag GL_BLEND flag Enable bits for the user-definable clipping planes GL_COLOR_MATERIAL GL_CULL_FACE flag GL_DEPTH_TEST flag GL_DITHER flag GL_FOG flag GL_LIGHT i where $0 \leq i < \text{GL_MAX_LIGHTS}$ GL_LIGHTING flag GL_LINE_SMOOTH flag GL_LINE_STIPPLE flag GL_COLOR_LOGIC_OP flag GL_INDEX_LOGIC_OP flag GL_MAP1_x where x is a map type GL_MAP2_x where x is a map type GL_NORMALIZE flag GL_POINT_SMOOTH flag GL_POLYGON_OFFSET_LINE flag GL_POLYGON_OFFSET_FILL flag GL_POLYGON_OFFSET_POINT flag GL_POLYGON_SMOOTH flag GL_POLYGON_STIPPLE flag GL_SCISSOR_TEST flag GL_STENCIL_TEST flag GL_TEXTURE_1D flag GL_TEXTURE_2D flag Flags GL_TEXTURE_GEN_x where x is S, T, R, or Q
GL_EVAL_BIT	GL_MAP1_x enable bits, where x is a map type GL_MAP2_x enable bits, where x is a map type 1D grid endpoints and divisions 2D grid endpoints and divisions GL_AUTO_NORMAL enable bit
GL_FOG_BIT	GL_FOG enable bit Fog color Fog density Linear fog start Linear fog end Fog index

	GL_FOG_MODE value
GL_HINT_BIT	GL_PERSPECTIVE_CORRECTION_HINT setting GL_POINT_SMOOTH_HINT setting GL_LINE_SMOOTH_HINT setting GL_POLYGON_SMOOTH_HINT setting GL_FOG_HINT setting
GL_LIGHTING_BIT	GL_COLOR_MATERIAL enable bit GL_COLOR_MATERIAL_FACE value Color material parameters that are tracking the current color Ambient scene color GL_LIGHT_MODEL_LOCAL_VIEWER value GL_LIGHT_MODEL_TWO_SIDE setting GL_LIGHTING enable bit Enable bit for each light Ambient, diffuse, and specular intensity for each light Direction, position, exponent, and cutoff angle Constant, linear, and quadratic attenuation Ambient, diffuse, specular, and emissive color for each material Ambient, diffuse, and specular color indices for each material
GL_LINE_BIT	GL_LINE_SMOOTH flag GL_LINE_STIPPLE enable bit Line stipple pattern and repeat counter Line width
GL_LIST_BIT	GL_LIST_BASE setting
GL_PIXEL_MODE_BIT	GL_RED_BIAS and GL_RED_SCALE settings GL_GREEN_BIAS and GL_GREEN_SCALE values GL_BLUE_BIAS and GL_BLUE_SCALE GL_ALPHA_BIAS and GL_ALPHA_SCALE GL_DEPTH_BIAS and GL_DEPTH_SCALE GL_INDEX_OFFSET and GL_INDEX_SHIFT values GL_MAP_COLOR and GL_MAP_STENCIL flags GL_ZOOM_X and GL_ZOOM_Y factors GL_READ_BUFFER setting
GL_POINT_BIT	GL_POINT_SMOOTH flag Point size
GL_POLYGON_BIT	GL_CULL_FACE enable bit GL_CULL_FACE_MODE value GL_FRONT_FACE indicator

GL_POLYGON_MODE setting
GL_POLYGON_SMOOTH flag
GL_POLYGON_STIPPLE enable bit
GL_POLYGON_OFFSET_FILL flag
GL_POLYGON_OFFSET_LINE flag
GL_POLYGON_OFFSET_POINT flag
GL_POLYGON_OFFSET_FACTOR
GL_POLYGON_OFFSET_UNITS

GL_POLYGON_STIPPLE_BIT Polygon stipple image

GL_SCISSOR_BIT **GL_SCISSOR_TEST** flag
 Scissor box

GL_STENCIL_BUFFER_BIT **GL_STENCIL_TEST** enable bit
 Stencil function and reference value
 Stencil value mask
 Stencil fail, pass, and depth buffer pass actions
 Stencil buffer clear value
 Stencil buffer writemask

GL_TEXTURE_BIT Enable bits for the four texture coordinates
 Border color for each texture image
 Minification function for each texture image
 Magnification function for each texture image
 Texture coordinates and wrap mode for each texture

image

Color and mode for each texture environment
 Enable bits **GL_TEXTURE_GEN_x**, x is S, T, R, and Q
GL_TEXTURE_GEN_MODE setting for S, T, R, and Q
glTexGen plane equations for S, T, R, and Q
 Current texture bindings (for example,

GL_TEXTURE_2D_BINDING)

GL_TRANSFORM_BIT Coefficients of the six clipping planes
 Enable bits for the user-definable clipping planes
GL_MATRIX_MODE value
GL_NORMALIZE flag

GL_VIEWPORT_BIT Depth range (near and far)
 Viewport origin and extent

glPopAttrib restores the values of the state variables saved
 with the last
glPushAttrib command. Those not saved are left unchanged.

It is an error to push attributes onto a full stack, or to
 pop attributes off an empty stack. In either case, the
 error flag is set and no other change is made to GL state.

Initially, the attribute stack is empty.

NOTES

Not all values for GL state can be saved on the attribute
 stack. For example, render mode state, and select and

feedback state cannot be saved. Client state must be saved with **glPushClientAttrib**.

The depth of the attribute stack depends on the implementation, but it must be at least 16.

ERRORS

GL_STACK_OVERFLOW is generated if **glPushAttrib** is called while the attribute stack is full.

GL_STACK_UNDERFLOW is generated if **glPopAttrib** is called while the attribute stack is empty.

GL_INVALID_OPERATION is generated if **glPushAttrib** or **glPopAttrib** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_ATTRIB_STACK_DEPTH**

glGet with argument **GL_MAX_ATTRIB_STACK_DEPTH**

SEE ALSO

glGet, **glGetClipPlane**, **glGetError**, **glGetLight**, **glGetMap**,
glGetMaterial,
glGetPixelMap, **glGetPolygonStipple**, **glGetString**,
glGetTexEnv, **glGetTexGen**, **glGetTexImage**,
glGetTexLevelParameter, **glGetTexParameter**, **glIsEnabled**,
glPushClientAttrib

NAME

glPushClientAttrib, glPopClientAttrib - push and pop the client attribute stack

C SPECIFICATION

```
void glPushClientAttrib( GLbitfield mask )
```

PARAMETERS

mask Specifies a mask that indicates which attributes to save. Values for *mask* are listed below.

C SPECIFICATION

```
void glPopClientAttrib( void )
```

DESCRIPTION

glPushClientAttrib takes one argument, a mask that indicates which groups of client-state variables to save on the client attribute stack. Symbolic constants are used to set bits in the mask. *mask* is typically constructed by OR'ing several of these constants together. The special mask **GL_CLIENT_ALL_ATTRIB_BITS** can be used to save all stackable client state.

The symbolic mask constants and their associated GL client state are as follows (the second column lists which attributes are saved):

GL_CLIENT_PIXEL_STORE_BIT	Pixel storage modes
GL_CLIENT_VERTEX_ARRAY_BIT	Vertex arrays (and enables)

glPopClientAttrib restores the values of the client-state variables saved with the last **glPushClientAttrib**. Those not saved are left unchanged.

It is an error to push attributes onto a full client attribute stack, or to pop attributes off an empty stack. In either case, the error flag is set, and no other change is made to GL state.

Initially, the client attribute stack is empty.

NOTES

glPushClientAttrib is available only if the GL version is 1.1 or greater.

Not all values for GL client state can be saved on the attribute stack. For example, select and feedback state cannot be saved.

The depth of the attribute stack depends on the implementation, but it must be at least 16.

Use **glPushAttrib** and **glPopAttrib** to push and restore state which is kept on the server. Only pixel storage modes and vertex array state may be pushed and popped with **glPushClientAttrib** and **glPopClientAttrib**.

ERRORS

GL_STACK_OVERFLOW is generated if **glPushClientAttrib** is called while the attribute stack is full.

GL_STACK_UNDERFLOW is generated if **glPopClientAttrib** is called while the attribute stack is empty.

ASSOCIATED GETS

glGet with argument **GL_ATTRIB_STACK_DEPTH**

glGet with argument **GL_MAX_CLIENT_ATTRIB_STACK_DEPTH**

SEE ALSO

glColorPointer, **glDisableClientState**, **glEdgeFlagPointer**, **glEnableClientState**, **glGet**, **glGetError**, **glIndexPointer**, **glNormalPointer**, **glNewList**, **glPixelStore**, **glPushAttrib**, **glTexCoordPointer**, **glVertexPointer**

NAME

glPushMatrix, **glPopMatrix** - push and pop the current matrix stack

C SPECIFICATION

```
void glPushMatrix( void )
```

C SPECIFICATION

```
void glPopMatrix( void )
```

DESCRIPTION

There is a stack of matrices for each of the matrix modes. In **GL_MODELVIEW** mode, the stack depth is at least 32. In the other two modes, **GL_PROJECTION** and **GL_TEXTURE**, the depth is at least 2. The current matrix in any mode is the matrix on the top of the stack for that mode.

glPushMatrix pushes the current matrix stack down by one, duplicating the current matrix. That is, after a **glPushMatrix** call, the matrix on top of the stack is identical to the one below it.

glPopMatrix pops the current matrix stack, replacing the current matrix with the one below it on the stack.

Initially, each of the stacks contains one matrix, an identity matrix.

It is an error to push a full matrix stack, or to pop a matrix stack that contains only a single matrix. In either case, the error flag is set and no other change is made to GL state.

ERRORS

GL_STACK_OVERFLOW is generated if **glPushMatrix** is called while the current matrix stack is full.

GL_STACK_UNDERFLOW is generated if **glPopMatrix** is called while the current matrix stack contains only a single matrix.

GL_INVALID_OPERATION is generated if **glPushMatrix** or

glPopMatrix is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_MATRIX_MODE**
glGet with argument **GL_MODELVIEW_MATRIX**
glGet with argument **GL_PROJECTION_MATRIX**
glGet with argument **GL_TEXTURE_MATRIX**
glGet with argument **GL_MODELVIEW_STACK_DEPTH**
glGet with argument **GL_PROJECTION_STACK_DEPTH**
glGet with argument **GL_TEXTURE_STACK_DEPTH**
glGet with argument **GL_MAX_MODELVIEW_STACK_DEPTH**
glGet with argument **GL_MAX_PROJECTION_STACK_DEPTH**
glGet with argument **GL_MAX_TEXTURE_STACK_DEPTH**

SEE ALSO

glFrustum, **glLoadIdentity**, **glLoadMatrix**, **glMatrixMode**,
glMultMatrix, **glOrtho**, **glRotate**, **glScale**, **glTranslate**,
glViewport

NAME

glPushName, **glPopName** - push and pop the name stack

C SPECIFICATION

```
void glPushName( GLuint name )
```

PARAMETERS

name Specifies a name that will be pushed onto the name stack.

C SPECIFICATION

```
void glPopName( void )
```

DESCRIPTION

The name stack is used during selection mode to allow sets of rendering commands to be uniquely identified. It consists of an ordered set of unsigned integers and is initially empty.

glPushName causes *name* to be pushed onto the name stack. **glPopName** pops one name off the top of the stack.

The maximum name stack depth is implementation-dependent; call **GL_MAX_NAME_STACK_DEPTH** to find out the value for a particular implementation. It is an error to push a name onto a full stack, or to pop a name off an empty stack. It is also an error to manipulate the name stack between the execution of **glBegin** and the corresponding execution of **glEnd**. In any of these cases, the error flag is set and no other change is made to GL state.

The name stack is always empty while the render mode is not **GL_SELECT**. Calls to **glPushName** or **glPopName** while the render mode is not **GL_SELECT** are ignored.

ERRORS

GL_STACK_OVERFLOW is generated if **glPushName** is called while the name stack is full.

GL_STACK_UNDERFLOW is generated if **glPopName** is called while the name stack is empty.

GL_INVALID_OPERATION is generated if **glPushName** or **glPopName** is executed between a call to **glBegin** and the corresponding call to **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_NAME_STACK_DEPTH**

glGet with argument **GL_MAX_NAME_STACK_DEPTH**

SEE ALSO

glInitNames, **glLoadName**, **glRenderMode**, **glSelectBuffer**

NAME

glRasterPos2d, **glRasterPos2f**, **glRasterPos2i**, **glRasterPos2s**,
glRasterPos3d, **glRasterPos3f**, **glRasterPos3i**, **glRasterPos3s**,
glRasterPos4d, **glRasterPos4f**, **glRasterPos4i**, **glRasterPos4s**,
glRasterPos2dv, **glRasterPos2fv**, **glRasterPos2iv**,
glRasterPos2sv, **glRasterPos3dv**, **glRasterPos3fv**,
glRasterPos3iv, **glRasterPos3sv**, **glRasterPos4dv**,
glRasterPos4fv, **glRasterPos4iv**, **glRasterPos4sv** - specify the
raster position for pixel operations

C SPECIFICATION

```
void glRasterPos2d( GLdouble x,  
                   GLdouble y )  
void glRasterPos2f( GLfloat x,  
                   GLfloat y )  
void glRasterPos2i( GLint x,  
                   GLint y )  
void glRasterPos2s( GLshort x,  
                   GLshort y )  
void glRasterPos3d( GLdouble x,  
                   GLdouble y,  
                   GLdouble z )  
void glRasterPos3f( GLfloat x,  
                   GLfloat y,  
                   GLfloat z )  
void glRasterPos3i( GLint x,  
                   GLint y,  
                   GLint z )  
void glRasterPos3s( GLshort x,  
                   GLshort y,  
                   GLshort z )  
void glRasterPos4d( GLdouble x,  
                   GLdouble y,  
                   GLdouble z,  
                   GLdouble w )  
void glRasterPos4f( GLfloat x,  
                   GLfloat y,  
                   GLfloat z,  
                   GLfloat w )  
void glRasterPos4i( GLint x,  
                   GLint y,  
                   GLint z,  
                   GLint w )  
void glRasterPos4s( GLshort x,
```

```
GLshort y,  
GLshort z,  
GLshort w )
```

PARAMETERS

x, y, z, w

Specify the *x*, *y*, *z*, and *w* object coordinates (if present) for the raster position.

C SPECIFICATION

```
void glRasterPos2dv( const GLdouble *v )  
void glRasterPos2fv( const GLfloat *v )  
void glRasterPos2iv( const GLint *v )  
void glRasterPos2sv( const GLshort *v )  
void glRasterPos3dv( const GLdouble *v )  
void glRasterPos3fv( const GLfloat *v )  
void glRasterPos3iv( const GLint *v )  
void glRasterPos3sv( const GLshort *v )  
void glRasterPos4dv( const GLdouble *v )  
void glRasterPos4fv( const GLfloat *v )  
void glRasterPos4iv( const GLint *v )  
void glRasterPos4sv( const GLshort *v )
```

PARAMETERS

v Specifies a pointer to an array of two, three, or four elements, specifying *x*, *y*, *z*, and *w* coordinates, respectively.

DESCRIPTION

The GL maintains a 3D position in window coordinates. This position, called the raster position, is used to position pixel and bitmap write operations. It is maintained with subpixel accuracy. See **glBitmap**, **glDrawPixels**, and **glCopyPixels**.

The current raster position consists of three window coordinates (*x*, *y*, *z*), a clip coordinate value (*w*), an eye coordinate distance, a valid bit, and associated color data and texture coordinates. The *w* coordinate is a clip coordinate, because *w* is not projected to window coordinates. **glRasterPos4** specifies object coordinates *x*, *y*, *z*, and *w* explicitly. **glRasterPos3** specifies object coordinate *x*, *y*, and *z* explicitly, while *w* is implicitly set to 1. **glRasterPos2** uses the argument values for *x* and *y*

while implicitly setting *z* and *w* to 0 and 1.

The object coordinates presented by **glRasterPos** are treated just like those of a **glVertex** command: They are transformed by the current modelview and projection matrices and passed to the clipping stage. If the vertex is not culled, then it is projected and scaled to window coordinates, which become the new current raster position, and the **GL_CURRENT_RASTER_POSITION_VALID** flag is set. If the vertex *is* culled, then the valid bit is cleared and the current raster position and associated color and texture coordinates are undefined.

The current raster position also includes some associated color data and texture coordinates. If lighting is enabled, then **GL_CURRENT_RASTER_COLOR** (in RGBA mode) or **GL_CURRENT_RASTER_INDEX** (in color index mode) is set to the color produced by the lighting calculation (see **glLight**, **glLightModel**, and **glShadeModel**). If lighting is disabled, current color (in RGBA mode, state variable **GL_CURRENT_COLOR**) or color index (in color index mode, state variable **GL_CURRENT_INDEX**) is used to update the current raster color.

Likewise, **GL_CURRENT_RASTER_TEXTURE_COORDS** is updated as a function of **GL_CURRENT_TEXTURE_COORDS**, based on the texture matrix and the texture generation functions (see **glTexGen**). Finally, the distance from the origin of the eye coordinate system to the vertex as transformed by only the modelview matrix replaces **GL_CURRENT_RASTER_DISTANCE**.

Initially, the current raster position is (0, 0, 0, 1), the current raster distance is 0, the valid bit is set, the associated RGBA color is (1, 1, 1, 1), the associated color index is 1, and the associated texture coordinates are (0, 0, 0, 1). In RGBA mode, **GL_CURRENT_RASTER_INDEX** is always 1; in color index mode, the current raster RGBA color always maintains its initial value.

NOTES

The raster position is modified both by **glRasterPos** and by **glBitmap**.

When the raster position coordinates are invalid, drawing commands that are based on the raster position are ignored (that is, they do not result in changes to GL state).

Calling **glDrawElements** may leave the current color or index indeterminate. If **glRasterPos** is executed while the current color or index is indeterminate, the current raster color or current raster index remains indeterminate.

To set a valid raster position outside the viewport, first set a valid raster position, then call **glBitmap** with NULL as the *bitmap* parameter.

ERRORS

GL_INVALID_OPERATION is generated if **glRasterPos** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_CURRENT_RASTER_POSITION**
glGet with argument **GL_CURRENT_RASTER_POSITION_VALID**
glGet with argument **GL_CURRENT_RASTER_DISTANCE**
glGet with argument **GL_CURRENT_RASTER_COLOR**
glGet with argument **GL_CURRENT_RASTER_INDEX**
glGet with argument **GL_CURRENT_RASTER_TEXTURE_COORDS**

SEE ALSO

glBitmap, **glCopyPixels**, **glDrawElements**, **glDrawPixels**,
glLight, **glLightModel**, **glShadeModel**, **glTexCoord**, **glTexGen**,
glVertex

NAME

glReadBuffer - select a color buffer source for pixels

C SPECIFICATION

```
void glReadBuffer( GLenum mode )
```

PARAMETERS

mode Specifies a color buffer. Accepted values are **GL_FRONT_LEFT**, **GL_FRONT_RIGHT**, **GL_BACK_LEFT**, **GL_BACK_RIGHT**, **GL_FRONT**, **GL_BACK**, **GL_LEFT**, **GL_RIGHT**, and **GL_AUX*i***, where *i* is between 0 and **GL_AUX_BUFFERS** - 1.

DESCRIPTION

glReadBuffer specifies a color buffer as the source for subsequent **glReadPixels**, **glCopyTexImage1D**, **glCopyTexImage2D**, **glCopyTexSubImage1D**, **glCopyTexSubImage2D**, and **glCopyPixels** commands. *mode* accepts one of twelve or more predefined values. (**GL_AUX0** through **GL_AUX3** are always defined.) In a fully configured system, **GL_FRONT**, **GL_LEFT**, and **GL_FRONT_LEFT** all name the front left buffer, **GL_FRONT_RIGHT** and **GL_RIGHT** name the front right buffer, and **GL_BACK_LEFT** and **GL_BACK** name the back left buffer.

Nonstereo double-buffered configurations have only a front left and a back left buffer. Single-buffered configurations have a front left and a front right buffer if stereo, and only a front left buffer if nonstereo. It is an error to specify a nonexistent buffer to **glReadBuffer**.

mode is initially **GL_FRONT** in single-buffered configurations, and **GL_BACK** in double-buffered configurations.

ERRORS

GL_INVALID_ENUM is generated if *mode* is not one of the twelve (or more) accepted values.

GL_INVALID_OPERATION is generated if *mode* specifies a buffer that does not exist.

GL_INVALID_OPERATION is generated if **glReadBuffer** is executed between the execution of **glBegin** and the

corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_READ_BUFFER**

SEE ALSO

glCopyPixels, **glCopyTexImage1D**, **glCopyTexImage2D**,
glCopyTexSubImage1D, **glCopyTexSubImage2D**, **glDrawBuffer**,
glReadPixels

NAME

glReadPixels - read a block of pixels from the frame buffer

C SPECIFICATION

```
void glReadPixels( GLint x,  
                  GLint y,  
                  GLsizei width,  
                  GLsizei height,  
                  GLenum format,  
                  GLenum type,  
                  GLvoid *pixels )
```

PARAMETERS

x, y Specify the window coordinates of the first pixel that is read from the frame buffer. This location is the lower left corner of a rectangular block of pixels.

width, height

Specify the dimensions of the pixel rectangle. *width* and *height* of one correspond to a single pixel.

format

Specifies the format of the pixel data. The following symbolic values are accepted: **GL_COLOR_INDEX**, **GL_STENCIL_INDEX**, **GL_DEPTH_COMPONENT**, **GL_RED**, **GL_GREEN**, **GL_BLUE**, **GL_ALPHA**, **GL_RGB**, **GL_RGBA**, **GL_LUMINANCE**, and **GL_LUMINANCE_ALPHA**.

type Specifies the data type of the pixel data. Must be one of **GL_UNSIGNED_BYTE**, **GL_BYTE**, **GL_BITMAP**, **GL_UNSIGNED_SHORT**, **GL_SHORT**, **GL_UNSIGNED_INT**, **GL_INT**, or **GL_FLOAT**.

pixels

Returns the pixel data.

DESCRIPTION

glReadPixels returns pixel data from the frame buffer, starting with the pixel whose lower left corner is at location (*x, y*), into client memory starting at location *pixels*. Several parameters control the processing of the pixel data before it is placed into client memory. These parameters are set with three commands: **glPixelStore**,

glPixelTransfer, and **glPixelMap**. This reference page describes the effects on **glReadPixels** of most, but not all of the parameters specified by these three commands.

glReadPixels returns values from each pixel with lower left corner at $(x + i, y + j)$ for $0 < i < \text{width}$ and $0 < j < \text{height}$. This pixel is said to be the i th pixel in the j th row. Pixels are returned in row order from the lowest to the highest row, left to right in each row.

format specifies the format for the returned pixel values; accepted values are:

GL_COLOR_INDEX

Color indices are read from the color buffer selected by **glReadBuffer**. Each index is converted to fixed point, shifted left or right depending on the value and sign of **GL_INDEX_SHIFT**, and added to **GL_INDEX_OFFSET**. If **GL_MAP_COLOR** is **GL_TRUE**, indices are replaced by their mappings in the table **GL_PIXEL_MAP_I_TO_I**.

GL_STENCIL_INDEX

Stencil values are read from the stencil buffer. Each index is converted to fixed point, shifted left or right depending on the value and sign of **GL_INDEX_SHIFT**, and added to **GL_INDEX_OFFSET**. If **GL_MAP_STENCIL** is **GL_TRUE**, indices are replaced by their mappings in the table **GL_PIXEL_MAP_S_TO_S**.

GL_DEPTH_COMPONENT

Depth values are read from the depth buffer. Each component is converted to floating point such that the minimum depth value maps to 0 and the maximum value maps to 1. Each component is then multiplied by **GL_DEPTH_SCALE**, added to **GL_DEPTH_BIAS**, and finally clamped to the range $[0,1]$.

GL_RED

GL_GREEN

GL_BLUE

GL_ALPHA

GL_RGB

GL_RGBA

GL_LUMINANCE

GL_LUMINANCE_ALPHA

Processing differs depending on whether color buffers store color indices or RGBA color components. If color indices are stored, they are read from the color buffer selected by **glReadBuffer**. Each index is converted to fixed point, shifted left or right depending on the value and sign of **GL_INDEX_SHIFT**, and added to **GL_INDEX_OFFSET**. Indices are then replaced by the red, green, blue, and alpha values obtained by indexing the tables **GL_PIXEL_MAP_I_TO_R**, **GL_PIXEL_MAP_I_TO_G**, **GL_PIXEL_MAP_I_TO_B**, and **GL_PIXEL_MAP_I_TO_A**. Each table must be of size 2^n , but n may be different for different tables. Before an index is used to look up a value in a table of size 2^n , it must be masked against $2^n - 1$.

If RGBA color components are stored in the color buffers, they are read from the color buffer selected by **glReadBuffer**. Each color component is converted to floating point such that zero intensity maps to 0.0 and full intensity maps to 1.0. Each component is then multiplied by **GL_c_SCALE** and added to **GL_c_BIAS**, where c is RED, GREEN, BLUE, or ALPHA. Finally, if **GL_MAP_COLOR** is **GL_TRUE**, each component is clamped to the range $[0,1]$, scaled to the size of its corresponding table, and is then replaced by its mapping in the table **GL_PIXEL_MAP_c_TO_c**, where c is R, G, B, or A.

Unneeded data is then discarded. For example, **GL_RED** discards the green, blue, and alpha components, while **GL_RGB** discards only the alpha component. **GL_LUMINANCE** computes a single-component value as the sum of the red, green, and blue components, and **GL_LUMINANCE_ALPHA** does the same, while keeping alpha as a second value. The

final values are clamped to the range [0,1].

The shift, scale, bias, and lookup factors just described are all specified by **glPixelTransfer**. The lookup table contents themselves are specified by **glPixelMap**.

Finally, the indices or components are converted to the proper format, as specified by *type*. If *format* is **GL_COLOR_INDEX** or **GL_STENCIL_INDEX** and *type* is not **GL_FLOAT**, each index is masked with the mask value given in the following table. If *type* is **GL_FLOAT**, then each integer index is converted to single-precision floating-point format.

If *format* is **GL_RED**, **GL_GREEN**, **GL_BLUE**, **GL_ALPHA**, **GL_RGB**, **GL_RGBA**, **GL_LUMINANCE**, or **GL_LUMINANCE_ALPHA** and *type* is not **GL_FLOAT**, each component is multiplied by the multiplier shown in the following table. If *type* is **GL_FLOAT**, then each component is passed as is (or converted to the client's single-precision floating-point format if it is different from the one used by the GL).

<i>type</i>	<i>index mask</i>	<i>component conversion</i>
GL_UNSIGNED_BYTE	2^8-1	$(2^8-1)c$
GL_BYTE	2^7-1	$[(2^8-1)c-1]/2$
GL_BITMAP	1	1
GL_UNSIGNED_SHORT	$2^{16}-1$	$(2^{16}-1)c$
GL_SHORT	$2^{15}-1$	$[(2^{16}-1)c-1]/2$
GL_UNSIGNED_INT	$2^{32}-1$	$(2^{32}-1)c$
GL_INT	$2^{31}-1$	$[(2^{32}-1)c-1]/2$
GL_FLOAT	none	c

Return values are placed in memory as follows. If *format* is **GL_COLOR_INDEX**, **GL_STENCIL_INDEX**, **GL_DEPTH_COMPONENT**, **GL_RED**, **GL_GREEN**, **GL_BLUE**, **GL_ALPHA**, or **GL_LUMINANCE**, a single value is returned and the data for the *i*th pixel in the *j*th row is placed in location $(j) \text{ width} + i$. **GL_RGB** returns three values, **GL_RGBA** returns four values, and **GL_LUMINANCE_ALPHA** returns two values for each pixel, with all values corresponding to a single pixel occupying contiguous space in *pixels*. Storage parameters set by

glPixelStore, such as **GL_PACK_LSB_FIRST** and **GL_PACK_SWAP_BYTES**, affect the way that data is written into memory. See **glPixelStore** for a description.

NOTES

Values for pixels that lie outside the window connected to the current GL context are undefined.

If an error is generated, no change is made to the contents of *pixels*.

ERRORS

GL_INVALID_ENUM is generated if *format* or *type* is not an accepted value.

GL_INVALID_ENUM is generated if *type* is **GL_BITMAP** and *format* is not **GL_COLOR_INDEX** or **GL_STENCIL_INDEX**.

GL_INVALID_VALUE is generated if either *width* or *height* is negative.

GL_INVALID_OPERATION is generated if *format* is **GL_COLOR_INDEX** and the color buffers store RGBA color components.

GL_INVALID_OPERATION is generated if *format* is **GL_STENCIL_INDEX** and there is no stencil buffer.

GL_INVALID_OPERATION is generated if *format* is **GL_DEPTH_COMPONENT** and there is no depth buffer.

GL_INVALID_OPERATION is generated if **glReadPixels** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_INDEX_MODE**

SEE ALSO

glCopyPixels, **glDrawPixels**, **glPixelMap**, **glPixelStore**,
glPixelTransfer,
glReadBuffer

NAME

glRectd, glRectf, glRecti, glRects, glRectdv, glRectfv, glRectiv, glRectsv - draw a rectangle

C SPECIFICATION

```
void glRectd( GLdouble x1,
              GLdouble y1,
              GLdouble x2,
              GLdouble y2 )
void glRectf( GLfloat x1,
              GLfloat y1,
              GLfloat x2,
              GLfloat y2 )
void glRecti( GLint x1,
              GLint y1,
              GLint x2,
              GLint y2 )
void glRects( GLshort x1,
              GLshort y1,
              GLshort x2,
              GLshort y2 )
```

PARAMETERS

x1, y1 Specify one vertex of a rectangle.

x2, y2 Specify the opposite vertex of the rectangle.

C SPECIFICATION

```
void glRectdv( const GLdouble *v1,
               const GLdouble *v2 )
void glRectfv( const GLfloat *v1,
               const GLfloat *v2 )
void glRectiv( const GLint *v1,
               const GLint *v2 )
void glRectsv( const GLshort *v1,
               const GLshort *v2 )
```

PARAMETERS

v1 Specifies a pointer to one vertex of a rectangle.

v2 Specifies a pointer to the opposite vertex of the rectangle.

DESCRIPTION

glRect supports efficient specification of rectangles as two corner points. Each rectangle command takes four arguments, organized either as two consecutive pairs of (x,y) coordinates, or as two pointers to arrays, each containing an (x,y) pair. The resulting rectangle is defined in the z=0 plane.

glRect(x1, y1, x2, y2) is exactly equivalent to the following sequence: **glBegin**(**GL_POLYGON**); **glVertex2**(x1, y1); **glVertex2**(x2, y1); **glVertex2**(x2, y2); **glVertex2**(x1, y2); **glEnd**(); Note that if the second vertex is above and to the right of the first vertex, the rectangle is constructed with a counterclockwise winding.

ERRORS

GL_INVALID_OPERATION is generated if **glRect** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

SEE ALSO

glBegin, **glVertex**

NAME

glRenderMode - set rasterization mode

C SPECIFICATION

GLint **glRenderMode**(GLenum *mode*)

PARAMETERS

mode Specifies the rasterization mode. Three values are accepted: **GL_RENDER**, **GL_SELECT**, and **GL_FEEDBACK**. The initial value is **GL_RENDER**.

DESCRIPTION

glRenderMode sets the rasterization mode. It takes one argument, *mode*, which can assume one of three predefined values:

GL_RENDER	Render mode. Primitives are rasterized, producing pixel fragments, which are written into the frame buffer. This is the normal mode and also the default mode.
GL_SELECT	Selection mode. No pixel fragments are produced, and no change to the frame buffer contents is made. Instead, a record of the names of primitives that would have been drawn if the render mode had been GL_RENDER is returned in a select buffer, which must be created (see glSelectBuffer) before selection mode is entered.
GL_FEEDBACK	Feedback mode. No pixel fragments are produced, and no change to the frame buffer contents is made. Instead, the coordinates and attributes of vertices that would have been drawn if the render mode had been GL_RENDER is returned in a feedback buffer, which must be created (see glFeedbackBuffer) before feedback mode is entered.

The return value of **glRenderMode** is determined by the render mode at the time **glRenderMode** is called, rather than by *mode*. The values returned for the three render modes are as follows:

GL_RENDER	0.
GL_SELECT	The number of hit records transferred to the select buffer.
GL_FEEDBACK	The number of values (not vertices) transferred to the feedback buffer.

See the **glSelectBuffer** and **glFeedbackBuffer** reference pages for more details concerning selection and feedback operation.

NOTES

If an error is generated, **glRenderMode** returns 0 regardless of the current render mode.

ERRORS

GL_INVALID_ENUM is generated if *mode* is not one of the three accepted values.

GL_INVALID_OPERATION is generated if **glSelectBuffer** is called while the render mode is **GL_SELECT**, or if **glRenderMode** is called with argument **GL_SELECT** before **glSelectBuffer** is called at least once.

GL_INVALID_OPERATION is generated if **glFeedbackBuffer** is called while the render mode is **GL_FEEDBACK**, or if **glRenderMode** is called with argument **GL_FEEDBACK** before **glFeedbackBuffer** is called at least once.

GL_INVALID_OPERATION is generated if **glRenderMode** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_RENDER_MODE**

SEE ALSO

glFeedbackBuffer, **glInitNames**, **glLoadName**, **glPassThrough**, **glPushName**, **glSelectBuffer**

NAME

glRotated, **glRotatef** - multiply the current matrix by a rotation matrix

C SPECIFICATION

```
void glRotated( GLdouble angle,
                GLdouble x,
                GLdouble y,
                GLdouble z )
void glRotatef( GLfloat angle,
                GLfloat x,
                GLfloat y,
                GLfloat z )
```

PARAMETERS

angle Specifies the angle of rotation, in degrees.

x, *y*, *z*
Specify the *x*, *y*, and *z* coordinates of a vector, respectively.

DESCRIPTION

glRotate produces a rotation of *angle* degrees around the vector (*x*,*y*,*z*). The current matrix (see **glMatrixMode**) is multiplied by a rotation matrix with the product replacing the current matrix, as if **glMultMatrix** were called with the following matrix as its argument:

$$\begin{pmatrix} xx(1-c)+c & xy(1-c)-zs & xz(1-c)+ys & 0 \\ yx(1-c)+zs & yy(1-c)+c & yz(1-c)-xs & 0 \\ xz(1-c)-ys & yz(1-c)+xs & zz(1-c)+c & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

Where $c = \cos(\text{angle})$, $s = \sin(\text{angle})$, and $||(\text{ } x,y,z \text{ })|| = 1$ (if not, the GL will normalize this vector).

If the matrix mode is either **GL_MODELVIEW** or **GL_PROJECTION**, all objects drawn after **glRotate** is called are rotated. Use **glPushMatrix** and **glPopMatrix** to save and restore the unrotated coordinate system.

NOTES

This rotation follows the right-hand rule, so if the vector (x,y,z) points toward the user, the rotation will be counterclockwise.

ERRORS

GL_INVALID_OPERATION is generated if **glRotate** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_MATRIX_MODE**
glGet with argument **GL_MODELVIEW_MATRIX**
glGet with argument **GL_PROJECTION_MATRIX**
glGet with argument **GL_TEXTURE_MATRIX**

SEE ALSO

glMatrixMode, **glMultMatrix**, **glPushMatrix**, **glScale**,
glTranslate

NAME

glScaled, glScalef - multiply the current matrix by a general scaling matrix

C SPECIFICATION

```
void glScaled( GLdouble x,  
               GLdouble y,  
               GLdouble z )  
void glScalef( GLfloat x,  
               GLfloat y,  
               GLfloat z )
```

PARAMETERS

x, y, z

Specify scale factors along the *x*, *y*, and *z* axes, respectively.

DESCRIPTION

glScale produces a nonuniform scaling along the *x*, *y*, and *z* axes. The three parameters indicate the desired scale factor along each of the three axes.

The current matrix (see **glMatrixMode**) is multiplied by this scale matrix, and the product replaces the current matrix as if **glScale** were called with the following matrix as its argument:

$$\begin{pmatrix} x & 0 & 0 & 0 \\ 0 & y & 0 & 0 \\ 0 & 0 & z & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

If the matrix mode is either **GL_MODELVIEW** or **GL_PROJECTION**, all objects drawn after **glScale** is called are scaled.

Use **glPushMatrix** and **glPopMatrix** to save and restore the unscaled coordinate system.

NOTES

If scale factors other than 1 are applied to the modelview matrix and lighting is enabled, lighting often appears

wrong. In that case, enable automatic normalization of normals by calling **glEnable** with the argument **GL_NORMALIZE**.

ERRORS

GL_INVALID_OPERATION is generated if **glScale** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_MATRIX_MODE**
glGet with argument **GL_MODELVIEW_MATRIX**
glGet with argument **GL_PROJECTION_MATRIX**
glGet with argument **GL_TEXTURE_MATRIX**

SEE ALSO

glMatrixMode, **glMultMatrix**, **glPushMatrix**, **glRotate**,
glTranslate

NAME

glScissor - define the scissor box

C SPECIFICATION

```
void glScissor( GLint x,  
                GLint y,  
                GLsizei width,  
                GLsizei height )
```

PARAMETERS

x, y Specify the lower left corner of the scissor box.
Initially (0, 0).

width, height

Specify the width and height of the scissor box. When a GL context is first attached to a window, *width* and *height* are set to the dimensions of that window.

DESCRIPTION

glScissor defines a rectangle, called the scissor box, in window coordinates. The first two arguments, *x* and *y*, specify the lower left corner of the box. *width* and *height* specify the width and height of the box.

To enable and disable the scissor test, call **glEnable** and **glDisable** with argument **GL_SCISSOR_TEST**. The test is initially disabled. While the test is enabled, only pixels that lie within the scissor box can be modified by drawing commands. Window coordinates have integer values at the shared corners of frame buffer pixels. **glScissor(0,0,1,1)** allows modification of only the lower left pixel in the window, and **glScissor(0,0,0,0)** doesn't allow modification of any pixels in the window.

When the scissor test is disabled, it is as though the scissor box includes the entire window.

ERRORS

GL_INVALID_VALUE is generated if either *width* or *height* is negative.

GL_INVALID_OPERATION is generated if **glScissor** is executed between the execution of **glBegin** and the corresponding

execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_SCISSOR_BOX**

glIsEnabled with argument **GL_SCISSOR_TEST**

SEE ALSO

glEnable, **glViewport**

NAME

glSelectBuffer - establish a buffer for selection mode values

C SPECIFICATION

```
void glSelectBuffer( GLsizei size,  
                    GLuint *buffer )
```

PARAMETERS

size Specifies the size of *buffer*.

buffer Returns the selection data.

DESCRIPTION

glSelectBuffer has two arguments: *buffer* is a pointer to an array of unsigned integers, and *size* indicates the size of the array. *buffer* returns values from the name stack (see **glInitNames**, **glLoadName**, **glPushName**) when the rendering mode is **GL_SELECT** (see **glRenderMode**). **glSelectBuffer** must be issued before selection mode is enabled, and it must not be issued while the rendering mode is **GL_SELECT**.

A programmer can use selection to determine which primitives are drawn into some region of a window. The region is defined by the current modelview and perspective matrices.

In selection mode, no pixel fragments are produced from rasterization. Instead, if a primitive or a raster position intersects the clipping volume defined by the viewing frustum and the user-defined clipping planes, this primitive causes a selection hit. (With polygons, no hit occurs if the polygon is culled.) When a change is made to the name stack, or when **glRenderMode** is called, a hit record is copied to *buffer* if any hits have occurred since the last such event (name stack change or **glRenderMode** call). The hit record consists of the number of names in the name stack at the time of the event, followed by the minimum and maximum depth values of all vertices that hit since the previous event, followed by the name stack contents, bottom name first.

Depth values (which are in the range [0,1]) are multiplied by $2^{32} - 1$, before being placed in the hit record.

An internal index into *buffer* is reset to 0 whenever selection mode is entered. Each time a hit record is copied into *buffer*, the index is incremented to point to the cell just past the end of the block of names - that is, to the next available cell. If the hit record is larger than the number of remaining locations in *buffer*, as much data as can fit is copied, and the overflow flag is set. If the name stack is empty when a hit record is copied, that record consists of 0 followed by the minimum and maximum depth values.

To exit selection mode, call **glRenderMode** with an argument other than **GL_SELECT**. Whenever **glRenderMode** is called while the render mode is **GL_SELECT**, it returns the number of hit records copied to *buffer*, resets the overflow flag and the selection buffer pointer, and initializes the name stack to be empty. If the overflow bit was set when **glRenderMode** was called, a negative hit record count is returned.

NOTES

The contents of *buffer* is undefined until **glRenderMode** is called with an argument other than **GL_SELECT**.

glBegin/**glEnd** primitives and calls to **glRasterPos** can result in hits.

ERRORS

GL_INVALID_VALUE is generated if *size* is negative.

GL_INVALID_OPERATION is generated if **glSelectBuffer** is called while the render mode is **GL_SELECT**, or if **glRenderMode** is called with argument **GL_SELECT** before **glSelectBuffer** is called at least once.

GL_INVALID_OPERATION is generated if **glSelectBuffer** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_NAME_STACK_DEPTH**

SEE ALSO

glFeedbackBuffer, **glInitNames**, **glLoadName**, **glPushName**, **glRenderMode**

NAME

glShadeModel - select flat or smooth shading

C SPECIFICATION

```
void glShadeModel( GLenum mode )
```

PARAMETERS

mode Specifies a symbolic value representing a shading technique. Accepted values are **GL_FLAT** and **GL_SMOOTH**. The initial value is **GL_SMOOTH**.

DESCRIPTION

GL primitives can have either flat or smooth shading. Smooth shading, the default, causes the computed colors of vertices to be interpolated as the primitive is rasterized, typically assigning different colors to each resulting pixel fragment. Flat shading selects the computed color of just one vertex and assigns it to all the pixel fragments generated by rasterizing a single primitive. In either case, the computed color of a vertex is the result of lighting if lighting is enabled, or it is the current color at the time the vertex was specified if lighting is disabled.

Flat and smooth shading are indistinguishable for points. Starting when **glBegin** is issued and counting vertices and primitives from 1, the GL gives each flat-shaded line segment *i* the computed color of vertex *i*+1, its second vertex. Counting similarly from 1, the GL gives each flat-shaded polygon the computed color of the vertex listed in the following table. This is the last vertex to specify the polygon in all cases except single polygons, where the first vertex specifies the flat-shaded color.

<i>primitive type of polygon i</i>	<i>vertex</i>
Single polygon (<i>i</i> =1)	1
Triangle strip	<i>i</i> +2
Triangle fan	<i>i</i> +2
Independent triangle	3 <i>i</i>
Quad strip	2 <i>i</i> +2
Independent quad	4 <i>i</i>

Flat and smooth shading are specified by **glShadeModel** with *mode* set to **GL_FLAT** and **GL_SMOOTH**, respectively.

ERRORS

GL_INVALID_ENUM is generated if *mode* is any value other than **GL_FLAT** or **GL_SMOOTH**.

GL_INVALID_OPERATION is generated if **glShadeModel** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_SHADE_MODEL**

SEE ALSO

glBegin, **glColor**, **glLight**, **glLightModel**

NAME

glStencilFunc - set function and reference value for stencil testing

C SPECIFICATION

```
void glStencilFunc( GLenum func,  
                   GLint ref,  
                   GLuint mask )
```

PARAMETERS

- func* Specifies the test function. Eight tokens are valid: **GL_NEVER**, **GL_LESS**, **GL_LEQUAL**, **GL_GREATER**, **GL_GEQUAL**, **GL_EQUAL**, **GL_NOTEQUAL**, and **GL_ALWAYS**. The initial value is **GL_ALWAYS**.
- ref* Specifies the reference value for the stencil test. *ref* is clamped to the range $[0, 2n-1]$, where n is the number of bitplanes in the stencil buffer. The initial value is 0.
- mask* Specifies a mask that is ANDed with both the reference value and the stored stencil value when the test is done. The initial value is all 1's.

DESCRIPTION

Stenciling, like depth-buffering, enables and disables drawing on a per-pixel basis. You draw into the stencil planes using GL drawing primitives, then render geometry and images, using the stencil planes to mask out portions of the screen. Stenciling is typically used in multipass rendering algorithms to achieve special effects, such as decals, outlining, and constructive solid geometry rendering.

The stencil test conditionally eliminates a pixel based on the outcome of a comparison between the reference value and the value in the stencil buffer. To enable and disable the test, call **glEnable** and **glDisable** with argument **GL_STENCIL_TEST**. To specify actions based on the outcome of the stencil test, call **glStencilOp**.

func is a symbolic constant that determines the stencil comparison function. It accepts one of eight values, shown in the following list. *ref* is an integer reference value

that is used in the stencil comparison. It is clamped to the range $[0, 2n-1]$, where n is the number of bitplanes in the stencil buffer. *mask* is bitwise ANDed with both the reference value and the stored stencil value, with the ANDed values participating in the comparison.

If *stencil* represents the value stored in the corresponding stencil buffer location, the following list shows the effect of each comparison function that can be specified by *func*. Only if the comparison succeeds is the pixel passed through to the next stage in the rasterization process (see **glStencilOp**). All tests treat *stencil* values as unsigned integers in the range $[0, 2n-1]$, where n is the number of bitplanes in the stencil buffer.

The following values are accepted by *func*:

GL_NEVER	Always fails.
GL_LESS	Passes if (<i>ref</i> & <i>mask</i>) < (<i>stencil</i> & <i>mask</i>).
GL_LEQUAL	Passes if (<i>ref</i> & <i>mask</i>) < (<i>stencil</i> & <i>mask</i>).
GL_GREATER	Passes if (<i>ref</i> & <i>mask</i>) > (<i>stencil</i> & <i>mask</i>).
GL_GEQUAL	Passes if (<i>ref</i> & <i>mask</i>) > (<i>stencil</i> & <i>mask</i>).
GL_EQUAL	Passes if (<i>ref</i> & <i>mask</i>) = (<i>stencil</i> & <i>mask</i>).
GL_NOTEQUAL	Passes if (<i>ref</i> & <i>mask</i>) / (<i>stencil</i> & <i>mask</i>).
GL_ALWAYS	Always passes.

NOTES

Initially, the stencil test is disabled. If there is no stencil buffer, no stencil modification can occur and it is as if the stencil test always passes.

ERRORS

GL_INVALID_ENUM is generated if *func* is not one of the eight

accepted values.

GL_INVALID_OPERATION is generated if **glStencilFunc** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_STENCIL_FUNC**
glGet with argument **GL_STENCIL_VALUE_MASK**
glGet with argument **GL_STENCIL_REF**
glGet with argument **GL_STENCIL_BITS**
glIsEnabled with argument **GL_STENCIL_TEST**

SEE ALSO

glAlphaFunc, **glBlendFunc**, **glDepthFunc**, **glEnable**,
glIsEnabled, **glLogicOp**, **glStencilOp**

NAME

glStencilMask - control the writing of individual bits in the stencil planes

C SPECIFICATION

```
void glStencilMask( GLuint mask )
```

PARAMETERS

mask Specifies a bit mask to enable and disable writing of individual bits in the stencil planes. Initially, the mask is all 1's.

DESCRIPTION

glStencilMask controls the writing of individual bits in the stencil planes. The least significant *n* bits of *mask*, where *n* is the number of bits in the stencil buffer, specify a mask. Where a 1 appears in the mask, it's possible to write to the corresponding bit in the stencil buffer. Where a 0 appears, the corresponding bit is write-protected. Initially, all bits are enabled for writing.

ERRORS

GL_INVALID_OPERATION is generated if **glStencilMask** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_STENCIL_WRITEMASK**
glGet with argument **GL_STENCIL_BITS**

SEE ALSO

glColorMask, **glDepthMask**, **glIndexMask**, **glStencilFunc**, **glStencilOp**

NAME

glStencilOp - set stencil test actions

C SPECIFICATION

```
void glStencilOp( GLenum fail,  
                  GLenum zfail,  
                  GLenum zpass )
```

PARAMETERS

- fail* Specifies the action to take when the stencil test fails. Six symbolic constants are accepted: **GL_KEEP**, **GL_ZERO**, **GL_REPLACE**, **GL_INCR**, **GL_DECR**, and **GL_INVERT**. The initial value is **GL_KEEP**.
- zfail* Specifies the stencil action when the stencil test passes, but the depth test fails. *zfail* accepts the same symbolic constants as *fail*. The initial value is **GL_KEEP**.
- zpass* Specifies the stencil action when both the stencil test and the depth test pass, or when the stencil test passes and either there is no depth buffer or depth testing is not enabled. *zpass* accepts the same symbolic constants as *fail*. The initial value is **GL_KEEP**.

DESCRIPTION

Stenciling, like depth-buffering, enables and disables drawing on a per-pixel basis. You draw into the stencil planes using GL drawing primitives, then render geometry and images, using the stencil planes to mask out portions of the screen. Stenciling is typically used in multipass rendering algorithms to achieve special effects, such as decals, outlining, and constructive solid geometry rendering.

The stencil test conditionally eliminates a pixel based on the outcome of a comparison between the value in the stencil buffer and a reference value. To enable and disable the test, call **glEnable** and **glDisable** with argument **GL_STENCIL_TEST**; to control it, call **glStencilFunc**.

glStencilOp takes three arguments that indicate what happens to the stored stencil value while stenciling is enabled. If

the stencil test fails, no change is made to the pixel's color or depth buffers, and *fail* specifies what happens to the stencil buffer contents. The following six actions are possible.

GL_KEEP	Keeps the current value.
GL_ZERO	Sets the stencil buffer value to 0.
GL_REPLACE	Sets the stencil buffer value to <i>ref</i> , as specified by glStencilFunc .
GL_INCR	Increments the current stencil buffer value. Clamps to the maximum representable unsigned value.
GL_DECR	Decrements the current stencil buffer value. Clamps to 0.
GL_INVERT	Bitwise inverts the current stencil buffer value.

Stencil buffer values are treated as unsigned integers. When incremented and decremented, values are clamped to 0 and $2^n - 1$, where n is the value returned by querying **GL_STENCIL_BITS**.

The other two arguments to **glStencilOp** specify stencil buffer actions that depend on whether subsequent depth buffer tests succeed (*zpass*) or fail (*zfail*) (see **glDepthFunc**). The actions are specified using the same six symbolic constants as *fail*. Note that *zfail* is ignored when there is no depth buffer, or when the depth buffer is not enabled. In these cases, *fail* and *zpass* specify stencil action when the stencil test fails and passes, respectively.

NOTES

Initially the stencil test is disabled. If there is no stencil buffer, no stencil modification can occur and it is as if the stencil tests always pass, regardless of any call to **glStencilOp**.

ERRORS

GL_INVALID_ENUM is generated if *fail*, *zfail*, or *zpass* is any value other than the six defined constant values.

GL_INVALID_OPERATION is generated if **glStencilOp** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_STENCIL_FAIL**
glGet with argument **GL_STENCIL_PASS_DEPTH_PASS**
glGet with argument **GL_STENCIL_PASS_DEPTH_FAIL**
glGet with argument **GL_STENCIL_BITS**
glIsEnabled with argument **GL_STENCIL_TEST**

SEE ALSO

glAlphaFunc, **glBlendFunc**, **glDepthFunc**, **glEnable**, **glLogicOp**,
glStencilFunc

NAME

glTexCoord1d, **glTexCoord1f**, **glTexCoord1i**, **glTexCoord1s**,
glTexCoord2d, **glTexCoord2f**, **glTexCoord2i**, **glTexCoord2s**,
glTexCoord3d, **glTexCoord3f**, **glTexCoord3i**, **glTexCoord3s**,
glTexCoord4d, **glTexCoord4f**, **glTexCoord4i**, **glTexCoord4s**,
glTexCoord1dv, **glTexCoord1fv**, **glTexCoord1iv**, **glTexCoord1sv**,
glTexCoord2dv, **glTexCoord2fv**, **glTexCoord2iv**, **glTexCoord2sv**,
glTexCoord3dv, **glTexCoord3fv**, **glTexCoord3iv**, **glTexCoord3sv**,
glTexCoord4dv, **glTexCoord4fv**, **glTexCoord4iv**, **glTexCoord4sv** -
set the current texture coordinates

C SPECIFICATION

```
void glTexCoord1d( GLdouble s )
void glTexCoord1f( GLfloat s )
void glTexCoord1i( GLint s )
void glTexCoord1s( GLshort s )
void glTexCoord2d( GLdouble s,
                   GLdouble t )
void glTexCoord2f( GLfloat s,
                   GLfloat t )
void glTexCoord2i( GLint s,
                   GLint t )
void glTexCoord2s( GLshort s,
                   GLshort t )
void glTexCoord3d( GLdouble s,
                   GLdouble t,
                   GLdouble r )
void glTexCoord3f( GLfloat s,
                   GLfloat t,
                   GLfloat r )
void glTexCoord3i( GLint s,
                   GLint t,
                   GLint r )
void glTexCoord3s( GLshort s,
                   GLshort t,
                   GLshort r )
void glTexCoord4d( GLdouble s,
                   GLdouble t,
                   GLdouble r,
                   GLdouble q )
void glTexCoord4f( GLfloat s,
                   GLfloat t,
                   GLfloat r,
                   GLfloat q )
```



```

void glTexCoord4i( GLint s,
                   GLint t,
                   GLint r,
                   GLint q )
void glTexCoord4s( GLshort s,
                   GLshort t,
                   GLshort r,
                   GLshort q )

```

PARAMETERS

s, *t*, *r*, *q*
Specify *s*, *t*, *r*, and *q* texture coordinates. Not all parameters are present in all forms of the command.

C SPECIFICATION

```

void glTexCoord1dv( const GLdouble *v )
void glTexCoord1fv( const GLfloat *v )
void glTexCoord1iv( const GLint *v )
void glTexCoord1sv( const GLshort *v )
void glTexCoord2dv( const GLdouble *v )
void glTexCoord2fv( const GLfloat *v )
void glTexCoord2iv( const GLint *v )
void glTexCoord2sv( const GLshort *v )
void glTexCoord3dv( const GLdouble *v )
void glTexCoord3fv( const GLfloat *v )
void glTexCoord3iv( const GLint *v )
void glTexCoord3sv( const GLshort *v )
void glTexCoord4dv( const GLdouble *v )
void glTexCoord4fv( const GLfloat *v )
void glTexCoord4iv( const GLint *v )
void glTexCoord4sv( const GLshort *v )

```

PARAMETERS

v Specifies a pointer to an array of one, two, three, or four elements, which in turn specify the *s*, *t*, *r*, and *q* texture coordinates.

DESCRIPTION

glTexCoord specifies texture coordinates in one, two, three, or four dimensions. **glTexCoord1** sets the current texture coordinates to (*s*, 0, 0, 1); a call to **glTexCoord2** sets them to (*s*, *t*, 0, 1). Similarly, **glTexCoord3** specifies the texture coordinates as (*s*, *t*, *r*,

1), and **glTexCoord4** defines all four components explicitly as (s, t, r, q) .

The current texture coordinates are part of the data that is associated with each vertex and with the current raster position. Initially, the values for s , t , r , and q are $(0, 0, 0, 1)$.

NOTES

The current texture coordinates can be updated at any time. In particular,

glTexCoord can be called between a call to **glBegin** and the corresponding call to **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_CURRENT_TEXTURE_COORDS**

SEE ALSO

glTexCoordPointer, **glVertex**

NAME

glTexCoordPointer - define an array of texture coordinates

C SPECIFICATION

```
void glTexCoordPointer( GLint size,  
                        GLenum type,  
                        GLsizei stride,  
                        const GLvoid *pointer )
```

PARAMETERS

<i>size</i>	Specifies the number of coordinates per array element. Must be 1, 2, 3 or 4. The initial value is 4.
<i>type</i>	Specifies the data type of each texture coordinate. Symbolic constants GL_SHORT , GL_INT , GL_FLOAT , or GL_DOUBLE are accepted. The initial value is GL_FLOAT .
<i>stride</i>	Specifies the byte offset between consecutive array elements. If <i>stride</i> is 0, the array elements are understood to be tightly packed. The initial value is 0.
<i>pointer</i>	Specifies a pointer to the first coordinate of the first element in the array.

DESCRIPTION

glTexCoordPointer specifies the location and data format of an array of texture coordinates to use when rendering. *size* specifies the number of coordinates per element, and must be 1, 2, 3, or 4. *type* specifies the data type of each texture coordinate and *stride* specifies the byte stride from one array element to the next allowing vertexes and attributes to be packed into a single array or stored in separate arrays. (Single-array storage may be more efficient on some implementations; see **glInterleavedArrays**.) When a texture coordinate array is specified, *size*, *type*, *stride*, and *pointer* are saved client-side state.

To enable and disable the texture coordinate array, call **glEnableClientState** and **glDisableClientState** with the

argument **GL_TEXTURE_COORD_ARRAY**. If enabled, the texture coordinate array is used when **glDrawArrays**, **glDrawElements** or **glArrayElement** is called.

Use **glDrawArrays** to construct a sequence of primitives (all of the same type) from prespecified vertex and vertex attribute arrays. Use **glArrayElement** to specify primitives by indexing vertexes and vertex attributes and **glDrawElements** to construct a sequence of primitives by indexing vertexes and vertex attributes.

NOTES

glTexCoordPointer is available only if the GL version is 1.1 or greater.

The texture coordinate array is initially disabled and it won't be accessed when

glArrayElement, **glDrawElements** or **glDrawArrays** is called.

Execution of **glTexCoordPointer** is not allowed between the execution of **glBegin** and the corresponding execution of **glEnd**, but an error may or may not be generated. If no error is generated, the operation is undefined.

glTexCoordPointer is typically implemented on the client side with no protocol.

The texture coordinate array parameters are client-side state and are therefore not saved or restored by **glPushAttrib** and **glPopAttrib**. Use **glPushClientAttrib** and **glPopClientAttrib** instead.

ERRORS

GL_INVALID_VALUE is generated if *size* is not 1, 2, 3, or 4.

GL_INVALID_ENUM is generated if *type* is not an accepted value.

GL_INVALID_VALUE is generated if *stride* is negative.

ASSOCIATED GETS

glIsEnabled with argument **GL_TEXTURE_COORD_ARRAY**

glGet with argument **GL_TEXTURE_COORD_ARRAY_SIZE**

glGet with argument **GL_TEXTURE_COORD_ARRAY_TYPE**

glGetPointerv with argument **GL_TEXTURE_COORD_ARRAY_POINTER**

SEE ALSO

`glArrayElement`, `glColorPointer`, `glDrawArrays`,
`glDrawElements`,
`glEdgeFlagPointer`, `glEnable`, `glGetPointerv`, `glIndexPointer`,
`glNormalPointer`, `glPopClientAttrib`, `glPushClientAttrib`,
`glTexCoord`, `glVertexPointer`

NAME

glTexEnvf, glTexEnvi, glTexEnvfv, glTexEnviv - set texture environment parameters

C SPECIFICATION

```
void glTexEnvf( GLenum target,
               GLenum pname,
               GLfloat param )
void glTexEnvi( GLenum target,
               GLenum pname,
               GLint param )
```

PARAMETERS

target Specifies a texture environment. Must be **GL_TEXTURE_ENV**.

pname Specifies the symbolic name of a single-valued texture environment parameter. Must be **GL_TEXTURE_ENV_MODE**.

param Specifies a single symbolic constant, one of **GL_MODULATE**, **GL_DECAL**, **GL_BLEND**, or **GL_REPLACE**.

C SPECIFICATION

```
void glTexEnvfv( GLenum target,
                GLenum pname,
                const GLfloat *params )
void glTexEnviv( GLenum target,
                GLenum pname,
                const GLint *params )
```

PARAMETERS

target Specifies a texture environment. Must be **GL_TEXTURE_ENV**.

pname Specifies the symbolic name of a texture environment parameter. Accepted values are **GL_TEXTURE_ENV_MODE** and **GL_TEXTURE_ENV_COLOR**.

params Specifies a pointer to a parameter array that contains either a single symbolic constant or an RGBA color.

DESCRIPTION

A texture environment specifies how texture values are interpreted when a fragment is textured. *target* must be

Base internal format	Texture functions			
	GL_MODULATE	GL_DECAL	GL_BLEND	GL_REPLACE
GL_ALPHA	$C = C$ $A = A \ A$	undefined	$C = C$ $Av = Af$	$C = C$ $Av = Af$
GL_LUMINANCE 1	$C = L \ C$ $v \ t \ f$ $A = A$	undefined	$C = (1-L)C$ $v + L \ Ct \ f$ $t \ c$ $A = A$	$C = L$ $v \ t$ $A = A$
GL_LUMINANCE _ALPHA 2	$C = L \ C$ $v \ t \ f$ $A = A \ A$	undefined	$C = (1-L)C$ $v + L \ C \ f$ $t \ c$ $A = A \ A$	$C = L$ $v \ t$ $A = A$
GL_INTENSITY	$C = C \ I$ $v \ f \ t$ $A = A \ I$ $v \ f \ t$	undefined	$C = (1-I)C$ $v + I \ Ct \ f$ $t \ c$ $A = (1-I)A$ $v + I \ At \ f$	$C = I$ $v \ t$ $A = I$ $v \ t$
GL_RGB 3	$C = C \ C$ $v \ t \ f$ $A = A$	$C = C$ $v \ t$ $A = A$	$C = (1-C \ C$ $v + C \ C) \ f$ $t \ c$ $A = A$	$C = C$ $v \ t$ $A = A$
GL_RGBA 4	$C = C \ C$ $v \ t \ f$ $A = A \ A$	$C = (1-A)C$ $v + A \ Ct \ f$ $t \ t$ $A = A$	$C = (1-C \ C$ $v + C \ C) \ f$ $t \ c$ $A = A \ A$	$C = C$ $v \ t$ $A = A$

If *pname* is **GL_TEXTURE_ENV_COLOR**, *params* is a pointer to an array that holds an RGBA color consisting of four values. Integer color components are interpreted linearly such that the most positive integer maps to 1.0, and the most negative integer maps to -1.0. The values are clamped to the range [0,1] when they are specified. *C* takes these four values.

C

GL_TEXTURE_ENV_MODE defaults to **GL_MODULATE** and
GL_TEXTURE_ENV_COLOR defaults to (0, 0, 0, 0).

NOTES

GL_REPLACE may only be used if the GL version is 1.1 or greater.

Internal formats other than 1, 2, 3, or 4 may only be used if the GL version is 1.1 or greater.

ERRORS

GL_INVALID_ENUM is generated when *target* or *pname* is not one of the accepted defined values, or when *params* should have a defined constant value (based on the value of *pname*) and does not.

GL_INVALID_OPERATION is generated if **glTexEnv** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGetTexEnv

SEE ALSO

glCopyPixels, **glCopyTexImage1D**, **glCopyTexImage2D**,
glCopyTexSubImage1D, **glCopyTexSubImage2D**, **glTexImage1D**,
glTexImage2D, **glTexParameter**, **glTexSubImage1D**,
glTexSubImage2D

NAME

glTexGend, glTexGenf, glTexGeni, glTexGendv, glTexGenfv, glTexGeniv - control the generation of texture coordinates

C SPECIFICATION

```
void glTexGend( GLenum coord,
               GLenum pname,
               GLdouble param )
void glTexGenf( GLenum coord,
               GLenum pname,
               GLfloat param )
void glTexGeni( GLenum coord,
               GLenum pname,
               GLint param )
```

PARAMETERS

coord Specifies a texture coordinate. Must be one of **GL_S**, **GL_T**, **GL_R**, or **GL_Q**.

pname Specifies the symbolic name of the texture-coordinate generation function. Must be **GL_TEXTURE_GEN_MODE**.

param Specifies a single-valued texture generation parameter, one of **GL_OBJECT_LINEAR**, **GL_EYE_LINEAR**, or **GL_SPHERE_MAP**.

C SPECIFICATION

```
void glTexGendv( GLenum coord,
                GLenum pname,
                const GLdouble *params )
void glTexGenfv( GLenum coord,
                GLenum pname,
                const GLfloat *params )
void glTexGeniv( GLenum coord,
                GLenum pname,
                const GLint *params )
```

PARAMETERS

coord Specifies a texture coordinate. Must be one of **GL_S**, **GL_T**, **GL_R**, or **GL_Q**.

pname

Specifies the symbolic name of the texture-coordinate generation function or function parameters. Must be **GL_TEXTURE_GEN_MODE**, **GL_OBJECT_PLANE**, or **GL_EYE_PLANE**.

params

Specifies a pointer to an array of texture generation parameters. If *pname* is **GL_TEXTURE_GEN_MODE**, then the array must contain a single symbolic constant, one of **GL_OBJECT_LINEAR**, **GL_EYE_LINEAR**, or **GL_SPHERE_MAP**. Otherwise, *params* holds the coefficients for the texture-coordinate generation function specified by *pname*.

DESCRIPTION

glTexGen selects a texture-coordinate generation function or supplies coefficients for one of the functions. *coord* names one of the (*s*, *t*, *r*, *q*) texture coordinates; it must be one of the symbols **GL_S**, **GL_T**, **GL_R**, or **GL_Q**. *pname* must be one of three symbolic constants: **GL_TEXTURE_GEN_MODE**, **GL_OBJECT_PLANE**, or **GL_EYE_PLANE**. If *pname* is **GL_TEXTURE_GEN_MODE**, then *params* chooses a mode, one of **GL_OBJECT_LINEAR**, **GL_EYE_LINEAR**, or **GL_SPHERE_MAP**. If *pname* is either **GL_OBJECT_PLANE** or **GL_EYE_PLANE**, *params* contains coefficients for the corresponding texture generation function.

If the texture generation function is **GL_OBJECT_LINEAR**, the function

$$g = p_1 x + p_2 y + p_3 z + p_4 w$$

is used, where *g* is the value computed for the coordinate named in *coord*, *p*₁, *p*₂, *p*₃, and *p*₄ are the four values supplied in *params*, and *x*₃, *y*₄, *z*₄, and *w* are the object coordinates of the vertex. This function can be used, for example, to texture-map terrain using sea level as a reference plane (defined by *p*₁, *p*₂, *p*₃, and *p*₄). The altitude of a terrain vertex is computed by the **GL_OBJECT_LINEAR** coordinate generation function as its distance from sea level; that altitude can then be used to index the texture image to map white snow onto peaks and green grass onto foothills.

If the texture generation function is **GL_EYE_LINEAR**, the function

$$g = p_1' x + p_2' y + p_3' z + p_4' w$$

is used, where

$$\begin{pmatrix} p_1 & p_2 & p_3 & p_4 \end{pmatrix} = \begin{pmatrix} p_1 & p_2 & p_3 & p_4 \end{pmatrix} M^{-1}$$

and x , y , z , and w are the eye coordinates of the vertex, p_1, p_2, p_3 , and p_4 are the values supplied in *params*, and M is the modelview matrix when **glTexGen** is invoked. If M is poorly conditioned or singular, texture coordinates generated by the resulting function may be inaccurate or undefined.

Note that the values in *params* define a reference plane in eye coordinates. The modelview matrix that is applied to them may not be the same one in effect when the polygon vertices are transformed. This function establishes a field of texture coordinates that can produce dynamic contour lines on moving objects.

If *pname* is **GL_SPHERE_MAP** and *coord* is either **GL_S** or **GL_T**, s and t texture coordinates are generated as follows. Let u be the unit vector pointing from the origin to the polygon vertex (in eye coordinates). Let n' be the current normal, after transformation to eye coordinates. Let

$$f = \begin{pmatrix} f_x & f_y & f_z \end{pmatrix}^T$$

be the reflection vector such that z

$$f = u - 2n' \cdot n'$$

Finally, let $m = 2 \sqrt{f_x^2 + f_y^2 + (f_z + 1)^2}$. Then the values assigned to the s and t texture coordinates are

$$s = \frac{f_x}{m} + \frac{f_y}{2}$$

$$t = \frac{f_y}{m} + \frac{f_z}{2}$$

To enable or disable a texture-coordinate generation function, call **glEnable** or **glDisable** with one of the symbolic texture-coordinate names (**GL_TEXTURE_GEN_S**, **GL_TEXTURE_GEN_T**, **GL_TEXTURE_GEN_R**, or **GL_TEXTURE_GEN_Q**) as the argument. When enabled, the specified texture coordinate is computed according to the generating function associated with that coordinate. When disabled, subsequent vertices take the specified texture coordinate from the current set of texture coordinates. Initially, all texture generation functions are set to **GL_EYE_LINEAR** and are disabled. Both s

plane equations are (1, 0, 0, 0), both t plane equations are (0, 1, 0, 0), and all r and q plane equations are (0, 0, 0, 0).

ERRORS

GL_INVALID_ENUM is generated when *coord* or *pname* is not an accepted defined value, or when *pname* is **GL_TEXTURE_GEN_MODE** and *params* is not an accepted defined value.

GL_INVALID_ENUM is generated when *pname* is **GL_TEXTURE_GEN_MODE**, *params* is **GL_SPHERE_MAP**, and *coord* is either **GL_R** or **GL_Q**.

GL_INVALID_OPERATION is generated if **glTexGen** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGetTexGen

glIsEnabled with argument **GL_TEXTURE_GEN_S**

glIsEnabled with argument **GL_TEXTURE_GEN_T**

glIsEnabled with argument **GL_TEXTURE_GEN_R**

glIsEnabled with argument **GL_TEXTURE_GEN_Q**

SEE ALSO

glCopyPixels, **glCopyTexImage2D**, **glCopyTexSubImage1D**,
glCopyTexSubImage2D, **glTexEnv**, **glTexImage1D**, **glTexImage2D**,
glTexParameter, **glTexSubImage1D**, **glTexSubImage2D**

NAME

glTexImage1D - specify a one-dimensional texture image

C SPECIFICATION

```
void glTexImage1D( GLenum target,  
                  GLint level,  
                  GLint internalformat,  
                  GLsizei width,  
                  GLint border,  
                  GLenum format,  
                  GLenum type,  
                  const GLvoid *pixels )
```

PARAMETERS

<i>target</i>	Specifies the target texture. Must be GL_TEXTURE_1D or GL_PROXY_TEXTURE_1D .
<i>level</i>	Specifies the level-of-detail number. Level 0 is the base image level. Level <i>n</i> is the <i>n</i> th mipmap reduction image.
<i>internalformat</i>	Specifies the number of color components in the texture. Must be 1, 2, 3, or 4, or one of the following symbolic constants: GL_ALPHA , GL_ALPHA4 , GL_ALPHA8 , GL_ALPHA12 , GL_ALPHA16 , GL_LUMINANCE , GL_LUMINANCE4 , GL_LUMINANCE8 , GL_LUMINANCE12 , GL_LUMINANCE16 , GL_LUMINANCE_ALPHA , GL_LUMINANCE4_ALPHA4 , GL_LUMINANCE6_ALPHA2 , GL_LUMINANCE8_ALPHA8 , GL_LUMINANCE12_ALPHA4 , GL_LUMINANCE12_ALPHA12 , GL_LUMINANCE16_ALPHA16 , GL_INTENSITY , GL_INTENSITY4 , GL_INTENSITY8 , GL_INTENSITY12 , GL_INTENSITY16 , GL_RGB , GL_R3_G3_B2 , GL_RGB4 , GL_RGB5 , GL_RGB8 , GL_RGB10 , GL_RGB12 , GL_RGB16 , GL_RGBA , GL_RGBA2 , GL_RGBA4 , GL_RGB5_A1 , GL_RGBA8 , GL_RGB10_A2 , GL_RGBA12 , or GL_RGBA16 .
<i>width</i>	Specifies the width of the texture image. Must be $2n+2(\text{border})$ for some integer <i>n</i> . All implementations support texture images that are at least 64 texels wide. The height of

the 1D texture image is 1.

<i>border</i>	Specifies the width of the border. Must be either 0 or 1.
<i>format</i>	Specifies the format of the pixel data. The following symbolic values are accepted: GL_COLOR_INDEX , GL_RED , GL_GREEN , GL_BLUE , GL_ALPHA , GL_RGB , GL_RGBA , GL_LUMINANCE , and GL_LUMINANCE_ALPHA .
<i>type</i>	Specifies the data type of the pixel data. The following symbolic values are accepted: GL_UNSIGNED_BYTE , GL_BYTE , GL_BITMAP , GL_UNSIGNED_SHORT , GL_SHORT , GL_UNSIGNED_INT , GL_INT , and GL_FLOAT .
<i>pixels</i>	Specifies a pointer to the image data in memory.

DESCRIPTION

Texturing maps a portion of a specified texture image onto each graphical primitive for which texturing is enabled. To enable and disable one-dimensional texturing, call **glEnable** and **glDisable** with argument **GL_TEXTURE_1D**.

Texture images are defined with **glTexImage1D**. The arguments describe the parameters of the texture image, such as width, width of the border, level-of-detail number (see **glTexParameter**), and the internal resolution and format used to store the image. The last three arguments describe how the image is represented in memory; they are identical to the pixel formats used for **glDrawPixels**.

If *target* is **GL_PROXY_TEXTURE_1D**, no data is read from *pixels*, but all of the texture image state is recalculated, checked for consistency, and checked against the implementation's capabilities. If the implementation cannot handle a texture of the requested texture size, it sets all of the image state to 0, but does not generate an error (see **glGetError**). To query for an entire mipmap array, use an image array level greater than or equal to 1.

If *target* is **GL_TEXTURE_1D**, data is read from *pixels* as a sequence of signed or unsigned bytes, shorts, or longs, or single-precision floating-point values, depending on *type*.

These values are grouped into sets of one, two, three, or four values, depending on *format*, to form elements. If *type* is **GL_BITMAP**, the data is considered as a string of unsigned bytes (and *format* must be **GL_COLOR_INDEX**). Each data byte is treated as eight 1-bit elements, with bit ordering determined by **GL_UNPACK_LSB_FIRST** (see **glPixelStore**).

The first element corresponds to the left end of the texture array. Subsequent elements progress left-to-right through the remaining texels in the texture array. The final element corresponds to the right end of the texture array.

format determines the composition of each element in *pixels*. It can assume one of nine symbolic values:

GL_COLOR_INDEX

Each element is a single value, a color index. The GL converts it to fixed point (with an unspecified number of zero bits to the right of the binary point), shifted left or right depending on the value and sign of **GL_INDEX_SHIFT**, and added to **GL_INDEX_OFFSET** (see **glPixelTransfer**). The resulting index is converted to a set of color components using the **GL_PIXEL_MAP_I_TO_R**, **GL_PIXEL_MAP_I_TO_G**, **GL_PIXEL_MAP_I_TO_B**, and **GL_PIXEL_MAP_I_TO_A** tables, and clamped to the range [0,1].

GL_RED

Each element is a single red component. The GL converts it to floating point and assembles it into an RGBA element by attaching 0 for green and blue, and 1 for alpha. Each component is then multiplied by the signed scale factor **GL_c_SCALE**, added to the signed bias **GL_c_BIAS**, and clamped to the range [0,1] (see **glPixelTransfer**).

GL_GREEN

Each element is a single green component. The GL converts it to floating point and assembles it into an RGBA element by attaching 0 for red and blue, and 1 for alpha. Each component is then multiplied by the signed scale factor **GL_c_SCALE**, added to the signed bias **GL_c_BIAS**, and clamped to the range [0,1] (see **glPixelTransfer**).

GL_BLUE

Each element is a single blue component. The GL converts it to floating point and assembles it

into an RGBA element by attaching 0 for red and green, and 1 for alpha. Each component is then multiplied by the signed scale factor **GL_c_SCALE**, added to the signed bias **GL_c_BIAS**, and clamped to the range [0,1] (see **glPixelTransfer**).

GL_ALPHA Each element is a single alpha component. The GL converts it to floating point and assembles it into an RGBA element by attaching 0 for red, green, and blue. Each component is then multiplied by the signed scale factor **GL_c_SCALE**, added to the signed bias **GL_c_BIAS**, and clamped to the range [0,1] (see **glPixelTransfer**).

GL_RGB Each element is an RGB triple. The GL converts it to floating point and assembles it into an RGBA element by attaching 1 for alpha. Each component is then multiplied by the signed scale factor **GL_c_SCALE**, added to the signed bias **GL_c_BIAS**, and clamped to the range [0,1] (see **glPixelTransfer**).

GL_RGBA Each element contains all four components. Each component is then multiplied by the signed scale factor **GL_c_SCALE**, added to the signed bias **GL_c_BIAS**, and clamped to the range [0,1] (see **glPixelTransfer**).

GL_LUMINANCE Each element is a single luminance value. The GL converts it to floating point, then assembles it into an RGBA element by replicating the luminance value three times for red, green, and blue and attaching 1 for alpha. Each component is then multiplied by the signed scale factor **GL_c_SCALE**, added to the signed bias **GL_c_BIAS**, and clamped to the range [0,1] (see **glPixelTransfer**).

GL_LUMINANCE_ALPHA Each element is a luminance/alpha pair. The GL converts it to floating point, then assembles it into an RGBA element by replicating the luminance value three times for red, green, and blue. Each component is then multiplied by the signed scale factor **GL_c_SCALE**, added to the signed bias **GL_c_BIAS**, and clamped to the range [0,1] (see

glPixelTransfer).

If an application wants to store the texture at a certain resolution or in a certain format, it can request the resolution and format with *internalformat*. The GL will choose an internal representation that closely approximates that requested by *internalformat*, but it may not match exactly. (The representations specified by **GL_LUMINANCE**, **GL_LUMINANCE_ALPHA**, **GL_RGB**, and **GL_RGBA** must match exactly. The numeric values 1, 2, 3, and 4 may also be used to specify the preceding representations.)

Use the **GL_PROXY_TEXTURE_1D** target to try out a resolution and format. The implementation will update and recompute its best match for the requested storage resolution and format. To query this state, call **glGetTexLevelParameter**. If the texture cannot be accommodated, texture state is set to 0.

A one-component texture image uses only the red component of the RGBA color extracted from *pixels*. A two-component image uses the R and A values. A three-component image uses the R, G, and B values. A four-component image uses all of the RGBA components.

NOTES

Texturing has no effect in color index mode.

The texture image can be represented by the same data formats as the pixels in a **glDrawPixels** command, except that **GL_STENCIL_INDEX** and **GL_DEPTH_COMPONENT** cannot be used. **glPixelStore** and **glPixelTransfer** modes affect texture images in exactly the way they affect **glDrawPixels**.

GL_PROXY_TEXTURE_1D may only be used if the GL version is 1.1 or greater.

Internal formats other than 1, 2, 3, or 4 may only be used if the GL version is 1.1 or greater.

In GL version 1.1 or greater, *pixels* may be a null pointer. In this case texture memory is allocated to accommodate a texture of width *width*. You can then download subtextures to initialize the texture memory. The image is undefined if the program tries to apply an uninitialized portion of the texture image to a primitive.

ERRORS

GL_INVALID_ENUM is generated if *target* is not **GL_TEXTURE_1D** or **GL_PROXY_TEXTURE_1D**.

GL_INVALID_ENUM is generated if *format* is not an accepted format constant. Format constants other than **GL_STENCIL_INDEX** and **GL_DEPTH_COMPONENT** are accepted.

GL_INVALID_ENUM is generated if *type* is not a type constant.

GL_INVALID_ENUM is generated if *type* is **GL_BITMAP** and *format* is not **GL_COLOR_INDEX**.

GL_INVALID_VALUE is generated if *level* is less than 0.

GL_INVALID_VALUE may be generated if *level* is greater than $\log \textit{max}$, where *max* is the returned value of **GL_MAX_TEXTURE_SIZE**.

GL_INVALID_VALUE is generated if *internalformat* is not 1, 2, 3, 4, or one of the accepted resolution and format symbolic constants.

GL_INVALID_VALUE is generated if *width* is less than 0 or greater than $2 + \text{GL_MAX_TEXTURE_SIZE}$, or if it cannot be represented as $2n+2(\textit{border})$ for some integer value of *n*.

GL_INVALID_VALUE is generated if *border* is not 0 or 1.

GL_INVALID_OPERATION is generated if **glTexImage1D** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGetTexImage **glIsEnabled** with argument **GL_TEXTURE_1D**

SEE ALSO

glCopyPixels, **glCopyTexImage1D**, **glCopyTexImage2D**, **glCopyTexSubImage1D**, **glCopyTexSubImage2D**, **glDrawPixels**, **glPixelStore**, **glPixelTransfer**, **glTexEnv**, **glTexGen**, **glTexImage2D**, **glTexSubImage1D**, **glTexSubImage2D**, **glTexParameter**

NAME

glTexImage2D - specify a two-dimensional texture image

C SPECIFICATION

```
void glTexImage2D( GLenum target,  
                   GLint level,  
                   GLint internalformat,  
                   GLsizei width,  
                   GLsizei height,  
                   GLint border,  
                   GLenum format,  
                   GLenum type,  
                   const GLvoid *pixels )
```

PARAMETERS

<i>target</i>	Specifies the target texture. Must be GL_TEXTURE_2D or GL_PROXY_TEXTURE_2D .
<i>level</i>	Specifies the level-of-detail number. Level 0 is the base image level. Level <i>n</i> is the <i>n</i> th mipmap reduction image.
<i>internalformat</i>	Specifies the number of color components in the texture. Must be 1, 2, 3, or 4, or one of the following symbolic constants: GL_ALPHA , GL_ALPHA4 , GL_ALPHA8 , GL_ALPHA12 , GL_ALPHA16 , GL_LUMINANCE , GL_LUMINANCE4 , GL_LUMINANCE8 , GL_LUMINANCE12 , GL_LUMINANCE16 , GL_LUMINANCE_ALPHA , GL_LUMINANCE4_ALPHA4 , GL_LUMINANCE6_ALPHA2 , GL_LUMINANCE8_ALPHA8 , GL_LUMINANCE12_ALPHA4 , GL_LUMINANCE12_ALPHA12 , GL_LUMINANCE16_ALPHA16 , GL_INTENSITY , GL_INTENSITY4 , GL_INTENSITY8 , GL_INTENSITY12 , GL_INTENSITY16 , GL_R3_G3_B2 , GL_RGB , GL_RGB4 , GL_RGB5 , GL_RGB8 , GL_RGB10 , GL_RGB12 , GL_RGB16 , GL_RGBA , GL_RGBA2 , GL_RGBA4 , GL_RGB5_A1 , GL_RGBA8 , GL_RGB10_A2 , GL_RGBA12 , or GL_RGBA16 .
<i>width</i>	Specifies the width of the texture image. Must be $2^{n+2}(\text{border})$ for some integer <i>n</i> . All implementations support texture images that

are at least 64 texels wide.

<i>height</i>	Specifies the height of the texture image. Must be $2m+2(\text{border})$ for some integer m . All implementations support texture images that are at least 64 texels high.
<i>border</i>	Specifies the width of the border. Must be either 0 or 1.
<i>format</i>	Specifies the format of the pixel data. The following symbolic values are accepted: GL_COLOR_INDEX , GL_RED , GL_GREEN , GL_BLUE , GL_ALPHA , GL_RGB , GL_RGBA , GL_LUMINANCE , and GL_LUMINANCE_ALPHA .
<i>type</i>	Specifies the data type of the pixel data. The following symbolic values are accepted: GL_UNSIGNED_BYTE , GL_BYTE , GL_BITMAP , GL_UNSIGNED_SHORT , GL_SHORT , GL_UNSIGNED_INT , GL_INT , and GL_FLOAT .
<i>pixels</i>	Specifies a pointer to the image data in memory.

DESCRIPTION

Texturing maps a portion of a specified texture image onto each graphical primitive for which texturing is enabled. To enable and disable two-dimensional texturing, call **glEnable** and **glDisable** with argument **GL_TEXTURE_2D**.

To define texture images, call **glTexImage2D**. The arguments describe the parameters of the texture image, such as height, width, width of the border, level-of-detail number (see **glTexParameter**), and number of color components provided. The last three arguments describe how the image is represented in memory; they are identical to the pixel formats used for **glDrawPixels**.

If *target* is **GL_PROXY_TEXTURE_2D**, no data is read from *pixels*, but all of the texture image state is recalculated, checked for consistency, and checked against the implementation's capabilities. If the implementation cannot handle a texture of the requested texture size, it sets all of the image state to 0, but does not generate an error (see **glGetError**). To query for an entire mipmap array, use an

image array level greater than or equal to 1.

If *target* is **GL_TEXTURE_2D**, data is read from *pixels* as a sequence of signed or unsigned bytes, shorts, or longs, or single-precision floating-point values, depending on *type*. These values are grouped into sets of one, two, three, or four values, depending on *format*, to form elements. If *type* is **GL_BITMAP**, the data is considered as a string of unsigned bytes (and *format* must be **GL_COLOR_INDEX**). Each data byte is treated as eight 1-bit elements, with bit ordering determined by **GL_UNPACK_LSB_FIRST** (see **glPixelStore**).

The first element corresponds to the lower left corner of the texture image. Subsequent elements progress left-to-right through the remaining texels in the lowest row of the texture image, and then in successively higher rows of the texture image. The final element corresponds to the upper right corner of the texture image.

format determines the composition of each element in *pixels*. It can assume one of nine symbolic values:

GL_COLOR_INDEX

Each element is a single value, a color index. The GL converts it to fixed point (with an unspecified number of zero bits to the right of the binary point), shifted left or right depending on the value and sign of **GL_INDEX_SHIFT**, and added to **GL_INDEX_OFFSET** (see **glPixelTransfer**). The resulting index is converted to a set of color components using the **GL_PIXEL_MAP_I_TO_R**, **GL_PIXEL_MAP_I_TO_G**, **GL_PIXEL_MAP_I_TO_B**, and **GL_PIXEL_MAP_I_TO_A** tables, and clamped to the range [0,1].

GL_RED

Each element is a single red component. The GL converts it to floating point and assembles it into an RGBA element by attaching 0 for green and blue, and 1 for alpha. Each component is then multiplied by the signed scale factor **GL_c_SCALE**, added to the signed bias **GL_c_BIAS**, and clamped to the range [0,1] (see **glPixelTransfer**).

GL_GREEN

Each element is a single green component. The GL converts it to floating point and assembles it into an RGBA element by attaching 0 for red and

blue, and 1 for alpha. Each component is then multiplied by the signed scale factor **GL_c_SCALE**, added to the signed bias **GL_c_BIAS**, and clamped to the range [0,1] (see **glPixelTransfer**).

GL_BLUE Each element is a single blue component. The GL converts it to floating point and assembles it into an RGBA element by attaching 0 for red and green, and 1 for alpha. Each component is then multiplied by the signed scale factor **GL_c_SCALE**, added to the signed bias **GL_c_BIAS**, and clamped to the range [0,1] (see **glPixelTransfer**).

GL_ALPHA Each element is a single alpha component. The GL converts it to floating point and assembles it into an RGBA element by attaching 0 for red, green, and blue. Each component is then multiplied by the signed scale factor **GL_c_SCALE**, added to the signed bias **GL_c_BIAS**, and clamped to the range [0,1] (see **glPixelTransfer**).

GL_RGB Each element is an RGB triple. The GL converts it to floating point and assembles it into an RGBA element by attaching 1 for alpha. Each component is then multiplied by the signed scale factor **GL_c_SCALE**, added to the signed bias **GL_c_BIAS**, and clamped to the range [0,1] (see **glPixelTransfer**).

GL_RGBA Each element contains all four components. Each component is multiplied by the signed scale factor **GL_c_SCALE**, added to the signed bias **GL_c_BIAS**, and clamped to the range [0,1] (see **glPixelTransfer**).

GL_LUMINANCE Each element is a single luminance value. The GL converts it to floating point, then assembles it into an RGBA element by replicating the luminance value three times for red, green, and blue and attaching 1 for alpha. Each component is then multiplied by the signed scale factor **GL_c_SCALE**, added to the signed bias **GL_c_BIAS**, and clamped to the range [0,1] (see **glPixelTransfer**).

GL_LUMINANCE_ALPHA

Each element is a luminance/alpha pair. The GL converts it to floating point, then assembles it into an RGBA element by replicating the luminance value three times for red, green, and blue. Each component is then multiplied by the signed scale factor **GL_c_SCALE**, added to the signed bias **GL_c_BIAS**, and clamped to the range [0,1] (see **glPixelTransfer**).

Refer to the **glDrawPixels** reference page for a description of the acceptable values for the *type* parameter.

If an application wants to store the texture at a certain resolution or in a certain format, it can request the resolution and format with *internalformat*. The GL will choose an internal representation that closely approximates that requested by *internalformat*, but it may not match exactly. (The representations specified by **GL_LUMINANCE**, **GL_LUMINANCE_ALPHA**, **GL_RGB**, and **GL_RGBA** must match exactly. The numeric values 1, 2, 3, and 4 may also be used to specify the above representations.)

Use the **GL_PROXY_TEXTURE_2D** target to try out a resolution and format. The implementation will update and recompute its best match for the requested storage resolution and format. To then query this state, call **glGetTexLevelParameter**. If the texture cannot be accommodated, texture state is set to 0.

A one-component texture image uses only the red component of the RGBA color extracted from *pixels*. A two-component image uses the R and A values. A three-component image uses the R, G, and B values. A four-component image uses all of the RGBA components.

NOTES

Texturing has no effect in color index mode.

The texture image can be represented by the same data formats as the pixels in a **glDrawPixels** command, except that **GL_STENCIL_INDEX** and **GL_DEPTH_COMPONENT** cannot be used. **glPixelStore** and **glPixelTransfer** modes affect texture images in exactly the way they affect **glDrawPixels**.

glTexImage2D and **GL_PROXY_TEXTURE_2D** are only available if the GL version is 1.1 or greater.

Internal formats other than 1, 2, 3, or 4 may only be used if the GL version is 1.1 or greater.

In GL version 1.1 or greater, *pixels* may be a null pointer. In this case texture memory is allocated to accommodate a texture of width *width* and height *height*. You can then download subtextures to initialize this texture memory. The image is undefined if the user tries to apply an uninitialized portion of the texture image to a primitive.

ERRORS

GL_INVALID_ENUM is generated if *target* is not **GL_TEXTURE_2D** or **GL_PROXY_TEXTURE_2D**.

GL_INVALID_ENUM is generated if *format* is not an accepted format constant. Format constants other than **GL_STENCIL_INDEX** and **GL_DEPTH_COMPONENT** are accepted.

GL_INVALID_ENUM is generated if *type* is not a type constant.

GL_INVALID_ENUM is generated if *type* is **GL_BITMAP** and *format* is not **GL_COLOR_INDEX**.

GL_INVALID_VALUE is generated if *level* is less than 0.

GL_INVALID_VALUE may be generated if *level* is greater than $\log \max$, where *max* is the returned value of **GL_MAX_TEXTURE_SIZE**.

GL_INVALID_VALUE is generated if *internalformat* is not 1, 2, 3, 4, or one of the accepted resolution and format symbolic constants.

GL_INVALID_VALUE is generated if *width* or *height* is less than 0 or greater than $2 + \text{GL_MAX_TEXTURE_SIZE}$, or if either cannot be represented as $2^k + 2(\text{border})$ for some integer value of *k*.

GL_INVALID_VALUE is generated if *border* is not 0 or 1.

GL_INVALID_OPERATION is generated if **glTexImage2D** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

`glGetTexImage`

`glIsEnabled` with argument `GL_TEXTURE_2D`

SEE ALSO

`glCopyPixels`, `glCopyTexImage1D`, `glCopyTexImage2D`,
`glCopyTexSubImage1D`, `glCopyTexSubImage2D`, `glDrawPixels`,
`glPixelStore`, `glPixelTransfer`, `glTexEnv`, `glTexGen`,
`glTexImage1D`, `glTexSubImage1D`, `glTexSubImage2D`,
`glTexParameter`

NAME

glTexParameterf, glTexParameteri, glTexParameterfv, glTexParameteriv - set texture parameters

C SPECIFICATION

```
void glTexParameterf( GLenum target,
                     GLenum pname,
                     GLfloat param )
void glTexParameteri( GLenum target,
                     GLenum pname,
                     GLint param )
```

PARAMETERS

target Specifies the target texture, which must be either **GL_TEXTURE_1D** or **GL_TEXTURE_2D**.

pname Specifies the symbolic name of a single-valued texture parameter. *pname* can be one of the following: **GL_TEXTURE_MIN_FILTER**, **GL_TEXTURE_MAG_FILTER**, **GL_TEXTURE_WRAP_S**, **GL_TEXTURE_WRAP_T**, or **GL_TEXTURE_PRIORITY**.

param Specifies the value of *pname*.

C SPECIFICATION

```
void glTexParameterfv( GLenum target,
                      GLenum pname,
                      const GLfloat *params )
void glTexParameteriv( GLenum target,
                      GLenum pname,
                      const GLint *params )
```

PARAMETERS

target Specifies the target texture, which must be either **GL_TEXTURE_1D** or **GL_TEXTURE_2D**.

pname Specifies the symbolic name of a texture parameter. *pname* can be one of the following: **GL_TEXTURE_MIN_FILTER**, **GL_TEXTURE_MAG_FILTER**, **GL_TEXTURE_WRAP_S**, **GL_TEXTURE_WRAP_T**,

GL_TEXTURE_BORDER_COLOR, or **GL_TEXTURE_PRIORITY**.

params

Specifies a pointer to an array where the value or values of *pname* are stored.

DESCRIPTION

Texture mapping is a technique that applies an image onto an object's surface as if the image were a decal or cellophane shrink-wrap. The image is created in texture space, with an (s, t) coordinate system. A texture is a one- or two-dimensional image and a set of parameters that determine how samples are derived from the image.

glTexParameter assigns the value or values in *params* to the texture parameter specified as *pname*. *target* defines the target texture, either **GL_TEXTURE_1D** or **GL_TEXTURE_2D**. The following symbols are accepted in *pname*:

GL_TEXTURE_MIN_FILTER

The texture minifying function is used whenever the pixel being textured maps to an area greater than one texture element. There are six defined minifying functions. Two of them use the nearest one or nearest four texture elements to compute the texture value. The other four use mipmaps.

A mipmap is an ordered set of arrays representing the same image at progressively lower resolutions. If the texture has dimensions $2n \times 2m$, there are $\max(n, m) + 1$ mipmaps. The first mipmap is the original texture, with dimensions $2n \times 2m$. Each subsequent mipmap has dimensions $2^k - 1 \times 2^l - 1$, where $2^k \times 2^l$ are the dimensions of the previous mipmap, until either $k = 0$ or $l = 0$. At that point, subsequent mipmaps have dimension $1 \times 2^l - 1$ or $2^k - 1 \times 1$ until the final mipmap, which has dimension 1×1 . To define the mipmaps, call **glTexImage1D**, **glTexImage2D**, **glCopyTexImage1D**, or **glCopyTexImage2D** with the *level* argument indicating the order of the mipmaps. Level 0 is the original texture; level $\max(n, m)$ is the final 1×1 mipmap.

params supplies a function for minifying the

texture as one of the following:

GL_NEAREST

Returns the value of the texture element that is nearest (in Manhattan distance) to the center of the pixel being textured.

GL_LINEAR Returns the weighted average of the four texture elements that are closest to the center of the pixel being textured. These can include border texture elements, depending on the values of **GL_TEXTURE_WRAP_S** and **GL_TEXTURE_WRAP_T**, and on the exact mapping.

GL_NEAREST_MIPMAP_NEAREST

Chooses the mipmap that most closely matches the size of the pixel being textured and uses the **GL_NEAREST** criterion (the texture element nearest to the center of the pixel) to produce a texture value.

GL_LINEAR_MIPMAP_NEAREST

Chooses the mipmap that most closely matches the size of the pixel being textured and uses the **GL_LINEAR** criterion (a weighted average of the four texture elements that are closest to the center of the pixel) to produce a texture value.

GL_NEAREST_MIPMAP_LINEAR

Chooses the two mipmaps that most closely match the size of the pixel being textured and uses the **GL_NEAREST** criterion (the texture element nearest to the center of the pixel) to produce a texture value from each mipmap. The final texture value is a weighted average of those two values.

GL_LINEAR_MIPMAP_LINEAR

Chooses the two mipmaps that most closely match the size of the pixel

being textured and uses the **GL_LINEAR** criterion (a weighted average of the four texture elements that are closest to the center of the pixel) to produce a texture value from each mipmap. The final texture value is a weighted average of those two values.

As more texture elements are sampled in the minification process, fewer aliasing artifacts will be apparent. While the **GL_NEAREST** and **GL_LINEAR** minification functions can be faster than the other four, they sample only one or four texture elements to determine the texture value of the pixel being rendered and can produce moire patterns or ragged transitions. The initial value of **GL_TEXTURE_MIN_FILTER** is **GL_NEAREST_MIPMAP_LINEAR**.

GL_TEXTURE_MAG_FILTER

The texture magnification function is used when the pixel being textured maps to an area less than or equal to one texture element. It sets the texture magnification function to either **GL_NEAREST** or **GL_LINEAR** (see below). **GL_NEAREST** is generally faster than **GL_LINEAR**, but it can produce textured images with sharper edges because the transition between texture elements is not as smooth. The initial value of **GL_TEXTURE_MAG_FILTER** is **GL_LINEAR**.

GL_NEAREST

Returns the value of the texture element that is nearest (in Manhattan distance) to the center of the pixel being textured.

GL_LINEAR Returns the weighted average of the four texture elements that are closest to the center of the pixel being textured. These can include border texture elements, depending on the values of **GL_TEXTURE_WRAP_S** and **GL_TEXTURE_WRAP_T**, and on the exact mapping.

GL_TEXTURE_WRAP_S

Sets the wrap parameter for texture coordinate *s* to either **GL_CLAMP** or **GL_REPEAT**. **GL_CLAMP** causes *s* coordinates to be clamped to the range [0,1] and is useful for preventing wrapping artifacts when mapping a single image onto an object. **GL_REPEAT** causes the integer part of the *s* coordinate to be ignored; the GL uses only the fractional part, thereby creating a repeating pattern. Border texture elements are accessed only if wrapping is set to **GL_CLAMP**. Initially, **GL_TEXTURE_WRAP_S** is set to **GL_REPEAT**.

GL_TEXTURE_WRAP_T

Sets the wrap parameter for texture coordinate *t* to either **GL_CLAMP** or **GL_REPEAT**. See the discussion under **GL_TEXTURE_WRAP_S**. Initially, **GL_TEXTURE_WRAP_T** is set to **GL_REPEAT**.

GL_TEXTURE_BORDER_COLOR

Sets a border color. *params* contains four values that comprise the RGBA color of the texture border. Integer color components are interpreted linearly such that the most positive integer maps to 1.0, and the most negative integer maps to -1.0. The values are clamped to the range [0,1] when they are specified. Initially, the border color is (0, 0, 0, 0).

GL_TEXTURE_PRIORITY

Specifies the texture residence priority of the currently bound texture. Permissible values are in the range [0, 1]. See **glPrioritizeTextures** and **glBindTexture** for more information.

NOTES

Suppose that a program has enabled texturing (by calling **glEnable** with argument **GL_TEXTURE_1D** or **GL_TEXTURE_2D**) and has set **GL_TEXTURE_MIN_FILTER** to one of the functions that requires a mipmap. If either the dimensions of the texture images currently defined (with previous calls to **glTexImage1D**, **glTexImage2D**, **glCopyTexImage1D**, or **glCopyTexImage2D**) do not follow the proper sequence for mipmaps (described above), or there are fewer texture images defined than are needed, or the set of texture images have differing numbers of texture components, then it is as if texture mapping were disabled.

Linear filtering accesses the four nearest texture elements only in 2D textures. In 1D textures, linear filtering accesses the two nearest texture elements.

ERRORS

GL_INVALID_ENUM is generated if *target* or *pname* is not one of the accepted defined values.

GL_INVALID_ENUM is generated if *params* should have a defined constant value (based on the value of *pname*) and does not.

GL_INVALID_OPERATION is generated if **glTexParameter** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGetTexParameter
glGetTexLevelParameter

SEE ALSO

glBindTexture, **glCopyPixels**, **glCopyTexImage1D**,
glCopyTexImage2D, **glCopyTexSubImage1D**, **glCopyTexSubImage2D**,
glDrawPixels, **glPixelStore**, **glPixelTransfer**,
glPrioritizeTextures, **glTexEnv**, **glTexGen**, **glTexImage1D**,
glTexImage2D, **glTexSubImage1D**, **glTexSubImage2D**

NAME

glTexSubImage1D - specify a two-dimensional texture subimage

C SPECIFICATION

```
void glTexSubImage1D( GLenum target,
                      GLint level,
                      GLint xoffset,
                      GLsizei width,
                      GLenum format,
                      GLenum type,
                      const GLvoid *pixels )
```

PARAMETERS

<i>target</i>	Specifies the target texture. Must be GL_TEXTURE_1D .
<i>level</i>	Specifies the level-of-detail number. Level 0 is the base image level. Level <i>n</i> is the <i>n</i> th mipmap reduction image.
<i>xoffset</i>	Specifies a texel offset in the x direction within the texture array.
<i>width</i>	Specifies the width of the texture subimage.
<i>format</i>	Specifies the format of the pixel data. The following symbolic values are accepted: GL_COLOR_INDEX , GL_RED , GL_GREEN , GL_BLUE , GL_ALPHA , GL_RGB , GL_RGBA , GL_LUMINANCE , and GL_LUMINANCE_ALPHA .
<i>type</i>	Specifies the data type of the pixel data. The following symbolic values are accepted: GL_UNSIGNED_BYTE , GL_BYTE , GL_BITMAP , GL_UNSIGNED_SHORT , GL_SHORT , GL_UNSIGNED_INT , GL_INT , and GL_FLOAT .
<i>pixels</i>	Specifies a pointer to the image data in memory.

DESCRIPTION

Texturing maps a portion of a specified texture image onto each graphical primitive for which texturing is enabled. To enable or disable one-dimensional texturing, call **glEnable**

and **glDisable** with argument **GL_TEXTURE_1D**.

glTexSubImage1D redefines a contiguous subregion of an existing one-dimensional texture image. The texels referenced by *pixels* replace the portion of the existing texture array with *x* indices *xoffset* and *xoffset + width - 1*, inclusive. This region may not include any texels outside the range of the texture array as it was originally specified. It is not an error to specify a subtexture with width of 0, but such a specification has no effect.

NOTES

glTexSubImage1D is available only if the GL version is 1.1 or greater.

Texturing has no effect in color index mode.

glPixelStore and **glPixelTransfer** modes affect texture images in exactly the way they affect **glDrawPixels**.

ERRORS

GL_INVALID_ENUM is generated if *target* is not one of the allowable values.

GL_INVALID_OPERATION is generated if the texture array has not been defined by a previous **glTexImage1D** operation.

GL_INVALID_VALUE is generated if *level* is less than 0.

GL_INVALID_VALUE may be generated if *level* is greater than $\log \max$, where *max* is the returned value of **GL_MAX_TEXTURE_SIZE**.

GL_INVALID_VALUE is generated if $xoffset < -b$, or if $(xoffset + width) > (w - b)$. Where *w* is the **GL_TEXTURE_WIDTH**, and *b* is the width of the **GL_TEXTURE_BORDER** of the texture image being modified. Note that *w* includes twice the border width.

GL_INVALID_VALUE is generated if *width* is less than 0.

GL_INVALID_ENUM is generated if *format* is not an accepted format constant.

GL_INVALID_ENUM is generated if *type* is not a type constant.

GL_INVALID_ENUM is generated if *type* is **GL_BITMAP** and *format* is not **GL_COLOR_INDEX**.

GL_INVALID_OPERATION is generated if **glTexSubImage1D** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGetTexImage

glIsEnabled with argument **GL_TEXTURE_1D**

SEE ALSO

glCopyTexImage1D, **glCopyTexImage2D**, **glCopyTexSubImage1D**,
glCopyTexSubImage2D, **glDrawPixels**, **glPixelStore**,
glPixelTransfer, **glTexEnv**, **glTexGen**, **glTexImage1D**,
glTexImage2D, **glTexParameter**, **glTexSubImage2D**

NAME

glTexSubImage2D - specify a two-dimensional texture subimage

C SPECIFICATION

```
void glTexSubImage2D( GLenum target,
                      GLint level,
                      GLint xoffset,
                      GLint yoffset,
                      GLsizei width,
                      GLsizei height,
                      GLenum format,
                      GLenum type,
                      const GLvoid *pixels )
```

PARAMETERS

<i>target</i>	Specifies the target texture. Must be GL_TEXTURE_2D .
<i>level</i>	Specifies the level-of-detail number. Level 0 is the base image level. Level <i>n</i> is the <i>n</i> th mipmap reduction image.
<i>xoffset</i>	Specifies a texel offset in the x direction within the texture array.
<i>yoffset</i>	Specifies a texel offset in the y direction within the texture array.
<i>width</i>	Specifies the width of the texture subimage.
<i>height</i>	Specifies the height of the texture subimage.
<i>format</i>	Specifies the format of the pixel data. The following symbolic values are accepted: GL_COLOR_INDEX , GL_RED , GL_GREEN , GL_BLUE , GL_ALPHA , GL_RGB , GL_RGBA , GL_LUMINANCE , and GL_LUMINANCE_ALPHA .
<i>type</i>	Specifies the data type of the pixel data. The following symbolic values are accepted: GL_UNSIGNED_BYTE , GL_BYTE , GL_BITMAP , GL_UNSIGNED_SHORT , GL_SHORT , GL_UNSIGNED_INT , GL_INT , and GL_FLOAT .

pixels Specifies a pointer to the image data in memory.

DESCRIPTION

Texturing maps a portion of a specified texture image onto each graphical primitive for which texturing is enabled. To enable and disable two-dimensional texturing, call **glEnable** and **glDisable** with argument **GL_TEXTURE_2D**.

glTexSubImage2D redefines a contiguous subregion of an existing two-dimensional texture image. The texels referenced by *pixels* replace the portion of the existing texture array with x indices *xoffset* and *xoffset + width - 1*, inclusive, and y indices *yoffset* and *yoffset + height - 1*, inclusive. This region may not include any texels outside the range of the texture array as it was originally specified. It is not an error to specify a subtexture with zero width or height, but such a specification has no effect.

NOTES

glTexSubImage2D is available only if the GL version is 1.1 or greater.

Texturing has no effect in color index mode.

glPixelStore and **glPixelTransfer** modes affect texture images in exactly the way they affect **glDrawPixels**.

ERRORS

GL_INVALID_ENUM is generated if *target* is not **GL_TEXTURE_2D**.

GL_INVALID_OPERATION is generated if the texture array has not been defined by a previous **glTexImage2D** operation.

GL_INVALID_VALUE is generated if *level* is less than 0.

P **GL_INVALID_VALUE** may be generated if *level* is greater than $\log \textit{max}$, where *max* is the returned value of **GL_MAX_TEXTURE_SIZE**.

GL_INVALID_VALUE is generated if $\textit{xoffset} < -\textit{b}$, $(\textit{xoffset} + \textit{width}) > (\textit{w} - \textit{b})$, $\textit{yoffset} < -\textit{b}$, or $(\textit{yoffset} + \textit{height}) > (\textit{h} - \textit{b})$. Where *w* is the **GL_TEXTURE_WIDTH**, *h* is the **GL_TEXTURE_HEIGHT**, and *b* is the border width of the texture image being modified. Note that

w and h include twice the border width.

GL_INVALID_VALUE is generated if *width* or *height* is less than 0.

GL_INVALID_ENUM is generated if *format* is not an accepted format constant.

GL_INVALID_ENUM is generated if *type* is not a type constant.

GL_INVALID_ENUM is generated if *type* is **GL_BITMAP** and *format* is not **GL_COLOR_INDEX**.

GL_INVALID_OPERATION is generated if **glTexSubImage2D** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGetTexImage

glIsEnabled with argument **GL_TEXTURE_2D**

SEE ALSO

glCopyTexImage1D, **glCopyTexImage2D**, **glCopyTexSubImage1D**,
glCopyTexSubImage2D, **glDrawPixels**, **glPixelStore**,
glPixelTransfer, **glTexEnv**, **glTexGen**, **glTexImage1D**,
glTexImage2D, **glTexSubImage1D**, **glTexParameter**

NAME

glTranslated, **glTranslatef** - multiply the current matrix by a translation matrix

C SPECIFICATION

```
void glTranslated( GLdouble x,  
                  GLdouble y,  
                  GLdouble z )  
void glTranslatef( GLfloat x,  
                  GLfloat y,  
                  GLfloat z )
```

PARAMETERS

x, y, z

Specify the *x*, *y*, and *z* coordinates of a translation vector.

DESCRIPTION

glTranslate produces a translation by (*x*,*y*,*z*). The current matrix (see **glMatrixMode**) is multiplied by this translation matrix, with the product replacing the current matrix, as if **glMultMatrix** were called with the following matrix for its argument:

$$\begin{pmatrix} 1 & 0 & 0 & x \\ 0 & 1 & 0 & y \\ 0 & 0 & 1 & z \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

If the matrix mode is either **GL_MODELVIEW** or **GL_PROJECTION**, all objects drawn after a call to **glTranslate** are translated.

Use **glPushMatrix** and **glPopMatrix** to save and restore the untranslated coordinate system.

ERRORS

GL_INVALID_OPERATION is generated if **glTranslate** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_MATRIX_MODE**
glGet with argument **GL_MODELVIEW_MATRIX**
glGet with argument **GL_PROJECTION_MATRIX**
glGet with argument **GL_TEXTURE_MATRIX**

SEE ALSO

glMatrixMode, glMultMatrix, glPushMatrix, glRotate, glScale

NAME

glVertex2d, **glVertex2f**, **glVertex2i**, **glVertex2s**, **glVertex3d**, **glVertex3f**, **glVertex3i**, **glVertex3s**, **glVertex4d**, **glVertex4f**, **glVertex4i**, **glVertex4s**, **glVertex2dv**, **glVertex2fv**, **glVertex2iv**, **glVertex2sv**, **glVertex3dv**, **glVertex3fv**, **glVertex3iv**, **glVertex3sv**, **glVertex4dv**, **glVertex4fv**, **glVertex4iv**, **glVertex4sv** - specify a vertex

C SPECIFICATION

```
void glVertex2d( GLdouble x,
                 GLdouble y )
void glVertex2f( GLfloat x,
                 GLfloat y )
void glVertex2i( GLint x,
                 GLint y )
void glVertex2s( GLshort x,
                 GLshort y )
void glVertex3d( GLdouble x,
                 GLdouble y,
                 GLdouble z )
void glVertex3f( GLfloat x,
                 GLfloat y,
                 GLfloat z )
void glVertex3i( GLint x,
                 GLint y,
                 GLint z )
void glVertex3s( GLshort x,
                 GLshort y,
                 GLshort z )
void glVertex4d( GLdouble x,
                 GLdouble y,
                 GLdouble z,
                 GLdouble w )
void glVertex4f( GLfloat x,
                 GLfloat y,
                 GLfloat z,
                 GLfloat w )
void glVertex4i( GLint x,
                 GLint y,
                 GLint z,
                 GLint w )
void glVertex4s( GLshort x,
                 GLshort y,
                 GLshort z,
```

GLshort w)

PARAMETERS

x, y, z, w

Specify *x, y, z*, and *w* coordinates of a vertex.
Not all parameters are present in all forms of the command.

C SPECIFICATION

```
void glVertex2dv( const GLdouble *v )
void glVertex2fv( const GLfloat *v )
void glVertex2iv( const GLint *v )
void glVertex2sv( const GLshort *v )
void glVertex3dv( const GLdouble *v )
void glVertex3fv( const GLfloat *v )
void glVertex3iv( const GLint *v )
void glVertex3sv( const GLshort *v )
void glVertex4dv( const GLdouble *v )
void glVertex4fv( const GLfloat *v )
void glVertex4iv( const GLint *v )
void glVertex4sv( const GLshort *v )
```

PARAMETERS

v Specifies a pointer to an array of two, three, or four elements. The elements of a two-element array are *x* and *y*; of a three-element array, *x, y*, and *z*; and of a four-element array, *x, y, z*, and *w*.

DESCRIPTION

glVertex commands are used within **glBegin**/**glEnd** pairs to specify point, line, and polygon vertices. The current color, normal, and texture coordinates are associated with the vertex when **glVertex** is called.

When only *x* and *y* are specified, *z* defaults to 0 and *w* defaults to 1. When *x, y*, and *z* are specified, *w* defaults to 1.

NOTES

Invoking **glVertex** outside of a **glBegin**/**glEnd** pair results in undefined behavior.

SEE ALSO

glBegin, glCallList, glColor, glEdgeFlag, glEvalCoord,

`glIndex, glMaterial,
glNormal, glRect, glTexCoord, glVertexPointer`

NAME

glVertexPointer - define an array of vertex data

C SPECIFICATION

```
void glVertexPointer( GLint size,  
                    GLenum type,  
                    GLsizei stride,  
                    const GLvoid *pointer )
```

PARAMETERS

<i>size</i>	Specifies the number of coordinates per vertex; must be 2, 3, or 4. The initial value is 4.
<i>type</i>	Specifies the data type of each coordinate in the array. Symbolic constants GL_SHORT , GL_INT , GL_FLOAT , and GL_DOUBLE are accepted. The initial value is GL_FLOAT .
<i>stride</i>	Specifies the byte offset between consecutive vertexes. If <i>stride</i> is 0, the vertexes are understood to be tightly packed in the array. The initial value is 0.
<i>pointer</i>	Specifies a pointer to the first coordinate of the first vertex in the array.

DESCRIPTION

glVertexPointer specifies the location and data format of an array of vertex coordinates to use when rendering. *size* specifies the number of coordinates per vertex and *type* the data type of the coordinates. *stride* specifies the byte stride from one vertex to the next allowing vertexes and attributes to be packed into a single array or stored in separate arrays. (Single-array storage may be more efficient on some implementations; see **glInterleavedArrays**.) When a vertex array is specified, *size*, *type*, *stride*, and *pointer* are saved as client-side state.

To enable and disable the vertex array, call **glEnableClientState** and **glDisableClientState** with the argument **GL_VERTEX_ARRAY**. If enabled, the vertex array is used when **glDrawArrays**,

glDrawElements, or **glArrayElement** is called.

Use **glDrawArrays** to construct a sequence of primitives (all of the same type) from prespecified vertex and vertex attribute arrays. Use **glArrayElement** to specify primitives by indexing vertexes and vertex attributes and **glDrawElements** to construct a sequence of primitives by indexing vertexes and vertex attributes.

NOTES

glVertexPointer is available only if the GL version is 1.1 or greater.

The vertex array is initially disabled and isn't accessed when **glArrayElement**, **glDrawElements** or **glDrawArrays** is called.

Execution of **glVertexPointer** is not allowed between the execution of **glBegin** and the corresponding execution of **glEnd**, but an error may or may not be generated. If no error is generated, the operation is undefined.

glVertexPointer is typically implemented on the client side.

Vertex array parameters are client-side state and are therefore not saved or restored by **glPushAttrib** and **glPopAttrib**. Use **glPushClientAttrib** and **glPopClientAttrib** instead.

ERRORS

GL_INVALID_VALUE is generated if *size* is not 2, 3, or 4.

GL_INVALID_ENUM is generated if *type* is not an accepted value.

GL_INVALID_VALUE is generated if *stride* is negative.

ASSOCIATED GETS

glIsEnabled with argument **GL_VERTEX_ARRAY**

glGet with argument **GL_VERTEX_ARRAY_SIZE**

glGet with argument **GL_VERTEX_ARRAY_TYPE**

glGet with argument **GL_VERTEX_ARRAY_STRIDE**

glGetPointerv with argument **GL_VERTEX_ARRAY_POINTER**

SEE ALSO

glArrayElement, **glColorPointer**, **glDrawArrays**,

`glDrawElements,`
`glEdgeFlagPointer, glEnable, glGetPointerv, glIndexPointer,`
`glInterleavedArrays, glNormalPointer, glPopClientAttrib,`
`glPushClientAttrib, glTexCoordPointer`

NAME

glViewport - set the viewport

C SPECIFICATION

```
void glViewport( GLint x,  
                 GLint y,  
                 GLsizei width,  
                 GLsizei height )
```

PARAMETERS

x, y Specify the lower left corner of the viewport rectangle, in pixels. The initial value is (0,0).

width, height

Specify the width and height of the viewport. When a GL context is first attached to a window, *width* and *height* are set to the dimensions of that window.

DESCRIPTION

glViewport specifies the affine transformation of *x* and *y* from normalized device coordinates to window coordinates. Let (*x* , *y*) be normalized device coordinates. Then the window coordinates (*x* , *y*) are computed as follows:

$$\begin{aligned}x_w &= (x_{nd} + 1) \left(\frac{w}{2} \right) + x_w \\y_w &= (y_{nd} + 1) \left(\frac{h}{2} \right) + y_w\end{aligned}$$

Viewport width and height are silently clamped to a range that depends on the implementation. To query this range, call **glGet** with argument **GL_MAX_VIEWPORT_DIMS**.

ERRORS

GL_INVALID_VALUE is generated if either *width* or *height* is negative.

GL_INVALID_OPERATION is generated if **glViewport** is executed between the execution of **glBegin** and the corresponding execution of **glEnd**.

ASSOCIATED GETS

glGet with argument **GL_VIEWPORT**

glGet with argument **GL_MAX_VIEWPORT_DIMS**

SEE ALSO
glDepthRange