



C Piscine

Day 07

Staff 42 pedago@42.fr

Summary: This document is the subject for Day07 of the C Piscine @ 42.

Contents

1	Instructions	2
2	Topics	4
3	Foreword	5
4	Exercise 00 : ft_strdup	7
5	Exercise 01 : ft_range	8
6	Exercise 02 : ft_ultimate_range	9
7	Exercise 03 : ft_concat_params	10
8	Exercise 04 : ft_split_whitespaces	11
9	Exercise 05 : ft_print_words_tables	12
10	Exercise 06 : ft_convert_base	13
11	Exercise 07 : ft_split	14

Chapter 1

Instructions

- The exercises are carefully laid out in order of difficulty, from easiest to hardest. An exercise is only graded if all previous ones are correct. In other words: the grading for a day stops at the first mistake.
- Be mindful of the submission procedures indicated at the start of every exercise.
- Your exercises will be checked and graded by your fellow classmates.
- On top of that, your exercises will be checked and graded by a program called Moulinette.
- Moulinette is very meticulous and strict in its evaluation of your work. It is entirely automated and there is no way to negotiate with it. Be as thorough as possible!
- Moulinette relies on a program called **norminette** to check if your files respect the Norm. An exercise containing files that do not respect the Norm will be graded 0.
- Using a forbidden function is considered cheating. Cheaters get -42, and this grade is non-negotiable.
- If **ft_putchar()** is an authorized function, we will compile your code with our **ft_putchar.c**.
- You'll only have to submit a **main()** function if we ask for a program.
- Moulinette compiles with these flags: **-Wall -Wextra -Werror**, and uses **gcc**.
- If your program doesn't compile, it will be graded 0.
- You should not leave any additional file in your directory than those specified in the subject.



norminette must be launched with the -R CheckForbiddenSourceHeader flag. Moulinette will use it too.



The forewords are entirely unrelated to the subjects and can safely be ignored.

Chapter 2

Topics

Today, you will have to learn about:

- Dynamic memory allocation

Chapter 3

Foreword

Morty: Rick!

Rick: Uhp-uhp-uhp! Morty, keep your hands off your ding-dong! It's the only way we can speak freely. Look around you, Morty. Do you really think this wuh-world is real? You'd have to be an idiot not to notice all the sloppy details. Look, that guy's putting a bun between two hot dogs.

Morty: I dunno, Rick, I mean, I've seen people do that before.

Rick: Well, look at that old lady. She's-she's walking a cat on a leash.

Morty: Uh, Mrs. Spencer does that all the time, Rick.

Rick: Look, I-I-I don't want to hear about Mrs. Spencer, Morty! She's an idiot! All right, all right, there. Wh-what about that, Morty?

Morty: Okay, okay, you got me on that one.

Rick: Oh, really, Morty? Are you sure you haven't seen that somewhere in real life before?

Morty: No, no, I haven't seen that. I mean, why would a Pop-Tart want to live inside a toaster, Rick? I mean, th-that would be like the scariest place for them to live. Y'know what I mean?

Rick: You're missing the point, Morty. Why would he drive a smaller toaster with wheels? I mean, does your car look like a smaller version of your house? No.

Morty: So, why are they doing this? W-what do they want?

Rick: Well, that would be obvious to you, Morty, if you'd been paying attention. [an ambulance drives past Rick and Morty and stops; open back doors]

Paramedic: We got the President of the United States in here! We need 10cc of concentrated dark matter, stat, or he'll die!

Morty: Concentrated dark matter? They were asking about that in class.

Rick: Yeah, it's a special fuel I invented to travel through space faster than anybody else. These Zigerions are always trying to scam me out of my secrets, but they made a big mistake this time, Morty. They dragged you into this. Now they're gonna pay!

Morty: What do you- w-w-what are we gonna do?

Rick: We're gonna scam the scammers, Morty. And we're gonna take 'em for everything they've got.

The following exercises will be easier to complete if you are a fan of "Rick and Morty"

Chapter 4

Exercise 00 : ft_strdup

Turn-in directory : ex00/

Files to turn in: ft_strdup.c

Allowed functions: malloc

- Reproduce the behavior of the function **strdup** [man strdup].
- Here's how it should be prototyped :

```
char    *ft_strdup(char *src);
```


Chapter 5

Exercise 01 : ft_range

Turn-in directory : ex01/

Files to turn in: ft_range.c

Allowed functions: malloc

- Create a function **ft_range** which returns an array of **ints**. This **int** array should contain all values between **min** and **max**.
- **min** included - **max** excluded.
- Here's how it should be prototyped :

```
int      *ft_range(int min, int max);
```

- If **min**'s value is greater or equal to **max**'s value, a null pointer should be returned.

Chapter 6

Exercise 02 : ft_ultimate_range

Turn-in directory : ex02/

Files to turn in: ft_ultimate_range.c

Allowed functions: malloc

- Create a function **ft_ultimate_range** which allocates and assigns an array of **ints** to **range**. This **int** array should contain all values between **min** and **max**.
- **min** included - **max** excluded.
- Here's how it should be prototyped :

```
int    ft_ultimate_range(int **range, int min, int max);
```

- If the value of **min** is greater or equal to **max**'s value, **range** should be NULL.
- The size of **range** should be returned [or 0 on error].

Chapter 7

Exercise 03 : ft_concat_params

Turn-in directory : ex03/

Files to turn in: ft_concat_params.c

Allowed functions: malloc

- Create a function that transforms arguments given as command-line into a single string of characters. Those arguments should be separated by a `"\n"`.
- Here's how it should be prototyped :

```
char *ft_concat_params(int argc, char **argv);
```

Chapter 8

Exercise 04 : ft_split_whitespaces

Turn-in directory : ex04/

Files to turn in: ft_split_whitespaces.c

Allowed functions: malloc

- Create a function that splits a string of characters into words.
- Words are separated by spaces, tabs and line breaks.
- This function returns an array of strings, each of these strings being a word from the argument **str**. The last element of this array should be equal to 0 to mark the end of the array.
- There can't be any empty strings in your array. Draw the necessary conclusions.
- The given string can't be modified.
- Here's how it should be prototyped :

```
char **ft_split_whitespaces(char *str);
```

Chapter 9

Exercise 05 : ft_print_words_tables

Turn-in directory : ex05/

Files to turn in: ft_print_words_tables.c

Allowed functions: ft_putchar

- Create a function that displays the content of the array you created in the last exercise's function.
- One word per line.
- Each word will be followed by a "\n", including the last one.
- This exercise will be compiled with your ft_split_whitespaces.c
- Watch out not to have **multiple define**.
- Here's how it should be prototyped :

```
void ft_print_words_tables(char **tab);
```

Chapter 10

Exercise 06 : ft_convert_base

Turn-in directory : ex06/

Files to turn in: ft_convert_base.c

Allowed functions: malloc, free

- Create a function that returns the result of the conversion of the string **nbr** from a base **base_from** to a base **base_to**. The string must have enough allocated memory. The number represented by **nbr** must fit inside an **int**.
- Here's how it should be prototyped :

```
char *ft_convert_base(char *nbr, char *base_from, char *base_to);
```

Chapter 11

Exercise 07 : ft_split

Turn-in directory : ex07/

Files to turn in: ft_split.c

Allowed functions: malloc

- Create a function that splits a string of characters depending on another string of characters.
- Separators are all characters in the string **charset**.
- This function returns an array of strings, each of these strings being a substring of the argument **str**, found between two separator characters. The last element of this array should be equal to 0 to mark the end of the array.
- There cannot be any empty strings in your array. Draw your conclusions accordingly.
- The string given as argument won't be modifiable.
- Here's how it should be prototyped :

```
char **ft_split(char *str, char *charset);
```