

Towards Accurate and Robust Modeling of Fluid-Driven Fracture

by

Andre Macieira Braga Costa

Department of Mechanical Engineering and Materials Science
Duke University

Date: _____

Approved:

John Dolbow, Advisor

Manolis Veveakis

Wilkins Aquino

Johann Guilleminot

Dissertation submitted in partial fulfillment of the requirements for the degree of
Doctor of Philosophy in the Department of Mechanical Engineering and Materials
Science
in the Graduate School of Duke University
2023

ABSTRACT

Towards Accurate and Robust Modeling of Fluid-Driven Fracture

by

Andre Macieira Braga Costa

Department of Mechanical Engineering and Materials Science
Duke University

Date: _____

Approved:

John Dolbow, Advisor

Manolis Veveakis

Wilkins Aquino

Johann Guilleminot

An abstract of a dissertation submitted in partial fulfillment of the requirements for
the degree of Doctor of Philosophy in the Department of Mechanical Engineering
and Materials Science
in the Graduate School of Duke University
2023

Copyright © 2023 by Andre Macieira Braga Costa
All rights reserved

Abstract

This work explores the application of the phase-field method to the simulation of fluid-driven fracture and proposes a framework to make simulations faster and more robust. It begins by addressing a modeling challenge related to the application of pressure loads on the diffuse crack interfaces. During the verification process, a new J-Integral for pressurized fractures in the phase-field context is developed.

Then, the focus turns into a hybrid method to describe fracture propagation. The so-called multi-resolution method uses a combination of enrichment schemes with the phase-field method to address the complex fluid-fracture interaction that happens in hydraulic fracture. On one hand, the phase-field method alleviate some of the difficulties associated with the geometric evolution of the fracture, which are usually the limiting aspect of purely enrichment-based schemes. On the other hand, the discrete representation allows for a better treatment of the fluid loads and crack apertures, which are the main challenges associated with phase-field approaches.

The multi-resolution method is first presented in a simplified scheme to treat two-dimensional problems, which is used to verify the framework against well-known analytical solutions. It is then extended to three-dimensions. A robust algorithm to handle planar cracks in 3D is developed and its extension to nonplanar cases is discussed. Opportunites for improvements and extensions are then discussed, paving the road for future work in the topic.

Contents

Abstract	iv
List of Tables	viii
List of Figures	ix
Acknowledgements	xiii
1 Introduction	1
1.1 Motivation	1
1.2 Background	3
1.3 Research contributions	8
1.4 Organization of the dissertation	10
1.5 Notation	10
2 Revisiting the Pressure Loading of Phase-Field Fractures	12
2.1 Introduction	12
2.2 Model	13
2.2.1 Quasi-static derivation	14
2.2.2 Derivation using the maximum dissipation principle	20
2.2.3 Constitutive choices of the phase-field formulation	23
2.3 A J-Integral for pressurized cracks in a phase-field setting	25
2.4 Finite Element Implementation	31
2.5 Results	33

2.5.1	Uniaxial bar under traction in a pressurized environment	34
2.5.2	Crack nucleation from a pressurized hole	37
2.5.3	Stable propagation of a pre-existing crack	40
3	A Multi-Resolution Approach for Hydraulic Fracture Simulation	46
3.1	Introduction	46
3.2	Model formulation	50
3.2.1	Governing equations for hydraulic fracture	50
3.2.2	The phase-field method for fracture	55
3.3	Multi-resolution method	58
3.3.1	General overview	58
3.3.2	Global problem discretization	60
3.3.3	Local problem initialization	62
3.3.4	Local problem discretization	64
3.3.5	Crack propagation: translating local damage updates into global crack extensions	67
3.3.6	Algorithm summary	69
3.4	Numerical Results	71
3.4.1	KGD problems	71
3.4.2	Poroelastic problem with coupled matrix-fracture flow	79
3.4.3	Propagation around an inclusion	84
3.5	Summary and conclusions	87
4	Extending the Multi-Resolution Approach to Three Dimensions	89
4.1	Introduction	89
4.2	Theory	90
4.3	Algorithm for planar fractures	92
4.3.1	Fracture front construction	93

4.3.2	Tracking damage in the fracture front elements	96
4.4	Numerical examples	97
4.4.1	Single fracture under fluid injection with non-homogenous boundary conditions	98
4.4.2	Two parallel circular fractures under fluid injection	98
4.4.3	Merging two circular fractures	102
4.5	Extension to non-planar fractures	105
4.5.1	Overview of a propagation algorithm for non-planar fractures .	105
4.5.2	Example problem	110
5	Conclusions and Future Work	113
5.1	Concluding Remarks	113
5.2	Acknowledgments	114
A	Equivalence to SIF condition	115
	Bibliography	121
	Biography	133

List of Tables

2.1	Material properties for uniaxial bar	35
2.2	Material properties, geometric parameters and applied loads for crack initiation problem	38
2.3	Parameters used for pressurized crack propagation problem	42
2.4	Absolute error in J vs. G_c^{eff} for the pressurized crack propagation problem, as a function of regularization length.	44
3.1	Material properties and problem parameters for the toughness-dominated KGD problem	73
3.2	Effect of subdomain size on the relative error in the crack length. . .	76
3.3	Material properties and problem parameters for the viscosity-dominated KGD problem	77
3.4	Material properties for poroelastic problem	81
3.5	Problem settings	81
3.6	Material properties for inclusion problem	85
3.7	Problem settings	85
4.1	Reference values	99
4.2	Reference values	102

List of Figures

1.1	These plots show the evolution of fracking, leading to it becoming the main source of oil and gas in the United States. The numbers shown in the graphs are behind the actual values mentioned in the text because the charts were last updated in 2015. Courtesy from the US Energy Information Administration.	2
1.2	Simplified depiction of an EGS system. Courtesy of Los Alamos National Laboratory.	3
2.1	Generic body containing cracks loaded in pressure.	14
2.2	(a) Unloaded virtual crack. (b) Pressure loaded virtual crack;	17
2.3	(a) The contour paths ζ_{in} and ζ_{out} and subdomain Λ , in the vicinity of a regularized crack.; (b) Color contour plot indicating the assumed variation in the function q	27
2.4	Uniaxial cohesive bar.	34
2.5	Traction-separation curves for pressurized uniaxial cohesive bar problem, obtained with various phase-field models: (a) (LVC) with linear indicator function; (b) (LVC) with quadratic indicator function; (c) (LVC) with $2d - d^2$ indicator function; and (d) Proposed approach (UVC) with linear indicator function.	36
2.6	(a) Problem schematic; (b) Mesh used in the computations, exploiting symmetry.	38
2.7	(a) Final crack pattern using proposed model; (b) Damage field using the model from [1].	40
2.8	(a) Geometry and boundary conditions for pressurized crack propagation problem; (b) J-Integral domain function q	41

2.9	Reference results with the LVC formulation. Curves with $\ell = a/160$ are not shown, as they are almost identical to the ones with $\ell = a/80$. (a) $I(d) = d$; (b) $I(d) = d^2$; (c) $I(d) = 2d - d^2$	43
2.10	Results with the proposed formulation (UVC) (a) $I(d) = d$; (b) $I(d) = d^2$; (c) $I(d) = 2d - d^2$	43
2.11	Convergence of the proposed formulation with $I(d) = d$	44
3.1	Schematic of a poroelastic rock with a fracture, inspired by [2]	51
3.2	Global domain Ω on the left and local domain Ω_L on the right. The surface corresponding to the local domain boundary $\partial\Omega_L$ is indicated within the global domain with the dashed red lines. The local domain is magnified to highlight the phase-field representation of the global crack Γ .	58
3.3	Global domain Ω on the left and local domain Ω_L on the right. The nodes in the subset \mathcal{K} , where d is set to 1 are colored in yellow.	62
3.4	Illustration of global cells (in gray) in the neighborhood of a local element, indicated in pink. The matrix pressure at a quadrature point in the local element is calculated using an average of global pressures from neighboring cells $\{i\}$, with weights corresponding to the distances r_i between the quadrature point and the cell center.	63
3.5	(a): Illustration of the global crack tip and global tip element. (b) Case when the local tip falls inside the tip element. (c) Case when the local tip falls outside the tip element.	68
3.6	(a): Construction of the segment connecting global and local tips. (b) New crack segment to be added. (c) Update of the global crack tip and global tip element.	69
3.7	Multi-resolution solution algorithm.	71
3.8	(a) Schematic of the KGD problem, inspired by [3]. (b) Computational domain for the KGD problem (not to scale).	72
3.9	Comparison of numerical results and analytical solution for the toughness-dominated KGD problem: (a) crack length vs. time and (b) pressure vs. time.	75
3.10	Study of the effects of subdomain size on the results of the toughness-dominated KGD problem: (a) influence on predicted crack length and (b) predicted pressure.	76

3.11 Numerical results and analytical solution for the viscosity-dominated KGD problem: (a) crack length vs. time; and (b) inlet pressure vs. time.	79
3.12 Geometry and notation for the coupled poroelastic-fracture problem.	80
3.13 Results from the fully coupled poroelastic-fracture problem for the multi-resolution method (with and without driving pressures) and a standard phase-field model: (a) crack size over time, (b) inlet pressure. The time for crack propagation (t_{ref}) in the phase-field model and the corresponding inlet pressure (p_{ref}) are used as references for the dimensionless charts above.	83
3.14 Fields from the coupled poroelastic-fracture problem, taken at the end of the simulation, contrasting results from the multi-resolution scheme without the driving pressures (top row) to those obtained using a standard phase-field model of fracture in poroelastic media (bottom row). (a) Contour plots of the damage field. (b) Contour plots of the pressure field.	83
3.15 Geometry for the inclusion problem.	84
3.16 Crack paths for the inclusion problem: (a) 2X stiffer inclusion; (b) 7X stiffer inclusion; and (c) 15X stiffer inclusion.	86
3.17 Inlet pressure as a function of time for the three inclusion problems, corresponding to inclusions with different stiffnesses. The reference values of the pressure p_{ref} and time t_{ref} were defined as the minimum pressure that led to fracture growth and the associated time, considering the simulated injection rate.	87
4.1 Multi-resolution solution algorithm.	92
4.2 Front elements shown in green. Red elements represent discretized fracture.	94
4.3 Schematic of propagation steps.	95
4.4 Parallel specimen.	100
4.5 Two quantities of interest for the parallel fracture problem. On the left, the time series of the pressure at the injection point, on the right, the fracture aperture. Both plots show results scaled by reference values, calculated at the onset of propagation.	100
4.6 (a) time 1; (b) time 2; (c) time 3; and (d) time 4.	101

4.7	Merging specimen.	103
4.8	Two quantities of interest for the merging fracture problem. On the left, the time series of the pressure at the injection point, on the right, the fracture aperture. Both plots show results scaled by reference values, calculated at the onset of propagation.	103
4.9	(a) time 1; (b) time 2; (c) time 3; and (d) time 4.	104
4.10	This figure shows a pathological case for the topological criterion proposed in 4.3.2. The element on the right is only partially damaged, however, the counts of cut edges and faces are higher than the ones for the element on the left, which is indeed fully cut.	106
4.11	Pre-cut basic shapes.	108
4.12	Flux in discontinuous fracture surfaces.	109
4.13	Algorithm modifications	110
4.14	Edge crack specimen.	112
4.15	(a) Initial crack; (b) Final damage path.	112

Acknowledgements

I want to thank Professor Ilinca Stanciulescu, with whom I worked during my undergraduate years, for her patient guidance in my first research project. I want to thank Dr. Henrique Versieux, my Masters advisor, for introducing me to the theory of phase-field and the mathematical background that was very important to me in this Ph.D. I want to thank Professor John Dolbow, my advisor, for his valuable advice, barbecues and Thanksgiving dinners, and for proofreading several poorly written drafts of mine. I want to thank Professors Wilkins Aquino, Johann Guilleminot, Manolis Vveakis for their time and service as my committee members. Most of the work in this dissertation originated from their course projects. I want to thank Dr. Matteo Cusini, Dr. Fan Fei, Dr. Tao Jin and Dr. Randolph Settgast from the Lawrence Livermore National Laboratory for many enlightening discussions. I want to thank my colleagues Dr. Gary Hu and Dr. Rudy Geelen for babysitting me during my first semesters as a graduate student.

I also want to thank my mom Celia, dad Fernando and sister Julia for all the support in these difficult years away from home. As well as my girlfriend Leticia for going through so much time on a long-distance relationship and for all our daily calls over these years.

1

Introduction

1.1 Motivation

Hydraulic fracturing, commonly known as fracking, is a complex process that involves the initiation and/or propagation of fractures resulting from the application of hydraulic pressure by a fluid. This technique finds extensive applications, particularly in the field of geology. [3].

In the realm of oil and gas production, fracking is used to stimulate tight shale reservoirs, creating pathways for the extraction of shale gas. Since the pioneering field test at the Hugoton field in 1947, advancements in fracking technology, such as multi-stage hydraulic fracturing and horizontal drilling, have significantly enhanced productivity in these reservoirs. In fact, recent data from the US Energy Information Administration[4, 5] reveals that a significant portion, around 66% of all oil and 80% of all gas, produced in the United States comes from wells that undergo hydraulic fracturing. (See Figure 1.1.)

Hydraulic fracturing also plays a crucial role in geothermal energy, which offers a promising avenue for generating renewable, carbon-free electricity. In general, the biggest challenge of these geothermal systems is the low permeability of most




FIGURE 1.1. These plots show the evolution of fracking, leading to it becoming the main source of oil and gas in the United States. The numbers shown in the graphs are behind the actual values mentioned in the text because the charts were last updated in 2015. Courtesy from the US Energy Information Administration.

suitable hot rock formations, which limits the productivity of these systems in their natural state. By employing hydraulic fracturing techniques, the permeability, and consequently the efficiency of geothermal systems can be improved. These specially treated systems are commonly referred to as Enhanced Geothermal Systems (EGS). Advances in fracking science and technology are thus one of the key steps towards making EGS a viable and reliable clean energy source. The process is depicted in Figure 1.2.

Another significant geological process that addresses the global CO₂ problem is Carbon Storage and Sequestration, where CO₂ is injected and trapped in tight rock formations deep beneath the surface, preventing its release into the atmosphere. In the context of CO₂ sequestration, caprock fracturing, which can happen during injection or through long-term thermo-chemo-mechanical processes may lead to CO₂ leakage.[6] This consists thus of case where, in contrast of the previous ones, hydraulic fracture must be prevented.

One can also find applications in various other fields, including the disposal of waste drill cuttings underground [7], measurement of in situ stresses [8, 9], goafing and fault reactivation in mining operations [10, 11], and stimulation of groundwater wells [12, 13].

Despite its significant economic benefits, the process has raised concerns among critics regarding potential seismic events, especially in the context of O&G and EGS applications. Additional objections center around the environmental impact, including air and noise pollution, as well as the risk of groundwater and surface water contamination when chemicals are mixed with the injection fluids.

Given the importance of these applications and the associated risks, it is evident that a comprehensive understanding of fracture processes is crucial for the well-being of our planet and society. However, obtaining sufficient experimental data for deep subsurface processes is challenging due to the depths involved and the difficulty in replicating true rock conditions in laboratory experiments. Consequently, there has been a growing focus on computational modeling and simulation of fluid-driven fracture. These computational approaches provide a cost-effective means to gain insights into the intricate physical processes associated with hydraulic fracturing.

1.2 Background

Any mathematical model that tries to represent the hydraulic fracturing phenomena has to account for at least three different processes. The deformation of the rock, the fluid flow and the fracture propagation [3]. These three processes are strongly coupled, which makes the derivation of analytical solutions very complicated, and only possible when the fracture has a predefined shape. Some examples of that are




FIGURE 1.2. Simplified depiction of an EGS system. Courtesy of Los Alamos National Laboratory.

the PKN model [14, 15, 16] and the KGD model [17, 18], developed in the early days of the hydraulic fracturing technology. Although limited by restrictive assumptions, they were extremely useful at that time, providing engineers with good estimations of treatment parameters.

The topic of analytical approaches is still an ongoing area of research with significant progress being made in the past decades, specifically in understanding propagation regimes, near-tip processes, and scaling laws. Extensive research has yielded valuable insights. For instance, near-tip solutions for zero-toughness, impermeable fractures were derived using asymptotic theory in [19], and the analysis was extended to leak-off dominated cases in [20]. Subsequent studies have incorporated additional factors, such as finite toughness and fluid-lag [21, 22, 23]. Moreover, similar techniques have been applied to identify the dimensionless groups that govern the key characteristics of the solutions, enabling the categorization of main regimes (leak-off, toughness, or viscosity dominated) within the parameter space. This parameter space includes rock properties like elastic moduli, toughness, and leak-off coefficient, as well as treatment characteristics such as fluid viscosity and injection rate [24, 25, 26, 27, 28].

Although these analytical methods provide valuable insight into the physics and allow for useful back of the envelope calculations, they can not be used to simulate most of the practical fracking treatments due to their restrictive assumptions regarding fracture geometry and homogenous material properties. They also are not able to capture other important phenomena that affect hydraulic fracturing, such as the presence of confining (*in situ*) stresses, pre-existing (natural) fractures, propellant transport and etc. All these issues have been demonstrated by experiments to affect the fracture propagation and therefore, motivated the development of more widely applicable computational approaches that aim to obtain approximations to the solutions of fluid-driven fracture models in their general form.

These approaches range from production-level reservoir modeling tools such as ResFrac[29, 30], Xsite[31], Kinetix[32, 33] (check [34] for an extensive list) to open-source alternatives, such as GEOS[35, 36, 37], PyFrac[38] and others. Many of the models and associated codes assume fracture networks that remain planar, but in recent years strides have been made towards modeling cracks that evolve in arbitrary ways in response to fluid-driven loads. Some works in this direction include (i) Gupta and Duarte [39, 40] which used a higher-order generalized finite element method (GFEM) to discretize the fracture surface and compute accurate stress intensity factors(SIFs); (ii) Salimzadeh et al. [271, 272, 273] and Paluszny et al. [238] which used adaptive remeshing and a pure FEM based approach, in combination with the displacement correlation method to calculate the SIFs even in the presence of multiple interacting fractures and (iii) Tang et al. [41] and Li et al. [42, 43] where the boundary element method is combined with the displacement discontinuity approach to propagate fractures which are loosely coupled to the mechanical problem using EDFM[44]. However, in all these approaches, the computation of crack front advancements still relies on phenomenological relations between the computed SIFs and some type of crack front velocity. They also have limitations when dealing with merging cracks (for example, when a hydraulic fracture approaches a natural fracture), as the formulations do not account for the possibility of a propagating crack to arrest in these cases.

All these approaches can be grouped together in the broad category of sharp interface models, where the fracture surface is explicitly modelled. These tend to be particularly advantageous when the fracture configuration is relatively simple, but face the aforementioned challenges when complex geometric evolution is involved.

Some of these challenges tend to be alleviated with the use of diffuse crack models, such as the phase-field model for fracture [45, 46, 47]. These offer more flexibility for representing complex fracture evolution, and, in many cases, have propagation fully

governed by energetic principles, being, in some sense, a generalization of Griffiths' law [48]. On the other hand, they introduce other challenges such as the lack of a well-defined fracture surface and an increased computational expense[49].

The first attempts towards a phase-field model for hydraulic fracture began with extensions of the traditional phase-field model [45, 46] to pressurized cracks, as in Bourdin et al. [1] and Wheeler et al. [50]. Subsequently, fluid flow in the fractures, and also poromechanics were considered. Miehe et al. [51, 52] developed a thermodynamically consistent framework, from minimization principles, to couple poromechanics, fluid-flow and phase-field fracture. The flow problem was modeled via the Darcy's equation, containing a permeability coefficient that used the phase-field variable and the crack opening to mimic the cubic relationship from the lubrication theory in the crack region. Mikelic et al. [53, 54] developed a model that separated the domain into fracture and reservoir, by using the phase-field variable as an indicator function. They also considered the flow inside the fracture as a Darcy flow, but their model treated the fracture as a three-dimensional entity, which led to a different permeability tensor compared to [51, 52]. Yet another approach concerns the work of Wilson and Landis [55], who proposed a model that included fluid velocities as primary variables. This allowed for a more detailed description of the flow within the fracture, which was modeled by a Brinkman-type equation [56]. The phase-field parameter acted as an indicator of the flow regime, between Darcy flow (away from cracks) and Stokes flow (inside cracks). Finally, the recent work of Chukwudzie et al. [57] presented a different model, wherein the lubrication theory equations were included in the weak form by means of a Γ -convergent regularization. These various formulations exhibit real differences in terms of their structure, mainly due to the different forms of incorporating the pressure loads and extracting an aperture value over diffuse fracture surfaces. Therefore, comparative investigations such as [58] and [59] are still needed for a better understanding of the

strengths and weakness of these models.

The use of a phase-field to represent a fracture network in a diffuse manner certainly facilitates the representation of complex geometric evolution, including crack branching and merging. However, it also requires the use of meshes or grids that are capable of resolving the regularization length, making these approaches computationally expensive. One approach to improving the efficiency of the method is the use of adaptive mesh refinement, such as in [60, 61, 62, 63]. In the specific case of hydraulic fracturing, another challenge concerns the crack opening or aperture, a field that is tightly coupled with the fluid pressure within fractures. In a phase-field setting, due to the lack of an explicit crack surface, extracting the aperture or accounting for its effects requires additional considerations. All the aforementioned works present some way to account for the aperture within a diffuse setting, but the robustness of these approaches remains unclear [64].

Outside the context of hydraulic fracturing, some researchers in the phase-field community have developed “hybrid” approaches, wherein the phase-field formulation was combined with a sharp crack representation. The motivation for these approaches varies, from “cutting” the mesh to remove artificial traction transmission and circumvent element distortion [65] to reducing the overall computational cost [66, 67, 68]. In the work of Giovanardi et al.[66], phase-field subproblems in the vicinity of crack tips were used to propagate a global, discrete crack. The eXtended Finite Element Method (XFEM)[69] was used to place fracture discontinuities in the displacement field within the background global mesh. More recently, Muixi et al.[67] created an approach that uses the phase-field method only at the crack tips, and XFEM in the rest of the domain. In contrast to [66], there is no overlap of the representations in crack tip areas. In Li et al. [68], the shifted boundary method is employed to represent the discrete fracture without mesh cutting techniques. This method preserves mesh independence of the crack path, which is governed by a

phase-field subproblem near the fracture process zones. This subproblem is blended to global one similarly to [66]. Interestingly, the authors are able to take advantage of the phase-field approach to solve problems involving crack branching and merging in 2D.

The success of these hybrid approaches for purely mechanical cases opens the door for their extension to hydraulic fracturing. Such approaches are appealing because in principle they can circumvent the need for a complicated reconstruction of the crack opening from the phase-field. This area began to gain traction in the past few years. In Sun et al. [70] the authors developed a Finite Element-Meshfree method to represent the crack surfaces in a discrete fashion. The computed displacement field was used to obtain a driving force which was employed within the phase-field equation. This approach eliminated the need for the reconstruction of crack openings from the diffuse crack representation, but it also largely decoupled the phase field from the equations governing the force balance and did not address the computational expense associated with the fine discretization needed to represent the phase-field. More recently, Burbulla et al. [71] devised a similar hybrid algorithm, with improved coupling between the damage and displacement fields, but they also did not attempt to circumvent the elevated computational cost incurred by the phase-field approach. That was only investigated by [72], where the phase-field problem is restricted to a small portion of the domain, with the goal of reducing the overall problem size. In their work, only two-dimensional problems are studied.

1.3 Research contributions

This dissertation revisits the computational modeling of hydraulic fracturing with emphasis in the phase-field approach and proposes a new hybrid scheme that overcomes the two main limitations of pure phase-field formulations. Namely, the computation of the fracture aperture and the expensive computational cost. On a different

take, this new scheme, when compared to standard discrete fracture models, removes the need for a phenomenological criterion for crack propagation by relying on the minimization of an energy functional to drive fracture growth. Fundamental modeling aspects, related to the phase-field description of fluid-driven fracture are also discussed. The main contributions of each chapter are summarized below.

- In Chapter 2, we present a new phase-field formulation for including crack-face pressure loads and discuss how this formulation can be achieved by modifying the trial space in the traditional variational principle or by introducing a new functional dependent on the rates of the primary variables. The key differences between the new formulation and existing models for pressurized cracks in a phase-field setting are emphasized. Model-based simulations developed with discretized versions of the new formulation and existing models are then used to illustrate the advantages and differences. In order to analyze the results, a domain form of the J-Integral is developed for diffuse cracks subjected to pressure loads.
- In Chapter 3, we propose a multi-resolution approach for constructing model-based simulations of fluid-driven fracture. The approach consists of a hybrid scheme that couples a discrete crack representation in a global domain to a phase-field representation in a local subdomain near the crack tip. The multi-resolution approach addresses issues such as the computational expense of accurate hydraulic fracture simulations and the difficulties associated with reconstructing crack apertures from diffuse fracture representations. The efficacy of the method is illustrated through various benchmark problems in hydraulic fracturing, as well as a new study of fluid-driven crack growth around a stiff inclusion.
- In Chapter 4, we present an extension of the multi-resolution approach to three

dimensions, which involves a modification to the propagation scheme used in Chapter 3. This part is dependent on the results I can get in the next 2 months.

→ We also show some results of simulations of reservoir scale problems with multiple fractures and realistic material data. Considerations about efficient implementations in supercomputers as well as extensions to non-planar cases are also discussed.

1.4 Organization of the dissertation

I read this section in Gary's and Rudy's thesis and it just feels like rewording the previous paragraphs. Do we really need it?

1.5 Notation

This is from Gary's dissertation, so, I need to check if there are some new symbols I used.

In what follows, deterministic scalar, vectors, second-order tensors, and fourth-order tensors are denoted by a (or A), \mathbf{a} (or \mathbf{A}), \mathbf{A} , and \mathbb{A} , respectively.

Let Ω be a collection of points $\mathbf{X} \in \mathbb{R}^d$, $d \in \{1, 2, 3\}$. Scalar- and vector-valued random fields defined on the probability space (Θ, Σ, P) , indexed by Ω , are denoted as $\{A(\mathbf{X}), \mathbf{X} \in \Omega\}$ and $\{\mathbf{A}(\mathbf{X}), \mathbf{X} \in \Omega\}$, respectively. At any fixed material point $\mathbf{X} \in \Omega$, $a(\mathbf{X})$ and $\mathbf{a}(\mathbf{X})$ are random variables defined on the probability space (Θ, Σ, P) . For any fixed $\theta \in \Theta$, $a(\theta)$ and $\mathbf{a}(\theta)$ are realizations of the random variables. Similarly, $\mathbf{X} \mapsto a(\mathbf{X}; \theta)$ and $\mathbf{X} \mapsto \mathbf{a}(\mathbf{X}; \theta)$ are realizations of the random fields $\{A(\mathbf{X}), \mathbf{X} \in \Omega\}$ and $\{\mathbf{A}(\mathbf{X}), \mathbf{X} \in \Omega\}$.

Einstein summations are assumed wherever applicable unless otherwise stated. For any vectors \mathbf{a} and \mathbf{b} of the same size, the inner product is defined as $\mathbf{a} \cdot \mathbf{b} = a_i b_i$ where a_i and b_i are components of the vectors. The associated vector norm is $\|\mathbf{a}\|^2 = \mathbf{a} \cdot \mathbf{a}$. Similarly, for any second-order tensors \mathbf{A} and \mathbf{B} of the same size, the

inner product is defined as $\mathbf{A} : \mathbf{B} = \text{tr}(\mathbf{A}^T \mathbf{B})$. The associated Frobenius norm reads $\|\mathbf{A}\| = \sqrt{\mathbf{A} : \mathbf{A}}$. Other matrix norms will be distinguished by subscripts. The outer (cross) product of two vectors is written as $\mathbf{a} \otimes \mathbf{b} = a_i b_j$.

The time derivative is denoted by an over-dot, e.g. \dot{a} . Partial derivative is denoted by a subscript starting with a comma, i.e. $a_{,bc} \equiv \partial^2 a / \partial b \partial c$. Macaulay brackets are denoted by triangle brackets $\langle a \rangle_{\pm}$ and are defined as $\langle a \rangle_{\pm} \equiv (a \pm |a|)/2$.

2

Revisiting the Pressure Loading of Phase-Field Fractures

2.1 Introduction

In this Chapter, a new formulation for the study of pressurized fractures, first proposed in the thesis of Hu [73] is examined. In particular, it is studied in combination with a cohesive version of the phase-field for fracture method, which was proposed in the recent works of [74, 75, 76]. This facilitates the study of pressurized fracture in quasi-brittle materials and reduces the sensitivity of the effective strength to the regularization length. To ensure that the cohesive fracture behavior is preserved, the implicit traction-separation law is evaluated for a simple one-dimensional problem and shown to be insensitive to the applied pressure with the new formulation. Fracture initiation and propagation examples are also examined to highlight advantages and limitations of the model, which is compared to other formulations for treating pressure-loaded fractures. This comparison also aids in understanding the implications of different modeling choices that have been widely used in the literature [1, 50, 77, 78, 79].

As part of the analysis conducted to evaluate the various formulations, the J-Integral is used to verify the extent to which mode-I crack propagation occurs when the energy release rate reaches the critical fracture energy. The contour form of the J-Integral and its modifications for some common cases of phase-field fracture has been examined by others, see e.g. the work of [80], [81] and [82]. In the case of pressurized cracks, the contour version of the J-Integral is not path independent. Many prior works have focused on developing domain forms of the J-Integral for sharp cracks that are domain independent [83, 84]. In this work, a domain form of the J-Integral that is suitable for pressurized phase-field cracks is developed for the first time.

The Chapter is organized as follows. In Section 2.2, a simple model for pressure-induced fracturing is presented and the new phase-field formulation is derived in two different ways. Section 2.3 provides the derivation of the domain form of the J-Integral for pressurized phase-field cracks. In Section 2.4, the discretization scheme using finite elements is presented. Then, in Section 2.5 some fundamental examples involving crack nucleation and propagation are used to illustrate the performance of the various models and choices of indicator functions.

2.2 Model

The formulation for treating pressurized cracks in a phase-field setting, first introduced by Hu [73], can be derived in two different ways. In what follows, it is first derived based on energy minimization in quasi-static conditions in subsection 2.2.1. This illustrates the main difference in the underlying hypothesis for this new model compared to the widely used formulations of [1] and [77], for example. A second derivation based on a maximum dissipation principle is then provided in subsection 2.2.2.

The following assumptions are invoked for both derivations. A linear elastic body

$\Omega \in \mathbb{R}^n$ ($n = 2$ or 3), containing cracks denoted by Γ is considered (Figure 2.1). The boundary $\partial\Omega$ is partitioned as $\partial\Omega = \partial\Omega_D \cup \partial\Omega_N$, where $\partial\Omega_D$ represents the portion of the boundary where displacements are prescribed and $\partial\Omega_N$ the portion where tractions are applied. Deformations and rotations are assumed to be small, so that a small-strain formulation is appropriate. For simplicity, body forces are neglected.

2.2.1 Quasi-static derivation




FIGURE 2.1. Generic body containing cracks loaded in pressure.

The quasi-static derivation of the formulation begins by considering the potential energy of a body with cracks which are internally loaded with a pressure p . Crack propagation is associated with a critical fracture energy density, G_c . The total potential energy is given by

$$U(\boldsymbol{\epsilon}(\mathbf{u})) = \int_{\Omega} \psi_e(\boldsymbol{\epsilon}(\mathbf{u})) \, dV + \int_{\Gamma} G_c \, dA - \int_{\Gamma} p \mathbf{n} \cdot \mathbf{u} \, dA - \int_{\partial\Omega_N} \mathbf{t} \cdot \mathbf{u} \, dA, \quad (2.1)$$

in which \mathbf{u} are the displacements, $\boldsymbol{\epsilon}(\mathbf{u}) = \nabla^s \mathbf{u}$ denotes the infinitesimal strain, ψ_e the strain energy density, \mathbf{t} the externally applied tractions and \mathbf{n} the unit normals of the crack set Γ (oriented outwards from Ω).

In a phase-field for fracture setting, the crack surface Γ is regularized with the aid of a scalar phase (or damage) field $d(\mathbf{x}) \in [0, 1]$. In this work, $d = 0$ represents intact

material (away from the crack surface) and $d = 1$ fully-damaged material (inside the crack). The damage field is employed in the approximation of the surface integrals in (2.1) as volume integrals. For the energy associated with fracture, several common formulations are encapsulated by the approximation

$$\int_{\Gamma} G_c dA \approx \int_{\Omega} \frac{G_c}{c_0 \ell} \left(\alpha(d) + \ell^2 \nabla d \cdot \nabla d \right) dV, \quad (2.2)$$

where $\alpha(d)$ denotes a local dissipation term, ℓ is the regularization length, and c_0 is a normalization constant given by $c_0 = 4 \int_0^1 \sqrt{\alpha(s)} ds$.

Such a regularization implies that the distinct crack surface Γ is no longer defined. As such, the second integral on the right of (2.1) also needs to be approximated as a volume integral in some manner. This is effected with the use of an indicator function $I(d)$. The surface integral involving the pressure is then approximated as

$$\int_{\Gamma} p \mathbf{n} \cdot \mathbf{u} dA \approx \int_{\Omega} p \left(-\frac{\nabla d}{\|\nabla d\|} \right) \cdot \mathbf{u} \|\nabla I(d)\| dV. \quad (2.3)$$

Note that the crack surface normal \mathbf{n} is approximated as $-\nabla d / \|\nabla d\|$, whereas the differential surface element dA becomes $\|\nabla I\| dV$. The indicator function must satisfy $I(0) = 0$, $I(1) = 1$ and be monotonically increasing. In Bourdin et al. [1], $I(d) = d$ was firstly proposed. Wheeler et al. [50] provide a derivation that avoids an explicit approximation of the normal, such as (2.3), but is in fact equivalent to using the indicator function $I(d) = 2d - d^2$. In Peco et al. [78] and Jiang et al. [79], $I(d) = d^2$ is used, with the motivation that $I'(0) = 0$ is required to avoid the effects of pressure in undamaged areas.

Combining the approximation in (2.3) with the traditional phase-field approximation of fracture based on the Ambrosio-Tortorelli functional [46] and applying the

chain rule, the regularized counterpart of (2.1) is given by

$$\begin{aligned} U(\boldsymbol{\epsilon}, d) = & \int_{\Omega} \psi_e(\boldsymbol{\epsilon}, d) \, dV + \int_{\Omega} p \nabla d \cdot \mathbf{u} \, I'(d) \, dV \\ & + \int_{\Omega} \frac{G_c}{c_0 \ell} \left(\alpha(d) + \ell^2 \nabla d \cdot \nabla d \right) \, dV - \int_{\partial\Omega_N} \mathbf{t} \cdot \mathbf{u} \, dA, \end{aligned} \quad (2.4)$$

where the explicit dependence of the strain on the displacements has been dropped.

Often, the strain energy density is split and part of it is degraded with the damage, i.e.

$$\psi_e(\boldsymbol{\epsilon}(\mathbf{u}), d) = g(d) \psi_e^+(\boldsymbol{\epsilon}(\mathbf{u})) + \psi_e^-(\boldsymbol{\epsilon}(\mathbf{u})), \quad (2.5)$$

where $g(d)$ denotes the degradation function, and $\psi_e^+(\boldsymbol{\epsilon}(\mathbf{u}))$ and $\psi_e^-(\boldsymbol{\epsilon}(\mathbf{u}))$ denote the “active” and “inactive” parts of the energy. The above form encapsulates most of the strain decompositions used in the literature [85],[86] to introduce asymmetry in the fracture behavior in tension and compression.

Typically, a minimization principle is applied to (2.4) to extract the governing equations for the displacements \mathbf{u} and the damage d . According to this principle, a pair (\mathbf{u}, d) is a valid state if and only if all neighboring states $(\mathbf{u} + \delta\mathbf{u}, d + \delta d)$ have a greater potential energy. In the case of pressurized cracks, a subtle consideration leads to the formulation proposed herein. Consider the two scenarios indicated in Figure 2.2 where a denotes the crack length and da an infinitesimal crack increment. In the situation depicted in Figure 2.2b, the pressure load (applied in the areas colored in blue), is assumed to accompany any crack propagation. Therefore, in an energetic analysis, the virtual crack extension da is assumed pressurized. By contrast, in Figure 2.2a, the pressure load is assumed to remain confined to the original crack geometry during propagation. As a result, the virtual crack extension da is not subject to any surface load.

In terms of the resulting formulation, the difference between the two scenarios

shown in Figure 2.2 translate into the question of whether or not the damage variation δd should enter the pressure work contribution (2.3).

For the family of formulations that derived from [1] and [50], the scenario depicted in Figure 2.2b is assumed as a consequence of including the damage variation δd in (2.3). The proposed model in this work, by contrast, assumes the case indicated by Figure 2.2a. While in a discrete crack model these competing views may lead to the same energy release rate when taking the limit $da \rightarrow 0$, their phase-field regularizations give rise to different sets of governing equations. As demonstrated in the numerical examples in Section 5, this can translate into significant differences in the results from model-based simulations.




FIGURE 2.2. (a) Unloaded virtual crack. (b) Pressure loaded virtual crack;

In what follows, the formulation associated with Figure 2.2a will be referred to as the Unloaded Virtual Crack formulation, or UVC for short. In the UVC, the variation of the pressure work is simply¹,

¹ On the other hand, if the assumption of Figure 2.2b is chosen, as in [1], two additional terms have to be accounted for,

$$\delta \left(\int_{\Omega} p \nabla d \cdot \mathbf{u} I'(d) dV \right) = \int_{\Omega} p \nabla d \cdot \delta \mathbf{u} I'(d) dV + \underbrace{\int_{\Omega} p \nabla \delta d \cdot \mathbf{u} I'(d) dV + \int_{\Omega} p \nabla d \cdot \mathbf{u} \delta d I''(d) dV}_{\text{additional terms}}.$$

$$\delta \left(\int_{\Omega} p \nabla d \cdot \mathbf{u} I'(d) dV \right) = \int_{\Omega} p \nabla d \cdot \delta \mathbf{u} I'(d) dV. \quad (2.6)$$

The variation of the potential energy δU can then be written as,

$$\begin{aligned} \delta U(\boldsymbol{\epsilon}, d) &= \int_{\Omega} \frac{\partial \psi_e}{\partial \boldsymbol{\epsilon}} : \delta \boldsymbol{\epsilon} dV + \int_{\Omega} p \nabla d \cdot \delta \mathbf{u} I'(d) dV - \int_{\partial \Omega_N} \mathbf{t} \cdot \delta \mathbf{u} dA \\ &\quad + \int_{\Omega} g'(d) \psi_e^+(\boldsymbol{\epsilon}) \delta d dV + \int_{\Omega} \frac{G_c}{c_0 \ell} \left(\alpha'(d) \delta d + 2\ell^2 \nabla d \cdot \nabla \delta d \right) dV, \end{aligned} \quad (2.7)$$

and, with the help of the divergence theorem,

$$\begin{aligned} \delta U(\boldsymbol{\epsilon}, d) &= \int_{\Omega} \left(-\nabla \cdot \frac{\partial \psi_e}{\partial \boldsymbol{\epsilon}} + p I'(d) \nabla d \right) \cdot \delta \mathbf{u} dV \\ &\quad + \int_{\Omega} \left(g'(d) \psi_e^+(\boldsymbol{\epsilon}) + \frac{G_c}{c_0 \ell} \alpha'(d) - \nabla \cdot \frac{2G_c \ell}{c_0} \nabla d \right) \delta d dV \\ &\quad + \int_{\partial \Omega_N} \left(\frac{\partial \psi_e}{\partial \boldsymbol{\epsilon}} \cdot \mathbf{n} - \mathbf{t} \right) \cdot \delta \mathbf{u} dA + \int_{\partial \Omega} \frac{2G_c \ell}{c_0} (\mathbf{n} \cdot \nabla d) \delta d dA. \end{aligned} \quad (2.8)$$

The local minimization principle requires the variation of the potential energy δU to be non-negative for any admissible state \mathbf{u}, d . In other words, $\delta U(\boldsymbol{\epsilon}, d) \geq 0$, giving rise to the following equation and boundary condition for \mathbf{u} , since the variation of the displacement field $\delta \mathbf{u}$ is arbitrary:

$$-\nabla \cdot \boldsymbol{\sigma} + p I'(d) \nabla d = \mathbf{0} \text{ in } \Omega, \quad (2.9)$$

$$\boldsymbol{\sigma} \cdot \mathbf{n} - \mathbf{t} = \mathbf{0} \text{ in } \partial \Omega_N. \quad (2.10)$$

In the above, $\boldsymbol{\sigma}$ denotes the Cauchy stress, defined as $\boldsymbol{\sigma} = \frac{\partial \psi_e}{\partial \boldsymbol{\epsilon}}$.

For the damage variable, it is assumed that the process is irreversible, such that $\dot{d} \geq 0$. As such, only positive variations in the damage are admissible, and $\delta U(\boldsymbol{\epsilon}, d) \geq 0$ implies

$$g'(d)\psi_e^+(\boldsymbol{\epsilon}) + \frac{G_c}{c_0\ell}\alpha'(d) - \nabla \cdot \frac{2G_c\ell}{c_0}\nabla d \geq 0 \text{ in } \Omega, \quad (2.11)$$

$$\frac{2G_c\ell}{c_0}\mathbf{n} \cdot \nabla d \geq 0 \text{ on } \partial\Omega. \quad (2.12)$$

Equations (2.11) and (2.12) are identical to those in the standard phase-field model for traction-free cracks. This is the main difference between the new formulation and existing ones derived from deriving from [1] and [50], in which the governing equation for the damage field contains additional terms to account for the pressure loads on the virtual cracks. In what follows, we refer to that as the Loaded Virtual Crack formulation, or LVC. In the boxes below, the governing equations for the UVC are compared to those of the LVC.

Unloaded Virtual Crack Formulation (UVC)

$$-\nabla \cdot \boldsymbol{\sigma} + pI'(d)\nabla d = \mathbf{0} \text{ in } \Omega, \quad (2.13)$$

$$\boldsymbol{\sigma} \cdot \mathbf{n} - \mathbf{t} = \mathbf{0} \text{ in } \partial\Omega_N. \quad (2.14)$$

$$g'(d)\psi_e^+(\boldsymbol{\epsilon}) + \frac{G_c}{c_0\ell}\alpha'(d) - \nabla \cdot \frac{2G_c\ell}{c_0}\nabla d \geq 0 \text{ in } \Omega, \quad (2.15)$$

$$\frac{2G_c\ell}{c_0}\mathbf{n} \cdot \nabla d \geq 0 \text{ on } \partial\Omega. \quad (2.16)$$

Loaded Virtual Crack Formulation

(LVC)

$$-\nabla \cdot \boldsymbol{\sigma} + pI'(d)\nabla d = \mathbf{0} \text{ in } \Omega, \quad (2.17)$$

$$\boldsymbol{\sigma} \cdot \mathbf{n} - \mathbf{t} = \mathbf{0} \text{ in } \partial\Omega_N. \quad (2.18)$$

$$\begin{aligned} g'(d)\psi_e^+(\boldsymbol{\epsilon}) + \frac{G_c}{c_0\ell}\alpha'(d) - \nabla \cdot \frac{2G_c\ell}{c_0}\nabla d \\ - \nabla \cdot [p\mathbf{u} I'(d)] + p\nabla d \cdot \mathbf{u} I''(d) \geq 0 \text{ in } \Omega, \end{aligned} \quad (2.19)$$

$$\mathbf{n} \cdot \left(\frac{2G_c\ell}{c_0}\nabla d + pI'(d)\mathbf{u} \right) \geq 0 \text{ on } \partial\Omega. \quad (2.20)$$

It is readily apparent that the governing equations for the displacements are identical in the UVC and the LVC. The main difference is in the absence of the additional pressure-dependent terms in the evolution for the damage field and the accompanying boundary condition.

In Appendix A, an analytical study of the energy release rate of a crack propagating under an arbitrary pressure load $p(x)$ is provided, under the assumptions of the UVC formulation and linear elastic fracture mechanics. The results of the study show that it is possible to recover the classic relationship between the energy release rate and the stress intensity factor with the UVC formulation. This ensures the consistency of the proposed formulation (UVC) with many theoretical works [87, 23, 24, 28, 88] in the field of hydraulic fracture, where the stress intensity factor is used as the propagation criterion.

2.2.2 Derivation using the maximum dissipation principle

In this subsection, an alternative approach to derive the (UVC) formulation is presented. It is based on the construction of a total potential functional which depends on the rates of the internal variables $\dot{\boldsymbol{\epsilon}}, \dot{d}$ and accounts for the work of the pressure

load as an external dissipation mechanism. This approach is described in more detail in [89] and [73], where it is used to derive a variationally consistent phase-field model for ductile fracture.

The total potential is postulated as,

$$L(\dot{\epsilon}, \dot{d}) = \int_{\Omega} \dot{u}(\dot{\epsilon}, \dot{d}) dV - \mathcal{P}^{ext}, \quad (2.21)$$

where u is the material internal energy, which relates to the Helmholtz free-energy ψ through $\dot{u} = \dot{\psi} + \dot{T}s$, where T is the temperature and s the entropy. In this work, only isothermal processes are considered, therefore, $\dot{u} = \dot{\psi}$. The term \mathcal{P}^{ext} denotes the external power expenditure. If cracks were represented by internal boundaries Γ instead of a damage field, one could write,

$$\mathcal{P}^{ext} = \int_{\partial\Omega \cup \Gamma} \mathbf{t} \cdot \dot{\mathbf{u}} dA = \int_{\partial\Omega} \mathbf{t} \cdot \dot{\mathbf{u}} dA + \int_{\Gamma} p \mathbf{n} \cdot \dot{\mathbf{u}} dA. \quad (2.22)$$

However, in a regularized setting this integral over Γ is once again transformed into a volume integral over Ω , as in (2.3),

$$\int_{\Gamma} p \mathbf{n} \cdot \dot{\mathbf{u}} dA \approx \int_{\Omega} p \left(-\frac{\nabla d}{\|\nabla d\|} \right) \cdot \dot{\mathbf{u}} \|\nabla I(d)\| dV = - \int_{\Omega} p \nabla d \cdot \dot{\mathbf{u}} I'(d) dV. \quad (2.23)$$

Recalling the equivalence between the internal energy and the Helmholtz free-energy, the Coleman-Noll procedure can be applied and, in combination with (2.22) and (2.23), leads to the following expression for L as a function of ψ :

$$L(\dot{\epsilon}, \dot{d}) = \int_{\Omega} \left(\frac{\partial \psi}{\partial \epsilon} : \dot{\epsilon} + \frac{\partial \psi}{\partial d} \dot{d} + \frac{\partial \psi}{\partial \nabla d} \cdot \nabla \dot{d} + p \nabla d \cdot \dot{\mathbf{u}} I'(d) \right) dV - \int_{\partial\Omega} \mathbf{t} \cdot \dot{\mathbf{u}} dA. \quad (2.24)$$

The evolution process is postulated to follow the minimizers of this total potential, with the supplemental conditions that damage is an irreversible process and that the displacements \mathbf{u} are prescribed over a subset $\partial\Omega_D$ of the boundary. In other words,

$$\dot{\boldsymbol{\epsilon}}, \dot{d} = \underset{\dot{\boldsymbol{\epsilon}}, \dot{d}}{\operatorname{argmin}} L(\dot{\boldsymbol{\epsilon}}, \dot{d}), \text{ subject to } \dot{d} \geq 0 \text{ and } \mathbf{u} = \mathbf{g} \text{ on } \partial\Omega_D. \quad (2.25)$$

Using the Euler-Lagrange equations, the following general evolution equations can then be obtained in terms of the free-energy function ψ :

$$\nabla \cdot \frac{\partial \psi}{\partial \boldsymbol{\epsilon}} - pI'(d)\nabla d = \mathbf{0} \text{ in } \Omega, \quad (2.26)$$

$$\nabla \cdot \frac{\partial \psi}{\partial \nabla d} - \frac{\partial \psi}{\partial d} \geq \mathbf{0} \text{ in } \Omega, \quad (2.27)$$

with the boundary conditions

$$\frac{\partial \psi}{\partial \boldsymbol{\epsilon}} \cdot \mathbf{n} - \mathbf{t} = \mathbf{0} \text{ on } \partial\Omega \setminus \partial\Omega_D \quad (2.28)$$

$$\mathbf{n} \cdot \frac{\partial \psi}{\partial \nabla d} \geq 0 \text{ on } \partial\Omega. \quad (2.29)$$

To be consistent with the derivation in subsection 2.2.1, the Helmholtz free-energy is postulated as,

$$\psi(\boldsymbol{\epsilon}, d) = \psi_e(\boldsymbol{\epsilon}, d) + \frac{G_c}{c_0 \ell} \left(\alpha(d) + \ell^2 \nabla d \cdot \nabla d \right), \quad (2.30)$$

following the regularization based on the Ambrosio-Tortorelli functional. In this case, the general equations (2.26)-(2.29) take the form

$$-\nabla \cdot \boldsymbol{\sigma} + pI'(d)\nabla d = \mathbf{0} \text{ in } \Omega, \quad (2.31)$$

$$g'(d)\psi_e^+(\boldsymbol{\epsilon}) + \frac{G_c}{c_0\ell}\alpha'(d) - \nabla \cdot \frac{2G_c\ell}{c_0}\nabla d \geq 0 \text{ in } \Omega, \quad (2.32)$$

with the boundary conditions

$$\boldsymbol{\sigma} \cdot \mathbf{n} - \mathbf{t} = \mathbf{0} \text{ on } \partial\Omega_N, \quad (2.33)$$

$$\mathbf{n} \cdot \nabla d \geq 0 \text{ on } \partial\Omega. \quad (2.34)$$

By inspection, (2.31)-(2.34) are identical to (2.9)-(2.12).

2.2.3 Constitutive choices of the phase-field formulation

In the previous subsection, the proposed model for pressurized cracks was developed for a general phase-field regularization of the variational approach to fracture [45], with a free-energy of the form

$$\psi(\boldsymbol{\epsilon}, d) = \underbrace{g(d)\psi_e^+(\boldsymbol{\epsilon}) + \psi_e^-(\boldsymbol{\epsilon})}_{\psi_e} + \underbrace{\frac{G_c}{c_0\ell}\left(\alpha(d) + \ell^2\nabla d \cdot \nabla d\right)}_{\psi_f}. \quad (2.35)$$

where ψ_f is used to indicate the part of the free-energy associated with fracture.

In what follows, the constitutive choices used in the example problems provided in Section 2.5 are described.

2.2.3.1 Elastic energy and decomposition

First, in terms of the solid bulk response, an elastic energy of the type (2.5) is assumed. When the material is undamaged, it reduces to a purely linear elastic energy, that is,

$$\psi_e(\boldsymbol{\epsilon}(\mathbf{u}), 0) = \psi_e^+(\boldsymbol{\epsilon}(\mathbf{u}), 0) + \psi_e^-(\boldsymbol{\epsilon}(\mathbf{u}), 0) = \frac{1}{2}\boldsymbol{\epsilon}(\mathbf{u}) : \mathbb{C} : \boldsymbol{\epsilon}(\mathbf{u}), \quad (2.36)$$

where \mathbb{C} is the elasticity tensor.

When damage is present, a decomposition of the energy is often assumed. In many cases, when the applied load to a fracturing body is predominately tensile, the “no-split” case given by,

$$\psi_e^-(\boldsymbol{\epsilon}(\mathbf{u}), d) = 0 \rightarrow \psi_e(\boldsymbol{\epsilon}(\mathbf{u}), d) = \frac{1}{2}g(d)\boldsymbol{\epsilon}(\mathbf{u}) : \mathbb{C} : \boldsymbol{\epsilon}(\mathbf{u}), \quad (2.37)$$

is capable of correctly predicting the material response, while leading to a simpler set of governing equations. However, in a wide range of scenarios, compressive forces are present, and an energy split is needed to prevent crack formation in zones of high compression, as well as to allow for transmission of compressive forces across fractured faces.

In Section 2.5, one of the example problems will employ the spectral split of Miehe et al. [86], given by,

$$\psi_e^+(\boldsymbol{\epsilon}(\mathbf{u}), d) = \frac{1}{2}\lambda \langle \text{Tr } \boldsymbol{\epsilon} \rangle_+^2 + \mu \boldsymbol{\epsilon}^+ : \boldsymbol{\epsilon}^+ \text{ and } \psi_e^-(\boldsymbol{\epsilon}(\mathbf{u}), d) = \frac{1}{2}\lambda \langle \text{Tr } \boldsymbol{\epsilon} \rangle_-^2 + \mu \boldsymbol{\epsilon}^- : \boldsymbol{\epsilon}^-. \quad (2.38)$$

Here, $\langle \cdot \rangle_+$ and $\langle \cdot \rangle_-$ denote the positive and negative parts of a number respectively, while $\boldsymbol{\epsilon}^+$ and $\boldsymbol{\epsilon}^-$ are the positive and negative parts of an additive decomposition of the strain tensor based on the signs of its eigenvalues. A more detailed description, including the derivation of the stiffness matrix in this case, is provided by Jiang et al. [90].

2.2.3.2 Brittle fracture

The first and more traditional phase-field model with an energy of the type (2.35) was proposed in [46]. It was developed to approximate the brittle fracture process of linear elastic materials in the limit of vanishing ℓ . In its original form, the degradation

function

$$g(d) = \xi + (1 - \xi)(1 - d)^2, \quad (2.39)$$

is used in combination with a quadratic local dissipation $\alpha(d) = d^2$, in what is now called the AT-2 formulation. However, the use of, $\alpha(d) = d$, (widely referred as the AT-1) comes with the advantage of a purely elastic response before the onset of damage and a compactly supported damage field. Therefore, it will be employed in the example in Section 2.5 where brittle fracture is investigated. The parameter ξ in (2.39) is the residual stiffness, a very small numerical parameter that avoids the loss of ellipticity in fully damaged material.

2.2.3.3 Cohesive fracture

The phase-field model for cohesive fracture was first proposed by Lorentz et al. [74, 91]. In this model, the use of a quasi-quadratic degradation function, given by

$$g(d) = \xi + (1 - \xi) \frac{(1 - d)^2}{(1 - d)^2 + md(1 + pd)}, \quad (2.40)$$

is combined with a linear local dissipation function $\alpha(d) = d$. The parameter m is defined as $m = \frac{G_c}{c_0 \ell \psi_c}$, where ψ_c is the nucleation energy, below which no damage is expected to form. The parameter p is a shape parameter that can be used to adjust the traction-separation response. In this work, $p = 1$ is used.

2.3 A J-Integral for pressurized cracks in a phase-field setting

This Section presents a modified J-Integral, capable of retrieving the energy release rate, denoted here by G in the case of pressurized cracks in a phase-field for fracture setting. The resulting integral is then re-cast into a domain-independent form that is more amenable to finite-element calculations.

A common form of the J-Integral, derived for phase-field fracture and applicable to traction-free cracks is given by [80, 81]

$$J = \mathbf{r} \cdot \int_{\zeta} \left(\psi(\boldsymbol{\epsilon}, d) \mathbb{I} - \nabla \mathbf{u}^T \boldsymbol{\sigma} - \nabla d \otimes \boldsymbol{\omega} \right) \mathbf{n} ds, \quad (2.41)$$

where $\psi(\boldsymbol{\epsilon}, d)$ is given by equation (2.35). In the above, the vector \mathbf{r} denotes the crack propagation direction, ζ is a closed path around the crack tip, \mathbb{I} is the second-order identity tensor, \mathbf{n} is the normal to the closed path ζ and $\boldsymbol{\omega} = \partial \psi / \partial \nabla d = (G_c \ell / c_0) \nabla d$. Compared to the original form of the J-Integral proposed by Rice [92, 93], this expression contains additional terms to account for the phase-field parameter d .

Importantly, Sicsic and Marigo [80] show that, under certain conditions, the standard form of the J-Integral widely employed for sharp cracks, viz.

$$J = \mathbf{r} \cdot \int_{\zeta} \left(\psi_e(\boldsymbol{\epsilon}, d) \mathbb{I} - \nabla \mathbf{u}^T \boldsymbol{\sigma} \right) \mathbf{n} ds, \quad (2.42)$$

can be used in a regularized phase-field setting. These conditions are:

H1 : The regularization length is sufficiently small, so that a separation of scales between the solution in the damage band and the outer solution can be achieved;

H2 : The path ζ intersects the crack plane at a ninety-degree angle;

H3 : The path ζ intersects the crack plane sufficiently far from the crack tip, so that the damage field only varies in a direction perpendicular to the crack plane.

In what follows, these same conditions are assumed, as they facilitate a simpler derivation of a modified J-Integral capable of retrieving the energy release rate even




FIGURE 2.3. (a) The contour paths ζ_{in} and ζ_{out} and subdomain Λ , in the vicinity of a regularized crack.; (b) Color contour plot indicating the assumed variation in the function q .

in the presence of pressure loads on the crack faces. The main result of this section can then be stated in the following way.

Claim: Consider a domain $\Omega \in \mathbb{R}^2$ with a straight phase-field crack and two closed, non-intersecting paths ζ_{in} and ζ_{out} around the crack tip, enclosing an area Λ as shown in Figure 2.3a. Let $q(x)$ be a sufficiently smooth function satisfying $q = 1$ on ζ_{in} and $q = 0$ on ζ_{out} . Further, assume that $q = 1$ for all points inside ζ_{in} and $q = 0$ for all points outside ζ_{out} , as shown in Figure 2.3b. Finally, assume that the fracture is loaded by a constant pressure p , and that one of the formulations described in Section 2.2 holds. Then, if conditions **H1**, **H2** and **H3** hold for ζ_{in} and ζ_{out} , the energy release rate can be approximated by the integral

$$J = \mathbf{r} \cdot \int_{\Lambda} \left(\psi_e(\boldsymbol{\epsilon}, d)\mathbb{I} - p\nabla d \cdot \mathbf{u} I'(d)\mathbb{I} - \nabla \mathbf{u}^T \boldsymbol{\sigma} \right) \cdot \nabla q \, dA, \quad (2.43)$$

with an error that vanishes as $\ell \rightarrow 0$. The proof can be established in three steps, as detailed below.

Proof: Define $\mathbf{T}_p = \psi_e(\boldsymbol{\epsilon}, d)\mathbb{I} - p\nabla d \cdot \mathbf{u} I'(d)\mathbb{I} - \nabla \mathbf{u}^T \boldsymbol{\sigma}$. Using the divergence theorem,

one can show that

$$\int_{\Lambda} \nabla \cdot (q \mathbf{T}_p) dA = \int_{\zeta_{in} \cup \zeta_{out}} q \mathbf{T}_p \cdot \mathbf{n} ds = 0 - \int_{\zeta_{in}} \mathbf{T}_p \cdot \mathbf{n} ds, \quad (2.44)$$

because q vanishes on ζ_{out} and the normal \mathbf{n} to ζ_{in} points inward to Λ , as shown in Figure 2.3a. Multiplying both sides by the crack direction \mathbf{r} and applying the chain rule yields

$$-\mathbf{r} \cdot \int_{\Lambda} \left(\mathbf{T}_p \cdot \nabla q + q \nabla \cdot \mathbf{T}_p \right) dA = \mathbf{r} \cdot \int_{\zeta_{in}} \mathbf{T}_p \cdot \mathbf{n} ds, \quad (2.45)$$

which completes the first step of the proof.

The second step consists of showing that the term $R = \mathbf{r} \cdot \int_{\Lambda} q \nabla \cdot \mathbf{T}_p dA$ is zero.

Expanding the expression for \mathbf{T}_p and using the chain rule yields

$$\begin{aligned} R &= \mathbf{r} \cdot \int_{\Lambda} q \nabla \cdot \left(\psi_e(\boldsymbol{\epsilon}, d) \mathbb{I} - p \nabla d \cdot \mathbf{u} I'(d) \mathbb{I} - \nabla \mathbf{u}^T \boldsymbol{\sigma} \right) dA \\ &= \int_{\Lambda} q \left(\frac{\partial \psi_e(\boldsymbol{\epsilon}, d)}{\partial \nabla^s \mathbf{u}} \cdot (\nabla (\nabla^s \mathbf{u}) \mathbf{r}) + \frac{\partial \psi_e(\boldsymbol{\epsilon}, d)}{\partial d} \nabla d \cdot \mathbf{r} - (\nabla \cdot \boldsymbol{\sigma}) \cdot (\nabla \mathbf{u} \mathbf{r}) \right. \\ &\quad \left. - \boldsymbol{\sigma} (\nabla (\nabla \mathbf{u}) \mathbf{r}) - p \nabla d \cdot (\nabla \mathbf{u} \mathbf{r}) I'(d) - p \mathbf{u} \nabla (I'(d) \nabla d) \mathbf{r} \right) dA. \end{aligned} \quad (2.46)$$

Re-arranging some terms, one can write,

$$\begin{aligned} R &= \int_{\Lambda} q \left[\left(\frac{\partial \psi_e(\boldsymbol{\epsilon}, d)}{\partial \nabla^s \mathbf{u}} - \boldsymbol{\sigma} \right) \cdot (\nabla (\nabla^s \mathbf{u}) \mathbf{r}) - \left(\nabla \cdot \boldsymbol{\sigma} - p I'(d) \nabla d \right) \cdot (\nabla \mathbf{u} \mathbf{r}) \right. \\ &\quad \left. + \frac{\partial \psi_e(\boldsymbol{\epsilon}, d)}{\partial d} \nabla d \cdot \mathbf{r} - p \mathbf{u} \nabla (I'(d) \nabla d) \mathbf{r} \right] dA. \end{aligned} \quad (2.47)$$

For any elastic material, the definition of stress implies $\frac{\partial \psi_e(\boldsymbol{\epsilon}, d)}{\partial \nabla^s \mathbf{u}} = \boldsymbol{\sigma}$, and due to equation (2.26), $\nabla \cdot \boldsymbol{\sigma} - p \nabla d = \mathbf{0}$, so, the expression above reduces to

$$R = \int_{\Lambda} q \left(\frac{\partial \psi_e(\boldsymbol{\epsilon}, d)}{\partial d} \nabla d \cdot \mathbf{r} - p \mathbf{u} \nabla (I'(d) \nabla d) \mathbf{r} \right) dA. \quad (2.48)$$

Assuming a separation of scales, the domain Λ can be separated into two regions: (i) Λ_{band} , which consists of the intersection between Λ and the support of the damage field representing the crack and (ii) Λ_{outer} , which denotes the remainder of Λ , outside of the damage band. In the asymptotic limit as $\ell \rightarrow 0$, the material in Λ_{outer} behaves as purely elastic. Within Λ_{outer} , one has $d \approx \nabla d \approx 0$, and therefore,

$$R_{outer} = \int_{\Lambda_{outer}} q \left(\frac{\partial \psi_e(\boldsymbol{\epsilon}, d)}{\partial d} \nabla d \cdot \mathbf{r} - p \mathbf{u} \nabla(I'(d) \nabla d) \mathbf{r} \right) dA \approx 0. \quad (2.49)$$

For the Λ_{band} region, by condition **H3**, ∇d is purely perpendicular to the crack direction, so, $\nabla d \cdot \mathbf{r} \approx 0$. Therefore,

$$R_{band} = \int_{\Lambda_{band}} q \left(\frac{\partial \psi_e(\boldsymbol{\epsilon}, d)}{\partial d} \nabla d \cdot \mathbf{r} - p \mathbf{u} \nabla(I'(d) \nabla d) \mathbf{r} \right) dA \approx 0. \quad (2.50)$$

Since $\Lambda = \Lambda_{band} \cup \Lambda_{outer}$, we must have

$$R = R_{outer} + R_{band} \approx 0. \quad (2.51)$$

This completes the second step.

The final step of the proof begins by invoking the separation of scales to decompose the contour integral in (2.45) via

$$\mathbf{r} \cdot \int_{\zeta_{in}} \mathbf{T}_p \cdot \mathbf{n} ds = \mathbf{r} \cdot \left(\int_{\zeta_{in}^{band}} \mathbf{T}_p \cdot \mathbf{n} ds + \int_{\zeta_{in}^{outer}} \mathbf{T}_p \cdot \mathbf{n} ds \right). \quad (2.52)$$

On the ζ_{in}^{outer} portion of the path, damage effects can be neglected and the integral simplifies to the standard (sharp) J-Integral. In the case of a uniformly pressurized crack [94], this gives

$$\int_{\zeta_{in}^{outer}} \mathbf{T}_p \cdot \mathbf{n} ds = G - pw, \quad (2.53)$$

where w denotes the crack aperture at the intersection of the crack and the contour ζ_{in} .

The other portion of the integral can be re-written as

$$\mathbf{r} \cdot \int_{\zeta_{in}^{band}} \mathbf{T}_p \cdot \mathbf{n} \, ds = \mathbf{r} \cdot \int_{-B}^B (\psi_e \mathbb{I} - \nabla \mathbf{u}^T \boldsymbol{\sigma}) \cdot \mathbf{n} dx - \mathbf{r} \cdot \int_{-B}^B p(\nabla d \cdot \mathbf{u} I'(d)) \cdot \mathbf{n} dx, \quad (2.54)$$

where B is the half-length of the damage band and condition **H2** is used to transform the integral over ζ_{in}^{band} to a simple real integral from $-B$ to B . Here, both \mathbf{r} and \mathbf{n} are unit vectors that point in opposite directions, and therefore, $\mathbf{r} \cdot \mathbf{n} = -1$, so,

$$\mathbf{r} \cdot \int_{\zeta_{in}^{band}} \mathbf{T}_p \cdot \mathbf{n} \, ds = \int_{-B}^B (\psi_e \mathbb{I} - \nabla \mathbf{u}^T \boldsymbol{\sigma}) dx + p \int_{-B}^B (\nabla d \cdot \mathbf{u} I'(d)) dx. \quad (2.55)$$

Following [1], the second integral on the right approaches the crack aperture w as the regularization length decreases, while the first integrand on the right is bounded [80], and therefore this term is $O(B)$, so,

$$\mathbf{r} \cdot \int_{\zeta_{in}^{band}} \mathbf{T}_p \cdot \mathbf{n} \, ds = O(B) + pw = O(\ell) + pw, \quad (2.56)$$

since the damage band half-length B scales with the regularization length ℓ . One can now go back to (2.52), and substitute (2.53) and (2.56) to obtain,

$$\mathbf{r} \cdot \int_{\zeta_{in}} \mathbf{T}_p \cdot \mathbf{n} \, ds = G + pw - pw + O(\ell). \quad (2.57)$$

Finally, combining (2.45), (2.51) and (2.57), one obtains

$$-\mathbf{r} \cdot \int_{\Lambda} \mathbf{T}_p \cdot \nabla q \, dA = G + O(\ell), \quad (2.58)$$

which concludes the proof.

2.4 Finite Element Implementation

In this Section, the details of the finite element discretization used to obtain approximations to the solution of the proposed model (UVC) are described. For analogous equations for the model (LVC), the reader is referred to [79]. First, the strong form of the governing equations, derived from the general free-energy (2.35) using the KKT[95, 96] conditions is presented.

Strong form

Linear momentum balance:

$$\nabla \cdot \boldsymbol{\sigma} - p \nabla d + \mathbf{b} = \mathbf{0}, \quad \forall x \in \Omega, \quad (2.59)$$

$$\boldsymbol{\sigma} = \frac{\partial \psi_e}{\partial \boldsymbol{\epsilon}}, \quad \forall x \in \Omega, \quad (2.60)$$

$$\boldsymbol{\sigma} \cdot \mathbf{n} = \mathbf{t}, \quad \partial_t \Omega, \quad (2.61)$$

$$\mathbf{u} = \mathbf{u}_g, \quad \partial_u \Omega, \quad (2.62)$$

Fracture evolution:

$$\dot{d} \left(\nabla \cdot \frac{2G_c \ell}{c_0} \nabla d - \frac{G_c}{c_0 \ell} \alpha'(d) - g'(d) \psi_e^+(\boldsymbol{\epsilon}) \right) = 0, \quad \forall x \in \Omega, \quad (2.63)$$

$$\nabla \cdot \frac{2G_c \ell}{c_0} \nabla d - \frac{G_c}{c_0 \ell} \alpha'(d) - g'(d) \psi_e^+(\boldsymbol{\epsilon}) \leq 0, \quad \forall x \in \Omega, \quad (2.64)$$

$$\dot{d} \geq 0, \quad \forall x \in \Omega, \quad (2.65)$$

$$\nabla d \cdot \mathbf{n} = 0, \quad \partial \Omega, \quad (2.66)$$

$$d(0, \mathbf{x}) = d_0, \quad \Omega. \quad (2.67)$$

For the derivation of an equivalent weak form, trial spaces for \mathbf{u} and d are first defined. Although the derivation is confined to quasi-static loadings, the spaces are indexed by a discrete load step parameter t . The trial spaces are given by

$$\mathcal{U}_t = \{\mathbf{u} \in \mathcal{H}^1(\Omega)^d \mid \mathbf{u} = \bar{\mathbf{u}}_t \text{ on } \partial_u \Omega\}, \quad (2.68)$$

$$\mathcal{D}_t = \{d \in \mathcal{H}^1(\Omega) \mid d_{t-1}(x) \leq d_t(x) \leq 1, \forall x \in \Omega\}, \quad (2.69)$$

and the accompanying weighting spaces \mathcal{V} and \mathcal{C} are

$$\mathcal{V} = \{\mathbf{w} \in \mathcal{H}^1(\Omega)^d \mid \mathbf{w} = \mathbf{0} \text{ on } \partial_u \Omega\}, \quad (2.70)$$

$$\mathcal{C} = \{c \in \mathcal{H}^1(\Omega) \mid c(x) \geq 0, \forall x \in \Omega\}. \quad (2.71)$$

The condition of monotonicity in the space \mathcal{D}_t is used to prevent damage healing and is the weak enforcement of the condition $\dot{d} \geq 0$, in a time discrete setting. Denoting the inner product in $\mathcal{H}^1(\Omega)$ and $\mathcal{H}^1(\Omega)^d$ by (\cdot, \cdot) and its restriction in the boundary by $\langle \cdot, \cdot \rangle$, the weak form of the problem can be written as

Weak form

Find $\mathbf{u} \in \mathcal{U}_t$ and $d \in \mathcal{D}_t$, such that $\forall \mathbf{w} \in \mathcal{V}$ and $\forall c \in \mathcal{C}$,

$$(\nabla \mathbf{w}, \boldsymbol{\sigma}) - (\mathbf{w}, p \nabla d) - (\mathbf{w}, \mathbf{b}) - \langle \mathbf{w}, \mathbf{t} \rangle_{\partial_t \Omega} = 0, \quad (2.72)$$

$$\frac{2\ell}{c_0} (\nabla c, G_c \nabla d) + \frac{1}{c_0 \ell} (c, G_c \alpha'(d)) + (c, g'(d) \psi_e^+(\boldsymbol{\epsilon}(\mathbf{u}))) = 0, \quad (2.73)$$

with the initial damage condition,

$$(c, d(0, \mathbf{x}) - d_0) = 0. \quad (2.74)$$

Observe that (2.73) is an equality rather than an inequality, such as (2.64). This reflects a view ahead, toward discretization, where in the present work the irreversibility constraint is enforced with an active-set strategy. The active set strategy effectively partitions the domain into active (where $\dot{d} = 0$) and inactive (where $\dot{d} > 0$) parts. Only the inactive part requires a discretization of the damage condition (2.64), where it is indeed treated as an equality. A detailed description of this constrained optimization algorithm is given by Heister et al. in [60], and some additional details pertinent to phase-field for fracture discretizations can be found in Hu et al. [97].

Finally, these function spaces can be discretized over a finite element mesh, that give rise to the discrete function spaces $\mathcal{U}_t^h \subset \mathcal{U}_t$, $\mathcal{V}^h \subset \mathcal{V}$, $\mathcal{D}_t^h \subset \mathcal{D}_t$, $\mathcal{C}^h \subset \mathcal{C}$. These are then used to construct the discrete form of the problem using the Galerkin method:

Spatially discretized form

Find $\mathbf{u}^h \in \mathcal{U}_t^h$ and $d^h \in \mathcal{D}_t^h$, such that $\forall \mathbf{w}^h \in \mathcal{V}^h$ and $\forall q^h \in \mathcal{C}^h$,

$$(\nabla \mathbf{w}^h, \boldsymbol{\sigma}^h) - (\mathbf{w}^h, p \nabla d^h) - (\mathbf{w}^h, \mathbf{b}) - \langle \mathbf{w}^h, \mathbf{t} \rangle_{\partial_t \Omega} = 0, \quad (2.75a)$$

$$\frac{2\ell}{c_0} (\nabla c^h, G_c \nabla d^h) + \frac{1}{c_0 \ell} (c^h, G_c \alpha'(d^h)) + (c^h, g'(d^h) \psi_e^+(\boldsymbol{\epsilon}(\mathbf{u}^h))) = 0, \quad (2.75b)$$

with the initial damage condition,

$$(c^h, d^h(0, \mathbf{x}) - d_0) = 0. \quad (2.76a)$$

In this work, bilinear finite elements are used to approximate the damage and displacement fields.

The coupling between the two discrete equations (2.75a) and (2.75b) is handled by an alternating minimization scheme. A detailed description of this scheme is given in [97]. This solution scheme is implemented using RACCOON [98], a parallel finite element code specializing in phase-field fracture problems. RACCOON is built upon the MOOSE framework [99, 100] developed and maintained by Idaho National Laboratory.

2.5 Results

We now present results for a set of problems that highlight the advantages, as well as some limitations, of the various models for pressurized cracks in a phase-field for fracture setting. In the first problem, the cohesive fracture of an uniaxial specimen in a pressurized environment is analyzed. We then consider the problem of crack nucleation from a pressurized hole in a medium subjected to far-field, biaxial com-

pression. Finally, a crack propagation example is studied to verify that in the limit of a vanishing regularization length Griffith-like behavior is recovered with the new model. In all cases, plane-strain conditions are assumed to hold.

In the course of explaining the results obtained with the cohesive phase-field model, it will be useful to characterize the effective cohesive strength σ_c of the material. To that end we will rely on the following relationship between the cohesive strength and the nucleation energy:

$$\sigma_c = \sqrt{\frac{2E\psi_c}{(1-\nu^2)}}, \quad (2.77)$$

where E denotes Young's modulus and ν Poisson's ratio. This equation results from the analysis of a one-dimensional system subjected to uniaxial loading [75], and should be viewed as an approximation to the cohesive strength in more general loading conditions.

2.5.1 Uniaxial bar under traction in a pressurized environment

We consider the fracture behavior of a cohesive material with pressure loading on the crack faces. The example is intended to examine the extent to which the pressure loading can artificially influence the apparent traction-separation law on the crack surface.




FIGURE 2.4. Uniaxial cohesive bar.

The problem consists of a bar under a displacement controlled load in a pressurized chamber, as shown in Figure 2.4. The bar is assumed to be made of a

Table 2.1. Material properties for uniaxial bar

	Value	Unit
Young's modulus (E)	4.0×10^5	MPa
Poisson's ratio (ν)	0.2	—
Nucleation energy (ψ_c)	5.6×10^{-5}	mJ mm^{-3}
Critical fracture energy (G_c)	0.12	mJ mm^{-2}
Residual stiffness (ξ)	1.0×10^{-8}	—

linear elastic material that undergoes cohesive fracture, with a traction-separation law $F(s)$. The bar has an undeformed length $2L = 400$ mm and width $2W = 2$ mm. The material properties are given in Table 2.1. Symmetry boundary conditions are invoked to reduce the computational domain to the top-right quarter of the bar. The applied load is modeled as a displacement boundary condition on the right end of the domain. The mesh consists of rectangular elements of size h along the length direction and size 1 mm in the width direction. The initial applied displacement increment is $\Delta u = 5 \times 10^{-4}$ mm. The displacement increment is adaptively refined when convergence is not obtained within a fixed set of iterations. A more detailed description of the adaptive stepping procedure is provided in [99, 100, 101].

Damage localization is triggered by introducing a small initial defect ($d = \mathcal{O}(\epsilon)$) on the left side of the domain. In what follows, results are reported using $\ell = L/20 = 10$ mm and $h = \ell/10 = 1$ mm. This choice of regularization length and mesh spacing was found to yield spatially-converged results. Different values of pressure, ranging from 0 to $\sigma_c/3$ are considered.

The problem is simulated using discretized versions of both the UVC and (LVC) formulations. For the indicator function $I(d)$, results are reported for: (1) $I(d) = d$, used for example in [1]; (2) $I(d) = d^2$, used in [79] and (3) $I(d) = 2d - d^2$, used in [50]. The effective traction-separation laws extracted from the set of simulations are shown in Figure 2.5. To generate these curves, the traction is computed as the internal force measured in the center of the bar. The separation s is the opening of

the crack, calculated as $s = - \int_{-\infty}^{\infty} \mathbf{u} \cdot \nabla I(d) dx$ [1].




FIGURE 2.5. Traction-separation curves for pressurized uniaxial cohesive bar problem, obtained with various phase-field models: (a) (LVC) with linear indicator function; (b) (LVC) with quadratic indicator function; (c) (LVC) with $2d - d^2$ indicator function; and (d) Proposed approach (UVC) with linear indicator function.

The results for the various models are shown in Figure 2.5, with tractions and pressures normalized by the critical stress σ_c from (2.77). As shown in Figure 2.5, the proposed model (UVC) exhibits minimal sensitivity to the pressure magnitude in the traction-separation behavior. By contrast, with the (LVC) formulation, only the case with $I(d) = 2d - d^2$ exhibits comparable results. In the other two cases (Figures

2.5a and 2.5b), the apparent traction-separation law shows a spurious dependence to the applied pressure. This is evident in the variations in the results as well as the presence of jumps in the aperture at sufficiently high pressures. The latter occur due to an instability of the partially damaged solutions as d approaches 1. More precisely, shortly after the damage at the center of the bar reaches $d \approx 0.8$, it jumps to $d = 1$, which in turns lead to a jump in the aperture. This jump is indicated via the squares that appear on selected curves in Figures 2.5a and 2.5b. The use of smaller displacement increments was not observed to significantly impact these results. By contrast, such instabilities were not observed for the simulations reported in Figures 2.5c and 2.5d.

2.5.2 Crack nucleation from a pressurized hole

Consider a square plate of dimensions $L \times L$, with a circular hole in the center subjected to an internal pressure p , as shown in Figure 2.6a. This problem is motivated by oil and gas wellbore systems. Far field stresses σ_V and σ_H are applied as tractions on the boundaries as shown. The pressure is increased until it reaches a “break-down pressure” p_b . When that happens, cracks initiate in the direction parallel to the maximum *in-situ* stress. Assuming $\sigma_H > \sigma_V$, this is expected to occur along a horizontal axis passing through the center of the hole. In this work, the pressure in the hole is assumed to follow the crack faces as the fracture grows into the interior of the domain.

The material properties selected for this problem, along with the dimensions and loading parameters are listed in Table 2.2. The material properties are taken to be representative of a Bebertal sandstone, as inspired by the experiments of [102]. The symmetry of the problem is exploited to reduce the computational domain to the top-left quarter. An unstructured triangular mesh is used, with local refinement along the x -axis, as shown in Figure 2.6b. The element size in the refined area is 10mm,




FIGURE 2.6. (a) Problem schematic; (b) Mesh used in the computations, exploiting symmetry.

Table 2.2. Material properties, geometric parameters and applied loads for crack initiation problem

	Value	Unit
Young's modulus (E)	19.0×10^3	MPa
Poisson's ratio (ν)	0.2	—
Nucleation energy (ψ_c)	7.96×10^{-4}	mJ mm^{-3}
Critical fracture energy (G_c)	7.70×10^{-2}	mJ mm^{-2}
Cavity radius (R)	400	mm
Specimen length (L)	5.0×10^3	mm
Horizontal stress (σ_H)	5.0	MPa
Vertical stress (σ_V)	2.5	MPa

whereas the phase-field regularization length is $\ell = 40\text{mm}$. For the results reported in this section, the phase-field model employs the cohesive formulation[74, 75] using the degradation function (2.40) and the spectral split of [86].

Intuitively, the magnitude of the pressure load required to initiate fracture in this problem is expected to be independent of whether or not the pressure follows the crack evolution. After initiation, the pressure effects become important and the fracture propagates unstably. Due to this unstable behavior, it is very difficult to numerically capture the crack path after the pressure p_b is reached. In order to have a glimpse into what this path looks like, a viscous term $\eta \dot{d}$ is added to the phase-field

equation, as in [86], with $\eta = 10^{-3} \text{ mJ} \cdot \text{mm}^{-3} \cdot \text{s}$.

It bears emphasis that the equations (2.9) and (2.11) indicate that, in the absence of any damage, the proposed model for pressurized cracks reduces to the standard phase-field fracture model for traction-free cracks. Therefore, one should expect the proposed model to capture fracture initiation properly in this scenario. On the other hand, for the (LVC) formulation, this only occurs if the indicator function satisfies $I'(0) = 0$. Among the many works which use the (LVC) formulation, only a few such as [79, 78] used an indicator function satisfying this condition. In [79], the authors were indeed able to predict fracture initiation from pressurized holes. To highlight the implications of having $I'(0) \neq 0$ in the model (LVC), the results for this problem will also be presented using the (LVC) formulation with the indicator function $I(d) = d$.

The final damage patterns obtained using the (UVC) formulation and the (LVC) formulation are shown in Figure 2.7. With the (UVC) formulation, damage localizes along the midplane when the hoop stress is approximately 85% of σ_c . This is not unexpected, as the expression (2.77) is based on a one-dimensional state of stress and strain which differs significantly from the state near the corner of the hole. The same comparison is not performed for the simulation using the model (LVC), since damage forms only on the boundary in the first steps leading to spurious rigid body motion.

The main takeaway is that the proposed model (UVC) allows one to study crack nucleation and subsequent propagation under a pressure load, whereas formulation (LVC) leads to spurious damage formation if $I'(0) \neq 0$. The presence of the term $p\nabla \cdot \mathbf{u}I'(d)$ in the damage equation (2.19) drives crack formation in areas which are not stressed. For this specific problem, this issue can be circumvented using for example $I(d) = d^2$, as shown in [79], but this option introduces a spurious dependence of the cohesive response of the material on the applied pressure, as indicated in the




FIGURE 2.7. (a) Final crack pattern using proposed model; (b) Damage field using the model from [1].

last section (Figure 2.5b).

2.5.3 Stable propagation of a pre-existing crack

Consider a strip of material with a pressurized crack, as shown in Figure 2.8a. The rectangular strip has a width W , height H and a crack with initial size a (values provided in Table 2.3), and is loaded by the “surfing” boundary condition $\widetilde{U}_y(x, y, t)$ on its top and bottom surfaces [82]. The boundary condition is given by

$$\widetilde{U}_y(x, y, t) = U_y(x - Vt, y), \quad (2.78)$$

where

$$U_y(x, y) = \hat{U}_y(r, \theta) = \frac{\sqrt{G_c E'}}{2\mu} \sqrt{\frac{r}{2\pi}} (\kappa - \cos \theta) \sin \frac{\theta}{2}, \quad (2.79)$$

and where r and θ are polar coordinates with respect to the origin, taken to be the midpoint of the left edge of the domain. The constant $V > 0$ is the target crack speed, prescribed by moving the boundary condition following (2.78). The Kolosov constant is defined as $\kappa = 3 - 4\nu$ in plane strain and the shear modulus $\mu = E/(2 + 2\nu)$. The pressure p applied to the crack faces as the crack evolves is

given by

$$p = \frac{1}{2} \sqrt{\frac{G_c E'}{\pi a}}, \quad (2.80)$$

in which a denotes the initial crack length. This value corresponds to half the critical pressure for an infinite plate with a pressurized crack of size a . This magnitude ensures that the applied pressure is considerably large, but not so large as to drive the problem beyond the stable propagation regime.

To calculate the energy release rate, the domain form of the J-Integral (2.43) developed in Section 2.3 is used. The function q is constructed by taking advantage of the finite element interpolation. In essence, the domain for the J-Integral is taken to be a single rectangular region of dimensions $a \times H/2$, centered on the initial crack tip. The value of q for all nodes outside of this region is set to 0, while $q = 1$ for all nodes inside. Using the finite element interpolation, this gives rise to a q function whose value changes continuously from 0 to 1 on the elements cut by the rectangular path. This function is illustrated in Figure 2.8b².




FIGURE 2.8. (a) Geometry and boundary conditions for pressurized crack propagation problem; (b) J-Integral domain function q .

² Due to mesh refinement near the crack surface, the width of the band where $0 < q < 1$ diminishes near the horizontal centerline of the domain.

Table 2.3. Parameters used for pressurized crack propagation problem

	Value	Unit
Young's modulus (E)	3.0×10^4	MPa
Poisson's ratio (ν)	0.2	—
Critical fracture energy (G_c)	0.12	mJ mm^{-2}
Initial crack length (a)	1.6	m
Specimen width (W)	8.0	m
Specimen height (H)	4.0	m
Target crack speed (V)	0.4	m/s

In order to verify that Griffith's law is approached as $\ell \rightarrow 0$, simulations are performed for this problem using a sequence of decreasing regularization lengths, ranging from $\ell = a/20$ to $\ell = a/160$. The mesh is locally refined along the x -axis, where the element size is set to $h = \ell/4$. The symmetry of the problem is exploited and only the response in the top half of the domain is simulated. In terms of constitutive choices of the phase-field model, the AT-1 formulation is employed without any decomposition of the strain. As in the previous examples, this problem is analyzed using the formulations (LVC) and (UVC), and the following choices of indicator function $I(d)$:

- $I(d) = d$
- $I(d) = d^2$
- $I(d) = 2d - d^2$

To evaluate how well the models approach Griffith's law, the ratio between the energy release rate measured by the J-Integral and the effective critical fracture energy $G_c^{eff} = (1 + 2h/c_0\ell)G_c$ ³ is plotted in Figures 2.9 and 2.10. In all figures, the time is scaled by a characteristic time τ , defined as $\tau = a/V$. The results

³ in fact, phase-field cracks actually dissipated a slightly larger energy per unit length in numerical models. A correction factor of $\left(1 + \frac{2h}{c_0\ell}\right)$ is then applied to G_c , following [59]. The factor of 2 here comes from the symmetry boundary condition employed.

using the traditional (LVC) formulation are presented in Figure 2.9. They indicate convergence towards $J/G_c^{eff} = 1$ as the regularization length is reduced, especially when the indicator function $I(d) = d$ is used. This is expected given the results obtained in [1]. Nevertheless, these results serve to verify the implementation of the J-Integral presented in Section 2.3. They also provide an estimate for how small the regularization length has to be in order to achieve a certain level of accuracy with these types of phase-field models.




FIGURE 2.9. Reference results with the LVC formulation. Curves with $\ell = a/160$ are not shown, as they are almost identical to the ones with $\ell = a/80$. (a) $I(d) = d$; (b) $I(d) = d^2$; (c) $I(d) = 2d - d^2$




FIGURE 2.10. Results with the proposed formulation (UVC) (a) $I(d) = d$; (b) $I(d) = d^2$; (c) $I(d) = 2d - d^2$

For the case of proposed formulation (UVC), the results shown in Figure 2.10 indicate a slower convergence towards a $J/G_c^{eff} = 1$ response. In contrast with




FIGURE 2.11. Convergence of the proposed formulation with $I(d) = d$.

ℓ/a	Error	$\text{Error}_{k+1}/\text{Error}_k$
1/40	0.067	—
1/80	0.052	0.78
1/160	0.040	0.77
1/320	0.031	0.77

Table 2.4. Absolute error in J vs. G_c^{eff} for the pressurized crack propagation problem, as a function of regularization length.

the (LVC) formulation, the curves converge from above, and therefore, the fracture toughness is slightly overestimated when larger regularization lengths are used. Nevertheless, they all seem to approach a Griffith-like response in the limit $\ell \rightarrow 0$. In Figure 2.11, an even finer result, using (UVC) with $I(d) = d$ and $\ell = a/320$ is added, to ensure that the convergence rates indicated in Figure 2.10 persist. In Table 2.4, the relative errors are provided, indicating a convergence rate of approximately 0.4 with respect to ℓ .

One potential explanation for the slower convergence rate is related to the different assumptions regarding the trial cracks, as discussed in Section 2.2. Although the different assumptions converge to the same propagation rule in the limit of an

infinitesimal crack increment, in the discretized case, the minimal crack increment is finite and related to the mesh spacing h and regularization length ℓ . In this case, a slightly different propagation behavior, resulting in slower convergence rates towards $J/G_c^{eff} = 1$ is not surprising.

3

A Multi-Resolution Approach for Hydraulic Fracture Simulation

3.1 Introduction

A wide range of approaches for model-based simulations of hydraulic fracturing have been developed over the past several decades [3, 64]. These range from production-level reservoir modeling tools such as ResFrac[29, 30], to GEOS[35, 36, 37], PyFrac[38], and others. Many of the models and associated codes assume fracture networks that remain planar, but in recent years strides have been made towards modeling cracks that evolve in arbitrary ways in response to fluid-driven loads. High-resolution models for complex fracture evolution generally fall into two categories: sharp interface models that explicitly model the fracture surface, and diffuse crack approaches that effectively smear the geometry over the underlying grid or mesh. Techniques that represent the crack as a sharp interface can be advantageous when the fracture configuration is relatively simple, but representing complex geometric evolution can be challenging [39, 40, 103]. By contrast, diffuse crack models offer more flexibility for representing complex fracture evolution, but introduce other challenges such as the

lack of a well-defined fracture surface and increased computational expense[49]. In this work, we introduce a multi-resolution scheme for hydraulic fracturing simulation that makes use of both sharp and diffuse crack representations within a single framework. The objective is to establish a methodology that makes use of the advantageous aspects of both sharp and diffuse crack models while circumventing some of the drawbacks.

Over the past several decades, the phase-field model for fracture [45, 46, 47] has emerged as a promising approach for constructing robust simulations of complex crack evolution. The method has shown considerable success for simulating fracture evolution in quasi-brittle materials, and there have been several recent efforts to extend the approach to hydraulic fracturing. In what follows, we review some prior works of particular relevance to the current manuscript. For additional references in this topic, we refer the reader to the recent review by Heider [49].

The first attempts towards a phase-field model for hydraulic fracture began with extensions of the traditional phase-field model to pressurized cracks, as in Bourdin et al. [1] and Wheeler et al. [50]. Subsequently, fluid flow in the fractures, and also poromechanics were considered. Miehe et al. [51, 52] developed a thermodynamically consistent framework, from minimization principles, to couple poromechanics, fluid-flow and phase-field fracture. The flow problem was modeled via the Darcy's equation, containing a permeability coefficient that used the phase-field variable and the crack opening to mimic the cubic relationship from the lubrication theory in the crack region. Mikelic et al. [53, 54] developed a model that separated the domain into fracture and reservoir, by using the phase-field variable as an indicator function. They also considered the flow inside the fracture as a Darcy flow, but their model treated the fracture as a three-dimensional entity, which led to a different permeability tensor compared to [51, 52]. Yet another approach concerns the work of Wilson and Landis [55], who proposed a model that included fluid velocities as

primary variables. This allowed for a more detailed description of the flow within the fracture, which was modeled by a Brinkman-type equation [56]. The phase-field parameter acted as an indicator of the flow regime, between Darcy flow (away from cracks) and Stokes flow (inside cracks). Finally, the recent work of Chukwudzie et al. [57] presented a different model, wherein the lubrication theory equations were included in the weak form by means of a Γ -convergent regularization.

The use of a phase-field to represent a fracture network in a diffuse manner certainly facilitates the representation of complex geometric evolution, including crack branching and merging. However, it also requires the use of meshes or grids that are capable of resolving the regularization length, making these approaches computationally expensive. One approach to improving the efficiency of the method is the use of adaptive mesh refinement, such as in [60, 61, 62, 63]. In the specific case of hydraulic fracturing, another challenge concerns the crack opening or aperture, a field that is tightly coupled with the fluid pressure within fractures. In a phase-field setting, due to the lack of an explicit crack surface, extracting the aperture or accounting for its effects requires additional considerations. All of the aforementioned works present some way to account for the aperture within a diffuse setting, but the robustness of these approaches remains unclear [64]. For a review of the most frequently used methods to calculate the crack aperture from phase-field simulations, see the recent work of Yoshioka et al. [59].

Outside of the context of hydraulic fracturing, some researchers in the phase-field community have developed “hybrid” approaches, wherein the phase-field formulation was combined with a sharp crack representation. The motivation for these approaches varies, from “cutting” the mesh to remove artificial traction transmission and circumvent element distortion [65] to reducing the overall computational cost [66, 67]. In the work of Giovanardi et al. [66], phase-field subproblems in the vicinity of crack tips were used to propagate a global, discrete crack. The eXtended

Finite Element Method (XFEM)[69] was used to place fracture discontinuities in the displacement field within the background global mesh. More recently, Muixi et al. [67] created an approach that uses the phase-field method only at the crack tips, and XFEM in the rest of the domain. In contrast to [66], there is no overlap of the representations in crack tip areas.

The success of these hybrid approaches for purely mechanical cases opens the door for their extension to hydraulic fracturing. Such approaches are appealing because in principle they can circumvent the need for a complicated reconstruction of the crack opening from the phase-field. This area is relatively unexplored, although there have been some recent efforts that are similar in spirit, such as the recent work of Sun et al. [70]. They developed a Finite Element-Meshfree method to represent the crack surfaces in a discrete fashion. The computed displacement field was used to obtain a driving force which was employed within a phase-field evolution equation near the crack tips. This approach eliminated the need for the reconstruction of crack openings from the diffuse crack representation, but it also largely decoupled the phase field from the equations governing the force balance near the crack tips.

The approach presented in this work, which we refer to as a multi-resolution method, extends the concept of a hybrid phase-field method to hydraulic fracturing. It discretizes the problem at a global level using a sharp interface approach based on the Embedded Finite Element Method of Cusini et al. [104]. It then approaches the simulation of fracture evolution by coupling the global fields with a phase-field fracture problem posed over a subdomain in the vicinity of the crack front. This approach has several advantages. The crack aperture and flow inside the fracture are handled at the global scale using techniques that work well and are efficient when the crack geometry is known. Then the phase-field model is employed in the subdomain to effectively update the crack geometry. This framework lends itself to incorporation with a wide range of existing hydraulic fracturing solvers, as the

phase-field sub-problem is agnostic about the type of numerical treatment used in the global domain. In the current work, we adopt relatively simple assumptions regarding material behavior, such as small deformations and linear poroelasticity, as they allow us to verify our scheme against analytical solutions. However, in principle the approach could be extended to model crack growth in a much broader class of poroelastic materials, such as hydrogels [105].

The paper is structured as follows. In Section 3.2, we present the governing equations and constitutive assumptions for both hydraulic fracturing and phase-field for fracture. In Section 3.3, we propose our multi-resolution framework and present numerical schemes to discretize both the hydrofracture and the phase-field subproblems. In Section 3.4, we apply our method to study hydraulic fracturing in some simple scenarios, in order to verify its accuracy. These include the well-known KGD[18, 17] problems and a case of non-planar fracture propagation around a stiff inclusion. Finally, in Section 5, we provide a summary and some concluding remarks.

3.2 Model formulation

In this section, we describe the models that are used to develop our multi-resolution scheme. We start by presenting the governing equations to model hydraulic fracture in poroelastic rock that forms the basis for the solver at the global scale. We then describe a phase-field model for fracture that forms the basis for the solver used in local subdomains near the crack tips.

3.2.1 Governing equations for hydraulic fracture

We consider a model that couples flow and elastic deformation in a porous media with evolving fracture surfaces. Consider the domain Ω consisting of a porous rock, that is fully saturated with a single-phase Newtonian fluid. The external boundary is composed of both traction $\partial\Omega_t$ and displacement $\partial\Omega_u$ surfaces, viz. $\partial\Omega = \partial\Omega_t \cup \partial\Omega_u$.




FIGURE 3.1. Schematic of a poroelastic rock with a fracture, inspired by [2].

The domain contains fractures Γ , as shown in Figure 3.1. For simplicity, we assume quasi-static conditions and small-strain kinematics. Neglecting inertial effects, the balance of linear momentum reads

$$\nabla \cdot \boldsymbol{\sigma} + \mathbf{b} = \mathbf{0} \text{ on } \Omega \setminus \Gamma, \quad (3.1)$$

where $\boldsymbol{\sigma}$ denotes the total Cauchy stress and \mathbf{b} the body force. The mechanical boundary conditions are given by

$$\boldsymbol{\sigma} \cdot \mathbf{n} = \mathbf{t} \text{ on } \partial\Omega_t, \quad (3.2)$$

$$\mathbf{u} = \bar{\mathbf{u}} \text{ on } \partial\Omega_u, \quad (3.3)$$

where \mathbf{n} denotes the normal direction at any point on $\partial\Omega$, \mathbf{t} are the applied tractions, and $\bar{\mathbf{u}}$ denotes the prescribed displacements.

Fluid flow within the cracks gives rise to pressure loads on the crack surfaces,

translating into the boundary condition

$$\boldsymbol{\sigma}^+ \cdot \mathbf{n}_\Gamma = -\boldsymbol{\sigma}^- \cdot \mathbf{n}_\Gamma = -p_f \mathbf{n}_\Gamma \text{ on } \Gamma, \quad (3.4)$$

where p_f is the pressure inside the crack and \mathbf{n}_Γ is the normal vector to Γ at any point. In this work, we assume that fractures are open and neglect contact conditions on crack faces. For additional considerations to account for closed fractures, see the model described in Cusini et al.[104].

In terms of the fluid flow, the fluid velocity \mathbf{v}_m in the matrix is governed by the mass balance

$$\frac{\partial(\rho\phi)}{\partial t} + \nabla \cdot (\rho\mathbf{v}_m) = Q_m + Q_{mf} \text{ on } \Omega \setminus \Gamma. \quad (3.5)$$

where ρ denotes the fluid density and ϕ is the porosity, and Q_m is a prescribed source term in the matrix. The source term Q_{mf} accounts for the exchange of fluid between the matrix and the fractures. The boundary is partitioned into pressure $\partial\Omega_p$ and flux $\partial\Omega_q$ portions, such that $\partial\Omega = \partial\Omega_p \cup \partial\Omega_q$, and the following boundary conditions are applied,

$$\rho\mathbf{v}_m \cdot \mathbf{n} = \mathbf{q} \text{ on } \partial\Omega_q, \quad (3.6)$$

$$p_m = \bar{p}_m \text{ on } \partial\Omega_p, \quad (3.7)$$

where p_m denotes the pore-pressure and \bar{p}_m is a prescribed pressure.

In a comparable manner, the fluid velocity \mathbf{v}_f within fractures is governed by the mass balance

$$\frac{\partial(\rho w)}{\partial t} + \nabla_\Gamma \cdot (\rho w \mathbf{v}_f) = Q_f + Q_{fm} \text{ on } \Gamma, \quad (3.8)$$

where w denotes the normal fracture aperture, Q_f is a prescribed source term within the fracture, and Q_{fm} accounts for the exchange of fluid between the fracture and

the matrix¹. In the above, ∇_Γ indicates a gradient operator taken on the lower dimensional manifold Γ . Boundary conditions similar to (3.6) and (3.7) can also be applied.

Constitutive relationships are required to close the system and tie the stresses to the displacements \mathbf{u} and the fluid velocities to the pressures. In particular, we adopt the basic assumptions of Biot's theory of poroelasticity [106], Darcy's law for the flow in the matrix, and a lubrication theory approximation for the flow in fractures. This gives rise to the following set of constitutive relationships for the stress, porosity, and velocities:

$$\boldsymbol{\sigma} = \mathbb{C} : \boldsymbol{\epsilon}(\mathbf{u}) - \alpha p_m \mathbb{I} \text{ on } \Omega \setminus \Gamma, \quad (3.9)$$

$$\dot{\phi} = \alpha \nabla \cdot \dot{\mathbf{u}} + \frac{\dot{p}_m}{N} \text{ on } \Omega \setminus \Gamma, \quad (3.10)$$

$$\mathbf{v}_m = -\frac{\kappa}{\mu} \nabla p_m \text{ on } \Omega \setminus \Gamma, \quad (3.11)$$

$$\mathbf{v}_f = -\frac{w^2}{12\mu} \nabla_\Gamma p_f \text{ on } \Gamma. \quad (3.12)$$

In the above, p_m is the pore-pressure, \mathbb{C} is the fourth-order isotropic tensor of drained elastic moduli, $\boldsymbol{\epsilon}(\mathbf{u})$ is the mechanical strain, α is the Biot coefficient, and \mathbb{I} is the second-order identity tensor. The temporal evolution of the porosity is governed by the rate of dilatation and time rate of change in the pore pressure, as modulated by the modulus N . The fluid velocity in the matrix is related to the gradient of the pressure through the ratio of the intrinsic permeability κ to the viscosity μ .

¹ the flux interactions Q_{fm} and Q_{mf} are modeled as in classical well models, following [44]. This ensures the balance of mass between the fractures and matrix $\int_V Q_{mf} dV = - \int_\Gamma Q_{fm} d\Gamma$.

The fluid is assumed to be linearly compressible. For both the fluid in the fractures and the matrix, this implies that the density is updated from its reference value ρ_{ref} based on the change in pressure according to

$$\rho = \rho_{ref} \left(1 + \frac{p - p_{ref}}{K_F} \right) \text{ on } \Omega, \quad (3.13)$$

where p_{ref} denotes a reference value for the pressure, and K_F is the fluid bulk modulus.

Finally, the initial conditions for the displacements and pressures are given by

$$\mathbf{u}(\mathbf{x}, 0) = \mathbf{u}^0 \text{ on } \Omega \setminus \Gamma, \quad (3.14)$$

$$p_m(\mathbf{x}, 0) = p_m^0 \text{ on } \Omega \setminus \Gamma, \quad (3.15)$$

$$p_f(\mathbf{x}, 0) = p_f^0 \text{ on } \Gamma. \quad (3.16)$$

For a given crack geometry, the combination of equations (3.1), (3.5) and (3.8), with constitutive assumptions (3.9) - (3.13), boundary conditions (3.2)-(3.4),(3.6),(3.7) and initial conditions (3.14)-(3.16) leads to a system of equations whose solution can be approximated by many different numerical methods. What remains is a model to describe the evolution of the crack geometry.

In the context of standard sharp interface approaches for hydraulic fracture, the evolution of the crack geometry is typically governed by a set of criteria that dictate whether or not a crack front extends and, if so, in what orientation. For crack extension, a standard approach is to adopt Griffith's criteria [48], which states that crack propagation should occur when the energy release rate G reaches the critical value G_c for the material, i.e. $G \leq G_c$. In terms of changes to orientation, several

different criteria are typically employed, such as the maximum hoop stress criteria [107, 108, 109] or the maximum energy release rate condition [110, 111, 112]. Examples of works from the hydraulic fracture field employing such criteria include [113, 114, 115].

Although such methods have seen some success in simulating the propagation of hydraulically-driven cracks, even in three dimensions [39, 40, 103], they struggle as crack evolution becomes sufficiently complex. By contrast, regularized methods have seen far more success in treating complex geometric evolution. In the next subsection, we present the governing equations for a phase-field method for fracture, a regularized approach for representing fractures and their evolution. Phase-field for fracture models generally start from a single energetic postulate that generalizes Griffith's criteria, and which is able to describe the entire fracture propagation process.

3.2.2 The phase-field method for fracture

The phase-field method for fracture started as an approximation [46] to the variational approach for fracture by Francfort and Marigo [45] for the quasi-static propagation of fracture in brittle materials. This model essentially states that a crack should evolve in a way that minimizes a total energy functional, among all admissible states, which are those that contain the current crack set (so that no healing is possible). For the method adopted in this work, we follow the work of Chukwudzie et al. [57] and associate the following total energy to a crack configuration Γ in a poroelastic brittle solid Ω : where the tractions applied to the boundary are denoted by \mathbf{t} , the normal to the crack is denoted by \mathbf{n}_Γ and $\mathcal{H}^{n-1}(\Gamma)$ is the $n - 1$ dimensional Hausdorff measure of Γ .

The strain energy density $W(\boldsymbol{\epsilon}(\mathbf{u}), p_m)$ is postulated as,

$$W(\boldsymbol{\epsilon}(\mathbf{u}), p_m) = \frac{1}{2} \left(\boldsymbol{\epsilon}(\mathbf{u}) - \frac{\alpha}{nK} p_m \mathbb{I} \right) : \mathbb{C} : \left(\boldsymbol{\epsilon}(\mathbf{u}) - \frac{\alpha}{nK} p_m \mathbb{I} \right), \quad (3.17)$$

with K denoting the bulk modulus and n the system's dimension (2 or 3). The phase-field regularization, based on the Ambrosio-Tortorelli [116] functional is then performed by the introduction of the damage parameter d and the regularization length ℓ ,

$$\begin{aligned} \mathcal{E}_\ell(\mathbf{u}, d, p_m, p_f) &= \int_{\Omega} \widetilde{W}(\boldsymbol{\epsilon}(\mathbf{u}), p_m, d) d\Omega - \int_{\partial\Omega_N} \mathbf{t} \cdot \mathbf{u} ds \\ &\quad - \int_{\Omega} \mathbf{b} \cdot \mathbf{u} d\Omega + \int_{\Omega} p_f \mathbf{u} \cdot \nabla d d\Omega + \frac{G_c}{c_0} \int_{\Omega} \left(\frac{\zeta(d)}{\ell} + \ell \nabla d \cdot \nabla d \right) d\Omega, \end{aligned} \quad (3.18)$$

where the function $\zeta(d)$ is the local dissipation function, which is usually taken as $\zeta(d) = d$ or d^2 . The constant c_0 is given by $c_0 = 4 \int_0^1 \sqrt{\zeta(z)} dz$ and the regularized strain energy is defined by,

$$\widetilde{W}(\boldsymbol{\epsilon}(\mathbf{u}), p_m, d) = \frac{1}{2} \left((1-d)\boldsymbol{\epsilon}(\mathbf{u}) - \frac{\alpha}{nK} p_m \mathbb{I} \right) : \mathbb{C} : \left((1-d)\boldsymbol{\epsilon}(\mathbf{u}) - \frac{\alpha}{nK} p_m \mathbb{I} \right), \quad (3.19)$$

which is consistent with an assumption of damage arising in the sub pore scale [57]. Finally, our regularized crack evolution problem is then stated as a minimization principle for the functional $\mathcal{E}_\ell(\mathbf{u}, d, p_m, p_f)$, with respect to the variables \mathbf{u} and d , with the added condition that the damage process is irreversible and that the damage variable d is bounded between the values of zero (undamaged state) and unity (fully broken state):

$$\mathbf{u}, d = \operatorname{argmin}_{\mathbf{u}, d} \mathcal{E}_\ell(\mathbf{u}, d, p_m, p_f), \text{ subject to } \dot{d} \geq 0, \text{ and } 0 \leq d \leq 1. \quad (3.20)$$

The following set of evolution equations can then be derived from the Karush–Kuhn–Tucker (KKT) [95, 96] conditions:

$$\nabla \cdot ((1-d)^2 \mathbb{C} : \boldsymbol{\epsilon}(\mathbf{u}) - (1-d)\alpha p_m \mathbb{I}) + \mathbf{b} = p_f \nabla d, \quad (3.21)$$

$$S_d := \frac{2G_c\ell}{c_0} \Delta d - \frac{G_c}{c_0\ell} \zeta'(d) - g'(d)W(\boldsymbol{\epsilon}(\mathbf{u}), 0) + \alpha p_m \nabla \cdot \mathbf{u} + \nabla \cdot (p_f \mathbf{u}) \leq 0, \quad (3.22)$$

$$\dot{d} \geq 0, \quad (3.23)$$

$$0 \leq d \leq 1, \quad (3.24)$$

$$S_d \dot{d} = 0, \quad (3.25)$$

with boundary conditions, $\boldsymbol{\sigma} \cdot \mathbf{n} = \mathbf{t}$ on $\partial\Omega_N$ and $(2G_c\ell \nabla d + c_0 p_f \mathbf{u}) \cdot \mathbf{n} \geq 0$ on $\partial\Omega$. The damaged stress is defined as $\boldsymbol{\sigma} = (1-d)^2 \mathbb{C} : \boldsymbol{\epsilon}(\mathbf{u}) - (1-d)\alpha p_m \mathbb{I}$.

In some cases, it is useful to decompose the energy (3.19) into positive and negative parts, in order to provide asymmetry between tension and compression states. In most problems studied in this Chapter, we found this decomposition to be important, and, unless otherwise mentioned, the spectral decomposition introduced in Miehe et al. [86] is used. With this decomposition, the equations for the macro-scale force balance (3.21) and the micro-force balance (3.22) are modified as

$$\nabla \cdot ((1-d)^2 \mathbb{C} : \boldsymbol{\epsilon}^+(\mathbf{u}) + \mathbb{C} : \boldsymbol{\epsilon}^-(\mathbf{u}) - (1-d)\alpha p_m \mathbb{I}) + \mathbf{b} = p_f \nabla d, \quad (3.22a)$$

$$S_d := \frac{2G_c\ell}{c_0} \Delta d - \frac{G_c}{c_0\ell} \zeta'(d) - g'(d)W(\boldsymbol{\epsilon}^+(\mathbf{u}), 0) - \alpha p_m \nabla \cdot \mathbf{u} + \nabla \cdot (p_f \mathbf{u}) \leq 0, \quad (3.23a)$$

and the damaged stress becomes $\boldsymbol{\sigma} = (1-d)^2 \mathbb{C} : \boldsymbol{\epsilon}^+(\mathbf{u}) + \mathbb{C} : \boldsymbol{\epsilon}^-(\mathbf{u}) - (1-d)\alpha p_m \mathbb{I}$.

In the above, $\boldsymbol{\epsilon}^+$ and $\boldsymbol{\epsilon}^-$ denote the positive and negative parts of the strain tensor as described in [86].

Finally, to close this section, we note that the extent to which the solution to (3.20) approaches a particular sharp model in hydraulic fracture in the limit as the regularization length $\ell \rightarrow 0$ has yet to be established. Nevertheless, the particular phase-field model adopted here contains all of the requisite components to allow for a proof of concept of the multi-resolution approach.

3.3 Multi-resolution method

3.3.1 General overview




FIGURE 3.2. Global domain Ω on the left and local domain Ω_L on the right. The surface corresponding to the local domain boundary $\partial\Omega_L$ is indicated within the global domain with the dashed red lines. The local domain is magnified to highlight the phase-field representation of the global crack Γ .

We propose a multi-resolution method to approximate the solution of the hydraulic fracture problem in porous media. It consists of coupling two problems

between a global domain and a local subdomain, as shown in Figure 3.2. In the global domain problem, the governing equations (3.1)-(3.8) are discretized, and the crack is represented with a sharp geometry. The crack geometry is assumed to be fixed during a solution step in the global domain, and relevant fields are calculated over the entire domain.

By contrast, the local subdomain concerns only a portion of the entire domain, namely in the vicinity of crack tips. It is encapsulated within the global domain as shown in Figure 3.2. In the local subdomain, a discretization of the variational principle (3.20) is used to simulate crack evolution. During a solution step in the local subdomain, the pressure fields within the fracture and matrix are assumed to be fixed.

The two problems are coupled in the following manner. The displacement and pressure fields are extracted from a solution step in the global domain and passed to the local subproblem in different ways. In particular, the global displacement fields are extracted along the surface $\partial\Omega_L$. These fields are then applied as Dirichlet boundary conditions for the local subproblem. The matrix pressure p_m and pressure in the fracture p_f are transferred as fields from the global domain to the local subdomain (see Section 3.3.3.2 for details), and assumed to be fixed for the local subproblem.

The aforementioned operations provide everything that is needed for the local subproblem from the global domain. Based on the imprint of the global crack geometry on the local subdomain, a regularized fracture surface is created (through an initial damage field) and then crack propagation is simulated in the local subdomain. Once an extension of the crack in a scale that can be represented in the global domain is identified, the sharp crack geometry in the global problem is updated accordingly.

In principle, the aforementioned multi-resolution approach can be implemented using a number of different discretization methods in the global domain and the

local subdomain. In the sections that follow, we describe the particular choices used in this work as well as some important implementation details. The method is described in a two-dimensional context, but many aspects can be readily extended to three-dimensional problems.

3.3.2 Global problem discretization

The global problem in our multi-resolution approach encompasses the physics of fluid flow in both the fractures and the pore structure of our domain, as well as the deformation of the solid media. The set of governing equations consists of (3.1)-(3.8), combined with constitutive assumptions (3.9)-(3.13) and appropriate boundary conditions.

In this work, we use the discretization method proposed by Cusini et al. [104] in the study of fluid flow in fractured porous media. The domain Ω is partitioned with a mesh \mathcal{T} . Then, the intersection of the fracture network Γ with \mathcal{T} defines the fracture triangulation \mathcal{F} . These meshes are then used to define discrete counterparts \mathbf{u}_G^h , p_m^h and p_f^h of the unknown fields \mathbf{u} , p_m and p_f , as well as discrete approximations of equations (3.1), (3.5) and (3.8).

A finite element approximation is constructed for the displacement field and employed in a standard Galerkin approximation to the global force balance (3.1). The continuous part of the displacement field is approximated with a standard space \mathcal{U} of 4-node bilinear shape functions $\{\boldsymbol{\eta}_a\}$. In the subset of elements that are “cut” by the global crack geometry, a space \mathcal{W} of discontinuous enrichment functions $\{\boldsymbol{\phi}_b\}$ is constructed using the formulation described in [117].

The full displacement field in the global problem is constructed using both con-

tinuous and discontinuous parts as

$$\mathbf{u}_G^h = \underbrace{\sum_{a=1}^{n_u} u_a \boldsymbol{\eta}_a}_{\text{continuous part}} + \underbrace{\sum_{b=1}^{n_w} w_b \boldsymbol{\phi}_b}_{\text{discontinuous part}}, \quad (3.26)$$

where $\{u_a\}, \{w_b\}$ are scalar degrees of freedom.

The flow equations (3.5) and (3.8) are discretized with a finite-volume method. Piecewise-constant pressure fields are constructed for p_m^h and p_f^h over the matrix mesh \mathcal{T} and the fracture mesh \mathcal{F} , respectively. Fluxes are computed using a two point flux approximation. The interaction between the flow in the fracture and matrix is effected via the embedded discrete fracture model (EDFM) [118, 44].

In terms of the temporal discretization, the parabolic nature of equations (3.5) and (3.8) gives rise to a stable time step for explicit schemes that scales with the cube of the mesh spacing [3, 64]. This upper bound is prohibitively small in most cases. Therefore, an implicit backward Euler method is used throughout. This gives rise to a fully-coupled system of nonlinear equations, whose solution is obtained with a Newton method, in a monolithic fashion.

One limitation of the construction (3.26) is that the discontinuous enrichment functions are not capable of representing a crack tip that terminates inside of an element. As such, any new extension of the crack geometry has to traverse from one side of a new element to another. The implementation of the fracture flow solver requires all cells to have non-zero volumes. Accordingly, new fracture cells are assigned a small aperture value (w_0). The total discrete aperture of the cell is thus given by $w_h = w_n + w_0$, where w_n is the mechanical aperture that is consistent with the jump provided by the displacement field. The minimum opening w_0 has been interpreted as a representation of the roughness of the fracture surfaces, providing a pathway for fluid flow even when the cracks are mechanically closed. See, for example

[104].

3.3.3 Local problem initialization

3.3.3.1 Construction of subdomain, submesh and damage-fixed nodes

A local subdomain of size $L \times L$ is constructed by simply centering it on a global crack tip. The size L is selected to be an even integer multiplier of the global mesh spacing, leading to a square bounding box that conforms to the background mesh. This choice is adopted for convenience in this work, although other constructions are possible, such as in [66].

To obtain the submesh \mathcal{T}_L , we start by considering the restriction of the global triangulation \mathcal{T} to the subdomain Ω_L . The mesh for the local subdomain is constructed by uniformly refining the set of elements in this restriction. This facilitates the transfer of nodal data from the global to the local problem. The mesh size h_{local} in the local subdomain is chosen to be sufficiently small to resolve the damage band, of size $\mathcal{O}(\ell)$. In this work, we use $\ell/h_{local} \approx 4$.




FIGURE 3.3. Global domain Ω on the left and local domain Ω_L on the right. The nodes in the subset \mathcal{K} , where d is set to 1 are colored in yellow.

The crack is represented by prescribing $d = 1$ in a set $\mathcal{K} \in \mathcal{T}_L$ of nodes in the local subdomain, as shown in Figure 3.3. This set is constructed in two steps. First, all elements of \mathcal{T}_L which are intersected by the global fracture triangulation \mathcal{F} are

identified. Then, \mathcal{K} is defined to be the set of all nodes that belong to any of these intersected elements.

3.3.3.2 Transfer of global pressures to local mesh

Due to the different levels of resolution between the global and local problems, we find it advantageous to transfer the pressure fields in a particular manner. We note that in the global problem, the fracture pressures p_f^h are available at the cell centers of 1D finite volumes, and the matrix pressures p_m^h are available at the cell centers of 2D finite volumes. These fields are transferred to quadrature points in the finite element mesh for the local subproblem using the transfer operators $\Pi_f^{\Omega_L}$ and $\Pi_m^{\Omega_L}$.




FIGURE 3.4. Illustration of global cells (in gray) in the neighborhood of a local element, indicated in pink. The matrix pressure at a quadrature point in the local element is calculated using an average of global pressures from neighboring cells $\{i\}$, with weights corresponding to the distances r_i between the quadrature point and the cell center.

The operator $\Pi_f^{\Omega_L}$ that transfers the fracture pressure is straightforward, and inspired by a similar operation described in Santillán et al. [119]. Given any point $\mathbf{x} \in \Omega_L$, and a global fracture pressure field p_f^h , $\Pi_f^{\Omega_L} p_f^h(\mathbf{x})$ is obtained by finding the closest cell of \mathcal{F} to x and taking the value of p_f^h at this cell. More precisely,

$$\Pi_f^{\Omega_L} p_f^h(\mathbf{x}) = p_f^h(\arg \min_{c \in \mathcal{F}} \text{dist}(c, \mathbf{x})). \quad (3.27)$$

For the operator $\Pi_m^{\Omega_L}$ that transfers the matrix pressure field, we use an averaging procedure. This has the effect of smoothing the matrix pressure field at the resolution of the local mesh. At a quadrature point $\mathbf{x}_Q \in \Omega_L$, the matrix pressure in the local domain is obtained from a weighted average of the pressures in the global cells that surround the point. Specifically,

$$\Pi_m^{\Omega_L} p_m^h(\mathbf{x}_Q) = \frac{\sum_{i=1}^s r_i^{-1} p_m^h(c_i)}{\sum_{i=1}^s r_i^{-1}}, \quad (3.28)$$

where r_i denotes the distance between the quadrature point location and the center of global cell i , as indicated in Figure 3.4. In the sum, all cells that neighbor the global cell containing quadrature point \mathbf{x}_Q are used. In the particular case when a quadrature point happens to reside in the center of the local element and $r_1 = 0$, the above sum is replaced with $\Pi_m^{\Omega_L} p_m^h(\mathbf{x}_Q) = p_m^h(c_1)$.

3.3.4 Local problem discretization

With the local subdomain properly identified and initialized, we now describe the additional steps to discretize the displacement and damage fields in the local subdomain and solve for their approximations. The governing equations for the macro-force balance (3.21) and the damage evolution (3.22) are both treated with the finite element method. The damage and displacement fields are both approximated using four-node bilinear quadrilateral elements.

Let Ω_L denote the local domain. From the finite-element approximation \mathbf{u}_G^h computed in the global problem, we extract $\mathbf{u}_G^h|_{\partial\Omega_L}$ and use it to constrain the displacements on the boundary of the subproblem ². As such, the trial space \mathcal{U}^h is

² In the multi-resolution method of Muixi et al. [67], the displacement boundary conditions near

given by

$$\mathcal{U}^h = \{\mathbf{u}_L^h \in H^1(\Omega_L)^n \mid \mathbf{u}_L^h = \mathbf{u}_G^h \text{ on } \partial\Omega_L\}. \quad (3.29)$$

The function space \mathcal{D}^h of admissible damage fields is given by

$$\mathcal{D}^h = \{d^h \in H^1(\Omega_L) \mid d^h = 1 \text{ on } \mathcal{K}\}, \quad (3.30)$$

where \mathcal{K} denotes the set of damage-fixed nodes that correspond to the global crack at the beginning of the load step, as described in subsection 3.3.3.1.

The test spaces are given by $\mathcal{W}^h = H_0^1(\Omega_L)^n$ for the displacements and $\mathcal{C}^h = \{c^h \in H^1(\Omega_L) \mid c^h = 0 \text{ on } \mathcal{K}\}$ for the damage field. The Galerkin approximation to the problem on the local subdomain is then:

The spatially discrete form

Find $\mathbf{u}_L^h \in \mathcal{U}^h$ and $d^h \in \mathcal{D}^h$, such that $\forall \mathbf{w}^h \in \mathcal{W}^h$ and $\forall c^h \in \mathcal{C}^h$,

$$(\nabla \mathbf{w}^h, \boldsymbol{\sigma}_L^h) - (\mathbf{w}^h, \Pi_f^{\Omega_L} p_f^h \nabla d^h) - (\mathbf{w}^h, \mathbf{b}) - \langle \mathbf{w}^h, \mathbf{t} \rangle_{\partial_t \Omega} = 0, \quad (3.31)$$

$$\frac{2G_c^h \ell}{c_0} (\nabla c^h, \nabla d^h) + \frac{G_c^h}{c_0 \ell} (c^h, \zeta'(d^h)) + (c^h, 2(d^h - 1)W(\boldsymbol{\epsilon}^+(\mathbf{u}_L^h), 0)) \quad (3.32)$$

$$+ (c^h, \alpha \Pi_m^{\Omega_L} p_m^h \nabla \cdot \mathbf{u}_L^h) + (\nabla c^h, \Pi_f^{\Omega_L} p_f^h \mathbf{u}_L^h) = 0,$$

where we have used (\cdot, \cdot) to denote the standard inner product in the $L^2(\Omega)$ space, and $\langle \cdot, \cdot \rangle$ to denote its restriction on the boundary. In the above, $\boldsymbol{\sigma}_L^h$ denotes the discrete stress, given by

$$\boldsymbol{\sigma}_L^h = ((1 - d^h)^2 \mathbb{C} : \boldsymbol{\epsilon}(\mathbf{u}_L^h) - (1 - d^h)\alpha p_m^h \mathbb{I}). \quad (3.33)$$

We employ an alternating minimization scheme to solve the coupled system of equations (3.31)-(3.32). Convergence is measured with respect to the L_2 -norms of the crack base were released. We did not find this to be necessary in our approach.

the change in the damage d^h and displacement fields \mathbf{u}_L^h , using a relative tolerance of 10^{-4} . With this approach, each of the equations becomes linear with respect to its primary variable, simplifying the solution process.

We note that (3.32) does not explicitly include the irreversibility constraint (3.25). Within the multi-resolution scheme, the Dirichlet condition $d^h = 1$ on the crack set \mathcal{K} is sufficient to prevent the healing of the fracture surface relative to the initial global crack. It does not, however, enforce irreversibility of the damage throughout the local subdomain, and it is possible that some crack healing could occur if regions are loaded and unloaded during a single time step. We did not find this to occur for the problems studied in this work, but it is possible that this could arise in more complex cases and the use of a more robust means of enforcing the constraint on the damage would be needed. Options include, for example, the active set solver described in [120].

In terms of the local dissipation function $\zeta(d)$, in this work we use $\zeta(d) = d$ which corresponds to the AT-1 phase-field model of fracture. This is selected due to the fact that it gives rise to a compactly supported damage field and a fully elastic stage prior to damage initiation [121]. When using the AT-1 model, it is necessary to explicitly enforce the constraint $d^h \geq 0$, as in some cases, this formulation can lead to negative damage values. In this work, this is effected by invoking a lower threshold on the active part of the strain energy $W(\boldsymbol{\epsilon}^+(\mathbf{u}_L^h), 0) = 3G_c/8\ell$, as in [52].

Finally, we note that phase-field models of fracture tend to give rise to a mesh and regularization length dependent critical fracture energy that is larger than G_c [122]. To account for this, we use a discrete value of G_c^h that is obtained as a function of the local mesh spacing and regularization length, as

$$G_c^h = G_c \left(1 + \frac{h_{local}}{c_0 \ell} \right)^{-1}, \quad (3.34)$$

such that the effective critical fracture energy is very close to that of the material.

3.3.5 Crack propagation: translating local damage updates into global crack extensions

A key step of the algorithm concerns how changes to the damage in the local sub-domain are translated into updates to the crack geometry in the global domain. We provide details of our algorithm for this procedure here. The scheme is presented in the context of a single crack tip that is propagating through the global domain. Although we do not consider much more complex cases in this work, such as changes in crack topology (due to crack branching or merging), we note that such problems have been examined in other works employing hybrid phase-field approaches. This includes the recent work of Muixi et al. [67], albeit in a purely mechanical context.

At each step in the solution algorithm, in the global problem, we keep track of two geometric entities, namely the global crack tip and the global tip element (Figure 3.5a). The global crack tip is defined by the interior endpoint of the crack. The global tip element is the element that contains the tip on one of its sides, but is not yet “cut” by the crack. In essence, it is the global element just ahead of the propagating crack tip. In the local subproblem, we identify a local version of the crack tip that is obtained from the discrete damage field d^h (Figure 3.5b and 3.5c). The algorithm to extend the global crack geometry depends on the relative location of the global crack tip, global tip element, and local crack tip, as described below.

The enrichment strategy described in Section 3.3.2 requires global elements that are completely cut by the crack geometry. As such, any extension of the crack geometry at the global scale must correspond to the global tip element being fractured. Accordingly, global crack propagation is triggered whenever the local tip falls outside the tip element. In this case, the new global tip is identified by connecting the current global tip and the local tip. Since the local tip is outside the tip element, a new




FIGURE 3.5. (a): Illustration of the global crack tip and global tip element. (b) Case when the local tip falls inside the tip element. (c) Case when the local tip falls outside the tip element.

segment will intersect the perimeter of the tip element exactly once (neglecting the obvious intersection at the current global tip). This process is illustrated in Figure 3.6. Any crack advance beyond this new tip location is neglected at this point, and the algorithm returns to a new global solve with an updated crack geometry.

In general, the problem of extracting a sharp crack front from a diffuse representation is not trivial. When the crack evolution involves complex topological changes, it is particularly difficult[123]. In the numerical examples studied in this Chapter, we take advantage of the relatively simple fracture geometry and predicted crack patterns to simplify this process. In particular, we first identify all elements in the local subdomain with nodes whose damage values are all above a threshold d_{tr} . A similar approach was proposed in [66]. The local crack tip is taken to be the center of the element in this set that is farthest from the base of the crack in the local subdomain. The threshold used for this process is taken to be $d_{tr} = 1 - h_{local}/(2\ell)$, which is based on the estimate for a damage field near a crack tip given in [59]. In essence, for a phase-field model of fracture, this threshold identifies nodes that are




FIGURE 3.6. (a): Construction of the segment connecting global and local tips. (b) New crack segment to be added. (c) Update of the global crack tip and global tip element.

expected to correspond to the peaks of the discrete damage field. For a damage band resolved with a mesh spacing of $\ell/h_{local} = 4$, this gives rise to a threshold of $d_{tr} = 0.875$.

3.3.6 Algorithm summary

Having described the solution strategies for both the global and local problems and the transfer of various quantities, we now detail the algorithm (1) that couples the two problems together to simulate crack propagation. Figure 3.7 provides an illustration of the algorithm. Within each time step (outer loop), the algorithm employs an inner loop that allows the global problem to be updated as soon as any large enough change in the crack geometry is detected in the local subproblem. The inner loop is terminated when the propagation step, described in subsection 3.3.5 does not identify any crack advance. The construction with two nested loops can be viewed as an implicit treatment of the fracture front position, which, according to Lecampion et al. [64] tends to be more accurate and robust, permitting the use of larger time

steps.

Algorithm 1: Solution algorithm for multi-resolution hydraulic fracture

```

Define initial and boundary conditions
n = 1
nF = endStep
while n ≤ nF do
     $\mathcal{F}_n^1 = \mathcal{F}_{n-1}$ 
    for 1 ≤ k ≤ maxItera do
        (1) Solve Global Problem and obtain  $\mathbf{u}_G^{k,n}, p_m^{k,n}, p_f^{k,n}$ 
        (2) Construct subdomain  $\Omega_L$  and submesh  $\mathcal{T}_L$ . Identify subset of cracked
            nodes  $\mathcal{K}$ .
        (3) Prescribe local boundary conditions  $\mathbf{u}_L^h|_{\partial\Omega_L} = \mathbf{u}_G^{k,n}|_{\partial\Omega_L}$  and  $d^h = 1$  on
             $\mathcal{K}$ .
        (4) Construct local pressure fields  $p_m = \Pi_m^{\Omega_L}(p_m^{k,n})$  and  $p_f = \Pi_f^{\Omega_L}(p_f^{k,n})$ 
        (5) Solve the Local Problem to obtain  $d^k$ .
        (6) Use  $d^k$  and the propagation step (subsection 3.3.5) to update discrete
            fracture  $\mathcal{F}_n^k$ .
    if  $\mathcal{F}_n^{k+1} = \mathcal{F}_n^k$  then
        n = n + 1
         $\mathcal{F}_n = \mathcal{F}_n^k$ 
         $\mathbf{u}_G^n = \mathbf{u}_G^{k,n}$ 
         $p_m^n = p_m^{k,n}$ 
         $p_f^n = p_f^{k,n}$ 
        break
    end
end
end

```

^a The index k is only a dummy variable for this loop that searches for the correct fracture geometry at a given time step.




FIGURE 3.7. Multi-resolution solution algorithm.

3.4 Numerical Results

We now present the results from various benchmark problems in fluid-driven fracture propagation. The problems range from those in which flow is only present within the cracks to fully coupled problems involving flow in both the matrix and the evolving manifold that is the fracture geometry. With the sole exception of the toughness-dominated KGD problem, all of the results in this section employ the spectral split of the energy, as described in Section 3.2.2.

3.4.1 KGD problems

We begin with the well-known Khristianovic, Geertsma and De Klerk (KGD) problems of hydraulic fracture [18, 17]. The problems concern the propagation of a planar fracture in an infinite, impermeable domain, under the injection of a viscous fluid at a constant rate (Figure 3.8).




FIGURE 3.8. (a) Schematic of the KGD problem, inspired by [3]. (b) Computational domain for the KGD problem (not to scale).

The response of the system can be characterized by the dimensionless group \mathcal{K} [87]:

$$\mathcal{K} = \frac{4G_c^{1/2}}{(6\pi^2 E' Q \mu)^{1/4}}, \quad (3.35)$$

where $E' = E/(1 - \nu^2)$. Values of $\mathcal{K} > 4$ correspond to the “toughness dominated regime” in which crack growth is largely controlled by the fracture toughness of the media. By contrast, when $\mathcal{K} < 1$, the fracture toughness is relatively small and the fluid viscosity is the main factor controlling the speed of crack growth. In the following, we explore the performance of the multi-resolution algorithm to simulate problems in both regimes.

3.4.1.1 Toughness-dominated regime

The toughness dominated regime is characterized by the creation of new fracture surfaces accounting for almost all of the energy dissipation. In this scenario, the fluid can be considered to be inviscid, which leads to a constant pressure distribution over

the entire crack. The assumption of inviscid flow reduces much of the complexity, allowing for the construction of a simple analytical solution for this problem. Here, we consider a problem in the toughness-dominated regime resulting from the material parameters and settings given in Table 3.1. Using these values in (3.35), we obtain $\mathcal{K} = 6.54$.

Table 3.1. Material properties and problem parameters for the toughness-dominated KGD problem

	Value	Unit
Young's modulus (E)	16.0	GPa
Poisson's ratio (ν)	0.18	—
Fluid viscosity (μ)	1.0×10^{-12}	GPa . s
Energy release rate (G_c)	1.85×10^3	N/m
Injection rate (Q)	1.0×10^{-3}	m ² /s
Initial crack size (a_0)	4	m

The analytical solution for this problem can be separated into two stages as a function of time. In the first stage, the pressure builds linearly with time and the crack does not propagate, as the pressure is below the critical threshold $p_{cr} = (G_c E' / \pi a_0)^{1/2}$. The pressure then reaches the critical value at $t = t_{cr}$, after which the crack begins to propagate. In the second stage the propagation is stable, since the amount of fluid injected is finite and crack propagation leads to a pressure drop as the total space available for the fluid to occupy increases.

The solution for the crack length and pressure in the crack can be written as

$$a(t) = \begin{cases} a_0, & t \leq t_{cr}, \\ \left(\frac{E'(Qt)^2}{\pi G_c} \right)^{1/3}, & t \geq t_{cr}, \end{cases} \quad (3.36)$$

$$p(t) = \begin{cases} \frac{t}{t_{cr}} p_{cr}, & t \leq t_{cr}, \\ \left(\frac{E' G_c^2}{\pi Q t} \right)^{1/3}, & t \geq t_{cr}, \end{cases} \quad (3.37)$$

where $t_{cr} = (\pi G_c a_0^3 / Q^2 E')^{1/2}$. A derivation of this solution can be found in Yoshioka [59].

For simulations using the multi-resolution scheme, a computational domain of size $W \times H = 30 \text{ m} \times 240 \text{ m}$ is used (Figure 3.8b). According to [124], this domain size should be sufficiently large to yield a good approximation to an infinite plane. We first report results using a sub-domain size of $L \times L = a_0 \times a_0$. The sensitivity of the results to the choice of sub-domain size will be discussed later in this subsection.

In what follows, we report results from a refinement study. In particular, we report results for three different regularization lengths of decreasing value, beginning with $\ell = a_0/15$. As the regularization length is decreased, we maintain a mesh size in the subdomain of $h_{local} = \ell/4$. This allows the finite-element approximation to sufficiently resolve the regularized fracture band. We also note that the effective fracture toughness in the computational problem depends on h/ℓ [59]. In the global domain, we maintain the mesh spacing at the ratio of $h_{global} = 3h_{local}$. For the coarsest global mesh, this translates into roughly 20 elements over the span of the initial crack geometry. This level of resolution is consistent with those found to be sufficient for resolving pressurized cracks using the Embedded Finite Element Method, in Cusini et al. [104].

The results obtained with the multi-resolution scheme are compared to the analytical solutions 3.36 and 3.37 in Figures 3.9a and 3.9b. We note the overall good match between the simulation results and the analytical solution, as well as the convergence of the results towards 3.36 and 3.37 when ℓ decreases. Although this problem is relatively simple as the matrix is assumed to be impermeable, it does test the coupling between the global and the local domains and verifies that the phase-field method, even when used only in a vicinity of the crack tip, can still provide accurate predictions of fracture propagation. Although the spectral split was not employed for this problem, we did examine the results using it. Qualitatively they




FIGURE 3.9. Comparison of numerical results and analytical solution for the toughness-dominated KGD problem: (a) crack length vs. time and (b) pressure vs. time.

were found to be very similar, with slightly less accuracy in the calculated values of the critical pressure.

We now examine the sensitivity of the results to changes in the subdomain size. This is accomplished by fixing the sizes of the global and local meshes as well as the regularization length, and varying only L in Figure 3.8b. In particular, we fix the regularization length to $\ell = 0.13$ m and vary the sub-domain size between 15ℓ and 45ℓ .

Figures 3.10a and 3.10b provide the results for the pressure and crack length as a function of time, for the various choices of subdomain size. Table 3.2 shows the error in the computation of the crack length relative to the analytical solution. The error is taken as an average over the time range, starting at the beginning of propagation.




FIGURE 3.10. Study of the effects of subdomain size on the results of the toughness-dominated KGD problem: (a) influence on predicted crack length and (b) predicted pressure.

Table 3.2. Effect of subdomain size on the relative error in the crack length.

Subdomain size	Relative error
$L = 15\ell$	11.5%
$L = 30\ell$	3.3%
$L = 45\ell$	1.1%

The results indicate that the error reduces as the subdomain size is increased. In this particular study, both the global and subdomain meshes are fairly refined, and so the improvement in accuracy as L increases is not likely due simply to better resolution in the local subdomain. Rather, it may be due to the fact that the two problems are coupled through the global displacements applied to the subdomain boundary. As the subdomain size is increased, the boundary of the subdomain moves farther from the crack tip singularity, and one would expect a better correspondence between the displacement fields obtained from the global problem and those obtained using a phase-field approximation over the entire domain. Furthermore, as the global displacements are held fixed until the regularized crack advances sufficiently far, there is some sensitivity of the proximity of the regularized crack tip to the subdomain

boundary.

In more general cases, one would expect the subdomain mesh to be at quite a bit higher resolution than the global mesh. Since the phase-field problem also requires several iterations in the alternate minimization scheme, problems are expected to become much more computationally expensive as L is increased. As a result, a trade-off between accuracy and computational cost is to be expected. In general, one should select a subdomain size that strikes a balance between being large enough to capture the crack evolution and small enough to render the overall calculation efficient.

3.4.1.2 Viscosity dominated KGD problem

We now consider a case in which the choice of parameters gives rise to conditions wherein the energy dissipation is dominated by viscous dissipation. In particular, we consider the material properties and problem parameters provided in Table 3.3. Consistent with (3.35), these values give rise to $\mathcal{K} = 0.57$, a result that is clearly within the viscosity-dominated regime.

Table 3.3. Material properties and problem parameters for the viscosity-dominated KGD problem

	Value	Unit
Young's modulus (E)	0.17	GPa
Poisson's ratio (ν)	0.20	—
Fluid viscosity (μ)	1.0×10^{-10}	GPa . s
Energy release rate (G_c)	21	N/m
Injection rate (Q)	1.0×10^{-3}	m ² /s
Initial crack size (a_0)	4.0	m

In this scenario, the toughness of the medium can be neglected, and the fracture evolution is effectively dictated by the motion of the fluid front. In this case, the pressure varies with time and space over the length of the fracture surface. Although this problem does not include a pressure field in the matrix, it bears emphasis that it does require the transfer of the pressure field in the fracture from the global scale

to the phase-field problem in the subdomain. As such, it serves as a test of that aspect of the multi-resolution scheme. The presence of dynamic terms in the fluid equation also implies the need for a discretization with sufficiently accurate temporal resolution, and in what follows we examine the sensitivity of the results to the choice of the time step size.

Once again, consider a computational domain with dimensions $W \times H = 30 \text{ m} \times 240 \text{ m}$. The sub-domain size is taken as $L \times L = a_0 \times a_0$, and the regularization length is taken to be $\ell = a_0/15$. In contrast to what we observed for the toughness regime, we note that the results to the viscosity-dominated problem were found to be largely insensitive to the choice of the regularization length, provided that $\ell < a_0/10$. This is not surprising, given that the phase-field subproblem only serves to propagate a crack that has effectively zero toughness.

In what follows, we report results using mesh spacings in the local and global domains of $h_{local} = \ell/4$ and $h_{global} = 3h_{local}$. As an initial condition, the pressure field is prescribed to match the analytical solution. We report on the temporal convergence of results obtained using fixed time steps, beginning with $dt_0 = 0.5\text{s}$. As (discrete) negative pressures arose in our simulations, the phase-field model was modified to account for a tension-compression asymmetry. In particular, consistent with the model described in Miehe et al. [86], the strain energy density was split into active and inactive parts, and only the “tensile” part was degraded with the damage.

Figure 3.11 compares the analytical solutions for the crack length and inlet pressure to the model-based simulation results for a sequence of decreasing time steps. The initial time ($t_0 = 8.5 \text{ s}$), initial inlet pressure ($p_0 = 40 \text{ kPa}$) and initial crack size ($a_0 = 4 \text{ m}$) were used to render the results dimensionless. The particular values of t_0 and p_0 were chosen in order to make our initial state a snapshot of the analytical solution. Overall, the good agreement between the results indicates that the




FIGURE 3.11. Numerical results and analytical solution for the viscosity-dominated KGD problem: (a) crack length vs. time; and (b) inlet pressure vs. time.

multi-resolution scheme is capable of handling a viscosity-dominated case.

The results for the crack length show an excellent agreement with the analytical solution as the time step is decreased. The results for the inlet pressure (Figure 3.11b) appear to converge to a trajectory that is slightly offset from the analytical solution as the time step is decreased. This relatively small discrepancy can be explained by the presence of a minimum aperture that is assigned to the newly-initialized finite volumes in the flow solver. As explained in [37], this is necessary to preserve the stability of the scheme when new crack segments are added. The recent work by Jin et al. [125] proposes a method for removing this parameter by employing partially fractured elements. The incorporation of similar modifications in the context of the multi-resolution scheme is the subject of future work.

3.4.2 Poroelastic problem with coupled matrix-fracture flow

We now examine a problem in which the matrix is permeable and there is a coupling between the fluid flow in the fracture, fluid flow in the matrix, and crack propagation. A schematic of the problem is shown in Figure 3.12. It corresponds to a rectangular




FIGURE 3.12. Geometry and notation for the coupled poroelastic-fracture problem.

domain subject to the injection of a viscous fluid at the mouth of an initial fracture. The fluid injection rate Q is assumed to be constant, and the displacement in the normal direction is fixed on all sides of the domain.

Although this problem is relatively simple, to our knowledge an analytical solution is not available. In what follows, we therefore compare our results to those that are obtained using an existing phase-field method for hydraulic fracture. In particular, we compare our results to those obtained using the method described by Miehe and Mauthe [51, 52]. This is arguably one of the simpler methods available for this class of problems, combining the equations for phase-field fracture, Biot's theory of linear poroelasticity in the matrix, and lubrication theory for fluid flow within fractures.

The model assumes that a Darcy model of flow holds in the matrix, with isotropic permeability. In the fractures, a lubrication flow model is assumed. The transition between the two flow regimes is effected through the use of a permeability tensor that varies as a function of the crack aperture and orientation. In particular, the permeability tensor κ is given by

$$\kappa = \kappa_0 + d^\xi \frac{w_n^2}{12} (\mathbf{I} - \mathbf{n}^d \otimes \mathbf{n}^d), \quad (3.38)$$

$$w_n = h(\mathbf{n}^d \cdot \boldsymbol{\epsilon} \cdot \mathbf{n}^d), \quad (3.39)$$

in which the normalized gradient $\mathbf{n}^d = \nabla d / |\nabla d|$ approximates the normal to the crack plane. In the above, κ_0 is an isotropic part of the permeability that accounts for the undamaged permeability of the matrix, w_n is the crack's normal aperture, and ξ is a weighting exponent. The weighting exponent concentrates the effects of the second term in 3.38 to areas where $d \approx 1$. Consistent with the work of Miehe and Mauthe [51, 52], we use $\xi = 50$.

Table 3.4. Material properties for poroelastic problem

	Value	Unit
Young's modulus (E)	16.0	GPa
Poisson's ratio (ν)	0.18	—
Fluid viscosity (μ)	1.0×10^{-12}	GPa . s
Energy release rate (G_c)	3.67	N/m
Biot coefficient (α)	0.79	—
Rock permeability (κ_0)	1.0×10^{-13}	m ²

Table 3.5. Problem settings

	Value	Unit
Phase-Field reg. length (ℓ)	0.2	m
Subdomain size (L)	4.0	m
Domain width (W)	30	m
Domain height (H)	10	m
Initial crack size (a_0)	4.0	m
Injection rate (Q)	1.0×10^{-3}	m ² /s

The material properties used in this problem are given in Table 3.4, while the problem and model parameters are provided in Table 3.5. The results reported in this section rely on the use of an eigen-decomposition of the strain energy, as described in Miehe et al. [86]. The subdomain size for the multi-resolution method was chosen to be proportional to the initial crack size, or $a_0 \times a_0$. The problem

was discretized spatially using a uniform mesh in the local domain with $h_{local} = \ell/4$, while $h_{global} = 3h_{local}$ was used in the global domain. For the temporal discretization, a uniform time step of $dt = 0.125$ s was used. This level of spatial and temporal discretization was found to yield results that were sufficiently converged.

An important difference between the phase-field formulation used in Miehe and Mauthe [51, 52] and that employed in the current multi-resolution method concerns the use of pressure-dependent driving forces. We draw the reader's attention to the terms involving the pressure fields p_m and p_f in the evolution equation (3.22) for the damage field. In our studies of the KGD problem, we found these terms necessary to include in order to obtain sufficiently accurate simulations. We refer to these terms as "driving pressures" as the pressure fields contribute directly to the evolution of the damage field. Importantly, the phase-field formulation of Miehe and Mauthe [51, 52] does not include these terms in the damage evolution equation. Accordingly, in what follows we find it useful to compare results from Miehe and Mauthe [51, 52] to those obtained using our multi-resolution method with and without the driving pressures.

Results for the crack length and inlet pressure as a function of time are provided in Figure 3.13. Contour plots of the damage and pressure fields for the multi-resolution scheme and the full phase-field formulation are provided in Figure 3.14. Despite the numerous differences in the models, the results obtained with the multi-resolution compare very favorably to those obtained using our implementation of the phase-field fracture model [52]. This is particularly the case when the driving pressures are removed from the multi-resolution method, such that the two phase-field models are as close as possible. At early times the crack remains stationary, as the pressure at the inlet increases. At some point the pressure near the crack tip reaches a magnitude that is sufficient to give rise to crack propagation. After crack propagation begins,




FIGURE 3.13. Results from the fully coupled poroelastic-fracture problem for the multi-resolution method (with and without driving pressures) and a standard phase-field model: (a) crack size over time, (b) inlet pressure. The time for crack propagation (t_{ref}) in the phase-field model and the corresponding inlet pressure (p_{ref}) are used as references for the dimensionless charts above.




FIGURE 3.14. Fields from the coupled poroelastic-fracture problem, taken at the end of the simulation, contrasting results from the multi-resolution scheme without the driving pressures (top row) to those obtained using a standard phase-field model of fracture in poroelastic media (bottom row). (a) Contour plots of the damage field. (b) Contour plots of the pressure field.

the rate of pressure increase begins to decrease with time, as crack growth allows for additional fluid to be accommodated within the fracture. Clearly the phase-field subproblem with a frozen pressure field that acts effectively as a body force is still capable of simulating crack propagation, even when there is flow in the crack and the matrix. It bears emphasis that the multi-resolution scheme does not need to rely on estimations such as 3.38,3.39 to extract an approximation to the aperture from the regularized crack geometry.

3.4.3 Propagation around an inclusion




FIGURE 3.15. Geometry for the inclusion problem.

We now consider a problem that gives rise to a non-planar crack evolution. Specifically, we investigate the effects of a stiff inclusion on the trajectory of a hydraulically-driven fracture in an impermeable medium. The problem setup is shown in Figure 3.15. A circular inclusion of radius r is placed in a rectangular domain, at a distance

s from the left boundary, and slightly offset from the axis of symmetry. The inclusion is assumed to have properties that are identical to the matrix, with the exception of the Young's modulus. An initial crack of size a_0 is placed in the left boundary and a fluid is injected at a constant rate Q . The complete set of material properties and geometric parameters are listed in Tables 3.6 and 3.7.

Table 3.6. Material properties for inclusion problem

	Value	Unit
Young's modulus (E)	9.0	GPa
Poisson's ratio (ν)	0.25	—
Fluid viscosity (μ)	1.0×10^{-12}	GPa . s
Energy release rate (G_c)	2.5×10^6	N/m

Table 3.7. Problem settings

	Value	Unit
Phase-Field reg. length (ℓ)	0.4	m
Subdomain size (L)	4.0	m
Domain width (W)	20	m
Domain height (H)	40	m
Initial crack size (a_0)	4.0	m
Injection rate (Q)	1.2×10^{-1}	m^2/s

Simulations using the multi-resolution scheme were conducted for three different values of inclusion stiffness, with $h_{local} = \ell/6$ in the local domain, and $h_{global} = 3h_{local}$ in the global domain. The objective was to test how the stiffness of the inclusion influenced the crack trajectory. Consider the following two limiting cases. When the inclusion is just slightly stiffer than the matrix, one would expect the crack trajectory to remain straight. At the other extreme, when the inclusion is much stiffer, one would expect the crack to propagate around it.

The crack paths predicted by the multi-resolution scheme are shown in Figure 3.16. The deformed meshes are shown with displacements exaggerated to highlight the crack trajectories. As expected, for an inclusion with much higher stiffness,




FIGURE 3.16. Crack paths for the inclusion problem: (a) 2X stiffer inclusion; (b) 7X stiffer inclusion; and (c) 15X stiffer inclusion.

the crack propagates around it. By contrast, when the stiffness of the inclusion is relatively close to that of the matrix (2X case), the trajectory remains nearly straight. Interestingly, for an intermediate value, where the inclusion is 7 times stiffer than the matrix, the crack trajectory gets deflected, but still goes through the inclusion.

The pressures at the injection point are plotted as a function of time in Figure 3.17. Due to the very high toughness of the material, they are almost uniform over the crack. For this problem, we did not observe much sensitivity of the results to the choice of time step size. By analyzing these curves, we can identify several different stages for this problem. At early times before any crack propagation begins, we observe a linear increase in pressure with time. Then, as we reach a certain pressure, which we denote as $p_{ref} = 60$ MPa, straight crack propagation starts and proceeds until the tip approaches the inclusion. Due to the higher stiffness of the inclusion, the crack arrests and pressure builds up again until it reaches a level that is sufficient to allow propagation to continue. This is accompanied by a pressure drop that is most pronounced for the higher-stiffness inclusion cases.

This problem highlights several capabilities of the multi-resolution scheme, such as the simple handling of crack curving as well as changes in the crack speed, including crack arrest. Although we are not aware of any analytical solution for problems like




FIGURE 3.17. Inlet pressure as a function of time for the three inclusion problems, corresponding to inclusions with different stiffnesses. The reference values of the pressure p_{ref} and time t_{ref} were defined as the minimum pressure that led to fracture growth and the associated time, considering the simulated injection rate.

this, the results we have obtained appear to make sense qualitatively.

3.5 Summary and conclusions

This manuscript presents a new approach for developing model-based simulations of hydraulic fracturing. The method relies on a global problem that captures flow and deformation fields, and a local problem that captures crack growth with the aid of a phase-field method. The two problems are coupled through the transfer of displacement and pressure fields, as well as updates to the crack geometry. This multi-resolution approach allows the phase-field method to be used as a tool to update the crack geometry without the need to explicitly reconstruct the crack aperture from the diffuse representation.

The accuracy of the multi-resolution approach is evaluated through several numerical examples. These include the well-known KGD problem, for which a good agreement with analytical solutions is obtained in both the toughness and viscosity regimes. A problem with a curved crack trajectory around a stiff inclusion also demonstrates the overall robustness of the approach. Several areas for future work

present themselves. These include, for example, an enhancement of the algorithm to identify the sharp crack tip from the diffuse damage field; treatment of problems involving crack branching and merging; three-dimensional geometries and crack nucleation in arbitrary locations.

4

Extending the Multi-Resolution Approach to Three Dimensions

4.1 Introduction

While two-dimensional simulations, based on the multi-resolution algorithm proposed in the previous chapter, can be useful to study fundamental processes in hydraulic fracturing, realistic systems are almost always three-dimensional. Therefore, an extension of the approach to 3D is certainly the most natural next step to be taken. In addition to that, due to the size of the problems, in which fractures of the size of kilometers have to be resolved in the scale of their apertures, high-performance computing(HPC) is a must.

To address these challenges, this chapter proposed a new propagation algorithm for the multi-resolution approach that is suited for planar fractures in three dimensions. This algorithm is implemented in the HPC solver GEOS [35, 36, 37] in a fruitful collaboration with the Lawrence Livermore National Laboratory.

The chapter begins with a brief recap of the multi-resolution algorithm and moves on to the detailed description of the new propagation algorithm for the case of

planar fractures. It then discusses the implementation in GEOS and some challenges associated with the parallelization of the scheme. Illustrative examples are then presented, including in-plane merging of two-penny shaped cracks. In the end, the extension to non-planar fractures in 3D is discussed, pointing out the limitations of the planar algorithm.

4.2 Theory

In Chapter 3, the mathematical model for single-phase fluid-driven fracture is described in Section 3.2. In what follows, this same model is assumed, as all derivations are independent of the system dimensionality as well as fracture shapes. More precisely, since the multi-resolution framework is employed, two coexisting descriptions are used. In a global domain, cracks are assumed to be represented by two-dimensional surfaces embedded in the 3D domain and the governing equations and boundary condition are those from (3.1) - (3.16), which assume a fixed fracture geometry. In the local domain, the fracture problem is treated with a variational phase-field formulation, given by (3.21)-(3.25) which assume flow quantities to be fixed.

A more detailed discussion of the motivation and fundamentals of the multi-resolution method is provided in Section 3.3. In a nutshell, it breaks a fracture problem in two separate problems. In the global one, that covers the whole domain, a discrete representation of the fracture is used, but its geometry is assumed to be fixed. To account for crack propagation, a local problem in a vicinity of the fracture front is set up, employing the phase-field method, taking advantage of its flexibility in representing evolving fracture geometries.

This type of approach is particularly interesting for simulating fluid-driven fracture due to the presence of a discrete fracture in the global level, which simplifies the computation of the fracture apertures that must be coupled to the fluid problem.

If a pure phase-field description is used, extracting these apertures becomes a challenging task. In addition to that, a multi-resolution approach can also alleviate the computational cost that comes with the highly-refined grids needed to solve phase-field problems. This becomes a remarkable limitation in the context of hydraulic fracturing since the length of fractures is usually of the order of kilometers.

An attentive reader will realize that the multi-resolution algorithm proposed in Chapter 3 is not easily extendable to three-dimensions only because of the propagation step described in the subsection 3.3.5. In this part of the algorithm, a crack tip location is extracted from the damage field in the local problem and used to inform the global problem how to advance the crack. The concept of a crack tip does not exist in three-dimensions (it becomes a fracture front). In addition to that, while in 2D it is possible to connect line cuts (which are just line segments) to form an approximation to the crack geometry, in 3D these become planar cuts, which may fail to connect on element boundaries. SHOW FIGURE.

The first extension discussed in this chapter deals with the case of planar fractures in 3D. The main challenge here consists of tracking the entire fracture front and evolve it according to the damage field computed in the local problem. This is done defining a discrete set of crack front elements which are investigated for damage throughout the problem execution. The construction of this layer of front elements ahead of the crack is important to preserve the accuracy of the solution, because the lack fluid flow in the local problem can lead to spurious unstable solutions.

For the more complex case of non-planar fracture propagation, some considerations will be discussed in Section 4.5. The prototype of an algorithm to handle this case will be shown together with some preliminary results. However, its robustness is not guaranteed.

4.3 Algorithm for planar fractures




FIGURE 4.1. Multi-resolution solution algorithm.

A high-level description of the propagation algorithm for planar fractures in 3D is shown in Figure 4.1. It summarizes each of the steps involved in the solution procedure for a single time-setp. The process begins with the solution of the global problem (i.e, the box colored in blue in 4.1). As pointed out in chapter 3, the algorithm is agnostic with respect to the numerical methods employed. The approximate fields for pressure and displacements are then transferred to the local problem, as explained in the steps (3) and (4) of Algorithm 3.7.

In the 2D algorithm, one would now move to the solution of the local problem with an alternate minimization approach and only then check for fracture propagation. In the proposed 3D algorithm, this is changed and a damage tracking function is launched in parallel with the damage solver. This function checks the amount of damage in the elements of the fracture front. Different measurements of damage can be employed, and they will likely depend on the discretization method employed. A simple one, which works well for planar fractures in structured grids is the volume

of damage, which is defined as the total volume of subdiscretization' elements with damage above a threshold (usually around 0.9). This approach is effective since, for planar fractures aligned with structured grids, the fracture area on each element can be predicted beforehand. This simplified criteria is used in the example problems that will be shown next. For more general discretization types, a more robust approach consists of checking the number of faces and edges in an element that are damaged above a certain level.

MENTION THAT PROPAGATION CRITERIA IS DISCRETIZATION DEPENDENT

If any of the front elements is identified as being cracked (i.e, the level of damage on it is very high), the alternate minimization iterations are halted. The geometry of the discrete fracture in the global is then updated. This update consists of the addition of a planar cut in this cracked element, followed by an advance in the fracture front.

If multiple front elements are cracked, this process is done for all of them. The current time-step is then re-launched. Convergence is achieved when the alternate minimization procedure reaches a prescribed tolerance without triggering the fracture propagation. When that happens, an equilibrium state is obtained and the time-step can be advanced.

4.3.1 Fracture front construction

The fracture front plays an important role in the propagation step. It greatly reduces the computational expense associated with the inspection of damage in the global elements while also serving to indicate a reference position to place the subdomains as the crack advances. Its construction happens during the initial discretization of the fracture in the global domain. One goes over all fractured elements and among its neighbors, adding to the front those elements that share a fractured face (but

are not yet fractured) with the fractured ones. This step is repeated every time the global fracture geometry is updated (i.e new fracture cells are inserted). Figure 4.2 shows the fracture front for an initial discretization (and fairly coarse) of a penny shaped fractured. Figure 4.3 shows the sequence of steps involved in the fracture propagation process, including the update of the fracture front.







FIGURE 4.2. Front elements shown in green. Red elements represent discretized fracture.



(a) Initial state.



(b) Damage advanced.



(c) Updated configuration.

FIGURE 4.3. Schematic of propagation steps.

4.3.2 Tracking damage in the fracture front elements

The process of tracking the damage in the front elements also deserves a more detailed explanation. In the set of preliminary results shown next, a simplified method suitable for planar cracks in structured grids is used. It consists of first computing the cross sectional area of the element along the fracture plane. For example, for a fracture whose normal is in the x direction, one gets $H_y H_z$.¹ This is only possible when the structured grid is aligned with the fracture (either in x, y or z).

Then, assuming that the fully damaged region of a phase-field fracture consists of a single element² across the band width, one expects the fully cracked region to have a volume of $h_x H_y H_z$. A simple criteria then consists of measuring the volume of local elements that have reached an average damage beyond a threshold close to 1 (In the examples shown next, this threshold was set to 0.9). A global element is then considered fractured if this volume reaches $h_x H_y H_z$.

This method contains multiple limitations, such as the need for planar fractures aligned with a structured grid and also the hypothesis that the damage band has a single fully degraded element along its width. An alternative method to circumvent these issues inspired by [67] consists of evaluating the damage field in the edges of an element. It assumes that a fractured element has at least three fractured faces and that a fractured face is cut on two of its edges.

For each global element in the crack front, the damage field, computed in the local mesh, is inspected on every edge. If damage above a threshold (typically 0.9 or 0.95) is identified in a given edge, that edge is considered cut. If any face contains two cut edges, it is marked as cut. An element is then marked as fracture when at least three of its faces are cut.

¹ Assume that the global element has dimensions H_x, H_y and H_z whereas the local one has h_x, h_y and h_z .

² this is not so obvious

This criteria circumvents some of the limitations of the simplified one, removing the need for structured grids. It is also applicable to nonplanar fractures as well. However, it is not perfectly robust and certain relative configurations between the damage field and the global element in the front can lead to unexpected results. This will be shown in Section 4.5 that discusses the case of nonplanar fractures.

4.4 Numerical examples

In this section, a set of example problems computed with the aforementioned method is presented. These examples illustrate the main capabilities of the approach, but also serve to demonstrate some of the limitations. They all consist of hydraulic fracture propagation in a poroelastic medium. However, different fracture geometries and boundary conditions are explored. The main goal is to ensure that the proposed algorithm works as expected and can handle different scenarios, such as multiple fractures and in-plane crack merging.

Importantly, a true verification procedure is not performed here. For example, mesh convergence studies and comparisons with well-known solutions are yet to be performed. Those require a few enhancements in the solver technology that are currently under development. First, due to the high discrepancy between the scales of degrees of freedom (matrix displacements, fracture apertures and pressures), general purpose linear solvers struggle to converge when the meshes are refined past a certain point. In this case, special preconditioners that take into account the block structure of the system are recommended. CITE SOMEONE. Second, analytical solutions for poroelastic problems are scarce, so, a common verification procedure consists in solving them with vanishing small permeability coefficients to verify convergence towards the KGD solutions (Section XXX) for impermeable media. However, as the permeability decreases, the poromechanics problem starts to display KBB-type instabilities (CITE SOMETHING), which require either modifications to element types

or a stabilized formulation, such as (CITE JOSH PAPER). This solver infrastructure enhancements are currently in progress.

For the problems in this Section, the material properties used are listed in Table XX.

4.4.1 Single fracture under fluid injection with non-homogenous boundary conditions

In this problem, an initial penny-shaped fracture is injected with a viscous fluid and the boundary conditions are these shown in Figure XXX. Since the boundary conditions are different in the outer faces, the fracture tend to have a prefered propagation direction and therefore, loses its initial circular shape.

This

4.4.2 Two parallel circular fractures under fluid injection

In this problem, a pair of parallel penny-shaped fractures is stimulated with the injection of a viscous fluid. Parallel fractures are very common in real-world fracking, in general, fracking sites will have dozens, if not hundreds of parallel fractures, which are stimulated simultaneously.

Depending on the distance between the fractures, they may grow away from each other, forming a cup shaped geometry. This is a consequence of the interaction between the stress fields in the vicinity of the multiple fractures, this interaction is often called stress shadow effect.

In this numerical example shown here, the initial fractures are placed far from each other to prevent this nonplanar behavior. The far-field boundary conditions are assumed to be homogenous for pressures and tractions. Figure XX illustrates the setup.

In this case, the fractures are expected to grow radially, preserving their circular shape. This feature is confirmed in the simulated results shown in Figure 4.6. In this

figure, the right-side of the domain shows the pressure field computed in the global domain whereas the left side shows the discrete crack geometry, colored in gray scale indicating the aperture field. It also shows the subdomain around the crack front, colored by the damage field.

The aperture and pressure at the injection sources are important quantities in this type of problem and their simulated time series are shown in Figure 4.5. Due to the symmetry, both fractures have the same pressure and aperture results. The reference values used to make the curves nondimensional are listed in Table 4.1.

Add details about meshing, subdomain size, time step and etc.

Table 4.1. Reference values

	Value	Unit
p_{ref}	0.2	MPa
w_{ref}	4.0	m
t_{ref}	30	s




FIGURE 4.4. Parallel specimen.




FIGURE 4.5. Two quantities of interest for the parallel fracture problem. On the left, the time series of the pressure at the injection point, on the right, the fracture aperture. Both plots show results scaled by reference values, calculated at the onset of propagation.




FIGURE 4.6. (a) time 1; (b) time 2; (c) time 3; and (d) time 4.

4.4.3 Merging two circular fractures

The second problem deals with the case of in-plane fracture merging. In general, fracture merging is one of the most difficult behaviors to simulate with discrete fracture approaches. That is due to the interaction between the stress fields of two fracture fronts, which makes most attempts to extract a stress intensity factor inaccurate.

In these types of problems, the phase-field method becomes handy, allowing for the computation of crack advances regardless of the front geometry. This is explored well in the multi-resolution approach, since the entire fracture front is inside the subdomain by construction, allowing for the use of the phase-field solver.

Since this problem deals with in-plane merging, getting the discrete fracture planes from the phase-field values is straightforward. However, it is important to mention that this can be a challenge in the case of non-planar merging.

The problem under consideration consists of two parallel fractures, initially of circular shape, embedded in a poroelastic matrix. Both are injected with a viscous fluid and propagate radially, eventually merging. The simulated behavior is depicted in Figure 4.9. As for the previous problem, the times series for the aperture and pressure in the injection point are shown in Figure 4.8. The reference values used to make these charts nondimensional are given in Table 4.2.

Add mesh quantites, time step, material properties, boundary conditions and conclusion.

Table 4.2. Reference values

	Value	Unit
p_{ref}	0.2	MPa
w_{ref}	4.0	m
t_{ref}	30	s




FIGURE 4.7. Merging specimen.




FIGURE 4.8. Two quantities of interest for the merging fracture problem. On the left, the time series of the pressure at the injection point, on the right, the fracture aperture. Both plots show results scaled by reference values, calculated at the onset of propagation.




FIGURE 4.9. (a) time 1; (b) time 2; (c) time 3; and (d) time 4.

4.5 Extension to non-planar fractures

Extending the multi-resolution approach presented herein to non-planar fractures is definitely the most natural follow-up task. However, this extension requires additional challenges to be addressed. In the last Section, a skeleton of a possible algorithm is described. A simplified nonplanar fracture problem in 2D is used to test it. Although the result is favorable, the extension of this algorithm to full 3D problems requires additional modifications whose robustness are unclear. Another possible direction of work is then proposed, but left for future work.

4.5.1 Overview of a propagation algorithm for non-planar fractures

Algorithm 4.1 showed how to use the multi-resolution method to treat planar fractures in 3D. To extend it to non-planar cases, certain parts must be modified.

- First, the algorithm for tracking the damage in the front elements described in subsection 4.3.2 must be modified to read a nonplanar damage field and assess if the element is fully fractured.
- The update of the geometry becomes more complex for the same reason. Given a nonplanar damage field in an element, how to insert a planar³ cut in the mesh that represents it well?
- Finally, while for planar cuts the continuity of the fracture surface is always guaranteed, in nonplanar case, local (element-wise) approximations of the damage field with discrete cuts may lead to a discontinuous fracture surfaces.

To address the first bullet point, one can start with the topological criterion proposed in 4.3.2, where the number of edges and faces with damage above a threshold

³ While it is possible to develop embedded methods that allow for curved cuts inside elements, those are rarely used in practice due to the complex integration techniques needed. Because of that, in the current work, while strong assumptions on the embedded scheme are avoided, the focus is on first-order (i.e planar cuts) methods.




FIGURE 4.10. This figure shows a pathological case for the topological criterion proposed in 4.3.2. The element on the right is only partially damaged, however, the counts of cut edges and faces are higher than the ones for the element on the left, which is indeed fully cut.

is used. In general, if the damage band is small compared to the global element size, there is likely no ambiguity in the identification of cutting points. However, if the regularization length or the mesh size in the local problem are not very small, some difficulties may arise. For example, a wide damage band approaching the element diagonally may cut two adjacent edges as shown in Figure 4.10. This leads to a configuration where the number of cut edges and faces is large albeit the actual global element is not yet fractured.

Overcoming this limitation likely requires the use of information about the damage in neighboring elements. One approach, used in the example problem shown next is to keep the topological criterion the same, but introduce a check on the cutting angle that is obtained after each element is cut. This check consists of comparing the normal to the new cut with the neighboring fractured elements. If the normals are too different (i.e $\mathbf{n} \cdot \mathbf{n}_{neighbor} \ll 1$), then, this newly insert cut is assumed to be due to a pathological case and then removed. The respective element is only considered

for cutting again when the number of damaged faces increase.

This heuristic relies on the assumption that fractures do not kink strongly over element boundaries, which is only true if the fracture curves have a large radius of curvature compared to the global element size.

Now, in terms of the second bullet point, regarding the extraction of the cutting plane from a damage field, an optimization algorithm such as [65] can be employed. In a nutshell, this method searches over the space of planes embedded in an element and constructs an idealized damage profile around this plane, using the optimal profile given by $d(x) = (1 - \text{dist}(x)/2\ell)^2$, where $\text{dist}(x)$ denotes the distance from x to the plane. These idealized profiles are compared to the actual damage field and the one which is closest in the L_2 sense is assumed to be the correct cutting plane for that damage field.

However, integrating this optimization approach with the angle check described above introduces another issue. That heuristic works under the assumption that an attempted cut on an element which is not yet fractured will lead to a cutting plane that does not conform well to its neighbors. If an optimization approach is employed, that might not always be true. For example, in the case shown in Figure 4.10, the optimization approach can find the cutting plane induced by the partial fracture which will conform well to the existing cuts, even though the element is only partially cut.

So, in order to use the angle check, instead of applying the optimization method and then comparing the calculated plane with its neighbors, a crude pre-cut is employed. The idea of these pre-cuts is to rely only on the relative position of the cut faces identified by the topological criterion. This is done to ensure that, if one is dealing with a pathological case for the topological criterion, the pre-cut will indicate that and fail the angle check. In a 2D scenario, these pre-cuts can be obtained for example by connecting the midpoints of the fractured faces. In 3D, the mapping

becomes a bit more complex. Figure 4.11 shows the basic pre-cut types in 3D.




FIGURE 4.11. Pre-cut basic shapes.

Even with these modifications, the third and last bullet point, that concerns the continuity of the fracture surface must be addressed. For general embedded fracture approaches, continuity of the fracture surface is a necessary feature for the construction of the approximation space for the displacement field. This imposes serious complications to any type of algorithm that tries to construct surface increments on an element to element basis such as the one used here. However, the EFEM/EDFM approach used in this work and first proposed in [104] does offer a possible way to handle this issue.

By construction, the EFEM method does not assume continuity of the displacement field across element boundaries. In fact, the enrichment employed to represent the displacement jump does not interact with the neighboring elements and the final aperture final might indeed be discontinuous. Still, the method does converge to the continuous solution in space. Figure XX, from [104] shows a typical aperture field computed with EFEM. This flexibility allows one to prescribe a fracture field that may have gaps in its geometry and still compute an accurate aperture field.

On the other hand, for the computation of the flow problem, some sense of continuity is still required to calculate fluxes from a fracture cell to its neighbors. In fact, two compute the flux between two embedded cells, their common edge is used. That is, if one obtains a discontinuous fracture surface, there will be neighboring cells that do not share an edge and therefore, there won't be flow between them.

Luckily, this issue can be circumvented by noting that the damage intersection on

any edge is the same for all elements that contain that edge. Therefore, instead of computing the fluxes directly from the common edge of neighboring fracture cells, one can store the intersections of the damage field with the global element edges and use them to build segments in between two neighboring cells. These segments can then be used to compute the fluxes, ensuring that even neighboring cells that happen to be on a surface discontinuity still get a reasonable flux. The drawback of this approach is its obvious dependence on the EFEM/EDFM scheme. It is unclear whether such modifications can be done if one chooses to use a XFEM enrichment instead.

ADD FIGURE.




FIGURE 4.12. Flux in discontinuous fracture surfaces.

While there appear to be answers to the three main challenges listed above, this work falls short of providing an example that shows all these modifications, mainly for a lack of time. Instead, only the first modification to the algorithm, which concerns the topological criterion and its enhancement with the angle check and pre-cuts is implemented and tested. The optimization scheme and the flux computations based on the damage intersections in the edges are left for future investigations.

In the next section, the simplified algorithm described above is applied to a 2.5D problem where the crack path is curved. It serves to check the efficacy of the proposed




FIGURE 4.13. Algorithm modifications

changes in the process of identifying the crack path. The fluid flow and poroelastic effects are turned off for simplicity.

4.5.2 Example problem

This subsection presents a small 2D problem used to test the simplified algorithm presented in 4.5.1. This problem consists of an edge crack in a square plate, which is loaded in the top edge by an inclined traction as shown in Figure 4.14. The material properties and geometric parameters are given in Table XX. All the fluid effects are removed, as the focus is only on the algorithm to track the fracture and insert the discrete cuts. The subdomain is set to be the entire domain, which simplifies the transfer of boundary conditions from the global to local problem.

Despite the simplification in defining the cut direction, the discrete fracture is still capable of tracking the damage band quite well, as shown in Figure 4.15b. Interestingly, this problem involves multiple cases of the damage band approaching the diagonal of an element, which constitutes a pathological case, described previously. This shows that the correction based on the neighboring cutting angles is indeed useful and necessary in this type of approach.

For a sake of comparison, this same problem was studied in [66] and the crack path results are in good agreement with the one displayed in Figure 4.15b. A relative straightforward improvement can be done with the introduction of an optimization method, such as [65] to produce cuts that better align with the damage band locally. However, the use of "crude" approximations is still important to test the angle criteria and prevent lightly damaged elements to be wrongly cut due to a pathological case, such as the one shown in Figure XX.

One the other hand, this example doesn't explore a lot of the difficulties that arise in full 3D problems. To begin, mapping damage on edges to the "crude" approximations shown in Figure XX becomes much more difficult in 3D. In addition to that, the angle criteria may work well in cracks that evolve progressively as the one in this example, however, it may get into a "locking" situation if two cracks are merging at an angle. This is, different neighbors may impose constraints in the cutting angle of an element that may be impossible to satisfy simultaneously.

Overcoming these challenges may require a more severe reformulation of the algorithm used for planar fractures. One promising approach is to employ a global method of surface reconstruction after the solution of the phase-field problem. This is a research topic on its own, with important contributions developed in recent years, such as []. In [], the authors actually looked at surface reconstruction in a similar framework, to improve the simulation of plasticity using phase-field methods. They used the gradient of the damage to guide the identification of a discrete fracture surface embedded in a triangular mesh. REVIEW THIS. While the robustness of their reconstruction in the presence of crack merging and branching is still unclear, it certainly points to a promising direction that can be explored in the context of the current work in hydraulic fracture.




FIGURE 4.14. Edge crack specimen.




FIGURE 4.15. (a) Initial crack; (b) Final damage path.

5

Conclusions and Future Work

This is the conclusion and suggestions for future work.

5.1 Concluding Remarks

This manuscript examines various models for phase-field fracture incorporating pressure loads on diffuse crack faces. This includes the analysis of a new formulation that can be obtained by assuming that the pressure load does not act on the virtual extension of a crack, or alternatively through a careful accounting in the minimization procedure. The new formulation is referred to as the “unloaded virtual crack formulation” (UVC). In order to verify the accuracy of the various models for propagating cracks, a new form of the J-Integral for pressurized cracks in the phase-field context is derived.

The (UVC) formulation proposed herein allows for a unified treatment of crack nucleation and propagation in scenarios involving either brittle or cohesive fracture, and provides for better accuracy in some problems compared to existing formulations of the (LVC) type. As it allows for the use of the same governing equation for the damage parameter, its computational implementation within existing phase-field

solvers is also simpler. In future work, its applicability to problems involving plastic deformation and strength-based fracture nucleation will be studied. In addition to that, modifications to accelerate the convergence of the model with respect to the phase-field parameter ℓ will also be considered.

5.2 Acknowledgments

The partial support of A. Costa and J.E. Dolbow by the National Science Foundation, through grant CMMMI-1933367 to Duke University, is gratefully acknowledged. Author T. Hu gratefully acknowledges the support of Argonne National Laboratory. Argonne National Laboratory is managed and operated by UChicago Argonne LLC. for the U.S. Department of Energy under Contract No. DE-AC02-06CH11357.

Appendix A

Equivalence to SIF condition

In this appendix, the energy release rate for a single, straight crack under an arbitrary pressure load $p(x)$ is computed, assuming that infinitesimal crack increments are traction-free, as shown in Figure 2.2a. Griffith's criterion states that propagation should happen whenever this energy release rate, which will be denoted by G , reaches G_c . This will give rise to a condition for propagation based on the pressure distribution $p(x)$, the crack size a and Young's modulus E' ¹. The purpose of the following derivation is to demonstrate that this condition is equivalent to the stress intensity factor criterion [126].

Initially, consider the Sneddon-Lowengrub solution for the aperture of a pressure loaded crack in an infinite plate, under plane strain conditions,

$$w(x) = \frac{4a}{\pi E'} \int_0^1 p(sa) Z(x/a, s) ds \quad (\text{A.1})$$

where

¹ assuming plane strain, $E' = E/(1 - \nu^2)$

$$Z(r, s) = \log \left| \frac{\sqrt{1 - r^2} + \sqrt{1 - s^2}}{\sqrt{1 - r^2} - \sqrt{1 - s^2}} \right| \quad (\text{A.2})$$

is a convolution kernel. The work done by the pressure load is then,

$$W_p = \int_{-a}^a p w dx = \int_{-a}^a p(y) \frac{4a}{\pi E'} \int_0^1 p(sa) Z(x/a, s) ds dy. \quad (\text{A.3})$$

Clayperon's theorem [127] states that the potential energy is negative half of the work exerted in the boundary, which, in this case is only W_p . Hence

$$U = -\frac{1}{2} W_p = -\frac{1}{2} \int_{-a}^a p w dx = -\frac{4a^2}{\pi E'} \int_0^1 p(ar) \int_0^1 p(sa) Z(r, s) ds dr. \quad (\text{A.4})$$

Let's write the energy release rate, assuming that the pressure field doesn't vary as the crack advances by a small amount da . That is,

$$p^{a+da}(x) = \begin{cases} p^a(x), & \text{if } x \leq a \\ 0, & \text{if } a \leq x \leq a + da \end{cases} \quad (\text{A.5})$$

$$dU = U(a + da, p^{a+da}) - U(a + da, p^a), \quad (\text{A.6})$$

$$\begin{aligned} dU = -\frac{4}{\pi E'} \int_0^{a+da} p^{a+da}(x) \int_0^{a+da} p^{a+da}(y) Z\left(\frac{x}{a+da}, \frac{y}{a+da}\right) dy dx \\ + \frac{4}{\pi E'} \int_0^a p^a(x) \int_0^a p^a(y) Z(x/a, y/a) dy dx. \end{aligned} \quad (\text{A.7})$$

Using the definition of p^{a+da} given above,

$$dU = -\frac{4}{\pi E'} \int_0^a p^a(x) \int_0^a p^a(y) \left(Z\left(\frac{x}{a+da}, \frac{y}{a+da}\right) - Z(x/a, y/a) \right) dy dx. \quad (\text{A.8})$$

By symmetry, both tips of the crack propagate with the same energy release rate, so, one can write,

$$2G = -\frac{dU}{da} = \frac{4}{\pi E'} \int_0^a p^a(x) \int_0^a p^a(y) \frac{1}{da} \left(Z\left(\frac{x}{a+da}, \frac{y}{a+da}\right) - Z(x/a, y/a) \right) dy dx. \quad (\text{A.9})$$

The term between parenthesis can be re-written as,

$$\begin{aligned} Z\left(\frac{x}{a+da}, \frac{y}{a+da}\right) - Z(x/a, y/a) &= \\ \log \left| \frac{\sqrt{(a+da)^2 - x^2} + \sqrt{(a+da)^2 - y^2}}{\sqrt{(a+da)^2 - x^2} - \sqrt{(a+da)^2 - y^2}} \right| - \log \left| \frac{\sqrt{a^2 - x^2} + \sqrt{a^2 - y^2}}{\sqrt{a^2 - x^2} - \sqrt{a^2 - y^2}} \right| \\ &= \log \left| \frac{\sqrt{(a+da)^2 - x^2} + \sqrt{(a+da)^2 - y^2}}{\sqrt{a^2 - x^2} + \sqrt{a^2 - y^2}} \right| \\ &\quad - \log \left| \frac{\sqrt{(a+da)^2 - x^2} - \sqrt{(a+da)^2 - y^2}}{\sqrt{a^2 - x^2} - \sqrt{a^2 - y^2}} \right|. \quad (\text{A.10}) \end{aligned}$$

The second term contains a singularity, which can be removed if one re-writes it as,

$$\begin{aligned}
& \log \left| \frac{\sqrt{(a+da)^2 - x^2} - \sqrt{(a+da)^2 - y^2}}{\sqrt{a^2 - x^2} - \sqrt{a^2 - y^2}} \right| = \\
& \quad \log \left| \frac{\sqrt{(a+da)^2 - x^2} - \sqrt{(a+da)^2 - y^2}}{\sqrt{a^2 - x^2} - \sqrt{a^2 - y^2}} \right. \\
& \quad \times \frac{\sqrt{(a+da)^2 - x^2} + \sqrt{(a+da)^2 - y^2}}{\sqrt{a^2 - x^2} + \sqrt{a^2 - y^2}} \\
& \quad \times \frac{\sqrt{a^2 - x^2} + \sqrt{a^2 - y^2}}{\sqrt{(a+da)^2 - x^2} + \sqrt{(a+da)^2 - y^2}} \left. \right| \\
& = \log \left| \frac{(a+da)^2 - x^2 - (a+da)^2 + y^2}{a^2 - x^2 - a^2 + y^2} \right. \\
& \quad \times \frac{\sqrt{a^2 - x^2} + \sqrt{a^2 - y^2}}{\sqrt{(a+da)^2 - x^2} + \sqrt{(a+da)^2 - y^2}} \left. \right| \\
& = -\log \left| \frac{\sqrt{(a+da)^2 - x^2} + \sqrt{(a+da)^2 - y^2}}{\sqrt{a^2 - x^2} + \sqrt{a^2 - y^2}} \right|. \quad (\text{A.11})
\end{aligned}$$

This expression can be plugged back into (A.10) to obtain,

$$\begin{aligned}
& Z\left(\frac{x}{a+da}, \frac{y}{a+da}\right) - Z(x/a, y/a) = \\
& \log \left| \frac{\sqrt{(a+da)^2 - x^2} + \sqrt{(a+da)^2 - y^2}}{\sqrt{(a+da)^2 - x^2} - \sqrt{(a+da)^2 - y^2}} \right| - \log \left| \frac{\sqrt{a^2 - x^2} + \sqrt{a^2 - y^2}}{\sqrt{a^2 - x^2} - \sqrt{a^2 - y^2}} \right| \\
& = 2 \log \left| \frac{\sqrt{(a+da)^2 - x^2} + \sqrt{(a+da)^2 - y^2}}{\sqrt{a^2 - x^2} + \sqrt{a^2 - y^2}} \right|. \quad (\text{A.12})
\end{aligned}$$

Hence,

$$\begin{aligned}
& \frac{1}{da} \left(Z\left(\frac{x}{a+da}, \frac{y}{a+da}\right) - Z(x/a, y/a) \right) \\
& = \frac{2}{da} \log \left| \frac{\sqrt{(a+da)^2 - x^2} + \sqrt{(a+da)^2 - y^2}}{\sqrt{a^2 - x^2} + \sqrt{a^2 - y^2}} \right|. \quad (\text{A.13})
\end{aligned}$$

Now, the terms in the numerator can be expanded with a Taylor series,

$$\sqrt{(a + da)^2 - x^2} = \sqrt{a^2 - x^2} + \frac{a}{\sqrt{a^2 - x^2}} da + O(da^2), \quad (\text{A.14})$$

leading to,

$$\begin{aligned} \frac{1}{da} \left(Z\left(\frac{x}{a + da}, \frac{y}{a + da}\right) - Z(x/a, y/a) \right) &= \\ \frac{2}{da} \log \left| \frac{\sqrt{a^2 - x^2} + \frac{a}{\sqrt{a^2 - x^2}} da + O(da^2)}{\sqrt{a^2 - x^2} + \sqrt{a^2 - y^2}} \right. \\ &\quad \left. + \frac{\sqrt{a^2 - y^2} + \frac{a}{\sqrt{a^2 - y^2}} da + O(da^2)}{\sqrt{a^2 - x^2} + \sqrt{a^2 - y^2}} \right|, \quad (\text{A.15}) \end{aligned}$$

which, after using a Taylor expansion, simplifies to,

$$\frac{1}{da} \left(Z\left(\frac{x}{a + da}, \frac{y}{a + da}\right) - Z(x/a, y/a) \right) = \frac{2a}{\sqrt{a^2 - x^2} \sqrt{a^2 - y^2}} + O(da). \quad (\text{A.16})$$

Now, we can finally go back to the energy release rate,

$$\begin{aligned} 2G &= -\frac{dU}{da} = \frac{4}{\pi E'} \int_0^a p^a(x) \int_0^a p^a(y) \frac{2a}{\sqrt{a^2 - x^2} \sqrt{a^2 - y^2}} dy dx = \\ &\quad \frac{8a}{\pi E'} \int_0^1 \frac{p^a(ar)}{\sqrt{1 - r^2}} \int_0^1 \frac{p^a(as)}{\sqrt{1 - s^2}} ds dr = \frac{8a}{\pi E'} \left(\int_0^1 \frac{p^a(as)}{\sqrt{1 - s^2}} ds \right)^2. \quad (\text{A.17}) \end{aligned}$$

From [128], the stress intensity factor under these same conditions is,

$$K_I = 2\sqrt{\frac{a}{\pi}} \left(\int_0^1 \frac{p^a(as)}{\sqrt{1 - s^2}} ds \right) \quad (\text{A.18})$$

From a simple inspection, one can see that $G = K_I^2/E'$, which guarantees the equivalence of the energy release rate criterion under the assumption in Figure 2.2a and

the stress intensity factor condition. If instead, one assumes that the pressure load in the vicinity of a propagating crack behaves as in Figure 2.2b, this equivalence between the energetic criterion and the stress intensity factor may be violated.

Bibliography

- [1] Blaise Bourdin, Chukwudi P Chukwudzie, Keita Yoshioka, et al. A variational approach to the numerical simulation of hydraulic fracturing. In *SPE Annual Technical Conference and Exhibition*. Society of Petroleum Engineers, 2012.
- [2] C. Landis and Z. Wilson. The Phase-field Modeling of Hydraulic Fracture. In *workshop: Variational Models of Fracture*, 2016. <http://www.birs.ca/workshops//2016/16w5090/files/Banff-Landis.pdf>, visited on 2022-05-05.
- [3] J Adachi, E Siebrits, A Peirce, and J Desroches. Computer simulation of hydraulic fractures. *International Journal of Rock Mechanics and Mining Sciences*, 44(5):739–757, 2007.
- [4] Eia data on u.s. gas sources, 2022. URL <https://www.eia.gov/tools/faqs/faq.php?id=847&t=6>.
- [5] Eia data on u.s. oil sources, 2022. URL <https://www.eia.gov/tools/faqs/faq.php?id=907&t=8>.
- [6] Peng-Zhi Pan, Jonny Rutqvist, Xia-Ting Feng, and Fei Yan. Tough–rdca modeling of multiple fracture interactions in caprock during co2 injection into a deep brine aquifer. *Computers & Geosciences*, 65:24–36, 2014.
- [7] Zissis Moschovidis, Ronald Steiger, Richard Peterson, Norm Warpinski, Chris Wright, Ed Chesney, Joe Hagan, Ahmed Abou-Sayed, Richard Keck, Matt Frankl, Carole Fleming, Steve Wolhart, Buddy McDaniel, Allen Sinor, Steinar Ottesen, Lynn Miller, Reid Beecher, John Dudley, Dick Zinno, and Oktay Akhmedov. The Mounds Drill-Cuttings Injection Field Experiment: Final Results and Conclusions. In *IADC/SPE Drilling Conference*. OnePetro, February 2000. doi: 10.2118/59115-MS. URL <https://dx.doi.org/10.2118/59115-MS>.
- [8] J. Desroches. Stress testing with the micro-hydraulic fracturing technique: Focus on fracture reopening. In *The 35th US Symposium on Rock Mechanics (USRMS)*. OnePetro, June 1995. URL <https://dx.doi.org/>.

- [9] J Desroches and M Thiercelin. Modelling the propagation and closure of micro-hydraulic fractures. In *International Journal of Rock Mechanics and Mining Sciences & Geomechanics Abstracts*, volume 30, pages 1231–1234. Elsevier, 1993.
- [10] Mark Board, Tony Rorke, Gary Williams, and Nick Gay. Fluid injection for rockburst control in deep mining. In *The 33rd US Symposium on Rock Mechanics (USRMS)*. OnePetro, June 1992. URL <https://dx.doi.org/>.
- [11] Xi Zhang, Emmanuel Detournay, and Rob Jeffrey. Propagation of a penny-shaped hydraulic fracture parallel to the free-surface of an elastic half-space. *International Journal of Fracture*, 115(2):125–158, May 2002. ISSN 1573-2673. doi: 10.1023/A:1016345906315. URL <https://doi.org/10.1023/A:1016345906315>.
- [12] Permeability and stress in crystalline rocks - Banks - 1996 - Terra Nova - Wiley Online Library, 1996. URL <https://onlinelibrary.wiley.com/doi/abs/10.1111/j.1365-3121.1996.tb00751.x>.
- [13] C. Less and N. Andersen. Hydrofracture: State Of The Art In South Africa. *Applied Hydrogeology*, 2(2):59–63, 1994. ISSN 1435-0157. doi: 10.1007/s100400050050.
- [14] TK Perkins and L Re Kern. Widths of hydraulic fractures. *Journal of Petroleum Technology*, 13(09):937–949, 1961.
- [15] IN Sneddon and HA Elliot. The opening of a griffith crack under internal pressure. *Quarterly of Applied Mathematics*, 4(3):262–267, 1946.
- [16] RP Nordgren. Propagation of a vertical hydraulic fracture. *Society of Petroleum Engineers Journal*, 12(04):306–314, 1972.
- [17] A Khristianovic Zheltov. 3. formation of vertical fractures by means of highly viscous liquid. In *4th World Petroleum Congress*. OnePetro, 1955.
- [18] J Geertsma and F De Klerk. A rapid method of predicting width and extent of hydraulically induced fractures. *Journal of Petroleum Technology*, 21(12):1571–1581, 1969.
- [19] J Desroches, E Detournay, B Lenoach, P Papanastasiou, John Richard Anthony Pearson, M Thiercelin, and Ailan Cheng. The crack tip region in hydraulic fracturing. *Proceedings of the Royal Society of London. Series A: Mathematical and Physical Sciences*, 447(1929):39–48, 1994.
- [20] B Lenoach. The crack tip solution for hydraulic fracturing in a permeable solid. *Journal of the Mechanics and Physics of Solids*, 43(7):1025–1043, 1995.

- [21] E Detournay, JI Adachi, DI Garagash, et al. Asymptotic and intermediate asymptotic behavior near the tip of a fluid-driven fracture propagating in a permeable elastic medium. *Structural Integrity and Fracture*, pages 9–18, 2002.
- [22] E Detournay and DI Garagash. The near-tip region of a fluid-driven fracture propagating in a permeable elastic solid. *Journal of Fluid Mechanics*, 494:1–32, 2003.
- [23] D Garagash and E Detournay. The tip region of a fluid-driven fracture in an elastic medium. *J. Appl. Mech.*, 67(1):183–192, 2000.
- [24] Emmanuel Detournay. Propagation regimes of fluid-driven fractures in impermeable rocks. *International Journal of Geomechanics*, 4(1):35–45, 2004.
- [25] JI Adachi and E Detournay. Self-similar solution of a plane-strain fracture driven by a power-law fluid. *International Journal for Numerical and Analytical Methods in Geomechanics*, 26(6):579–604, 2002.
- [26] R Carbonell, Jean Desroches, and Emmanuel Detournay. A comparison between a semi-analytical and a numerical solution of a two-dimensional hydraulic fracture. *International journal of solids and structures*, 36(31-32):4869–4888, 1999.
- [27] AA Savitski and E Detournay. Propagation of a penny-shaped fluid-driven fracture in an impermeable rock: asymptotic solutions. *International journal of solids and structures*, 39(26):6311–6337, 2002.
- [28] Dmitry I. Garagash and Emmanuel Detournay. Plane-Strain Propagation of a Fluid-Driven Fracture: Small Toughness Solution. *Journal of Applied Mechanics*, 72(6):916–928, 04 2005. ISSN 0021-8936. doi: 10.1115/1.2047596.
- [29] Mark W McClure and Charles A Kang. A Three-Dimensional Reservoir, Wellbore, and Hydraulic Fracturing simulator that is Compositional and Thermal, Tracks Proppant and Water Solute Transport, Includes Non-Darcy and Non-Newtonian Flow, and Handles Fracture Closure. In *SPE Reservoir Simulation Conference*. OnePetro, 2017.
- [30] M. McClure, C. Kang, S. Medam, and C. Hewson. ResFrac technical writeup. *arXiv preprint arXiv:1804.02092*, 2018.
- [31] Itasca Consulting Group, Inc. Xsite, ver. 3.0. minneapolis: Itasca., 2019. Accessed June 10th, 2023. <https://www.itascacg.com/software/XSite>.
- [32] Schlumberger Ltd. Kinetix reservoir-centric stimulation-to-production software., 2021. Accessed June 10th, 2023. <https://www.slb.com/completions/stimulation/stimulation-optimization/kinetix-reservoir-centric-stimulation-to-production-software>.

- [33] Schlumberger USTC. Kinetix for petrel 2020.1., 2020. Accessed June 10th, 2023. <https://www.ocean.slb.com/en/plug-ins/plugindetails?ProductId=PMPW-B1>.
- [34] Bin Chen, Beatriz Ramos Barboza, Yanan Sun, Jie Bai, Hywel R Thomas, Martin Dutko, Mark Cottrell, and Chenfeng Li. A review of hydraulic fracturing simulation. *Archives of Computational Methods in Engineering*, pages 1–58, 2021.
- [35] R. R. Settgast, S. M. Johnson, P. Fu, S. D. C. Walsh, and F. Ryerson. Simulation of hydraulic fracture networks in three dimensions. Technical report, Lawrence Livermore National Lab.(LLNL), Livermore, CA (United States), 2012.
- [36] R. R. Settgast, S. M. Johnson, P. Fu, and S. D. C. Walsh. Simulation of hydraulic fracture networks in three dimensions utilizing massively parallel computing resources. In *SPE/AAPG/SEG Unconventional Resources Technology Conference*. OnePetro, 2014.
- [37] Randolph R Settgast, Pengcheng Fu, Stuart DC Walsh, Joshua A White, Chandrasekhar Annavarapu, and Frederick J Ryerson. A fully coupled method for massively parallel simulation of hydraulically driven fractures in 3-dimensions. *International Journal for Numerical and Analytical Methods in Geomechanics*, 41(5):627–653, 2017.
- [38] H. Zia and B. Lecampion. PyFrac: A planar 3D hydraulic fracture simulator. *Comput. Phys. Commun.*, 255:107368, 2020.
- [39] P Gupta and Carlos Armando Duarte. Simulation of non-planar three-dimensional hydraulic fracture propagation. *International Journal for Numerical and Analytical Methods in Geomechanics*, 38(13):1397–1430, 2014.
- [40] P Gupta and Carlos Armando Duarte. Coupled hydromechanical-fracture simulations of nonplanar three-dimensional hydraulic fracture propagation. *International Journal for Numerical and Analytical Methods in Geomechanics*, 42(1):143–180, 2018.
- [41] Huiying Tang, Shihao Wang, Ruihan Zhang, Sanbai Li, Liehui Zhang, and Yu-Shu Wu. Analysis of stress interference among multiple hydraulic fractures using a fully three-dimensional displacement discontinuity method. *Journal of Petroleum Science and Engineering*, 179:378–393, 2019.
- [42] Sanbai Li, Abbas Firoozabadi, and Dongxiao Zhang. Hydromechanical modeling of nonplanar three-dimensional fracture propagation using an iteratively coupled approach. *Journal of Geophysical Research: Solid Earth*, 125(8):e2020JB020115, 2020.

- [43] Sanbai Li and Dongxiao Zhang. Development of 3-d curved fracture swarms in shale rock driven by rapid fluid pressure buildup: Insights from numerical modeling. *Geophysical Research Letters*, 48(8):e2021GL092638, 2021.
- [44] Hadi Hajibeygi, Dimitris Karvounis, and Patrick Jenny. A hierarchical fracture model for the iterative multiscale finite volume method. *Journal of Computational Physics*, 230(24):8729–8743, 2011.
- [45] Gilles A Francfort and J-J Marigo. Revisiting brittle fracture as an energy minimization problem. *Journal of the Mechanics and Physics of Solids*, 46(8):1319–1342, 1998.
- [46] Blaise Bourdin, Gilles A Francfort, and Jean-Jacques Marigo. Numerical experiments in revisited brittle fracture. *Journal of the Mechanics and Physics of Solids*, 48(4):797–826, 2000.
- [47] Alain Karma, David A Kessler, and Herbert Levine. Phase-field model of mode iii dynamic fracture. *Physical Review Letters*, 87(4):045501, 2001.
- [48] Alan Arnold Griffith. Vi. the phenomena of rupture and flow in solids. *Philosophical Transactions of the Royal Society of London. Series A*, 221(582-593):163–198, 1921.
- [49] Yousef Heider. A review on phase-field modeling of hydraulic fracturing. *Engineering Fracture Mechanics*, 253:107881, 2021.
- [50] Mary F Wheeler, Thomas Wick, and W Wollner. An augmented-lagrangian method for the phase-field approach for pressurized fractures. *Computer Methods in Applied Mechanics and Engineering*, 271:69–85, 2014.
- [51] Christian Miehe, Steffen Mauthe, and Stephan Teichtmeister. Minimization principles for the coupled problem of darcy–biot-type fluid transport in porous media linked to phase field modeling of fracture. *Journal of the Mechanics and Physics of Solids*, 82:186–217, 2015.
- [52] Christian Miehe and Steffen Mauthe. Phase field modeling of fracture in multi-physics problems. part iii. crack driving forces in hydro-poro-elasticity and hydraulic fracturing of fluid-saturated porous media. *Computer Methods in Applied Mechanics and Engineering*, 304:619–655, 2016.
- [53] A Mikelić, Mary F Wheeler, and Thomas Wick. Phase-field modeling of a fluid-driven fracture in a poroelastic medium. *Computational Geosciences*, 19(6):1171–1195, 2015.
- [54] Andro Mikelić, Mary F Wheeler, and Thomas Wick. A phase-field method for propagating fluid-filled fractures coupled to a surrounding porous medium. *Multiscale Modeling & Simulation*, 13(1):367–398, 2015.

- [55] Zachary A Wilson and Chad M Landis. Phase-field modeling of hydraulic fracture. *Journal of the Mechanics and Physics of Solids*, 96:264–290, 2016.
- [56] H. C. Brinkman. A calculation of the viscous force exerted by a flowing fluid on a dense swarm of particles. *Flow Turbul. Combust.*, 1(1):27–34, 1949.
- [57] Chukwudi Chukwudozie, Blaise Bourdin, and Keita Yoshioka. A variational phase-field model for hydraulic fracturing in porous media. *Computer Methods in Applied Mechanics and Engineering*, 347:957–982, 2019.
- [58] Bin Chen, Yanan Sun, Beatriz R Barboza, Andrew R Barron, and Chenfeng Li. Phase-field simulation of hydraulic fracturing with a revised fluid model and hybrid solver. *Engineering Fracture Mechanics*, 229:106928, 2020.
- [59] Keita Yoshioka, Dmitri Naumov, and Olaf Kolditz. On crack opening computation in variational phase-field models for fracture. *Computer Methods in Applied Mechanics and Engineering*, 369:113210, 2020.
- [60] Timo Heister, Mary F Wheeler, and Thomas Wick. A primal-dual active set method and predictor-corrector mesh adaptivity for computing fracture propagation using a phase-field approach. *Computer Methods in Applied Mechanics and Engineering*, 290:466–495, 2015.
- [61] Sanghyun Lee, Mary F Wheeler, and Thomas Wick. Iterative coupling of flow, geomechanics and adaptive phase-field fracture including level-set crack width approaches. *Journal of Computational and Applied Mathematics*, 314:40–60, 2017.
- [62] Timo Heister and Thomas Wick. pfm-cracks: A parallel-adaptive framework for phase-field fracture propagation. *Software Impacts*, 6:100045, 2020.
- [63] Abhinav Gupta, U.~Meenu Krishnan, Tushar Kanti Mandal, Rajib Chowdhury, and Vinh Phu Nguyen. An adaptive mesh refinement algorithm for phase-field fracture models: Application to brittle, cohesive, and dynamic fracture. *Comput. Methods Appl. Mech. Engrg.*, 399:115347, 2022.
- [64] Brice Lecampion, Andrew Bunger, and Xi Zhang. Numerical methods for hydraulic fracture propagation: a review of recent trends. *Journal of Natural Gas Science and Engineering*, 49:66–83, 2018.
- [65] Rudy JM Geelen, Yingjie Liu, John E Dolbow, and Antonio Rodríguez-Ferran. An optimization-based phase-field method for continuous-discontinuous crack propagation. *International Journal for Numerical Methods in Engineering*, 116(1):1–20, 2018.

- [66] Bianca Giovanardi, Anna Scotti, and Luca Formaggia. A hybrid xfem–phase field (xfield) method for crack propagation in brittle elastic materials. *Computer Methods in Applied Mechanics and Engineering*, 320:396–420, 2017.
- [67] Alba Muixí, Onofre Marco, Antonio Rodríguez-Ferran, and Sonia Fernández-Méndez. A combined xfem phase-field computational model for crack growth without remeshing. *Computational Mechanics*, 67(1):231–249, 2021.
- [68] Kangan Li, Antonio Rodríguez-Ferran, and Guglielmo Scovazzi. A blended shifted-fracture/phase-field framework for sharp/diffuse crack modeling. *International Journal for Numerical Methods in Engineering*, 124(4):998–1030, 2023.
- [69] Nicolas Moës, John Dolbow, and Ted Belytschko. A finite element method for crack growth without remeshing. *International Journal for Numerical Methods in Engineering*, 46(1):131–150, 1999.
- [70] Yuan Sun, Zhiyuan Liu, and Xuhai Tang. A hybrid femm-phase field method for fluid-driven fracture propagation in three dimension. *Engineering Analysis with Boundary Elements*, 113:40–54, 2020.
- [71] Samuel Burbulla, Luca Formaggia, Christian Rohde, and Anna Scotti. Modeling fracture propagation in poro-elastic media combining phase-field and discrete fracture models. *Computer Methods in Applied Mechanics and Engineering*, 403:115699, 2023.
- [72] JiaNing Zhang, Hao Yu, WenLong Xu, ChengSi Lv, Marembo Micheal, Fang Shi, and HengAn Wu. A hybrid numerical approach for hydraulic fracturing in a naturally fractured formation combining the xfem and phase-field model. *Engineering Fracture Mechanics*, 271:108621, 2022.
- [73] Tianchen Hu. *A Variational Framework for Phase-Field Fracture Modeling with Applications to Fragmentation, Desiccation, Ductile Failure, and Spallation*. PhD thesis, Duke University, 2021.
- [74] Eric Lorentz, Sam Cuvilliez, and Kyrylo Kazymyrenko. Convergence of a gradient damage model toward a cohesive zone model. *Comptes Rendus Mécanique*, 339(1):20–26, 2011.
- [75] Rudy JM Geelen, Yingjie Liu, Tianchen Hu, Michael R Tupek, and John E Dolbow. A phase-field formulation for dynamic cohesive fracture. *Computer Methods in Applied Mechanics and Engineering*, 348:680–711, 2019.
- [76] Jian-Ying Wu. A unified phase-field theory for the mechanics of damage and quasi-brittle failure. *Journal of the Mechanics and Physics of Solids*, 103:72–99, 2017.

- [77] Andro Mikelić, Mary F Wheeler, and Thomas Wick. A quasi-static phase-field approach to pressurized fractures. *Nonlinearity*, 28(5):1371, 2015.
- [78] Christian Peco, Wei Chen, Yingjie Liu, MM Bandi, John E Dolbow, and Eliot Fried. Influence of surface tension in the surfactant-driven fracture of closely-packed particulate monolayers. *Soft Matter*, 13(35):5832–5841, 2017.
- [79] Wen Jiang, Tianchen Hu, Larry K Aagesen, Sudipta Biswas, and Kyle A Gamble. A phase-field model of quasi-brittle fracture for pressurized cracks: Application to UO₂ high-burnup microstructure fragmentation. *Theoretical and Applied Fracture Mechanics*, 119:103348, 2022.
- [80] Paul Sicsic and Jean-Jacques Marigo. From gradient damage laws to griffith's theory of crack propagation. *Journal of Elasticity*, 113(1):55–74, 2013.
- [81] Roberto Ballarini and Gianni Royer-Carfagni. Closed-path j-integral analysis of bridged and phase-field cracks. *Journal of Applied Mechanics*, 83(6), 2016.
- [82] MZ Hossain, C-J Hsueh, B Bourdin, and K Bhattacharya. Effective toughness of heterogeneous media. *Journal of the Mechanics and Physics of Solids*, 71:15–32, 2014.
- [83] Fang Zhong Li, C Fong Shih, and A Needleman. A comparison of methods for calculating energy release rates. *Engineering Fracture Mechanics*, 21(2):405–421, 1985.
- [84] CF Shih, B Moran, and T Nakamura. Energy release rate along a three-dimensional crack front in a thermally stressed body. *International Journal of Fracture*, 30(2):79–102, 1986.
- [85] Hanen Amor, Jean-Jacques Marigo, and Corrado Maurini. Regularized formulation of the variational brittle fracture with unilateral contact: Numerical experiments. *Journal of the Mechanics and Physics of Solids*, 57(8):1209–1229, 2009.
- [86] Christian Miehe, Martina Hofacker, and Fabian Welschinger. A phase field model for rate-independent crack propagation: Robust algorithmic implementation based on operator splits. *Computer Methods in Applied Mechanics and Engineering*, 199(45-48):2765–2778, 2010.
- [87] Emmanuel Detournay. Mechanics of hydraulic fractures. *Annual Review of Fluid Mechanics*, 48:311–339, 2016.
- [88] Andrew P Bunger, Emmanuel Detournay, and Dmitry I Garagash. Toughness-dominated hydraulic fracture with leak-off. *International Journal of Fracture*, 134(2):175–190, 2005.

- [89] Tianchen Hu, Brandon Talamini, Andrew J Stershic, Michael R Tupek, and John E Dolbow. A variational phase-field model for ductile fracture with coalescence dissipation. *Computational Mechanics*, 68(2):311–335, 2021.
- [90] Wen Jiang, Tianchen Hu, Larry K Aagesen, and Yongfeng Zhang. Three-dimensional phase-field modeling of porosity dependent intergranular fracture in UO₂. *Computational Materials Science*, 171:109269, 2020.
- [91] Eric Lorentz and V Godard. Gradient damage models: Toward full-scale computations. *Computer Methods in Applied Mechanics and Engineering*, 200(21–22):1927–1944, 2011.
- [92] James R Rice et al. Mathematical analysis in the mechanics of fracture. *Fracture: an advanced treatise*, 2:191–311, 1968.
- [93] James R Rice. A path independent integral and the approximate analysis of strain concentration by notches and cracks. *Journal of Applied Mechanics*, 35(2):379–386, 1968.
- [94] A. Karlsson and J. Backlund. J-integral at loaded crack surfaces. *International Journal of Fracture*, 14:311–318, 1978.
- [95] W. Karush. Minima of functions of several variables with inequalities as side constraints. *M. Sc. Dissertation. Dept. of Mathematics, Univ. of Chicago*, 1939.
- [96] H. W. Kuhn and A. W. Tucker. Nonlinear Programming. In *Proceedings of the Second Berkeley Symposium on Mathematical Statistics and Probability*, pages 481–492. University of California Press, 1951.
- [97] Tianchen Hu, Johann Guilleminot, and John E Dolbow. A phase-field model of fracture with frictionless contact and random fracture properties: Application to thin-film fracture and soil desiccation. *Computer Methods in Applied Mechanics and Engineering*, 368:113106, 2020.
- [98] Tianchen Hu. RACCOON - a parallel finite-element code specialized in phase-field for fracture, 2020. URL <https://hugary1995.github.io/raccoon/index.html>.
- [99] Derek Gaston, Chris Newman, Glen Hansen, and Damien Lebrun-Grandjean. Moose: A parallel computational framework for coupled systems of nonlinear equations. *Nuclear Engineering and Design*, 239(10):1768–1778, 2009.
- [100] Cody J Permann, Derek R Gaston, David Andrs, Robert W Carlsen, Fande Kong, Alexander D Lindsay, Jason M Miller, John W Peterson, Andrew E Slaughter, Roy H Stogner, et al. Moose: Enabling massively parallel multi-physics simulation. *SoftwareX*, 11:100430, 2020.

- [101] Alexander D Lindsay, Derek R Gaston, Cody J Permann, Jason M Miller, David Andrš, Andrew E Slaughter, Fande Kong, Joshua Hansel, Robert W Carlsen, Casey Icenhour, et al. 2.0-moose: Enabling massively parallel multi-physics simulation. *SoftwareX*, 20:101202, 2022.
- [102] Ferdinand Stoeckhert, Michael Molenda, Sebastian Brenne, and Michael Alber. Fracture propagation in sandstone and slate—laboratory experiments, acoustic emissions and fracture mechanics. *Journal of Rock Mechanics and Geotechnical Engineering*, 7(3):237–249, 2015.
- [103] N. Shauer and C. A. Duarte. A three-dimensional Generalized Finite Element Method for simultaneous propagation of multiple hydraulic fractures from a wellbore. *Eng. Fract. Mech.*, 265:108360, 2022.
- [104] Matteo Cusini, Joshua A White, Nicola Castelletto, and Randolph R Settgast. Simulation of coupled multiphase flow and geomechanics in porous media with embedded discrete fractures. *International Journal for Numerical and Analytical Methods in Geomechanics*, 45(5):563–584, 2021.
- [105] R.A. Cook and M.L. Oyen. On the failure and fracture of hydrogels for cartilage replacement. *Journal of Physics: Materials*, 4(2):021001, 2021.
- [106] Maurice A Biot. General theory of three-dimensional consolidation. *Journal of Applied Physics*, 12(2):155–164, 1941.
- [107] F. Erdogan and G. C. Sih. On the Crack Extension in Plates Under Plane Loading and Transverse Shear. *Jour. of Basic Eng.*, 85(4):519–525, 12 1963. ISSN 0021-9223.
- [108] JG Williams and PD Ewing. Fracture under complex stress—the angled crack problem. *Int. J. of Frac. Mech.*, 8(4):441–446, 1972.
- [109] I Finnie and A Saith. A note on the angled crack problem and the directional stability of cracks. *Int. J. of Fracture*, 9(4):484–486, 1973.
- [110] PD Ewing, JL Swedlow, and JG Williams. Further results on the angled crack problem. *Int. J. of Fracture*, 12(1):85–93, 1976.
- [111] B Cotterell. On brittle fracture paths. *Int. J. of Frac. Mech.*, 1(2):96–103, 1965.
- [112] MA Hussain, L Pu, and J Underwood. Strain energy release rate for. In *Proceedings of the 1973 National Symposium on Fracture Mechanics, University of Maryland, College Park, Md., 27-29 Aug. 1973*, volume 559, page 2, 1974.
- [113] Bo He and Xiaoying Zhuang. Modeling hydraulic cracks and inclusion interaction using xfem. *Underground Space*, 3(3):218–228, 2018.

- [114] Youngho Jang, Gayoung Park, Seoyoon Kwon, and Baehyun Min. Analysis of hydraulic fracture propagation using a mixed mode and a uniaxial strain model considering geomechanical properties in a naturally fractured shale reservoir. *Geofluids*, 2020, 2020.
- [115] Benjamin E Grossman-Ponemon and Adrian J Lew. An algorithm for the simulation of curvilinear plane-strain and axisymmetric hydraulic fractures with lag using the universal meshes. *Int. J. Numer. Anal. Methods Geomech.*, 43(6):1251–1278, 2019.
- [116] Luigi Ambrosio and Vincenzo Maria Tortorelli. Approximation of functional depending on jumps by elliptic functional via t-convergence. *Communications on Pure and Applied Mathematics*, 43(8):999–1036, 1990.
- [117] Christian Linder and Francisco Armero. Finite elements with embedded strong discontinuities for the modeling of failure in solids. *International Journal for Numerical Methods in Engineering*, 72(12):1391–1433, 2007.
- [118] Seong H Lee, MF Lough, and CL Jensen. Hierarchical modeling of flow in naturally fractured formations with multiple length scales. *Water Resources Research*, 37(3):443–455, 2001.
- [119] David Santillán, Ruben Juanes, and Luis Cueto-Felgueroso. Phase field model of hydraulic fracturing in poroelastic media: Fracture propagation, arrest, and branching under fluid injection and extraction. *Journal of Geophysical Research: Solid Earth*, 123(3):2127–2155, 2018.
- [120] Hu Tianchen, Johann Guilleminot, and John Dolbow. A phase-field model of fracture with frictionless contact and random fracture properties: Application to thin-film fracture and soil desiccation. *Computer Methods in Applied Mechanics and Engineering*, 368, 2020.
- [121] K. Pham, H. Amor, J.-J. Marigo, and C. Maurini. Gradient damage models and their use to approximate brittle fracture. *Int. J. Damage Mech.*, 20(4):618–652, 2011.
- [122] Blaise Bourdin, Gilles A Francfort, and Jean-Jacques Marigo. The variational approach to fracture. *Journal of elasticity*, 91(1-3):5–148, 2008.
- [123] Elena Tamayo-Mas and Antonio Rodríguez-Ferran. A medial-axis-based model for propagating cracks in a regularised bulk. *Internat. J. Numer. Methods Engrg.*, 101(7):489–520, 2015.
- [124] M. Isida. Analysis of stress intensity factors for the tension of a centrally cracked strip with stiffened edges. *Eng. Fract. Mech.*, 5(3):647–665, 1973.

- [125] T. Jin, J. A. White, and R. R. Settgast. A robust finite element-finite volume strategy for viscosity-dominated hydraulic fracture propagation using asymptotic tip enrichment. *Int. J. Numer. Anal. Methods Geomech.*, 2022.
- [126] G. R. Irwin. Analysis of Stresses and Strains Near the End of a Crack Traversing a Plate. *Journal of Applied Mechanics*, 24(3):361–364, 1957.
- [127] R. Fosdick and L. Truskinovsky. About Clapeyron’s Theorem in Linear Elasticity. *Journal of Elasticity*, 72:145–172, 2003.
- [128] Zdenek P Bazant and Jaime Planas. *Fracture and size effect in concrete and other quasibrittle materials*. Routledge, 2019.

Biography

Andre Costa earned his B.S. degree in Mechanical Engineering and M.S. degree in Mathematics from Universidade Federal de Minas Gerais, in Brazil. He joined the Department of Mechanical Engineering and Materials Science at Duke University in 2018 as a graduate research assistant. His Ph.D. degree was awarded in the Fall of 2023 and he will be working as a Software Engineer at Cadence Design Systems Inc.