

Modbus RTU Live Sniffer

<

Baudrate: 19200 ▾ Protokoll: 8E1 ▾

JSON Herunterladen

[WiFi Conifuration](#)

ID Filter (0:Alle) 0 ▾

Filter setzen ▶ Start || Stopp Reset

stopped

Trigger pattern

enter 1- 16 Hex Bytes:

01 06

FF FF

["0x01", "0x06", "0x00", "0x00", "0x00", "0x00", "0x00", "0x00", "0x00", "0x00", "0x00", "0x00", "0x00", "0x00", "0x00", "0x00"]

["0xFF", "0xFF", "0x00", "0x00", "0x00", "0x00", "0x00", "0x00", "0x00", "0x00", "0x00", "0x00", "0x00", "0x00", "0x00", "0x00"]

set

Statistik-Matrix

Registertype	captured Register-Addresses	Reads	Writes	Exception
Coil	-	0	0	0
Discrete	-	0	0	0
Holding	257:6R, 261:1W	213	2	0
Input	4:15R	1033	0	819
OTHER	-	0	0	0

Status Information

Device List	Fragments	CRC Erros	NO Response	NO Request
1	0	0	1	0

Function Code Data Monitor

Time	Device	FC	Address	Data
1102841	1 ▾ set	Input 04 ▾	4 ▾ set	01 08 00 02 00 3C 00 3D 00 3E 00 2C 00 E7 00 E8 00 E9 00 01 01 90 00 00 00 00 00 00 00
1102917	1 ▾ set	Holdr 03 ▾	257 ▾ set	00 00 00 00 00 00 00 00 00 00 66 00 00
925795	1 ▾ set	Holdw 06 ▾	261 ▾ set	00 66
0	1 ▾ set	Input 04 ▾	0 ▾ set	

Chronologische Liste (11/100)

Time (ms)	Distance	Device	FC	Address	P-Type	R-Type	R / W	Length	Payload (hex)	Status
1090829	2	1	04		RESPONSE	INPUT	READ	35	CMD: 01 04 1E - DATA: 01 08 00 02 00 3C 00 3D 00 3E 00 2C 00 E7 00 E8 00 E9 00 01 01 90 00 00 00 00 00 00 00 00 - CRC: 20 3C	OK
1090898	49	1	03	257	REQUEST	HOLDING	CMD	8	CMD: 01 03 01 01 00 06 - CRC: 95 F4	OK
1090905	2	1	03		RESPONSE	HOLDING	READ	17	CMD: 01 03 0C - DATA: 00 00 00 00 00 00 00 00 00 66 00 00 - CRC: 73 6F	OK