Savannah how to

May 23, 2012

This is a short guide for using the savannah server project, while savannah should run on any OS that supports java, this guide will assume ubuntu server 11.04. Savannah has also been briefly tested on a windows machine, a few changes is required in the source code, more on this in the windows section.

Dependencies

JDOM 1.1.3

http://www.jdom.org/dist/binary/archive/jdom-1.1.3.tar.gz

Connector/J mysql JDBC driver

http://www.mysql.com/downloads/connector/j/

JUnit (only needed if you downloaded the source and want to avoid compiler warnings from junit test cases in the project

http://www.junit.org/

Tomcat 6 (can be installed from a terminal in ubuntu 12.04)

http://tomcat.apache.org/

Ubuntu server

the server needs java, mysql-server and tomcat installed, you can choose to install mysql and java during installation of the OS or install the packages afterwards. This can be done by entering the following commands in a terminal

```
sudo apt-get update
sudo apt-get install mysql-server
sudo apt-get install openjdk-6-jre
```

You can choose a different version of java if you like, however we have tested with openJDK-6, it should work just fine with oracle java(6 or 7) or openJDK-7, no guaruantees though.

Installation of externals

It is easiest to install the external libraries(JDOM, JUnit and mysql JDBC) directly on the systems jvm, do this by copying all .jar files to

```
/usr/lib/jvm/java-6-openjdk/jre/lib/ext
```

If you use a different version of java, replace "java-6-openjdk" with your version.

if you are using ubuntu server 12.04, tomcat6 can be installed by typing sudo apt-get install tomcat6

in a terminal, if using any earlier version, like 11.04 you will need to download it manually from tomcats homepage, provided in the dependencies list. and follow the installation guide on their homepage.

Source

You can check out the source code from our google code repository, use your favourit syn tool(tortoise on windows, or syn checkout on most linux distroes)

https://sw6-2012.googlecode.com/svn/branches/Group_3_Server/savannah local_name

configuration

Import the project into your favorite JAVA editor. Savannah is currently hardwired to connect to a specific database, you will need to navigate to

dk.aau.cs.giraf.savannah.server.QueryHandler.java

and change line 12 to the IP of your host machine and provide username(currently eder), password(currently 123456) and database name(currently /04). when done, export as a runnable jar and select

ServerMain (dk.aau.cs.giraf.savannah/serverMain/ServerMain.java) as launch configuration.

.jar

After exporting the jar, drop it somewhere on your server where your user has write access (/server will do just fine) open a terminal, if you have not already, cd to the directory and type

java -jar savannah.jar

Windows

If you wish to run savannah on a windows server, you will need to navigate to

dk.aau.cs.giraf.savannah.io.Configuration.java

and change line 23 and 28 to something a windows machine understands.