



OPTIONAL MODULE OF THE VIDEUS FAMILY

MULTIVIEWER

DISPLAY OUTPUT MODULE FOR MONITORING

MULTIVIEWER

The module allows you to generate SDI / HDMI outputs or also allows you to make IP TS, TS over HTTP or HLS outputs.

The module allows you to generate SDI / HDMI outputs or also allows you to make IP TS, TS over HTTP or HLS outputs. All the signals received in the system can be configured to display in one or several outputs.

When visualizing a service, you can choose to see printed stream information such as EPG, loudness in graphic form or through VU meters, subtitles, closed captions, etc.

Each image panel has tools to display metadata, turn audio on or off, send that panel to another monitor, or view it full screen. The visualization can be made up of images presented in different resolutions and framerates, and arranged in the most useful way, graphics and navigation can also be added with other screens. For the operation of this mode, custom views that apply exactly to the need can be configured.

FEATURES

- Visualization of multiple audio and video streams.
- Outputs with more than 64 simultaneous PIPs.
- Scalable systems combining multiple equipment.
- PIP's with Round Robin.
- Visualization of QoS and QoE alarms.
- 100% remote operation from web interface with preview.
- Configuration of Layouts by Drag & Drop.
- Carousel of failed programs (Donkey Corner). On-screen graphics, UMD, analog and digital clock, PCR information, subtitles and ClosedCaption. Visualization of loudness, momentary, short term and truepeak.
- Multiple LU meters , truepeak meters, support multiple channels.
- Information on the content screen such as codecs, bitrates, types of services.
- Configuration of Layouts with images, texts and graphics defined by the user.
- Timeline graphs for the different parametric sources like levels, bitrates, etc.
- Controllable and monitorable by SNMP integrable with NMS.

DISPLAY QUALITY

Centralize monitoring of multiple signals.

Cable and IPTV operators, broadcasters, and TV and Satellite networks can view all their signals on multiple screens with various alarm methods (sound, visual, mail, SNMP).

- Digital TV Head Ends.
- Monitoring of Digital TV transmission sites (ISDB-Tb, ATSC and DVB).
- TV signal operators.
- Satellite operators.
- Government entities.
- OTT technical monitoring.



The multi-view output is applicable to any ViDeus system or it can be a stand-alone system that centralizes the display of many systems.

The monitoring output can be generated in an IP Stream fully compatible with PCs, Notebooks, Tablets and cell phones, so you can see the monitoring from any device and place.

“

The hybrid multiviewer allows signals from HDMI, SDI, RF, ISDBT, OTT, etc. to be integrated into the same screen.

3Way Solutions is a company dedicated to developing products and solutions for the broadcasting, cable, professional video and government sectors focused on television recording, content detection, media monitoring, legal copying, content repurposing, regulatory compliance verification and QoS/QoE monitoring.