Claude Code Attribution

Managing AI co-authorship trailers in git commits and pull request descriptions

Default Attribution

Commit Trailer

Claude Code appends a `Co-Authored-By` trailer to every commit. The model name reflects the active session model.

```
$ git log -1
commit a1b2c3d (HEAD -> feature/add-validation)
Author: Your Name <you@example.com>
Date:   Thu Oct 22 10:30:00 2026 +0100

    Add input validation for email field

    Co-Authored-By: Claude Opus 5.5 <noreply@anthropic.com>
```

PR Footer

PRs created via `gh pr create` get a footer line in the description:

```
🤖 Generated with
[Claude Code](https://claude.com/claude-
```

Both make AI involvement visible in git history and on GitHub. The model name varies: `Fable 5.1`, `Opus 5.5`, `Sonnet 5.5`, or `Haiku 5.5`. Sessions on 1M context read `Opus 5.5 (1M context)`.

When to Keep Attribution

- **Audit trail** — Permanent, searchable record of AI-assisted commits. Use `git log --grep="Co-Authored-By: Claude"` to find them.
- **Team transparency** — Signals AI involvement so reviewers apply extra scrutiny for hallucinated APIs or missed conventions.
- **Compliance** — Automatically satisfies organizational policies requiring AI-generated code disclosure.

When to Remove Attribution

- **Git log noise** — Two extra lines per commit. Clutters history when AI assistance is routine.
- **Contribution-graph noise** — GitHub only counts a co-author toward contributor stats when the email is tied to a GitHub account, and `noreply@anthropic.com` is not — but the trailer still shows up in any tooling that parses commit metadata.
- **Personal preference** — On solo or internal projects, the trailer may not serve any practical purpose.

How to Remove Attribution

Settings Scope

The `attribution` setting can live in three places you control:

File	Scope
`~/.claude/settings.json`	All projects (current user)
`.claude/settings.json`	Everyone on the project
`.claude/settings.local.json`	Just you, this project only

> **Warning:** Don't modify `.claude/settings.json` to remove attribution. It's shared with the entire team. Use user or local project settings instead. An IT-deployed *managed* settings file can override all three.

Disable Both

Set `commit` and `pr` to empty strings:

```
{
  "attribution": {
    "commit": "",
    "pr": ""
  }
}
```

Instead of removing attribution entirely, set `commit` and `pr` to any custom string to replace the default text with your own wording. A third key, `sessionUrl` (boolean, default `true`), controls the extra `Claude-Session:` trailer added to commits and PRs from web or Remote Control sessions. Local terminal sessions are unaffected.