

Enhanced Local Binary Covariance Matrices (ELBCM) for texture analysis and object tracking

Andrés Romero Mier y Terán¹

Michèle Gouiffès²

Lionel Lacassagne¹

¹Laboratoire de Recherche en Informatique

²Laboratoire d'Informatique pour la Mécanique et les Sciences de l'Ingénieur
Université Paris-Sud XI

andres.romero@iri.fr

lionel.lacassagne@iri.fr

michele.gouiffes@u-psud.fr

June 5, 2013

Outline

Introduction

Local Binary Patterns (LBP)

Covariance region descriptors

ELBCM descriptor

Experiments

Introduction: ELBCM characteristics

Enhanced Local Binary Covariance Matrix (ELBCM) proposes:

- ▶ A novel way to represent textures using local binary patterns (LBP's) and covariance descriptors.
- ▶ Averages and covariances of LBP's codes have no textural interpretation.
- ▶ ELBCM is based on the angles described by the uniform LBP patterns (ULBP's) and not on their codes (decimal values).

Advantages:

- ▶ + compact and robust.
- ▶ - affected by noise and small rotations.

Introduction: Texture analysis

Why are **textures** important?

- ▶ Textures provide strong cues for **object** and **material** recognition.
- ▶ Useful to recognize object and material properties such as: **hardness**, **smoothness** and **opaqueness**.

Possible difficulties:

- ▶ Intra-class variation.
- ▶ Clutter.
- ▶ Occlusions.
- ▶ Changes in **scale**, **illumination** and **pose**.

Introduction: Methods

Some popular texture analysis methods are:

- ▶ Statistical: Co-occurrence matrices and histograms [2].
- ▶ Primitive combination: spots, bars, edges, etc.
- ▶ Signal-processing based: Filter banks, Wavelets [9], Gabor filtering [7], etc.
- ▶ Key-point descriptors: Harris [4], SIFT [6], SURF [1].
- ▶ Texture classifiers (using Machine Learning): SVM's[11]), AdaBoost, etc.

Local Binary Patterns (LBP)

- ▶ The $LBP_{P,R}(x_c, y_c)$ operator compares P pixels regularly distributed across the circle of radius R and centre (x_c, y_c) .
- ▶ A P -length binary code is formed comparing the value at the center with pixels in the neighbourhood.
- ▶ A weight is associated to their position as powers of two $\{2^0, 2^1, \dots, 2^{P-1}\}$, and accumulating their thresholded differences

$$LBP_{P,R}(x_c, y_c) = \sum_{p=0}^{P-1} s(g_p - g_c)2^p$$

, where $s(z)$ is the step function.

- ▶ A P -pixel LBP operator maps to 2^P possible labels.

Local Binary Patterns (LBP)

LBP Original Form

6	5	2
7	6	1
9	8	7

Pattern = 11110001


1	0	0
1		0
1	1	1

LBP = 1 + 16 + 32 + 64 + 128 = 241

$$C = (6+7+9+8+7)/5 - (5+2+1)/3 = 4.7$$


1	2	4
128		8
64	32	16

LBP Circular Forms




$LBP_{8,1}(x_c, y_c)$

(a)



$LBP_{16,2}(x_c, y_c)$

(b)



$LBP_{8,2}(x_c, y_c)$

(c)

Covariance region descriptors

- ▶ Covariance matrix representations [13, 10] and [5] are very practical to build models based on local feature correlations.
- ▶ Commonly used features:
 - ▶ pixel coordinates,
 - ▶ brightness and colour,
 - ▶ gradients,
 - ▶ optical flow, etc.
- ▶ Considerations:
 - ▶ Covariance descriptors are SPD (symmetric positive-definite) matrices of size $n \times n$, where n is the length of the feature vector.
 - ▶ Euclidean geometry is not applicable to compute matrix distances in this set.
 - ▶ Distances are measured using geodesics.

Covariance region descriptors: Texture analysis

Gabor based:

- ▶ Pang et al. use **Gabor filter bank responses** to form their Gabor Region Covariance Matrix (**GRCM**) [8] and [12].
- ▶ **Highly discriminant.**
- ▶ Due to the large number of features used (one for each filter), these models are **expensive to compute and match**.

LBP-based:

- ▶ A complementary representation to the traditional LBP histogram analysis.
- ▶ Possible to integrate other sources of information such as spatial correlation, luminance and colour, etc.
 - ▶ Local Binary Covariance Matrix (**LBCM**)[3].
 - ▶ Gabor-LBP based Region Covariance Descriptor (**GLRCD**) [14].

Covariance region descriptors: **GLRCD** and **LBCM**

GLRCD:

- ▶ LBP decimal values are included directly in the feature vector.
- ▶ **Problems:**
 - ▶ Arithmetic operations width LBP values have **no textural meaning**
 - ▶ Very unstable for the case of small local neighbourhood rotations.

LBCM:

- ▶ Each bit in the pattern acts as an independent feature.
- ▶ **Advantages:** Arithmetic operations are well defined, stable for small local neighbourhood rotations.
- ▶ **Problem:** The **number of features** grows with the number of bits in the LBP pattern.

ELBCM descriptor

Using the angles defined by the uniform LBP patterns (**ULBP**), a more compact and stable version of the **LBCM** descriptor is obtained.

- ▶ Using a $LBP_{8,R}$ operator there are 58 different codes.
- ▶ The starting and ending angles θ_0 and θ_1 of the **ULBP** are used as features in the covariance feature vector.
- ▶ θ_0 and θ_1 are converted from polar to **Cartesian** coordinates to avoid using circular arithmetic:


$$\mathbf{v}(\theta_0, \theta_1) = [\cos(\theta_0) \ \sin(\theta_0) \ \cos(\theta_1) \ \sin(\theta_1)].$$

- ▶ Our Enhanced Local binary Covariance Matrix (**ELBCM**) for texture description is constructed using the mapping function


$$\phi(I, x, y) = [x \ y \ I(x, y) \ \mathbf{v}(LBP(x, y))] .$$

ELBCM descriptor(2)

Example:



Example: ELBCM mapping for decimal value 63



$$\theta_0 = \frac{\pi}{8} \rightarrow (\cos(\theta_0), \sin(\theta_0))$$


$$\theta_1 = \frac{5\pi}{8} \rightarrow (\cos(\theta_1), \sin(\theta_1))$$

$$\mathbf{v}(\theta_0, \theta_1) = [\cos(\theta_0) \ \sin(\theta_0) \ \cos(\theta_1) \ \sin(\theta_1)]$$

(b)


Experiments: Texture analysis

Texture classification Brodatz dataset:




Experiments: Texture analysis(2)

Texture classification KTH-TIPS dataset:




Experiments: Texture analysis(3)

Facial expression classification results for the JAFFE database using 21 learning samples:




Experiments: Object tracking



Tracking results Jumping sequence


Features	time/frame [ms]	w _{error}
Tuzel	4.83	1.83294
LBCM	10.3	0.362136
ELBCM	4.82	0.268516
LRCD	2.25	2.35453

Experiments: Object tracking (2)



Tracking results Panda sequence		
Features	time/frame [ms]	w_{error}
Tuzel	3.65	1.9342
LBCM	7.57	0.282194
ELBCM	3.65	0.279785
LRCD	1.71	0.388786

Experiments: Object tracking (3)



Tracking results Pedxing3 sequence		
Features	time/frame [ms]	w_error
Tuzel	20.5	-
LBCM	40.6	-
ELBCM	20.5	-
LRCD	6.69	-

Conclusions

- ▶ **ELBCM** can be used for **texture analysis** and **tracking** applications.
- ▶ It is more **robust**, **precise** and **compact** than other similar LBP-Covariance matrix approaches.
- ▶ Its performance rivals with more elaborated and consuming techniques.

Thanks!

References |

-  Herbert Bay, Tinne Tuytelaars, and Luc Van Gool.
Surf: Speeded up robust features.
Computer Vision ECCV 2006, page 404417, 2006.
-  N. Dalal and B. Triggs.
Histograms of oriented gradients for human detection.
In *Computer Vision and Pattern Recognition, 2005. CVPR 2005. IEEE Computer Society Conference on*, volume 1, page 886893, 2005.
-  Song Guo and Qiuqi Ruan.
Facial expression recognition using local binary covariance matrices.
In *Wireless, Mobile & Multimedia Networks (ICWMMN 2011), 4th IET International Conference on*, page 237242, 2011.
-  C. Harris and M. Stephens.
A combined corner and edge detector.
In *Alvey vision conference*, volume 15, page 50, 1988.

References II

-  Peihua Li and Qilong Wang.
Local log-euclidean covariance matrix (L2ECM) for image representation and its applications.
In Andrew Fitzgibbon, Svetlana Lazebnik, Pietro Perona, Yoichi Sato, and Cordelia Schmid, editors, *Computer Vision ECCV 2012*, volume 7574 of *Lecture Notes in Computer Science*, pages 469–482. Springer Berlin Heidelberg, 2012.
-  David G Lowe.
Distinctive image features from scale-invariant keypoints.
International journal of computer vision, 60(2):91–110, 2004.
-  Javier R Movellan.
Tutorial on gabor filters.
Open Source Document, 2002.

References III

-  Yanwei Pang, Yuan Yuan, and Xuelong Li.
Gabor-based region covariance matrices for face recognition.
Circuits and Systems for Video Technology, IEEE Transactions on,
18(7):989 –993, july 2008.
-  Gabriel Peyré.
Sparse modeling of textures.
Journal of Mathematical Imaging and Vision, 34(1):1731, 2009.
-  F. Porikli, O. Tuzel, and P. Meer.
Covariance tracking using model update based on lie algebra.
In *Computer Vision and Pattern Recognition, 2006 IEEE Computer Society Conference on*, volume 1, pages 728–735. IEEE, 2006.
-  Bernhard Schölkopf and Alexander J Smola.
Learning with kernels: Support vector machines, regularization, optimization, and beyond.
MIT press, 2001.

References IV

-  Jing Tou, Yong Tay, and Phooi Lau.
Gabor filters as feature images for covariance matrix on texture classification problem.
Advances in Neuro-Information Processing, page 745751, 2009.
-  O. Tuzel, F. Porikli, and P. Meer.
Region covariance: A fast descriptor for detection and classification.
Computer Vision–ECCV 2006, pages 589–600, 2006.
-  Ying Zhang and Shutao Li.
Gabor-LBP based region covariance descriptor for person re-identification.
In *Image and Graphics (ICIG), 2011 Sixth International Conference on*, page 368371, 2011.