

Neural Networks

Andresito Ponce

April 11, 2020

The general idea behind neural networks is to maintain a **basis function** whose parameters can change during testing. Then the function can know how to perform "better" as the testing goes on.

Previously, we had only considered a linear combination of a fixed basis function, which usually took the form

$$y(x, w) = f\left(\sum_{j=1}^M w_j \phi_j(x)\right)$$

However, our goal is to make some sort of these functions depend on certain parameters.

$$a_j = \sum_{i=1}^D w_{ji}^{(1)} x_i + w_{j0}^{(1)}$$

where a_j is the **activation** value.¹

A common activation function is $y = \frac{1}{1+e^{-x}}$. We then transform the activation value by another nonlinear function h , and are left with the final result $z_j = h(a_j)$.

To summarize the basic structure: supposing the result fits into K classes, we then sum the weights of the D nodes in the first layer and the M nodes of the second layer, and we get a formula in the end resembling²

$$y_k(x, w) = \phi\left(\sum_{j=1}^M w_{kj}^{(2)} h\left(\sum_{i=1}^D w_{ji}^{(1)} x_i + w_{j0}^{(1)}\right) + w_{k0}^{(2)}\right)$$

Feed-Forward Neural Networks

In this scheme, there are a set of **input nodes**, which only connect to the nodes on the next layer, and do not form cycles. There might be some **hidden layers** connected which lie between the input layers and the final output layer.

Out of this simple model arises **deep learning**, where we have more than one hidden layers, **convolutional neural networks**, where nodes of one layer are not necessarily connected to the nodes of a different layer (in contrast to multilayer perceptron).³

For the problem of **regression**, using only one layer, we would also have to minimize the sum of the squares between the target vector and the output of our model $y(x, w)$. If we wanted a function with K

¹ Remember the activation is the final output of this node. In classification, it determines which class we eventually assign to an input. The (1) superscript indicates they are the first layer of the NN.

² This equation basically says that the final value of class k is the result of adding all the nodes from all the layers that feed into k for the two levels?




Figure 1: The input layers feed into the hidden layers, the combinations of weights and basis functions can then determine the results of the output layers.

³ The lack of full connectedness means that the model is less prone to overfit data. Instead of matrix multiplication, CNNs also use **convolution** in at least one layer.

dimensions, our final layer could have K output nodes, one for each dimension.

For a classification problem, we might again use the sigmoid function to model our confidence of $p(C_1|x)$ for $p(C_2|x)$, by measuring the probability of one, say $y(x, w) = p(C_1|x)$ and doing $1 - y(x, w)$.

For multiclass classification, we can still optimize the set of weights w^4 and then apply the **softmax** function ⁵

$$y_k(x, w) = \frac{e^{a_k(x, w)}}{\sum_j e^{a_j(x, w)}}$$

⁴ does this refer to optimizing for *every* node in the network?

⁵ This would be the probs an input belongs to class K right?