
Inductive general game playing


Andrew Cropper, Richard Evans, and Mark Law

Inductive general game playing


Andrew Cropper, Richard Evans, and Mark Law


General game playing competition






8		6
4	7	3
5	2	1







Game description language

- initial game state
- legal moves
- how moves update the game state
- how the game terminates

Game description language

```
(succ 0 1)
(succ 1 2)
(succ 2 3)
(beats scissors paper)
(beats paper stone)
(beats stone scissors)
(<= (next (step ?n)) (true (step ?m)) (succ ?m ?n))
(<= (next (score ?p ?n)) (true (score ?p ?n)) (draws ?p))
(<= (next (score ?p ?n)) (true (score ?p ?n)) (loses ?p))
(<= (next (score ?p ?n)) (true (score ?p ?n2)) (succ ?n2 ?n) (wins ?p))
(<= (draws ?p) (does ?p ?a) (does ?q ?a) (distinct ?p ?q)
(<= (wins ?p) (does ?p ?a1) (does ?q ?a2) (distinct ?p ?q) (beats ?a1 ?a2))
(<= (loses ?p) (does ?p ?a1) (does ?q ?a2) (distinct ?p ?q) (beats ?a2 ?a1))</pre>
```

Our problem

Learn rules from observations

- goal
- legal
- next
- terminal

Why?

- Diverse games
- New problems each year
- Independent language
- Hard problems?

Capablanca



Rock, paper, scissors

```
% BK
                              % E+
beats(paper, stone).
                              next_score(p1,0).
beats(scissors, paper).
                              next_score(p2,1).
beats(stone, scissors).
                              next_step(1).
player(p1).
player(p2).
                              % E-
succ(0,1).
                              next_score(p2,0).
succ(1,2).
                              next_score(p1,1).
succ(2,3).
                              next_score(p1,2).
does(p1, stone).
                              next_score(p2,2).
does(p2,paper).
                              next_score(p1,3).
true_score(p1,0).
                              next_score(p2,3).
true_score(p2, ∅).
                              next_step(∅).
true_step(0).
                              next_step(2).
                              next_step(3).
```

Rock, paper, scissors

```
draws(P):-
next_step(N):-
    true_step(M),
                                does(P,A),
                                does(Q,A),
    succ(M,N).
                                distinct(P,Q).
next_score(P,N):-
    true_score(P,N),
                           loses(P):-
    draws(P).
                                does(P,A1),
next_score(P,N):-
                                does(Q,A2),
    true_score(P,N),
                                distinct(P,Q),
    loses(P).
                                beats(A2,A1).
next_score(P,N2):-
                           wins(P):-
    true_score(P,N1),
                                does(P,A1),
                                does(Q,A2),
    succ(N2,N1),
                                distinct(P,Q),
    wins(P).
                                beats(A1,A2).
```

Game	R	L	D	P
Minimal Decay	2	6	0	1
Minimal Even	8	19	0	1
Rainbow	10	48	0	1
Rock Paper Scissors	12	36	0	1
GT Chicken	16	78	0	2
GT Attrition	16	60	0	2
Coins	16	45	0	1
Buttons and Lights	16	44	1	1
Leafy	17	80	2	2
GT Prisoner	17	75	0	2
Eight Puzzle	17	60	2	1
Lightboard	18	69	2	2
Knights Tour	18	46	2	1
Sukoshi	19	49	1	2
Walkabout	22	66	2	2
Horseshoe	22	59	2	2
GT Ultimatum	22	67	0	2
Tron	23	76	2	2
9x Buttons and Lights	24	77	2	1
Hunter	24	69	2	1
GT Centipede	24	69	0	2
Fizz Buzz	25	74	0	1
Untwisty Corridor	27	68	0	1
Don't Touch	29	84	2	2
Tiger vs Dogs	30	88	2	2

Game	R	L	D	P
Sheep and Wolf	30	89	2	2
Duikoshi	31	76	2	2
TicTacToe	32	92	2	2
HexForThree	35	130	2	3
Connect 4	36	124	2	4
Breakthrough	36	126	2	2
Centipede	37	134	2	1
Forager	40	106	2	1
Sudoku	41	101	2	1
Sokoban	41	172	2	1
9х ТісТасТое	42	149	2	2
Switches	44	183	2	1
Battle of Numbers	44	134	2	2
Free For All	46	130	2	2
Alquerque	49	134	2	2
Kono	50	134	2	2
Checkers	52	167	2	2
Pentago	53	188	2	2
Platform Jumpers	62	168	2	2
Pilgrimage	80	240	2	2
Firesheep	85	290	2	2
Farming Quandries	88	451	2	2
TTCC4	94	301	2	2
Frogs and Toads	97	431	2	2
Asylum	101	273	2	2

Fizzbuzz BK

```
divisible(12,1).
                               less_than(0,1).
divisible(12,2).
                               less_than(0,2).
divisible(12,12).
                               less_than(30, 31).
input_say(player,1).
                               minus(1,1,0).
input_say(player,2).
                               minus(2,1,1).
                               minus(31, 31, 0).
input_say(player, 30).
input_say(player, fizz).
                               positive_int(1).
input_say(player,buzz).
                               positive_int(2).
input_say(player, fizzbuzz).
role(player).
                               positive_int(31).
int(0).
                               succ(0,1).
int(1).
                               succ(0,2).
int(31).
                               succ(30,31).
```

Fizzbuzz legal

```
% BK
true_count(9).
true_success(6).
% F+
legal_say(player,9)
legal_say(player,buzz)
legal_say(player,fizz)
legal_say(player, fizzbuzz)
% F-
legal_say(player, ∅).
legal_say(player,1).
legal_say(player,8).
legal_say(player, 10).
legal_say(player, 31).
```

Fizzbuzz legal

```
% BK
                           % Hypothesis
true_count(9).
                           legal_say(player,N):-
true_success(6).
                               true_count(N).
                           legal_say(player, fizz).
% E+
                           legal_say(player,buzz).
legal_say(player,9)
                           legal_say(player, fizzbuzz).
legal_say(player,buzz)
legal_say(player,fizz)
legal_say(player, fizzbuzz)
% F-
legal_say(player, ∅).
legal_say(player,1).
legal_say(player,8).
legal_say(player, 10).
legal_say(player, 31).
```

Fizzbuzz next count

```
% BK
does_say(player,buzz).
true_count(12).
% E+
next_count(13).
% E-
next_count(∅).
next_count(1).
next_count(12).
next_count(14).
next_count(31).
```

Fizzbuzz next count

```
% BK
does_say(player,buzz).
true_count(12).
% E+
next_count(13).
% E-
next_count(∅).
next_count(1).
next_count(12).
next_count(14).
next_count(31).
```

```
% hypothesis
next_count(After):-
    true_count(Before),
    succ(Before,after).
```

Fizzbuzz next success

```
% BK
does_say(player,buzz).
true_success(3).
% E+
next_success(3).
% E-
next_success(∅).
next_success(1).
next_success(2).
next_success(4).
next_success(31).
```

Fizzbuzz next success

```
correct:-
next_success(After):-
                               true_count(N),
    correct,
                               divisible(N, 15),
    true_success(Before),
                               does_player_say(fizzbuzz).
    succ(Before, After).
                           correct:-
                               true_count(N),
next_success(A):-
                               divisible(N,3),
    \+ correct,
                               \+ divisible(N,5),
    true_success(A).
                               does_player_say(fizz).
                           correct:-
correct:-
                               true_count(N),
    true_count(N),
                               divisible(N,5),
    \+ divisible(N,5),
                               \+ divisible(N,3),
    \+ divisible(N,3),
                               does_player_say(buzz).
    does_player_say(N).
```

Results

Metric	Baseline	Inertia	Mean	KNN_1	KNN ₅	Aleph	ASPAL	Metagol	ILASP*
BA (%)	48	56	64	80	80	66	55	69	86
PS (%)	4	4	15	16	19	18	10	34	40

Results

Metric	Aleph	ASPAL	Metagol	ILASP*
BA (%)	66	55	69	86
PS (%)	18	10	34	40

Results balanced accuracy

Approach	goal	legal	next	terminal
True	47	56	47	42
Inertia	47	56	80	42
Mean	82	61	62	53
Knn1	92	78	86	63
Knn5	92	79	86	64
Aleph	83	60	59	60
ASPAL	52	59	50	59
Metagol	74	66	60	77
Ilasp	92	86	88	80
Mean	73	67	69	60

Results perfectly solved

Approach	goal	legal	next	terminal
True	0	16	0	0
Inertia	0	16	0	0
Mean	32	16	0	12
Knn ₁	34	16	0	12
Knn ₅	34	22	0	18
Aleph	32	18	4	16
ASPAL	4	18	0	18
Metagol	48	28	6	52
ILASP	46	44	18	52
Mean	26	22	3	20

Why?

- Diverse games
- New problems each year
- Independent language
- Hard problems

IGGP competition?