

# **LEHD Public Use Data Schema V4.0.5**

# Contents

<b>1</b>	<b>Purpose</b>	<b>1</b>
<b>2</b>	<b>File naming</b>	<b>1</b>
<b>3</b>	<b>Extends</b>	<b>1</b>
<b>4</b>	<b>Basic Schema</b>	<b>1</b>
4.1	Generic structure . . . . .	1
4.2	Identifiers . . . . .	3
4.2.1	Identifiers for qwi . . . . .	3
4.3	Indicators . . . . .	4
<b>5</b>	<b>Categorical Variables</b>	<b>5</b>
5.1	agegrp . . . . .	5
5.2	education . . . . .	5
5.3	ethnicity . . . . .	5
5.4	firmage . . . . .	5
5.5	firmsize . . . . .	6
5.6	ownercode . . . . .	6
5.7	periodicity . . . . .	6
5.8	race . . . . .	6
5.9	seasonadj . . . . .	6
5.10	sex . . . . .	7
5.11	Industry . . . . .	8
5.11.1	Industry levels . . . . .	8
5.11.2	Industry . . . . .	8
5.12	Geography . . . . .	9
5.12.1	Geographic levels . . . . .	9
5.12.2	State-level values . . . . .	9
5.12.3	Detailed state and substate level values . . . . .	9
<b>6</b>	<b>Status flags</b>	<b>12</b>
<b>7</b>	<b>Changes</b>	<b>13</b>
7.1	This version (revisions) . . . . .	13
7.2	Version 4.0.1 from 4.0 . . . . .	13
7.3	Version 4.0.2 from 4.0.1 . . . . .	13
7.4	Version 4.0.3 from 4.0.2 . . . . .	13
7.5	Version 4.0.4 from 4.0.3 . . . . .	13
7.6	Version 4.0.5 from 4.0.4 . . . . .	13

( [Printable version](#) )

**Important**

Feedback is welcome. Please write us at [ces.qwi.feedback@census.gov](mailto:ces.qwi.feedback@census.gov).

## 1 Purpose

The public-use Quarterly Workforce Indicators (QWI) data from the Longitudinal Employer-Household Dynamics Program are available for download with the following data schema. These data are available as Comma-Separated Value (CSV) files through the LEHD website's Data page at <http://lehd.ces.census.gov/data/> and through LED Extraction Tool at <http://ledextract.ces.census.gov/>.

This document describes the data schema for QWI files. For each variable, a set of allowable values is defined. Definitions are provided as CSV files, with header variable definitions. Changes relative to the original v4.0 version are listed [at the end](#).

## 2 File naming

The naming conventions of the data files is documented in [lehd\\_csv\\_naming.html](#).

## 3 Extends

This version extends v4.0. Any file compliant with LEHD or QWI Schema v4.0 will also be compliant with this schema.

## 4 Basic Schema

Each data file is structured as a CSV file. The first columns contain [identifiers](#), subsequent columns contain [indicators](#), followed by [status flags](#).

### 4.1 Generic structure

Column name
[ Identifier1 ]
[ Identifier2 ]
[ Identifier3 ]
[ ... ]
[ Indicator 1 ]
[ Indicator 2 ]
[ Indicator 3 ]
[ ... ]
[ Status Flag 1 ]
[ Status Flag 2 ]
[ Status Flag 3 ]
[ ... ]

Note: A full list of indicators for each type of file are shown below in the [Indicators](#) section. While all indicators are included in the CSV files, only the requested indicators will be included in data outputs from the LED Extraction Tool.

## 4.2 Identifiers

Records, unless otherwise noted, are parts of time-series data. Unique record identifiers are noted below, by file type. Identifiers without the year and quarter component can be considered a series identifier.

### 4.2.1 Identifiers for qwi

( [lehd\\_identifiers\\_qwi.csv](#) )

Variable	Type	label
periodicity	Char(1)	Periodicity of report
seasonadj	Char(1)	Seasonal Adjustment Indicator
geo_level	Char(1)	Group: Geographic level of aggregation
geography	Char(8)	Group: Geography code
ind_level	Char(1)	Group: Industry level of aggregation
industry	Char(5)	Group: Industry code
ownercode	Char(3)	Group: Ownership group code
sex	Char(1)	Group: Gender code
agegrp	Char(3)	Group: Age group code (WIA)
race	Char(2)	Group: race
ethnicity	Char(2)	Group: ethnicity
education	Char(2)	Group: education
firmage	Char(1)	Group: Firm Age group
firmsize	Char(1)	Group: Firm Size group
year	Num	Time: Year
quarter	Num	Time: Quarter

### 4.3 Indicators

The following tables and associated mapping files list the indicators available on each file. The '*Indicator Variable*' is the short name of the variable on the CSV files, suitable for machine processing in a wide variety of statistical applications. When given, the '*Alternate name*' may appear in related documentation and articles. The '*Status Flag*' is used to indicate publication or data quality status (see [Status Flags](#)). The '*Indicator Name*' is a more verbose description of the indicator.

( [variables\\_qwipu.csv](#) )

Indicator Variable	Alternate name	Status Flag	Indicator Name
Emp	B	sEmp	Beginning-of-Quarter Employment: Counts
EmpEnd	E	sEmpEnd	End-of-Quarter Employment: Counts
EmpS	F	sEmpS	Full-Quarter Employment (Stable): Counts
EmpSpv	Fprev	sEmpSpv	Full-Quarter Employment in the Previous Quarter: Counts
EmpTotal	M	sEmpTotal	Employment - Reference Quarter: Counts
HirA	A	sHirA	Hires All: Counts (Accessions)
HirN	H1	sHirN	Hires New: Counts
HirR	R1	sHirR	Hires Recalls: Counts
Sep	S	sSep	Separations: Counts
HirAEnd	A2	sHirAEnd	End-of-Quarter Hires
HirAEndR	A2R	sHirAEndR	End-of-Quarter Hiring Rate
SepBeg	S2	sSepBeg	Beginning-of-Quarter Separations
SepBegR	S2R	sSepBegR	Beginning-of-Quarter Separation Rate
HirAS	A3	sHirAS	Hires All (Stable): Counts (Flows into Full-Quarter Employment)
HirNS	H3	sHirNS	Hires New (Stable): Counts (New Hires to Full-Quarter Status)
SepS	S3	sSepS	Separations (Stable): Counts (Flow out of Full-Quarter Employment)
SepSnx	S3R	sSepSnx	Separations (Stable): Next Quarter: Counts (Flow out of Full-Quarter Employment)
TurnOvrS	FT	sTurnOvrS	Turnover (Stable)
FrmJbGn	JC	sFrmJbGn	Firm Job Gains: Counts (Job Creation)
FrmJbLs	JD	sFrmJbLs	Firm Job Loss: Counts (Job Destruction)
FrmJbC	JF	sFrmJbC	Firm Job Change: Net Change
HirAEndRepl	EI	sHirAEndRepl	Replacement Hires
HirAEndReplr	EIR	sHirAEndReplr	Replacement Hiring Rate
FrmJbGnS	FJC	sFrmJbGnS	Firm Job Gains (Stable): Counts
FrmJbLsS	FJD	sFrmJbLsS	Firm Job Loss (Stable): Counts
FrmJbCS	FJF	sFrmJbCS	Job Change (Stable): Net Change
EarnS	ZW3	sEarnS	Full Quarter Employment (Stable): Average Monthly Earnings
EarnBeg	ZW1	sEarnBeg	Beginning-of-Quarter Employment: Average Monthly Earnings
EarnHirAS	ZWFA	sEarnHirAS	Hires All (Stable): Average Monthly Earnings
EarnHirNS	ZWFH	sEarnHirNS	Hires New (Stable): Average Monthly Earnings
EarnSepS	ZWFS	sEarnSepS	Separations (Stable): Average Monthly Earnings
Payroll	W1	sPayroll	Total Quarterly Payroll: Sum

## 5 Categorical Variables

Categorical variable descriptions are displayed above each table, with the variable name shown in parentheses. Unless otherwise stated, every possible value/label combination for each categorical variable is listed. Please note that not all values will be available in every table.

### 5.1 agegrp

( [label\\_agegrp.csv](#) )

agegrp	label
A00	All Ages (14-99)
A01	14-18
A02	19-21
A03	22-24
A04	25-34
A05	35-44
A06	45-54
A07	55-64
A08	65-99

### 5.2 education

( [label\\_education.csv](#) )

education	label
E0	All Education Categories
E1	Less than high school
E2	High school or equivalent, no college
E3	Some college or Associate degree
E4	Bachelor's degree or advanced degree
E5	Educational attainment not available (workers aged 24 or younger)

### 5.3 ethnicity

( [label\\_ethnicity.csv](#) )

ethnicity	label
A0	All Ethnicities
A1	Not Hispanic or Latino
A2	Hispanic or Latino

### 5.4 firmage

( [label\\_firmage.csv](#) )

firmage	label
0	All Firm Ages
1	0-1 Years
2	2-3 Years
3	4-5 Years

<b>firmage</b>	<b>label</b>
4	6-10 Years
5	11+ Years

## 5.5 firmsize

( [label\\_firmsize.csv](#) )

<b>firmsize</b>	<b>label</b>
0	All Firm Sizes
1	0-19 Employees
2	20-49 Employees
3	50-249 Employees
4	250-499 Employees
5	500+ Employees

## 5.6 ownercode

( [label\\_ownercode.csv](#) )

<b>ownercode</b>	<b>label</b>
A00	All (1-5)
A05	All Private (5)

## 5.7 periodicity

( [label\\_periodicity.csv](#) )

<b>periodicity</b>	<b>label</b>
A	Annual data
Q	Quarterly data

## 5.8 race

( [label\\_race.csv](#) )

<b>race</b>	<b>label</b>
A0	All Races
A1	White Alone
A2	Black or African American Alone
A3	American Indian or Alaska Native Alone
A4	Asian Alone
A5	Native Hawaiian or Other Pacific Islander Alone
A6	Some Other Race Alone (Not Used)
A7	Two or More Race Groups

## 5.9 seasonadj

( [label\\_seasonadj.csv](#) )

<b>seasonadj</b>	<b>label</b>
S	Seasonally adjusted



seasonadj	label
U	Not seasonally adjusted

**5.10 sex**

( [label\\_sex.csv](#) )

sex	label
0	All Sexes
1	Male
2	Female

## 5.11 Industry

### 5.11.1 Industry levels

( [label\\_ind\\_level.csv](#) )

ind_level	label
3	NAICS Subsectors
4	NAICS Industry Groups
A	All Industries
S	NAICS Sectors

### 5.11.2 Industry

( [label\\_industry.csv](#) )

Only a small subset of available values shown. The 2012 NAICS (North American Industry Classification System) is used for all years. QWI releases prior to R2015Q3 used the 2007 NAICS classification (see [Schema v4.0.1](#)). For a full listing of all valid 2012 NAICS codes, see <http://www.census.gov/cgi-bin/sssd/naics/naicsrch?chart=2012>.

industry	label
00	All NAICS Sectors
000	All NAICS Subsectors
0000	All NAICS Industry Groups
11	Agriculture, Forestry, Fishing and Hunting
111	Crop Production
1111	Oilseed and Grain Farming
1112	Vegetable and Melon Farming
...	
2382	Building Equipment Contractors
2383	Building Finishing Contractors
2389	Other Specialty Trade Contractors
31-33	Manufacturing
311	Food Manufacturing
3111	Animal Food Manufacturing
3112	Grain and Oilseed Milling
3113	Sugar and Confectionery Product Manufacturing
...	

## 5.12 Geography

### 5.12.1 Geographic levels

( [label\\_geo\\_level.csv](#) )

geo_level	label
C	Counties
M	Metropolitan/Micropolitan
N	National (50 States + DC)
S	States
W	Workforce Investment Areas

Geography labels are provided in separate files, in directories by state. Note that cross-state CBSA will have state-specific parts, and thus will appear in multiple files. A separate [label\\_fipsnum.csv](#) contains values and labels for all entities of [geo\\_level](#) *n* or *s*, and is a summary of separately available files. For convenience

### 5.12.2 State-level values

( [label\\_fipsnum.csv](#) )

geography	label
02	Alaska
01	Alabama
05	Arkansas
04	Arizona
06	California
08	Colorado
09	Connecticut
...	
46	South Dakota
47	Tennessee
48	Texas
00	National (50 States + DC)
49	Utah
51	Virginia
50	Vermont
53	Washington

### 5.12.3 Detailed state and substate level values

For a full listing of all valid geography codes (except for WIA codes), see <http://www.census.gov/geo/maps-data/data/tiger.html>. Note about geography codes: Four types of geography codes are represented with this field, depending on the value of [geo\\_level](#). Each geography has its own code structure:

- State is the 2-digit [FIPS 55-2](#) (now INCITS 38:200x) code ([geo\\_level](#) = *s*)
- A two-digit *00* reflects coverage for "National (50 States + DC)" ([geo\\_level](#) = *n*)
- County is the 5-digit [FIPS 6-4](#) (now INCITS 31:200x) code ([geo\\_level](#) = *c*)
- Metropolitan/Micropolitan codes are constructed from the 2-digit state FIPS code and the 5-digit [CBSA](#) code provided by the Census Bureau's Geography Division. ([geo\\_level](#) = *m*)
  - In the QWI, the metropolitan/micropolitan areas are the state parts of the full CBSA areas.

- The WIA code is constructed from the 2-digit state FIPS code and the 6-digit WIA identifier provided by LED State Partners. ([geo\\_level](#) = *w*)

The 2015 vintage of Census TIGER/Line geography is used for all tabulations as of the R2015Q4 release.

For convenience, a composite file containing all geocodes is available as [label\\_geography\\_all.csv](#).

State	Format file
AK	<a href="#">ak/label_geography.csv</a>
AL	<a href="#">al/label_geography.csv</a>
AR	<a href="#">ar/label_geography.csv</a>
AZ	<a href="#">az/label_geography.csv</a>
CA	<a href="#">ca/label_geography.csv</a>
CO	<a href="#">co/label_geography.csv</a>
CT	<a href="#">ct/label_geography.csv</a>
DC	<a href="#">dc/label_geography.csv</a>
DE	<a href="#">de/label_geography.csv</a>
FL	<a href="#">fl/label_geography.csv</a>
GA	<a href="#">ga/label_geography.csv</a>
HI	<a href="#">hi/label_geography.csv</a>
IA	<a href="#">ia/label_geography.csv</a>
ID	<a href="#">id/label_geography.csv</a>
IL	<a href="#">il/label_geography.csv</a>
IN	<a href="#">in/label_geography.csv</a>
KS	<a href="#">ks/label_geography.csv</a>
KY	<a href="#">ky/label_geography.csv</a>
LA	<a href="#">la/label_geography.csv</a>
MA	<a href="#">ma/label_geography.csv</a>
MD	<a href="#">md/label_geography.csv</a>
ME	<a href="#">me/label_geography.csv</a>
MI	<a href="#">mi/label_geography.csv</a>
MN	<a href="#">mn/label_geography.csv</a>
MO	<a href="#">mo/label_geography.csv</a>
MS	<a href="#">ms/label_geography.csv</a>
MT	<a href="#">mt/label_geography.csv</a>
NC	<a href="#">nc/label_geography.csv</a>
ND	<a href="#">nd/label_geography.csv</a>
NE	<a href="#">ne/label_geography.csv</a>
NH	<a href="#">nh/label_geography.csv</a>
NJ	<a href="#">nj/label_geography.csv</a>
NM	<a href="#">nm/label_geography.csv</a>
NV	<a href="#">nv/label_geography.csv</a>
NY	<a href="#">ny/label_geography.csv</a>
OH	<a href="#">oh/label_geography.csv</a>
OK	<a href="#">ok/label_geography.csv</a>
OR	<a href="#">or/label_geography.csv</a>
PA	<a href="#">pa/label_geography.csv</a>
RI	<a href="#">ri/label_geography.csv</a>
SC	<a href="#">sc/label_geography.csv</a>
SD	<a href="#">sd/label_geography.csv</a>
TN	<a href="#">tn/label_geography.csv</a>
TX	<a href="#">tx/label_geography.csv</a>
US	<a href="#">us/label_geography.csv</a>
UT	<a href="#">ut/label_geography.csv</a>
VA	<a href="#">va/label_geography.csv</a>
VT	<a href="#">vt/label_geography.csv</a>
WA	<a href="#">wa/label_geography.csv</a>

State	Format file
WI	<a href="#">wi/label_geography.csv</a>
WV	<a href="#">wv/label_geography.csv</a>
WY	<a href="#">wy/label_geography.csv</a>

## 6 Status flags

( [label\\_flags.csv](#) )

Each status flag in the tables above contains one of the following valid values. The values and their interpretation are listed in the table below.

flag	label
-2	no data available in this category for this quarter
-1	data not available to compute this estimate
1	OK
5	Value suppressed because it does not meet US Census Bureau publication standards.
6	Value calculated from other released measures - no significant distortion
7	Value calculated from other released measures - some of which have significantly distorted data
9	Data significantly distorted - fuzzed value released
10	Aggregate of cells - no significant distortion
11	Aggregate of cells not released because component cells do not meet U.S. Census Bureau publication standards
12	Aggregate of cells - some of which have significantly distorted data

## 7 Changes

For a description of how schema files are versioned, see [main directory](#).

### 7.1 This version (revisions)

- 2016-03-15: Initial release
- 2016-04-07: Fixed typo in variables\_qwipu.csv (FrmJbLS, EarnHirNS and status variables)
- 2016-04-13: Fixed typo in variables\_qwipu.csv (HirAS, HirNS, and status variables)

### 7.2 Version 4.0.1 from 4.0

- 2015-02-24: removed obsolete flag values
- 2015-04-01: updated IL, NE geography definitions

### 7.3 Version 4.0.2 from 4.0.1

- 2015-04-01: switched NAICS coding from 2007 to 2012

### 7.4 Version 4.0.3 from 4.0.2

- 2015-09-14: switched Geovintage to 2014, updated AK and SD files, added MA.

### 7.5 Version 4.0.4 from 4.0.3

- 2015-11-30: updated OR.
- 2015-12-10: Added consolidated geography label file label\_geography\_all.csv
- 2015-12-22: Updated the identification of the correct geo vintage
- 2015-12-22: Added a link to NAICS 2012 tables
- 2015-12-22: Removing the 99 row in industry values - only used for internal error checking

### 7.6 Version 4.0.5 from 4.0.4

- 2016-03-15: updated MO (new WIB code).
  - 2016-03-15: Added us/label\_geography.csv to have an entry for the National QWI
  - 2016-03-15: Added better cross-links between CSV naming scheme, and datafile schema
  - 2016-03-15: Corrected label\_geo\_level.csv to include the national level value.
  - 2016-03-15: Clarified description of geography codes
-

This revision: Fri Apr 15 11:24:06 EDT 2016