DDMnle: a calibrated neural likelihood for the DDM with variability

Draft of 2026-10-25.

0. Summary

- **DDMnle** is a single neural likelihood for the diffusion model (DDM) with trial-to-trial variability in drift (sv), start point (SZ) and non-decision time (st0), usable in EMC2 as a drop-in replacement for the analytic DDM.
- **Validation.** Held-out likelihood does not show whether posteriors are right, so we validate by calibration: a score-bias screen of every trained checkpoint, then simulation-based calibration (SBC) at N = 400 trials with 500 replicates in six variability cases, each against the analytic DDM as control. DDMnle falls outside the 95% rank-ECDF envelope once in 35 parameter tests (a, in the st0-only model), which is what chance gives, and needs no correction.
- **Speed.** DDMnle is 1.9–6.2x faster at N = 100 and 2.9–11.5x faster at N = 400 than EMC2's default-precision (5e-3) compiled WienR, and 9–685x faster than WienR at the project's reference precision 1e-8, with the largest gains where st0 and SZ are both free (§1).
- **Availability.** DDMnle ships with EMC2 on the `main` branch of the DMC2 repository and is the default network of `DDMnn()`. Two more neural likelihoods ship with it: the conflict racing diffusion model (CRDM, `CRDMnn()`; Appendix D), whose exact likelihood, a slow numerical (Volterra) solution with an exact simulator, also ships as the model `CRDM()`, and the RTCON2 confidence-rating model (`RTCONnn()`), which has no analytic likelihood in EMC2. The Python package nleflow trains such networks, exports them as cards and as ONNX graphs, and converts published LANs (§6).
- **LAN.** In Appendix A we use our methodology to test a published LAN from HSSM for the st0 case. It is not calibrated in its own box (four of five parameters outside the envelope; coverage of `a` 0.71), while the analytic control is clean.

1. Speed

Cases with no variability, or with sv only, are not covered here, because the analytic DDM is faster there. Milliseconds per likelihood evaluation, single thread. Speed-up = WienR time / DDMnle time.

Model	N	WienR 5e-3	WienR 1e-8	DDMnle compiled	speed-up vs 5e-3	speed-up vs 1e-8
st0+SZ	100	0.32	20.9	0.0525	6.1x	399x
st0+SZ	400	1.55	92.4	0.135	11.5x	685x
st0+sv	100	0.11	0.65	0.0575	1.9x	11x
st0+sv	400	0.455	2.15	0.143	3.2x	15x
sv+SZ	100	0.0875	0.4	0.035	2.5x	11x
sv+SZ	400	0.34	1.15	0.0775	4.4x	15x
st0	100	0.09	0.55	0.0475	1.9x	12x
st0	400	0.523	3.2	0.182	2.9x	18x
SZ	100	0.127	0.45	0.0512	2.5x	9x
SZ	400	0.54	1.4	0.113	4.8x	12x
sv+SZ+st0	100	0.4	24.1	0.065	6.2x	371x

Model	N	WienR 5e-3	WienR 1e-8	DDMnle compiled	speed-up vs 5e-3	speed-up vs 1e-8
sv+SZ+st0	400	1.85	105	0.177	10.4x	590x

Notes.

- Timings are single thread, in ms per likelihood evaluation at N trials, median over repeats and prior draws.
- WienR at 5e-3 is EMC2's default DDM precision; `DDM(precision = )` sets it. 1e-8 is the precision the project uses as ground truth. At 5e-3 the log density can be off by up to 0.04 when sv, SZ and st0 are all free (about 1e-3 otherwise); at 1e-8 the error is 2e-7 or smaller.
- The laptop was also running the 8-core LAN SBC while these were timed, so absolute times are probably a little high for all columns.
- Models with st0 cost somewhat more for DDMnle than those without, because each trial needs two CDF evaluations instead of one density.

2. How neural likelihoods are judged

A neural likelihood is worth using only if the posteriors it produces are the posteriors the true likelihood would produce. Held-out likelihood does not test that: it can order networks opposite to calibration. EMC2's default-precision analytic DDM is pointwise worse than a good network but better calibrated, because its error is series truncation that does not depend on the parameters and cancels; and networks that differ only in seed have indistinguishable validation losses but score biases on `a` that differ by 0.15, with half failing SBC. So we use two calibration measures:

- **Score bias** per parameter, $g = E[\partial \log \hat{L}/\partial\theta - \partial \log L/\partial\theta]$ over prior draws. It is cheap (about a minute per network) and is used to rank many checkpoints. It is necessary, not sufficient.
- **SBC** (rank-ECDF with 95% simultaneous envelopes, standardised posterior bias, coverage, KS test), the final test.

3. The scaled DDM network

Three of the DDM's parameters enter the likelihood in closed form, so DDMnle does not learn them:

- **a and s set the scale.** Dividing space by a and multiplying time by $(s/a)^2$ maps the diffusion onto one with boundary 1 and noise 1: $f(d) = (s/a)^2 \cdot g(d\cdot(s/a)^2; \kappa, \eta, Z, SZ)$, with $\kappa = v\cdot a/s^2$ and $\eta = sv\cdot a/s^2$. Z and SZ are relative to a and unchanged. The network therefore has four inputs (κ, η, Z, SZ), plus the response.
- **t0 is a shift.** The network models the decision time $d = rt - t0$.
- **st0 is an exact convolution.** With $u_1 = d\cdot(s/a)^2$ and $u_0 = (d - st0)\cdot(s/a)^2$, the likelihood is $[G(u_1) - G(u_0)]/st0$, where G is the network's own (defective) CDF. This matches the analytic convolution to 2e-6.
- **Exact zeros.** $\eta = 0$ is $sv = 0$ and $SZ = 0$ is no start-point variability; both are exact zeros of the input encoding, and $st0 = 0$ is the plain density.
- **Box.** $\kappa \in [-10, 10]$, $\eta \in \{0\} \cup (0, 8]$, $Z \in [0.1, 0.9]$, $SZ \in \{0\} \cup [0.05, 0.99]$. The SBC priors ($v \approx 1$, $a \approx 0.8$, $s = 1$, $sv \approx 0.1$) give $\kappa \approx 0.4$–1.6 and $\eta \approx 0.05$–0.2, well inside.
- **Architecture.** A conditional spline flow over log u ([256, 128] conditioner, 64 bins, batch 1024) with a separate classifier for P(R) trained on exact pWDM targets.

- **Verification.** With the network replaced by the exact unit-scale density, the likelihood agrees with the analytic DDM to 8e-12 at st0 = 0 and ≤ 5e-5 with st0 > 0, with exact zeros below t0. The compiled likelihood agrees with the reference implementation to ≤ 1.1e-11 in the log-likelihood over 200 prior draws in each of the six models.

3.1 How DDMnle is incorporated in EMC2

A trained network is exported as a card: a file holding the weights, spline settings, input transforms, and golden test vectors computed from the training code. The loader asserts the card's input order (κ, η, Z, SZ) on load instead of trusting metadata, because a mis-ordered network gives a large, silent bias.

- **A model function, not a new model.** DDMnle is EMC2's own `DDM()` with only the likelihood replaced. The parameter transforms, bounds, the exact-zero rules for sv, SZ and st0, and the simulator (so `make_data`) are the analytic DDM's. Designs, priors, samplers and plotting therefore work unchanged; a fit differs from an analytic-DDM fit only in the likelihood call.
- **What runs per likelihood call.** All trials in a call share one parameter set, so the network's conditioner runs once per response, not once per trial; each trial then costs a spline evaluation. For each trial the compiled code reads v, a, sv, t0, st0, s, Z, SZ from EMC2's parameter table, forms κ, η, Z, SZ and $c = (s/a)^2$, and makes one network call: a density when st0 = 0, a CDF pair when st0 > 0. It returns c·g or $[G(u_1) - G(u_0)]$/st0. Out-of-box parameters, and RTs at or below t0, get the same floor or zero the analytic model uses.
- **Checks.** An oracle test (network replaced by the exact unit-scale density), a golden-vector test of the card, and agreement of the compiled path with the reference implementation, as above.

4. Selection

- **Training:** 6 seeds × 300 epochs, 600k parameter draws × 40 rows each, 30 checkpoints kept per seed (180 in all). Final validation losses (−1.4358 to −1.4372) were indistinguishable across seeds, so selection does not use them.
- **Screening:** every checkpoint was screened by score bias in 7 regimes (full, η = 0, SZ = 0, st0 = 0, and combinations of zeros), in two stages (100 draws, then the leaders at 300). The score is Σ over regimes of $|g_v| + |g_a| + |g_Z|$. The analytic oracle scores ≤ 7e-5 in every regime, so the screen has a floor well below the networks'. max $|g_{st0}|$ over all 180 checkpoints is 0.005, so the exact convolution does what it should. The best checkpoint per seed ranged from 0.042 to 0.081: seed variance is large, which is why selection is on score bias.
- **Criteria set in advance:** st0 clean in every cell; a inside the envelope in the three models with two variability sources. The top 3 checkpoints went to SBC and DDMnle is the one that met them.

5. SBC results

Six models (listed parameters free, the others pinned at exactly 0): st0+SZ, st0+sv, sv+SZ, st0, SZ, and sv+SZ+st0. N = 400 trials, 500 replicates per model, network only, against the analytic DDM as control. Appendix B contains the SBC plots (rank-ECDF differences with 95% envelopes) for each model.

Standardised posterior bias by parameter, and parameters outside the 95% rank-ECDF envelope:

Model	v	a	t0	Z	SZ	st0	sv	DDMnle outside envelope	analytic control outside envelope
st0+SZ	−0.06	−0.03	+0.01	+0.08	−0.04	+0.05		none	none
st0+sv	+0.01	+0.02	+0.05	+0.05		+0.02	+0.02	none	none
sv+SZ	−0.02	−0.04	+0.08	−0.05	+0.04		+0.01	none	none
st0	+0.05	+0.05	+0.05	−0.06		−0.00		a	t0
SZ	+0.04	−0.03	+0.01	−0.04	−0.01			none	none
sv+SZ+st0	−0.07	−0.10	+0.13	+0.01	−0.00	+0.02	+0.02	none	not run

- **Size of the bias:** worst |standardised bias| is 0.13 (t0, sv+SZ+st0); coverage is 0.932–0.968 and the smallest KS p-value is 0.020.
- **The only flag** is a in the st0 model, one of 35 tests; its standardised bias is +0.05. The analytic control in the same cell has t0 outside the envelope, so that cell is not a clean one even for the analytic likelihood.
- **Residual pattern:** t0 is slightly high (up to +0.13) and a slightly low in the fullest model (−0.10), both inside the envelope. No correction is applied.
- **Caveats:** calibration is shown at N = 400 trials and one participant per replicate; larger N and hierarchical fits are untested. The SBC was run on the reference implementation; the compiled path was verified against it by likelihood agreement (≤ 1.1e-11), not by rerunning SBC.

6. Using DDMnle

- **In EMC2.** The network is a card in the DMC2 repository (`main`, private), registered by `DDMnn()`; designs, priors, samplers and plots are those of the analytic DDM. The same repository ships the CRDM card (`CRDMnn()`) and the RTCON2 card (`RTCONnn()`), each with golden vectors that one verification command checks together with DDMnle's. The vignette "Using a trained flow" fits one participant (200 trials, sv, SZ and st0 free) with the standard DDM, the DDM at precision 1e-8 and DDMnle: the posteriors agree to within 0.09 posterior sd, and the fits take 52 s, 1410 s and 8 s. DDMnle's log-likelihood sits about 4 units below the exact one, a roughly constant offset.
- **Keep the prior inside the box.** A network returns its floor outside the region it was trained on, which truncates a posterior there; EMC2 checks that a prior's mean ± 4 sd lies inside the box before a cell or an SBC run.
- **Response-time resolution.** The default `rt_resolution = 1/60` floors each RT to a 1/60 s grid, which corrects the delay a 60 Hz display adds to real data but, on simulated or millisecond-accurate data, shifts t0 down by about 8 ms (about −1.3 posterior sd at N = 100). The bias is in the data, not the likelihood, and holds for analytic and neural likelihoods alike. Use 1/1000 unless the RTs carry that noise.
- **Training your own.** nleflow takes a short model specification and a simulator, trains a race or choice flow, and exports a card and an ONNX graph; the same checks as here (golden vectors, score bias, SBC) are run in EMC2. It also converts a published LAN (Appendix A). A trained flow varies as much by seed and by checkpoint as by architecture, so several checkpoints should be screened before one is adopted.

Appendix A: ONNX, EMC2, and LAN Comparison

A.1 Bringing ONNX networks into EMC2

The field distributes its likelihood approximation networks (LANs; Fengler et al.) as ONNX files, consumed by HSSM. EMC2 does not run an ONNX file directly, and does not need to: a LAN is a small multilayer perceptron (for the DDM with uniform non-decision time, 7 inputs, three tanh layers of 100 units, one output, with a log-likelihood floor at -16.12), and an MLP can be converted.

- **Conversion.** A converter reads the ONNX graph and writes the same kind of card as DDMnle's. The converted card is checked against onnxruntime before it is accepted.
- **Registration.** The card is registered with EMC2's compiled evaluator together with an analytic "twin" model that has the same structure. The network reuses the twin's simulator, so data can be generated from the analytic model and fitted with the network, and the twin supplies the control for SBC.
- **Parameterisation is checked, not inferred.** The LAN's parameters are not EMC2's. For this LAN the mapping is $a_{EMC2} = 2 \cdot a_{LAN}$, $Z = z$, $t0 = t - st$, $st0 = 2 \cdot st$, $sv = SZ = 0$, $s = 1$, determined empirically against WienR and verified to 4e-7. It is implemented as a model function, with the prior and bounds taken from the LAN's own training box and out-of-box parameters returning the model floor.
- **Why this is useful.** It makes the published LAN library (angle, Levy, Ornstein, Weibull and others, many with no analytic likelihood) available to EMC2 designs, and it gives a like-for-like test: the same SBC cell run with the LAN and with the analytic DDM in the LAN's parameterisation as control.

A.2 DDMnle as an ONNX graph

DDMnle exports to ONNX in the shape of a published LAN, so code written for a LAN can call it.

- **Interface.** The graph takes EMC2's eight natural parameters (v, a, t0, s, Z, SZ, sv, st0), then rt and choice (-1 lower, $+1$ upper), in float64, and returns log p(rt, choice | θ), the joint defective log-density a LAN returns. It does the rest itself: the preprocessing (κ, η, c from v, a, sv, s), the t0 shift, the st0 branch as a difference of two CDFs, $-$Inf for rt at or below t0 and the network's floor outside its box. The network's CDF is in the graph (the spline CDF, and a normal CDF and its inverse written as graph operations because the runtime has no double-precision Erf). Probit and log transforms stay with the caller.
- **Two signatures.** A trial-wise graph takes one row per trial, each with its own parameters, as a LAN does. A shared graph takes the parameters once and rt and choice as vectors; it runs the network's conditioner twice (once per response) instead of once per trial. For a DDM flow, 100 000 trials at one parameter vector take 16 µs per trial trial-wise and 1.1 µs shared, about 15 times faster, so trials that share parameters should be grouped and sent to the shared graph.
- **Agreement with EMC2.** Against the compiled DDMnle over 200 prior draws in each of the six variability models, and against the card's golden vectors:

comparison	rows above the floor	max |Δ log p|	median
golden vectors	1010	5.3e-11	7e-15
EMC2, st0 = 0 (a density)	38 400	4.4e-11	1e-14
EMC2, st0 > 0 (a CDF difference)	78 400	5.6e-9	4e-15

The st0 > 0 branch is a difference of two CDFs, which amplifies round-off; the same difference appears between EMC2 and an independent float64 implementation. - **What an HSSM contribution would still need.** A model

configuration for the seven-parameter DDM (v, a, z, t, sz, sv, st), the parameter-conversion wrapper above, bounds from DDMnle's box and, as the project would insist, an SBC run through HSSM's own sampler rather than EMC2's.

A.3 The LAN SBC

We ran the HSSM `ddm_uniform_st` LAN (the DDM with uniform non-decision-time variability, st0 the only variability) through the same SBC as DDMnle: N = 400 trials, 500 replicates, in the LAN's own training box, with the prior inside the box at ±4 sd. The control is the analytic DDM in the same parameterisation, design and prior ($a_{EMC2} = 2a_{LAN}$, t0 = t − st, st0 = 2 st, s = 1). The LAN's box and prior differ from those of DDMnle's st0-only model, so each is read against its own control and the two are not compared with each other.

Parameter	LAN std bias	LAN coverage	LAN in envelope	Control std bias	Control coverage	Control in envelope
v	+0.16	0.902	no	+0.03	0.932	yes
a	−1.19	0.710	no	+0.06	0.945	yes
z	−0.06	0.924	yes	−0.07	0.961	yes
t	+0.20	0.930	no	−0.03	0.950	yes
st	+0.10	0.910	no	−0.03	0.952	yes

- **The LAN is not calibrated in this box.** Four of five parameters leave the envelope. The boundary separation `a` is the clear failure: standardised bias −1.19, coverage 0.71. The posterior for `a` is too narrow and shifted, so a user would be overconfident about it.
- **The control is clean.** All five parameters are inside the envelope (worst |std bias| 0.07, coverage 0.932–0.961, min KS p 0.068), so the failures belong to the LAN and not to the cell.
- **The control has 458 of 500 replicates.** The analytic DDM's WienR code returns too few densities at a few extreme sampler proposals; rows it cannot evaluate were given zero density, which the likelihood floors, so the replicates complete. The remaining 42 did not complete.
- The rank-ECDF plots are in Figures A1 (LAN) and A2 (control).




Figure A1. LAN.




Figure A2. Analytic DDM control.

Appendix B: SBC plots

Rank-ECDF difference plots for DDMnle, N = 400 trials, 500 replicates per model; the shaded region is the 95% envelope. Each panel gives coverage, bias, precision and the KS p-value.




Figure B1. st0+SZ.




Figure B2. st0+sv.




Figure B3. sv+SZ.




Figure B4. st0.




Figure B5. SZ.




Figure B6. sv+SZ+st0.

Appendix C: Our RDM flow, and how it compares with Malte's

C.1 The flow

- **Model.** A conditional rational-quadratic spline flow over log rt for a single accumulator. The race likelihood is assembled at inference from each accumulator's flow density and survivor: $L(rt, R) = f_R(rt) \cdot \Pi_{j \neq R} S_j(rt)$. For the plain RDM a closed form exists, so the flow is a demonstration of generality, not a speed gain (both flows are slower than the closed form).
- **Box and exact zero for A.** $v \in [10^{-3}, 5]$, $B \in [0.1, 3]$, $t0 \in [0.05, 1]$, $s \in [0.1, 2]$, $A \in [0, 2]$ continuous to zero. A is encoded as asinh(A/0.05), which is exactly 0 at $A = 0$, and is sampled as a mixture: 70% uniform on [0, 2], 15% uniform in the asinh coordinate, 15% exactly 0 (the plain Wald). Training data are 24 million rows, one trial per parameter draw.
- **Architecture and training.** [256, 128] conditioner, 64 bins, batch 1024, 300 epochs, 30 checkpoints kept per seed. Four seeds gave 120 checkpoints, each screened by score bias in two cells (the standard cell and the $A = 0$ cell); the flow with the smallest worst-case score bias $W = \max |g|$ over both cells was kept ($W = 0.0022$; the median checkpoint is 0.0139 and the quartiles are 0.0103 and 0.0208). Selection matters: the median checkpoint is worse than Malte's flow on every measure below.

C.2 Checks on our flow

- **Density error over A.** Between 0.0068 and 0.0118 at A from 0 to 1, against a target of at most 0.014, so it is flat in A and the approach to $A = 0$ is no longer a weak spot.
- **Score bias.** Max $|g| = 0.0022$ in the standard cell, no worse than the earlier flow's 0.004.
- **SBC, five cells, all clean.** $A = 0$ at $N = 400$ (250 replicates; our flow and Malte's final flow, both run), $A = 0$ at $N = 100$, and the standard cell at $N = 100$ and $N = 400$ (500 replicates; network and analytic control). Across the cells |standardised bias| ≤ 0.13 for network and control, coverage 0.92–0.98, and 2 of 40 rank ECDFs touch the envelope (one control, one network; KS p 0.057 and 0.052), which is the chance rate. The analytic control does it as often as the network.

C.3 Comparison with Malte's flow

Malte's flow models decision time (t0 an exact shift) with a per-context affine stage on log time, 12 bins and a [128, 128] conditioner, a plain Wald (no A), $\log(x+\varepsilon)$ inputs, online simulation, right-censored loss and float64. It is a single run with no checkpoint selection. We ingest it through a converter that reproduces his evaluator to 3.6×10^{-11} in log density, and our reproduction of his published density comparison agrees set by set to a KL of 2×10^{-7}.

The comparison uses the $A = 0$ cell, which lies inside both boxes ($s = 1$), on 200 prior draws. Three measures, with the decision rule fixed before any number was seen: density error (median KL to the reference), score bias (max |g|) and posterior shift (largest shift in analytic posterior standard deviations).

flow	median KL	max |g|	max posterior shift (sd)
Malte, final	2.7×10^{-5}	0.0043	0.021
Malte, plain (no affine stage)	4.4×10^{-4}	0.037	0.431 (t0)
Ours, selected	1.5×10^{-4}	0.0010	0.041
Ours, median checkpoint	1.6×10^{-4}	0.0076	0.113

- **Ours against Malte's final flow: not separated.** His density is 5.6 times closer in KL, but both flows are below the floors for score bias and posterior shift, and inference depends on those, not on density error. The A = 0 SBC cell at N = 400 confirms that both pass; the predicted difference between them (about 0.02 posterior sd) is far below what that cell can resolve (about 0.13).
- **Ours against Malte's plain flow: ours as good or better.** The plain flow cannot place mass below 6.7 ms (its spline lives on log t in [−5, 5] with no affine stage), so it fails whenever b/s is below about 0.2 and is poor above 3.
- **Open question.** Whether adding his affine stage to our flow improves its score bias is an arm of our seed study that has not yet been screened, so it is not claimed either way.

C.4 SBC plots

Rank-ECDF difference plots for the A = 0 cell at N = 400 (250 replicates), the cell in which the two flows were compared; the shaded region is the 95% envelope.




Figure C1. Our flow, A = 0 cell, N = 400.




Figure C2. Malte's final flow, A = 0 cell, N = 400.

Appendix D: The CRDM

The CRDM is the RDM with a gamma-shaped drift pulse (amplitude and time constant) on the accumulator matching a distractor, and it is nested in the RDM at amplitude 0. It has no closed-form density: the reference is a Volterra (Fortet) integral-equation solver, which is slow. The CRDM flow is Malte's; our work is its integration into EMC2 and its validation.

D.1 What we built

- **A hybrid race likelihood in EMC2.** The flow supplies the density and survivor of the pulsed accumulator and the analytic Wald supplies the other, assembled in the compiled likelihood. Amplitude is exactly 0 outside the distractor-matched condition, so such trials reduce to the plain RDM.
- **A CRDM model with a reference.** A compiled simulator and a Volterra solver, usable as the analytic comparison and shipped with EMC2 as the model `CRDM()`: the exact CRDM likelihood, which can be fitted directly where its cost is acceptable, and the simulator that `CRDMnn()` uses to generate data. Our solver agrees with Malte's to a relative error of 9×10^{-14} (time step 0.002) and 3.7×10^{-13} (0.0005); at amplitude 0 it equals the closed-form Wald to 4×10^{-14}. Its convergence in the time step has order about 1.5–1.9, with a density error relative to the peak of 5.9×10^{-3}, 2.1×10^{-3} and 5.6×10^{-4} at steps 0.002, 0.001 and 0.0005 (against a step of 0.00025). Our simulator matches his draws (KS $p \geq 0.33$) and the Volterra CDF ($p \geq 0.084$).
- **Exact ingestion.** Our evaluator reproduces his flow's log density to 3.6×10^{-11}, and the compiled hybrid likelihood agrees with an independent reference race implementation to 1.5×10^{-13} or better.

D.2 Checks on the flow

- **Density.** For the flow trained against the 0.0005 reference, median KL 9.7×10^{-5} and KS 2.5×10^{-3} against that reference; at amplitude 0 it matches the Wald with a maximum KL of 5.4×10^{-5}. Flows trained against coarser references inherit their error: the 0.05 flow is poor on its own terms (median KS 0.018, maximum 0.16 here and 0.43 on his grid), and the 0.0005 reference itself has an error of up to 1.5×10^{-3} in KS.
- **SBC at N = 400, six parameters.** The hybrid network (500 replicates): |standardised bias| ≤ 0.092, coverage 0.948–0.966, all six rank ECDFs inside the envelope (smallest KS p 0.063). The Volterra analytic control at step 0.002 (250 replicates): ≤ 0.153, coverage 0.944–0.972, all inside. At step 0.0005 (50 replicates): ≤ 0.156, coverage 0.94–0.98, one ECDF (amplitude) outside the envelope, accepted as chance (1 of 18 control cells; the network and the 0.002 control are clean on it). Network against each control: no disagreement beyond chance (smallest p 0.114 and 0.075, Bonferroni over 18 tests).
- **Posterior shift against the reference** (200 datasets, the largest shift in analytic posterior sd): 0.017 for the 0.0005 flow, below the 0.10 floor, so it passes; 0.117 for the 0.005 flow, narrowly over; 0.59 for the 0.05 flow, which fails.
- **Speed.** Per likelihood evaluation in the timing check: hybrid flow 0.23 ms, Volterra at step 0.002 3.4 ms, at 0.0005 42.5 ms, so the flow is 15 times and 185 times faster. A full Volterra SBC cell took 2.7 h (step 0.002, 250 replicates) and 8.5 h (0.0005, 50 replicates) on 48 cores, against 22 minutes for the 500-replicate network cell. The solver's cost grows with the square of the longest decision time, so the gap widens with slower responses: on 400 trials with responses up to 2.3 s, one evaluation takes 0.16 ms with the flow and 113 ms with the solver at step 0.0005, about 700 times longer.
- **Verdict.** The hybrid network with the 0.0005 flow passes SBC at N = 400 and is indistinguishable from the Volterra reference at both resolutions. It ships with EMC2 as `CRDMnn()`; the 0.005 and 0.05 flows, which failed the posterior-shift check, do not.
- **Limit.** The score-bias screen cannot yet resolve amplitude: its analytic control is 0.021 on that parameter, 21 times its floor, so the screen cannot separate flow bias from solver noise there. The posterior-shift and SBC measures are unaffected.

D.3 SBC plots

Rank-ECDF difference plots at N = 400; the shaded region is the 95% envelope.




Figure D1. Hybrid network, 500 replicates.




Figure D2. Volterra analytic control, step 0.002, 250 replicates.




Figure D3. Volterra analytic control, step 0.0005, 50 replicates (amplitude is the parameter at the envelope edge).