



DOT-std Medical Aluminum Oxygen Cylinders Series

Model Number	Service Pressure (psi / bar)	Diameter (in/mm)	Length (in/mm)	Empty Weight (lbs/kgs)	Oxygen (cu ft/lites)	Water Capacity (lbs/lites)	Standard Thread Size*
★ M150	2015/139	8.0/203.2	47.0/1194	48.8/22.1	48.8/4248	63.7/28.9	1.125-12UNF-2B
M122	2216/153	8.0/203.2	36.2/919	39.5/17.9	122.0/3455	47.1/21.4	1.125-12UNF-2B
★ M90	2216/153	7.25/184.2	32.6/828	30.3/13.7	90.0/2549	34.7/15.7	1.125-12UNF-2B
★ M60	2216/153	7.25/184.2	22.9/582	22.3/10.1	60.0/1699	23.2/10.5	1.125-12UNF-2B
★ ME	2015/139	4.38/111.3	25.4/645	7.8/3.6	24.0/679	10.2/4.6	0.75-16UNF-2B
M22	2216/153	5.25/133.4	16.3/414	8.0/3.7	22.0/623	8.5/3.9	0.75-16UNF-2B
★ MD	2015/139	4.38/111.3	16.7/424	5.4/2.4	15.0/425	6.4/2.9	0.75-16UNF-2B
M9	2015/139	4.38/111.3	10.9/277	3.7/1.7	9.0/255	3.8/1.7	0.75-16UNF-2B
ML7	2015/139	4.38/111.3	9.1/231	3.2/1.5	7.0/198	3.0/1.4	0.75-16UNF-2B
ML6	2015/139	4.38/111.3	7.8/198	2.9/1.3	6.0/170	2.5/1.2	0.75-16UNF-2B
M6	2216/153	3.21/81.5	11.8/300	2.3/1.0	6.0/170	2.3/1.0	0.75-16UNF-2B
M4	2216/153	3.21/81.5	8.7/221	1.7/0.8	4.0/113	1.5/0.7	0.75-16UNF-2B
M2	2216/153	2.50/63.5	5.7/145	0.7/0.3	1.5/42	0.6/0.3	0.75-16UNF-2B

MT-PH-G



MT-PH-B2

★ Notes: a).1 bar ≈ 14.5psi; b).Marks "★" mean CBMTEC well-sold DOT standard ones. Medical CBMTEC aluminum oxygen cylinders can be equipped with OPTIONAL O₂ gas valves, cylinder caps, regulators, cylinder carts as per preferred.



40L

20L

15L

10L



CBM Technologies
(China-Base Medical Technologies)



Click-Style Oxygen Regulators

- Aluminum body with brass high pressure chamber;
- 3000 psi maximum inlet pressure;
- 1-1/2" diameter UL-listed gauge;
- Inlet connection complies to CGA standards;
- Internal relief valve;
- Customized color(green, blue, yellow....);
- Piston design regulator;
- Sintered bronze inlet filter for longer service life;
- Easy to read flow rate window;
- Selection of 0-0.5; 0-1; 0-2; 0-3; 0-4; 0-5; 0-6; 0-8; 0-10; 0-12; 0-15; 0-25 LPM;
- Each with 12 flow settings.



YR-MT870-85



YR-MT870-125



YR-MT540-G



YR-MT870-115



YR-MT870-165



YR-MT540-S

Model Number	Length	Inlet Connection	Outlet Connection	Packaging
YR-MT540-85	85mm	CGA540	Diss Outlet/Barb Outlet Φ8mm	20PCS/CTN 40.5x15.5x35.5 G.W./N.W.: 9/8Kg
YR-MT540-2CV	85mm	CGA540	Diss Outlet/Barb Outlet Φ8mm/G3/4	
YR-MT540-G3/4	85mm	CGA540	Diss Outlet/Barb Outlet, G3/4	
YR-MT540-S	85mm	CGA540	Diss Outlet/Barb Outlet, G3/4	
YR-MT870-115	115mm	CGA870 pin index type	Diss Outlet/Barb Outlet Φ8mm	
YR-MT870-120	120mm	CGA870 pin index type	Diss Outlet/Barb Outlet Φ8mm	
YR-MT870-125	125mm	CGA870 pin index type	Diss Outlet/Barb Outlet Φ8mm	
YR-MT870-165	165mm	CGA870 pin index type	Diss Outlet/Barb Outlet Φ8mm	



YR-MT870-R



YR-MT540-F(Y/S)

YR-MT870-Y



YR-MT540-L