

# CS23336-Introduction to Python Programming

**Started on** Monday, 21 October 2024, 8:38 PM

**State** Finished

**Completed on** Monday, 21 October 2024, 9:17 PM

**Time taken** 38 mins 40 secs

**Marks** 10.00/10.00

**Grade** 100.00 out of 100.00

## Question 1

Correct

Mark 1.00 out of 1.00

Flag question

### Question text

The program must accept **N** integers and an integer **K** as the input. The program must print every **K** integers in descending order as the output.

-

**Note:** If  $N \% K \neq 0$ , then sort the final  $N \% K$  integers in descending order.

### Boundary Condition(s):

$1 \leq N \leq 10^4$

$-99999 \leq \text{Array Element Value} \leq 99999$

### Input Format:

The first line contains the values of **N** and **K** separated by a space.

The second line contains **N** integers separated by space(s).

### Output Format:

The first line contains **N** integers.

### Example Input/Output 1:

Input:

7 3  
48 541 23 68 13 41 6

Output:

541 48 23 68 41 13 6

Explanation:

The first three integers are 48 541 23, after sorting in descending order the integers are **541 48 23**.

The second three integers are 68 13 41, after sorting in descending order the integers are **68 41 13**.

The last integer is **6**.

The integers are **541 48 23 68 41 13 6**

Hence the output is **541 48 23 68 41 13 6**.

Answer:(penalty regime: 0 %)

```
1 n,k=map(int,input().split())
2 arr=list(map(int,input().split()))
3 for i in range(0,n,k):
4     chunk=arr[i:i+k]
5     chunk.sort(reverse=True)
6     print(*chunk,end=' ')
```

Feedback

**Input**

**Expected**

**Got**

7 3  
48 541 23 68 13 41 6 541 48 23 68 41 13 6 541 48 23 68 41 13 6

Passed all tests!

Correct

Marks for this submission: 1.00/1.00.

## Question 2

Correct

Mark 1.00 out of 1.00

Flag question

### Question text

Assume you have an array of length  $n$  initialized with all 0's and are given  $k$  update operations.

Each operation is represented as a triplet: **[startIndex, endIndex, inc]** which increments each element of subarray **A[startIndex ... endIndex]** (startIndex and endIndex inclusive) with **inc**.

Return the modified array after all  $k$  operations were executed.

### Example:

#### Input:

5  
3  
1 3 2  
2 4 3  
0 2 -2

#### Output:

-2 0 3 5 3

### Explanation:

Initial state:

length = 5, updates = [[1,3,2],[2,4,3],[0,2,-2]]

[0,0,0,0,0]

After applying operation [1,3,2]:

[0,2,2,2,0]

After applying operation [2,4,3]:

[0,2,5,5,3]

After applying operation [0,2,-2]:

[-2,0,3,5,3]

Answer:(penalty regime: 0 %)

```
1 n=int(input())
2 k=int(input())
3 arr=[0]*(n+1)
4 for _ in range(k):
5     s,e,inc=map(int,input().split())
6     arr[s]+=inc
7     if e+1<n:
8         arr[e+1]-=inc
9 for i in range(1,n):
10     arr[i]+=arr[i-1]
11 print(' '.join(map(str,arr[:n])))
```

## Feedback

Input	Expected	Got
5		
3		
1 3 2	-2 0 3 5 3	-2 0 3 5 3
2 4 3		
0 2 -2		

Passed all tests!  
Correct  
Marks for this submission: 1.00/1.00.

### Question 3

Correct  
Mark 1.00 out of 1.00  
Flag question

#### Question text

Program to print all the distinct elements in an array. Distinct elements are nothing but the unique (non-duplicate) elements present in the given array.

Input Format:

First line take an Integer input from stdin which is array length n.

Second line take n Integers which is inputs of array.

Output Format:

Print the Distinct Elements in Array in single line which is space Separated

Example Input:

5

1

2

2

3

4

Output:

1 2 3 4

Example Input:

6

1

1

2

2

3

3

Output:

1 2 3

For example:

**Input    Result**

5	
1	
2	1 2 3 4
2	
3	
4	

6	
1	
1	
2	1 2 3
2	
3	
3	

Answer:(penalty regime: 0 %)

```
1 n=int(input())
2 array=[int(input()) for i in range(n)]
3 ele=set(array)
4 print(" ".join(map(str,ele)))
```

**Feedback**

**Input Expected    Got**

5	1 2 3 4	1 2 3 4
1		

## Input Expected Got

```
2
2
3
4

6
1
1
2    1 2 3    1 2 3
2
3
3
```

Passed all tests!

Correct

Marks for this submission: 1.00/1.00.

## Question 4

Correct

Mark 1.00 out of 1.00

Flag question

### Question text

Given an integer  $n$ , return an list of length  $n + 1$  such that for each  $i$  ( $0 \leq i \leq n$ ),  $\text{ans}[i]$  is the number of 1's in the binary representation of  $i$ .

Example:

**Input:**  $n = 2$

**Output:**  $[0, 1, 1]$

**Explanation:**

```
0 --> 0
1 --> 1
2 --> 10
```

Example2:

**Input:**  $n = 5$

**Output:**  $[0, 1, 1, 2, 1, 2]$

**Explanation:**

```
0 --> 0
1 --> 1
2 --> 10
3 --> 11
4 --> 100
5 --> 101
```

Note: Complete the given function alone

For example:

**Test**

**Result**

```
print(CountingBits(5)) [0, 1, 1, 2, 1, 2]
```

Answer:(penalty regime: 0 %)

Reset answer

```
1 def CountingBits(n):
2     ans=[0]*(n+1)
3     for i in range(1,n+1):
4         ans[i]=ans[i>>1]+(i&1)
5     return ans
```

## Feedback

Test	Expected	Got
print(CountingBits(2))	[0, 1, 1]	[0, 1, 1]
print(CountingBits(5))	[0, 1, 1, 2, 1, 2]	[0, 1, 1, 2, 1, 2]

Passed all tests!

Correct

Marks for this submission: 1.00/1.00.

## Question 5

Correct

Mark 1.00 out of 1.00

Flag question

### Question text

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that  $A[i] - A[j] = k$ ,  $i \neq j$ .

Input Format

1. First line is number of test cases T. Following T lines contain:
2. N, followed by N integers of the array



3. The non-negative integer k

Output format

Print 1 if such a pair exists and 0 if it doesn't.

Example

Input

1

3

1

3

5

4

Output:

1

Input

1

3

1

3

5

99

Output

0

For example:

**Input Result**

1

3

1

1

3

5

4

1

0

3

## Input Result

1  
3  
5  
99

Answer:(penalty regime: 0 %)

```
1 T=int(input())
2 for test in range(T):
3     n=int(input())
4     a=[int(input()) for _ in range(n)]
5     k=int(input())
6     res=0
7     for i in range(n):
8         for j in range(n):
9             if i!=j:
10                d=a[i]-a[j]
11                if d == k:
12                    res=1
13 print(res)
```

## Feedback

### Input Expected Got

1		
3		
1		
3	1	1
5		
4		

1		
3		
1		
3	0	0
5		
99		

Passed all tests!

Correct

Marks for this submission: 1.00/1.00.

## Question 6

Correct  
Mark 1.00 out of 1.00  
Flag question

### Question text

Given two arrays of positive integers, for each element in the second array, find the total number of elements in the first array which are *less than or equal* to that element. Store the values determined in an array.

For example, if the first array is  $[1, 2, 3]$  and the second array is  $[2, 4]$ , then there are 2 elements in the first array *less than or equal* to 2. There are 3 elements in the first array which are *less than or equal* to 4. We can store these answers in an array,  $answer = [2, 3]$ .

### Program Description

The program must return an array of  $m$  positive integers, one for each  $maxes[i]$  representing the total number of elements  $nums[j]$  satisfying  $nums[j] \leq maxes[i]$  where  $0 \leq j < n$  and  $0 \leq i < m$ , in the given order.

The program has the following:

$nums[nums[0], \dots, nums[n-1]]$ : first array of positive integers

$maxes[maxes[0], \dots, maxes[m-1]]$ : second array of positive integers

### Constraints

- $2 \leq n, m \leq 10^5$
- $1 \leq nums[j] \leq 10^9$ , where  $0 \leq j < n$ .
- $1 \leq maxes[i] \leq 10^9$ , where  $0 \leq i < m$ .

### Input Format For Custom Testing

Input from stdin will be processed as follows and passed to the program.

The first line contains an integer  $n$ , the number of elements in  $nums$ .

The next  $n$  lines each contain an integer describing  $nums[j]$  where  $0 \leq j < n$ .

The next line contains an integer  $m$ , the number of elements in  $maxes$ .

The next  $m$  lines each contain an integer describing  $maxes[i]$  where  $0 \leq i < m$ .

### Sample Case 0

### Sample Input 0

```
4
1
4
2
4
2
```

3  
5

### Sample Output 0

2  
4

### Explanation 0

We are given  $n = 4$ ,  $nums = [1, 4, 2, 4]$ ,  $m = 2$ , and  $maxes = [3, 5]$ .

1. For  $maxes[0] = 3$ , we have 2 elements in  $nums$  ( $nums[0] = 1$  and  $nums[2] = 2$ ) that are  $\leq maxes[0]$ .
2. For  $maxes[1] = 5$ , we have 4 elements in  $nums$  ( $nums[0] = 1$ ,  $nums[1] = 4$ ,  $nums[2] = 2$ , and  $nums[3] = 4$ ) that are  $\leq maxes[1]$ .

Thus, the program returns the array  $[2, 4]$  as the answer.

### Sample Case 1

### Sample Input 1

5  
2  
10  
5  
4  
8  
4  
3  
1  
7  
8

### Sample Output 1

1  
0  
3  
4

### Explanation 1

We are given,  $n = 5$ ,  $nums = [2, 10, 5, 4, 8]$ ,  $m = 4$ , and  $maxes = [3, 1, 7, 8]$ .

1. For  $maxes[0] = 3$ , we have 1 element in  $nums$  ( $nums[0] = 2$ ) that is  $\leq maxes[0]$ .

2. For  $maxes[1] = 1$ , there are 0 elements in  $nums$  that are  $\leq maxes[1]$ .
3. For  $maxes[2] = 7$ , we have 3 elements in  $nums$  ( $nums[0] = 2$ ,  $nums[2] = 5$ , and  $nums[3] = 4$ ) that are  $\leq maxes[2]$ .
4. For  $maxes[3] = 8$ , we have 4 elements in  $nums$  ( $nums[0] = 2$ ,  $nums[2] = 5$ ,  $nums[3] = 4$ , and  $nums[4] = 8$ ) that are  $\leq maxes[3]$ .

Thus, the program returns the array  $[1, 0, 3, 4]$  as the answer.

Answer:(penalty regime: 0 %)

```

1 n=int(input())
2 nums=[int(input()) for _ in range(n)]
3 m=int(input())
4 maxes=[int(input()) for _ in range(m)]
5 res=[]
6 for max1 in maxes:
7     count=0
8     for num in nums:
9         if num<=max1:
10             count+=1
11     res.append(count)
12 for count in res:
13     print(count)

```

## Feedback

### Input Expected Got

4		
1		
4		
2	2	2
4	4	4
2		
3		
5		
5		
2		
10		
5		
4	1	1
4	0	0
8	3	3
4	4	4
3		
1		
7		
8		

Passed all tests!  
Correct  
Marks for this submission: 1.00/1.00.

## Question 7

Correct  
Mark 1.00 out of 1.00  
Flag question

### Question text

Determine the factors of a number (i.e., all positive integer values that evenly divide into a number) and then return the  $p^{\text{th}}$  element of the list, sorted ascending. If there is no  $p^{\text{th}}$  element, return 0.

### Example

$n = 20$

$p = 3$

The factors of 20 in ascending order are  $\{1, 2, 4, 5, 10, 20\}$ . Using 1-based indexing, if  $p = 3$ , then 4 is returned. If  $p > 6$ , 0 would be returned.

### Constraints

$$1 \leq n \leq 10^{15}$$

$$1 \leq p \leq 10^9$$

The first line contains an integer  $n$ , the number to factor.

The second line contains an integer  $p$ , the 1-based index of the factor to return.

### Sample Case 0

#### Sample Input 0

10

3

#### Sample Output 0

5

### Explanation 0

Factoring  $n = 10$  results in  $\{1, 2, 5, 10\}$ . Return the  $p = 3^{\text{rd}}$  factor, 5, as the answer.

### Sample Case 1

#### Sample Input 1

10

5

### Sample Output 1

0

### Explanation 1

Factoring  $n = 10$  results in  $\{1, 2, 5, 10\}$ . There are only 4 factors and  $p = 5$ , therefore 0 is returned as the answer.

### Sample Case 2

### Sample Input 2

1

1

### Sample Output 2

1

### Explanation 2

Factoring  $n = 1$  results in  $\{1\}$ . The  $p = 1$ st factor of 1 is returned as the answer.

For example:

### Input Result

10 5  
3

10 0  
5

1 1  
1

Answer:(penalty regime: 0 %)

```
1 n=int(input())
2 p=int(input())
3 def factor(num):
4     fact=[]
5     for i in range(1,num+1):
6         if num%i==0:
7             fact.append(i)
8     return fact
9 fact1=factor(n)
10 if p<=len(fact1):
11     print(fact1[p-1])
12 else:
13     print(0)
```

## Feedback

### Input Expected Got

10	5	5
3		

10	0	0
5		

1	1	1
1		

Passed all tests!

Correct

Marks for this submission: 1.00/1.00.

## Question 8

Correct

Mark 1.00 out of 1.00

Flag question

### Question text

Complete the program to count frequency of each element of an array. Frequency of a particular element will be printed once.

### Sample Test Cases

#### Test Case 1

#### Input

7

23



45

23

56

45

23

40

## Output

23 occurs 3 times

45 occurs 2 times

56 occurs 1 times

40 occurs 1 times

Answer:(penalty regime: 0 %)

```
1 n=int(input())
2 ele=[]
3 for _ in range(n):
4     ele.append(int(input()))
5 f={}
6 for n in ele:
7     if n in f:
8         f[n]+=1
9     else:
10        f[n]=1
11 for n,count in f.items():
12     print(f"{n} occurs {count} times")
```

## Feedback

Input	Expected	Got
7	23 occurs 3 times	23 occurs 3 times
23	45 occurs 2 times	45 occurs 2 times
45		

Input	Expected	Got
23	56 occurs 1 times	56 occurs 1 times
56	40 occurs 1 times	40 occurs 1 times
45		
23		
40		

Passed all tests!

Correct

Marks for this submission: 1.00/1.00.

## Question 9

Correct

Mark 1.00 out of 1.00

Flag question

### Question text

Given a matrix mat where every row is sorted in **strictly increasing** order, return the **smallest common element** in all rows.

If there is no common element, return -1.

### Example 1:

#### Input:

```

4 5
1 2 3 4 5
2 4 5 8 10
3 5 7 9 11
1 3 5 7 9

```

#### Output:

```

5

```

#### Constraints:

- $1 \leq \text{mat.length}, \text{mat}[i].\text{length} \leq 500$
- $1 \leq \text{mat}[i][j] \leq 10^4$
- $\text{mat}[i]$  is sorted in strictly increasing order.

Answer:(penalty regime: 0 %)

```

1 rows,col=map(int,input().split())
2 matrix=[list(map(int,input().split())) for _ in range(rows)]
3
4 count={}
5 for elem in matrix[0]:
6     count[elem]=1
7 for i in range(1,rows):
8     for elem in matrix[i]:
9         if elem in count and count[elem]==i + 1 - 1:
10            count[elem]+=1
11 smallestcommonelemnt=1
12 for elem in matrix[0]:
13     if count.get(elem)==rows:
14         smallestcommonelement=elem
15         break
16 print(smallestcommonelement)

```

## Feedback

Input	Expected Got
4 5	
1 2 3 4 5	
2 4 5 8 10 5	5
3 5 7 9 11	
1 3 5 7 9	

Passed all tests!

Correct

Marks for this submission: 1.00/1.00.

## Question 10

Correct

Mark 1.00 out of 1.00

Flag question

## Question text

An array is monotonic if it is either **monotone increasing** or **monotone decreasing**.

An array A is monotone increasing if for all  $i \leq j$ ,  $A[i] \leq A[j]$ . An array A is monotone decreasing if for all  $i \leq j$ ,  $A[i] \geq A[j]$ .

Write a program if n array is monotonic or not. Print "True" if is monotonic or "False" if it is not. Array can be monotone increasing or decreasing.

Input Format:

First line n-get number of elements

Next n Lines is the array of elements

Output Format:

True ,if array is monotone increasing or decreasing.

otherwise False is printed

Sample Input1

4

5

6

7

8

Sample Output1

True

Sample Input2

4

6

5

4

3

Sample Output2

True

Sample Input 3

4

6

7

8

7

Sample Output3

False

For example:

**Input Result**

4  
6  
5     True  
4  
3

Answer:(penalty regime: 0 %)

```
1  n=int(input())
2  arr=[]
3  for _ in range(n):
4      arr.append(int(input()))
5  def ismonotonic(array):
6      inc=dec=True
7      for i in range(1,len(array)):
8          if array[i]<array[i-1]:
9              inc=False
10         if array[i]>array[i-1]:
11             dec=False
12         return "True" if inc or dec else "False"
13 print(ismonotonic(arr))
```

**Feedback**

**Input Expected    Got**

4  
6  
5     True     True  
4  
3

	Input	Expected	Got
--	-------	----------	-----

4			
3			
5	False	False	
7			
4			

4			
1			
6	False	False	
9			
2			

4			
9			
6	True	True	
4			
2			

3			
2	False	False	
1			
4			

Passed all tests!

Correct

Marks for this submission: 1.00/1.00.

[Finish review](#)