MPUTER	inal Title	PUNCH	COMP.	<u>4</u>	8	e 4	, d	4	9		7.8	4 4	REPLY	PUNCH	READER	SELECT	RESET.	COMP. CODE	CODE	COPE	+	4 6 7	CODE	3 S	CODE	C00E	L 9		
920B COMPUTER	Destination	ON THE	UNIT 5 PIN 20	3 PL2 /A	3 PL2/B	3PL2/C	4/ 2/ de		3PL2/F		3PL2/G	3PL2/H	3PL2/W	D LIND		N N	P I I N I	PIN 24 UNIT 8 PIN H	PIN K	8). E.	Z	o a E N	UNIT B	Pin V	S Z	ONIT &	P N A E	Issue	Approved
0) 4.	T EX	90	52	- tr	1	1	a	•	· +		AA	A A B) V	72	7		22	61 73	30	tn		9	9_	=	±	ū	n]=" 4	*
		13																									G 1	7 12 12 12 12 12 12 12 12 12 12 12 12 12	
		π \$4											2 X X 4 7 4 7						-	,				3			がまらが数例が低ががばばがばばばばばばばばに A B C D E F G	州域時が開始が開始が開め、 X X X P P A X B B A X B B A X B B A X B B B A X B B B A X B B B B	=
LLER			a		2	69	키 [코	- 27	E)			2]	El Z		2		<u> </u>	,		<u> </u>								X X X	5 _ =
PE CONTRO						(h)) () (-	/ `	5	(<u>-</u>)	+) (<u>i</u>		S AL						4.				C D	N 18 18 X	5
TITLE PAPER TAPE CONTROLLER MARK I																	1					· .					1 8 7	धीआ है।	=
TT.																											73.	I	<u></u>
																	L												
													6																
					22	<u></u>	1	21	n		_	21	<u>5</u>		12		E A	(a)	E C	a =		<u></u>			a =	<u> </u>		la:	
			ō	4		in	ō -) m	ın	[]			un o		+		(a) 1/2		(RL)	7		<u>a</u>	2 RL	(A)	[]) (
									į					_															6
	Source Pin	PL2/3 27	PINIS 24	UNIT 4 E	UNIT PINE	UNIT 4 C	4 TWO		MODE SWITCH		SWITCH E	MODE SWITCH Y	NIT3 FIN H	PL2/h 18	2		L2/4 6	3PL2/J AF	PL2/K AE	3	E /9	1/2/	12/8	L2 /N B	PL2 / S 13	9	*	INT 5 20	
	Title So	e e	COMP. U	39-	200E	300		4 930 M			CODE	CODE SW	REPLY	FUNCH 3 P	READER	n .	COMP. 3 PI	Ide Ide	092 339	4	0	993 3PI	0P6 3P	0P5 3P	968	2	5	COMP. UNIT 5 RESET PIN 25	