

CSC 211: Object Oriented Programming

Copy Constructors and Assignment Operator

Michael Conti

Department of Computer Science and Statistics
University of Rhode Island

Spring 2020



Original design and development by Dr. Marco Alvarez

More on constructors ...

- So far ...
 - default constructors, overloaded constructors
- C++ also defines **copy constructors**
 - used to create an object as a copy of an existing object
 - if you don't define your own, C++ will synthesize one copy constructor for you

```
Point2D obj1;           // default constructor
Point2D obj2(4.5, 3.2); // overloaded constructor
Point2D obj3(obj2);      // copy constructor
Point2D obj4 = obj3;     // copy constructor
```

2

When are copy constructors invoked?

```
Point2D myfunc(Point2D obj) {
    Point2D newobj;
    // ...
    return newobj;
}

int main () {
    // copy constructor is invoked when an object is initialized from
    // another object of the same type
    Point2D obj2(4.5, 3.2); // overloaded constructor
    Point2D obj3(obj2);     // copy constructor
    Point2D obj4 = obj3;    // copy constructor

    // copy constructor is invoked when a non-reference object is
    // passed to a function
    myfunc(obj4);           // copy constructor

    // copy constructor is invoked when a non-reference object is
    // returned from a function
    Point2D obj5 = myfunc(obj2);
}
```

3

Shallow vs deep copies

- Synthesized copy constructors perform **shallow copies**
 - a shallow copy is a byte-to-byte copy of all data members (works fine most of the cases, except when pointers are used)
- ```
Point2D::Point2D(const Point2D& obj) {
 x = obj.x;
 y = obj.y;
 // ...
}
```
- Sometimes a **deep copy** is necessary (can handle more complex objects)
    - must define your own copy constructor

4

```


class Array {
public:
 Array(int cap);
 ~Array();
private:
 int size;
 int capacity;
 int *ptr;
};

Array::Array(int cap) {
 size = 0;
 capacity = cap;
 ptr = new int[cap];
}

Array::~Array() {
 delete [] ptr;
}

int main () {
 Array obj1(10);
 Array obj2(obj1);
 Array obj3 = obj2;
}

```



shallow copies

5

```


Array::Array(int cap) {
 size = 0;
 capacity = cap;
 ptr = new int[cap];
}

Array::Array(Array& obj) {
 size = obj.size;
 capacity = obj.capacity;
 ptr = new int[capacity];
 for (int i = 0 ; i < size ; i++) {
 ptr[i] = obj.ptr[i];
 }
}

Array::~Array() {
 delete [] ptr;
}

int main () {
 Array obj1(10);
 Array obj2(obj1);
 Array obj3 = obj2;
}

```



deep copies

6

## The assignment operator =

- Assignment is not construction
- The assignment operator '=' assigns an object to an existing object (already constructed)

```

Point2D obj1; // default constructor
Point2D obj2(4.5, 3.2); // overloaded constructor
Point2D obj3(obj2); // copy constructor
Point2D obj4 = obj3; // copy constructor
obj1 = obj4; // assignment operator

```

- If you don't define your own, C++ will synthesize one assignment operator for you (performs **shallow copy**)

7

## How to overload the '=' operator?

```

Point2D& Point2D::operator=(const Point2D &obj) {
 // always check against self-assignment
 // especially when performing deep copies
 if (this != &obj) {
 x = obj.x;
 y = obj.y;
 }
 // always return *this, necessary for
 // cascade assignments (a = b = c)
 return *this;
}

```

can perform either shallow or deep copies

8

## The `this` pointer

- Pointer accessible only within member functions of a class
  - ✓ it points to the object for which the member function is called
  - ✓ static member functions do not have this pointer

```
void Date::set_year(int y) {
 // statements below are equivalent
 year = y;
 this->year = y;
 (*this).year = y;
}
```

9

## How many calls?

```
Point2D myfunc(const Point2D& obj) {
 Point2D newobj;
 newobj = obj;
 // ...
 return newobj;
}

int main () {
 Point2D obj2(4.3, 1.1);
 Point2D obj3(obj2);
 Point2D obj4 = myfunc(obj3);
 Point2D obj5;
 obj5 = obj4 = obj2;
}
```

10