Group 54 Progress Report: X-Ray Vision

Luna Aljammal, Andrew Goetz, Djordje Kokot
{aljammal,goetz3,kokotd}@mcmaster.ca

1 Introduction

Pneumonia is a severe respiratory infection causing significant morbidity and mortality worldwide, especially in young children. Accurate and timely diagnosis is crucial for effective treatment and improving outcomes. Traditionally, diagnosis relies on expert radiologists interpreting chest X-rays, but deep learning-based automated detection systems offer potential for faster and scalable assessment. Our project aims to develop a binary classification model that distinguishes between normal and bacterial pneumonia pediatric chest X-ray images using convolutional neural networks (CNNs) and transfer learning with pretrained weights.

2 Related Work

One of the most influential works in this area is CheXNet by Rajpurkar et al., who trained a 121-layer DenseNet on a much larger dataset "NIH ChestX-ray14 dataset" (over 100,000 adult radiographs with 14 labels) and showed that their model could detect pneumonia at or above average radiologist performance on a held-out test set (for certain pathologies). They later extended this approach to CheXNeXt, a multi-label model that jointly predicts multiple thoracic pathologies from a single chest X-ray (Rajpurkar, 2018). These works popularized the use of deep, CNNs on large CXR datasets. We drew insipiration from this paradigmin our own model.

Previous work done on a similar task by

$$x$$

has shown the effectiveness of both Convolutional Neural Networks and transfer learning in the domain medical image classification managing to achieve accuracies of >90% on multi-label classification problems using Optical Coherence Tomography Images with Choroidal Neovascularization(CNV)/Drusen/Diabetic Macular Edema(DME); and Chest X-Rays with either Viral/Bacterial Pneumonia. According to

$$x$$

transfer learning is a great tool for domains when only limited data is available, a major issue faced in using these models is that they are quite large compared to the dataset and when fine tuning deeper layers they can easily overfit to the training set.

A contrasting line of work to the transfer-learning paradigm uses classical machine learning on hand-crafted features rather than deep CNNs. (Nagashree and Mahanand, 2023) present a system for pneumonia chest X-ray classification using a Support Vector Machine (SVM), targeting the same type of task as ours: distinguishing pneumonia from normal cases in chest radiographs. Instead of learning features from scratch, they first extract Haar, shape, and texture descriptors from each X-ray and then train an SVM on these fixed feature vectors. Their study compares SVM performance against several other classifiers (decision trees, naive Bayes, k-nearest neighbours) and reports that SVM achieves the best overall accuracy for pneumonia detection. This pipeline is an example of a non–transfer-learning approach: all discriminative information comes from manually engineered features, and no pretrained deep network or ImageNet-style initialization is used.

Another strand of work in medical image classification explicitly tries to go beyond the standard of transfer learning. (Hosny, 2025) proposed an attention-enhanced deep learning framework for multiclass gastrointestinal (GI) disease classification that they explicitly frame as “beyond transfer learning”. They argue that many existing GI pipelines rely on standard transfer learning with pretrained CNNs either as standalone classifiers, as components in ensembles, or as frozen feature extractors feeding shallow classifiers. They claim

that these pipelines can be overly generic, computationally heavy, and perhaps not ideal for clinical settings. They propose a novel end-to-end DL model for multiclass GI disease classification called IRA-DenseNet201. They still start from a pretrained DenseNet201, but instead of just using a new layer on top, they wrap it in extra blocks (Inception, residual, attention, etc.). THese extra layers are designed specifically for GI disease images. In other words, they use transfer learning, but then customize and extend the backbone so the whole network is more specialized for their medical task. This is not directly related to our work as it is a different disease being classified but it does propose a valuable insight and potential strategy into how we can impove our work.

3 Dataset

We use the publicly available pediatric chest X-ray dataset sourced from Guangzhou Women and Children's Medical Center. This dataset contains over 5,800 frontal chest X-ray images of pediatric patients aged between 1 and 5 years. Images are categorized as Normal, Viral Pneumonia, or Bacterial Pneumonia. For our project, we focus on distinguishing Normal images from those showing Bacterial Pneumonia, making it a binary classification task aligned with clinical priorities.

The dataset we received has already undergone thorough quality control and was expertly annotated by radiologists before release. Poor-quality scans or unreadable images were excluded, and all images bear reliable labels confirmed by multiple reviewers. This ensures that the dataset is well-suited for training without requiring additional manual cleanup from our side.

The data is split into training, validation, and test sets, comprising 80%, 10%, and 10% of the dataset respectively. Stratified sampling maintains equal class distribution proportions across splits to prevent skewed training or evaluation.

Each image is resized to a fixed 160×160 pixel resolution. This size was chosen to balance model input requirements, computational efficiency, and sufficient preservation of pulmonary detail crucial for diagnosis. Pixel intensities are normalized using ImageNet channel mean and standard deviation statistics, a standard practice that promotes better convergence when fine-tuning pretrained convolutional neural networks.

To increase training data diversity and reduce overfitting due to limited sample variety, we apply several augmentation techniques. These include random resized cropping to simulate scale variation, random horizontal flips to capture left-right anatomical invariance, slight random rotations to accommodate patient positioning variability, and brightness jittering to model differences in imaging conditions.

Additionally, we introduced an optional histogram equalization step performed prior to other augmentations. This enhances the contrast of lung fields, potentially highlighting subtle features such as infiltrates or consolidations that aid model learning.

Figure 1 shows the class distribution in the training subset. Pneumonia cases are approximately



Figure 1: Class distribution in the training set.

three times more frequent than normal cases. To mitigate training bias from this class imbalance, we employ class weighting in the loss function, encouraging the model to learn balanced representations for both classes. The patients' have their personal information removed for the purposes of maintaining their privacy. The Operationalization of medical diagnoses is simple because the problem is very objective and requires the use of Experts to do the labeling.

Together, these dataset preparation strategies provide a solid and clinically relevant foundation for building an automated pediatric pneumonia diagnosis system.

4 Features

Our model processes the input chest X-ray images by first applying augmentations and normalization to prepare the data for training. The images are originally grayscale but are converted into three-channel format to be compatible with the pretrained ResNet18 model we use. The network learns features automatically through fine-tuning

the pretrained model. This means the model adjusts both low-level and higher-level layers to better capture patterns specific to pneumonia detection. We do not perform any manual feature engineering beyond the applied data augmentations. The representations are learned end-to-end, enabling the model to identify relevant structures and textures within the X-ray images that distinguish normal lungs from bacterial pneumonia.

5 Implementation

The model uses a ResNet18 convolutional neural network pretrained on ImageNet. Initially, we freeze all pretrained layers except the final fully connected layer, which is replaced to suit our binary pneumonia classification task. In this stage, only the classification head is trained, enabling the network to learn the mapping from extracted features to target labels while keeping the general feature extractor unchanged. Once the classification head achieves satisfactory performance, we unfreeze the last convolutional block to fine-tune deeper layers. This process allows the network to adapt more task-specific features relevant to pediatric chest X-rays and pneumonia detection. We apply a reduced learning rate during fine-tuning to stabilize training and preserve useful pretrained representations.

To address class imbalance in the dataset, we use a weighted cross-entropy loss, formulated as:

$$\mathcal{L} = -\sum_{i=1}^{N} w_{y_i} \log p(y_i \mid \mathbf{x}_i) \tag{1}$$

Here, N is the number of samples, y_i is the true label of sample i, w_{y_i} is the corresponding class weight compensating for imbalance, and $p(y_i \mid \mathbf{x}_i)$ is the predicted probability for the correct class given input $\mathbf{x}_i$.

Training is performed using the Adam optimizer with weight decay to regularize model parameters and reduce overfitting. We utilize early stopping based on the validation F1-score to halt training when improvements plateau, ensuring the preservation of the best model weights. For baseline comparison, a simple majority-class classifier is implemented, which always predicts the most frequent class in the training set. This baseline sets a minimal performance bar that our trained model is expected to exceed. Data augmentation and preprocessing during training contribute to model robustness. Challenges encountered include tuning when to freeze or unfreeze layers and selecting appropriate learning rates, addressed through iterative experimentation guided by validation metrics.

The modular design of the implementation facilitates easy extension with alternative models, loss functions, or augmentation methods in future work. Overall, this transfer learning approach provides a strong framework for pediatric pneumonia classification with promising initial results.

6 Results and Evaluation

We evaluate our model using stratified training, validation, and test splits.The validation set is used for hyperparameter tuning and early stopping, while the test set provides an unbiased estimate of final model performance.

Our evaluation metrics include accuracy, precision, recall, F1-score, and ROC-AUC. Accuracy measures the overall correct predictions; precision and recall focus on positive (pneumonia) detection performance, which is critical in a medical context to minimize missed diagnoses. The F1-score balances precision and recall, and the ROC-AUC quantifies the model's discrimination ability across thresholds.

The baseline model used for comparison is a majority-class classifier that predicts the most frequent class in the training data.

We also compare against a majority-class baseline and visualize performance using a confusion matrix. The CNN substantially outperforms the baseline across all metrics, with F1-score improving from 0.55 to >0.85 and recall notably higher, indicating fewer missed pneumonia cases.

We plan to incorporate k-fold cross-validation in future work for more robust performance estimates.




Figure 2: Confusion matrix showing model performance on the test set.

Specifically, the validation F1-score improved

from approximately 0.55 (baseline) to over 0.85 with the CNN. Recall increased notably, signaling fewer missed pneumonia cases. Confusion matrices further confirm enhanced true positive detection while controlling false positives. These preliminary results demonstrate that fine-tuning the pretrained ResNet18 with our preprocessing and augmentation pipeline yields a robust pneumonia classifier with strong generalization to unseen data. Future milestones include implementing k-fold cross-validation for more reliable estimates and further interpreting misclassification patterns to refine the model.

7 TA Feedback and Reflection

The primary feedback from our TA emphasized the importance of using a simple baseline for comparison, specifically the majority-class classifier. This baseline predicts the most frequent class in the training data and establishes a clear performance threshold that the CNN model should surpass. Including such a baseline is essential for contextualizing model results and avoiding overstated performance claims.

Reflecting on this advice, we integrated the majority baseline into our evaluation framework and confirmed that our CNN model consistently outperforms it across key metrics. This strengthens confidence in the effectiveness of our transfer learning approach for pneumonia detection.

The TA also recommended focusing on binary classification between Normal and Bacterial Pneumonia instead of including Viral Pneumonia. This simplifies the task and keeps the project scope focused. All data preparation and model design follow this two-class goal, with the majority baseline serving as a clear reference point. A multiclass version may be explored later as an extension to this project.

In addition, the TA, mentioned that we could attempt to use multiple models (ie in a strategy similar to transfer learning), to use CNN features with an SVM which is a useful consideration we can make as we move forward

Overall, the TA's guidance reinforced the importance of rigorous benchmarking and comparative evaluation, which will remain central to our approach in future milestones.The guidance also helps us view transfer learning as simply one component of a larger paradigm. Based on the TA's feedback we will continue to experiment with different methods and small tweaks. Transfer learning is just one small part of our pipeline, and we are planning on exploring additional ways of differentiating our model as well.

One area where we faced issues was with training on our local machine and subsequently had to switch to cloud. This was an reminder that going forward we may need to consider model complexity and training time, at least to some extent.

Our implementation so far has highlighted several areas for improvement. First, the initial ResNet-18 transfer-learning model (with only the final layer trained) shows signs of overfitting, with training loss decreasing while validation loss and F1 sometimes degrade. This indicates that for the remaining weeks we need to experiment more with stronger regularization, data augmentation, and hyperparameter tuning.

We plan on extending our model both with and without transfer learning (using pre-trained weights). We will continue to experiment with transfer learning by adding a tuning phase where the last ResNet block is unfrozen and trained with a small learning rate, to attempt a deeper adaptation to our data. As previously mentioned, based on feedback we may also introduced our own models for learning features or introduce new models that make use of the wights learned by our existing model.

Since transfer learning relies on the pretrained weights of a generalized model they will always underperform compared to Specialized models that have been trained on a large dataset. Our next steps will be to investigate other Image classifying networks such as basic CNNs to gauge whether or not our dataset is large enough to continue pursuing Transfer Learning and provide another baseline for our model evaluation.

8 Template Notes

8.1 Tables and figures

See Table 1 for an example of a table and its caption. See Figure **??** for an example of a figure and its caption.

8.2 Citations

Table 1 shows the syntax supported by the style files. We encourage you to use the natbib styles. You can use the command `\citet` (cite in text) to get "author (year)" citations, like this citation to a paper by Gusfield (1997). You can use the

Output	natbib command	ACL only command
(Gusfield, 1997)	\citep	
Gusfield, 1997	\citealp	
Gusfield (1997)	\citet	
(1997)	\citeyearpar	
Gusfield's (1997)		\citeposs

Table 1: Citation commands supported by the style file.

command \citep (cite in parentheses) to get "(author, year)" citations (Gusfield, 1997). You can use the command \citealp (alternative cite without parentheses) to get "author, year" citations, which is useful for using citations within parentheses (e.g. Gusfield, 1997).

8.3 References

Many websites where you can find academic papers also allow you to export a bib file for citation or bib formatted entry. Copy this into the custom.bib and you will be able to cite the paper in the LaTeX. You can remove the example entries.

8.4 Equations

An example equation is shown below:

$$A = \pi r^2 \tag{2}$$

Labels for equation numbers, sections, subsections, figures and tables are all defined with the \label{label} command and cross references to them are made with the \ref{label} command. This an example cross-reference to Equation 2. You can also write equations inline, like this: $A = \pi r^2$.

Team Contributions

Luna worked on data preprocessing and augmentation, addressing class imbalance. Andrew focused on model adaptation, training, and hyperparameter tuning. Djordje handled evaluation, baselines, and visualization. All contributed equally to report writing and refinement.

References

Rie Kubota Ando and Tong Zhang. 2005. A framework for learning predictive structures from multiple tasks and unlabeled data. *Journal of Machine Learning Research*, 6:1817–1853.

Galen Andrew and Jianfeng Gao. 2007. Scalable training of L1-regularized log-linear models. In *Proceedings of the 24th International Conference on Machine Learning*, pages 33–40.

Dan Gusfield. 1997. *Algorithms on Strings, Trees and Sequences*. Cambridge University Press, Cambridge, UK.

Mohammad Sadegh Rasooli and Joel R. Tetreault. 2015. Yara parser: A fast and accurate dependency parser. *Computing Research Repository*, arXiv:1503.06733. Version 2.