

UNIVERSITY OF CALIFORNIA
Los Angeles

An Application of Split Attention Networks:
Melanoma Detection

A thesis submitted in partial satisfaction
of the requirements for the degree
Master of Applied Statistics

by

Andrew Mashhadi

2023

© Copyright by
Andrew Mashhadi
2023

ABSTRACT OF THE THESIS

An Application of Split Attention Networks:
Melanoma Detection

by

Andrew Mashhadi

Master of Applied Statistics

University of California, Los Angeles, 2023

Professor Yingnian Wu, Chair

(Abstract temporarily omitted)

The thesis of Andrew Mashhadi is approved.

Michael Tsiang

Frederic Paik Schoenberg

Yingnian Wu, Committee Chair

University of California, Los Angeles

2023

TABLE OF CONTENTS

1	Introduction	1
1.1	Background	1
1.2	Problem Statement	2
2	Dataset	3
2.1	ISIC 2020 Challenge Dataset	3
2.2	Training, Validation, and Testing Sets	4
2.3	Exploratory Analysis	4
2.4	Image Augmentations	4
3	Modeling	5
3.1	Multi-Network Ensemble Learning	5
3.2	Network for Contextual Features	5
3.3	Network for Lesion Images	5
3.3.1	Convolutional Neural Network	5
3.3.2	ResNeSt	6
4	Results	7
4.1	CNN + MLP Ensemble Results	7
4.2	ResNeSt + MLP Ensemble Results	7
5	Conclusion and Future Work	8
	References	9

LIST OF FIGURES

LIST OF TABLES

CHAPTER 1

Introduction

1.1 Background

In the past decade, machine learning has exploded in popularity. Machine learning methods have demonstrated endless applications to a variety of industries including but not limited to engineering, science, finance, medicine, and technology. A large branch of machine learning that has recently taken the world by storm is *deep learning*. Deep learning is made up of *artificial neural networks* (ANN) and is generally trained with a form of *feature learning*.

Neural network architectures have evolved and expanded since the original perceptron and ANN models. Through different areas of application, variations in neural network architecture such as *deep neural networks*, *convolutional neural networks*, *recurrent neural networks*, and more recently *transformers*, have all been proposed and adopted. It is no secret that the transformer model has quickly become a front-runner for applications in computer vision due to its successes in natural language processing. However, deep convolutional neural networks are still state-of-the-art for tasks such as image classification, object detection, semantic segmentation, and instance segmentation

Different learning methods have also been adopted. However, the type of learning method used generally depends on the model's particular objective. *Supervised Learning* is one of the most common methods for classification or regression models. It is the process of using labeled datasets to train machine learning models to classify or predict outcomes appropriately. *Unsupervised Learning* generally involves the analysis or clustering of unlabeled datasets. And *Reinforcement Learning* is based on rewarding desired behaviors and/or punishing undesired ones.

More recently, the medical community has been opening it's doors to modern deep learning techniques. In particular, convolutional neural networks have often been used to develop more efficient, and accurate, diagnostic tools to analyze medical images. Due to the growth of effective image recognition models, collection of medical images for specific applications in the healthcare community have been growing.

1.2 Problem Statement

Skin cancer is one of the most common types of cancer. Although melanoma only accounts for about 1% of skin cancer, the death rate was still about 2.1 per 100,000 men and women per year based on 2016-2020 deaths [Ins23]. In 2023, the American Cancer Society estimates that about 7,990 people are expected to die from a total of about 97,610 new melanoma cases in the United States alone [Soc23]. It is well known that early detection of melanoma will provide the best chance for successful treatment and greater chance of survival.

Image analysis tools that automate the diagnosis of melanoma will improve dermatologist's diagnostic accuracy, and better detection of melanoma has the opportunity to positively impact millions of people. Providing an accurate machine learning model to aid dermatologist's in their evaluations of patients moles may lead to an earlier diagnoses, and could therefore provide the best chance for appropriate intervention. The goal of this paper is to identify the presence of melanoma using images of skin lesions. In particular, we want to use a patients skin-lesion images along with any patient-level contextual information to determine which patients are likely to have melanoma skin cancer.

CHAPTER 2

Dataset

2.1 ISIC 2020 Challenge Dataset

For this paper, we used the “ISIC 2020 Challenge Dataset”. This was the official dataset of the SIIM-ISIC Melanoma Classification Challenge hosted as a Kaggle sponsored competition in the Summer of 2020. It contains over 30,000 dermoscopic images of distinct skin lesions from approximately 2,000 patients. Each image is labeled with an associated “beniegn” or “malignant” status, and the corresponding patient-level features:

- *patient_id*: unique patient idenitfier
- *sex*: sex of the patient
- *age_approx*: approximate age of the of the patient
- *anatom_site_general_challenge*: the general location of imaged lesion
- *diagnosis*: additional details regarding the diagnosis

We should note that all associated malignant and benign diagnoses have been confirmed using histopathology, expert agreement, or longitudinal follow-up [ISI20].

The International Skin Imaging Collaboration (ISIC) was responsible for compiling the images from the Hospital Clínic de Barcelona, Medical University of Vienna, Memorial Sloan Kettering Cancer Center, Melanoma Institute Australia, University of Queensland, and the University of Athens Medical School to form this official dataset. The ISIC Archive contains the largest collection of quality-controlled dermoscopic images of skin lesions available to the public.

The resolution of each image varied drastically throughout the dataset, with some images reaching as high as 4000x6000 pixels. The set of images consisted of over 110GB, so we hosted the data on UCLA's Hoffman2 Linux Cluster. To support the size of each image and the large number of individual images within the dataset, we used computing resources from the Hoffman2 cluster and Google Colab to tune, train, and test our models with powerful *Graphical Processing Units* (GPUs). Although the GPU would occasionally change, we mostly used a single NVIDIA A100 GPU with approximately 40GB VRAM to train our larger models.

2.2 Training, Validation, and Testing Sets

Write about class imbalance (up sampling + bootstrapping in training), and the train+val+test split made.

The training/testing split was set to 80/20 percent. While validating, the validation set consisted of an additional split from the training set. Once hyper-parameters were tuned, the entire training set was used to train the networks and ultimately make predictions on the test set.

Ultimately, I found that the only way to train efficiently with sufficient batch-size (16+ images per batch) was to center cropped or resize (using bilinear interpolation) the original lesion images to 512x512. This saved training time, and allowed for optimal results from my models.

2.3 Exploratory Analysis

Write about EDA results, and provide examples of benign vs malignant images.

2.4 Image Augmentations

Write about cropping augmentations to training data, etc.

CHAPTER 3

Modeling

3.1 Multi-Network Ensemble Learning

Discuss the idea of using the two network ensemble. One MLP for meta data and the CNN for the image data. Discuss the use of the mentioned Image Augmentations and then discuss the idea of Batch Normalization, Adam Optimizer, L2 Regularization, and Dropout layers. Discuss the difference between starting the CNN weights at random values, vs starting the ResNeSt weights at the IMAGENET trained weights and finetuned for our set of data (effectively leveraging their training).

3.2 Network for Contextual Features

Give back-ground on Multi-Layer Perceptron for metadata.

3.3 Network for Lesion Images

3.3.1 Convolutional Neural Network

Write here. Discuss final implementation of Batch Normalization, Adam Optimizer, L2 Regularization, and Dropout layers.

3.3.2 ResNeSt

Write about evolution from CNN to ResNet to ResNeSt. Also use the following description of ResNeSt somewhere (from pytorch website):

While image classification models have recently continued to advance, most downstream applications such as object detection and semantic segmentation still employ ResNet variants as the backbone network due to their simple and modular structure. We present a simple and modular Split-Attention block that enables attention across feature-map groups. By stacking these Split-Attention blocks ResNet-style, we obtain a new ResNet variant which we call ResNeSt. Our network preserves the overall ResNet structure to be used in downstream tasks straightforwardly without introducing additional computational costs. ResNeSt models outperform other networks with similar model complexities, and also help downstream tasks including object detection, instance segmentation and semantic segmentation.

Discuss final implementation of Batch Normalization, Adam Optimizer (different rates), L2 Regularization, and Dropout layers.

CHAPTER 4

Results

4.1 CNN + MLP Ensemble Results

Write here. Give all plots from analysis notebook. Give table of statistics and confusion matrix.

4.2 ResNeSt + MLP Ensemble Results

Write here. Write here. Give all plots from analysis notebook. Give table of statistics and confusion matrix. Compare to regular CNN + MLP model.

CHAPTER 5

Conclusion and Future Work

Write here.

REFERENCES

- [Ins23] National Cancer Institute. “Cancer Stat Facts: Melanoma of the Skin.”, 2023. Last Accessed: 2023-03-20.
- [ISI20] “The ISIC 2020 Challenge Dataset.”, 2020. Last Accessed: 2023-02-13.
- [Soc23] American Cancer Society. “Key Statistics for Melanoma Skin Cancer.”, 2023. Last Accessed: 2023-03-20.