

EPICS QT Framework

2.0.0

Generated by Doxygen 1.7.4

Wed Nov 21 2012 15:31:41

Contents

1	QE framework - EPICS aware Qt Widgets and data access classes	1
1.1	Documentation	1
1.2	License	2
1.3	Platforms	2
1.4	Screenshots	2
1.5	Downloads	2
1.6	Installation	2
1.7	Support	3
1.8	Related Projects	3
1.9	Credits:	3
2	GNU General Public License	5
3	ASgui screen shots	7
4	other applications using epicsqt widgets	13
5	Qt Designer	15
6	Qt Creator	17
7	Class Index	19
7.1	Class Hierarchy	19
8	Class Index	23
8.1	Class List	23
9	Class Documentation	27
9.1	_Field Class Reference	27

9.2	_Item Class Reference	28
9.3	_QDialogItem Class Reference	28
9.4	_QDialogLogin Class Reference	28
9.5	_QPushButtonGroup Class Reference	29
9.6	_QTableWidgetFileBrowser Class Reference	29
9.7	_QTableWidgetLog Class Reference	30
9.8	_QTableWidgetScript Class Reference	30
9.9	QEAnalogIndicator::Band Struct Reference	30
9.10	QEAnalogIndicator::BandList Class Reference	31
9.11	qcastatemachine::ConnectionQCaStateMachine Class Reference	31
9.12	ContainerProfile Class Reference	31
9.13	contextMenu Class Reference	33
9.14	contextMenuObject Class Reference	35
9.15	QEPeriodic::elementInfoStruct Struct Reference	35
9.16	flipRotateMenu Class Reference	36
9.17	imageContextMenu Class Reference	36
9.18	imageMarkup Class Reference	37
9.19	localEnumerationItem Class Reference	38
9.20	managePixmap Class Reference	39
9.21	markupBeam Class Reference	39
9.22	markupHLine Class Reference	40
9.23	markupItem Class Reference	41
9.24	markupLine Class Reference	42
9.25	markupRegion Class Reference	43
9.26	markupTarget Class Reference	43
9.27	markupText Class Reference	44
9.28	markupVLine Class Reference	45
9.29	PeriodicDialog Class Reference	45
9.30	PeriodicElementSetupForm Class Reference	46
9.31	PeriodicSetupDialog Class Reference	46
9.32	QEStripChart::PrivateData Class Reference	46
9.33	QEStripChartItem::PrivateData Class Reference	47
9.34	profilePlot Class Reference	47
9.35	PushButtonSpecifications Struct Reference	47

9.36	QBitStatus Class Reference	48
9.37	QCaAlarmInfo Class Reference	49
9.38	QCaConnectionInfo Class Reference	50
9.39	QCaDataPoint Struct Reference	50
9.40	QCaDataPointList Class Reference	51
9.41	QCaDateTime Class Reference	51
9.42	QCaEventFilter Class Reference	51
9.43	QCaEventItem Class Reference	51
9.44	QCaEventUpdate Class Reference	52
9.45	QCaInstalledFiltersListItem Class Reference	52
9.46	qcaobject::QCaObject Class Reference	53
9.47	qcastatemachine::QCaStateMachine Class Reference	54
9.48	QCaVariableNamePropertyManager Class Reference	55
9.49	QEAnalogIndicator Class Reference	55
9.50	QEAnalogProgressBar Class Reference	57
9.50.1	Member Function Documentation	60
9.50.1.1	dbValueChanged	60
9.50.1.2	requestEnabled	60
9.50.2	Property Documentation	60
9.50.2.1	addUnits	60
9.50.2.2	allowDrop	61
9.50.2.3	arrayAction	61
9.50.2.4	enabled	61
9.50.2.5	format	61
9.50.2.6	int	61
9.50.2.7	leadingZero	62
9.50.2.8	localEnumeration	62
9.50.2.9	notation	62
9.50.2.10	precision	62
9.50.2.11	trailingZeros	62
9.50.2.12	useDbPrecision	62
9.50.2.13	userLevelEnabled	62
9.50.2.14	userLevelEngineerStyle	62
9.50.2.15	userLevelScientistStyle	63

9.50.2.16	userLevelUserStyle	63
9.50.2.17	userLevelVisibility	63
9.50.2.18	variable	63
9.50.2.19	variableAsToolTip	63
9.50.2.20	variableSubstitutions	63
9.50.2.21	visible	64
9.51	QEBitStatus Class Reference	64
9.51.1	Member Function Documentation	66
9.51.1.1	dbValueChanged	66
9.51.1.2	requestEnabled	66
9.51.2	Property Documentation	66
9.51.2.1	allowDrop	66
9.51.2.2	enabled	66
9.51.2.3	int	66
9.51.2.4	userLevelEnabled	67
9.51.2.5	userLevelEngineerStyle	67
9.51.2.6	userLevelScientistStyle	67
9.51.2.7	userLevelUserStyle	67
9.51.2.8	userLevelVisibility	67
9.51.2.9	variable	68
9.51.2.10	variableAsToolTip	68
9.51.2.11	variableSubstitutions	68
9.51.2.12	visible	68
9.52	QEByteArray Class Reference	68
9.53	QEComboBox Class Reference	69
9.53.1	Member Function Documentation	71
9.53.1.1	dbValueChanged	71
9.53.1.2	requestEnabled	71
9.53.2	Member Data Documentation	71
9.53.2.1	writeOnChange	71
9.53.3	Property Documentation	72
9.53.3.1	allowDrop	72
9.53.3.2	enabled	72
9.53.3.3	int	72

9.53.3.4	subscribe	72
9.53.3.5	userLevelEnabled	72
9.53.3.6	userLevelEngineerStyle	72
9.53.3.7	userLevelScientistStyle	73
9.53.3.8	userLevelUserStyle	73
9.53.3.9	userLevelVisibility	73
9.53.3.10	variable	73
9.53.3.11	variableAsToolTip	73
9.53.3.12	variableSubstitutions	73
9.53.3.13	visible	74
9.54	QEConfiguredLayout Class Reference	74
9.55	QEConfiguredLayoutManager Class Reference	76
9.56	QEDragDrop Class Reference	76
9.57	QEFileBrowser Class Reference	78
9.58	QEFloating Class Reference	79
9.59	QEFloatingFormatting Class Reference	80
9.60	QEForm Class Reference	81
9.61	QEFrame Class Reference	82
9.61.1	Member Function Documentation	83
9.61.1.1	requestEnabled	83
9.61.2	Property Documentation	84
9.61.2.1	allowDrop	84
9.61.2.2	enabled	84
9.61.2.3	int	84
9.61.2.4	userLevelEnabled	84
9.61.2.5	userLevelEngineerStyle	84
9.61.2.6	userLevelScientistStyle	85
9.61.2.7	userLevelUserStyle	85
9.61.2.8	userLevelVisibility	85
9.61.2.9	variableAsToolTip	85
9.61.2.10	visible	85
9.62	QEGenericButton Class Reference	86
9.63	QEGroupBox Class Reference	88
9.63.1	Member Function Documentation	89

9.63.1.1	requestEnabled	89
9.63.2	Property Documentation	89
9.63.2.1	allowDrop	89
9.63.2.2	enabled	89
9.63.2.3	int	89
9.63.2.4	userLevelEnabled	90
9.63.2.5	userLevelEngineerStyle	90
9.63.2.6	userLevelScientistStyle	90
9.63.2.7	userLevelUserStyle	90
9.63.2.8	userLevelVisibility	90
9.63.2.9	variableAsToolTip	91
9.63.2.10	visible	91
9.64	QEImage Class Reference	91
9.64.1	Member Function Documentation	96
9.64.1.1	dbValueChanged	96
9.64.1.2	requestEnabled	96
9.64.2	Property Documentation	96
9.64.2.1	allowDrop	96
9.64.2.2	beamXVariable	96
9.64.2.3	beamYVariable	96
9.64.2.4	clippingHighVariable	97
9.64.2.5	clippingLowVariable	97
9.64.2.6	clippingOnOffVariable	97
9.64.2.7	enabled	97
9.64.2.8	heightVariable	97
9.64.2.9	imageVariable	97
9.64.2.10	int	97
9.64.2.11	regionOfInterestHVariable	97
9.64.2.12	regionOfInterestWVariable	98
9.64.2.13	regionOfInterestXVariable	98
9.64.2.14	regionOfInterestYVariable	98
9.64.2.15	targetTriggerVariable	98
9.64.2.16	targetXVariable	98
9.64.2.17	targetYVariable	98

9.64.2.18	userLevelEnabled	98
9.64.2.19	userLevelEngineerStyle	99
9.64.2.20	userLevelScientistStyle	99
9.64.2.21	userLevelUserStyle	99
9.64.2.22	userLevelVisibility	99
9.64.2.23	variableAsToolTip	99
9.64.2.24	variableSubstitutions	100
9.64.2.25	visible	100
9.64.2.26	widthVariable	100
9.65	QEInteger Class Reference	100
9.66	QEIntegerFormatting Class Reference	101
9.66.1	Detailed Description	101
9.66.2	Member Function Documentation	102
9.66.2.1	formatInteger	102
9.66.2.2	formatIntegerArray	102
9.66.2.3	formatValue	102
9.67	QELabel Class Reference	102
9.67.1	Detailed Description	106
9.67.2	Member Enumeration Documentation	106
9.67.2.1	updateOptions	106
9.67.3	Constructor & Destructor Documentation	106
9.67.3.1	QELabel	106
9.67.3.2	QELabel	106
9.67.4	Member Function Documentation	106
9.67.4.1	dbValueChanged	106
9.67.4.2	requestEnabled	107
9.67.5	Property Documentation	107
9.67.5.1	addUnits	107
9.67.5.2	allowDrop	107
9.67.5.3	arrayAction	107
9.67.5.4	enabled	107
9.67.5.5	format	108
9.67.5.6	int	108
9.67.5.7	leadingZero	108

9.67.5.8	localEnumeration	108
9.67.5.9	notation	108
9.67.5.10	pixmap0	108
9.67.5.11	pixmap1	108
9.67.5.12	pixmap2	109
9.67.5.13	pixmap3	109
9.67.5.14	pixmap4	109
9.67.5.15	pixmap5	109
9.67.5.16	pixmap6	109
9.67.5.17	pixmap7	109
9.67.5.18	precision	109
9.67.5.19	trailingZeros	109
9.67.5.20	updateOption	109
9.67.5.21	useDbPrecision	110
9.67.5.22	userLevelEnabled	110
9.67.5.23	userLevelEngineerStyle	110
9.67.5.24	userLevelScientistStyle	110
9.67.5.25	userLevelUserStyle	110
9.67.5.26	userLevelVisibility	111
9.67.5.27	variable	111
9.67.5.28	variableAsToolTip	111
9.67.5.29	variableSubstitutions	111
9.67.5.30	visible	111
9.68	QLineEdit Class Reference	111
9.68.1	Constructor & Destructor Documentation	114
9.68.1.1	QLineEdit	114
9.68.1.2	QLineEdit	114
9.68.2	Member Function Documentation	115
9.68.2.1	dbValueChanged	115
9.68.2.2	getConfirmWrite	115
9.68.2.3	getSubscribe	115
9.68.2.4	getWriteOnEnter	115
9.68.2.5	getWriteOnFinish	115
9.68.2.6	getWriteOnLoseFocus	115

9.68.2.7	requestEnabled	115
9.68.2.8	setConfirmWrite	115
9.68.2.9	setSubscribe	116
9.68.2.10	setWriteOnEnter	116
9.68.2.11	setWriteOnFinish	116
9.68.2.12	setWriteOnLoseFocus	116
9.68.3	Property Documentation	116
9.68.3.1	addUnits	116
9.68.3.2	allowDrop	116
9.68.3.3	arrayAction	116
9.68.3.4	confirmWrite	117
9.68.3.5	enabled	117
9.68.3.6	format	117
9.68.3.7	int	117
9.68.3.8	leadingZero	117
9.68.3.9	localEnumeration	117
9.68.3.10	notation	118
9.68.3.11	precision	118
9.68.3.12	subscribe	118
9.68.3.13	trailingZeros	118
9.68.3.14	useDbPrecision	118
9.68.3.15	userLevelEnabled	118
9.68.3.16	userLevelEngineerStyle	118
9.68.3.17	userLevelScientistStyle	119
9.68.3.18	userLevelUserStyle	119
9.68.3.19	userLevelVisibility	119
9.68.3.20	variable	119
9.68.3.21	variableAsToolTip	119
9.68.3.22	variableSubstitutions	119
9.68.3.23	visible	120
9.68.3.24	writeOnEnter	120
9.68.3.25	writeOnFinish	120
9.68.3.26	writeOnLoseFocus	120
9.69	QELineEditManager Class Reference	120

9.70 QELink Class Reference	121
9.71 QELog Class Reference	123
9.72 QELogin Class Reference	125
9.73 QEPeriodic Class Reference	126
9.73.1 Member Function Documentation	129
9.73.1.1 dbElementChanged	129
9.73.1.2 dbValueChanged	130
9.73.1.3 requestEnabled	130
9.73.2 Member Data Documentation	130
9.73.2.1 allowDrop	130
9.73.3 Property Documentation	130
9.73.3.1 enabled	130
9.73.3.2 int	130
9.73.3.3 readbackLabelVariable1	130
9.73.3.4 readbackLabelVariable2	131
9.73.3.5 subscribe	131
9.73.3.6 userLevelEnabled	131
9.73.3.7 userLevelEngineerStyle	131
9.73.3.8 userLevelScientistStyle	131
9.73.3.9 userLevelUserStyle	131
9.73.3.10 userLevelVisibility	132
9.73.3.11 variableAsToolTip	132
9.73.3.12 variableSubstitutions	132
9.73.3.13 visible	132
9.73.3.14 writeButtonVariable1	132
9.73.3.15 writeButtonVariable2	132
9.74 QEPeriodicComponentData Class Reference	133
9.75 QEPeriodicTaskMenu Class Reference	133
9.76 QEPeriodicTaskMenuFactory Class Reference	133
9.77 QEPicsPV Class Reference	134
9.78 QEPlot Class Reference	135
9.78.1 Member Function Documentation	138
9.78.1.1 dbValueChanged	138
9.78.1.2 dbValueChanged	138

9.78.1.3	requestEnabled	139
9.78.2	Member Data Documentation	139
9.78.2.1	allowDrop	139
9.78.3	Property Documentation	139
9.78.3.1	enabled	139
9.78.3.2	int	139
9.78.3.3	userLevelEnabled	139
9.78.3.4	userLevelEngineerStyle	139
9.78.3.5	userLevelScientistStyle	140
9.78.3.6	userLevelUserStyle	140
9.78.3.7	userLevelVisibility	140
9.78.3.8	variable1	140
9.78.3.9	variable2	140
9.78.3.10	variable3	141
9.78.3.11	variable4	141
9.78.3.12	variableAsToolTip	141
9.78.3.13	variableSubstitutions	141
9.78.3.14	visible	141
9.79	QEPushButton Class Reference	141
9.79.1	Member Function Documentation	145
9.79.1.1	dbValueChanged	145
9.79.1.2	requestEnabled	145
9.79.2	Property Documentation	145
9.79.2.1	allowDrop	145
9.79.2.2	altReadbackVariable	145
9.79.2.3	enabled	145
9.79.2.4	int	145
9.79.2.5	subscribe	146
9.79.2.6	userLevelEnabled	146
9.79.2.7	userLevelEngineerStyle	146
9.79.2.8	userLevelScientistStyle	146
9.79.2.9	userLevelUserStyle	146
9.79.2.10	userLevelVisibility	147
9.79.2.11	variable	147

9.79.2.12	variableAsToolTip	147
9.79.2.13	visible	147
9.80	QEPvProperties Class Reference	147
9.80.1	Member Function Documentation	149
9.80.1.1	requestEnabled	149
9.80.2	Property Documentation	149
9.80.2.1	allowDrop	149
9.80.2.2	enabled	150
9.80.2.3	int	150
9.80.2.4	userLevelEnabled	150
9.80.2.5	userLevelEngineerStyle	150
9.80.2.6	userLevelScientistStyle	150
9.80.2.7	userLevelUserStyle	151
9.80.2.8	userLevelVisibility	151
9.80.2.9	variable	151
9.80.2.10	variableAsToolTip	151
9.80.2.11	variableSubstitutions	151
9.80.2.12	visible	151
9.81	QEPvPropertiesManager Class Reference	152
9.82	QERadioButton Class Reference	152
9.82.1	Member Function Documentation	155
9.82.1.1	dbValueChanged	155
9.82.1.2	requestEnabled	156
9.82.2	Property Documentation	156
9.82.2.1	allowDrop	156
9.82.2.2	enabled	156
9.82.2.3	int	156
9.82.2.4	subscribe	156
9.82.2.5	userLevelEnabled	156
9.82.2.6	userLevelEngineerStyle	157
9.82.2.7	userLevelScientistStyle	157
9.82.2.8	userLevelUserStyle	157
9.82.2.9	userLevelVisibility	157
9.82.2.10	variable	157

9.82.2.11	variableAsToolTip	157
9.82.2.12	variableSubstitutions	158
9.82.2.13	visible	158
9.83	QERecipe Class Reference	158
9.84	QEScript Class Reference	160
9.85	QEShape Class Reference	162
9.85.1	Detailed Description	166
9.85.2	Member Enumeration Documentation	166
9.85.2.1	animationOptions	166
9.85.2.2	shapeOptions	166
9.85.3	Constructor & Destructor Documentation	167
9.85.3.1	QEShape	167
9.85.3.2	QEShape	167
9.85.4	Member Function Documentation	167
9.85.4.1	dbValueChanged1	167
9.85.4.2	dbValueChanged2	167
9.85.4.3	dbValueChanged3	167
9.85.4.4	dbValueChanged4	167
9.85.4.5	dbValueChanged5	167
9.85.4.6	dbValueChanged6	168
9.85.4.7	requestEnabled	168
9.85.5	Property Documentation	168
9.85.5.1	allowDrop	168
9.85.5.2	animation1	168
9.85.5.3	animation2	168
9.85.5.4	animation3	168
9.85.5.5	animation4	168
9.85.5.6	animation5	168
9.85.5.7	animation6	169
9.85.5.8	color1	169
9.85.5.9	color10	169
9.85.5.10	color2	169
9.85.5.11	color3	169
9.85.5.12	color4	169

9.85.5.13 color5	169
9.85.5.14 color6	169
9.85.5.15 color7	169
9.85.5.16 color8	170
9.85.5.17 color9	170
9.85.5.18 enabled	170
9.85.5.19 int	170
9.85.5.20 offset1	170
9.85.5.21 offset2	170
9.85.5.22 offset3	170
9.85.5.23 offset4	171
9.85.5.24 offset5	171
9.85.5.25 offset6	171
9.85.5.26 point1	171
9.85.5.27 point10	171
9.85.5.28 point2	171
9.85.5.29 point3	171
9.85.5.30 point4	171
9.85.5.31 point5	171
9.85.5.32 point6	172
9.85.5.33 point7	172
9.85.5.34 point8	172
9.85.5.35 point9	172
9.85.5.36 scale2	172
9.85.5.37 scale3	172
9.85.5.38 scale4	172
9.85.5.39 scale5	172
9.85.5.40 scale6	172
9.85.5.41 userLevelEnabled	173
9.85.5.42 userLevelEngineerStyle	173
9.85.5.43 userLevelScientistStyle	173
9.85.5.44 userLevelUserStyle	173
9.85.5.45 userLevelVisibility	173
9.85.5.46 variable1	174

9.85.5.47	variable2	174
9.85.5.48	variable3	174
9.85.5.49	variable4	174
9.85.5.50	variable5	174
9.85.5.51	variable6	174
9.85.5.52	variableAsToolTip	174
9.85.5.53	variableSubstitutions	175
9.85.5.54	visible	175
9.86	QESlider Class Reference	175
9.86.1	Member Function Documentation	177
9.86.1.1	dbValueChanged	177
9.86.1.2	requestEnabled	177
9.86.2	Member Data Documentation	177
9.86.2.1	writeOnChange	177
9.86.3	Property Documentation	177
9.86.3.1	allowDrop	177
9.86.3.2	enabled	178
9.86.3.3	int	178
9.86.3.4	subscribe	178
9.86.3.5	userLevelEnabled	178
9.86.3.6	userLevelEngineerStyle	178
9.86.3.7	userLevelScientistStyle	178
9.86.3.8	userLevelUserStyle	179
9.86.3.9	userLevelVisibility	179
9.86.3.10	variable	179
9.86.3.11	variableAsToolTip	179
9.86.3.12	variableSubstitutions	179
9.86.3.13	visible	179
9.87	QESpinBox Class Reference	180
9.87.1	Member Function Documentation	182
9.87.1.1	dbValueChanged	182
9.87.1.2	requestEnabled	182
9.87.2	Property Documentation	182
9.87.2.1	allowDrop	182

9.87.2.2	enabled	182
9.87.2.3	int	183
9.87.2.4	subscribe	183
9.87.2.5	userLevelEnabled	183
9.87.2.6	userLevelEngineerStyle	183
9.87.2.7	userLevelScientistStyle	183
9.87.2.8	userLevelUserStyle	183
9.87.2.9	userLevelVisibility	184
9.87.2.10	variable	184
9.87.2.11	variableAsToolTip	184
9.87.2.12	variableSubstitutions	184
9.87.2.13	visible	184
9.88	QString Class Reference	185
9.89	QStringFormatting Class Reference	185
9.90	QStringFormattingMethods Class Reference	186
9.91	QStripChart Class Reference	187
9.92	QStripChartItem Class Reference	189
9.93	QStripChartItemDialog Class Reference	190
9.94	QStripChartTimeDialog Class Reference	190
9.95	QSubstitutedLabel Class Reference	190
9.95.1	Member Data Documentation	191
9.95.1.1	labelText	191
9.95.2	Property Documentation	191
9.95.2.1	textSubstitutions	191
9.96	QEToolTip Class Reference	191
9.97	QEWidget Class Reference	192
9.98	QEWidgets Class Reference	194
9.99	qcastatemachine::ReadQCaStateMachine Class Reference	194
9.100	RecordSpec Class Reference	195
9.101	RecordSpecList Class Reference	195
9.102	selectMenu Class Reference	196
9.103	standardProperties Class Reference	196
9.104	StateMachineTemplate Class Reference	198
9.105	qcastatemachine::SubscriptionQCaStateMachine Class Reference	198

9.106trace Class Reference	199
9.107TrackRange Class Reference	199
9.108userInfoStruct Class Reference	200
9.109QEPeriodic::userInfoStructArray Struct Reference	200
9.110userLevelSignal Class Reference	200
9.111userLevelSlot Class Reference	201
9.112UserMessage Class Reference	201
9.113UserMessageSignal Class Reference	203
9.114UserMessageSlot Class Reference	203
9.115VideoWidget Class Reference	204
9.116WidgetRef Class Reference	205
9.117qcastatemachine::WriteQCaStateMachine Class Reference	205
9.118zoomMenu Class Reference	206

Chapter 1

QE framework - EPICS aware Qt Widgets and data access classes

- QE is a layered software framework for accessing EPICS data using Channel Access on a range of platforms.
- The QE framework provides object oriented C++ access to control systems using EPICS (Experimental Physics and Industrial Control System). It is based on Qt, a widely used cross-platform application development framework.
- GUI or console based applications can be written that use QE at several levels. QE includes Qt plugin libraries, EPICS aware widgets, data formatting classes, and classes for accessing raw EPICS data in a Qt friendly way.
- QE also includes an application - QEgui - for displaying forms produced by the Qt development tool 'Designer'. Using this application a complete EPICS GUI system can be generated without writing any code. A GUI system produced in this way can interact with existing EPICS display tools such as EDM.
- QE handles much of the complexities of Channel Access including initiating and managing a channel. Applications using QE can interact with Channel Access using Qt based classes and data types. Channel Access updates are delivered using Qt's signals and slots mechanism.

1.1 Documentation

Support documents can be found in the [documentation](#) section of the epicsqt sourceforge project. The framework download (available on the epicsqt sourceforge [homepage](#)) also includes this documentation as well as full Doxygen generated documentation of all the epicsqt classes and widgets.

1.2 License

epicsqt is distributed under the terms of the [GNU General Public License](#).

1.3 Platforms

epicsqt might be usable in all environments where you find [Qt](#). It is compatible with Qt ≥ 4.4 .

1.4 Screenshots

- [ASgui screen shots](#)
- [other applications using epicsqt widgets](#)
- [Qt Designer](#)
- [Qt Creator](#)

Screenshots are only available in the HTML docs.

1.5 Downloads

Stable releases and development snapshots are available at the [epicsqt project page](#).

For getting a development snapshot from the SVN repository:

```
svn svn co https://epicsqt.svn.sourceforge.net/svnroot/epicsqt epicsqt
```

1.6 Installation

Read [QE_GettingStarted.pdf](#) in the documentation for setting up an environment for building or using the epicsqt framework.

To build the framework, open epicsqt.pro in QtCreator, ensure shadow build is turned off, and hit build.

The resultant library libQEPlugin.so will need to be installed or referenced up according to how it is to be used - see QE_GettingStarted.pdf for details.

Any Qt specific queries? start at [the Qt Project](#)

1.7 Support

Visit the sourceforge epicsqt [support page](#) for assistance.

1.8 Related Projects

[Qwt](#), The core of a Channel Access aware plotting widget.

1.9 Credits:

Authors:

Andrew Rhyder, Anthony Owen, Glenn Jackson

Project admin:

Andrew Rhyder <andrew.rhyder@synchrotron.org.au>

Chapter 2

GNU General Public License

The EPICS QT Framework is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

The EPICS QT Framework is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with the EPICS QT Framework.

If not, see "<http://www.gnu.org/licenses/>

Chapter 3

ASgui screen shots




Figure 3.1: Australian Synchrotron mock up




Figure 3.2: Monochromator referencing




Figure 3.3: Beam position monitor




Figure 3.4: Insertion device



Figure 3.5: Injection efficiency monitor

Chapter 4

other applications using epicsqt widgets




Figure 4.1: Medical Imaging beamline

2B SampleTable Z <@SR08ID01OPI01>

PV name: SR08ID01:MTR32B View mode: Macro

Description: 2B SampleTable Z

Precision: 5 Units: mm

Message: Connection established. clean

User: 6mm Move absolutely Raw: -80932

JOG< UNDO >JOG

LIMIT< Move relatively >LIMIT

< 1mm >

step/10 step/2 step*2 step*10

User: 6mm = Hi limit

Resolution: 0.0001mm/step * 42271.2068mm

Raw: -80932 + Lo limit

Offset: -2.0932mm -42275.3932mm

Speed Acceleration

Maximum: 1.2mm/s

Normal: 0.8mm/s 1s

Backlash: 0mm/s 1s

log: 1mm/s 10s

Backlash: 0mm

Figure 4.2: Motor controller

MotorMx <@SR08ID01OPI01>

- ▲ ▼	DEI Theta Mono	109.5mm	<	0.1	>	UNDO
- ▲ ▼	DEI Mono Z	-0.3mm	<	0.1	>	UNDO
- ▲ ▼	2B Sample Table Y	0mm	<	1	>	UNDO
- ▲ ▼	2B SampleTable Z	6mm	<	1	>	UNDO
- ▲ ▼	2B Detector Table Z	42mm	<	5	>	UNDO
- ▲ ▼	2B Sample Rotate	-1deg	<	1	>	UNDO
- ▲ ▼	2B Detector Table Y	13.9025mm	<	1	>	UNDO
- ▲ ▼	SETUP	0	<	relative	>	STOP
- ▲ ▼	SLW01:LEFT	9.99975mm	<	3456	>	UNDO

Add motor

Figure 4.3: Motor controller

Qt Designer




Figure 5.1: Editing multiple GUIs




Figure 5.2: Editing a GUI

Chapter 6

Qt Creator




Figure 6.1: Application using epicsqt data source classes

Chapter 7

Class Index

7.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

_Field	27
_Item	28
_QDialogItem	28
_QDialogLogin	28
_QPushButtonGroup	29
_QTableWidgetFileBrowser	29
_QTableWidgetLog	30
_QTableWidgetScript	30
QEEAnalogIndicator::Band	30
QEEAnalogIndicator::BandList	31
ContainerProfile	31
QEWidget	192
QEEAnalogProgressBar	57
QEBitStatus	64
QEComboBox	69
QEConfiguredLayout	74
QEFileBrowser	78
QEForm	81
QEFrame	82
QEGenericButton	86
QEPushButton	141
QERadioButton	152
QEGroupBox	88
QEImage	91
QELabel	102
QELineEdit	111
QELink	121
QELog	123
QELogin	125

QEPeriodic	126
QEPlot	135
QEPvProperties	147
QERecipe	158
QEScript	160
QEShape	162
QESlider	175
QESpinBox	180
QEStripChart	187
QESubstitutedLabel	190
contextMenu	33
QEWidget	192
contextMenuObject	35
QEPeriodic::elementInfoStruct	35
flipRotateMenu	36
imageContextMenu	36
imageMarkup	37
VideoWidget	204
localEnumerationItem	38
managePixmaps	39
QEGenericButton	86
QELabel	102
markupItem	41
markupBeam	39
markupHLine	40
markupLine	42
markupRegion	43
markupTarget	43
markupText	44
markupVLine	45
PeriodicDialog	45
PeriodicElementSetupForm	46
PeriodicSetupDialog	46
QEStripChart::PrivateData	46
QEStripChartItem::PrivateData	47
profilePlot	47
PushButtonSpecifications	47
QBitStatus	48
QEBitStatus	64
QCaAlarmInfo	49
QCaConnectionInfo	50
QCaDataPoint	50
QCaDataPointList	51
QCaDateTime	51
QCaEventFilter	51
QCaEventItem	51
QCaEventUpdate	52
QCaInstalledFiltersListItem	52

qcaobject::QCaObject	53
QEByteArray	68
QEFloating	79
QEInteger	100
QEString	185
QCaVariableNamePropertyManager	55
QEAnalogIndicator	55
QEAnalogProgressBar	57
QEConfiguredLayoutManager	76
QEDragDrop	76
QEWidget	192
QEFloatingFormatting	80
QEIntegerFormatting	101
QELineEditManager	120
QEPeriodicComponentData	133
QEPeriodicTaskMenu	133
QEPeriodicTaskMenuFactory	133
QEpicsPV	134
QEPvPropertiesManager	152
QEStringFormatting	185
QEStringFormattingMethods	186
QEAnalogProgressBar	57
QEGenericButton	86
QELabel	102
QELineEdit	111
QEStripChartItem	189
QEStripChartItemDialog	190
QEStripChartTimeDialog	190
QEToolTip	191
QEWidget	192
QEWidgets	194
RecordSpec	195
RecordSpecList	195
selectMenu	196
standardProperties	196
QEWidget	192
StateMachineTemplate	198
qcastatemachine::QCaStateMachine	54
qcastatemachine::ConnectionQCaStateMachine	31
qcastatemachine::ReadQCaStateMachine	194
qcastatemachine::SubscriptionQCaStateMachine	198
qcastatemachine::WriteQCaStateMachine	205
trace	199
TrackRange	199
userInfoStruct	200
QEPeriodic::userInfoStructArray	200
userLevelSignal	200

userLevelSlot	201
UserMessage	201
QEWidget	192
UserMessageSignal	203
UserMessageSlot	203
WidgetRef	205
zoomMenu	206

Chapter 8

Class Index

8.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

_Field	27
_Item	28
_QDialogItem	28
_QDialogLogin	28
_QPushButtonGroup	29
_QTableWidgetFileBrowser	29
_QTableWidgetLog	30
_QTableWidgetScript	30
QEAnalogIndicator::Band	30
QEAnalogIndicator::BandList	31
qcastatemachine::ConnectionQCaStateMachine	31
ContainerProfile	31
contextMenu	33
contextMenuObject	35
QEPeriodic::elementInfoStruct	35
flipRotateMenu	36
imageContextMenu	36
imageMarkup	37
localEnumerationItem	38
managePixmaps	39
markupBeam	39
markupHLine	40
markupItem	41
markupLine	42
markupRegion	43
markupTarget	43
markupText	44
markupVLine	45
PeriodicDialog	45

PeriodicElementSetupForm	46
PeriodicSetupDialog	46
QEStripChart::PrivateData	46
QEStripChartItem::PrivateData	47
profilePlot	47
PushButtonSpecifications	47
QBitStatus	48
QCaAlarmInfo	49
QCaConnectionInfo	50
QCaDataPoint	50
QCaDataPointList	51
QCaDateTime	51
QCaEventFilter	51
QCaEventItem	51
QCaEventUpdate	52
QCaInstalledFiltersListItem	52
qcaobject::QCaObject	53
qcastatemachine::QCaStateMachine	54
QCaVariableNamePropertyManager	55
QESetupForm	55
QESetupForm	57
QESetupForm	64
QESetupForm	68
QESetupForm	69
QESetupForm	74
QESetupForm	76
QESetupForm	76
QESetupForm	78
QESetupForm	79
QESetupForm	80
QESetupForm	81
QESetupForm	82
QESetupForm	86
QESetupForm	88
QESetupForm	91
QESetupForm	100
QESetupForm	101
QESetupForm	102
QESetupForm	111
QESetupForm	120
QESetupForm	121
QESetupForm	123
QESetupForm	125
QESetupForm	126
QESetupForm	133
QESetupForm	133
QESetupForm	133
QESetupForm	134
QESetupForm	135
QESetupForm	141

QEPvProperties	147
QEPvPropertiesManager	152
QERadioButton	152
QERecipe	158
QEScript	160
QEShape	162
QESlider	175
QESpinBox	180
QEStrng	185
QEStrngFormatting	185
QEStrngFormattingMethods	186
QEStrngChart	187
QEStrngChartItem	189
QEStrngChartItemDialog	190
QEStrngChartTimeDialog	190
QESubstitutedLabel	190
QEToolTip	191
QEWidget	192
QEWidgets	194
qcastatemachine::ReadQCaStateMachine	194
RecordSpec	195
RecordSpecList	195
selectMenu	196
standardProperties	196
StateMachineTemplate	198
qcastatemachine::SubscriptionQCaStateMachine	198
trace	199
TrackRange	199
userInfoStruct	200
QEPeriodic::userInfoStructArray	200
userLevelSignal	200
userLevelSlot	201
UserMessage	201
UserMessageSignal	203
UserMessageSlot	203
VideoWidget	204
WidgetRef	205
qcastatemachine::WriteQCaStateMachine	205
zoomMenu	206

Chapter 9

Class Documentation

9.1 _Field Class Reference

Public Member Functions

- [QEObject](#) * **getObject** ()
- void **setObject** (QString *pValue)
- QString **getName** ()
- void **setName** (QString pValue)
- QString **getProcessVariable** ()
- void **setProcessVariable** (QString pValue)
- void **setJoin** (bool pValue)
- bool **getJoin** ()
- int **getType** ()
- void **setType** (int pValue)
- QString **getGroup** ()
- void **setGroup** (QString pValue)
- QString **getVisible** ()
- void **setVisible** (QString pValue)
- QString **getEditable** ()
- void **setEditable** (QString pValue)
- bool **getVisibility** ()
- void **setVisibility** (bool pValue)

Public Attributes

- [QEObject](#) * **qCaWidget**

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEObjectifiedLayout/QEObjectifiedLayout.h
- /home/rhydera/epicsqt/framework/widgets/QEObjectifiedLayout/QEObjectifiedLayout.cpp

9.2 _Item Class Reference

Public Member Functions

- void **setName** (QString pValue)
- QString **getName** ()
- void **setSubstitution** (QString pValue)
- QString **getSubstitution** ()
- void **setVisible** (QString pValue)
- QString **getVisible** ()

Public Attributes

- QList< [_Field](#) * > **fieldList**

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEConfiguredLayout/QEConfiguredLayout.h
- /home/rhydera/epicsqt/framework/widgets/QEConfiguredLayout/QEConfiguredLayout.cpp

9.3 _QDialogItem Class Reference

Public Member Functions

- **_QDialogItem** (QWidget *pParent=0, QString pItemName="", QString pGroupName="", QList< [_Field](#) * > *pCurrentFieldList=0, Qt::WindowFlags pF=0)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEConfiguredLayout/QEConfiguredLayout.h
- /home/rhydera/epicsqt/framework/widgets/QEConfiguredLayout/QEConfiguredLayout.cpp

9.4 _QDialogLogin Class Reference

Public Member Functions

- **_QDialogLogin** (QWidget *pParent=0, int pUserType=-1, Qt::WindowFlags pF=0)
- void **setCurrentUserType** (int pValue)
- void **setPassword** (QString pValue)

Protected Attributes

- `QGridLayout` * **qGridLayout**
- `QVBoxLayout` * **qVBoxLayout**
- `QGroupBox` * **qGroupBox**
- `QRadioButton` * **qRadioButtonUser**
- `QRadioButton` * **qRadioButtonScientist**
- `QRadioButton` * **qRadioButtonEngineer**
- `QLabel` * **qLabelType**
- `QLineEdit` * **qLineEditPassword**
- `QPushButton` * **qPushButtonOk**
- `QPushButton` * **qPushButtonCancel**
- `int` **userType**

The documentation for this class was generated from the following files:

- `/home/rhydera/epicsqt/framework/widgets/QELogin/QELogin.h`
- `/home/rhydera/epicsqt/framework/widgets/QELogin/QELogin.cpp`

9.5 `_QPushButtonGroup` Class Reference

Public Slots

- `void` **buttonGroupClicked** ()

Public Member Functions

- **`_QPushButtonGroup`** (`QWidget` *pParent=0, `QString` pItemName="", `QString` pGroupName="", `QList`< `_Field` * > *pCurrentFieldList=0)
- `void` **mouseReleaseEvent** (`QMouseEvent` *qMouseEvent)
- `void` **keyPressEvent** (`QKeyEvent` *pKeyEvent)
- `void` **showDialogGroup** ()

The documentation for this class was generated from the following files:

- `/home/rhydera/epicsqt/framework/widgets/QEConfiguredLayout/QEConfiguredLayout.h`
- `/home/rhydera/epicsqt/framework/widgets/QEConfiguredLayout/QEConfiguredLayout.cpp`

9.6 `_QTableWidgetFileBrowser` Class Reference

Public Member Functions

- **`_QTableWidgetFileBrowser`** (`QWidget` *pParent=0)

- void **refreshSize** ()
- void **resizeEvent** (QResizeEvent *)
- void **resize** (int w, int h)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QFileBrowser/QFileBrowser.h
- /home/rhydera/epicsqt/framework/widgets/QFileBrowser/QFileBrowser.cpp

9.7 _QTableWidgetLog Class Reference

Public Member Functions

- **_QTableWidgetLog** (QWidget *pParent=0)
- void **refreshSize** ()
- void **resizeEvent** (QResizeEvent *)
- void **resize** (int w, int h)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QELog/QELog.h
- /home/rhydera/epicsqt/framework/widgets/QELog/QELog.cpp

9.8 _QTableWidgetScript Class Reference

Public Member Functions

- **_QTableWidgetScript** (QWidget *pParent=0)
- void **refreshSize** ()
- void **resizeEvent** (QResizeEvent *)
- void **resize** (int w, int h)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEScript/QEScript.h
- /home/rhydera/epicsqt/framework/widgets/QEScript/QEScript.cpp

9.9 QEAnalogIndicator::Band Struct Reference

Public Attributes

- double **lower**

- double **upper**
- QColor **colour**

The documentation for this struct was generated from the following file:

- /home/rhydera/epicsqt/framework/widgets/QEAnalogIndicator/QEAnalogIndicator.h


9.10 QEAnalogIndicator::BandList Class Reference

The documentation for this class was generated from the following file:

- /home/rhydera/epicsqt/framework/widgets/QEAnalogIndicator/QEAnalogIndicator.h

9.11 qcastatemachine::ConnectionQCaStateMachine Class Reference

Inheritance diagram for qcastatemachine::ConnectionQCaStateMachine:



Public Member Functions


- **ConnectionQCaStateMachine** (void *parent)
- bool **process** (int requestedState)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/data/include/QCaStateMachine.h
- /home/rhydera/epicsqt/framework/data/src/QCaStateMachine.cpp

9.12 ContainerProfile Class Reference

Inheritance diagram for ContainerProfile:



Public Member Functions

- void **takeLocalCopy** ()
- void **setupProfile** (QObject *guiLaunchConsumerIn, QStringList pathListIn, QString parentPathIn, QString macroSubstitutionsIn)
- void **setupLocalProfile** (QObject *guiLaunchConsumerIn, QStringList pathListIn, QString parentPathIn, QString macroSubstitutionsIn)
- void **updateConsumers** (QObject *guiLaunchConsumerIn)
- QObject * **replaceGuiLaunchConsumer** (QObject *newGuiLaunchConsumerIn)

- void **addMacroSubstitutions** (QString macroSubstitutionsIn)
- void **removeMacroSubstitutions** ()
- QObject * **getGuiLaunchConsumer** ()
- QString **getPath** ()
- QStringList **getPathList** ()
- QString **getParentPath** ()
- void **setPublishedParentPath** (QString publishedParentPathIn)
- QString **getMacroSubstitutions** ()


- bool **isProfileDefined** ()
- void **addContainedWidget** (QWidget *containedWidget)
- QWidget * **getNextContainedWidget** ()
- void **removeContainedWidget** (QWidget *containedWidget)
- unsigned int **getMessageFormId** ()
- unsigned int **getPublishedMessageFormId** ()
- void **setPublishedMessageFormId** (unsigned int publishedMessageFormIdIn)
- void **releaseProfile** ()
- void **publishOwnProfile** ()
- void **setUserLevel** (userLevels level)
- userLevels **getUserLevel** ()
- virtual void **userLevelChanged** (userLevels)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/include/ContainerProfile.h
- /home/rhydera/epicsqt/framework/widgets/src/ContainerProfile.cpp

9.13 contextMenu Class Reference

Inheritance diagram for contextMenu:



Public Types

- enum **contextMenuOptions** {
CM_NONE, **CM_COPY_VARIABLE**, **CM_COPY_DATA**, **CM_PASTE**,
CM_DRAG_VARIABLE, **CM_DRAG_DATA**, **CM_SPECIFIC_WIDGETS_START_ - HERE** }

Public Member Functions

- void **addContextMenuToWidget** (QWidget *w)
- bool **isDraggingVariable** ()
- QMenu * **getContextMenu** ()
- virtual QString **copyVariable** ()
- virtual QVariant **copyData** ()
- virtual void **paste** (QVariant)

Friends

- class [contextMenuObject](#)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/include/contextMenu.h
- /home/rhydera/epicsqt/framework/widgets/src/contextMenu.cpp

9.14 contextMenuObject Class Reference

Public Slots

- void **contextMenuTriggered** (QAction *selectedItem)
- void **showContextMenu** (const QPoint &pos)
- void **setChecked** ()

Public Member Functions

- void **addContextMenuToWidget** (QWidget *w)
- void **manageChecked** (bool draggingVariable)
- void **setMenu** ([contextMenu](#) *menuIn)
- bool **isDraggingVariable** ()

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/include/contextMenu.h
- /home/rhydera/epicsqt/framework/widgets/src/contextMenu.cpp

9.15 QEP periodic::elementInfoStruct Struct Reference

Public Attributes

- unsigned int **number**
- double **atomicWeight**
- QString **name**
- QString **symbol**
- double **meltingPoint**
- double **boilingPoint**
- double **density**
- unsigned int **group**
- double **ionizationEnergy**
- unsigned int **tableRow**

- unsigned int **tableCol**

The documentation for this struct was generated from the following file:

- /home/rhydera/epicsqt/framework/widgets/QEPeriodic/QEPeriodic.h

9.16 flipRotateMenu Class Reference

Public Member Functions

- **flipRotateMenu** (QWidget *parent=0)
- imageContextMenu::imageContextMenuOptions **getFlipRotate** (const QPoint &pos)
- void **setChecked** (const int rotation, const bool flipH, const bool flipV)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEImage/flipRotateMenu.h
- /home/rhydera/epicsqt/framework/widgets/QEImage/flipRotateMenu.cpp

9.17 imageContextMenu Class Reference

Public Types

- enum **imageContextMenuOptions** {
ICM_NONE = contextMenu::CM_SPECIFIC_WIDGETS_START_HERE, **ICM_SAVE**,
ICM_PAUSE, **ICM_ENABLE_TIME**,
ICM_ENABLE_CURSOR_PIXEL, **ICM_ENABLE_CONTRAST_REVERSAL**, **ICM_-**
ENABLE_PAN, **ICM_ENABLE_VERT**,
ICM_ENABLE_HOZ, **ICM_ENABLE_AREA**, **ICM_ENABLE_LINE**, **ICM_ENABLE_-**
TARGET,
ICM_DISPLAY_BUTTON_BAR, **ICM_ZOOM_SELECTED**, **ICM_ZOOM_FIT**, **ICM_-**
ZOOM_10,
ICM_ZOOM_25, **ICM_ZOOM_50**, **ICM_ZOOM_75**, **ICM_ZOOM_100**,
ICM_ZOOM_150, **ICM_ZOOM_200**, **ICM_ZOOM_300**, **ICM_ZOOM_400**,
ICM_ROTATE_NONE, **ICM_ROTATE_RIGHT**, **ICM_ROTATE_LEFT**, **ICM_ROTATE_-**
180,
ICM_FLIP_HORIZONTAL, **ICM_FLIP_VERTICAL**, **ICM_SELECT_PAN**, **ICM_-**
SELECT_HSLICE,
ICM_SELECT_VSLICE, **ICM_SELECT_AREA**, **ICM_SELECT_PROFILE**, **ICM_-**
SELECT_TARGET,
ICM_SELECT_BEAM }

Public Member Functions


- **imageContextMenu** (QWidget *parent=0)
- void **getContextMenuOption** (const QPoint &, imageContextMenuOptions *option, bool *checked)
- void **addMenuItem** (const QString &title, const bool checkable, const bool checked, const imageContextMenuOptions option)
- void **addOptionMenuItem** (const QString &title, const bool checkable, const bool checked, const imageContextMenuOptions option)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEImage/imageContextMenu.h
- /home/rhydera/epicsqt/framework/widgets/QEImage/imageContextMenu.cpp

9.18 imageMarkup Class Reference

Inheritance diagram for imageMarkup:



Public Types

- enum **markupIds** {
MARKUP_ID_REGION, **MARKUP_ID_H_SLICE**, **MARKUP_ID_V_SLICE**, **MARKUP_ID_LINE**,
MARKUP_ID_TARGET, **MARKUP_ID_BEAM**, **MARKUP_ID_TIMESTAMP**, **MARKUP_ID_COUNT**,
MARKUP_ID_NONE }

Public Member Functions

- void **markupMousePressEvent** (QMouseEvent *event)
- void **markupMouseReleaseEvent** (QMouseEvent *event)
- void **markupMouseMoveEvent** (QMouseEvent *event)
- void **setShowTime** (bool visibleIn)
- bool **getShowTime** ()
- markupIds **getMode** ()
- void **setMode** (markupIds modeIn)

- `QVector< QRect > &getMarkupAreas ()`
- `bool anyVisibleMarkups ()`
- `QCursor getDefaultMarkupCursor ()`
- `void setMarkupTime (QCaDateTime &time)`
- `void setMarkupColor (markupIds mode, QColor markupColorIn)`
- `QColor getMarkupColor (markupIds mode)`
- `QCursor getCircleCursor ()`
- `QCursor getTargetCursor ()`
- `virtual void markupSetCursor (QCursor cursor)=0`

Public Attributes

- `QImage * markupImage`
- `QVector< markupItem * > items`
- `QPoint grabOffset`
- `bool markupAreasStale`

Protected Member Functions

- `void markupResize (QSize newSize)`
- `virtual void markupChange (QImage &markups, QVector< QRect > &changedAreas)=0`
- `virtual void markupAction (markupIds mode, QPoint point1, QPoint point2)=0`

The documentation for this class was generated from the following files:

- `/home/rhydera/epicsqt/framework/widgets/QEImage/imageMarkup.h`
- `/home/rhydera/epicsqt/framework/widgets/QEImage/imageMarkup.cpp`

9.19 localEnumerationItem Class Reference

Public Types

- `enum operations {`
`LESS, LESS_EQUAL, EQUAL, NOT_EQUAL,`
`GREATER_EQUAL, GREATER, ALWAYS, UNKNOWN }`

Public Attributes


- `double dValue`
- `QString sValue`
- `operations op`
- `QString text`

The documentation for this class was generated from the following file:

- /home/rhydera/epicsqt/framework/data/include/QEStringFormatting.h

9.20 managePixmaps Class Reference

Inheritance diagram for managePixmaps:



Public Member Functions


- void **setDataPixmap** (const QPixmap &Pixmap, const unsigned int index)
- QPixmap **getDataPixmap** (const unsigned int index)
- QPixmap **getDataPixmap** (const QString value)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/include/managePixmaps.h
- /home/rhydera/epicsqt/framework/widgets/src/managePixmaps.cpp

9.21 markupBeam Class Reference

Inheritance diagram for markupBeam:



Public Member Functions

- **markupBeam** (imageMarkup *ownerIn, bool interactiveIn, bool reportOnMoveIn)
- void **startDrawing** (QPoint pos)


- void **setArea** ()
- void **drawMarkup** (QPainter &p)
- void **moveTo** (QPoint pos)
- bool **isOver** (QPoint point, QCursor *cursor)
- QPoint **origin** ()
- QPoint **getPoint1** ()
- QPoint **getPoint2** ()
- QCursor **defaultCursor** ()

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEImage/imageMarkup.h
- /home/rhydera/epicsqt/framework/widgets/QEImage/imageMarkup.cpp

9.22 markupHLine Class Reference

Inheritance diagram for markupHLine:



Public Member Functions


- **markupHLine** ([imageMarkup](#) *ownerIn, bool interactiveIn, bool reportOnMoveIn)
- void **startDrawing** (QPoint pos)
- void **setArea** ()
- void **drawMarkup** (QPainter &p)
- void **moveTo** (QPoint pos)
- bool **isOver** (QPoint point, QCursor *cursor)
- QPoint **origin** ()
- QPoint **getPoint1** ()
- QPoint **getPoint2** ()
- QCursor **defaultCursor** ()

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEImage/imageMarkup.h
- /home/rhydera/epicsqt/framework/widgets/QEImage/imageMarkup.cpp

9.23 markupItem Class Reference

Inheritance diagram for markupItem:



Public Types

- enum **isOverOptions** { OVER_LINE, OVER_BORDER, OVER_AREA }
- enum **markupHandles** {
 MARKUP_HANDLE_NONE, MARKUP_HANDLE_START, MARKUP_HANDLE_END, MARKUP_HANDLE_TL,
 MARKUP_HANDLE_TR, MARKUP_HANDLE_BL, MARKUP_HANDLE_BR, MARKUP_HANDLE_T,
 MARKUP_HANDLE_B, MARKUP_HANDLE_L, MARKUP_HANDLE_R }

Public Member Functions

- **markupItem** ([imageMarkup](#) *ownerIn, isOverOptions over, bool interactiveIn, bool reportOnMoveIn)
- virtual void **setArea** ()=0
- virtual QPoint **origin** ()=0
- virtual void **moveTo** (QPoint pos)=0
- void **erase** ()
- virtual void **drawMarkup** (QPainter &p)=0
- virtual void **startDrawing** (QPoint pos)=0
- virtual bool **isOver** (QPoint point, QCursor *cursor)=0
- virtual QPoint **getPoint1** ()=0
- virtual QPoint **getPoint2** ()=0
- virtual QCursor **defaultCursor** ()=0
- bool **pointsNear** (QPoint p1, QPoint p)
- void **drawMarkupIn** ()
- void **drawMarkupOut** ()
- void **setColor** (QColor colorIn)
- QColor **getColor** ()

Public Attributes

- markupHandles **activeHandle**
- isOverOptions **isOverType**
- QRect **area**


- bool **visible**
- bool **interactive**
- bool **reportOnMove**
- bool **highlighted**
- int **highlightMargin**
- QColor **color**
- [imageMarkup](#) * **owner**

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEImage/imageMarkup.h
- /home/rhydera/epicsqt/framework/widgets/QEImage/imageMarkup.cpp

9.24 markupLine Class Reference

Inheritance diagram for markupLine:



Public Member Functions


- **markupLine** ([imageMarkup](#) *ownerIn, bool interactiveIn, bool reportOnMoveIn)
- void **startDrawing** (QPoint pos)
- void **setArea** ()
- void **drawMarkup** (QPainter &p)
- void **moveTo** (QPoint pos)
- bool **isOver** (QPoint point, QCursor *cursor)
- QPoint **origin** ()
- QPoint **getPoint1** ()
- QPoint **getPoint2** ()
- QCursor **defaultCursor** ()

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEImage/imageMarkup.h
- /home/rhydera/epicsqt/framework/widgets/QEImage/imageMarkup.cpp

9.25 markupRegion Class Reference

Inheritance diagram for markupRegion:



Public Member Functions


- **markupRegion** ([imageMarkup](#) *ownerIn, bool interactiveIn, bool reportOnMoveIn)
- void **startDrawing** (QPoint pos)
- void **setArea** ()
- void **drawMarkup** (QPainter &p)
- void **moveTo** (QPoint pos)
- bool **isOver** (QPoint point, QCursor *cursor)
- QPoint **origin** ()
- QPoint **getPoint1** ()
- QPoint **getPoint2** ()
- QCursor **defaultCursor** ()

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEImage/imageMarkup.h
- /home/rhydera/epicsqt/framework/widgets/QEImage/imageMarkup.cpp

9.26 markupTarget Class Reference

Inheritance diagram for markupTarget:



Public Member Functions

- **markupTarget** ([imageMarkup](#) *ownerIn, bool interactiveIn, bool reportOnMoveIn)


- void **startDrawing** (QPoint pos)
- void **setArea** ()
- void **drawMarkup** (QPainter &p)
- void **moveTo** (QPoint pos)
- bool **isOver** (QPoint point, QCursor *cursor)
- QPoint **origin** ()
- QPoint **getPoint1** ()
- QPoint **getPoint2** ()
- QCursor **defaultCursor** ()

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEImage/imageMarkup.h
- /home/rhydera/epicsqt/framework/widgets/QEImage/imageMarkup.cpp

9.27 markupText Class Reference

Inheritance diagram for markupText:



Public Member Functions


- **markupText** ([imageMarkup](#) *ownerIn, bool interactiveIn, bool reportOnMoveIn)
- void **setText** (QString textIn, bool draw)
- void **startDrawing** (QPoint pos)
- void **setArea** ()
- void **drawMarkup** (QPainter &p)
- void **moveTo** (QPoint pos)
- bool **isOver** (QPoint point, QCursor *cursor)
- QPoint **origin** ()
- QPoint **getPoint1** ()
- QPoint **getPoint2** ()
- QCursor **defaultCursor** ()

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEImage/imageMarkup.h
- /home/rhydera/epicsqt/framework/widgets/QEImage/imageMarkup.cpp

9.28 markupVLine Class Reference

Inheritance diagram for markupVLine:



Public Member Functions

- **markupVLine** ([imageMarkup](#) *ownerIn, bool interactiveIn, bool reportOnMoveIn)
- void **startDrawing** (QPoint pos)
- void **setArea** ()
- void **drawMarkup** (QPainter &p)
- void **moveTo** (QPoint pos)
- bool **isOver** (QPoint point, QCursor *cursor)
- QPoint **origin** ()
- QPoint **getPoint1** ()
- QPoint **getPoint2** ()
- QCursor **defaultCursor** ()

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEImage/imageMarkup.h
- /home/rhydera/epicsqt/framework/widgets/QEImage/imageMarkup.cpp

9.29 PeriodicDialog Class Reference

Public Member Functions

- **PeriodicDialog** (QWidget *parent=0)
- QString **getElement** ()
- void **setElement** (QString elementIn, QList< bool > &enabledList, QList< QString > &elementList)

Protected Member Functions

- void **changeEvent** (QEvent *e)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEPeriodic/PeriodicDialog.h
- /home/rhydera/epicsqt/framework/widgets/QEPeriodic/PeriodicDialog.cpp

9.30 PeriodicElementSetupForm Class Reference

Public Member Functions

- **PeriodicElementSetupForm** (QWidget *parent=0)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEPeriodic/PeriodicElementSetupForm.h
- /home/rhydera/epicsqt/framework/widgets/QEPeriodic/PeriodicElementSetupForm.cpp

9.31 PeriodicSetupDialog Class Reference

Public Member Functions

- **PeriodicSetupDialog** (QWidget *parent=0)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEPeriodic/PeriodicSetupDialog.h
- /home/rhydera/epicsqt/framework/widgets/QEPeriodic/PeriodicSetupDialog.cpp

9.32 QEStripChart::PrivateData Class Reference

Public Member Functions

- **PrivateData** (QEStripChart *chartIn)
- QEStripChartItem * **getItem** (unsigned int slot)
- QwtPlotCurve * **allocateCurve** ()
- void **calcDisplayMinMax** ()
- void **plotData** ()
- void **setReadOut** (QString text)

Public Attributes

- enum ChartYScale **chartYScale**
- enum ChartTimeMode **chartTimeMode**

Protected Member Functions

- bool **eventFilter** (QObject *obj, QEvent *event)

The documentation for this class was generated from the following file:

- /home/rhydera/epicsqt/framework/widgets/QEStripChart/QEStripChart.cpp

9.33 QEStripChartItem::PrivateData Class Reference

Public Attributes

- [QEStripChart](#) * **chart**
- [QLabel](#) * **pvName**
- [QELabel](#) * **caLabel**

The documentation for this class was generated from the following file:

- /home/rhydera/epicsqt/framework/widgets/QEStripChart/QEStripChartItem.cpp

9.34 profilePlot Class Reference

Public Member Functions

- **profilePlot** (QWidget *parent=0)
- void **setScale** (int scaleIn)
- void **setProfile** (QVector< QPointF > &profile, double minX, double maxX, double minY, double maxY)
- void **setCursor** (int cursorIn)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEImage/profilePlot.h
- /home/rhydera/epicsqt/framework/widgets/QEImage/profilePlot.cpp

9.35 QPushButtonSpecifications Struct Reference

Public Attributes


- int **width**
- const QString **caption**
- const QString **iconName**
- const QString **toolTip**
- const char * **member**

The documentation for this struct was generated from the following file:

- /home/rhydera/epicsqt/framework/widgets/QEStripChart/QEStripChart.cpp

9.36 QBitStatus Class Reference

Inheritance diagram for QBitStatus:



Public Types

- enum **Orientations** { **LSB_On_Right**, **LSB_On_Bottom**, **LSB_On_Left**, **LSB_On_Top** }
- enum **Shapes** { **Rectangle**, **Circle** }

Public Slots

- void **setValue** (const int value)

Public Member Functions

- **QBitStatus** (QWidget *parent=0)
- virtual QSize **sizeHint** () const
- void **setBorderColour** (const QColor value)
- QColor **getBorderColour** ()
- void **setOnColour** (const QColor value)
- QColor **getOnColour** ()
- void **setOffColour** (const QColor value)
- QColor **getOffColour** ()
- void **setInvalidColour** (const QColor value)
- QColor **getInvalidColour** ()
- void **setClearColour** (const QColor value)
- QColor **getClearColour** ()
- void **setDrawBorder** (const bool value)
- bool **getDrawBorder** ()
- void **setNumberOfBits** (const int value)
- int **getNumberOfBits** ()
- void **setGap** (const int value)
- int **getGap** ()
- void **setShift** (const int value)
- int **getShift** ()
- void **setOnClearMask** (const QString value)
- QString **getOnClearMask** ()

- void **setOffClearMask** (const QString value)
- QString **getOffClearMask** ()
- void **setReversePolarityMask** (const QString value)
- QString **getReversePolarityMask** ()
- void **setIsValid** (const bool value)
- bool **getIsValid** ()
- void **setOrientation** (const enum Orientations value)
- enum Orientations **getOrientation** ()
- void **setShape** (const enum Shapes value)
- enum Shapes **getShape** ()
- int **getValue** ()

Properties

- int **value**
- int **numberOfBits**
- int **shift**
- Orientations **Orientation**
- Shapes **shape**
- int **gap**
- QString **reversePolarityMask**
- QString **onClearMask**
- QString **offClearMask**
- QColor **boarderColour**
- QColor **invalidColour**
- QColor **onColour**
- QColor **offColour**
- QColor **clearColour**
- bool **drawBorder**
- bool **isValid**

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEBitStatus/QBitStatus.h
- /home/rhydera/epicsqt/framework/widgets/QEBitStatus/QBitStatus.cpp

9.37 QCaAlarmInfo Class Reference

Public Member Functions

- **QCaAlarmInfo** (unsigned short statusIn, unsigned short severityIn)
- QString **statusName** ()
- QString **severityName** ()
- bool **isInAlarm** ()
- bool **isMinor** ()

- bool **isMajor** ()
- bool **isInvalid** ()
- QString **style** ()
- QString **getColorName** ()
- QCAALARMINFO_SEVERITY **getSeverity** ()

Static Public Member Functions

- static QCAALARMINFO_SEVERITY **getInvalidSeverity** ()

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/data/include/QCaAlarmInfo.h
- /home/rhydera/epicsqt/framework/data/src/QCaAlarmInfo.cpp

9.38 QCaConnectionInfo Class Reference

Public Member Functions

- **QCaConnectionInfo** (unsigned short channelStateIn, unsigned short linkStateIn)
- bool **isChannelConnected** ()
- bool **isLinkUp** ()

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/data/include/QCaConnectionInfo.h
- /home/rhydera/epicsqt/framework/data/src/QCaConnectionInfo.cpp

9.39 QCaDataPoint Struct Reference

Public Attributes

- double **value**
- [QCaDateTime](#) **datetime**
- [QCaAlarmInfo](#) **alarm**

The documentation for this struct was generated from the following file:

- /home/rhydera/epicsqt/framework/data/include/QCaDataPoint.h

9.40 QCaDataPointList Class Reference

The documentation for this class was generated from the following file:

- /home/rhydera/epicsqt/framework/data/include/QCaDataPoint.h

9.41 QCaDateTime Class Reference

Public Member Functions

- **QCaDateTime** (QDateTime dt)
- void **operator=** (const [QCaDateTime](#) &other)
- **QCaDateTime** (unsigned long seconds, unsigned long nanoseconds)
- QString **text** ()
- double **floating** (QDateTime base)

Public Attributes

- unsigned long **nSec**

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/data/include/QCaDateTime.h
- /home/rhydera/epicsqt/framework/data/src/QCaDateTime.cpp

9.42 QCaEventFilter Class Reference

Public Member Functions

- void **addFilter** (QObject *objectIn)
- void **deleteFilter** (QObject *objectIn)
- bool **eventFilter** (QObject *watched, QEvent *e)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/data/include/QCaEventFilter.h
- /home/rhydera/epicsqt/framework/data/src/QCaEventFilter.cpp

9.43 QCaEventItem Class Reference

Public Member Functions

- **QCaEventItem** ([QCaEventUpdate](#) *newEvent)

Public Attributes

- [QCaEventUpdate](#) * **event**

The documentation for this class was generated from the following file:

- /home/rhydera/epicsqt/framework/data/include/QCaEventUpdate.h

9.44 QCaEventUpdate Class Reference

Public Member Functions

- **QCaEventUpdate** ([qcaobject::QCaObject](#) *emitterObjectIn, long newReason, void *newDataPtr)

Public Attributes

- bool **acceptThisEvent**
- [qcaobject::QCaObject](#) * **emitterObject**
- long **reason**
- void * **dataPtr**

Static Public Attributes

- static QEvent::Type **EVENT_UPDATE_TYPE** = QEvent::User

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/data/include/QCaEventUpdate.h
- /home/rhydera/epicsqt/framework/data/src/QCaEventUpdate.cpp

9.45 QCaInstalledFiltersListItem Class Reference

Public Member Functions

- **QCaInstalledFiltersListItem** (QObject *eventObjectIn)

Public Attributes


- QObject * **eventObject**
- long **referenceCount**

The documentation for this class was generated from the following file:

- /home/rhydera/epicsqt/framework/data/include/QCaEventFilter.h

9.46 qcaobject::QCaObject Class Reference

Inheritance diagram for qcaobject::QCaObject:



Public Slots

- bool **writeData** (const QVariant &value)
- void **resendLastData** ()

Signals

- void **dataChanged** (const QVariant &value, [QCaAlarmInfo](#) &alarmInfo, [QCaDateTime](#) &timeStamp)
- void **dataChanged** (const QByteArray &value, unsigned long dataSize, [QCaAlarmInfo](#) &alarmInfo, [QCaDateTime](#) &timeStamp)
- void **connectionChanged** ([QCaConnectionInfo](#) &connectionInfo)

Public Member Functions

- **QCaObject** (const QString &recordName, QObject *eventObject, unsigned char signalsToSendIn=SIG_VARIANT)
- **QCaObject** (const QString &recordName, QObject *eventObject, [UserMessage](#) *userMessageIn, unsigned char signalsToSendIn=SIG_VARIANT)
- bool **subscribe** ()
- bool **singleShotRead** ()
- bool **dataTypeKnown** ()
- bool **createChannel** ()
- void **deleteChannel** ()
- bool **createSubscription** ()
- bool **getChannel** ()
- bool **putChannel** ()
- bool **isChannelConnected** ()
- void **startConnectionTimer** ()
- void **stopConnectionTimer** ()
- void **setUserMessage** ([UserMessage](#) *userMessageIn)
- void **enableWriteCallbacks** (bool enable)
- bool **isWriteCallbacksEnabled** ()
- QString **getEgu** ()
- QStringList **getEnumerations** ()

- unsigned int **getPrecision** ()
- double **getDisplayLimitUpper** ()
- double **getDisplayLimitLower** ()
- double **getAlarmLimitUpper** ()
- double **getAlarmLimitLower** ()
- double **getWarningLimitUpper** ()
- double **getWarningLimitLower** ()
- double **getControlLimitUpper** ()
- double **getControlLimitLower** ()
- generic::generic_types **getDataType** ()

Static Public Member Functions


- static void **processEventStatic** (QCaEventUpdate *dataUpdateEvent)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/data/include/QCaObject.h
- /home/rhydera/epicsqt/framework/data/src/QCaObject.cpp

9.47 qcastatemachine::QCaStateMachine Class Reference

Inheritance diagram for qcastatemachine::QCaStateMachine:



Public Member Functions

- **QCaStateMachine** (void *parent)
- virtual bool **process** (int requestedState)=0

Public Attributes

- QMutex **lock**
- bool **pending**
- bool **active**
- bool **expired**
- void * **myWorker**

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/data/include/QCaStateMachine.h
- /home/rhydera/epicsqt/framework/data/src/QCaStateMachine.cpp

9.48 QCaVariableNamePropertyManager Class Reference

Signals

- void **newVariableNameProperty** (QString variable, QString Substitutions, unsigned int variableIndex)

Public Member Functions


- QString **getVariableNameProperty** ()
- void **setVariableNameProperty** (QString variableNamePropertyIn)
- QString **getSubstitutionsProperty** ()
- void **setSubstitutionsProperty** (QString substitutionsPropertyIn)
- void **setVariableIndex** (unsigned int variableIndexIn)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/data/include/QCaVariableNamePropertyManager.h
- /home/rhydera/epicsqt/framework/data/src/QCaVariableNamePropertyManager.cpp

9.49 QEAnalogIndicator Class Reference

Inheritance diagram for QEAnalogIndicator:



Classes

- struct [Band](#)
- class [BandList](#)

Public Types

- enum **Orientations** { **Left_To_Right**, **Top_To_Bottom**, **Right_To_Left**, **Bottom_To_Top** }
- enum **Modes** { **Bar**, **Scale**, **Meter** }

Public Slots

- void **setRange** (const double MinimumIn, const double MaximumIn)
- void **setValue** (const double ValueIn)

Public Member Functions

- **QEAnalogIndicator** (QWidget *parent=0)
- virtual QSize **sizeHint** () const
- double **getValue** ()
- void **setMinimum** (const double value)
- double **getMinimum** ()
- void **setMaximum** (const double value)
- double **getMaximum** ()
- void **setOrientation** (const enum Orientations value)
- enum Orientations **getOrientation** ()
- void **setMode** (const enum Modes value)
- enum Modes **getMode** ()
- void **setCentreAngle** (const int value)
- int **getCentreAngle** ()
- void **setSpanAngle** (const int value)
- int **getSpanAngle** ()
- void **setMinorInterval** (const double value)
- double **getMinorInterval** ()
- void **setMajorInterval** (const double value)
- double **getMajorInterval** ()
- void **setLogScaleInterval** (const int value)
- int **getLogScaleInterval** ()
- void **setBorderColour** (const QColor value)
- QColor **getBorderColour** ()
- void **setForegroundColour** (const QColor value)
- QColor **getForegroundColour** ()
- void **setBackgroundColour** (const QColor value)
- QColor **getBackgroundColour** ()
- void **setFontColour** (const QColor value)
- QColor **getFontColour** ()
- void **setShowText** (const bool value)
- bool **getShowText** ()
- void **setShowScale** (const bool value)
- bool **getShowScale** ()
- void **setLogScale** (const bool value)
- bool **getLogScale** ()

Protected Member Functions

- virtual QString **getTextImage** ()
- virtual [BandList](#) **getBandList** ()

Properties


- double **value**
- double **minimum**
- double **maximum**
- double **minorInterval**
- double **majorInterval**
- int **logScaleInterval**
- bool **showText**
- bool **showScale**
- bool **logScale**
- Modes **mode**
- Orientations **orientation**
- int **centreAngle**
- int **spanAngle**
- QColor **borderColour**
- QColor **backgroundColour**
- QColor **foregroundColour**
- QColor **fontColour**

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEAnalogIndicator/QEAnalogIndicator.h
- /home/rhydera/epicsqt/framework/widgets/QEAnalogIndicator/QEAnalogIndicator.cpp

9.50 QEAnalogProgressBar Class Reference

Inheritance diagram for QEAnalogProgressBar:



Public Types

- enum **UserLevels** { **User** = USERLEVEL_USER, **Scientist** = USERLEVEL_SCIENTIST, **Engineer** = USERLEVEL_ENGINEER }

User friendly enumerations for userLevelVisibility and userLevelEnabled properties - refer to userLevelVisibility and userLevelEnabled properties and userLevel enumeration for details.

- enum [Formats](#) {
Default = QQStringFormatting::FORMAT_DEFAULT, **Floating** = QQStringFormatting::FORMAT_FLOATING, **Integer** = QQStringFormatting::FORMAT_INTEGER, **UnsignedInteger** = QQStringFormatting::FORMAT_UNSIGNEDINTEGER,
Time = QQStringFormatting::FORMAT_TIME, **LocalEnumeration** = QQStringFormatting::FORMAT_LOCAL_ENUMERATE }
User friendly enumerations for format property - refer to QQStringFormatting::formats for details.
- enum [Notations](#) { **Fixed** = QQStringFormatting::NOTATION_FIXED, **Scientific** = QQStringFormatting::NOTATION_SCIENTIFIC, **Automatic** = QQStringFormatting::NOTATION_AUTOMATIC }
User friendly enumerations for notation property - refer to QQStringFormatting::notations for details.
- enum [ArrayActions](#) { **Append** = QQStringFormatting::APPEND, **Ascii** = QQStringFormatting::ASCII, **Index** = QQStringFormatting::INDEX }
User friendly enumerations for arrayAction property - refer to QQStringFormatting::arrayActions for details.
- enum **AlarmSeverityDisplayModes** { **none**, **foreground**, **background** }

Public Slots

- void [requestEnabled](#) (const bool &state)

Signals

- void [dbValueChanged](#) (const double &out)
- void [requestResend](#) ()
Internal use only. Used when changing a property value to force a re-display to reflect the new property value.

Public Member Functions

- bool [isEnabled](#) () const
Access function for 'enabled' property - refer to 'enabled' property for details.
- void [setEnabled](#) (bool state)
Access function for 'enabled' property - refer to 'enabled' property for details.
- [UserLevels](#) [getUserLevelVisibilityProperty](#) ()
Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.
- void [setUserLevelVisibilityProperty](#) ([UserLevels](#) level)
Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.
- [UserLevels](#) [getUserLevelEnabledProperty](#) ()
Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.

- void **setUserLevelEnabledProperty** ([UserLevels](#) level)

Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.
- void **setFormatProperty** ([Formats](#) format)

Access function for 'format' property - refer to 'format' property for details.
- [Formats](#) **getFormatProperty** ()

Access function for 'format' property - refer to 'format' property for details.
- void **setNotationProperty** ([Notations](#) notation)

Access function for 'notation' property - refer to 'notation' property for details.
- [Notations](#) **getNotationProperty** ()

Access function for 'notation' property - refer to 'notation' property for details.
- void **setArrayActionProperty** ([ArrayActions](#) arrayAction)

Access function for 'arrayAction' property - refer to 'arrayAction' property for details.
- [ArrayActions](#) **getArrayActionProperty** ()

Access function for 'arrayAction' property - refer to 'arrayAction' property for details.
- **QEAnalogProgressBar** (QWidget *parent=0)
- **QEAnalogProgressBar** (const QString &variableName, QWidget *parent=0)
- void **setVariableNameAndSubstitutions** (QString variableNameIn, QString variableNameSubstitutionsIn, unsigned int variableIndex)
- void **setUseDbDisplayLimits** (bool useDbDisplayLimitsIn)
- bool **getUseDbDisplayLimits** ()
- void **setAlarmSeverityDisplayMode** (AlarmSeverityDisplayModes value)
- AlarmSeverityDisplayModes **getAlarmSeverityDisplayMode** ()

Protected Member Functions

- QString **getTextImage** ()
- [BandList](#) **getBandList** ()
- void **establishConnection** (unsigned int variableIndex)
- void **stringFormattingChange** ()
- void **dragEnterEvent** (QDragEnterEvent *event)
- void **dropEvent** (QDropEvent *event)
- void **mousePressEvent** (QMouseEvent *event)
- void **setDrop** (QVariant drop)
- QVariant **getDrop** ()
- QString **copyVariable** ()
- QVariant **copyData** ()

Protected Attributes

- [QEFloatingFormatting](#) **floatingFormatting**

Properties

- QString [variable](#)
- QString [variableSubstitutions](#)
- bool [variableAsToolTip](#)
- bool [enabled](#)
- bool [allowDrop](#)
- bool [visible](#)
- unsigned [int](#)
- QString [userLevelUserStyle](#)
- QString [userLevelScientistStyle](#)
- QString [userLevelEngineerStyle](#)
- [UserLevels](#) [userLevelVisibility](#)
- [UserLevels](#) [userLevelEnabled](#)
- int [precision](#)
- bool [useDbPrecision](#)
- bool [leadingZero](#)
- bool [trailingZeros](#)
- bool [addUnits](#)
- QString [localEnumeration](#)
- [Formats](#) [format](#)
- [Notations](#) [notation](#)
- [ArrayActions](#) [arrayAction](#)
- bool **useDbDisplayLimits**
- [AlarmSeverityDisplayModes](#) **alarmSeverityDisplayMode**

9.50.1 Member Function Documentation

9.50.1.1 void `QEAnalogProgressBar::dbValueChanged (const double & out)` [signal]

Sent when the widget is updated following a data change Can be used to pass on EPICS data (as presented in this widget) to other widgets. For example a QList widget could log updates from this widget.

9.50.1.2 void `QEAnalogProgressBar::requestEnabled (const bool & state)` [inline, slot]

Similar to standard `setEnabled` slot, but allows QE widget to determine if the widget remains disabled due to invalid data. If disabled due to invalid data, a request to enable the widget will be honoured when the data is no longer invalid.

9.50.2 Property Documentation

9.50.2.1 bool `QEAnalogProgressBar::addUnits` [read, write]

If true (default), add engineering units supplied with the data.

9.50.2.2 `bool QEAnalogProgressBar::allowDrop` [read, write]

Allow drag/drops operations to this widget. Default is false. Any dropped text will be used as a new variable name.

Reimplemented from [QEDragDrop](#).

9.50.2.3 `ArrayActions QEAnalogProgressBar::arrayAction` [read, write]

Text formatting option for array data. Default is ASCII. Options are:

- ASCII - treat array as a single text string. For example an array of three characters 'a' 'b' 'c' will be formatted as 'abc'.
- APPEND - treat array as an array of numbers and format a string containing them all with a space between each. For example, an array of three numbers 10, 11 and 12 will be formatted as '10 11 12'.
- INDEX - Extract a single item from the array. The item is then formatted as any other non array data would be. The item selected is determined by the `arrayIndex` property. For example, if `arrayIndex` property is 1, an array of three numbers 10, 11 and 12 will be formatted as '11'.

9.50.2.4 `bool QEAnalogProgressBar::enabled` [read, write]

Set the preferred 'enabled' state. Default is true. This property is copied to the standard Qt 'enabled' property if the data being displayed is valid. If the data being displayed is invalid the standard Qt 'enabled' property will always be set to false to indicate invalid data. The value of this property will only be copied to the standard Qt 'enabled' property once data is valid.

9.50.2.5 `Formats QEAnalogProgressBar::format` [read, write]

Format to apply to data. Default is 'Default' in which case the data type supplied with the data determines how the data is formatted. For all other options, an attempt is made to format the data as requested (whatever its native form).

9.50.2.6 `unsigned QEAnalogProgressBar::int` [read, write]

Set the ID used by the message filtering system. Default is zero. Widgets or applications that use messages from the framework have the option of filtering on this ID. For example, by using a unique message source ID a [QELog](#) widget may be set up to only log messages from a select set of widgets.

Base used for when formatting integers. Default is 10 (duh!)

Index used to select a single item of data for formatting from an array of data. Default is 0. Only used when the `arrayAction` property is INDEX. Refer to the `arrayAction` property for more details.

9.50.2.7 `bool QEAnalogProgressBar::leadingZero` [read, write]

If true (default), always add a leading zero when formatting numbers.

9.50.2.8 `QString QEAnalogProgressBar::localEnumeration` [read, write]

An enumeration list used to data values. Used only when the formatting option is 'local enumeration'. Value is converted to an integer and used to select a string from this list.

9.50.2.9 `Notations QEAnalogProgressBar::notation` [read, write]

Notation used for numerical formatting. Default is fixed.

9.50.2.10 `int QEAnalogProgressBar::precision` [read, write]

Precision used when formatting floating point numbers. The default is 4. This is only used if `useDbPrecision` is false.

9.50.2.11 `bool QEAnalogProgressBar::trailingZeros` [read, write]

If true (default), always remove any trailing zeros when formatting numbers.

9.50.2.12 `bool QEAnalogProgressBar::useDbPrecision` [read, write]

If true (default), format floating point numbers using the precision supplied with the data. If false, the precision property is used.

9.50.2.13 `UserLevels QEAnalogProgressBar::userLevelEnabled` [read, write]

Lowest user level at which the widget is enabled. Default is 'User'. Used when designing GUIs that allow access to more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through `setUserLevel()` Widgets that are always accessable should be visible at 'User'. Widgets that are only accessable to scientists managing the facility should be visible at 'Scientist'. Widgets that are only accessable to engineers maintaining the facility should be visible at 'Engineer'.

9.50.2.14 `QString QEAnalogProgressBar::userLevelEngineerStyle` [read, write]

Style Sheet string to be applied when the widget is displayed in 'Engineer' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the `styleManager` class. Refer to the `styleManager` class for details about how this Style Sheet string

will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.50.2.15 QString QEAnalogProgressBar::userLevelScientistStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'Scientist' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.50.2.16 QString QEAnalogProgressBar::userLevelUserStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'User' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.50.2.17 UserLevels QEAnalogProgressBar::userLevelVisibility [read, write]

Lowest user level at which the widget is visible. Default is 'User'. Used when designing GUIs that display more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through setUserLevel() Widgets that are always visible should be visible at 'User'. Widgets that are only used by scientists managing the facility should be visible at 'Scientist'. Widgets that are only used by engineers maintaining the facility should be visible at 'Engineer'.

9.50.2.18 QString QEAnalogProgressBar::variable [read, write]

EPICS variable name (CA PV)

9.50.2.19 bool QEAnalogProgressBar::variableAsToolTip [read, write]

Use the variable as the tool tip. Default is true. Tool tip property will be overwritten by the variable name.

Reimplemented from [QEWidget](#).

9.50.2.20 QString QEAnalogProgressBar::variableSubstitutions [read, write]

Macro substitutions. The default is no substitutions. The format is NAME1=VALUE1[, NAME2=VALUE2... Values may be quoted strings. For example, 'PUMP=PMP3, NAME

= "My Pump" These substitutions are applied to variable names for all QE widgets. In some widgets are also used for other purposes.

9.50.2.21 bool QEAnalogProgressBar::visible [read, write]


Display the widget. Default is true. Setting this property false is usefull if widget is only used to provide a signal - for example, when supplying data to a [QELink](#) widget. Note, when false the widget will still be visible in Qt Designer.

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEAnalogProgressBar/QEAnalogProgressBar.h
- /home/rhydera/epicsqt/framework/widgets/QEAnalogProgressBar/QEAnalogProgressBar.cpp

9.51 QEBitStatus Class Reference

Inheritance diagram for QEBitStatus:



Public Types

- enum [UserLevels](#) { **User** = USERLEVEL_USER, **Scientist** = USERLEVEL_SCIENTIST, **Engineer** = USERLEVEL_ENGINEER }

User friendly enumerations for userLevelVisibility and userLevelEnabled properties - refer to userLevelVisibility and userLevelEnabled properties and userLevel enumeration for details.

Public Slots

- void [requestEnabled](#) (const bool &state)

Signals

- void [dbValueChanged](#) (const long &out)

Public Member Functions

- bool [isEnabled](#) () const
Access function for 'enabled' property - refer to 'enabled' property for details.
- void [setEnabled](#) (bool state)
Access function for 'enabled' property - refer to 'enabled' property for details.
- [UserLevels](#) [getUserLevelVisibilityProperty](#) ()
Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.
- void [setUserLevelVisibilityProperty](#) ([UserLevels](#) level)
Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.
- [UserLevels](#) [getUserLevelEnabledProperty](#) ()
Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.
- void [setUserLevelEnabledProperty](#) ([UserLevels](#) level)
Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.
- **QEBitStatus** (QWidget *parent=0)
- **QEBitStatus** (const QString &variableName, QWidget *parent=0)
- void **setVariableNameAndSubstitutions** (QString variableNameIn, QString variableNameSubstitutionsIn, unsigned int variableIndex)

Protected Member Functions

- void **establishConnection** (unsigned int variableIndex)
- void **dragEnterEvent** (QDragEnterEvent *event)
- void **dropEvent** (QDropEvent *event)
- void **mousePressEvent** (QMouseEvent *event)
- void **setDrop** (QVariant drop)
- QVariant **getDrop** ()
- QString **copyVariable** ()
- QVariant **copyData** ()

Protected Attributes

- [QEIntegerFormatting](#) **integerFormatting**

Properties

- QString [variable](#)
- QString [variableSubstitutions](#)
- bool [variableAsToolTip](#)
- bool [enabled](#)
- bool [allowDrop](#)

- bool [visible](#)
- unsigned [int](#)
- QString [userLevelUserStyle](#)
- QString [userLevelScientistStyle](#)
- QString [userLevelEngineerStyle](#)
- [UserLevels](#) [userLevelVisibility](#)
- [UserLevels](#) [userLevelEnabled](#)

9.51.1 Member Function Documentation

9.51.1.1 void QEBitStatus::dbValueChanged (const long & *out*) [signal]

Sent when the widget is updated following a data change Can be used to pass on EPICS data (as presented in this widget) to other widgets. For example a QList widget could log updates from this widget.

9.51.1.2 void QEBitStatus::requestEnabled (const bool & *state*) [inline, slot]

Similar to standard setEnabled slot, but allows QE widget to determine if the widget remains disabled due to invalid data. If disabled due to invalid data, a request to enable the widget will be honoured when the data is no longer invalid.

9.51.2 Property Documentation

9.51.2.1 bool QEBitStatus::allowDrop [read, write]

Allow drag/drops operations to this widget. Default is false. Any dropped text will be used as a new variable name.

Reimplemented from [QEDragDrop](#).

9.51.2.2 bool QEBitStatus::enabled [read, write]

Set the preferred 'enabled' state. Default is true. This property is copied to the standard Qt 'enabled' property if the data being displayed is valid. If the data being displayed is invalid the standard Qt 'enabled' property will always be set to false to indicate invalid data. The value of this property will only be copied to the standard Qt 'enabled' property once data is valid.

9.51.2.3 unsigned QEBitStatus::int [read, write]

Set the ID used by the message filtering system. Default is zero. Widgets or applications that use messages from the framework have the option of filtering on this ID. For example, by using a unique message source ID a [QELog](#) widget may be set up to only log messages from a select set of widgets.

9.51.2.4 UserLevels QEBitStatus::userLevelEnabled [read, write]

Lowest user level at which the widget is enabled. Default is 'User'. Used when designing GUIs that allow access to more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through `setUserLevel()` Widgets that are always accessible should be visible at 'User'. Widgets that are only accessible to scientists managing the facility should be visible at 'Scientist'. Widgets that are only accessible to engineers maintaining the facility should be visible at 'Engineer'.

9.51.2.5 QString QEBitStatus::userLevelEngineerStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'Engineer' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the `styleManager` class. Refer to the `styleManager` class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.51.2.6 QString QEBitStatus::userLevelScientistStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'Scientist' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the `styleManager` class. Refer to the `styleManager` class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.51.2.7 QString QEBitStatus::userLevelUserStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'User' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the `styleManager` class. Refer to the `styleManager` class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.51.2.8 UserLevels QEBitStatus::userLevelVisibility [read, write]

Lowest user level at which the widget is visible. Default is 'User'. Used when designing GUIs that display more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through `setUserLevel()` Widgets that are always visible should be visible at 'User'. Widgets that are only used by scientists managing the facility should be visible at 'Scientist'. Widgets that are only used by engineers maintaining the facility should be visible at 'Engineer'.

9.51.2.9 QString QEBitStatus::variable [read, write]

EPICS variable name (CA PV)

9.51.2.10 bool QEBitStatus::variableAsToolTip [read, write]

Use the variable as the tool tip. Default is true. Tool tip property will be overwritten by the variable name.

Reimplemented from [QEWidget](#).

9.51.2.11 QString QEBitStatus::variableSubstitutions [read, write]

Macro substitutions. The default is no substitutions. The format is NAME1=VALUE1[, NAME2=VALUE2... Values may be quoted strings. For example, 'PUMP=PMP3, NAME = "My Pump"' These substitutions are applied to variable names for all QE widgets. In some widgets are also used for other purposes.

9.51.2.12 bool QEBitStatus::visible [read, write]


Display the widget. Default is true. Setting this property false is usefull if widget is only used to provide a signal - for example, when supplying data to a [QELink](#) widget. Note, when false the widget will still be visible in Qt Designer.

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEBitStatus/QEBitStatus.h
- /home/rhydera/epicsqt/framework/widgets/QEBitStatus/QEBitStatus.cpp

9.52 QByteArray Class Reference

Inheritance diagram for QByteArray:



Public Slots

- void **writeByteArray** (const QByteArray &data)

Signals

- void **byteArrayConnectionChanged** (QCaConnectionInfo &connectionInfo, const unsigned int &variableIndex)
- void **byteArrayChanged** (const QByteArray &value, unsigned long dataSize, QCaAlarmInfo &alarmInfo, QCaDateTime &timeStamp, const unsigned int &variableIndex)

Public Member Functions


- **QEByteArray** (QString recordName, QObject *eventObject, unsigned int variableIndexIn)
- **QEByteArray** (QString recordName, QObject *eventObject, unsigned int variableIndexIn, UserMessage *userMessageIn)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/data/include/QEByteArray.h
- /home/rhydera/epicsqt/framework/data/src/QEByteArray.cpp

9.53 QEComboBox Class Reference

Inheritance diagram for QEComboBox:



Public Types

- enum **UserLevels** { **User** = USERLEVEL_USER, **Scientist** = USERLEVEL_SCIENTIST, **Engineer** = USERLEVEL_ENGINEER }

User friendly enumerations for userLevelVisibility and userLevelEnabled properties - refer to userLevelVisibility and userLevelEnabled properties and userLevel enumeration for details.

Public Slots

- void **requestEnabled** (const bool &state)

Signals

- void [dbValueChanged](#) (const qulonglong &out)
- void [userChange](#) (const QString &oldValue, const QString &newValue, const QString &lastValue)

Internal use only. Used by [QEConfiguredLayout](#) to be notified when one of its widgets has written something.

Public Member Functions

- **QEComboBox** (QWidget *parent=0)
- **QEComboBox** (const QString &variableName, QWidget *parent=0)
- void **setWriteOnChange** (bool writeOnChangeIn)
- bool **getWriteOnChange** ()
- void **setSubscribe** (bool subscribe)
- bool **getSubscribe** ()
- void **setUseDbEnumerations** (bool useDbEnumerations)
- bool **getUseDbEnumerations** ()
- bool [isEnabled](#) () const
- *Access function for 'enabled' property - refer to 'enabled' property for details.*
- void [setEnabled](#) (bool state)
- *Access function for 'enabled' property - refer to 'enabled' property for details.*
- [UserLevels](#) **getUserLevelVisibilityProperty** ()
- *Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.*
- void [setEnabled](#) ([UserLevels](#) level)
- *Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.*
- [UserLevels](#) **getUserLevelEnabledProperty** ()
- *Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.*
- void [setEnabled](#) ([UserLevels](#) level)
- *Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.*

Protected Member Functions

- void **establishConnection** (unsigned int variableIndex)
- void **dragEnterEvent** (QDragEnterEvent *event)
- void **dropEvent** (QDropEvent *event)
- void **setDrop** (QVariant drop)
- QVariant **getDrop** ()

Protected Attributes

- [QEIntegerFormatting](#) **integerFormatting**
- bool **useDbEnumerations**
- bool [writeOnChange](#)

Properties

- QString [variable](#)
- QString [variableSubstitutions](#)
- bool [subscribe](#)
- bool [variableAsToolTip](#)
- bool [enabled](#)
- bool [allowDrop](#)
- bool [visible](#)
- unsigned [int](#)
- QString [userLevelUserStyle](#)
- QString [userLevelScientistStyle](#)
- QString [userLevelEngineerStyle](#)
- [UserLevels](#) [userLevelVisibility](#)
- [UserLevels](#) [userLevelEnabled](#)

9.53.1 Member Function Documentation

9.53.1.1 void QComboBox::dbValueChanged (const qulonglong & *out*) [signal]

Sent when the widget is updated following a data change Can be used to pass on EPICS data (as presented in this widget) to other widgets. For example a QList widget could log updates from this widget.

9.53.1.2 void QComboBox::requestEnabled (const bool & *state*) [inline, slot]

Similar to standard setEnabled slot, but allows QE widget to determine if the widget remains disabled due to invalid data. If disabled due to invalid data, a request to enable the widget will be honoured when the data is no longer invalid.

9.53.2 Member Data Documentation

9.53.2.1 bool QComboBox::writeOnChange [read, write, protected]

Sets if this widget writes any changes as the user selects values (the QComboBox 'activated' signal is emitted). Default is 'true' (writes any changes when the QComboBox 'activated' signal is emitted).

9.53.3 Property Documentation

9.53.3.1 `bool QComboBox::allowDrop` [read, write]

Allow drag/drops operations to this widget. Default is false. Any dropped text will be used as a new variable name.

Reimplemented from [QEDragDrop](#).

9.53.3.2 `bool QComboBox::enabled` [read, write]

Set the preferred 'enabled' state. Default is true. This property is copied to the standard Qt 'enabled' property if the data being displayed is valid. If the data being displayed is invalid the standard Qt 'enabled' property will always be set to false to indicate invalid data. The value of this property will only be copied to the standard Qt 'enabled' property once data is valid.

9.53.3.3 `unsigned QComboBox::int` [read, write]

Set the ID used by the message filtering system. Default is zero. Widgets or applications that use messages from the framework have the option of filtering on this ID. For example, by using a unique message source ID a [QELog](#) widget may be set up to only log messages from a select set of widgets.

9.53.3.4 `bool QComboBox::subscribe` [read, write]

Sets if this widget subscribes for data updates and displays current data. Default is 'true' (subscribes for and displays data updates)

Reimplemented from [QEWidget](#).

9.53.3.5 `UserLevels QComboBox::userLevelEnabled` [read, write]

Lowest user level at which the widget is enabled. Default is 'User'. Used when designing GUIs that allow access to more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through `setUserLevel()` Widgets that are always accessible should be visible at 'User'. Widgets that are only accessible to scientists managing the facility should be visible at 'Scientist'. Widgets that are only accessible to engineers maintaining the facility should be visible at 'Engineer'.

9.53.3.6 `QString QComboBox::userLevelEngineerStyle` [read, write]

Style Sheet string to be applied when the widget is displayed in 'Engineer' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the `styleManager` class. Refer to the `styleManager` class for details about how this Style Sheet string

will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.53.3.7 QString QComboBox::userLevelScientistStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'Scientist' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.53.3.8 QString QComboBox::userLevelUserStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'User' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.53.3.9 UserLevels QComboBox::userLevelVisibility [read, write]

Lowest user level at which the widget is visible. Default is 'User'. Used when designing GUIs that display more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through setUserLevel() Widgets that are always visible should be visible at 'User'. Widgets that are only used by scientists managing the facility should be visible at 'Scientist'. Widgets that are only used by engineers maintaining the facility should be visible at 'Engineer'.

9.53.3.10 QString QComboBox::variable [read, write]

EPICS variable name (CA PV)

9.53.3.11 bool QComboBox::variableAsToolTip [read, write]

Use the variable as the tool tip. Default is true. Tool tip property will be overwritten by the variable name.

Reimplemented from [QEWidget](#).

9.53.3.12 QString QComboBox::variableSubstitutions [read, write]

Macro substitutions. The default is no substitutions. The format is NAME1=VALUE1[, NAME2=VALUE2... Values may be quoted strings. For example, 'PUMP=PMP3, NAME

= "My Pump" These substitutions are applied to variable names for all QE widgets. In some widgets are also used for other purposes.

9.53.3.13 bool QEComboBox::visible [read, write]


Display the widget. Default is true. Setting this property false is useful if widget is only used to provide a signal - for example, when supplying data to a [QELink](#) widget. Note, when false the widget will still be visible in Qt Designer.

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEComboBox/QEComboBox.h
- /home/rhydera/epicsqt/framework/widgets/QEComboBox/QEComboBox.cpp

9.54 QEConfiguredLayout Class Reference

Inheritance diagram for QEConfiguredLayout:



Public Types

- enum **configurationTypesProperty** { **File** = FROM_FILE, **Text** = FROM_TEXT }
- enum **detailsLayoutProperty** { **Top** = TOP, **Bottom** = BOTTOM, **Left** = LEFT, **Right** = RIGHT }
- enum **userTypesProperty** { **User** = USERLEVEL_USER, **Scientist** = USERLEVEL_SCIENTIST, **Engineer** = USERLEVEL_ENGINEER }

Public Member Functions

- **QEConfiguredLayout** (QWidget *pParent=0, bool pSubscription=true)
- void **setItemDescription** (QString pValue)
- QString **getItemDescription** ()
- void **setShowItemList** (bool pValue)
- bool **getShowItemList** ()
- void **setConfigurationType** (int pValue)
- int **getConfigurationType** ()
- void **setConfigurationFile** (QString pValue)
- QString **getConfigurationFile** ()
- void **setConfigurationText** (QString pValue)

- QString **getConfigurationText** ()
- void **setDetailsLayout** (int pValue)
- int **getDetailsLayout** ()
- void **setCurrentUserType** (int pValue)
- int **getCurrentUserType** ()
- void **refreshFields** ()
- void **userLevelChanged** (userLevels pValue)
- void **setConfigurationTypeProperty** (configurationTypesProperty pConfigurationType)
- configurationTypesProperty **getConfigurationTypeProperty** ()
- void **setDetailsLayoutProperty** (detailsLayoutProperty pDetailsLayout)
- detailsLayoutProperty **getDetailsLayoutProperty** ()
- void **setCurrentUserTypeProperty** (userTypesProperty pUserType)
- userTypesProperty **getCurrentUserTypeProperty** ()

Public Attributes

- QList< [_Item](#) * > **itemList**
- QList< [_Field](#) * > **currentFieldList**

Protected Attributes

- QLabel * **qLabelItemDescription**
- QComboBox * **qComboBoxItemList**
- QVBoxLayout * **qVBoxLayoutFields**
- QScrollArea * **qScrollArea**
- QString **configurationFile**
- QString **configurationText**
- int **configurationType**
- int **detailsLayout**
- int **currentUserType**
- bool **subscription**

Properties

- QString **itemDescription**
- bool **showItemList**
- configurationTypesProperty **configurationType**
- detailsLayoutProperty **detailsLayout**
- userTypesProperty **currentUserType**

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEConfiguredLayout/QEConfiguredLayout.h
- /home/rhydera/epicsqt/framework/widgets/QEConfiguredLayout/QEConfiguredLayout.cpp

9.55 QEConfiguredLayoutManager Class Reference

Public Member Functions


- **QEConfiguredLayoutManager** (QObject *pParent=0)
- bool **isContainer** () const
- bool **isInitialized** () const
- QIcon **icon** () const
- QString **group** () const
- QString **includeFile** () const
- QString **name** () const
- QString **toolTip** () const
- QString **whatsThis** () const
- QWidget * **createWidget** (QWidget *pParent)
- void **initialize** (QDesignerFormEditorInterface *pCore)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEConfiguredLayout/QEConfiguredLayoutManager.h
- /home/rhydera/epicsqt/framework/widgets/QEConfiguredLayout/QEConfiguredLayoutManager.cpp

9.56 QEDragDrop Class Reference

Inheritance diagram for QEDragDrop:



Public Member Functions

- **QEDragDrop** (QWidget *ownerIn)

Protected Member Functions


- void **qcaDragEnterEvent** (QDragEnterEvent *event)
- void **qcaDropEvent** (QDropEvent *event)
- void **qcaMousePressEvent** (QMouseEvent *event)
- virtual void **setDrop** (QVariant)
- virtual QVariant **getDrop** ()
- void **setAllowDrop** (bool allowDropIn)
- bool **getAllowDrop** ()

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/include/QEDragDrop.h
- /home/rhydera/epicsqt/framework/widgets/src/QEDragDrop.cpp

9.57 QFileBrowser Class Reference

Inheritance diagram for QFileBrowser:



Public Types

- enum **detailsLayoutProperty** { **Top** = TOP, **Bottom** = BOTTOM, **Left** = LEFT, **Right** = RIGHT }

Signals

- void **selected** (QString pFilename)

Public Member Functions

- **QFileBrowser** (QWidget *pParent=0)
- void **setDirectoryPath** (QString pValue)
- QString **getDirectoryPath** ()
- void **setShowDirectoryPath** (bool pValue)
- bool **getShowDirectoryPath** ()
- void **setShowDirectoryBrowser** (bool pValue)
- bool **getShowDirectoryBrowser** ()
- void **setShowRefresh** (bool pValue)
- bool **getShowRefresh** ()
- void **setShowColumnTime** (bool pValue)
- bool **getShowColumnTime** ()
- void **setShowColumnSize** (bool pValue)
- bool **getShowColumnSize** ()
- void **setShowColumnFilename** (bool pValue)
- bool **getShowColumnFilename** ()
- void **setShowFileExtension** (bool pValue)
- bool **getShowFileExtension** ()
- void **setFileFilter** (QString pValue)
- QString **getFileFilter** ()
- void **setDetailsLayout** (int pValue)
- int **getDetailsLayout** ()
- void **updateTable** ()
- void **setDetailsLayoutProperty** (detailsLayoutProperty pDetailsLayout)
- detailsLayoutProperty **getDetailsLayoutProperty** ()

Protected Attributes

- QLineEdit * **qlineEditDirectoryPath**
- QPushButton * **qPushButtonDirectoryBrowser**
- QPushButton * **qPushButtonRefresh**
- [_QTableWidgetFileBrowser](#) * **qTableWidgetFileBrowser**
- QString **fileFilter**
- bool **showFileExtension**
- int **detailsLayout**

Properties


- QString **directoryPath**
- bool **showDirectoryPath**
- bool **showDirectoryBrowser**
- bool **showRefresh**
- bool **showColumnTime**
- bool **showColumnSize**
- bool **showColumnFilename**
- detailsLayoutProperty **detailsLayout**

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEFileBrowser/QEFileBrowser.h
- /home/rhydera/epicsqt/framework/widgets/QEFileBrowser/QEFileBrowser.cpp

9.58 QEFloating Class Reference

Inheritance diagram for QEFloating:



Public Slots

- void **writeFloating** (const double &data)

Signals

- void **floatingConnectionChanged** ([QCaConnectionInfo](#) &connectionInfo, const unsigned int &variableIndex)
- void **floatingChanged** (const double &value, [QCaAlarmInfo](#) &alarmInfo, [QCaDateTime](#) &timeStamp, const unsigned int &variableIndex)
- void **floatingArrayChanged** (const QVector< double > &values, [QCaAlarmInfo](#) &alarmInfo, [QCaDateTime](#) &timeStamp, const unsigned int &variableIndex)

Public Member Functions

- **QEFloating** (QString recordName, QObject *eventObject, [QEFloatingFormatting](#) *floatingFormattingIn, unsigned int variableIndexIn)
- **QEFloating** (QString recordName, QObject *eventObject, [QEFloatingFormatting](#) *floatingFormattingIn, unsigned int variableIndexIn, [UserMessage](#) *userMessageIn)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/data/include/QEFloating.h
- /home/rhydera/epicsqt/framework/data/src/QEFloating.cpp

9.59 QEFloatingFormatting Class Reference

Public Types

- enum **formats** {
FORMAT_e = 'e', **FORMAT_E** = 'E', **FORMAT_f** = 'f', **FORMAT_g** = 'g',
FORMAT_G = 'G' }

Public Member Functions


- double **formatFloating** (const QVariant &value)
- QVector< double > **formatFloatingArray** (const QVariant &value)
- QVariant **formatValue** (const double &floatingValue, generic::generic_types valueType)
- void **setPrecision** (unsigned int precision)
- void **setFormat** (formats format)
- unsigned int **getPrecision** ()
- int **getFormat** ()

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/data/include/QEFloatingFormatting.h
- /home/rhydera/epicsqt/framework/data/src/QEFloatingFormatting.cpp

9.60 QEForm Class Reference

Inheritance diagram for QEForm:



Public Types

- enum **creationOptions** { **CREATION_OPTION_OPEN**, **CREATION_OPTION_NEW_TAB**, **CREATION_OPTION_NEW_WINDOW** }
- enum **MessageFilterOptions** { **Match** = UserMessage::MESSAGE_FILTER_MATCH, **None** = UserMessage::MESSAGE_FILTER_NONE }

Public Slots

- bool **readUiFile** ()
- void **launchGui** (QString guiName, QEForm::creationOptions createOption)

Public Member Functions

- **QEForm** (QWidget *parent=0)
- **QEForm** (const QString &uiFileNameIn, QWidget *parent=0)
- void **commonInit** (const bool alertIfUINoFoundIn)
- QString **getASGuiTitle** ()
- QString **getFullFileName** ()
- void **setVariableNameAndSubstitutions** (QString variableNameIn, QString variableNameSubstitutionsIn, unsigned int variableIndex)
- void **setUiFileName** (QString uiFile)
- QString **getUiFileName** ()
- void **setHandleGuiLaunchRequests** (bool handleGuiLaunchRequests)
- bool **getHandleGuiLaunchRequests** ()
- void **setResizeContents** (bool resizeContentsIn)
- bool **getResizeContents** ()
- void **setVariableNameSubstitutionsProperty** (QString variableNameSubstitutions)
- QString **getVariableNameSubstitutionsProperty** ()
- MessageFilterOptions **getMessageFormFilter** ()
- void **setMessageFormFilter** (MessageFilterOptions messageFormFilter)
- MessageFilterOptions **getMessageSourceFilter** ()
- void **setMessageSourceFilter** (MessageFilterOptions messageSourceFilter)

Protected Member Functions

- void **setVariableNameSubstitutions** (QString variableNameSubstitutionsIn)

Protected Attributes

- QString **uiFileName**
- QString **fullUiFileName**
- bool **handleGuiLaunchRequests**
- bool **resizeContents**

Properties


- QString **uiFile**
- QString **variableSubstitutions**
- unsigned **int**
- MessageFilterOptions **messageFormFilter**
- MessageFilterOptions **messageSourceFilter**

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEForm/QEForm.h
- /home/rhydera/epicsqt/framework/widgets/QEForm/QEForm.cpp

9.61 QEFrame Class Reference

Inheritance diagram for QEFrame:



Public Types

- enum **UserLevels** { **User** = USERLEVEL_USER, **Scientist** = USERLEVEL_SCIENTIST, **Engineer** = USERLEVEL_ENGINEER }

User friendly enumerations for userLevelVisibility and userLevelEnabled properties - refer to userLevelVisibility and userLevelEnabled properties and userLevel enumeration for details.

Public Slots

- void [requestEnabled](#) (const bool &state)

Public Member Functions

- bool [isEnabled](#) () const
Access function for 'enabled' property - refer to 'enabled' property for details.
- void [setEnabled](#) (bool state)
Access function for 'enabled' property - refer to 'enabled' property for details.
- [UserLevels](#) [getUserLevelVisibilityProperty](#) ()
Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.
- void [setUserLevelVisibilityProperty](#) ([UserLevels](#) level)
Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.
- [UserLevels](#) [getUserLevelEnabledProperty](#) ()
Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.
- void [setUserLevelEnabledProperty](#) ([UserLevels](#) level)
Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.
- **QEFrame** (QWidget *parent=0)
- QSize [sizeHint](#) () const

Properties

- bool [variableAsToolTip](#)
- bool [enabled](#)
- bool [allowDrop](#)
- bool [visible](#)
- unsigned int
- QString [userLevelUserStyle](#)
- QString [userLevelScientistStyle](#)
- QString [userLevelEngineerStyle](#)
- [UserLevels](#) [userLevelVisibility](#)
- [UserLevels](#) [userLevelEnabled](#)

9.61.1 Member Function Documentation

9.61.1.1 void QEFrame::requestEnabled (const bool & *state*) [inline, slot]

Similar to standard `setEnabled` slot, but allows QE widget to determine if the widget remains disabled due to invalid data. If disabled due to invalid data, a request to enable the widget will be honoured when the data is no longer invalid.

9.61.2 Property Documentation

9.61.2.1 `bool QFrame::allowDrop` [read, write]

Allow drag/drops operations to this widget. Default is false. Any dropped text will be used as a new variable name.

Reimplemented from [QEDragDrop](#).

9.61.2.2 `bool QFrame::enabled` [read, write]

Set the preferred 'enabled' state. Default is true. This property is copied to the standard Qt 'enabled' property if the data being displayed is valid. If the data being displayed is invalid the standard Qt 'enabled' property will always be set to false to indicate invalid data. The value of this property will only be copied to the standard Qt 'enabled' property once data is valid.

9.61.2.3 `unsigned QFrame::int` [read, write]

Set the ID used by the message filtering system. Default is zero. Widgets or applications that use messages from the framework have the option of filtering on this ID. For example, by using a unique message source ID a [QELog](#) widget may be set up to only log messages from a select set of widgets.

9.61.2.4 `UserLevels QFrame::userLevelEnabled` [read, write]

Lowest user level at which the widget is enabled. Default is 'User'. Used when designing GUIs that allow access to more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programmatically through `setUserLevel()`. Widgets that are always accessible should be visible at 'User'. Widgets that are only accessible to scientists managing the facility should be visible at 'Scientist'. Widgets that are only accessible to engineers maintaining the facility should be visible at 'Engineer'.

9.61.2.5 `QString QFrame::userLevelEngineerStyle` [read, write]

Style Sheet string to be applied when the widget is displayed in 'Engineer' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the `styleManager` class. Refer to the `styleManager` class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.61.2.6 QString QEFrame::userLevelScientistStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'Scientist' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.61.2.7 QString QEFrame::userLevelUserStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'User' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.61.2.8 UserLevels QEFrame::userLevelVisibility [read, write]

Lowest user level at which the widget is visible. Default is 'User'. Used when designing GUIs that display more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through setUserLevel(). Widgets that are always visible should be visible at 'User'. Widgets that are only used by scientists managing the facility should be visible at 'Scientist'. Widgets that are only used by engineers maintaining the facility should be visible at 'Engineer'.

9.61.2.9 bool QEFrame::variableAsToolTip [read, write]

Use the variable as the tool tip. Default is true. Tool tip property will be overwritten by the variable name.

Reimplemented from [QEWidget](#).

9.61.2.10 bool QEFrame::visible [read, write]


Display the widget. Default is true. Setting this property false is usefull if widget is only used to provide a signal - for example, when supplying data to a [QELink](#) widget. Note, when false the widget will still be visible in Qt Designer.

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEFrame/QEFrame.h
- /home/rhydera/epicsqt/framework/widgets/QEFrame/QEFrame.cpp

9.62 QEGenericButton Class Reference

Inheritance diagram for QEGenericButton:



Public Types

- enum **updateOptions** { **UPDATE_TEXT**, **UPDATE_ICON**, **UPDATE_TEXT_AND_ICON**, **UPDATE_STATE** }

Public Member Functions

- **QEGenericButton** (QWidget *owner)
- void **setSubscribe** (bool subscribe)
- bool **getSubscribe** ()
- void **setUpdateOption** (updateOptions updateOptionIn)
- updateOptions **getUpdateOption** ()
- void **setTextAlignment** (Qt::Alignment alignment)
- Qt::Alignment **getTextAlignment** ()
- void **setPassword** (QString password)
- QString **getPassword** ()
- void **setWriteOnPress** (bool writeOnPress)
- bool **getWriteOnPress** ()
- void **setWriteOnRelease** (bool writeOnRelease)
- bool **getWriteOnRelease** ()
- void **setWriteOnClick** (bool writeOnClick)
- bool **getWriteOnClick** ()
- void **setPressText** (QString pressText)
- QString **getPressText** ()
- void **setReleaseText** (QString releaseTextIn)
- QString **getReleaseText** ()
- void **setClickText** (QString clickTextIn)
- QString **getClickText** ()
- void **setClickCheckedText** (QString clickCheckedTextIn)
- QString **getClickCheckedText** ()
- void **setProgram** (QString program)
- QString **getProgram** ()
- void **setArguments** (QStringList arguments)
- QStringList **getArguments** ()
- void **setGuiName** (QString guiName)

- QString **getGuiName** ()
- void **setCreationOption** (QForm::creationOptions creationOption)
- QForm::creationOptions **getCreationOption** ()
- void **setLabelTextProperty** (QString labelTextIn)
- QString **getLabelTextProperty** ()
- void **onGeneralMessage** (QString message)

Protected Member Functions

- void **connectionChanged** (QCaConnectionInfo &connectionInfo)
- void **setGenericButtonText** (const QString &text, QCaAlarmInfo &alarmInfo, QCa-
Date~~Time~~ &, const unsigned int &variableIndex)
- void **userPressed** ()
- void **userReleased** ()
- void **userClicked** (bool checked)
- void **launchGui** (QString guiName, QForm::creationOptions creationOption)
- virtual updateOptions **getDefaultUpdateOption** ()=0
- void **establishConnection** (unsigned int variableIndex)
- bool **getIsConnected** ()
- void **setup** ()

Protected Attributes


- Qt::Alignment **textAlignment**
- QString **password**
- bool **writeOnPress**
- bool **writeOnRelease**
- bool **writeOnClick**
- QString **releaseText**
- QString **pressText**
- QString **clickText**
- QString **clickCheckedText**
- QString **program**
- QStringList **arguments**
- QString **guiName**
- QForm::creationOptions **creationOption**
- bool **localEnabled**
- updateOptions **updateOption**
- QString **labelText**

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEButton/QEGenericButton.h
- /home/rhydera/epicsqt/framework/widgets/QEButton/QEGenericButton.cpp

9.63 QEGroupBox Class Reference

Inheritance diagram for QEGroupBox:



Public Types

- enum [UserLevels](#) { **User** = USERLEVEL_USER, **Scientist** = USERLEVEL_SCIENTIST, **Engineer** = USERLEVEL_ENGINEER }

User friendly enumerations for userLevelVisibility and userLevelEnabled properties - refer to userLevelVisibility and userLevelEnabled properties and userLevel enumeration for details.

Public Slots

- void [requestEnabled](#) (const bool &state)

Public Member Functions

- bool [isEnabled](#) () const
Access function for 'enabled' property - refer to 'enabled' property for details.
- void [setEnabled](#) (bool state)
Access function for 'enabled' property - refer to 'enabled' property for details.
- [UserLevels](#) [getUserLevelVisibilityProperty](#) ()
Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.
- void [setUserLevelVisibilityProperty](#) ([UserLevels](#) level)
Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.
- [UserLevels](#) [getUserLevelEnabledProperty](#) ()
Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.
- void [setUserLevelEnabledProperty](#) ([UserLevels](#) level)
Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.
- QEGroupBox** ([QWidget](#) *parent=0)
- QSize [sizeHint](#) () const

Properties

- bool [variableAsToolTip](#)
- bool [enabled](#)
- bool [allowDrop](#)
- bool [visible](#)
- unsigned [int](#)
- QString [userLevelUserStyle](#)
- QString [userLevelScientistStyle](#)
- QString [userLevelEngineerStyle](#)
- [UserLevels](#) [userLevelVisibility](#)
- [UserLevels](#) [userLevelEnabled](#)

9.63.1 Member Function Documentation

9.63.1.1 void QEGroupBox::requestEnabled (const bool & *state*) [inline, slot]

Similar to standard setEnabled slot, but allows QE widget to determine if the widget remains disabled due to invalid data. If disabled due to invalid data, a request to enable the widget will be honoured when the data is no longer invalid.

9.63.2 Property Documentation

9.63.2.1 bool QEGroupBox::allowDrop [read, write]

Allow drag/drops operations to this widget. Default is false. Any dropped text will be used as a new variable name.

Reimplemented from [QEDragDrop](#).

9.63.2.2 bool QEGroupBox::enabled [read, write]

Set the preferred 'enabled' state. Default is true. This property is copied to the standard Qt 'enabled' property if the data being displayed is valid. If the data being displayed is invalid the standard Qt 'enabled' property will always be set to false to indicate invalid data. The value of this property will only be copied to the standard Qt 'enabled' property once data is valid.

9.63.2.3 unsigned QEGroupBox::int [read, write]

Set the ID used by the message filtering system. Default is zero. Widgets or applications that use messages from the framework have the option of filtering on this ID. For example, by using a unique message source ID a [QELog](#) widget may be set up to only log messages from a select set of widgets.

9.63.2.4 UserLevels QEGroupBox::userLevelEnabled [read, write]

Lowest user level at which the widget is enabled. Default is 'User'. Used when designing GUIs that allow access to more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through `setUserLevel()` Widgets that are always accessible should be visible at 'User'. Widgets that are only accessible to scientists managing the facility should be visible at 'Scientist'. Widgets that are only accessible to engineers maintaining the facility should be visible at 'Engineer'.

9.63.2.5 QString QEGroupBox::userLevelEngineerStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'Engineer' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.63.2.6 QString QEGroupBox::userLevelScientistStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'Scientist' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.63.2.7 QString QEGroupBox::userLevelUserStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'User' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.63.2.8 UserLevels QEGroupBox::userLevelVisibility [read, write]

Lowest user level at which the widget is visible. Default is 'User'. Used when designing GUIs that display more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through `setUserLevel()` Widgets that are always visible should be visible at 'User'. Widgets that are only used by scientists managing the facility should be visible at 'Scientist'. Widgets that are only used by engineers maintaining the facility should be visible at 'Engineer'.

9.63.2.9 bool QEGroupBox::variableAsToolTip [read, write]

Use the variable as the tool tip. Default is true. Tool tip property will be overwritten by the variable name.

Reimplemented from [QEObject](#).

9.63.2.10 bool QEGroupBox::visible [read, write]


Display the widget. Default is true. Setting this property false is usefull if widget is only used to provide a signal - for example, when supplying data to a [QELink](#) widget. Note, when false the widget will still be visible in Qt Designer.

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEGroupBox/QEGroupBox.h
- /home/rhydera/epicsqt/framework/widgets/QEGroupBox/QEGroupBox.cpp

9.64 QEImage Class Reference

Inheritance diagram for QEImage:



Public Types

- enum **selectOptions** {
SO_NONE, **SO_PANNING**, **SO_VSLICE**, **SO_HSLICE**,
SO_AREA, **SO_PROFILE**, **SO_TARGET**, **SO_BEAM** }
- enum **formatOptions** { **GREY8**, **GREY12**, **GREY16**, **RGB_888** }
- enum **resizeOptions** { **RESIZE_OPTION_ZOOM**, **RESIZE_OPTION_FIT** }
- enum **rotationOptions** { **ROTATION_0**, **ROTATION_90_RIGHT**, **ROTATION_90_LEFT**, **ROTATION_180** }
- enum **UserLevels** { **User** = USERLEVEL_USER, **Scientist** = USERLEVEL_SCIENTIST, **Engineer** = USERLEVEL_ENGINEER }
User friendly enumerations for userLevelVisibility and userLevelEnabled properties - refer to userLevelVisibility and userLevelEnabled properties and userLevel enumeration for details.
- enum **FormatOptions** { **Grey_8** = QEImage::GREY8, **Grey_12** = QEImage::GREY12, **Grey_16** = QEImage::GREY16, **RGB** = QEImage::RGB_888 }

- enum **ResizeOptions** { **Zoom** = QImage::RESIZE_OPTION_ZOOM, **Fit** = QImage::RESIZE_OPTION_FIT }
- enum **RotationOptions** { **NoRotation** = QImage::ROTATION_0, **Rotate90Right** = QImage::ROTATION_90_RIGHT, **Rotate90Left** = QImage::ROTATION_90_LEFT, **Rotate180** = QImage::ROTATION_180 }

Public Slots

- void **setSelectPanMode** ()
- void **setSelectVSliceMode** ()
- void **setSelectHSliceMode** ()
- void **setSelectAreaMode** ()
- void **setSelectProfileMode** ()
- void **setSelectTargetMode** ()
- void **setSelectBeamMode** ()
- void **pauseClicked** ()
- void **saveClicked** ()
- void **roiClicked** ()
- void **resetRoiClicked** ()
- void **targetClicked** ()
- void **requestEnabled** (const bool &state)

Signals

- void **dbValueChanged** (const QString &out)
- void **requestResend** ()

Internal use only. Used when changing a property value to force a re-display to reflect the new property value.

Public Member Functions

- **QEImage** (QWidget *parent=0)
- **QEImage** (const QString &variableName, QWidget *parent=0)
- selectOptions **getSelectionOption** ()
- void **setFormatOption** (formatOptions formatOption)
- formatOptions **getFormatOption** ()
- void **setResizeOption** (resizeOptions resizeOptionIn)
- resizeOptions **getResizeOption** ()
- void **setZoom** (int zoomIn)
- int **getZoom** ()
- void **setRotation** (rotationOptions rotationIn)
- rotationOptions **getRotation** ()
- void **setHorizontalFlip** (bool flipHozIn)
- bool **getHorizontalFlip** ()
- void **setVerticalFlip** (bool flipVertIn)

- bool **getVerticalFlip** ()
- void **setInitialHozScrollPos** (int initialHosScrollPosIn)
- int **getInitialHozScrollPos** ()
- void **setInitialVertScrollPos** (int initialVertScrollPosIn)
- int **getInitialVertScrollPos** ()
- void **setDisplayAcquirePeriod** (bool displayAcquirePeriodIn)
- bool **getDisplayAcquirePeriod** ()
- void **setDisplayExposureTime** (bool displayExposureTimeIn)
- bool **getDisplayExposureTime** ()
- void **setDisplayButtonBar** (bool displayButtonBarIn)
- bool **getDisplayButtonBar** ()
- void **setShowTime** (bool pValue)
- bool **getShowTime** ()
- void **setVertSliceMarkupColor** (QColor pValue)
- QColor **getVertSliceMarkupColor** ()
- void **setHozSliceMarkupColor** (QColor pValue)
- QColor **getHozSliceMarkupColor** ()
- void **setProfileMarkupColor** (QColor pValue)
- QColor **getProfileMarkupColor** ()
- void **setAreaMarkupColor** (QColor pValue)
- QColor **getAreaMarkupColor** ()
- void **setTargetMarkupColor** (QColor pValue)
- QColor **getTargetMarkupColor** ()
- void **setBeamMarkupColor** (QColor pValue)
- QColor **getBeamMarkupColor** ()
- void **setTimeMarkupColor** (QColor pValue)
- QColor **getTimeMarkupColor** ()
- void **setDisplayCursorPixelInfo** (bool displayCursorPixelInfoIn)
- bool **getDisplayCursorPixelInfo** ()
- void **setContrastReversal** (bool contrastReversalIn)
- bool **getContrastReversal** ()
- void **setEnablePan** (bool enablePanIn)
- bool **getEnablePan** ()
- void **setEnableVertSliceSelection** (bool enableVSliceSelectionIn)
- bool **getEnableVertSliceSelection** ()
- void **setEnableHozSliceSelection** (bool enableHSliceSelectionIn)
- bool **getEnableHozSliceSelection** ()
- void **setEnableAreaSelection** (bool enableAreaSelectionIn)
- bool **getEnableAreaSelection** ()
- void **setEnableProfileSelection** (bool enableProfileSelectionIn)
- bool **getEnableProfileSelection** ()
- void **setEnableTargetSelection** (bool enableTargetSelectionIn)
- bool **getEnableTargetSelection** ()
- bool **isEnabled** () const
Access function for 'enabled' property - refer to 'enabled' property for details.
- void **setEnabled** (bool state)

Access function for 'enabled' property - refer to 'enabled' property for details.

- [UserLevels](#) **getUserLevelVisibilityProperty** ()

Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.

- void [setUserLevelVisibilityProperty](#) ([UserLevels](#) level)

Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.

- [UserLevels](#) **getUserLevelEnabledProperty** ()

Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.

- void [setUserLevelEnabledProperty](#) ([UserLevels](#) level)

Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.

- void **setFormatOptionProperty** (FormatOptions formatOption)
- FormatOptions **getFormatOptionProperty** ()
- void **setResizeOptionProperty** (ResizeOptions resizeOption)
- ResizeOptions **getResizeOptionProperty** ()
- void **setRotationProperty** (RotationOptions rotation)
- RotationOptions **getRotationProperty** ()

Protected Types

- enum **variableIndexes** {
IMAGE_VARIABLE, **WIDTH_VARIABLE**, **HEIGHT_VARIABLE**, **ROI_X_VARIABLE**,
ROI_Y_VARIABLE, **ROI_W_VARIABLE**, **ROI_H_VARIABLE**, **TARGET_X_VARIABLE**,
TARGET_Y_VARIABLE, **BEAM_X_VARIABLE**, **BEAM_Y_VARIABLE**, **TARGET_**-
TRIGGER_VARIABLE,
CLIPPING_ONOFF_VARIABLE, **CLIPPING_LOW_VARIABLE**, **CLIPPING_HIGH_**-
VARIABLE, **QEIMAGE_NUM_VARIABLES** }

Protected Member Functions

- void **establishConnection** (unsigned int variableIndex)
- void **dragEnterEvent** (QDragEnterEvent *event)
- void **dropEvent** (QDropEvent *event)
- void **setDrop** (QVariant drop)
- QVariant **getDrop** ()
- QString **copyVariable** ()
- QVariant **copyData** ()
- void **paste** (QVariant v)
- void **resizeEvent** (QResizeEvent *)

Protected Attributes

- [QEIntegerFormatting](#) **integerFormatting**
- **resizeOptions** **resizeOption**
- **int zoom**
- **rotationOptions** **rotation**
- **bool flipVert**
- **bool flipHoz**
- **int initialHozScrollPos**
- **int initialVertScrollPos**
- **bool displayButtonBar**

Properties

- **QString** [imageVariable](#)
- **QString** [widthVariable](#)
- **QString** [heightVariable](#)
- **QString** [regionOfInterestXVariable](#)
- **QString** [regionOfInterestYVariable](#)
- **QString** [regionOfInterestWVariable](#)
- **QString** [regionOfInterestHVariable](#)
- **QString** [targetXVariable](#)
- **QString** [targetYVariable](#)
- **QString** [beamXVariable](#)
- **QString** [beamYVariable](#)
- **QString** [targetTriggerVariable](#)
- **QString** [clippingOnOffVariable](#)
- **QString** [clippingLowVariable](#)
- **QString** [clippingHighVariable](#)
- **QString** [variableSubstitutions](#)
- **bool** [variableAsToolTip](#)
- **bool** [enabled](#)
- **bool** [allowDrop](#)
- **bool** [visible](#)
- **unsigned int**
- **QString** [userLevelUserStyle](#)
- **QString** [userLevelScientistStyle](#)
- **QString** [userLevelEngineerStyle](#)
- **UserLevels** [userLevelVisibility](#)
- **UserLevels** [userLevelEnabled](#)
- **FormatOptions** **formatOption**
- **bool** **enableVertSliceSelection**
- **bool** **enableHozSliceSelection**
- **bool** **showTime**
- **QColor** **vertSliceColor**
- **QColor** **hozSliceColor**

- QColor **profileColor**
- QColor **areaColor**
- QColor **beamColor**
- QColor **targetColor**
- QColor **timeColor**
- ResizeOptions **resizeOption**
- RotationOptions **rotation**
- bool **verticalFlip**
- bool **horizontalFlip**
- int **initialHosScrollPos**

9.64.1 Member Function Documentation

9.64.1.1 void QEImage::dbValueChanged (const QString & *out*) [signal]

Sent when the widget is updated following a data change Can be used to pass on EPICS data (as presented in this widget) to other widgets. For example a QList widget could log updates from this widget.

9.64.1.2 void QEImage::requestEnabled (const bool & *state*) [inline, slot]

Similar to standard setEnabled slot, but allows QE widget to determine if the widget remains disabled due to invalid data. If disabled due to invalid data, a request to enable the widget will be honoured when the data is no longer invalid.

9.64.2 Property Documentation

9.64.2.1 bool QEImage::allowDrop [read, write]

Allow drag/drops operations to this widget. Default is false. Any dropped text will be used as a new variable name.

Reimplemented from [QEDragDrop](#).

9.64.2.2 QString QEImage::beamXVariable [read, write]

EPICS variable name (CA PV). This variable is used to write the selected beam X position.

9.64.2.3 QString QEImage::beamYVariable [read, write]

EPICS variable name (CA PV). This variable is used to write the selected beam Y position.

9.64.2.4 `QString QEImage::clippingHighVariable` [read, write]

EPICS variable name (CA PV). This variable is used to write the areadetector clipping high level.

9.64.2.5 `QString QEImage::clippingLowVariable` [read, write]

EPICS variable name (CA PV). This variable is used to write the areadetector clipping low level.

9.64.2.6 `QString QEImage::clippingOnOffVariable` [read, write]

EPICS variable name (CA PV). This variable is used to write the areadetector clipping on/off command.

9.64.2.7 `bool QEImage::enabled` [read, write]

Set the preferred 'enabled' state. Default is true. This property is copied to the standard Qt 'enabled' property if the data being displayed is valid. If the data being displayed is invalid the standard Qt 'enabled' property will always be set to false to indicate invalid data. The value of this property will only be copied to the standard Qt 'enabled' property once data is valid.

9.64.2.8 `QString QEImage::heightVariable` [read, write]

EPICS variable name (CA PV). This variable is used to read the height of the image.

9.64.2.9 `QString QEImage::imageVariable` [read, write]

EPICS variable name (CA PV). This variable is used as the source the image waveform.

9.64.2.10 `unsigned QEImage::int` [read, write]

Set the ID used by the message filtering system. Default is zero. Widgets or applications that use messages from the framework have the option of filtering on this ID. For example, by using a unique message source ID a [QELog](#) widget may be set up to only log messages from a select set of widgets.

9.64.2.11 `QString QEImage::regionOfInterestHVariable` [read, write]

EPICS variable name (CA PV). This variable is used to write the region of interest height.

9.64.2.12 QString QEImage::regionOfInterestWVariable [read, write]

EPICS variable name (CA PV). This variable is used to write the region of interest width.

9.64.2.13 QString QEImage::regionOfInterestXVariable [read, write]

EPICS variable name (CA PV). This variable is used to write the region of interest X position.

9.64.2.14 QString QEImage::regionOfInterestYVariable [read, write]

EPICS variable name (CA PV). This variable is used to write the region of interest Y position.

9.64.2.15 QString QEImage::targetTriggerVariable [read, write]

EPICS variable name (CA PV). This variable is used to write a 'trigger' to initiate movement of the target into the beam as defined by the target and beam X and Y positions.

9.64.2.16 QString QEImage::targetXVariable [read, write]

EPICS variable name (CA PV). This variable is used to write the selected target X position.

9.64.2.17 QString QEImage::targetYVariable [read, write]

EPICS variable name (CA PV). This variable is used to write the selected target Y position.

9.64.2.18 UserLevels QEImage::userLevelEnabled [read, write]

Lowest user level at which the widget is enabled. Default is 'User'. Used when designing GUIs that allow access to more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programmatically through `setUserLevel()`. Widgets that are always accessible should be visible at 'User'. Widgets that are only accessible to scientists managing the facility should be visible at 'Scientist'. Widgets that are only accessible to engineers maintaining the facility should be visible at 'Engineer'.

9.64.2.19 QString QImage::userLevelEngineerStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'Engineer' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.64.2.20 QString QImage::userLevelScientistStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'Scientist' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.64.2.21 QString QImage::userLevelUserStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'User' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.64.2.22 UserLevels QImage::userLevelVisibility [read, write]

Lowest user level at which the widget is visible. Default is 'User'. Used when designing GUIs that display more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through setUserLevel() Widgets that are always visible should be visible at 'User'. Widgets that are only used by scientists managing the facility should be visible at 'Scientist'. Widgets that are only used by engineers maintaining the facility should be visible at 'Engineer'.

9.64.2.23 bool QImage::variableAsToolTip [read, write]

Use the variable as the tool tip. Default is true. Tool tip property will be overwritten by the variable name.

Reimplemented from [QEWWidget](#).

9.64.2.24 QString QEImage::variableSubstitutions [read, write]

Macro substitutions. The default is no substitutions. The format is NAME1=VALUE1[, NAME2=VALUE2... Values may be quoted strings. For example, 'CAM=1, NAME = "Image 1"' These substitutions are applied to all the variable names.

9.64.2.25 bool QEImage::visible [read, write]

Display the widget. Default is true. Setting this property false is usefull if widget is only used to provide a signal - for example, when supplying data to a [QELink](#) widget. Note, when false the widget will still be visible in Qt Designer.

9.64.2.26 QString QEImage::widthVariable [read, write]


EPICS variable name (CA PV). This variable is used to read the width of the image.

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEImage/QEImage.h
- /home/rhydera/epicsqt/framework/widgets/QEImage/QEImage.cpp

9.65 QEInteger Class Reference

Inheritance diagram for QEInteger:



Public Slots

- void **writelInteger** (const long &data)

Signals

- void **integerConnectionChanged** ([QCaConnectionInfo](#) &connectionInfo, const unsigned int &variableIndex)
- void **integerChanged** (const long &value, [QCaAlarmInfo](#) &alarmInfo, [QCaDateTime](#) &timeStamp, const unsigned int &variableIndex)
- void **integerArrayChanged** (const QVector< long > &values, [QCaAlarmInfo](#) &alarmInfo, [QCaDateTime](#) &timeStamp, const unsigned int &variableIndex)

Public Member Functions

- **QEInteger** (QString recordName, QObject *eventObject, [QEIntegerFormatting](#) *integerFormattingIn, unsigned int variableIndexIn)
- **QEInteger** (QString recordName, QObject *eventObject, [QEIntegerFormatting](#) *integerFormattingIn, unsigned int variableIndexIn, [UserMessage](#) *userMessageIn)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/data/include/QEInteger.h
- /home/rhydera/epicsqt/framework/data/src/QEInteger.cpp

9.66 QEIntegerFormatting Class Reference

```
#include <QEIntegerFormatting.h>
```

Public Member Functions

- [QEIntegerFormatting](#) ()
Constructor.
- long [formatInteger](#) (const QVariant &value)
- QVector< long > [formatIntegerArray](#) (const QVariant &value)
- QVariant [formatValue](#) (const long &integerValue, generic::generic_types valueType)
- void [setRadix](#) (unsigned int radix)
Set the radix used for all conversions. Default is 10.
- unsigned int [getPrecision](#) ()
Get the precision used for all conversions.
- unsigned int [getRadix](#) ()
Get the radix used for all conversions.

9.66.1 Detailed Description

This class holds formatting instructions and uses them to convert between an integer and a QVariant of any type. It is generally set up with its formatting instructions and then passed to a [QEInteger](#) class that will sink and source integer data to widgets or other code. It is used to convert data to and from a QCaObject (which sources and sinks data in the form of a QVariant where the QVariant reflects the underlying variable data type) and the [QEInteger](#) class. An example of a requirement for integer data is a combo box which must determine an integer index to select a menu option.

9.66.2 Member Function Documentation

9.66.2.1 `long QEIntegerFormatting::formatInteger (const QVariant & value)`

Given a data value of any type, format it as an integer according to the formatting instructions held by the class. This is used to convert the QVariant value received from a QCaObject, which is still based on the data variable type, to an integer.

9.66.2.2 `QVector< long > QEIntegerFormatting::formatIntegerArray (const QVariant & value)`

Given a data value of any type, format it as an array of integers according to the formatting instructions held by the class. This is used to convert the QVariant value received from a QCaObject, which is still based on the data variable type, to an integer array. Typically used where the input QVariant value is an array of data values, but will work for any QVariant type.

9.66.2.3 `QVariant QEIntegerFormatting::formatValue (const long & integerValue, generic::generic_types valueType)`

Given an integer value, format it as a data value of the specified type, according to the formatting instructions held by the class. This is used when writing integer data to a QCaObject.


The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/data/include/QEIntegerFormatting.h
- /home/rhydera/epicsqt/framework/data/src/QEIntegerFormatting.cpp

9.67 QELabel Class Reference

```
#include <QELabel.h>
```

Inheritance diagram for QELabel:



Public Types

- enum `updateOptions` { `UPDATE_TEXT`, `UPDATE_PIXMAP` }
- enum `UserLevels` { `User` = `USERLEVEL_USER`, `Scientist` = `USERLEVEL_SCIENTIST`, `Engineer` = `USERLEVEL_ENGINEER` }

User friendly enumerations for userLevelVisibility and userLevelEnabled properties - refer to userLevelVisibility and userLevelEnabled properties and userLevel enumeration for details.

- enum [Formats](#) {
Default = QQStringFormatting::FORMAT_DEFAULT, **Floating** = QQStringFormatting::FORMAT_FLOATING, **Integer** = QQStringFormatting::FORMAT_INTEGER, **UnsignedInteger** = QQStringFormatting::FORMAT_UNSIGNEDINTEGER,
Time = QQStringFormatting::FORMAT_TIME, **LocalEnumeration** = QQStringFormatting::FORMAT_LOCAL_ENUMERATE }

User friendly enumerations for format property - refer to QQStringFormatting::formats for details.

- enum [Notations](#) { **Fixed** = QQStringFormatting::NOTATION_FIXED, **Scientific** = QQStringFormatting::NOTATION_SCIENTIFIC, **Automatic** = QQStringFormatting::NOTATION_AUTOMATIC }

User friendly enumerations for notation property - refer to QQStringFormatting::notations for details.

- enum [ArrayActions](#) { **Append** = QQStringFormatting::APPEND, **Ascii** = QQStringFormatting::ASCII, **Index** = QQStringFormatting::INDEX }

User friendly enumerations for arrayAction property - refer to QQStringFormatting::arrayActions for details.

- enum [UpdateOptions](#) { **Text** = QELabel::UPDATE_TEXT, **Picture** = QELabel::UPDATE_Pixmap }

User friendly enumerations for updateOption property - refer to [QELabel::updateOptions](#) for details.

Public Slots

- void [requestEnabled](#) (const bool &state)

Signals

- void [dbValueChanged](#) (const QString &out)
- void [requestResend](#) ()

Internal use only. Used when changing a property value to force a re-display to reflect the new property value.

Public Member Functions

- [QELabel](#) (QWidget *parent=0)
- [QELabel](#) (const QString &variableName, QWidget *parent=0)
- bool [isEnabled](#) () const
Access function for 'enabled' property - refer to 'enabled' property for details.
- void [setEnabled](#) (bool state)
Access function for 'enabled' property - refer to 'enabled' property for details.
- [UserLevels](#) [getUserLevelVisibilityProperty](#) ()

Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.

- void [setUserLevelVisibilityProperty](#) ([UserLevels](#) level)

Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.

- [UserLevels](#) [getUserLevelEnabledProperty](#) ()

Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.

- void [setUserLevelEnabledProperty](#) ([UserLevels](#) level)

Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.

- void [setFormatProperty](#) ([Formats](#) format)

Access function for 'format' property - refer to 'format' property for details.

- [Formats](#) [getFormatProperty](#) ()

Access function for 'format' property - refer to 'format' property for details.

- void [setNotationProperty](#) ([Notations](#) notation)

Access function for 'notation' property - refer to 'notation' property for details.

- [Notations](#) [getNotationProperty](#) ()

Access function for 'notation' property - refer to 'notation' property for details.

- void [setArrayActionProperty](#) ([ArrayActions](#) arrayAction)

Access function for 'arrayAction' property - refer to 'arrayAction' property for details.

- [ArrayActions](#) [getArrayActionProperty](#) ()

Access function for 'arrayAction' property - refer to 'arrayAction' property for details.

- void [setUpdateOptionProperty](#) ([UpdateOptions](#) updateOption)

Access function for 'updateOption' property - refer to 'updateOption' property for details.

- [UpdateOptions](#) [getUpdateOptionProperty](#) ()

Access function for 'updateOption' property - refer to 'updateOption' property for details.

- void [setPixmap0Property](#) (QPixmap pixmap)

Access function for 'pixmap0' property - refer to 'pixmap0' property for details.

- void [setPixmap1Property](#) (QPixmap pixmap)

Access function for 'pixmap1' property - refer to 'pixmap1' property for details.

- void [setPixmap2Property](#) (QPixmap pixmap)

Access function for 'pixmap2' property - refer to 'pixmap2' property for details.

- void [setPixmap3Property](#) (QPixmap pixmap)

Access function for 'pixmap3' property - refer to 'pixmap3' property for details.

- void [setPixmap4Property](#) (QPixmap pixmap)

Access function for 'pixmap4' property - refer to 'pixmap4' property for details.

- void [setPixmap5Property](#) (QPixmap pixmap)

Access function for 'pixmap5' property - refer to 'pixmap5' property for details.

- void [setPixmap6Property](#) (QPixmap pixmap)

Access function for 'pixmap6' property - refer to 'pixmap6' property for details.

- void [setPixmap7Property](#) (QPixmap pixmap)

- Access function for 'pixmap7' property - refer to 'pixmap7' property for details.*
- QPixmap [getPixmap0Property](#) ()
Access function for 'pixmap0' property - refer to 'pixmap0' property for details.
- QPixmap [getPixmap1Property](#) ()
Access function for 'pixmap1' property - refer to 'pixmap1' property for details.
- QPixmap [getPixmap2Property](#) ()
Access function for 'pixmap2' property - refer to 'pixmap2' property for details.
- QPixmap [getPixmap3Property](#) ()
Access function for 'pixmap3' property - refer to 'pixmap3' property for details.
- QPixmap [getPixmap4Property](#) ()
Access function for 'pixmap4' property - refer to 'pixmap4' property for details.
- QPixmap [getPixmap5Property](#) ()
Access function for 'pixmap5' property - refer to 'pixmap5' property for details.
- QPixmap [getPixmap6Property](#) ()
Access function for 'pixmap6' property - refer to 'pixmap6' property for details.
- QPixmap [getPixmap7Property](#) ()
Access function for 'pixmap7' property - refer to 'pixmap7' property for details.

Properties

- QString [variable](#)
- QString [variableSubstitutions](#)
- bool [variableAsToolTip](#)
- bool [enabled](#)
- bool [allowDrop](#)
- bool [visible](#)
- unsigned int
- QString [userLevelUserStyle](#)
- QString [userLevelScientistStyle](#)
- QString [userLevelEngineerStyle](#)
- UserLevels [userLevelVisibility](#)
- UserLevels [userLevelEnabled](#)
- int [precision](#)
- bool [useDbPrecision](#)
- bool [leadingZero](#)
- bool [trailingZeros](#)
- bool [addUnits](#)
- QString [localEnumeration](#)
- [Formats](#) [format](#)
- [Notations](#) [notation](#)
- [ArrayActions](#) [arrayAction](#)
- [UpdateOptions](#) [updateOption](#)
- QPixmap [pixmap0](#)
- QPixmap [pixmap1](#)
- QPixmap [pixmap2](#)

- QPixmap [pixmap3](#)
- QPixmap [pixmap4](#)
- QPixmap [pixmap5](#)
- QPixmap [pixmap6](#)
- QPixmap [pixmap7](#)

9.67.1 Detailed Description

This class is a EPICS aware label widget based on the Qt label widget. When a variable is defined, the label text (or optionally the background pixmap) will be updated. The label will be disabled if the variable is invalid. It is tightly integrated with the base class [QEWidget](#) which provides generic support such as macro substitutions, drag/drop, and standard properties.

9.67.2 Member Enumeration Documentation

9.67.2.1 enum `QELabel::updateOptions`

Options for updating the label. The formatted text is used to update the label text, or select a background pixmap.

Enumerator:

`UPDATE_TEXT` Update the label text.

`UPDATE_PIXMAP` Update the label background pixmap.

9.67.3 Constructor & Destructor Documentation

9.67.3.1 `QELabel::QELabel (QWidget * parent = 0)`

Create without a variable. Use `setVariableNameProperty()` and `setSubstitutionsProperty()` to define a variable and, optionally, macro substitutions later.

9.67.3.2 `QELabel::QELabel (const QString & variableName, QWidget * parent = 0)`

Create with a variable. A connection is automatically established. If macro substitutions are required, create without a variable and set the variable and macro substitutions after creation.

9.67.4 Member Function Documentation

9.67.4.1 `void QELabel::dbValueChanged (const QString & out) [signal]`

Sent when the widget is updated following a data change Can be used to pass on EPICS data (as presented in this widget) to other widgets. For example a QList widget could log updates from this widget.

9.67.4.2 void QELabel::requestEnabled (const bool & state) [inline, slot]

Similar to standard setEnabled slot, but allows QE widget to determine if the widget remains disabled due to invalid data. If disabled due to invalid data, a request to enable the widget will be honoured when the data is no longer invalid.

9.67.5 Property Documentation

9.67.5.1 bool QELabel::addUnits [read, write]

If true (default), add engineering units supplied with the data.

9.67.5.2 bool QELabel::allowDrop [read, write]

Allow drag/drops operations to this widget. Default is false. Any dropped text will be used as a new variable name.

Reimplemented from [QEDragDrop](#).

9.67.5.3 ArrayActions QELabel::arrayAction [read, write]

Text formatting option for array data. Default is ASCII. Options are:

- ASCII - treat array as a single text string. For example an array of three characters 'a' 'b' 'c' will be formatted as 'abc'.
- APPEND - treat array as an array of numbers and format a string containing them all with a space between each. For example, an array of three numbers 10, 11 and 12 will be formatted as '10 11 12'.
- INDEX - Extract a single item from the array. The item is then formatted as any other non array data would be. The item selected is determined by the arrayIndex property. For example, if arrayIndex property is 1, an array of three numbers 10, 11 and 12 will be formatted as '11'.

9.67.5.4 bool QELabel::enabled [read, write]

Set the preferred 'enabled' state. Default is true. This property is copied to the standard Qt 'enabled' property if the data being displayed is valid. If the data being displayed is invalid the standard Qt 'enabled' property will always be set to false to indicate invalid data. The value of this property will only be copied to the standard Qt 'enabled' property once data is valid.

9.67.5.5 **Formats** `QELabel::format` [read, write]

Format to apply to data. Default is 'Default' in which case the data type supplied with the data determines how the data is formatted. For all other options, an attempt is made to format the data as requested (whatever its native form).

9.67.5.6 **unsigned** `QELabel::int` [read, write]

Set the ID used by the message filtering system. Default is zero. Widgets or applications that use messages from the framework have the option of filtering on this ID. For example, by using a unique message source ID a [QELog](#) widget may be set up to only log messages from a select set of widgets.

Base used for when formatting integers. Default is 10 (duh!)

Index used to select a single item of data for formatting from an array of data. Default is 0. Only used when the `arrayAction` property is `INDEX`. Refer to the `arrayAction` property for more details.

9.67.5.7 **bool** `QELabel::leadingZero` [read, write]

If true (default), always add a leading zero when formatting numbers.

9.67.5.8 **QString** `QELabel::localEnumeration` [read, write]

An enumeration list used to data values. Used only when the formatting option is 'local enumeration'. Value is converted to an integer and used to select a string from this list.

9.67.5.9 **Notations** `QELabel::notation` [read, write]

Notation used for numerical formatting. Default is fixed.

9.67.5.10 **QPixmap** `QELabel::pixmap0` [read, write]

Pixmap displayed when `updateOption` property is 'Picture' and data is interpreted as 0.

9.67.5.11 **QPixmap** `QELabel::pixmap1` [read, write]

Pixmap displayed when `updateOption` property is 'Picture' and data is interpreted as 1.

9.67.5.12 QPixmap QELabel::pixmap2 [read, write]

Pixmap displayed when updateOption property is 'Picture' and data is interpreted as 2.

9.67.5.13 QPixmap QELabel::pixmap3 [read, write]

Pixmap displayed when updateOption property is 'Picture' and data is interpreted as 3.

9.67.5.14 QPixmap QELabel::pixmap4 [read, write]

Pixmap displayed when updateOption property is 'Picture' and data is interpreted as 4.

9.67.5.15 QPixmap QELabel::pixmap5 [read, write]

Pixmap displayed when updateOption property is 'Picture' and data is interpreted as 5.

9.67.5.16 QPixmap QELabel::pixmap6 [read, write]

Pixmap displayed when updateOption property is 'Picture' and data is interpreted as 6.

9.67.5.17 QPixmap QELabel::pixmap7 [read, write]

Pixmap displayed when updateOption property is 'Picture' and data is interpreted as 7.

9.67.5.18 int QELabel::precision [read, write]

Precision used when formatting floating point numbers. The default is 4. This is only used if useDbPrecision is false.

9.67.5.19 bool QELabel::trailingZeros [read, write]

If true (default), always remove any trailing zeros when formatting numbers.

9.67.5.20 UpdateOptions QELabel::updateOption [read, write]

Determines if data updates the label text, or the label pixmap. For both options all normal string formatting is applied. If Text, the formatted text is simply presented as the

label text. If Picture, the FORMATTED text is then interpreted as an integer and used to select one of the pixmaps specified by properties pixmap0 through to pixmap7.

9.67.5.21 `bool QELabel::useDbPrecision` [read, write]

If true (default), format floating point numbers using the precision supplied with the data. If false, the precision property is used.

9.67.5.22 `UserLevels QELabel::userLevelEnabled` [read, write]

Lowest user level at which the widget is enabled. Default is 'User'. Used when designing GUIs that allow access to more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through `setUserLevel()` Widgets that are always accessible should be visible at 'User'. Widgets that are only accessible to scientists managing the facility should be visible at 'Scientist'. Widgets that are only accessible to engineers maintaining the facility should be visible at 'Engineer'.

9.67.5.23 `QString QELabel::userLevelEngineerStyle` [read, write]

Style Sheet string to be applied when the widget is displayed in 'Engineer' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the `styleManager` class. Refer to the `styleManager` class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.67.5.24 `QString QELabel::userLevelScientistStyle` [read, write]

Style Sheet string to be applied when the widget is displayed in 'Scientist' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the `styleManager` class. Refer to the `styleManager` class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.67.5.25 `QString QELabel::userLevelUserStyle` [read, write]

Style Sheet string to be applied when the widget is displayed in 'User' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the `styleManager` class. Refer to the `styleManager` class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.67.5.26 UserLevels QELabel::userLevelVisibility [read, write]

Lowest user level at which the widget is visible. Default is 'User'. Used when designing GUIs that display more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through `setUserLevel()` Widgets that are always visible should be visible at 'User'. Widgets that are only used by scientists managing the facility should be visible at 'Scientist'. Widgets that are only used by engineers maintaining the facility should be visible at 'Engineer'.

9.67.5.27 QString QELabel::variable [read, write]

EPICS variable name (CA PV)

9.67.5.28 bool QELabel::variableAsToolTip [read, write]

Use the variable as the tool tip. Default is true. Tool tip property will be overwritten by the variable name.

Reimplemented from [QEWidget](#).

9.67.5.29 QString QELabel::variableSubstitutions [read, write]

Macro substitutions. The default is no substitutions. The format is NAME1=VALUE1[, NAME2=VALUE2... Values may be quoted strings. For example, 'PUMP=PMP3, NAME = "My Pump"' These substitutions are applied to variable names for all QE widgets. In some widgets are are also used for other purposes.

9.67.5.30 bool QELabel::visible [read, write]


Display the widget. Default is true. Setting this property false is usefull if widget is only used to provide a signal - for example, when supplying data to a [QELink](#) widget. Note, when false the widget will still be visible in Qt Designer.

The documentation for this class was generated from the following files:

- `/home/rhydera/epicsqt/framework/widgets/QELabel/QELabel.h`
- `/home/rhydera/epicsqt/framework/widgets/QELabel/QELabel.cpp`

9.68 QELineEdit Class Reference

Inheritance diagram for QELineEdit:



Public Types

- enum [UserLevels](#) { **User** = USERLEVEL_USER, **Scientist** = USERLEVEL_SCIENTIST, **Engineer** = USERLEVEL_ENGINEER }
User friendly enumerations for userLevelVisibility and userLevelEnabled properties - refer to userLevelVisibility and userLevelEnabled properties and userLevel enumeration for details.
- enum [Formats](#) {
Default = QEStringFormatting::FORMAT_DEFAULT, **Floating** = QEStringFormatting::FORMAT_FLOATING, **Integer** = QEStringFormatting::FORMAT_INTEGER, **UnsignedInteger** = QEStringFormatting::FORMAT_UNSIGNEDINTEGER,
Time = QEStringFormatting::FORMAT_TIME, **LocalEnumeration** = QEStringFormatting::FORMAT_LOCAL_ENUMERATE }
User friendly enumerations for format property - refer to QEStringFormatting::formats for details.
- enum [Notations](#) { **Fixed** = QEStringFormatting::NOTATION_FIXED, **Scientific** = QEStringFormatting::NOTATION_SCIENTIFIC, **Automatic** = QEStringFormatting::NOTATION_AUTOMATIC }
User friendly enumerations for notation property - refer to QEStringFormatting::notations for details.
- enum [ArrayActions](#) { **Append** = QEStringFormatting::APPEND, **Ascii** = QEStringFormatting::ASCII, **Index** = QEStringFormatting::INDEX }
User friendly enumerations for arrayAction property - refer to QEStringFormatting::arrayActions for details.

Public Slots

- void [requestEnabled](#) (const bool &state)

Signals

- void [dbValueChanged](#) (const QString &out)
- void [userChange](#) (const QString &oldValue, const QString &newValue, const QString &lastValue)
Internal use only. Used by [QEConfiguredLayout](#) to be notified when one of its widgets has written something.
- void [requestResend](#) ()
Internal use only. Used when changing a property value to force a re-display to reflect the new property value.

Public Member Functions

- bool [isEnabled](#) () const
Access function for 'enabled' property - refer to 'enabled' property for details.
- void [setEnabled](#) (bool state)
Access function for 'enabled' property - refer to 'enabled' property for details.
- [UserLevels](#) [getUserLevelVisibilityProperty](#) ()
Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.
- void [setUserLevelVisibilityProperty](#) ([UserLevels](#) level)
Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.
- [UserLevels](#) [getUserLevelEnabledProperty](#) ()
Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.
- void [setUserLevelEnabledProperty](#) ([UserLevels](#) level)
Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.
- void [setFormatProperty](#) ([Formats](#) format)
Access function for 'format' property - refer to 'format' property for details.
- [Formats](#) [getFormatProperty](#) ()
Access function for 'format' property - refer to 'format' property for details.
- void [setNotationProperty](#) ([Notations](#) notation)
Access function for 'notation' property - refer to 'notation' property for details.
- [Notations](#) [getNotationProperty](#) ()
Access function for 'notation' property - refer to 'notation' property for details.
- void [setArrayActionProperty](#) ([ArrayActions](#) arrayAction)
Access function for 'arrayAction' property - refer to 'arrayAction' property for details.
- [ArrayActions](#) [getArrayActionProperty](#) ()
Access function for 'arrayAction' property - refer to 'arrayAction' property for details.
- [QELineEdit](#) (QWidget *parent=0)
- [QELineEdit](#) (const QString &variableName, QWidget *parent=0)
- void [setWriteOnLoseFocus](#) (bool writeOnLoseFocus)
- bool [getWriteOnLoseFocus](#) ()
- void [setWriteOnEnter](#) (bool writeOnEnter)
- bool [getWriteOnEnter](#) ()
- void [setWriteOnFinish](#) (bool writeOnFinish)
- bool [getWriteOnFinish](#) ()
- void [setConfirmWrite](#) (bool confirmWrite)
- bool [getConfirmWrite](#) ()
- void [setSubscribe](#) (bool subscribe)
- bool [getSubscribe](#) ()

Properties

- QString [variable](#)
- QString [variableSubstitutions](#)
- bool [subscribe](#)
- bool [writeOnLoseFocus](#)
- bool [writeOnEnter](#)
- bool [writeOnFinish](#)
- bool [confirmWrite](#)
- bool [variableAsToolTip](#)
- bool [enabled](#)
- bool [allowDrop](#)
- bool [visible](#)
- unsigned [int](#)
- QString [userLevelUserStyle](#)
- QString [userLevelScientistStyle](#)
- QString [userLevelEngineerStyle](#)
- [UserLevels](#) [userLevelVisibility](#)
- [UserLevels](#) [userLevelEnabled](#)
- int [precision](#)
- bool [useDbPrecision](#)
- bool [leadingZero](#)
- bool [trailingZeros](#)
- bool [addUnits](#)
- QString [localEnumeration](#)
- [Formats](#) [format](#)
- [Notations](#) [notation](#)
- [ArrayActions](#) [arrayAction](#)

9.68.1 Constructor & Destructor Documentation

9.68.1.1 `QLineEdit::QLineEdit (QWidget * parent = 0)`

Create without a variable. Use `setVariableNameProperty()` and `setSubstitutionsProperty()` to define a variable and, optionally, macro substitutions later.

9.68.1.2 `QLineEdit::QLineEdit (const QString & variableName, QWidget * parent = 0)`

Create with a variable. A connection is automatically established. If macro substitutions are required, create without a variable and set the variable and macro substitutions after creation.

9.68.2 Member Function Documentation

9.68.2.1 void QELineEdit::dbValueChanged (const QString & *out*) [signal]

Sent when the widget is updated following a data change Can be used to pass on EPICS data (as presented in this widget) to other widgets. For example a QList widget could log updates from this widget.

9.68.2.2 bool QELineEdit::getConfirmWrite ()

Returns 'true' if this widget will ask for confirmation (using a dialog box) prior to writing data.

9.68.2.3 bool QELineEdit::getSubscribe ()

Returns 'true' if this widget subscribes for data updates and displays current data.

9.68.2.4 bool QELineEdit::getWriteOnEnter ()

Returns 'true' if this widget writes any changes when the user presses 'enter'.

9.68.2.5 bool QELineEdit::getWriteOnFinish ()

Returns 'true' if this widget writes any changes when the user finished editing (the QLineEdit 'editingFinished' signal is emitted).

9.68.2.6 bool QELineEdit::getWriteOnLoseFocus ()

Returns 'true' if this widget automatically writes any changes when it loses focus.

9.68.2.7 void QELineEdit::requestEnabled (const bool & *state*) [inline, slot]

Similar to standard setEnabled slot, but allows QE widget to determine if the widget remains disabled due to invalid data. If disabled due to invalid data, a request to enable the widget will be honoured when the data is no longer invalid.

9.68.2.8 void QELineEdit::setConfirmWrite (bool *confirmWrite*)

Sets if this widget will ask for confirmation (using a dialog box) prior to writing data. Default is 'false' (will not ask for confirmation (using a dialog box) prior to writing data).

9.68.2.9 void QLEdit::setSubscribe (bool *subscribe*)

Sets if this widget subscribes for data updates and displays current data. Default is 'true' (subscribes for and displays data updates)

9.68.2.10 void QLEdit::setWriteOnEnter (bool *writeOnEnter*)

Sets if this widget writes any changes when the user presses 'enter'. Note, the current value will be written even if the user has not changed it. Default is 'true' (writes any changes when the user presses 'enter').

9.68.2.11 void QLEdit::setWriteOnFinish (bool *writeOnFinish*)

Sets if this widget writes any changes when the user finished editing (the QLEdit 'editingFinished' signal is emitted). No writing occurs if no changes were made. Default is 'true' (writes any changes when the QLEdit 'editingFinished' signal is emitted).

9.68.2.12 void QLEdit::setWriteOnLoseFocus (bool *writeOnLoseFocus*)

Sets if this widget automatically writes any changes when it loses focus. Default is 'false' (does not write any changes when it loses focus).

9.68.3 Property Documentation

9.68.3.1 bool QLEdit::addUnits [read, write]

If true (default), add engineering units supplied with the data.

9.68.3.2 bool QLEdit::allowDrop [read, write]

Allow drag/drops operations to this widget. Default is false. Any dropped text will be used as a new variable name.

Reimplemented from [QEDragDrop](#).

9.68.3.3 ArrayActions QLEdit::arrayAction [read, write]

Text formatting option for array data. Default is ASCII. Options are:

- ASCII - treat array as a single text string. For example an array of three characters 'a' 'b' 'c' will be formatted as 'abc'.
- APPEND - treat array as an array of numbers and format a string containing them all with a space between each. For example, an array of three numbers 10, 11 and 12 will be formatted as '10 11 12'.

- INDEX - Extract a single item from the array. The item is then formatted as any other non array data would be. The item selected is determined by the `arrayIndex` property. For example, if `arrayIndex` property is 1, an array of three numbers 10, 11 and 12 will be formatted as '11'.

9.68.3.4 `bool QLEdit::confirmWrite` [read, write]

Sets if this widget will ask for confirmation (using a dialog box) prior to writing data. Default is 'false' (will not ask for confirmation (using a dialog box) prior to writing data).

9.68.3.5 `bool QLEdit::enabled` [read, write]

Set the preferred 'enabled' state. Default is true. This property is copied to the standard Qt 'enabled' property if the data being displayed is valid. If the data being displayed is invalid the standard Qt 'enabled' property will always be set to false to indicate invalid data. The value of this property will only be copied to the standard Qt 'enabled' property once data is valid.

9.68.3.6 `Formats QLEdit::format` [read, write]

Format to apply to data. Default is 'Default' in which case the data type supplied with the data determines how the data is formatted. For all other options, an attempt is made to format the data as requested (whatever its native form).

9.68.3.7 `unsigned QLEdit::int` [read, write]

Set the ID used by the message filtering system. Default is zero. Widgets or applications that use messages from the framework have the option of filtering on this ID. For example, by using a unique message source ID a [QELog](#) widget may be set up to only log messages from a select set of widgets.

Base used for when formatting integers. Default is 10 (duh!)

Index used to select a single item of data for formatting from an array of data. Default is 0. Only used when the `arrayAction` property is INDEX. Refer to the `arrayAction` property for more details.

9.68.3.8 `bool QLEdit::leadingZero` [read, write]

If true (default), always add a leading zero when formatting numbers.

9.68.3.9 `QString QLEdit::localEnumeration` [read, write]

An enumeration list used to data values. Used only when the formatting option is 'local enumeration'. Value is converted to an integer and used to select a string from this list.

9.68.3.10 Notations `QLineEdit::notation` [read, write]

Notation used for numerical formatting. Default is fixed.

9.68.3.11 int `QLineEdit::precision` [read, write]

Precision used when formatting floating point numbers. The default is 4. This is only used if `useDbPrecision` is false.

9.68.3.12 bool `QLineEdit::subscribe` [read, write]

Sets if this widget subscribes for data updates and displays current data. Default is 'true' (subscribes for and displays data updates)

Reimplemented from [QEWidget](#).

9.68.3.13 bool `QLineEdit::trailingZeros` [read, write]

If true (default), always remove any trailing zeros when formatting numbers.

9.68.3.14 bool `QLineEdit::useDbPrecision` [read, write]

If true (default), format floating point numbers using the precision supplied with the data. If false, the precision property is used.

9.68.3.15 UserLevels `QLineEdit::userLevelEnabled` [read, write]

Lowest user level at which the widget is enabled. Default is 'User'. Used when designing GUIs that allow access to more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through `setUserLevel()` Widgets that are always accessible should be visible at 'User'. Widgets that are only accessible to scientists managing the facility should be visible at 'Scientist'. Widgets that are only accessible to engineers maintaining the facility should be visible at 'Engineer'.

9.68.3.16 QString `QLineEdit::userLevelEngineerStyle` [read, write]

Style Sheet string to be applied when the widget is displayed in 'Engineer' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the `styleManager` class. Refer to the `styleManager` class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.68.3.17 QString QLEdit::userLevelScientistStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'Scientist' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.68.3.18 QString QLEdit::userLevelUserStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'User' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.68.3.19 UserLevels QLEdit::userLevelVisibility [read, write]

Lowest user level at which the widget is visible. Default is 'User'. Used when designing GUIs that display more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through setUserLevel() Widgets that are always visible should be visible at 'User'. Widgets that are only used by scientists managing the facility should be visible at 'Scientist'. Widgets that are only used by engineers maintaining the facility should be visible at 'Engineer'.

9.68.3.20 QString QLEdit::variable [read, write]

EPICS variable name (CA PV)

9.68.3.21 bool QLEdit::variableAsToolTip [read, write]

Use the variable as the tool tip. Default is true. Tool tip property will be overwritten by the variable name.

Reimplemented from [QEWidget](#).

9.68.3.22 QString QLEdit::variableSubstitutions [read, write]

Macro substitutions. The default is no substitutions. The format is NAME1=VALUE1[, NAME2=VALUE2... Values may be quoted strings. For example, 'PUMP=PMP3, NAME = "My Pump"' These substitutions are applied to variable names for all QE widgets. In some widgets are also used for other purposes.

9.68.3.23 `bool QLEdit::visible` [read, write]

Display the widget. Default is true. Setting this property false is usefull if widget is only used to provide a signal - for example, when supplying data to a [QELink](#) widget. Note, when false the widget will still be visible in Qt Designer.

9.68.3.24 `bool QLEdit::writeOnEnter` [read, write]

Sets if this widget writes any changes when the user presses 'enter'. Note, the current value will be written even if the user has not changed it. Default is 'true' (writes any changes when the user presses 'enter').

9.68.3.25 `bool QLEdit::writeOnFinish` [read, write]

Sets if this widget writes any changes when the user finished editing (the QLEdit 'editingFinished' signal is emitted). No writing occurs if no changes were made. Default is 'true' (writes any changes when the QLEdit 'editingFinished' signal is emitted).

9.68.3.26 `bool QLEdit::writeOnLoseFocus` [read, write]

Sets if this widget automatically writes any changes when it loses focus. Default is 'false' (does not write any changes when it loses focus).

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QLEdit/QLEdit.h
- /home/rhydera/epicsqt/framework/widgets/QLEdit/QLEdit.cpp

9.69 QLEditManager Class Reference

Public Member Functions


- **QLEditManager** (QObject *parent=0)
- **bool isContainer** () const
- **bool isInitialized** () const
- QIcon **icon** () const
- QString **group** () const
- QString **includeFile** () const
- QString **name** () const
- QString **toolTip** () const
- QString **whatsThis** () const
- QWidget * **createWidget** (QWidget *parent)
- void **initialize** (QDesignerFormEditorInterface *core)

The documentation for this class was generated from the following file:

- /home/rhydera/epicsqt/framework/widgets/QELineEdit/QELineEditManager.h

9.70 QELink Class Reference

Inheritance diagram for QELink:



Public Types

- enum **conditions** {
CONDITION_EQ, **CONDITION_NE**, **CONDITION_GT**, **CONDITION_GE**,
CONDITION_LT, **CONDITION_LE** }
- enum **ConditionNames** {
Equal = QELink::CONDITION_EQ, **NotEqual** = QELink::CONDITION_NE, **GreaterThan**
= QELink::CONDITION_GT, **GreaterThanOrEqual** = QELink::CONDITION_GE,
LessThan = QELink::CONDITION_LT, **LessThanOrEqual** = QELink::CONDITION_
LE }

Public Slots

- void **in** (const bool &in)
- void **in** (const qlonglong &in)
- void **in** (const double &in)
- void **in** (const QString &in)
- void **autoFillBackground** (const bool &enable)

Signals

- void **out** (const bool &out)
- void **out** (const qlonglong &out)
- void **out** (const double &out)
- void **out** (const QString &out)

Public Member Functions

- **QELink** (QWidget *parent=0)
- void **setCondition** (conditions conditionIn)
- conditions **getCondition** ()
- void **setComparisonValue** (QString comparisonValue)
- QString **getComparisonValue** ()
- void **setSignalTrue** (bool signalTrue)
- bool **getSignalTrue** ()
- void **setSignalFalse** (bool signalFalse)
- bool **getSignalFalse** ()
- void **setOutTrueValue** (QString outTrueValue)
- QString **getOutTrueValue** ()
- void **setOutFalseValue** (QString outFalseValue)
- QString **getOutFalseValue** ()
- void **setRunVisible** (bool visibleIn)
- bool **getRunVisible** ()
- void **setConditionProperty** (ConditionNames condition)
- ConditionNames **getConditionProperty** ()

Protected Attributes

- conditions **condition**
- QVariant **comparisonValue**
- bool **signalTrue**
- bool **signalFalse**
- QVariant **outTrueValue**
- QVariant **outFalseValue**
- bool **visible**

Properties


- ConditionNames **condition**
- QString **comparisonValue**
- QString **outTrueValue**
- QString **outFalseValue**
- bool **runVisible**

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QELink/QELink.h
- /home/rhydera/epicsqt/framework/widgets/QELink/QELink.cpp

9.71 QELog Class Reference

Inheritance diagram for QELog:



Public Types

- enum **detailsLayoutProperty** { **Top** = TOP, **Bottom** = BOTTOM, **Left** = LEFT, **Right** = RIGHT }
- enum **MessageFilterOptions** { **Any** = UserMessage::MESSAGE_FILTER_ANY, **Match** = UserMessage::MESSAGE_FILTER_MATCH, **None** = UserMessage::MESSAGE_FILTER_NONE }

Public Member Functions

- **QLog** (QWidget *pParent=0)
- void **setShowColumnTime** (bool pValue)
- bool **getShowColumnTime** ()
- void **setShowColumnType** (bool pValue)
- bool **getShowColumnType** ()
- void **setShowColumnMessage** (bool pValue)
- bool **getShowColumnMessage** ()
- void **setShowMessageFilter** (bool pValue)
- bool **getShowMessageFilter** ()
- void **setShowClear** (bool pValue)
- bool **getShowClear** ()
- void **setShowSave** (bool pValue)
- bool **getShowSave** ()
- void **setDetailsLayout** (int pValue)
- int **getDetailsLayout** ()
- void **setScrollToBottom** (bool pValue)
- bool **getScrollToBottom** ()
- void **setInfoColor** (QColor pValue)
- QColor **getInfoColor** ()
- void **setWarningColor** (QColor pValue)
- QColor **getWarningColor** ()
- void **setErrorColor** (QColor pValue)
- QColor **getErrorColor** ()
- void **clearLog** ()

- void **addLog** (int pType, QString pMessage)
- void **refreshLog** ()
- void **setDetailsLayoutProperty** (detailsLayoutProperty pDetailsLayout)
- detailsLayoutProperty **getDetailsLayoutProperty** ()
- MessageFilterOptions **getMessageFormFilter** ()
- void **setMessageFormFilter** (MessageFilterOptions messageFormFilter)
- MessageFilterOptions **getMessageSourceFilter** ()
- void **setMessageSourceFilter** (MessageFilterOptions messageSourceFilter)

Protected Attributes

- [_QTableWidgetLog](#) * **qTableWidgetLog**
- QCheckBox * **qCheckBoxInfoMessage**
- QCheckBox * **qCheckBoxWarningMessage**
- QCheckBox * **qCheckBoxErrorMessage**
- QPushButton * **qPushButtonClear**
- QPushButton * **qPushButtonSave**
- QColor **qColorInfo**
- QColor **qColorWarning**
- QColor **qColorError**
- bool **scrollToBottom**
- int **detailsLayout**

Properties


- bool **showColumnTime**
- bool **showColumnType**
- bool **showColumnMessage**
- bool **showMessageFilter**
- bool **showClear**
- bool **showSave**
- detailsLayoutProperty **detailsLayout**
- QColor **infoColor**
- QColor **warningColor**
- QColor **errorColor**
- MessageFilterOptions **messageFormFilter**
- MessageFilterOptions **messageSourceFilter**

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QELog/QELog.h
- /home/rhydera/epicsqt/framework/widgets/QELog/QELog.cpp

9.72 QELogin Class Reference

Inheritance diagram for QELogin:



Public Types

- enum **userTypesProperty** { **User** = USERLEVEL_USER, **Scientist** = USERLEVEL_SCIENTIST, **Engineer** = USERLEVEL_ENGINEER }
- enum **detailsLayoutProperty** { **Top** = TOP, **Bottom** = BOTTOM, **Left** = LEFT, **Right** = RIGHT }

Public Member Functions

- **QELogin** (QWidget *pParent=0)
- void **setShowUserType** (bool pValue)
- bool **getShowUserType** ()
- void **setShowLogin** (bool pValue)
- bool **getShowButtonLogin** ()
- void **setShowLogout** (bool pValue)
- bool **getShowButtonLogout** ()
- void **setUserPassword** (QString pValue)
- QString **getUserPassword** ()
- void **setScientistPassword** (QString pValue)
- QString **getScientistPassword** ()
- void **setEngineerPassword** (QString pValue)
- QString **getEngineerPassword** ()
- void **setCurrentUserType** (int pValue)
- int **getCurrentUserType** ()
- void **setDetailsLayout** (int pValue)
- int **getDetailsLayout** ()
- QString **getUserTypeName** (userLevels type)
- void **logoutCurrentUserType** ()
- void **setCurrentUserTypeProperty** (userTypesProperty pUserType)
- userTypesProperty **getCurrentUserTypeProperty** ()
- void **setDetailsLayoutProperty** (detailsLayoutProperty pDetailsLayout)
- detailsLayoutProperty **getDetailsLayoutProperty** ()

Protected Attributes

- `QStack< int > loginHistory`
- `QPushButton * qPushButtonLogin`
- `QPushButton * qPushButtonLogout`
- `QLabel * qLabelUserType`
- `QString userPassword`
- `QString scientistPassword`
- `QString engineerPassword`
- `int currentUserType`
- `int detailsLayout`

Properties


- `bool showUserType`
- `bool showLogin`
- `bool showLogout`
- `userTypesProperty currentUserType`
- `detailsLayoutProperty detailsLayout`

The documentation for this class was generated from the following files:

- `/home/rhydera/epicsqt/framework/widgets/QELogin/QELogin.h`
- `/home/rhydera/epicsqt/framework/widgets/QELogin/QELogin.cpp`

9.73 QEPeiodic Class Reference

Inheritance diagram for QEPeiodic:



Classes

- `struct elementInfoStruct`
- `struct userInfoStructArray`

Public Types

- enum **variableTypes** {
VARIABLE_TYPE_NUMBER, **VARIABLE_TYPE_ATOMIC_WEIGHT**, **VARIABLE_TYPE_MELTING_POINT**, **VARIABLE_TYPE_BOILING_POINT**,
VARIABLE_TYPE_DENSITY, **VARIABLE_TYPE_GROUP**, **VARIABLE_TYPE_IONIZATION_ENERGY**, **VARIABLE_TYPE_USER_VALUE_1**,
VARIABLE_TYPE_USER_VALUE_2 }
- enum **presentationOptions** { **PRESENTATION_BUTTON_AND_LABEL**, **PRESENTATION_BUTTON_ONLY**, **PRESENTATION_LABEL_ONLY** }
- enum **UserLevels** { **User** = USERLEVEL_USER, **Scientist** = USERLEVEL_SCIENTIST, **Engineer** = USERLEVEL_ENGINEER }
User friendly enumerations for userLevelVisibility and userLevelEnabled properties - refer to userLevelVisibility and userLevelEnabled properties and userLevel enumeration for details.
- enum **PresentationOptions** { **buttonAndLabel** = QEPeiodic::PRESENTATION_BUTTON_AND_LABEL, **buttonOnly** = QEPeiodic::PRESENTATION_BUTTON_ONLY, **labelOnly** = QEPeiodic::PRESENTATION_LABEL_ONLY }
- enum **VariableTypes** {
Number = QEPeiodic::VARIABLE_TYPE_NUMBER, **atomicWeight** = QEPeiodic::VARIABLE_TYPE_ATOMIC_WEIGHT, **meltingPoint** = QEPeiodic::VARIABLE_TYPE_MELTING_POINT, **boilingPoint** = QEPeiodic::VARIABLE_TYPE_BOILING_POINT,
density = QEPeiodic::VARIABLE_TYPE_DENSITY, **group** = QEPeiodic::VARIABLE_TYPE_GROUP, **ionizationEnergy** = QEPeiodic::VARIABLE_TYPE_IONIZATION_ENERGY, **userValue1** = QEPeiodic::VARIABLE_TYPE_USER_VALUE_1,
userValue2 = QEPeiodic::VARIABLE_TYPE_USER_VALUE_2 }

Public Slots

- void **requestEnabled** (const bool &state)

Signals

- void **dbValueChanged** (const double &out)
- void **dbElementChanged** (const QString &out)
- void **requestResend** ()
Internal use only. Used when changing a property value to force a re-display to reflect the new property value.

Public Member Functions

- **QEPeiodic** (QWidget *parent=0)
- **QEPeiodic** (const QString &variableName, QWidget *parent=0)
- void **setSubscribe** (bool subscribe)

- bool **getSubscribe** ()
- void **setPresentationOption** (presentationOptions presentationOptionIn)
- presentationOptions **getPresentationOption** ()
- void **setVariableType1** (variableTypes variableType1In)
- variableTypes **getVariableType1** ()
- void **setVariableType2** (variableTypes variableType2In)
- variableTypes **getVariableType2** ()
- void **setVariableTolerance1** (double variableTolerance1In)
- double **getVariableTolerance1** ()
- void **setVariableTolerance2** (double variableTolerance2In)
- double **getVariableTolerance2** ()
- void **setUserInfo** (QString userInfo)
- QString **getUserInfo** ()
- bool **isEnabled** () const
Access function for 'enabled' property - refer to 'enabled' property for details.
- void **setEnabled** (bool state)
Access function for 'enabled' property - refer to 'enabled' property for details.
- [UserLevels](#) **getUserLevelVisibilityProperty** ()
Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.
- void **setUserLevelVisibilityProperty** ([UserLevels](#) level)
Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.
- [UserLevels](#) **getUserLevelEnabledProperty** ()
Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.
- void **setUserLevelEnabledProperty** ([UserLevels](#) level)
Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.
- void **setPresentationOptionProperty** (PresentationOptions presentationOption)
- PresentationOptions **getPresentationOptionProperty** ()
- void **setVariableType1Property** (VariableTypes variableType)
- void **setVariableType2Property** (VariableTypes variableType)
- VariableTypes **getVariableType1Property** ()
- VariableTypes **getVariableType2Property** ()

Public Attributes

- [userInfoStruct](#) **userInfo** [NUM_ELEMENTS]

Static Public Attributes

- static [elementInfoStruct](#) **elementInfo** [NUM_ELEMENTS]

Protected Member Functions

- void **establishConnection** (unsigned int variableIndex)
- void **dragEnterEvent** (QDragEnterEvent *event)
- void **dropEvent** (QDropEvent *event)
- void **setDrop** (QVariant drop)
- QVariant **getDrop** ()

Protected Attributes

- [QEFloatingFormatting](#) **floatingFormatting**
- bool **localEnabled**
- bool [allowDrop](#)
- variableTypes **variableType1**
- variableTypes **variableType2**
- double **variableTolerance1**
- double **variableTolerance2**

Properties

- QString [writeButtonVariable1](#)
- QString [writeButtonVariable2](#)
- QString [readbackLabelVariable1](#)
- QString [readbackLabelVariable2](#)
- QString [variableSubstitutions](#)
- bool [subscribe](#)
- bool [variableAsToolTip](#)
- bool [enabled](#)
- bool [visible](#)
- unsigned int
- QString [userLevelUserStyle](#)
- QString [userLevelScientistStyle](#)
- QString [userLevelEngineerStyle](#)
- [UserLevels](#) [userLevelVisibility](#)
- [UserLevels](#) [userLevelEnabled](#)
- PresentationOptions **presentationOption**
- VariableTypes **variableType1**
- VariableTypes **variableType2**
- QString **userInfo**

9.73.1 Member Function Documentation

9.73.1.1 void QEPeiodic::dbElementChanged (const QString & out) [signal]

Sent when the widget is updated following a data change Can be used to pass on EPICS data (as presented in this widget) to other widgets. For example a QList widget could log updates from this widget.

9.73.1.2 void QEPeiodic::dbValueChanged (const double & out) [signal]

Sent when the widget is updated following a data change Can be used to pass on EPICS data (as presented in this widget) to other widgets. For example a QList widget could log updates from this widget.

9.73.1.3 void QEPeiodic::requestEnabled (const bool & state) [inline, slot]

Similar to standard setEnabled slot, but allows QE widget to determine if the widget remains disabled due to invalid data. If disabled due to invalid data, a request to enable the widget will be honoured when the data is no longer invalid.

9.73.2 Member Data Documentation

9.73.2.1 bool QEPeiodic::allowDrop [read, write, protected]

Allow drag/drops operations to this widget. Default is false. Any dropped text will be used as a new variable name.

Reimplemented from [QEDragDrop](#).

9.73.3 Property Documentation

9.73.3.1 bool QEPeiodic::enabled [read, write]

Set the prefered 'enabled' state. Default is true. This property is copied to the standard Qt 'enabled' property if the data being displayed is valid. If the data being displayed is invalid the standard Qt 'enabled' property will always be set to false to indicate invalid data. The value of this property will only be copied to the standard Qt 'enabled' property once data is valid.

9.73.3.2 unsigned QEPeiodic::int [read, write]

Set the ID used by the message filtering system. Default is zero. Widgets or applications that use messages from the framework have the option of filtering on this ID. For example, by using a unique message source ID a [QELog](#) widget may be set up to only log messages from a select set of widgets.

9.73.3.3 QString QEPeiodic::readbackLabelVariable1 [read, write]

EPICS variable name (CA PV). This variable is used to read the value to the first of two positioners to determine which (if any) element is currently selected.

9.73.3.4 QString QEPeiodic::readbackLabelVariable2 [read, write]

EPICS variable name (CA PV). This variable is used to read the value to the second of two positioners to determine which (if any) element is currently selected.

9.73.3.5 bool QEPeiodic::subscribe [read, write]

Sets if this widget subscribes for data updates and displays current data. Default is 'true' (subscribes for and displays data updates)

Reimplemented from [QEWidget](#).

9.73.3.6 UserLevels QEPeiodic::userLevelEnabled [read, write]

Lowest user level at which the widget is enabled. Default is 'User'. Used when designing GUIs that allow access to more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through setUserLevel() Widgets that are always accessible should be visible at 'User'. Widgets that are only accessible to scientists managing the facility should be visible at 'Scientist'. Widgets that are only accessible to engineers maintaining the facility should be visible at 'Engineer'.

9.73.3.7 QString QEPeiodic::userLevelEngineerStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'Engineer' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.73.3.8 QString QEPeiodic::userLevelScientistStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'Scientist' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.73.3.9 QString QEPeiodic::userLevelUserStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'User' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string

will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.73.3.10 `UserLevels QEP periodic::userLevelVisibility` [read, write]

Lowest user level at which the widget is visible. Default is 'User'. Used when designing GUIs that display more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programmatically through `setUserLevel()`. Widgets that are always visible should be visible at 'User'. Widgets that are only used by scientists managing the facility should be visible at 'Scientist'. Widgets that are only used by engineers maintaining the facility should be visible at 'Engineer'.

9.73.3.11 `bool QEP periodic::variableAsToolTip` [read, write]

Use the variable as the tool tip. Default is true. Tool tip property will be overwritten by the variable name.

Reimplemented from [QEWidget](#).

9.73.3.12 `QString QEP periodic::variableSubstitutions` [read, write]

Macro substitutions. The default is no substitutions. The format is NAME1=VALUE1[, NAME2=VALUE2... Values may be quoted strings. For example, 'SAMPLE=SAM1, NAME = "Ref foil"' These substitutions are applied to all the variable names.

9.73.3.13 `bool QEP periodic::visible` [read, write]

Display the widget. Default is true. Setting this property false is useful if widget is only used to provide a signal - for example, when supplying data to a [QELink](#) widget. Note, when false the widget will still be visible in Qt Designer.

9.73.3.14 `QString QEP periodic::writeButtonVariable1` [read, write]

EPICS variable name (CA PV). This variable is used to write a value to the first of two positioners that will position the select element.

9.73.3.15 `QString QEP periodic::writeButtonVariable2` [read, write]

EPICS variable name (CA PV). This variable is used to write a value to the second of two positioners that will position the select element.

The documentation for this class was generated from the following files:

- `/home/rhydera/epicsqt/framework/widgets/QEP periodic/QEP periodic.h`
- `/home/rhydera/epicsqt/framework/widgets/QEP periodic/QEP periodic.cpp`

9.74 QEPeriodicComponentData Class Reference

Public Attributes

- unsigned int **variableIndex1**
- double **lastData1**
- bool **haveLastData1**
- unsigned int **variableIndex2**
- double **lastData2**
- bool **haveLastData2**

The documentation for this class was generated from the following file:

- /home/rhydera/epicsqt/framework/widgets/QEPeriodic/QEPeriodic.h

9.75 QEPeriodicTaskMenu Class Reference

Public Member Functions

- **QEPeriodicTaskMenu** ([QEPeriodic](#) *periodic, QObject *parent)
- QAction * **preferredEditAction** () const
- QList< QAction * > **taskActions** () const

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEPeriodic/QEPeriodicTaskMenu.h
- /home/rhydera/epicsqt/framework/widgets/QEPeriodic/QEPeriodicTaskMenuExtension.cpp

9.76 QEPeriodicTaskMenuFactory Class Reference

Public Member Functions

- **QEPeriodicTaskMenuFactory** (QExtensionManager *parent=0)

Protected Member Functions

- QObject * **createExtension** (QObject *object, const QString &iid, QObject *parent)
const

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEPeriodic/QEPeriodicTaskMenu.h
- /home/rhydera/epicsqt/framework/widgets/QEPeriodic/QEPeriodicTaskMenuExtension.cpp

9.77 QEpicsPV Class Reference

Public Slots

- const QVariant & **set** (QVariant value, int delay=-1)
- void **setPV** (const QString &_pvName="")

Signals

- void **connectionChanged** (bool connected)
- void **connected** ()
- void **disconnected** ()
- void **valueChanged** (const QVariant &value)
- void **valueUpdated** (const QVariant &value)
- void **valueInitd** (const QVariant &value)

Public Member Functions

- **QEpicsPV** (const QString &_pvName, QObject *parent=0)
- **QEpicsPV** (QObject *parent=0)
- const QVariant & **get** () const
- void **needUpdated** () const
- const QVariant & **getUpdated** (int delay=defaultDelay) const
- bool **isConnected** () const
- const QStringList & **getEnum** () const
- const QString & **pv** () const
- const QVariant & **getReady** (int delay=defaultDelay) const

Static Public Member Functions


- static void **setDebugLevel** (unsigned level=0)
- static QVariant **get** (const QString &_pvName, int delay=defaultDelay)
- static QVariant **set** (QString &_pvName, const QVariant &value, int delay=-1)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/data/include/qepicspv.h
- /home/rhydera/epicsqt/framework/data/src/qepicspv.cpp

9.78 QEPlot Class Reference

Inheritance diagram for QEPlot:



Public Types

- enum **UserLevels** { **User** = USERLEVEL_USER, **Scientist** = USERLEVEL_SCIENTIST, **Engineer** = USERLEVEL_ENGINEER }
User friendly enumerations for userLevelVisibility and userLevelEnabled properties - refer to userLevelVisibility and userLevelEnabled properties and userLevel enumeration for details.
- enum **TraceStyles** { **Lines** = QwtPlotCurve::Lines, **Sticks** = QwtPlotCurve::Sticks, **Steps** = QwtPlotCurve::Steps, **Dots** = QwtPlotCurve::Dots }

Public Slots

- void **requestEnabled** (const bool &state)

Signals

- void **dbValueChanged** (const double &out)
- void **dbValueChanged** (const QVector< double > &out)

Public Member Functions

- QEPlot** (QWidget *parent=0)
- QEPlot** (const QString &variableName, QWidget *parent=0)
- void **setYMin** (double yMin)
- double **getYMin** ()
- void **setYMax** (double yMax)
- double **getYMax** ()
- void **setAutoScale** (bool autoScale)
- bool **getAutoScale** ()
- void **setAxisEnableX** (bool axisEnableXIn)
- bool **getAxisEnableX** ()
- void **setAxisEnableY** (bool axisEnableYIn)
- bool **getAxisEnableY** ()

- QString **getTitle** ()
- void **setBackgroundColor** (QColor backgroundColor)
- QColor **getBackgroundColor** ()
- void **setTraceStyle** (QwtPlotCurve::CurveStyle traceStyle, const unsigned int variableIndex)
- QwtPlotCurve::CurveStyle **getTraceStyle** (const unsigned int variableIndex)
- void **setTraceColor** (QColor traceColor, const unsigned int variableIndex)
- void **setTraceColor1** (QColor traceColor)
- void **setTraceColor2** (QColor traceColor)
- void **setTraceColor3** (QColor traceColor)
- void **setTraceColor4** (QColor traceColor)
- QColor **getTraceColor** (const unsigned int variableIndex)
- QColor **getTraceColor1** ()
- QColor **getTraceColor2** ()
- QColor **getTraceColor3** ()
- QColor **getTraceColor4** ()
- void **setTraceLegend1** (QString traceLegend)
- void **setTraceLegend2** (QString traceLegend)
- void **setTraceLegend3** (QString traceLegend)
- void **setTraceLegend4** (QString traceLegend)
- QString **getTraceLegend1** ()
- QString **getTraceLegend2** ()
- QString **getTraceLegend3** ()
- QString **getTraceLegend4** ()
- void **setXUnit** (QString xUnit)
- QString **getXUnit** ()
- void **setYUnit** (QString yUnit)
- QString **getYUnit** ()
- void **setGridEnableMajorX** (bool gridEnableMajorXIn)
- void **setGridEnableMajorY** (bool gridEnableMajorYIn)
- void **setGridEnableMinorX** (bool gridEnableMinorXIn)
- void **setGridEnableMinorY** (bool gridEnableMinorYIn)
- bool **getGridEnableMajorX** ()
- bool **getGridEnableMajorY** ()
- bool **getGridEnableMinorX** ()
- bool **getGridEnableMinorY** ()
- void **setGridMajorColor** (QColor gridMajorColorIn)
- void **setGridMinorColor** (QColor gridMinorColorIn)
- QColor **getGridMajorColor** ()
- QColor **getGridMinorColor** ()
- void **setXStart** (double xStart)
- double **getXStart** ()
- void **setXIncrement** (double xIncrement)
- double **getXIncrement** ()
- void **setTimeSpan** (unsigned int timeSpan)
- unsigned int **getTimeSpan** ()

- void **setTickRate** (unsigned int tickRate)
- unsigned int **getTickRate** ()
- bool **isEnabled** () const
Access function for 'enabled' property - refer to 'enabled' property for details.
- void **setEnabled** (bool state)
Access function for 'enabled' property - refer to 'enabled' property for details.
- [UserLevels](#) **getUserLevelVisibilityProperty** ()
Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.
- void **setUserLevelVisibilityProperty** ([UserLevels](#) level)
Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.
- [UserLevels](#) **getUserLevelEnabledProperty** ()
Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.
- void **setUserLevelEnabledProperty** ([UserLevels](#) level)
Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.
- void **setTraceStyle1** (TraceStyles traceStyle)
- void **setTraceStyle2** (TraceStyles traceStyle)
- void **setTraceStyle3** (TraceStyles traceStyle)
- void **setTraceStyle4** (TraceStyles traceStyle)
- TraceStyles **getTraceStyle1** ()
- TraceStyles **getTraceStyle2** ()
- TraceStyles **getTraceStyle3** ()
- TraceStyles **getTraceStyle4** ()

Protected Member Functions

- void **establishConnection** (unsigned int variableIndex)
- void **dragEnterEvent** (QDragEnterEvent *event)
- void **dropEvent** (QDropEvent *event)
- void **mousePressEvent** (QMouseEvent *event)
- void **setDrop** (QVariant drop)
- QVariant **getDrop** ()

Protected Attributes

- [QEFloatingFormatting](#) **floatingFormatting**
- bool **localEnabled**
- bool [allowDrop](#)

Properties

- QString [variable1](#)
- QString [variable2](#)
- QString [variable3](#)
- QString [variable4](#)
- QString [variableSubstitutions](#)
- bool [variableAsToolTip](#)
- bool [enabled](#)
- bool [visible](#)
- unsigned [int](#)
- QString [userLevelUserStyle](#)
- QString [userLevelScientistStyle](#)
- QString [userLevelEngineerStyle](#)
- [UserLevels](#) [userLevelVisibility](#)
- [UserLevels](#) [userLevelEnabled](#)
- QColor **traceColor1**
- QColor **traceColor2**
- QColor **traceColor3**
- QColor **traceColor4**
- TraceStyles **traceStyle1**
- TraceStyles **traceStyle2**
- TraceStyles **traceStyle3**
- TraceStyles **traceStyle4**
- QString **traceLegend1**
- QString **traceLegend2**
- QString **traceLegend3**
- QString **traceLegend4**
- QString **title**
- QColor **backgroundColor**
- QString **xUnit**
- QString **yUnit**

9.78.1 Member Function Documentation

9.78.1.1 void QEPlot::dbValueChanged (const double & *out*) [signal]

Sent when the widget is updated following a data change Can be used to pass on EPICS data (as presented in this widget) to other widgets. For example a QList widget could log updates from this widget.

9.78.1.2 void QEPlot::dbValueChanged (const QVector< double > & *out*) [signal]

Sent when the widget is updated following a data change Can be used to pass on EPICS data (as presented in this widget) to other widgets. For example a QList widget could log updates from this widget.

9.78.1.3 void QEPlot::requestEnabled (const bool & state) [inline, slot]

Similar to standard setEnabled slot, but allows QE widget to determine if the widget remains disabled due to invalid data. If disabled due to invalid data, a request to enable the widget will be honoured when the data is no longer invalid.

9.78.2 Member Data Documentation

9.78.2.1 bool QEPlot::allowDrop [read, write, protected]

Allow drag/drops operations to this widget. Default is false. Any dropped text will be used as a new variable name.

Reimplemented from [QEDragDrop](#).

9.78.3 Property Documentation

9.78.3.1 bool QEPlot::enabled [read, write]

Set the preferred 'enabled' state. Default is true. This property is copied to the standard Qt 'enabled' property if the data being displayed is valid. If the data being displayed is invalid the standard Qt 'enabled' property will always be set to false to indicate invalid data. The value of this property will only be copied to the standard Qt 'enabled' property once data is valid.

9.78.3.2 unsigned QEPlot::int [read, write]

Set the ID used by the message filtering system. Default is zero. Widgets or applications that use messages from the framework have the option of filtering on this ID. For example, by using a unique message source ID a [QELog](#) widget may be set up to only log messages from a select set of widgets.

9.78.3.3 UserLevels QEPlot::userLevelEnabled [read, write]

Lowest user level at which the widget is enabled. Default is 'User'. Used when designing GUIs that allow access to more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through setUserLevel(). Widgets that are always accessible should be visible at 'User'. Widgets that are only accessible to scientists managing the facility should be visible at 'Scientist'. Widgets that are only accessible to engineers maintaining the facility should be visible at 'Engineer'.

9.78.3.4 QString QEPlot::userLevelEngineerStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'Engineer' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example,

'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.78.3.5 QString QEPlot::userLevelScientistStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'Scientist' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.78.3.6 QString QEPlot::userLevelUserStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'User' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.78.3.7 UserLevels QEPlot::userLevelVisibility [read, write]

Lowest user level at which the widget is visible. Default is 'User'. Used when designing GUIs that display more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through setUserLevel() Widgets that are always visible should be visible at 'User'. Widgets that are only used by scientists managing the facility should be visible at 'Scientist'. Widgets that are only used by engineers maintaining the facility should be visible at 'Engineer'.

9.78.3.8 QString QEPlot::variable1 [read, write]

EPICS variable name (CA PV). This variable is used to read updating values or waveforms for plotting in the first trace.

9.78.3.9 QString QEPlot::variable2 [read, write]

EPICS variable name (CA PV). This variable is used to read updating values or waveforms for plotting in the second trace.

9.78.3.10 QString QEPlot::variable3 [read, write]

EPICS variable name (CA PV). This variable is used to read updating values or waveforms for plotting in the third trace.

9.78.3.11 QString QEPlot::variable4 [read, write]

EPICS variable name (CA PV). This variable is used to read updating values or waveforms for plotting in the fourth trace.

9.78.3.12 bool QEPlot::variableAsToolTip [read, write]

Use the variable as the tool tip. Default is true. Tool tip property will be overwritten by the variable name.

Reimplemented from [QEWidget](#).

9.78.3.13 QString QEPlot::variableSubstitutions [read, write]

Macro substitutions. The default is no substitutions. The format is NAME1=VALUE1[, NAME2=VALUE2... Values may be quoted strings. For example, 'SAMPLE=SAM1, NAME = "Ref foil"' These substitutions are applied to all the variable names.

9.78.3.14 bool QEPlot::visible [read, write]


Display the widget. Default is true. Setting this property false is usefull if widget is only used to provide a signal - for example, when supplying data to a [QELink](#) widget. Note, when false the widget will still be visible in Qt Designer.

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEPlot/QEPlot.h
- /home/rhydera/epicsqt/framework/widgets/QEPlot/QEPlot.cpp

9.79 QEPushButton Class Reference

Inheritance diagram for QEPushButton:



Public Types

- enum **UserLevels** { **User** = USERLEVEL_USER, **Scientist** = USERLEVEL_SCIENTIST, **Engineer** = USERLEVEL_ENGINEER }
User friendly enumerations for userLevelVisibility and userLevelEnabled properties - refer to userLevelVisibility and userLevelEnabled properties and userLevel enumeration for details.
- enum **UpdateOptions** { **Text** = QEPushButton::UPDATE_TEXT, **Icon** = QEPushButton::UPDATE_ICON, **TextAndIcon** = QEPushButton::UPDATE_TEXT_AND_ICON, **State** = QEPushButton::UPDATE_STATE }
- enum **Formats** {
Default = QQStringFormatting::FORMAT_DEFAULT, **Floating** = QQStringFormatting::FORMAT_FLOATING, **Integer** = QQStringFormatting::FORMAT_INTEGER, **UnsignedInteger** = QQStringFormatting::FORMAT_UNSIGNEDINTEGER,
Time = QQStringFormatting::FORMAT_TIME, **LocalEnumeration** = QQStringFormatting::FORMAT_LOCAL_ENUMERATE }
- enum **Notations** { **Fixed** = QQStringFormatting::NOTATION_FIXED, **Scientific** = QQStringFormatting::NOTATION_SCIENTIFIC, **Automatic** = QQStringFormatting::NOTATION_AUTOMATIC }
- enum **CreationOptionNames** { **Open** = QEForm::CREATION_OPTION_OPEN, **NewTab** = QEForm::CREATION_OPTION_NEW_TAB, **NewWindow** = QEForm::CREATION_OPTION_NEW_WINDOW }

Public Slots

- void **launchGui** (QString guiName, QEForm::creationOptions creationOption)
- void **onGeneralMessage** (QString message)
- void **requestEnabled** (const bool &state)

Signals

- void **dbValueChanged** (const QString &out)
- void **requestResend** ()
Internal use only. Used when changing a property value to force a re-display to reflect the new property value.
- void **newGui** (QString guiName, QEForm::creationOptions creationOption)
Internal use only. Request a new GUI is created. Typically, this is caught by the QEGui application.

Public Member Functions

- **QEPushButton** (QWidget *parent=0)
- **QEPushButton** (const QString &variableName, QWidget *parent=0)
- bool **isEnabled** () const
Access function for 'enabled' property - refer to 'enabled' property for details.

- void **setEnabled** (bool state)
Access function for 'enabled' property - refer to 'enabled' property for details.
- **UserLevels** **getUserLevelVisibilityProperty** ()
Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.
- void **setUserLevelVisibilityProperty** (**UserLevels** level)
Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.
- **UserLevels** **getUserLevelEnabledProperty** ()
Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.
- void **setUserLevelEnabledProperty** (**UserLevels** level)
Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.
- void **setUpdateOptionProperty** (UpdateOptions updateOption)
- UpdateOptions **getUpdateOptionProperty** ()
- void **setPixmap0Property** (QPixmap pixmap)
- void **setPixmap1Property** (QPixmap pixmap)
- void **setPixmap2Property** (QPixmap pixmap)
- void **setPixmap3Property** (QPixmap pixmap)
- void **setPixmap4Property** (QPixmap pixmap)
- void **setPixmap5Property** (QPixmap pixmap)
- void **setPixmap6Property** (QPixmap pixmap)
- void **setPixmap7Property** (QPixmap pixmap)
- QPixmap **getPixmap0Property** ()
- QPixmap **getPixmap1Property** ()
- QPixmap **getPixmap2Property** ()
- QPixmap **getPixmap3Property** ()
- QPixmap **getPixmap4Property** ()
- QPixmap **getPixmap5Property** ()
- QPixmap **getPixmap6Property** ()
- QPixmap **getPixmap7Property** ()
- void **setFormatProperty** (Formats format)
- Formats **getFormatProperty** ()
- void **setNotationProperty** (Notations notation)
- Notations **getNotationProperty** ()
- void **setCreationOptionProperty** (CreationOptionNames creationOptionIn)
- CreationOptionNames **getCreationOptionProperty** ()

Protected Member Functions

- void **dragEnterEvent** (QDragEnterEvent *event)
- void **dropEvent** (QDropEvent *event)
- void **setDrop** (QVariant drop)
- QVariant **getDrop** ()

Properties

- QString [variable](#)
- QString [altReadbackVariable](#)
- QString **variableSubstitutions**
- bool [subscribe](#)
- bool [variableAsToolTip](#)
- bool [enabled](#)
- bool [allowDrop](#)
- bool [visible](#)
- unsigned [int](#)
- QString [userLevelUserStyle](#)
- QString [userLevelScientistStyle](#)
- QString [userLevelEngineerStyle](#)
- [UserLevels](#) [userLevelVisibility](#)
- [UserLevels](#) [userLevelEnabled](#)
- UpdateOptions **updateOption**
- QPixmap **pixmap0**
- QPixmap **pixmap1**
- QPixmap **pixmap2**
- QPixmap **pixmap3**
- QPixmap **pixmap4**
- QPixmap **pixmap5**
- QPixmap **pixmap6**
- QPixmap **pixmap7**
- bool **useDbPrecision**
- bool **leadingZero**
- bool **trailingZeros**
- bool **addUnits**
- QString **localEnumeration**
- Qt::Alignment **alignment**
- Formats **format**
- Notations **notation**
- QString **password**
- bool **writeOnPress**
- bool **writeOnRelease**
- bool **writeOnClick**
- QString **pressText**
- QString **releaseText**
- QString **clickText**
- QString **clickCheckedText**
- QString **labelText**
- QString **program**
- QStringList **arguments**
- QString **guiFile**
- CreationOptionNames **creationOption**

9.79.1 Member Function Documentation

9.79.1.1 void QEPushButton::dbValueChanged (const QString & *out*) [signal]

Sent when the widget is updated following a data change Can be used to pass on EPICS data (as presented in this widget) to other widgets. For example a QList widget could log updates from this widget.

9.79.1.2 void QEPushButton::requestEnabled (const bool & *state*) [inline, slot]

Similar to standard setEnabled slot, but allows QE widget to determine if the widget remains disabled due to invalid data. If disabled due to invalid data, a request to enable the widget will be honoured when the data is no longer invalid.

9.79.2 Property Documentation

9.79.2.1 bool QEPushButton::allowDrop [read, write]

Allow drag/drops operations to this widget. Default is false. Any dropped text will be used as a new variable name.

Reimplemented from [QEDragDrop](#).

9.79.2.2 QString QEPushButton::altReadbackVariable [read, write]

EPICS variable name (CA PV). This variable is used to provide a readback value when different to the variable written to by a button press.

9.79.2.3 bool QEPushButton::enabled [read, write]

Set the preferred 'enabled' state. Default is true. This property is copied to the standard Qt 'enabled' property if the data being displayed is valid. If the data being displayed is invalid the standard Qt 'enabled' property will always be set to false to indicate invalid data. The value of this property will only be copied to the standard Qt 'enabled' property once data is valid.

9.79.2.4 unsigned QEPushButton::int [read, write]

Set the ID used by the message filtering system. Default is zero. Widgets or applications that use messages from the framework have the option of filtering on this ID. For example, by using a unique message source ID a [QELog](#) widget may be set up to only log messages from a select set of widgets.

9.79.2.5 `bool QEPushButton::subscribe` [read, write]

Sets if this widget subscribes for data updates and displays current data. Default is 'true' (subscribes for and displays data updates)

Reimplemented from [QWidget](#).

9.79.2.6 `UserLevels QEPushButton::userLevelEnabled` [read, write]

Lowest user level at which the widget is enabled. Default is 'User'. Used when designing GUIs that allow access to more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through `setUserLevel()`. Widgets that are always accessible should be visible at 'User'. Widgets that are only accessible to scientists managing the facility should be visible at 'Scientist'. Widgets that are only accessible to engineers maintaining the facility should be visible at 'Engineer'.

9.79.2.7 `QString QEPushButton::userLevelEngineerStyle` [read, write]

Style Sheet string to be applied when the widget is displayed in 'Engineer' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.79.2.8 `QString QEPushButton::userLevelScientistStyle` [read, write]

Style Sheet string to be applied when the widget is displayed in 'Scientist' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.79.2.9 `QString QEPushButton::userLevelUserStyle` [read, write]

Style Sheet string to be applied when the widget is displayed in 'User' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.79.2.10 UserLevels QEPushButton::userLevelVisibility [read, write]

Lowest user level at which the widget is visible. Default is 'User'. Used when designing GUIs that display more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through setUserLevel(). Widgets that are always visible should be visible at 'User'. Widgets that are only used by scientists managing the facility should be visible at 'Scientist'. Widgets that are only used by engineers maintaining the facility should be visible at 'Engineer'.

9.79.2.11 QString QEPushButton::variable [read, write]

EPICS variable name (CA PV). This variable is used for both writing (on button press), and reading if subscribed and no alternate readback variable is provided.

9.79.2.12 bool QEPushButton::variableAsToolTip [read, write]

Use the variable as the tool tip. Default is true. Tool tip property will be overwritten by the variable name.

Reimplemented from [QEWidget](#).

9.79.2.13 bool QEPushButton::visible [read, write]


Display the widget. Default is true. Setting this property false is usefull if widget is only used to provide a signal - for example, when supplying data to a [QELink](#) widget. Note, when false the widget will still be visible in Qt Designer.

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEButton/QEPushButton.h
- /home/rhydera/epicsqt/framework/widgets/QEButton/QEPushButton.cpp

9.80 QEPvProperties Class Reference

Inheritance diagram for QEPvProperties:



Classes

- struct **WidgetHolder**

Public Types

- enum [UserLevels](#) { **User** = USERLEVEL_USER, **Scientist** = USERLEVEL_SCIENTIST, **Engineer** = USERLEVEL_ENGINEER }

User friendly enumerations for userLevelVisibility and userLevelEnabled properties - refer to userLevelVisibility and userLevelEnabled properties and userLevel enumeration for details.

Public Slots

- void [requestEnabled](#) (const bool &state)

Signals

- void **setCurrentBoxIndex** (int index)

Public Member Functions

- bool [isEnabled](#) () const
Access function for 'enabled' property - refer to 'enabled' property for details.
- void [setEnabled](#) (bool state)
Access function for 'enabled' property - refer to 'enabled' property for details.
- [UserLevels](#) [getUserLevelVisibilityProperty](#) ()
Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.
- void [setUserLevelVisibilityProperty](#) ([UserLevels](#) level)
Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.
- [UserLevels](#) [getUserLevelEnabledProperty](#) ()
Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.
- void [setUserLevelEnabledProperty](#) ([UserLevels](#) level)
Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.
- **QEPvProperties** (QWidget *parent=0)
- **QEPvProperties** (const QString &variableName, QWidget *parent=0)
- QSize **sizeHint** () const
- void **establishConnection** (unsigned int variableIndex)
- void **updateToolTip** (const QString &tip)

Protected Member Functions

- void **setup** ()
- [qcaobject::QCaObject](#) * **createQcalItem** (unsigned int variableIndex)
- void **dragEnterEvent** (QDragEnterEvent *event)
- void **dropEvent** (QDropEvent *event)
- void **mousePressEvent** (QMouseEvent *event)
- QString **copyVariable** ()
- QVariant **copyData** ()
- void **paste** (QVariant s)
- void **setDrop** (QVariant drop)
- QVariant **getDrop** ()

Properties

- QString [variable](#)
- QString [variableSubstitutions](#)
- bool [variableAsToolTip](#)
- bool [enabled](#)
- bool [allowDrop](#)
- bool [visible](#)
- unsigned [int](#)
- QString [userLevelUserStyle](#)
- QString [userLevelScientistStyle](#)
- QString [userLevelEngineerStyle](#)
- [UserLevels](#) [userLevelVisibility](#)
- [UserLevels](#) [userLevelEnabled](#)

9.80.1 Member Function Documentation

9.80.1.1 void QEPvProperties::requestEnabled (const bool & *state*) [inline, slot]

Similar to standard setEnabled slot, but allows QE widget to determine if the widget remains disabled due to invalid data. If disabled due to invalid data, a request to enable the widget will be honoured when the data is no longer invalid.

9.80.2 Property Documentation

9.80.2.1 bool QEPvProperties::allowDrop [read, write]

Allow drag/drops operations to this widget. Default is false. Any dropped text will be used as a new variable name.

Reimplemented from [QEDragDrop](#).

9.80.2.2 `bool QEPvProperties::enabled` [read, write]

Set the preferred 'enabled' state. Default is true. This property is copied to the standard Qt 'enabled' property if the data being displayed is valid. If the data being displayed is invalid the standard Qt 'enabled' property will always be set to false to indicate invalid data. The value of this property will only be copied to the standard Qt 'enabled' property once data is valid.

9.80.2.3 `unsigned QEPvProperties::int` [read, write]

Set the ID used by the message filtering system. Default is zero. Widgets or applications that use messages from the framework have the option of filtering on this ID. For example, by using a unique message source ID a [QELog](#) widget may be set up to only log messages from a select set of widgets.

9.80.2.4 `UserLevels QEPvProperties::userLevelEnabled` [read, write]

Lowest user level at which the widget is enabled. Default is 'User'. Used when designing GUIs that allow access to more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through `setUserLevel()`. Widgets that are always accessible should be visible at 'User'. Widgets that are only accessible to scientists managing the facility should be visible at 'Scientist'. Widgets that are only accessible to engineers maintaining the facility should be visible at 'Engineer'.

9.80.2.5 `QString QEPvProperties::userLevelEngineerStyle` [read, write]

Style Sheet string to be applied when the widget is displayed in 'Engineer' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.80.2.6 `QString QEPvProperties::userLevelScientistStyle` [read, write]

Style Sheet string to be applied when the widget is displayed in 'Scientist' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.80.2.7 QString QEPvProperties::userLevelUserStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'User' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.80.2.8 UserLevels QEPvProperties::userLevelVisibility [read, write]

Lowest user level at which the widget is visible. Default is 'User'. Used when designing GUIs that display more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through setUserLevel() Widgets that are always visible should be visible at 'User'. Widgets that are only used by scientists managing the facility should be visible at 'Scientist'. Widgets that are only used by engineers maintaining the facility should be visible at 'Engineer'.

9.80.2.9 QString QEPvProperties::variable [read, write]

EPICS variable name (CA PV)

9.80.2.10 bool QEPvProperties::variableAsToolTip [read, write]

Use the variable as the tool tip. Default is true. Tool tip property will be overwritten by the variable name.

Reimplemented from [QEWidget](#).

9.80.2.11 QString QEPvProperties::variableSubstitutions [read, write]

Macro substitutions. The default is no substitutions. The format is NAME1=VALUE1[, NAME2=VALUE2... Values may be quoted strings. For example, 'PUMP=PMP3, NAME = "My Pump"' These substitutions are applied to variable names for all QE widgets. In some widgets are also used for other purposes.

9.80.2.12 bool QEPvProperties::visible [read, write]

Display the widget. Default is true. Setting this property false is usefull if widget is only used to provide a signal - for example, when supplying data to a [QELink](#) widget. Note, when false the widget will still be visible in Qt Designer.

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEPvProperties/QEPvProperties.h
- /home/rhydera/epicsqt/framework/widgets/QEPvProperties/QEPvProperties.cpp

9.81 QEPvPropertiesManager Class Reference

Public Member Functions


- **QEPvPropertiesManager** (QObject *parent=0)
- bool **isContainer** () const
- bool **isInitialized** () const
- QIcon **icon** () const
- QString **group** () const
- QString **includeFile** () const
- QString **name** () const
- QString **toolTip** () const
- QString **whatsThis** () const
- QWidget * **createWidget** (QWidget *parent)
- void **initialize** (QDesignerFormEditorInterface *core)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEPvProperties/QEPvPropertiesManager.h
- /home/rhydera/epicsqt/framework/widgets/QEPvProperties/QEPvPropertiesManager.cpp

9.82 QERadioButton Class Reference

Inheritance diagram for QERadioButton:



Public Types

- enum **UserLevels** { **User** = USERLEVEL_USER, **Scientist** = USERLEVEL_SCIENTIST, **Engineer** = USERLEVEL_ENGINEER }
- User friendly enumerations for userLevelVisibility and userLevelEnabled properties - refer to userLevelVisibility and userLevelEnabled properties and userLevel enumeration for details.*
- enum **UpdateOptions** { **Text** = QERadioButton::UPDATE_TEXT, **Icon** = QERadioButton::UPDATE_ICON, **TextAndIcon** = QERadioButton::UPDATE_TEXT_AND_ICON, **State** = QERadioButton::UPDATE_STATE }

- enum **Formats** {
Default = QStringFormatting::FORMAT_DEFAULT, **Floating** = QStringFormatting::FORMAT_FLOATING, **Integer** = QStringFormatting::FORMAT_INTEGER, **UnsignedInteger** = QStringFormatting::FORMAT_UNSIGNEDINTEGER,
Time = QStringFormatting::FORMAT_TIME }
- enum **Notations** { **Fixed** = QStringFormatting::NOTATION_FIXED, **Scientific** = QStringFormatting::NOTATION_SCIENTIFIC, **Automatic** = QStringFormatting::NOTATION_AUTOMATIC }
- enum **CreationOptionNames** { **Open** = QForm::CREATION_OPTION_OPEN, **NewTab** = QForm::CREATION_OPTION_NEW_TAB, **NewWindow** = QForm::CREATION_OPTION_NEW_WINDOW }

Public Slots

- void **launchGui** (QString guiName, QForm::creationOptions creationOption)
- void **onGeneralMessage** (QString message)
- void **requestEnabled** (const bool &state)

Signals

- void **dbValueChanged** (const QString &out)
- void **requestResend** ()
Internal use only. Used when changing a property value to force a re-display to reflect the new property value.
- void **newGui** (QString guiName, QForm::creationOptions creationOption)
Internal use only. Request a new GUI is created. Typically, this is caught by the QEGui application.

Public Member Functions

- **QERadioButton** (QWidget *parent=0)
- **QERadioButton** (const QString &variableName, QWidget *parent=0)
- bool **isEnabled** () const
Access function for 'enabled' property - refer to 'enabled' property for details.
- void **setEnabled** (bool state)
Access function for 'enabled' property - refer to 'enabled' property for details.
- **UserLevels getUserLevelVisibilityProperty** ()
Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.
- void **setUserLevelVisibilityProperty** (**UserLevels** level)
Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.
- **UserLevels getUserLevelEnabledProperty** ()
Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.

- void **setUserLevelEnabledProperty** (UserLevels level)
Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.
- void **setUpdateOptionProperty** (UpdateOptions updateOption)
- UpdateOptions **getUpdateOptionProperty** ()
- void **setPixmap0Property** (QPixmap pixmap)
- void **setPixmap1Property** (QPixmap pixmap)
- void **setPixmap2Property** (QPixmap pixmap)
- void **setPixmap3Property** (QPixmap pixmap)
- void **setPixmap4Property** (QPixmap pixmap)
- void **setPixmap5Property** (QPixmap pixmap)
- void **setPixmap6Property** (QPixmap pixmap)
- void **setPixmap7Property** (QPixmap pixmap)
- QPixmap **getPixmap0Property** ()
- QPixmap **getPixmap1Property** ()
- QPixmap **getPixmap2Property** ()
- QPixmap **getPixmap3Property** ()
- QPixmap **getPixmap4Property** ()
- QPixmap **getPixmap5Property** ()
- QPixmap **getPixmap6Property** ()
- QPixmap **getPixmap7Property** ()
- void **setFormatProperty** (Formats format)
- Formats **getFormatProperty** ()
- void **setNotationProperty** (Notations notation)
- Notations **getNotationProperty** ()
- void **setCreationOptionProperty** (CreationOptionNames creationOptionIn)
- CreationOptionNames **getCreationOptionProperty** ()

Protected Member Functions

- void **dragEnterEvent** (QDragEnterEvent *event)
- void **dropEvent** (QDropEvent *event)
- void **setDrop** (QVariant drop)
- QVariant **getDrop** ()

Properties

- QString **variable**
- QString **variableSubstitutions**
- bool **subscribe**
- bool **variableAsToolTip**
- bool **enabled**
- bool **allowDrop**
- bool **visible**
- unsigned **int**

- QString [userLevelUserStyle](#)
- QString [userLevelScientistStyle](#)
- QString [userLevelEngineerStyle](#)
- [UserLevels](#) [userLevelVisibility](#)
- [UserLevels](#) [userLevelEnabled](#)
- UpdateOptions **updateOption**
- QPixmap **pixmap0**
- QPixmap **pixmap1**
- QPixmap **pixmap2**
- QPixmap **pixmap3**
- QPixmap **pixmap4**
- QPixmap **pixmap5**
- QPixmap **pixmap6**
- QPixmap **pixmap7**
- bool **useDbPrecision**
- bool **leadingZero**
- bool **trailingZeros**
- bool **addUnits**
- Qt::Alignment **alignment**
- Formats **format**
- Notations **notation**
- QString **password**
- bool **writeOnPress**
- bool **writeOnRelease**
- bool **writeOnClick**
- QString **pressText**
- QString **releaseText**
- QString **clickText**
- QString **clickCheckedText**
- QString **labelText**
- QString **program**
- QStringList **arguments**
- QString **guiFile**
- CreationOptionNames **creationOption**

9.82.1 Member Function Documentation

9.82.1.1 void QERadioButton::dbValueChanged (const QString & *out*) [signal]

Sent when the widget is updated following a data change Can be used to pass on EPICS data (as presented in this widget) to other widgets. For example a QList widget could log updates from this widget.

9.82.1.2 void QERadioButton::requestEnabled (const bool & *state*) [inline, slot]

Similar to standard setEnabled slot, but allows QE widget to determine if the widget remains disabled due to invalid data. If disabled due to invalid data, a request to enable the widget will be honoured when the data is no longer invalid.

9.82.2 Property Documentation

9.82.2.1 bool QERadioButton::allowDrop [read, write]

Allow drag/drops operations to this widget. Default is false. Any dropped text will be used as a new variable name.

Reimplemented from [QEDragDrop](#).

9.82.2.2 bool QERadioButton::enabled [read, write]

Set the preferred 'enabled' state. Default is true. This property is copied to the standard Qt 'enabled' property if the data being displayed is valid. If the data being displayed is invalid the standard Qt 'enabled' property will always be set to false to indicate invalid data. The value of this property will only be copied to the standard Qt 'enabled' property once data is valid.

9.82.2.3 unsigned QERadioButton::int [read, write]

Set the ID used by the message filtering system. Default is zero. Widgets or applications that use messages from the framework have the option of filtering on this ID. For example, by using a unique message source ID a [QELog](#) widget may be set up to only log messages from a select set of widgets.

9.82.2.4 bool QERadioButton::subscribe [read, write]

Sets if this widget subscribes for data updates and displays current data. Default is 'true' (subscribes for and displays data updates)

Reimplemented from [QEWidget](#).

9.82.2.5 UserLevels QERadioButton::userLevelEnabled [read, write]

Lowest user level at which the widget is enabled. Default is 'User'. Used when designing GUIs that allow access to more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through setUserLevel() Widgets that are always accessible should be visible at 'User'. Widgets that are only accessible to scientists managing the facility should be visible at 'Scientist'. Widgets that are only accessible to engineers maintaining the facility should be visible at 'Engineer'.

9.82.2.6 QString QERadioButton::userLevelEngineerStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'Engineer' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.82.2.7 QString QERadioButton::userLevelScientistStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'Scientist' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.82.2.8 QString QERadioButton::userLevelUserStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'User' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.82.2.9 UserLevels QERadioButton::userLevelVisibility [read, write]

Lowest user level at which the widget is visible. Default is 'User'. Used when designing GUIs that display more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through setUserLevel() Widgets that are always visible should be visible at 'User'. Widgets that are only used by scientists managing the facility should be visible at 'Scientist'. Widgets that are only used by engineers maintaining the facility should be visible at 'Engineer'.

9.82.2.10 QString QERadioButton::variable [read, write]

EPICS variable name (CA PV)

9.82.2.11 bool QERadioButton::variableAsToolTip [read, write]

Use the variable as the tool tip. Default is true. Tool tip property will be overwritten by the variable name.

Reimplemented from [QEWWidget](#).

9.82.2.12 QString QERadioButton::variableSubstitutions [read, write]

Macro substitutions. The default is no substitutions. The format is NAME1=VALUE1[, NAME2=VALUE2... Values may be quoted strings. For example, 'PUMP=PMP3, NAME = "My Pump"' These substitutions are applied to variable names for all QE widgets. In some widgets are also used for other purposes.

9.82.2.13 bool QERadioButton::visible [read, write]


Display the widget. Default is true. Setting this property false is useful if widget is only used to provide a signal - for example, when supplying data to a [QELink](#) widget. Note, when false the widget will still be visible in Qt Designer.

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEButton/QERadioButton.h
- /home/rhydera/epicsqt/framework/widgets/QEButton/QERadioButton.cpp

9.83 QERecipe Class Reference

Inheritance diagram for QERecipe:



Public Types

- enum **configurationTypesProperty** { **File** = FROM_FILE, **Text** = FROM_TEXT }
- enum **detailsLayoutProperty** { **Top** = TOP, **Bottom** = BOTTOM, **Left** = LEFT, **Right** = RIGHT }
- enum **userTypesProperty** { **User** = USERLEVEL_USER, **Scientist** = USERLEVEL_SCIENTIST, **Engineer** = USERLEVEL_ENGINEER }

Public Member Functions

- **QERecipe** (QWidget *pParent=0)
- void **setRecipeDescription** (QString pValue)
- QString **getRecipeDescription** ()
- void **setShowRecipeList** (bool pValue)
- bool **getShowRecipeList** ()
- void **setShowNew** (bool pValue)

- bool **getShowNew** ()
- void **setShowSave** (bool pValue)
- bool **getShowSave** ()
- void **setShowDelete** (bool pValue)
- bool **getShowDelete** ()
- void **setShowApply** (bool pValue)
- bool **getShowApply** ()
- void **setShowRead** (bool pValue)
- bool **getShowRead** ()
- void **setShowFields** (bool pValue)
- bool **getShowFields** ()
- void **setConfigurationType** (int pValue)
- int **getConfigurationType** ()
- void **setConfigurationFile** (QString pValue)
- QString **getConfigurationFile** ()
- void **setRecipeFile** (QString pValue)
- QString **getRecipeFile** ()
- void **setConfigurationText** (QString pValue)
- QString **getConfigurationText** ()
- void **setDetailsLayout** (int pValue)
- int **getDetailsLayout** ()
- void **setCurrentUserType** (int pValue)
- int **getCurrentUserType** ()
- bool **saveRecipeList** ()
- void **refreshRecipeList** ()
- void **refreshButton** ()
- void **userLevelChanged** (userLevels pValue)
- void **setConfigurationTypeProperty** (configurationTypesProperty pConfigurationType)
- configurationTypesProperty **getConfigurationTypeProperty** ()
- void **setDetailsLayoutProperty** (detailsLayoutProperty pDetailsLayout)
- detailsLayoutProperty **getDetailsLayoutProperty** ()
- void **setCurrentUserTypeProperty** (userTypesProperty pUserType)
- userTypesProperty **getCurrentUserTypeProperty** ()

Protected Attributes

- QLabel * **qLabelRecipeDescription**
- QComboBox * **qComboBoxRecipeList**
- QPushButton * **qPushButtonNew**
- QPushButton * **qPushButtonSave**
- QPushButton * **qPushButtonDelete**
- QPushButton * **qPushButtonApply**
- QPushButton * **qPushButtonRead**
- [QEConfiguredLayout](#) * **qEConfiguredLayoutRecipeFields**
- QDomDocument **document**

- QString **recipeFile**
- QString **filename**
- int **detailsLayout**
- int **currentUserType**

Properties


- QString **recipeDescription**
- bool **showRecipeList**
- bool **showNew**
- bool **showSave**
- bool **showDelete**
- bool **showApply**
- bool **showRead**
- bool **showFields**
- configurationTypesProperty **configurationType**
- QString **configurationFile**
- QString **configurationText**
- detailsLayoutProperty **detailsLayout**
- userTypesProperty **currentUserType**

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QERecipe/QERecipe.h
- /home/rhydera/epicsqt/framework/widgets/QERecipe/QERecipe.cpp

9.84 QEScript Class Reference

Inheritance diagram for QEScript:



Public Types

- enum **detailsLayoutProperty** { **Top** = TOP, **Bottom** = BOTTOM, **Left** = LEFT, **Right** = RIGHT }

Signals

- void **selected** (QString pFilename)

Public Member Functions

- **QEScript** (QWidget *pParent=0)
- void **setDirectoryPath** (QString pValue)
- QString **getDirectoryPath** ()
- void **setShowDirectoryPath** (bool pValue)
- bool **getShowDirectoryPath** ()
- void **setShowDirectoryBrowser** (bool pValue)
- bool **getShowDirectoryBrowser** ()
- void **setShowRefresh** (bool pValue)
- bool **getShowRefresh** ()
- void **setShowColumnTime** (bool pValue)
- bool **getShowColumnTime** ()
- void **setShowColumnSize** (bool pValue)
- bool **getShowColumnSize** ()
- void **setShowColumnFilename** (bool pValue)
- bool **getShowColumnFilename** ()
- void **setShowFileExtension** (bool pValue)
- bool **getShowFileExtension** ()
- void **setFileFilter** (QString pValue)
- QString **getFileFilter** ()
- void **setDetailsLayout** (int pValue)
- int **getDetailsLayout** ()
- void **updateTable** ()
- void **setDetailsLayoutProperty** (detailsLayoutProperty pDetailsLayout)
- detailsLayoutProperty **getDetailsLayoutProperty** ()

Protected Attributes

- QLineEdit * **qlineEditDirectoryPath**
- QPushButton * **qPushButtonDirectoryBrowser**
- QPushButton * **qPushButtonRefresh**
- [_QTableWidgetScript](#) * **qTableWidgetScript**
- QString **fileFilter**
- bool **showFileExtension**
- int **detailsLayout**

Properties

- QString **directoryPath**
- bool **showDirectoryPath**
- bool **showDirectoryBrowser**
- bool **showRefresh**
- bool **showColumnTime**
- bool **showColumnSize**
- bool **showColumnFilename**

Signals

- void [dbValueChanged1](#) (const qlonglong &out)
- void [dbValueChanged2](#) (const qlonglong &out)
- void [dbValueChanged3](#) (const qlonglong &out)
- void [dbValueChanged4](#) (const qlonglong &out)
- void [dbValueChanged5](#) (const qlonglong &out)
- void [dbValueChanged6](#) (const qlonglong &out)

Public Member Functions

- [QEShape](#) (QWidget *parent=0)
- [QEShape](#) (const QString &variableName, QWidget *parent=0)
- void [setAnimation](#) ([animationOptions](#) animation, const int index)
Access function for 'animation' properties - refer to 'animation' properties for details.
- [animationOptions](#) [getAnimation](#) (const int index)
Access function for 'animation' properties - refer to 'animation' properties for details.
- void [setScale](#) (const double scale, const int index)
Access function for 'scale' properties - refer to 'scale' properties for details.
- double [getScale](#) (const int index)
Access function for 'scale' properties - refer to 'scale' properties for details.
- void [setOffset](#) (const double offset, const int index)
Access function for 'offset' properties - refer to 'offset' properties for details.
- double [getOffset](#) (const int index)
Access function for 'offset' properties - refer to 'offset' properties for details.
- void [setBorder](#) (const bool border)
Access function for 'border' properties - refer to 'border' properties for details.
- bool [getBorder](#) ()
Access function for 'border' properties - refer to 'border' properties for details.
- void [setFill](#) (const bool fill)
Access function for 'fill' properties - refer to 'fill' properties for details.
- bool [getFill](#) ()
Access function for 'fill' properties - refer to 'fill' properties for details.
- void [setShape](#) ([shapeOptions](#) shape)
Access function for 'shape' properties - refer to 'shape' properties for details.
- [shapeOptions](#) [getShape](#) ()
Access function for 'shape' properties - refer to 'shape' properties for details.
- void [setNumPoints](#) (const unsigned int numPoints)
Access function for 'number of points' properties - refer to 'number of points' properties for details.
- unsigned int [getNumPoints](#) ()
Access function for 'number of points' properties - refer to 'number of points' properties for details.
- void [setOriginTranslation](#) (const QPoint originTranslation)

Access function for 'origin translation' properties - refer to 'origin translation' properties for details.

- QPoint [getOriginTranslation](#) ()

Access function for 'origin translation' properties - refer to 'origin translation' properties for details.

- void [setPoint](#) (const QPoint point, const int index)

Access function for 'point' properties - refer to 'point' properties for details.

- QPoint [getPoint](#) (const int index)

Access function for 'point' properties - refer to 'point' properties for details.

- void [setColor](#) (const QColor color, const int index)

Access function for 'colour' properties - refer to 'colour' properties for details.

- QColor [getColor](#) (const int index)

Access function for 'colour' properties - refer to 'colour' properties for details.

- void [setDrawBorder](#) (const bool drawBorder)

Access function for 'draw border' properties - refer to 'draw border' properties for details.

- bool [getDrawBorder](#) ()

Access function for 'draw border' properties - refer to 'draw border' properties for details.

- void [setLineWidth](#) (const unsigned int lineWidth)

Access function for 'line width' properties - refer to 'line width' properties for details.

- unsigned int [getLineWidth](#) ()

Access function for 'line width' properties - refer to 'line width' properties for details.

- void [setStartAngle](#) (const double startAngle)

Access function for 'start angle' properties - refer to 'start angle' properties for details.

- double [getStartAngle](#) ()

Access function for 'start angle' properties - refer to 'start angle' properties for details.

- void [setRotation](#) (const double rotation)

Access function for 'rotation' properties - refer to 'rotation' properties for details.

- double [getRotation](#) ()

Access function for 'rotation' properties - refer to 'rotation' properties for details.

- void [setArcLength](#) (const double arcLength)

Access function for 'arc length' properties - refer to 'arc length' properties for details.

- double [getArcLength](#) ()

Access function for 'arc length' properties - refer to 'arc length' properties for details.

- void [setText](#) (const QString text)

Access function for 'text' properties - refer to 'text' properties for details.

- QString [getText](#) ()

Access function for 'text' properties - refer to 'text' properties for details.

- bool [isEnabled](#) () const

Access function for 'enabled' property - refer to 'enabled' property for details.

- void [setEnabled](#) (bool state)

Access function for 'enabled' property - refer to 'enabled' property for details.

- [UserLevels](#) [getUserLevelVisibilityProperty](#) ()

Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.

- void [setUserLevelVisibilityProperty](#) ([UserLevels](#) level)

Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.

- [UserLevels](#) [getUserLevelEnabledProperty](#) ()

Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.

- void [setUserLevelEnabledProperty](#) ([UserLevels](#) level)

Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.

Properties

- QString [variable1](#)
- QString [variable2](#)
- QString [variable3](#)
- QString [variable4](#)
- QString [variable5](#)
- QString [variable6](#)
- QString [variableSubstitutions](#)
- bool [variableAsToolTip](#)
- bool [enabled](#)
- bool [allowDrop](#)
- bool [visible](#)
- unsigned int
- QString [userLevelUserStyle](#)
- QString [userLevelScientistStyle](#)
- QString [userLevelEngineerStyle](#)
- [UserLevels](#) [userLevelVisibility](#)
- [UserLevels](#) [userLevelEnabled](#)
- [animationOptions](#) [animation1](#)
- [animationOptions](#) [animation2](#)
- [animationOptions](#) [animation3](#)
- [animationOptions](#) [animation4](#)
- [animationOptions](#) [animation5](#)
- [animationOptions](#) [animation6](#)
- double [scale1](#)

Scale factor applied to data from the 1st variable before it is used to animate the shape.

- double [scale2](#)
- double [scale3](#)
- double [scale4](#)
- double [scale5](#)
- double [scale6](#)
- double [offset1](#)
- double [offset2](#)

- double [offset3](#)
- double [offset4](#)
- double [offset5](#)
- double [offset6](#)
- QPoint [point1](#)
- QPoint [point2](#)
- QPoint [point3](#)
- QPoint [point4](#)
- QPoint [point5](#)
- QPoint [point6](#)
- QPoint [point7](#)
- QPoint [point8](#)
- QPoint [point9](#)
- QPoint [point10](#)
- QColor [color1](#)
- QColor [color2](#)
- QColor [color3](#)
- QColor [color4](#)
- QColor [color5](#)
- QColor [color6](#)
- QColor [color7](#)
- QColor [color8](#)
- QColor [color9](#)
- QColor [color10](#)

9.85.1 Detailed Description

This class is a EPICS aware shape widget based on the Qt widget. One of several shapes can be drawn within the widget, and up to 6 variables can be used to animate various attributes of the shape. For example to represent beam positino and size, an elipse can be drawn with four variables animating its vertcal and horizontal size and position. It is tightly integrated with the base class [QEWWidget](#) which provides generic support such as macro substitutions, drag/drop, and standard properties.

9.85.2 Member Enumeration Documentation

9.85.2.1 enum [QEShape::animationOptions](#)

Options for how a variable will animate the shape.

9.85.2.2 enum [QEShape::shapeOptions](#)

Options for the type of shape.

9.85.3 Constructor & Destructor Documentation

9.85.3.1 QEShape::QEShape (QWidget * *parent* = 0)

Create without a variable. Use `setVariableNameProperty()` and `setSubstitutionsProperty()` to define a variable and, optionally, macro substitutions later.

9.85.3.2 QEShape::QEShape (const QString & *variableName*, QWidget * *parent* = 0)

Create with a single variable. A connection is automatically established. If macro substitutions are required, create without a variable and set the variable and macro substitutions after creation.

9.85.4 Member Function Documentation

9.85.4.1 void QEShape::dbValueChanged1 (const qlonglong & *out*) [signal]

Sent when the widget is updated following a data change for the first variable Can be used to pass on EPICS data (as presented in this widget) to other widgets. For example a QList widget could log updates from this widget.

9.85.4.2 void QEShape::dbValueChanged2 (const qlonglong & *out*) [signal]

Sent when the widget is updated following a data change for the second variable Can be used to pass on EPICS data (as presented in this widget) to other widgets. For example a QList widget could log updates from this widget.

9.85.4.3 void QEShape::dbValueChanged3 (const qlonglong & *out*) [signal]

Sent when the widget is updated following a data change for the third variable Can be used to pass on EPICS data (as presented in this widget) to other widgets. For example a QList widget could log updates from this widget.

9.85.4.4 void QEShape::dbValueChanged4 (const qlonglong & *out*) [signal]

Sent when the widget is updated following a data change for the fourth variable Can be used to pass on EPICS data (as presented in this widget) to other widgets. For example a QList widget could log updates from this widget.

9.85.4.5 void QEShape::dbValueChanged5 (const qlonglong & *out*) [signal]

Sent when the widget is updated following a data change for the fifth variable Can be used to pass on EPICS data (as presented in this widget) to other widgets. For example a QList widget could log updates from this widget.

9.85.4.6 void QEShape::dbValueChanged6 (const qlonglong & out) [signal]

Sent when the widget is updated following a data change for the sixth variable. Can be used to pass on EPICS data (as presented in this widget) to other widgets. For example a QList widget could log updates from this widget.

9.85.4.7 void QEShape::requestEnabled (const bool & state) [inline, slot]

Similar to standard setEnabled slot, but allows QE widget to determine if the widget remains disabled due to invalid data. If disabled due to invalid data, a request to enable the widget will be honoured when the data is no longer invalid.

9.85.5 Property Documentation

9.85.5.1 bool QEShape::allowDrop [read, write]

Allow drag/drops operations to this widget. Default is false. Any dropped text will be used as a new variable name.

Reimplemented from [QEDragDrop](#).

9.85.5.2 animationOptions QEShape::animation1 [read, write]

Animation to be effected by the 1st variable. This is used to select what the effect changing data for the 1st variable will have on the shape.

9.85.5.3 animationOptions QEShape::animation2 [read, write]

Animation to be effected by the 2nd variable. This is used to select what the effect changing data for the 2nd variable will have on the shape.

9.85.5.4 animationOptions QEShape::animation3 [read, write]

Animation to be effected by the 3rd variable. This is used to select what the effect changing data for the 3rd variable will have on the shape.

9.85.5.5 animationOptions QEShape::animation4 [read, write]

Animation to be effected by the 4th variable. This is used to select what the effect changing data for the 4th variable will have on the shape.

9.85.5.6 animationOptions QEShape::animation5 [read, write]

Animation to be effected by the 5th variable. This is used to select what the effect changing data for the 5th variable will have on the shape.

9.85.5.7 animationOptions QEShape::animation6 [read, write]

Animation to be effected by the 6th variable. This is used to select what the effect changing data for the 6th variable will have on the shape.

9.85.5.8 QColor QEShape::color1 [read, write]

Used by the color animation to determine the color based on a data value. The scaled and offset data is used as an index to select color properties 'color1' to 'color10'.

9.85.5.9 QColor QEShape::color10 [read, write]

Used by the color animation to determine the color based on a data value. The scaled and offset data is used as an index to select color properties 'color1' to 'color10'.

9.85.5.10 QColor QEShape::color2 [read, write]

Used by the color animation to determine the color based on a data value. The scaled and offset data is used as an index to select color properties 'color1' to 'color10'.

9.85.5.11 QColor QEShape::color3 [read, write]

Used by the color animation to determine the color based on a data value. The scaled and offset data is used as an index to select color properties 'color1' to 'color10'.

9.85.5.12 QColor QEShape::color4 [read, write]

Used by the color animation to determine the color based on a data value. The scaled and offset data is used as an index to select color properties 'color1' to 'color10'.

9.85.5.13 QColor QEShape::color5 [read, write]

Used by the color animation to determine the color based on a data value. The scaled and offset data is used as an index to select color properties 'color1' to 'color10'.

9.85.5.14 QColor QEShape::color6 [read, write]

Used by the color animation to determine the color based on a data value. The scaled and offset data is used as an index to select color properties 'color1' to 'color10'.

9.85.5.15 QColor QEShape::color7 [read, write]

Used by the color animation to determine the color based on a data value. The scaled and offset data is used as an index to select color properties 'color1' to 'color10'.

9.85.5.16 QColor QEShape::color8 [read, write]

Used by the color animation to determine the color based on a data value. The scaled and offset data is used as an index to select color properties 'color1' to 'color10'.

9.85.5.17 QColor QEShape::color9 [read, write]

Used by the color animation to determine the color based on a data value. The scaled and offset data is used as an index to select color properties 'color1' to 'color10'.

9.85.5.18 bool QEShape::enabled [read, write]

Set the preferred 'enabled' state. Default is true. This property is copied to the standard Qt 'enabled' property if the data being displayed is valid. If the data being displayed is invalid the standard Qt 'enabled' property will always be set to false to indicate invalid data. The value of this property will only be copied to the standard Qt 'enabled' property once data is valid.

9.85.5.19 unsigned QEShape::int [read, write]

Set the ID used by the message filtering system. Default is zero. Widgets or applications that use messages from the framework have the option of filtering on this ID. For example, by using a unique message source ID a [QELog](#) widget may be set up to only log messages from a select set of widgets.

The number of points to use when drawing shapes that are defined by a variable number of points, such as polyline, polygon, path, and series of points.

Sets the width of the pen. Used for the following shapes: Line, Points, Polyline, Polygon, Rect, RoundedRect, Ellipse, Arc, Chord, Pie, Path

9.85.5.20 double QEShape::offset1 [read, write]

Offset applied to data from the 1st variable before it is used to animate the shape

9.85.5.21 double QEShape::offset2 [read, write]

Offset applied to data from the 2nd variable before it is used to animate the shape

9.85.5.22 double QEShape::offset3 [read, write]

Offset applied to data from the 3rd variable before it is used to animate the shape

9.85.5.23 `double QEShape::offset4` [read, write]

Offset applied to data from the 4th variable before it is used to animate the shape

9.85.5.24 `double QEShape::offset5` [read, write]

Offset applied to data from the 5th variable before it is used to animate the shape

9.85.5.25 `double QEShape::offset6` [read, write]

Offset applied to data from the 6th variable before it is used to animate the shape

9.85.5.26 `QPoint QEShape::point1` [read, write]

1st coordinate used when drawing the shape. Used for the following shapes: Line, Points, Polyline, Polygon, Rect, RoundedRect, Ellipse, Arc, Chord, Pie, Path, Text, Pixmap

9.85.5.27 `QPoint QEShape::point10` [read, write]

10th coordinate used when drawing the shape. Used for the following shapes: Points, Polyline, Polygon, Path

9.85.5.28 `QPoint QEShape::point2` [read, write]

2nd coordinate used when drawing the shape. Used for the following shapes: Line, Points, Polyline, Polygon, Rect, RoundedRect, Ellipse, Arc, Chord, Pie, Path, Pixmap

9.85.5.29 `QPoint QEShape::point3` [read, write]

3rd coordinate used when drawing the shape. Used for the following shapes: Points, Polyline, Polygon, Path

9.85.5.30 `QPoint QEShape::point4` [read, write]

4th coordinate used when drawing the shape. Used for the following shapes: Points, Polyline, Polygon, Path

9.85.5.31 `QPoint QEShape::point5` [read, write]

5th coordinate used when drawing the shape. Used for the following shapes: Points, Polyline, Polygon, Path

9.85.5.32 QPoint QEShape::point6 [read, write]

6th coordinate used when drawing the shape. Used for the following shapes: Points, Polyline, Polygon, Path

9.85.5.33 QPoint QEShape::point7 [read, write]

7th coordinate used when drawing the shape. Used for the following shapes: Points, Polyline, Polygon, Path

9.85.5.34 QPoint QEShape::point8 [read, write]

8th coordinate used when drawing the shape. Used for the following shapes: Points, Polyline, Polygon, Path

9.85.5.35 QPoint QEShape::point9 [read, write]

9th coordinate used when drawing the shape. Used for the following shapes: Points, Polyline, Polygon, Path

9.85.5.36 double QEShape::scale2 [read, write]

Scale factor applied to data from the 2nd variable before it is used to animate the shape

9.85.5.37 double QEShape::scale3 [read, write]

Scale factor applied to data from the 3rd variable before it is used to animate the shape

9.85.5.38 double QEShape::scale4 [read, write]

Scale factor applied to data from the 4th variable before it is used to animate the shape

9.85.5.39 double QEShape::scale5 [read, write]

Scale factor applied to data from the 5th variable before it is used to animate the shape

9.85.5.40 double QEShape::scale6 [read, write]

Scale factor applied to data from the 6th variable before it is used to animate the shape

9.85.5.41 UserLevels QEShape::userLevelEnabled [read, write]

Lowest user level at which the widget is enabled. Default is 'User'. Used when designing GUIs that allow access to more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through `setUserLevel()` Widgets that are always accessible should be visible at 'User'. Widgets that are only accessible to scientists managing the facility should be visible at 'Scientist'. Widgets that are only accessible to engineers maintaining the facility should be visible at 'Engineer'.

9.85.5.42 QString QEShape::userLevelEngineerStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'Engineer' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the `styleManager` class. Refer to the `styleManager` class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.85.5.43 QString QEShape::userLevelScientistStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'Scientist' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the `styleManager` class. Refer to the `styleManager` class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.85.5.44 QString QEShape::userLevelUserStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'User' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the `styleManager` class. Refer to the `styleManager` class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.85.5.45 UserLevels QEShape::userLevelVisibility [read, write]

Lowest user level at which the widget is visible. Default is 'User'. Used when designing GUIs that display more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through `setUserLevel()` Widgets that are always visible should be visible at 'User'. Widgets that are only used by scientists managing the facility should be visible at 'Scientist'. Widgets that are only used by engineers maintaining the facility should be visible at 'Engineer'.

9.85.5.46 `QString QEShape::variable1` [read, write]

EPICS variable name (CA PV). This variable is read and used to animate an attribute of the shape. The value read is first scaled and offset by properties `scale1` and `offset1` then the attribute selected for animation is selected by the property `animation1`.

9.85.5.47 `QString QEShape::variable2` [read, write]

EPICS variable name (CA PV). This variable is read and used to animate an attribute of the shape. The value read is first scaled and offset by properties `scale2` and `offset2` then the attribute selected for animation is selected by the property `animation2`.

9.85.5.48 `QString QEShape::variable3` [read, write]

EPICS variable name (CA PV). This variable is read and used to animate an attribute of the shape. The value read is first scaled and offset by properties `scale3` and `offset3` then the attribute selected for animation is selected by the property `animation3`.

9.85.5.49 `QString QEShape::variable4` [read, write]

EPICS variable name (CA PV). This variable is read and used to animate an attribute of the shape. The value read is first scaled and offset by properties `scale4` and `offset4` then the attribute selected for animation is selected by the property `animation4`.

9.85.5.50 `QString QEShape::variable5` [read, write]

EPICS variable name (CA PV). This variable is read and used to animate an attribute of the shape. The value read is first scaled and offset by properties `scale5` and `offset5` then the attribute selected for animation is selected by the property `animation5`.

9.85.5.51 `QString QEShape::variable6` [read, write]

EPICS variable name (CA PV). This variable is read and used to animate an attribute of the shape. The value read is first scaled and offset by properties `scale6` and `offset6` then the attribute selected for animation is selected by the property `animation6`.

9.85.5.52 `bool QEShape::variableAsToolTip` [read, write]

Use the variable as the tool tip. Default is true. Tool tip property will be overwritten by the variable name.

Reimplemented from [QEObject](#).

9.85.5.53 **QString QEShape::variableSubstitutions** [read, write]

Macro substitutions. The default is no substitutions. The format is NAME1=VALUE1[, NAME2=VALUE2... Values may be quoted strings. For example, 'SAMPLE=SAM1, NAME = "Ref foil"' These substitutions are applied to all the variable names.

9.85.5.54 **bool QEShape::visible** [read, write]


Display the widget. Default is true. Setting this property false is usefull if widget is only used to provide a signal - for example, when supplying data to a [QELink](#) widget. Note, when false the widget will still be visible in Qt Designer.

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEShape/QEShape.h
- /home/rhydera/epicsqt/framework/widgets/QEShape/QEShape.cpp

9.86 QESlider Class Reference

Inheritance diagram for QESlider:



Public Types

- enum **UserLevels** { **User** = USERLEVEL_USER, **Scientist** = USERLEVEL_SCIENTIST, **Engineer** = USERLEVEL_ENGINEER }

User friendly enumerations for `userLevelVisibility` and `userLevelEnabled` properties - refer to `userLevelVisibility` and `userLevelEnabled` properties and `userLevel` enumeration for details.

Public Slots

- void **requestEnabled** (const bool &state)

Signals

- void **dbValueChanged** (const qlonglong &out)

Public Member Functions

- **QESlider** (QWidget *parent=0)
- **QESlider** (const QString &variableName, QWidget *parent=0)
- void **setWriteOnChange** (bool [writeOnChange](#))
- bool **getWriteOnChange** ()
- void **setSubscribe** (bool subscribe)
- bool **getSubscribe** ()
- void **setScale** (double scaleIn)
- double **getScale** ()
- void **setOffset** (double offsetIn)
- double **getOffset** ()
- bool [isEnabled](#) () const
- Access function for 'enabled' property - refer to 'enabled' property for details.*
- void [setEnabled](#) (bool state)
- Access function for 'enabled' property - refer to 'enabled' property for details.*
- [UserLevels](#) **getUserLevelVisibilityProperty** ()
- Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.*
- void [setEnabled](#) ([UserLevels](#) level)
- Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.*
- [UserLevels](#) **getUserLevelEnabledProperty** ()
- Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.*
- void [setEnabled](#) ([UserLevels](#) level)
- Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.*

Protected Member Functions

- void **establishConnection** (unsigned int variableIndex)
- void **dragEnterEvent** (QDragEnterEvent *event)
- void **dropEvent** (QDropEvent *event)
- void **setDrop** (QVariant drop)
- QVariant **getDrop** ()

Protected Attributes

- [QEFloatingFormatting](#) **floatingFormatting**
- bool [writeOnChange](#)

Properties

- QString [variable](#)
- QString [variableSubstitutions](#)
- bool [subscribe](#)
- bool [variableAsToolTip](#)
- bool [enabled](#)
- bool [allowDrop](#)
- bool [visible](#)
- unsigned [int](#)
- QString [userLevelUserStyle](#)
- QString [userLevelScientistStyle](#)
- QString [userLevelEngineerStyle](#)
- [UserLevels](#) [userLevelVisibility](#)
- [UserLevels](#) [userLevelEnabled](#)

9.86.1 Member Function Documentation

9.86.1.1 void QESlider::dbValueChanged (const qlonglong & *out*) [[signal](#)]

Sent when the widget is updated following a data change Can be used to pass on EPICS data (as presented in this widget) to other widgets. For example a QList widget could log updates from this widget.

9.86.1.2 void QESlider::requestEnabled (const bool & *state*) [[inline](#), [slot](#)]

Similar to standard setEnabled slot, but allows QE widget to determine if the widget remains disabled due to invalid data. If disabled due to invalid data, a request to enable the widget will be honoured when the data is no longer invalid.

9.86.2 Member Data Documentation

9.86.2.1 bool QESlider::writeOnChange [[read](#), [write](#), [protected](#)]

Sets if this widget writes any changes as the user moves the slider (the QSlider 'valueChanged' signal is emitted). Default is 'true' (writes any changes when the QSlider 'valueChanged' signal is emitted).

9.86.3 Property Documentation

9.86.3.1 bool QESlider::allowDrop [[read](#), [write](#)]

Allow drag/drops operations to this widget. Default is false. Any dropped text will be used as a new variable name.

Reimplemented from [QEDragDrop](#).

9.86.3.2 `bool QESlider::enabled` [read, write]

Set the preferred 'enabled' state. Default is true. This property is copied to the standard Qt 'enabled' property if the data being displayed is valid. If the data being displayed is invalid the standard Qt 'enabled' property will always be set to false to indicate invalid data. The value of this property will only be copied to the standard Qt 'enabled' property once data is valid.

9.86.3.3 `unsigned QESlider::int` [read, write]

Set the ID used by the message filtering system. Default is zero. Widgets or applications that use messages from the framework have the option of filtering on this ID. For example, by using a unique message source ID a [QELog](#) widget may be set up to only log messages from a select set of widgets.

9.86.3.4 `bool QESlider::subscribe` [read, write]

Sets if this widget subscribes for data updates and displays current data. Default is 'true' (subscribes for and displays data updates)

Reimplemented from [QEWidget](#).

9.86.3.5 `UserLevels QESlider::userLevelEnabled` [read, write]

Lowest user level at which the widget is enabled. Default is 'User'. Used when designing GUIs that allow access to more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through `setUserLevel()` Widgets that are always accessible should be visible at 'User'. Widgets that are only accessible to scientists managing the facility should be visible at 'Scientist'. Widgets that are only accessible to engineers maintaining the facility should be visible at 'Engineer'.

9.86.3.6 `QString QESlider::userLevelEngineerStyle` [read, write]

Style Sheet string to be applied when the widget is displayed in 'Engineer' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.86.3.7 `QString QESlider::userLevelScientistStyle` [read, write]

Style Sheet string to be applied when the widget is displayed in 'Scientist' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the styleManager

class. Refer to the `styleManager` class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.86.3.8 QString QESlider::userLevelUserStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'User' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the `styleManager` class. Refer to the `styleManager` class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.86.3.9 UserLevels QESlider::userLevelVisibility [read, write]

Lowest user level at which the widget is visible. Default is 'User'. Used when designing GUIs that display more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through `setUserLevel()` Widgets that are always visible should be visible at 'User'. Widgets that are only used by scientists managing the facility should be visible at 'Scientist'. Widgets that are only used by engineers maintaining the facility should be visible at 'Engineer'.

9.86.3.10 QString QESlider::variable [read, write]

EPICS variable name (CA PV)

9.86.3.11 bool QESlider::variableAsToolTip [read, write]

Use the variable as the tool tip. Default is true. Tool tip property will be overwritten by the variable name.

Reimplemented from [QEWidget](#).

9.86.3.12 QString QESlider::variableSubstitutions [read, write]

Macro substitutions. The default is no substitutions. The format is NAME1=VALUE1[, NAME2=VALUE2... Values may be quoted strings. For example, 'PUMP=PMP3, NAME = "My Pump"' These substitutions are applied to variable names for all QE widgets. In some widgets are also used for other purposes.

9.86.3.13 bool QESlider::visible [read, write]


Display the widget. Default is true. Setting this property false is usefull if widget is only used to provide a signal - for example, when supplying data to a [QELink](#) widget. Note, when false the widget will still be visible in Qt Designer.

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QESlider/QESlider.h
- /home/rhydera/epicsqt/framework/widgets/QESlider/QESlider.cpp

9.87 QESpinBox Class Reference

Inheritance diagram for QESpinBox:



Public Types

- enum [UserLevels](#) { **User** = USERLEVEL_USER, **Scientist** = USERLEVEL_SCIENTIST, **Engineer** = USERLEVEL_ENGINEER }

User friendly enumerations for userLevelVisibility and userLevelEnabled properties - refer to userLevelVisibility and userLevelEnabled properties and userLevel enumeration for details.

Public Slots

- void [requestEnabled](#) (const bool &state)

Signals

- void [dbValueChanged](#) (const double &out)
- void [userChange](#) (const QString &oldValue, const QString &newValue, const QString &lastValue)

Internal use only. Used by [QEConfiguredLayout](#) to be notified when one of its widgets has written something.

Public Member Functions

- **QESpinBox** (QWidget *parent=0)
- **QESpinBox** (const QString &variableName, QWidget *parent=0)
- void **setWriteOnChange** (bool writeOnChangeIn)
- bool **getWriteOnChange** ()
- void **setSubscribe** (bool subscribe)

- bool **getSubscribe** ()
- void **setAddUnitsAsSuffix** (bool addUnitsAsSuffixIn)
- bool **getAddUnitsAsSuffix** ()
- void **setUseDbPrecisionForDecimals** (bool useDbPrecisionForDecimalIn)
- bool **getUseDbPrecisionForDecimals** ()
- bool **isEnabled** () const
Access function for 'enabled' property - refer to 'enabled' property for details.
- void **setEnabled** (bool state)
Access function for 'enabled' property - refer to 'enabled' property for details.
- [UserLevels](#) **getUserLevelVisibilityProperty** ()
Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.
- void **setUserLevelVisibilityProperty** ([UserLevels](#) level)
Access function for 'userLevelVisibility' property - refer to 'userLevelVisibility' property for details.
- [UserLevels](#) **getUserLevelEnabledProperty** ()
Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.
- void **setUserLevelEnabledProperty** ([UserLevels](#) level)
Access function for 'userLevelEnabled' property - refer to 'userLevelEnabled' property for details.

Protected Member Functions

- void **establishConnection** (unsigned int variableIndex)
- void **dragEnterEvent** (QDragEnterEvent *event)
- void **dropEvent** (QDropEvent *event)
- void **setDrop** (QVariant drop)
- QVariant **getDrop** ()

Protected Attributes

- [QEFloatingFormatting](#) **floatingFormatting**
- bool **writeOnChange**
- bool **addUnitsAsSuffix**
- bool **useDbPrecisionForDecimal**

Properties

- QString [variable](#)
- QString [variableSubstitutions](#)
- bool [variableAsToolTip](#)
- bool [enabled](#)
- bool [allowDrop](#)

- bool [visible](#)
- unsigned [int](#)
- QString [userLevelUserStyle](#)
- QString [userLevelScientistStyle](#)
- QString [userLevelEngineerStyle](#)
- [UserLevels](#) [userLevelVisibility](#)
- [UserLevels](#) [userLevelEnabled](#)
- bool [subscribe](#)
- bool **useDbPrecision**
- bool **addUnits**

9.87.1 Member Function Documentation

9.87.1.1 void [QESpinBox::dbValueChanged](#) (const double & *out*) [[signal](#)]

Sent when the widget is updated following a data change Can be used to pass on EPICS data (as presented in this widget) to other widgets. For example a QList widget could log updates from this widget.

9.87.1.2 void [QESpinBox::requestEnabled](#) (const bool & *state*) [[inline](#), [slot](#)]

Similar to standard [setEnabled](#) slot, but allows QE widget to determine if the widget remains disabled due to invalid data. If disabled due to invalid data, a request to enable the widget will be honoured when the data is no longer invalid.

9.87.2 Property Documentation

9.87.2.1 bool [QESpinBox::allowDrop](#) [[read](#), [write](#)]

Allow drag/drops operations to this widget. Default is false. Any dropped text will be used as a new variable name.

Reimplemented from [QEDragDrop](#).

9.87.2.2 bool [QESpinBox::enabled](#) [[read](#), [write](#)]

Set the preferred 'enabled' state. Default is true. This property is copied to the standard Qt 'enabled' property if the data being displayed is valid. If the data being displayed is invalid the standard Qt 'enabled' property will always be set to false to indicate invalid data. The value of this property will only be copied to the standard Qt 'enabled' property once data is valid.

9.87.2.3 unsigned QESpinBox::int [read, write]

Set the ID used by the message filtering system. Default is zero. Widgets or applications that use messages from the framework have the option of filtering on this ID. For example, by using a unique message source ID a [QELog](#) widget may be set up to only log messages from a select set of widgets.

9.87.2.4 bool QESpinBox::subscribe [read, write]

Sets if this widget subscribes for data updates and displays current data. Default is 'true' (subscribes for and displays data updates)

Reimplemented from [QEWidget](#).

9.87.2.5 UserLevels QESpinBox::userLevelEnabled [read, write]

Lowest user level at which the widget is enabled. Default is 'User'. Used when designing GUIs that allow access to more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through `setUserLevel()` Widgets that are always accessible should be visible at 'User'. Widgets that are only accessible to scientists managing the facility should be visible at 'Scientist'. Widgets that are only accessible to engineers maintaining the facility should be visible at 'Engineer'.

9.87.2.6 QString QESpinBox::userLevelEngineerStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'Engineer' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the `styleManager` class. Refer to the `styleManager` class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.87.2.7 QString QESpinBox::userLevelScientistStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'Scientist' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example, 'background-color: red' This Style Sheet string will be applied by the `styleManager` class. Refer to the `styleManager` class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.87.2.8 QString QESpinBox::userLevelUserStyle [read, write]

Style Sheet string to be applied when the widget is displayed in 'User' mode. Default is an empty string. The syntax is the standard Qt Style Sheet syntax. For example,

'background-color: red' This Style Sheet string will be applied by the styleManager class. Refer to the styleManager class for details about how this Style Sheet string will be merged with any pre-existing Style Sheet string and any Style Sheet strings generated during the display of data.

9.87.2.9 UserLevels QESpinBox::userLevelVisibility [read, write]

Lowest user level at which the widget is visible. Default is 'User'. Used when designing GUIs that display more and more detail according to the user mode. The user mode is set application through the [QELogin](#) widget, or programatically through setUserLevel() Widgets that are always visible should be visible at 'User'. Widgets that are only used by scientists managing the facility should be visible at 'Scientist'. Widgets that are only used by engineers maintaining the facility should be visible at 'Engineer'.

9.87.2.10 QString QESpinBox::variable [read, write]

EPICS variable name (CA PV)

9.87.2.11 bool QESpinBox::variableAsToolTip [read, write]

Use the variable as the tool tip. Default is true. Tool tip property will be overwritten by the variable name.

Reimplemented from [QEWidget](#).

9.87.2.12 QString QESpinBox::variableSubstitutions [read, write]

Macro substitutions. The default is no substitutions. The format is NAME1=VALUE1[, NAME2=VALUE2... Values may be quoted strings. For example, 'PUMP=PMP3, NAME = "My Pump"' These substitutions are applied to variable names for all QE widgets. In some widgets are are also used for other purposes.

9.87.2.13 bool QESpinBox::visible [read, write]


Display the widget. Default is true. Setting this property false is usefull if widget is only used to provide a signal - for example, when supplying data to a [QELink](#) widget. Note, when false the widget will still be visible in Qt Designer.

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QESpinBox/QESpinBox.h
- /home/rhydera/epicsqt/framework/widgets/QESpinBox/QESpinBox.cpp

9.88 QEString Class Reference

Inheritance diagram for QEString:



Public Slots

- void **writeString** (const QString &data)

Signals

- void **stringConnectionChanged** ([QCaConnectionInfo](#) &connectionInfo, const unsigned int &variableIndex)
- void **stringChanged** (const QString &value, [QCaAlarmInfo](#) &alarmInfo, [QCaDateTime](#) &timeStamp, const unsigned int &variableIndex)

Public Member Functions

- **QEString** (QString recordName, QObject *eventObject, [QEStringFormatting](#) *stringFormattingIn, unsigned int variableIndexIn)
- **QEString** (QString recordName, QObject *eventObject, [QEStringFormatting](#) *stringFormattingIn, unsigned int variableIndexIn, [UserMessage](#) *userMessageIn)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/data/include/QEString.h
- /home/rhydera/epicsqt/framework/data/src/QEString.cpp

9.89 QEStringFormatting Class Reference

Public Types

- enum **formats** {
FORMAT_DEFAULT, **FORMAT_FLOATING**, **FORMAT_INTEGER**, **FORMAT_UNSIGNEDINTEGER**,
FORMAT_TIME, **FORMAT_LOCAL_ENUMERATE** }
- enum **notations** { **NOTATION_FIXED** = QTextStream::FixedNotation, **NOTATION_SCIENTIFIC** = QTextStream::ScientificNotation, **NOTATION_AUTOMATIC** = QTextStream::SmartNotation }
- enum **arrayActions** { **APPEND**, **ASCII**, **INDEX** }

Public Member Functions


- QString **formatString** (const QVariant &value)
- QVariant **formatValue** (const QString &text)
- void **setDbEgu** (QString egu)
- void **setDbEnumerations** (QStringList enumerations)
- void **setDbPrecision** (unsigned int dbPrecisionIn)
- void **setDbVariablesStatField** (bool isStatField)
- void **setPrecision** (int precision)
- void **setUseDbPrecision** (bool useDbPrecision)
- void **setLeadingZero** (bool leadingZero)
- void **setTrailingZeros** (bool trailingZeros)
- void **setFormat** (formats format)
- void **setRadix** (unsigned int radix)
- void **setNotation** (notations notation)
- void **setArrayAction** (arrayActions arrayActionIn)
- void **setArrayIndex** (unsigned int arrayIndexIn)
- void **setAddUnits** (bool addUnits)
- void **setLocalEnumeration** (QString localEnumerationIn)
- int **getPrecision** ()
- bool **getUseDbPrecision** ()
- bool **getLeadingZero** ()
- bool **getTrailingZeros** ()
- formats **getFormat** ()
- unsigned int **getRadix** ()
- notations **getNotation** ()
- arrayActions **getArrayAction** ()
- unsigned int **getArrayIndex** ()
- bool **getAddUnits** ()
- QString **getLocalEnumeration** ()

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/data/include/QEStringFormatting.h
- /home/rhydera/epicsqt/framework/data/src/QEStringFormatting.cpp

9.90 QEStringFormattingMethods Class Reference

Inheritance diagram for QEStringFormattingMethods:



Public Member Functions

- virtual void **stringFormattingChange** ()=0
- void **setPrecision** (int precision)
- int **getPrecision** ()
- void **setUseDbPrecision** (bool useDbPrecision)
- bool **getUseDbPrecision** ()
- void **setLeadingZero** (bool leadingZero)
- bool **getLeadingZero** ()
- void **setTrailingZeros** (bool trailingZeros)
- bool **getTrailingZeros** ()
- void **setAddUnits** (bool addUnits)
- bool **getAddUnits** ()
- void **setLocalEnumeration** (QString localEnumeration)
- QString **getLocalEnumeration** ()
- void **setFormat** (QESTringFormatting::formats format)
- QESTringFormatting::formats **getFormat** ()
- void **setRadix** (unsigned int radix)
- unsigned int **getRadix** ()
- void **setNotation** (QESTringFormatting::notations notation)
- QESTringFormatting::notations **getNotation** ()
- void **setArrayAction** (QESTringFormatting::arrayActions arrayAction)
- QESTringFormatting::arrayActions **getArrayAction** ()
- void **setArrayIndex** (unsigned int arrayIndex)
- unsigned int **getArrayIndex** ()

Protected Attributes


- [QESTringFormatting](#) **stringFormatting**

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/include/QESTringFormattingMethods.h
- /home/rhydera/epicsqt/framework/widgets/src/QESTringFormattingMethods.cpp

9.91 QESTripChart Class Reference

Inheritance diagram for QESTripChart:



Classes

- class [PrivateData](#)

Public Types

- enum **Constants** { **NUMBER_OF_PVS** = 12 }

Public Member Functions

- **QEStripChart** (QWidget *parent=0)
- QSize **sizeHint** () const
- QDateTime **getStartDateTime** ()
- QDateTime **getEndDateTime** ()
- void **setEndDateTime** (QDateTime endTimeIn)
- int **getDuration** ()
- void **setDuration** (int durationIn)
- double **getYMinimum** ()
- void **setYMinimum** (double yMinimumIn)
- double **getYMaximum** ()
- void **setYMaximum** (double yMaximumIn)
- void **plotData** ()

Protected Member Functions

- void **dragEnterEvent** (QDragEnterEvent *event)
- void **dropEvent** (QDropEvent *event)
- void **mousePressEvent** (QMouseEvent *event)
- void **setDrop** (QVariant drop)
- QVariant **getDrop** ()
- QString **copyVariable** ()
- QVariant **copyData** ()
- void **paste** (QVariant s)
- void **setup** ()
- [qcaobject::QCaObject](#) * **createQcaltem** (unsigned int variableIndex)
- void **establishConnection** (unsigned int variableIndex)
- void **updateToolTip** (const QString &tip)

Properties

- int **duration**
- double **yMinimum**
- double **yMaximum**
- QString **variable1**
- QString **variable2**

- QString **variable3**
- QString **variable4**
- QString **variable5**
- QString **variable6**
- QString **variable7**
- QString **variable8**
- QString **variable9**
- QString **variable10**
- QString **variable11**
- QString **variable12**
- QColor **colour1**
- QColor **colour2**
- QColor **colour3**
- QColor **colour4**
- QColor **colour5**
- QColor **colour6**
- QColor **colour7**
- QColor **colour8**
- QColor **colour9**
- QColor **colour10**
- QColor **colour11**
- QColor **colour12**

Friends

- class **PrivateData**
- class [QEStripChartItem](#)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEStripChart/QEStripChart.h
- /home/rhydera/epicsqt/framework/widgets/QEStripChart/QEStripChart.cpp

9.92 QEStripChartItem Class Reference

Classes

- class [PrivateData](#)

Friends

- class [QEStripChart](#)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEStripChart/QEStripChartItem.h
- /home/rhydera/epicsqt/framework/widgets/QEStripChart/QEStripChartItem.cpp

Public Member Functions

- **QESubstitutedLabel** (QWidget *parent=0)
- void **establishConnection** (unsigned int variableIndex)
- void **setLabelTextProperty** (QString labelTextIn)
- QString **getLabelTextProperty** ()
- QString **getLabelTextPropertyFormat** ()
- void **setLabelTextPropertyFormat** (QString labelTextIn)

Protected Attributes

- QString [labelText](#)

Properties

- QString [textSubstitutions](#)

9.95.1 Member Data Documentation

9.95.1.1 **QString QESubstitutedLabel::labelText** [read, write, protected]

Label text to be substituted. This text will be copied to the label text after applying any macro substitutions from the textSubstitutions property

9.95.2 Property Documentation

9.95.2.1 **QString QESubstitutedLabel::textSubstitutions** [read, write]


Text substitutions. These substitutions are applied to the 'labelText' property prior to copying it to the label text.

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QESubstitutedLabel/QESubstitutedLabel.h
- /home/rhydera/epicsqt/framework/widgets/QESubstitutedLabel/QESubstitutedLabel.cpp

9.96 QEToolTip Class Reference

Inheritance diagram for QEToolTip:



Public Member Functions


- void **updateToolTipVariable** (const QString &variable)
- void **updateToolTipAlarm** (const QString &alarm)
- void **updateToolTipConnection** (bool connection)
- virtual void **updateToolTip** (const QString &)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/include/QEToolTip.h
- /home/rhydera/epicsqt/framework/widgets/src/QEToolTip.cpp

9.97 QEWidget Class Reference

Inheritance diagram for QEWidget:



Public Member Functions

- **QEWidget** (QWidget *ownerIn)
- void **activate** ()
- unsigned int **getMessageSourceId** ()
- void **setMessageSourceId** (unsigned int messageSourceId)
- [qcaobject::QCaObject](#) * **getQcaltem** (unsigned int variableIndex)
- void **setupContextMenu** (QWidget *w)
- QColor **getColor** ([QCaAlarmInfo](#) &alarmInfo, const int saturation)
- void **readNow** ()
- virtual void **writeNow** ()
- virtual void **setVariableNameAndSubstitutions** (QString variableNameIn, QString variableNameSubstitutionsIn, unsigned int variableIndex)
- QFile * **openQEFile** (QString name, QFile::OpenModeFlag mode)
- QString **defaultFileLocation** ()

Static Public Member Functions

- static bool **inDesigner** ()

Protected Member Functions

- void **setNumVariables** (unsigned int numVariablesIn)
- [qcaobject::QCaObject](#) * **createConnection** (unsigned int variableIndex)
- virtual [qcaobject::QCaObject](#) * **createQcaltem** (unsigned int variableIndex)
- virtual void **establishConnection** (unsigned int variableIndex)
- void **setVariableAsToolTip** (bool variableAsToolTip)
- bool **getVariableAsToolTip** ()

Protected Attributes

- bool **subscribe**
- bool **variableAsToolTip**

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/include/QEWidget.h
- /home/rhydera/epicsqt/framework/widgets/src/QEWidget.cpp

9.98 QEWidgets Class Reference

Public Member Functions


- **QEWidgets** (QObject *parent=0)
- virtual QList< QDesignerCustomWidgetInterface * > **customWidgets** () const

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/include/QEDesignerPlugin.h
- /home/rhydera/epicsqt/framework/widgets/src/QEDesignerPlugin.cpp

9.99 qcastatemachine::ReadQCaStateMachine Class Reference

Inheritance diagram for qcastatemachine::ReadQCaStateMachine:



Public Member Functions

- **ReadQCaStateMachine** (void *parent)
- bool **process** (int requestedState)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/data/include/QCaStateMachine.h
- /home/rhydera/epicsqt/framework/data/src/QCaStateMachine.cpp

9.100 RecordSpec Class Reference

Public Member Functions

- **RecordSpec** (const QString theRecordType)
- QString **getRecordType** ()
- QString **getFieldName** (const int index)

The documentation for this class was generated from the following file:

- /home/rhydera/epicsqt/framework/widgets/QEPvProperties/QEPvProperties.cpp

9.101 RecordSpecList Class Reference

Public Member Functions

- [RecordSpec](#) * **find** (const QString recordType)

The documentation for this class was generated from the following file:

- /home/rhydera/epicsqt/framework/widgets/QEPvProperties/QEPvProperties.cpp

9.102 selectMenu Class Reference

Public Member Functions


- **selectMenu** (QWidget *parent=0)
- imageContextMenu::imageContextMenuOptions **getSelectOption** (const QPoint &pos)
- void **setChecked** (const int mode)
- void **setPanEnabled** (bool enablePan)
- void **setVSliceEnabled** (bool enableVSliceSelection)
- void **setHSliceEnabled** (bool enableHSliceSelection)
- void **setAreaEnabled** (bool enableAreaSelection)
- void **setProfileEnabled** (bool enableProfileSelection)
- void **setTargetEnabled** (bool enableTargetSelection)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEImage/selectMenu.h
- /home/rhydera/epicsqt/framework/widgets/QEImage/selectMenu.cpp

9.103 standardProperties Class Reference

Inheritance diagram for standardProperties:



Public Member Functions

- **standardProperties** (QWidget *ownerIn)

Protected Member Functions


- userLevels **getUserLevelVisibility** ()
- void **setUserLevelVisibility** (userLevels level)
- userLevels **getUserLevelEnabled** ()
- void **setUserLevelEnabled** (userLevels level)
- bool **getApplicationEnabled** () const
- void **setApplicationEnabled** (bool state)
- void **setDataDisabled** (bool disable)
- void **setRunVisible** (bool visibleIn)
- bool **getRunVisible** ()
- void **checkVisibilityEnabledLevel** (userLevels level)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/include/standardProperties.h
- /home/rhydera/epicsqt/framework/widgets/src/standardProperties.cpp

9.104 StateMachineTemplate Class Reference

Inheritance diagram for StateMachineTemplate:



Public Member Functions

- virtual bool **process** (int requestedState)=0

Public Attributes


- int **currentState**
- int **requestState**

The documentation for this class was generated from the following file:

- /home/rhydera/epicsqt/framework/data/include/QCaStateMachine.h

9.105 qcastatemachine::SubscriptionQCaStateMachine Class Reference

Inheritance diagram for qcastatemachine::SubscriptionQCaStateMachine:



Public Member Functions

- **SubscriptionQCaStateMachine** (void *parent)
- bool **process** (int requestedState)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/data/include/QCaStateMachine.h
- /home/rhydera/epicsqt/framework/data/src/QCaStateMachine.cpp

9.106 trace Class Reference

Public Attributes

- QVector< [QCaDateTime](#) > **timeStamps**
- QVector< double > **xdata**
- QVector< double > **ydata**
- QwtPlotCurve * **curve**
- QColor **color**
- QString **legend**
- bool **waveform**
- QwtPlotCurve::CurveStyle **style**

The documentation for this class was generated from the following file:

- /home/rhydera/epicsqt/framework/widgets/QEPlot/QEPlot.h

9.107 TrackRange Class Reference

Public Member Functions

- void **clear** ()
- void **merge** (const double d)
- void **merge** (const [TrackRange](#) that)
- bool **getMinMax** (double &min, double &max)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEStripChart/QEStripChartItem.h
- /home/rhydera/epicsqt/framework/widgets/QEStripChart/QEStripChartItem.cpp

9.108 userInfoStruct Class Reference

Public Attributes

- bool **enable**
- double **value1**
- double **value2**
- QString **elementText**

The documentation for this class was generated from the following file:

- /home/rhydera/epicsqt/framework/widgets/QEPeriodic/QEPeriodic.h

9.109 QEPeriodic::userInfoStructArray Struct Reference

Public Attributes

- [userInfoStruct](#) **array** [NUM_ELEMENTS]

The documentation for this struct was generated from the following file:

- /home/rhydera/epicsqt/framework/widgets/QEPeriodic/QEPeriodic.h

9.110 userLevelSignal Class Reference

Signals

- void [userChanged](#) (userLevels level)
Internal use only. Send when the user level has changed.

Public Member Functions

- void **setLevel** (userLevels levelIn)
- userLevels **getLevel** ()

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/include/ContainerProfile.h
- /home/rhydera/epicsqt/framework/widgets/src/ContainerProfile.cpp

9.111 userLevelSlot Class Reference

Public Slots

- void **userChanged** (userLevels level)

Public Member Functions


- void **setOwner** ([ContainerProfile](#) *ownerIn)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/include/ContainerProfile.h
- /home/rhydera/epicsqt/framework/widgets/src/ContainerProfile.cpp

9.112 UserMessage Class Reference

Inheritance diagram for UserMessage:



Public Types

- enum **message_filter_options** { **MESSAGE_FILTER_ANY**, **MESSAGE_FILTER_MATCH**, **MESSAGE_FILTER_NONE** }

Public Member Functions

- void **setSourceId** (unsigned int sourceId)
- void **setFormId** (unsigned int formId)
- void **setFormFilter** (message_filter_options formFilterIn)
- void **setSourceFilter** (message_filter_options sourceFilterIn)
- unsigned int **getSourceId** ()
- unsigned int **getFormId** ()
- message_filter_options **getFormFilter** ()
- message_filter_options **getSourceFilter** ()
- void **setChildFormId** (unsigned int)
- unsigned int **getChildFormId** ()

- unsigned int **getNextMessageFormId** ()
- void **sendMessage** (QString message, message_types type=MESSAGE_TYPE_INFO)
- void **sendMessage** (QString message, QString source, message_types type=MESSAGE_TYPE_INFO)
- QString **getMessageTypeName** (message_types type)
- virtual void **newMessage** (QString, message_types)

Friends

- class [UserMessageSlot](#)
- class [UserMessageSignal](#)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/include/UserMessage.h
- /home/rhydera/epicsqt/framework/widgets/src/UserMessage.cpp

9.113 UserMessageSignal Class Reference

Signals

- void **message** (QString msg, message_types type, unsigned int formId, unsigned int sourceId, [UserMessage](#) *originator)

Public Member Functions

- void **sendMessage** (QString msg, message_types type, unsigned int formId, unsigned int sourceId, [UserMessage](#) *originator)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/include/UserMessage.h
- /home/rhydera/epicsqt/framework/widgets/src/UserMessage.cpp

9.114 UserMessageSlot Class Reference

Public Slots

- void **message** (QString msg, message_types type, unsigned int formId, unsigned int sourceId, [UserMessage](#) *originator)

Public Member Functions


- void **setOwner** ([UserMessage](#) *ownerIn)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/include/UserMessage.h
- /home/rhydera/epicsqt/framework/widgets/src/UserMessage.cpp

9.115 VideoWidget Class Reference

Inheritance diagram for VideoWidget:



Signals

- void **userSelection** ([imageMarkup::markupIds](#) mode, [QPoint](#) point1, [QPoint](#) point2)
- void **zoomInOut** (int zoomAmount)
- void **currentPixelInfo** ([QPoint](#) pos)
- void **pan** ([QPoint](#) pos)

Public Member Functions

- **VideoWidget** ([QWidget](#) *parent=0)
- void **setNewImage** (const [QImage](#) image, [QCaDateTime](#) &time)
- void **setPanning** (bool panningIn)
- bool **getPanning** ()
- [QPoint](#) **scalePoint** ([QPoint](#) pnt)
- int **scaleOrdinate** (int ord)
- [QImage](#) **getImage** ()

Protected Member Functions

- void **paintEvent** ([QPaintEvent](#) *)
- void **mousePressEvent** ([QMouseEvent](#) *event)
- void **mouseReleaseEvent** ([QMouseEvent](#) *event)
- void **mouseMoveEvent** ([QMouseEvent](#) *event)

- void **wheelEvent** (QWheelEvent *event)
- void **markupChange** (QImage &markups, QVector< QRect > &changedAreas)
- void **resizeEvent** (QResizeEvent *event)
- void **markupSetCursor** (QCursor cursor)
- void **markupAction** (markupIds mode, QPoint point1, QPoint point2)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEImage/videowidget.h
- /home/rhydera/epicsqt/framework/widgets/QEImage/videowidget.cpp

9.116 WidgetRef Class Reference

Public Member Functions


- **WidgetRef** (QEWidget *refIn)
- QEWidget * **getRef** ()

The documentation for this class was generated from the following file:

- /home/rhydera/epicsqt/framework/widgets/include/ContainerProfile.h

9.117 qcastatemachine::WriteQCaStateMachine Class Reference

Inheritance diagram for qcastatemachine::WriteQCaStateMachine:



Public Member Functions

- **WriteQCaStateMachine** (void *parent)
- bool **process** (int requestedState)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/data/include/QCaStateMachine.h
- /home/rhydera/epicsqt/framework/data/src/QCaStateMachine.cpp

9.118 zoomMenu Class Reference

Public Member Functions

- **zoomMenu** (QWidget *parent=0)
- void **enableAreaSelected** (bool enable)
- imageContextMenu::imageContextMenuOptions **getZoom** (const QPoint &pos)

The documentation for this class was generated from the following files:

- /home/rhydera/epicsqt/framework/widgets/QEImage/zoomMenu.h
- /home/rhydera/epicsqt/framework/widgets/QEImage/zoomMenu.cpp

Index

- [_Field, 27](#)
 - [_Item, 28](#)
 - [_QDialogItem, 28](#)
 - [_QDialogLogin, 28](#)
 - [_QPushButtonGroup, 29](#)
 - [_QTableWidgetFileBrowser, 29](#)
 - [_QTableWidgetLog, 30](#)
 - [_QTableWidgetScript, 30](#)
- addUnits
 - [QEAAnalogProgressBar, 60](#)
 - [QELabel, 107](#)
 - [QELineEdit, 116](#)
- allowDrop
 - [QEAAnalogProgressBar, 60](#)
 - [QEBitStatus, 66](#)
 - [QEComboBox, 72](#)
 - [QEFrame, 84](#)
 - [QEGroupBox, 89](#)
 - [QEImage, 96](#)
 - [QELabel, 107](#)
 - [QELineEdit, 116](#)
 - [QEPeriodic, 130](#)
 - [QEPlot, 139](#)
 - [QEPushButton, 145](#)
 - [QEPvProperties, 149](#)
 - [QERadioButton, 156](#)
 - [QEShape, 168](#)
 - [QESlider, 177](#)
 - [QESpinBox, 182](#)
- altReadbackVariable
 - [QEPushButton, 145](#)
- animation1
 - [QEShape, 168](#)
- animation2
 - [QEShape, 168](#)
- animation3
 - [QEShape, 168](#)
- animation4
 - [QEShape, 168](#)
- animation5
 - [QEShape, 168](#)
- animation6
 - [QEShape, 168](#)
- animationOptions
 - [QEShape, 166](#)
- arrayAction
 - [QEAAnalogProgressBar, 61](#)
 - [QELabel, 107](#)
 - [QELineEdit, 116](#)
- beamXVariable
 - [QEImage, 96](#)
- beamYVariable
 - [QEImage, 96](#)
- clippingHighVariable
 - [QEImage, 96](#)
- clippingLowVariable
 - [QEImage, 97](#)
- clippingOnOffVariable
 - [QEImage, 97](#)
- color1
 - [QEShape, 169](#)
- color10
 - [QEShape, 169](#)
- color2
 - [QEShape, 169](#)
- color3
 - [QEShape, 169](#)
- color4
 - [QEShape, 169](#)
- color5
 - [QEShape, 169](#)
- color6
 - [QEShape, 169](#)
- color7
 - [QEShape, 169](#)
- color8
 - [QEShape, 169](#)
- color9
 - [QEShape, 170](#)

- confirmWrite
 - QELineEdit, [117](#)
- ContainerProfile, [31](#)
- contextMenu, [33](#)
- contextMenuObject, [35](#)
- dbElementChanged
 - QEPeriodic, [129](#)
- dbValueChanged
 - QEAnalogProgressBar, [60](#)
 - QEBitStatus, [66](#)
 - QEComboBox, [71](#)
 - QEImage, [96](#)
 - QELabel, [106](#)
 - QELineEdit, [115](#)
 - QEPeriodic, [129](#)
 - QEPlot, [138](#)
 - QEPushButton, [145](#)
 - QERadioButton, [155](#)
 - QESlider, [177](#)
 - QESpinBox, [182](#)
- dbValueChanged1
 - QEShape, [167](#)
- dbValueChanged2
 - QEShape, [167](#)
- dbValueChanged3
 - QEShape, [167](#)
- dbValueChanged4
 - QEShape, [167](#)
- dbValueChanged5
 - QEShape, [167](#)
- dbValueChanged6
 - QEShape, [167](#)
- enabled
 - QEAnalogProgressBar, [61](#)
 - QEBitStatus, [66](#)
 - QEComboBox, [72](#)
 - QEFrame, [84](#)
 - QEGroupBox, [89](#)
 - QEImage, [97](#)
 - QELabel, [107](#)
 - QELineEdit, [117](#)
 - QEPeriodic, [130](#)
 - QEPlot, [139](#)
 - QEPushButton, [145](#)
 - QEPvProperties, [149](#)
 - QERadioButton, [156](#)
 - QEShape, [170](#)
 - QESlider, [177](#)
 - QESpinBox, [182](#)
- flipRotateMenu, [36](#)
- format
 - QEAnalogProgressBar, [61](#)
 - QELabel, [107](#)
 - QELineEdit, [117](#)
- formatInteger
 - QEIntegerFormatting, [102](#)
- formatIntegerArray
 - QEIntegerFormatting, [102](#)
- formatValue
 - QEIntegerFormatting, [102](#)
- getConfirmWrite
 - QELineEdit, [115](#)
- getSubscribe
 - QELineEdit, [115](#)
- getWriteOnEnter
 - QELineEdit, [115](#)
- getWriteOnFinish
 - QELineEdit, [115](#)
- getWriteOnLoseFocus
 - QELineEdit, [115](#)
- heightVariable
 - QEImage, [97](#)
- imageContextMenu, [36](#)
- imageMarkup, [37](#)
- imageVariable
 - QEImage, [97](#)
- int
 - QEAnalogProgressBar, [61](#)
 - QEBitStatus, [66](#)
 - QEComboBox, [72](#)
 - QEFrame, [84](#)
 - QEGroupBox, [89](#)
 - QEImage, [97](#)
 - QELabel, [108](#)
 - QELineEdit, [117](#)
 - QEPeriodic, [130](#)
 - QEPlot, [139](#)
 - QEPushButton, [145](#)
 - QEPvProperties, [150](#)
 - QERadioButton, [156](#)
 - QEShape, [170](#)
 - QESlider, [178](#)
 - QESpinBox, [182](#)
- labelText

Generated on Wed Nov 21 2012 15:31:41 for EPICS QT Framework by Doxygen

- qcastatemachine::ReadQCaStateMachine, [QComboBox](#), [69](#)
[194](#)
- qcastatemachine::SubscriptionQCaStateMachine, [dbValueChanged](#), [71](#)
[198](#)
- qcastatemachine::WriteQCaStateMachine,
[205](#)
[requestEnabled](#), [71](#)
- QCaVariableNamePropertyManager, [55](#)
- QEAnalogIndicator, [55](#)
- QEAnalogIndicator::Band, [30](#)
- QEAnalogIndicator::BandList, [31](#)
- QEAnalogProgressBar, [57](#)
 - [addUnits](#), [60](#)
 - [allowDrop](#), [60](#)
 - [arrayAction](#), [61](#)
 - [dbValueChanged](#), [60](#)
 - [enabled](#), [61](#)
 - [format](#), [61](#)
 - [int](#), [61](#)
 - [leadingZero](#), [61](#)
 - [localEnumeration](#), [62](#)
 - [notation](#), [62](#)
 - [precision](#), [62](#)
 - [requestEnabled](#), [60](#)
 - [trailingZeros](#), [62](#)
 - [useDbPrecision](#), [62](#)
 - [userLevelEnabled](#), [62](#)
 - [userLevelEngineerStyle](#), [62](#)
 - [userLevelScientistStyle](#), [63](#)
 - [userLevelUserStyle](#), [63](#)
 - [userLevelVisibility](#), [63](#)
 - [variable](#), [63](#)
 - [variableAsToolTip](#), [63](#)
 - [variableSubstitutions](#), [63](#)
 - [visible](#), [64](#)
- QEBitStatus, [64](#)
 - [allowDrop](#), [66](#)
 - [dbValueChanged](#), [66](#)
 - [enabled](#), [66](#)
 - [int](#), [66](#)
 - [requestEnabled](#), [66](#)
 - [userLevelEnabled](#), [66](#)
 - [userLevelEngineerStyle](#), [67](#)
 - [userLevelScientistStyle](#), [67](#)
 - [userLevelUserStyle](#), [67](#)
 - [userLevelVisibility](#), [67](#)
 - [variable](#), [67](#)
 - [variableAsToolTip](#), [68](#)
 - [variableSubstitutions](#), [68](#)
 - [visible](#), [68](#)
- QEByteArray, [68](#)
- [QComboBox](#), [69](#)
 - [allowDrop](#), [72](#)
- [dbValueChanged](#), [71](#)
- [enabled](#), [72](#)
- [int](#), [72](#)
- [requestEnabled](#), [71](#)
- [subscribe](#), [72](#)
- [userLevelEnabled](#), [72](#)
- [userLevelEngineerStyle](#), [72](#)
- [userLevelScientistStyle](#), [73](#)
- [userLevelUserStyle](#), [73](#)
- [userLevelVisibility](#), [73](#)
- [variable](#), [73](#)
- [variableAsToolTip](#), [73](#)
- [variableSubstitutions](#), [73](#)
- [visible](#), [74](#)
- [writeOnChange](#), [71](#)
- QEConfiguredLayout, [74](#)
- QEConfiguredLayoutManager, [76](#)
- QEDragDrop, [76](#)
- QEFileBrowser, [78](#)
- QEFloating, [79](#)
- QEFloatingFormatting, [80](#)
- QEForm, [81](#)
- QEFrame, [82](#)
 - [allowDrop](#), [84](#)
 - [enabled](#), [84](#)
 - [int](#), [84](#)
 - [requestEnabled](#), [83](#)
 - [userLevelEnabled](#), [84](#)
 - [userLevelEngineerStyle](#), [84](#)
 - [userLevelScientistStyle](#), [84](#)
 - [userLevelUserStyle](#), [85](#)
 - [userLevelVisibility](#), [85](#)
 - [variableAsToolTip](#), [85](#)
 - [visible](#), [85](#)
- QEGenericButton, [86](#)
- QEGroupBox, [88](#)
 - [allowDrop](#), [89](#)
 - [enabled](#), [89](#)
 - [int](#), [89](#)
 - [requestEnabled](#), [89](#)
 - [userLevelEnabled](#), [89](#)
 - [userLevelEngineerStyle](#), [90](#)
 - [userLevelScientistStyle](#), [90](#)
 - [userLevelUserStyle](#), [90](#)
 - [userLevelVisibility](#), [90](#)
 - [variableAsToolTip](#), [90](#)
 - [visible](#), [91](#)
- QEImage, [91](#)

- allowDrop, [96](#)
- beamXVariable, [96](#)
- beamYVariable, [96](#)
- clippingHighVariable, [96](#)
- clippingLowVariable, [97](#)
- clippingOnOffVariable, [97](#)
- dbValueChanged, [96](#)
- enabled, [97](#)
- heightVariable, [97](#)
- imageVariable, [97](#)
- int, [97](#)
- regionOfInterestHVariable, [97](#)
- regionOfInterestWVariable, [97](#)
- regionOfInterestXVariable, [98](#)
- regionOfInterestYVariable, [98](#)
- requestEnabled, [96](#)
- targetTriggerVariable, [98](#)
- targetXVariable, [98](#)
- targetYVariable, [98](#)
- userLevelEnabled, [98](#)
- userLevelEngineerStyle, [98](#)
- userLevelScientistStyle, [99](#)
- userLevelUserStyle, [99](#)
- userLevelVisibility, [99](#)
- variableAsToolTip, [99](#)
- variableSubstitutions, [99](#)
- visible, [100](#)
- widthVariable, [100](#)
- QEInteger, [100](#)
- QEIntegerFormatting, [101](#)
 - formatInteger, [102](#)
 - formatIntegerArray, [102](#)
 - formatValue, [102](#)
- QELabel, [102](#)
 - addUnits, [107](#)
 - allowDrop, [107](#)
 - arrayAction, [107](#)
 - dbValueChanged, [106](#)
 - enabled, [107](#)
 - format, [107](#)
 - int, [108](#)
 - leadingZero, [108](#)
 - localEnumeration, [108](#)
 - notation, [108](#)
 - pixmap0, [108](#)
 - pixmap1, [108](#)
 - pixmap2, [108](#)
 - pixmap3, [109](#)
 - pixmap4, [109](#)
 - pixmap5, [109](#)
 - pixmap6, [109](#)
 - pixmap7, [109](#)
 - precision, [109](#)
 - QELabel, [106](#)
 - requestEnabled, [106](#)
 - trailingZeros, [109](#)
 - UPDATE_PIXMAP, [106](#)
 - UPDATE_TEXT, [106](#)
 - updateOption, [109](#)
 - updateOptions, [106](#)
 - useDbPrecision, [110](#)
 - userLevelEnabled, [110](#)
 - userLevelEngineerStyle, [110](#)
 - userLevelScientistStyle, [110](#)
 - userLevelUserStyle, [110](#)
 - userLevelVisibility, [110](#)
 - variable, [111](#)
 - variableAsToolTip, [111](#)
 - variableSubstitutions, [111](#)
 - visible, [111](#)
- QELineEdit, [111](#)
 - addUnits, [116](#)
 - allowDrop, [116](#)
 - arrayAction, [116](#)
 - confirmWrite, [117](#)
 - dbValueChanged, [115](#)
 - enabled, [117](#)
 - format, [117](#)
 - getConfirmWrite, [115](#)
 - getSubscribe, [115](#)
 - getWriteOnEnter, [115](#)
 - getWriteOnFinish, [115](#)
 - getWriteOnLoseFocus, [115](#)
 - int, [117](#)
 - leadingZero, [117](#)
 - localEnumeration, [117](#)
 - notation, [117](#)
 - precision, [118](#)
 - QELineEdit, [114](#)
 - requestEnabled, [115](#)
 - setConfirmWrite, [115](#)
 - setSubscribe, [115](#)
 - setWriteOnEnter, [116](#)
 - setWriteOnFinish, [116](#)
 - setWriteOnLoseFocus, [116](#)
 - subscribe, [118](#)
 - trailingZeros, [118](#)
 - useDbPrecision, [118](#)
 - userLevelEnabled, [118](#)
 - userLevelEngineerStyle, [118](#)

- userLevelScientistStyle, 118
 - userLevelUserStyle, 119
 - userLevelVisibility, 119
 - variable, 119
 - variableAsToolTip, 119
 - variableSubstitutions, 119
 - visible, 119
 - writeOnEnter, 120
 - writeOnFinish, 120
 - writeOnLoseFocus, 120
- QELineEditManager, 120
- QELink, 121
- QELog, 123
- QELogin, 125
- QEPeriodic, 126
 - allowDrop, 130
 - dbElementChanged, 129
 - dbValueChanged, 129
 - enabled, 130
 - int, 130
 - readbackLabelVariable1, 130
 - readbackLabelVariable2, 130
 - requestEnabled, 130
 - subscribe, 131
 - userLevelEnabled, 131
 - userLevelEngineerStyle, 131
 - userLevelScientistStyle, 131
 - userLevelUserStyle, 131
 - userLevelVisibility, 132
 - variableAsToolTip, 132
 - variableSubstitutions, 132
 - visible, 132
 - writeButtonVariable1, 132
 - writeButtonVariable2, 132
- QEPeriodic::elementInfoStruct, 35
- QEPeriodic::userInfoStructArray, 200
- QEPeriodicComponentData, 133
- QEPeriodicTaskMenu, 133
- QEPeriodicTaskMenuFactory, 133
- QEpicsPV, 134
- QEPlot, 135
 - allowDrop, 139
 - dbValueChanged, 138
 - enabled, 139
 - int, 139
 - requestEnabled, 138
 - userLevelEnabled, 139
 - userLevelEngineerStyle, 139
 - userLevelScientistStyle, 140
 - userLevelUserStyle, 140
 - userLevelVisibility, 140
 - variable1, 140
 - variable2, 140
 - variable3, 140
 - variable4, 141
 - variableAsToolTip, 141
 - variableSubstitutions, 141
 - visible, 141
- QEPushButton, 141
 - allowDrop, 145
 - altReadbackVariable, 145
 - dbValueChanged, 145
 - enabled, 145
 - int, 145
 - requestEnabled, 145
 - subscribe, 145
 - userLevelEnabled, 146
 - userLevelEngineerStyle, 146
 - userLevelScientistStyle, 146
 - userLevelUserStyle, 146
 - userLevelVisibility, 146
 - variable, 147
 - variableAsToolTip, 147
 - visible, 147
- QEPvProperties, 147
 - allowDrop, 149
 - enabled, 149
 - int, 150
 - requestEnabled, 149
 - userLevelEnabled, 150
 - userLevelEngineerStyle, 150
 - userLevelScientistStyle, 150
 - userLevelUserStyle, 150
 - userLevelVisibility, 151
 - variable, 151
 - variableAsToolTip, 151
 - variableSubstitutions, 151
 - visible, 151
- QEPvPropertiesManager, 152
- QERadioButton, 152
 - allowDrop, 156
 - dbValueChanged, 155
 - enabled, 156
 - int, 156
 - requestEnabled, 155
 - subscribe, 156
 - userLevelEnabled, 156
 - userLevelEngineerStyle, 156
 - userLevelScientistStyle, 157
 - userLevelUserStyle, 157

- userLevelVisibility, 157
- variable, 157
- variableAsToolTip, 157
- variableSubstitutions, 157
- visible, 158
- QERecipe, 158
- QEScript, 160
- QEShape, 162
 - allowDrop, 168
 - animation1, 168
 - animation2, 168
 - animation3, 168
 - animation4, 168
 - animation5, 168
 - animation6, 168
 - animationOptions, 166
 - color1, 169
 - color10, 169
 - color2, 169
 - color3, 169
 - color4, 169
 - color5, 169
 - color6, 169
 - color7, 169
 - color8, 169
 - color9, 170
 - dbValueChanged1, 167
 - dbValueChanged2, 167
 - dbValueChanged3, 167
 - dbValueChanged4, 167
 - dbValueChanged5, 167
 - dbValueChanged6, 167
 - enabled, 170
 - int, 170
 - offset1, 170
 - offset2, 170
 - offset3, 170
 - offset4, 170
 - offset5, 171
 - offset6, 171
 - point1, 171
 - point10, 171
 - point2, 171
 - point3, 171
 - point4, 171
 - point5, 171
 - point6, 171
 - point7, 172
 - point8, 172
 - point9, 172
 - QEShape, 167
 - requestEnabled, 168
 - scale2, 172
 - scale3, 172
 - scale4, 172
 - scale5, 172
 - scale6, 172
 - shapeOptions, 166
 - userLevelEnabled, 172
 - userLevelEngineerStyle, 173
 - userLevelScientistStyle, 173
 - userLevelUserStyle, 173
 - userLevelVisibility, 173
 - variable1, 173
 - variable2, 174
 - variable3, 174
 - variable4, 174
 - variable5, 174
 - variable6, 174
 - variableAsToolTip, 174
 - variableSubstitutions, 174
 - visible, 175
- QESlider, 175
 - allowDrop, 177
 - dbValueChanged, 177
 - enabled, 177
 - int, 178
 - requestEnabled, 177
 - subscribe, 178
 - userLevelEnabled, 178
 - userLevelEngineerStyle, 178
 - userLevelScientistStyle, 178
 - userLevelUserStyle, 179
 - userLevelVisibility, 179
 - variable, 179
 - variableAsToolTip, 179
 - variableSubstitutions, 179
 - visible, 179
 - writeOnChange, 177
- QESpinBox, 180
 - allowDrop, 182
 - dbValueChanged, 182
 - enabled, 182
 - int, 182
 - requestEnabled, 182
 - subscribe, 183
 - userLevelEnabled, 183
 - userLevelEngineerStyle, 183
 - userLevelScientistStyle, 183
 - userLevelUserStyle, 183

- userLevelVisibility, 184
 - variable, 184
 - variableAsToolTip, 184
 - variableSubstitutions, 184
 - visible, 184
- QString, 185
- QStringFormatting, 185
- QStringFormattingMethods, 186
- QStripChart, 187
- QStripChart::PrivateData, 46
- QStripChartItem, 189
- QStripChartItem::PrivateData, 47
- QStripChartItemDialog, 190
- QStripChartTimeDialog, 190
- QSubstitutedLabel, 190
 - labelText, 191
 - textSubstitutions, 191
- QToolTip, 191
- QWidget, 192
- QWidgets, 194
- readbackLabelVariable1
 - QEPeiodic, 130
- readbackLabelVariable2
 - QEPeiodic, 130
- RecordSpec, 195
- RecordSpecList, 195
- regionOfInterestHVariable
 - QEImage, 97
- regionOfInterestWVariable
 - QEImage, 97
- regionOfInterestXVariable
 - QEImage, 98
- regionOfInterestYVariable
 - QEImage, 98
- requestEnabled
 - QEAnalogProgressBar, 60
 - QEBitStatus, 66
 - QEComboBox, 71
 - QEFrame, 83
 - QEGroupBox, 89
 - QEImage, 96
 - QELabel, 106
 - QELineEdit, 115
 - QEPeiodic, 130
 - QEPlot, 138
 - QEPushButton, 145
 - QEPvProperties, 149
 - QERadioButton, 155
 - QEShape, 168
 - QESlider, 177
 - QESpinBox, 182
 - scale2
 - QEShape, 172
 - scale3
 - QEShape, 172
 - scale4
 - QEShape, 172
 - scale5
 - QEShape, 172
 - scale6
 - QEShape, 172
 - selectMenu, 196
 - setConfirmWrite
 - QELineEdit, 115
 - setSubscribe
 - QELineEdit, 115
 - setWriteOnEnter
 - QELineEdit, 116
 - setWriteOnFinish
 - QELineEdit, 116
 - setWriteOnLoseFocus
 - QELineEdit, 116
 - shapeOptions
 - QEShape, 166
 - standardProperties, 196
 - StateMachineTemplate, 198
 - subscribe
 - QEComboBox, 72
 - QELineEdit, 118
 - QEPeiodic, 131
 - QEPushButton, 145
 - QERadioButton, 156
 - QESlider, 178
 - QESpinBox, 183
 - targetTriggerVariable
 - QEImage, 98
 - targetXVariable
 - QEImage, 98
 - targetYVariable
 - QEImage, 98
 - textSubstitutions
 - QESubstitutedLabel, 191
 - trace, 199
 - TrackRange, 199
 - trailingZeros
 - QEAnalogProgressBar, 62
 - QELabel, 109

- QELineEdit, [118](#)
- UPDATE_PIXMAP
 - QELabel, [106](#)
- UPDATE_TEXT
 - QELabel, [106](#)
- updateOption
 - QELabel, [109](#)
- updateOptions
 - QELabel, [106](#)
- useDbPrecision
 - QEAnalogProgressBar, [62](#)
 - QELabel, [110](#)
 - QELineEdit, [118](#)
- userInfoStruct, [200](#)
- userLevelEnabled
 - QEAnalogProgressBar, [62](#)
 - QEBitStatus, [66](#)
 - QEComboBox, [72](#)
 - QEFrmae, [84](#)
 - QEGroupBox, [89](#)
 - QEImage, [98](#)
 - QELabel, [110](#)
 - QELineEdit, [118](#)
 - QEPeiodic, [131](#)
 - QEPlot, [139](#)
 - QEPushButton, [146](#)
 - QEPvProperties, [150](#)
 - QERadioButton, [156](#)
 - QEShape, [172](#)
 - QESlider, [178](#)
 - QESpinBox, [183](#)
- userLevelEngineerStyle
 - QEAnalogProgressBar, [62](#)
 - QEBitStatus, [67](#)
 - QEComboBox, [72](#)
 - QEFrmae, [84](#)
 - QEGroupBox, [90](#)
 - QEImage, [98](#)
 - QELabel, [110](#)
 - QELineEdit, [118](#)
 - QEPeiodic, [131](#)
 - QEPlot, [139](#)
 - QEPushButton, [146](#)
 - QEPvProperties, [150](#)
 - QERadioButton, [156](#)
 - QEShape, [173](#)
 - QESlider, [178](#)
 - QESpinBox, [183](#)
- userLevelScientistStyle
 - QEAnalogProgressBar, [63](#)
 - QEBitStatus, [67](#)
 - QEComboBox, [73](#)
 - QEFrmae, [84](#)
 - QEGroupBox, [90](#)
 - QEImage, [99](#)
 - QELabel, [110](#)
 - QELineEdit, [118](#)
 - QEPeiodic, [131](#)
 - QEPlot, [140](#)
 - QEPushButton, [146](#)
 - QEPvProperties, [150](#)
 - QERadioButton, [157](#)
 - QEShape, [173](#)
 - QESlider, [178](#)
 - QESpinBox, [183](#)
- userLevelSignal, [200](#)
- userLevelSlot, [201](#)
- userLevelUserStyle
 - QEAnalogProgressBar, [63](#)
 - QEBitStatus, [67](#)
 - QEComboBox, [73](#)
 - QEFrmae, [85](#)
 - QEGroupBox, [90](#)
 - QEImage, [99](#)
 - QELabel, [110](#)
 - QELineEdit, [119](#)
 - QEPeiodic, [131](#)
 - QEPlot, [140](#)
 - QEPushButton, [146](#)
 - QEPvProperties, [150](#)
 - QERadioButton, [157](#)
 - QEShape, [173](#)
 - QESlider, [179](#)
 - QESpinBox, [183](#)
- userLevelVisibility
 - QEAnalogProgressBar, [63](#)
 - QEBitStatus, [67](#)
 - QEComboBox, [73](#)
 - QEFrmae, [85](#)
 - QEGroupBox, [90](#)
 - QEImage, [99](#)
 - QELabel, [110](#)
 - QELineEdit, [119](#)
 - QEPeiodic, [132](#)
 - QEPlot, [140](#)
 - QEPushButton, [146](#)
 - QEPvProperties, [151](#)
 - QERadioButton, [157](#)
 - QEShape, [173](#)

writeOnLoseFocus

zoomMenu, [206](#)