Z39.50 server file

When you select the **Z39.50 server file** menu option in Admin Corner, the Z39.50 SERVERS screen displays. For example:

```
                                Z39.50 SERVERS

      1 > RLIN
      2 > OCLC FirstSearch Databases
      3 > Univ. of Calif. MELVYL system
      4 > Univ. Wisconsin-Madison (NLC code)
      5 > Indiana Univ (NOTIS)
      6 > Penn State University
      7 > CARL Systems
      8 > Library of Congress
      9 > Acadia University
_____________________________________________________________________________
Select server to edit or
A > ADD server        Z > Z39.50 Server     Q > QUIT
D > DELETE server     M > MOVE line
Choose one (1-9,A,D,Z,M,Q)
```

The numbered entries represent remote servers listed in your system's Z39.50 server file.

The **Z39.50 server file** menu option and its submenus are used to configure Innovative's separately available Z39.50 server and Z39.50 client programs.

- The Z39.50 server program allows your library to run a Z39.50 server. A Z39.50 server hosts databases that can be accessed by anyone using the Z39.50 protocol.
- The Z39.50 client program allows you to use the Z39.50 protocol to access databases hosted remotely (for example, by another library). The Z39.50 client program provides the "remote search" feature in the following Innovative products:
    - Sierra
    - Inter-Library Loan
    - WebPAC

> **Z39.50 Searches and User Licenses**
>
> Initiating a Z39.50 (remote) search through your library's WebPAC, which causes the Innovative Z39.50 client to contact the Z39.50 server of another library, uses a user license.
>
> When the Innovative Z39.50 server at your library responds to a request from a Z39.50 client at another library, a user license is used to grant access to the requesting client.

Setting Up the Z39.50 Client (Remote Searching)

Remote searching from Sierra, ILL, and WebPAC uses the Z39.50 client program.

When the Z39.50 client program is installed, Innovative staff enter a number of example remote servers and databases into the Z39.50 server file. Before you can use the Z39.50 client program, or when the servers accessible to your library change, you must edit this file.

> After you edit your Z39.50 server file, you must restart the WebPAC in order to see your changes.

To set up the Z39.50 client program:

1. Add server entries to the Z39.50 server file (each entry represents a remote server).
2. Add databases to each server entry in the Z39.50 server file. Each server might offer multiple databases. For example, the MELVYL server offers two databases; the Full catalog and the Periodicals catalog databases.
3. If necessary, edit server entries in the Z39.50 server file.

4. Delete unused entries in the Z39.50 server file. You may delete the example entries provided during installation of your system.
5. Move the server entries in the Z39.50 server file into your preferred order.

Editing Server Entries in the Z39.50 Server File

To edit an entry in the Z39.50 server file:

1. Choose the **Z39.50 server file** option in Admin Corner. The Z39.50 server file displays:

```
                                Z39.50 SERVERS

      1 > RLIN
      2 > OCLC FirstSearch Databases
      3 > Univ. of Calif. MELVYL system
      4 > Univ. Wisconsin-Madison (NLC code)
      5 > Indiana Univ (NOTIS)
      6 > Penn State University
      7 > CARL Systems
      8 > Library of Congress
      9 > Acadia University
_____________________________________________________________________________
Select server to edit or
A > ADD server          Z > Z39.50 Server      Q > QUIT
D > DELETE server       M > MOVE line
Choose one (1-9,A,D,Z,M,Q)
```

2. Enter the number for the server. The SERVER entry displays:

```
SERVER - Some University

        1 > Library Catalog
_____________________________________________________________________________
Select server to edit or
E > Edit server information        D > DELETE database        Q > QUIT
A > ADD database                   M > MOVE line
Choose one (1-1,E,A,D,M,Q)
```

3. Choose **E > Edit server information**. The SERVER INFORMATION displays:

```
SERVER INFORMATION

      1 > Internal code for server:  SOMEUNI
      2 > Display name for server:   Some University
      3 > IP address of server:      110.110.101.101
      4 > Port:                      210
      5 > Authentication/Password:
      6 > Character Set:
      7 > Enable SCAN Facility?      NO
_____________________________________________________________________________
Key a number or
Q > QUIT
Choose one (1-7,Q)
```

4. Choose a number and enter the correct information.
5. Save and quit.

© 2014 Innovative Interfaces, Inc.