

PYTHON LISTS, DICTIONARIES, AND DATA ABSTRACTION

CS 61A

July 7, 2021

1 Lists

Lists Introduction:

Lists are a type of sequence, which is to say they're ordered collections of values that have both a length and the ability to select elements.

```
>>> lst = [1, False, [2, 3], 4] # a list can contain anything
>>> len(lst)
4
>>> lst[0] # Indexing starts at 0
1
>>> lst[4] # Indexing ends at len(lst) - 1
Error: list index out of range
```

We can iterate over lists using their index, or iterate over elements directly

```
for index in range(len(lst)):
    # do things
for item in lst:
    # do things
```

List comprehensions are a useful way to iterate over lists when your desired result is a list.

```
new_list2 = [<expression> for <element> in <sequence> if <
    condition>]
```

We can use **list slicing** to create a copy of a certain portion or all of a list.

```
new_list = lst[<starting index>:<ending index>]  
copy = lst[:]
```

1. What would Python display? Draw box-and-pointer diagrams for the following:

```
>>> a = [1, 2, 3]  
>>> a
```

```
>>> a[2]
```

```
>>> b = a  
>>> a = a + [4, [5, 6]]  
>>> a
```

```
>>> b
```

```
>>> c = a  
>>> a = [4, 5]  
>>> a
```

```
>>> c
```

```
>>> d = c[3:5]
>>> c[3] = 9
>>> d
```

```
>>> c[4][0] = 7
>>> d
```

```
>>> c[4] = 10
>>> d
```

```
>>> c
```

2. Draw the environment diagram that results from running the code.

```
def reverse(lst):
    if len(lst) <= 1:
        return lst
    return reverse(lst[1:]) + [lst[0]]
```

```
lst = [1, [2, 3], 4]
rev = reverse(lst)
```

3. Write a function that takes in a list `nums` and returns a new list with only the primes from `nums`. Assume that `is_prime(n)` is defined. You may use a `while` loop, a `for` loop, or a list comprehension.

```
def all_primes(nums):
```

4. Write a list comprehension that accomplishes each of the following tasks.

(a) Square all the elements of a given list, `lst`.

(b) Compute the dot product of two lists `lst1` and `lst2`. *Hint:* The dot product is defined as $lst1[0] \cdot lst2[0] + lst1[1] \cdot lst2[1] + \dots + lst1[n] \cdot lst2[n]$. The Python `zip` function may be useful here.

(c) Return a list of lists such that `a = [[0], [0, 1], [0, 1, 2], [0, 1, 2, 3], [0, 1, 2, 3, 4]]`.

(d) Return the same list as above, except now excluding every instance of the number 2: `b = [[0], [0, 1], [0, 1], [0, 1, 3], [0, 1, 3, 4]]`.

2 Dictionaries

Dictionaries are data structures that map keys to values. In Python, the key-value pairs in a dictionary are unordered.

1. Write a function `replace_all` that replaces all occurrences of `x` as a value (not a key) in `d` with `y`.

```
def replace_all(d, x, y):
    """Replace all occurrences of x as a value (not a key) in
        d with y.
    >>> d = {3: '3', 'foo': 2, 'bar': 3, 'garply': 3, 'xyzzzy':
        99}
    >>> replace_all(d, 3, 'poof')
    >>> d == {3: '3', 'foo': 2, 'bar': 'poof', 'garply': 'poof',
        'xyzzzy': 99}
    True
    """
```

2. Write a function `counter` that takes in an input string, `message`, and returns a dictionary that maps each unique word in `message` to the number of times it appears.

```
def counter(message):  
    """ Returns a dictionary of each word in message mapped  
    to the number of times it appears in the input string.  
    >>> x = counter('to be or not to be')  
    >>> x['to']  
    2  
    >>> x['be']  
    2  
    >>> x['not']  
    1  
    >>> y = counter('run forrest run')  
    >>> y['run']  
    2  
    >>> y['forrest']  
    1  
    """  
    word_list = message.split() # .split() returns a list of  
    the words in the string. Try printing it!
```

3 Abstraction

Data Abstraction Overview:

Abstraction allows us to create and access different types of data through a controlled, restricted programming interface, hiding implementation details and encouraging programmers to focus on how data is used, rather than how data is organized. The two fundamental components of a programming interface are a constructor and selectors.

1. **Constructor:** The interface that creates a piece of data; e.g. calling `c = car("Tesla")` creates a new car object and assigns it to the variable `c`.
2. **Selectors:** The interface by which we access attributes of a piece of data; e.g. calling `get_brand(c)` should return `"Tesla"`.

Through constructors and selectors, a data type can hide its implementation, and a programmer doesn't need to *know* its implementation to *use* it.

1. The following is an **Abstract Data Type (ADT)** for elephants. Each elephant keeps track of its name, age, and whether or not it can fly. Given our provided constructor, fill out the selectors:

```
def elephant(name, age, can_fly):  
    """  
    Takes in a string name, an int age, and a boolean can_fly.  
    Constructs an elephant with these attributes.  
    >>> dumbo = elephant("Dumbo", 10, True)  
    >>> elephant_name(dumbo)  
    "Dumbo"  
    >>> elephant_age(dumbo)  
    10  
    >>> elephant_can_fly(dumbo)  
    True  
    """  
    return [name, age, can_fly]  
  
def elephant_name(e):
```

```
def elephant_age(e):
```

```
def elephant_can_fly(e):
```

2. This function returns the correct result, but there's something wrong about its implementation. How do we fix it?

```
def elephant_roster(elephants):  
    """  
    Takes in a list of elephants and returns a list of their  
    names.  
    """  
    return [elephant[0] for elephant in elephants]
```


3. Fill out the following constructor for the given selectors.

```
def elephant(name, age, can_fly):
```

```
    def elephant_name(e):  
        return e[0][0]
```

```
    def elephant_age(e):  
        return e[0][1]
```

```
    def elephant_can_fly(e):  
        return e[1]
```

4. How can we write the fixed `elephant_roster` function for the constructors and selectors in the previous question?

5. (Optional) Fill out the following constructor for the given selectors.

```
def elephant(name, age, can_fly):
    """
    >>> alex = elephant("Alex Kassil", 22, False)
    >>> elephant_name(alex)
    "Alex Kassil"
    >>> elephant_age(alex)
    22
    >>> elephant_can_fly(alex)
    False
    >> alex("size")
    "Breaking abstraction barrier!"
    """
    def select(command):

        return select

    def elephant_name(e):
        return e("name")

    def elephant_age(e):
        return e("age")

    def elephant_can_fly(e):
        return e("can_fly")
```