

In []:

```
from pandas import DataFrame
from pandas import Series
from pandas import concat
from pandas import read_csv
from pandas import datetime
from sklearn.metrics import mean_squared_error
from sklearn.preprocessing import MinMaxScaler
from keras.models import Sequential
from keras.layers import Dense
from keras.layers import LSTM
from math import sqrt
from matplotlib import pyplot
from numpy import array

# Credit: https://machinelearningmastery.com/multi-step-time-series-forecasting-long-short-term-memory-networks-python/

# convert time series into supervised learning problem
def series_to_supervised(data, n_in=1, n_out=1, dropnan=True):
    n_vars = 1 if type(data) is list else data.shape[1]
    df = DataFrame(data)
    cols, names = list(), list()
    # input sequence (t-n, ... t-1)
    for i in range(n_in, 0, -1):
        cols.append(df.shift(i))
        names += [('var%d(t-%d)' % (j+1, i)) for j in range(n_vars)]
    # forecast sequence (t, t+1, ... t+n)
    for i in range(0, n_out):
        cols.append(df.shift(-i))
        if i == 0:
            names += [('var%d(t)' % (j+1)) for j in range(n_vars)]
        else:
            names += [('var%d(t+%d)' % (j+1, i)) for j in range(n_vars)]
    # put it all together
    agg = concat(cols, axis=1)
    agg.columns = names
    # drop rows with NaN values
    if dropnan:
        agg.dropna(inplace=True)
    return agg

# create a differenced series
def difference(dataset, interval=1):
    diff = list()
    for i in range(interval, len(dataset)):
        value = dataset[i] - dataset[i - interval]
        diff.append(value)
    return Series(diff)

# transform series into train and test sets for supervised learning
def prepare_data(series, n_test, n_lag, n_seq):
    # extract raw values
    raw_values = series.values
    # transform data to be stationary
    diff_series = difference(raw_values, 1)
```

```

diff_values = diff_series.values
diff_values = diff_values.reshape(len(diff_values), 1)
# rescale values to -1, 1
scaler = MinMaxScaler(feature_range=(-1, 1))
scaled_values = scaler.fit_transform(diff_values)
scaled_values = scaled_values.reshape(len(scaled_values), 1)
# transform into supervised learning problem X, y
supervised = series_to_supervised(scaled_values, n_lag, n_seq)
supervised_values = supervised.values
# split into train and test sets
train, test = supervised_values[0:-n_test], supervised_values[-n_test:]
return scaler, train, test

# fit an LSTM network to training data
def fit_lstm(train, n_lag, n_seq, n_batch, nb_epoch, n_neurons):
    # reshape training into [samples, timesteps, features]
    X, y = train[:, 0:n_lag], train[:, n_lag:]
    X = X.reshape(X.shape[0], 1, X.shape[1])
    # design network
    model = Sequential()
    model.add(LSTM(n_neurons, batch_input_shape=(n_batch, X.shape[1],
X.shape[2]), stateful=True))
    model.add(Dense(y.shape[1]))
    model.compile(loss='mean_squared_error', optimizer='adam')
    # fit network
    for i in range(nb_epoch):
        model.fit(X, y, epochs=1, batch_size=n_batch, verbose=1, shuffle=False)
        model.reset_states()
    return model

# make one forecast with an LSTM,
def forecast_lstm(model, X, n_batch):
    # reshape input pattern to [samples, timesteps, features]
    X = X.reshape(1, 1, len(X))
    # make forecast
    forecast = model.predict(X, batch_size=n_batch)
    # convert to array
    return [x for x in forecast[0, :]]

# evaluate the persistence model
def make_forecasts(model, n_batch, train, test, n_lag, n_seq):
    forecasts = list()
    for i in range(len(test)):
        X, y = test[i, 0:n_lag], test[i, n_lag:]
        # make forecast
        forecast = forecast_lstm(model, X, n_batch)
        # store the forecast
        forecasts.append(forecast)
    return forecasts

# invert differenced forecast
def inverse_difference(last_ob, forecast):
    # invert first forecast
    inverted = list()
    inverted.append(forecast[0] + last_ob)
    # propagate difference forecast using inverted first value
    for i in range(1, len(forecast)):
        inverted.append(forecast[i] + inverted[i-1])
    return inverted

```

```

# inverse data transform on forecasts
def inverse_transform(series, forecasts, scaler, n_test):
    inverted = list()
    for i in range(len(forecasts)):
        # create array from forecast
        forecast = array(forecasts[i])
        forecast = forecast.reshape(1, len(forecast))
        # invert scaling
        inv_scale = scaler.inverse_transform(forecast)
        inv_scale = inv_scale[0, :]
        # invert differencing
        index = len(series) - n_test + i - 1
        last_ob = series.values[index]
        inv_diff = inverse_difference(last_ob, inv_scale)
        # store
        inverted.append(inv_diff)
    return inverted

# evaluate the RMSE for each forecast time step
def evaluate_forecasts(test, forecasts, n_lag, n_seq):
    for i in range(n_seq):
        actual = [row[i] for row in test]
        predicted = [forecast[i] for forecast in forecasts]
        rmse = sqrt(mean_squared_error(actual, predicted))
        print('t+%d RMSE: %f' % ((i+1), rmse))

# plot the forecasts in the context of the original dataset
def plot_forecasts(series, forecasts, n_test):
    # plot the entire dataset in blue
    pyplot.plot(series.values)
    # plot the forecasts in red
    for i in range(len(forecasts)):
        off_s = len(series) - n_test + i - 1
        off_e = off_s + len(forecasts[i]) + 1
        xaxis = [x for x in range(off_s, off_e)]
        yaxis = [series.values[off_s]] + forecasts[i]
        pyplot.plot(xaxis, yaxis, color='red')
    # show the plot
    pyplot.xlabel("Time (days)")
    pyplot.ylabel("Price")
    pyplot.title("Amazon Closing Prices")
    pyplot.show()

if __name__ == '__main__':
    # Load the data
    amazon = read_csv('data/AMZN_2006-01-01_to_2017-11-01.csv')
    series = amazon['Close'][2000:2600]

    # configure
    n_lag = 5
    n_seq = 5
    n_test = 50
    n_epochs = 5
    n_batch = 1
    n_neurons = 8

    # prepare data
    scaler, train, test = prepare_data(series, n_test, n_lag, n_seq)

    # fit model

```

```
# fit model
model = fit_lstm(train, n_lag, n_seq, n_batch, n_epochs, n_neurons)

# make forecasts
forecasts = make_forecasts(model, n_batch, train, test, n_lag, n_seq)

# inverse transform forecasts and test
forecasts = inverse_transform(series, forecasts, scaler, n_test+2)
actual = [row[n_lag:] for row in test]
actual = inverse_transform(series, actual, scaler, n_test+2)

# evaluate forecasts
evaluate_forecasts(actual, forecasts, n_lag, n_seq)

# plot forecasts
plot_forecasts(series, forecasts, n_test+2)
```