OpenML-Python: an extensible Python API for OpenML

Matthias Feurer FEURERM@CS.UNI-FREIBURG.DE

University of Freiburg, Freiburg, Germany

Jan N. van Rijn J.N.VAN.RIJN@LIACS.LEIDENUNIV.NL

Leiden University, Leiden, Netherlands

Arlind Kadra Kadraa@cs.uni-freiburg.de

University of Freiburg, Freiburg, Germany

Pieter Gijsbers P.GIJSBERS@TUE.NL

 $Eindhoven\ University\ of\ Technology,\ Eindhoven,\ Netherlands$

Neeratyoy Mallik Mallik@cs.uni-freiburg.de

University of Freiburg, Freiburg, Germany

Sahithya Ravi S.RAVI@TUE.NL

Eindhoven University of Technology, Eindhoven, Netherlands

Andreas Müller Acm2248@columbia.edu

Columbia University, New York, USA

JOAQUIN Vanschoren J.VANSCHOREN@TUE.NL

Eindhoven University of Technology, Eindhoven, Netherlands

Frank Hutter FH@CS.UNI-FREIBURG.DE

University of Freiburg, Freiburg & Bosch Center for Artificial Intelligence, Germany

Abstract

OpenML is an online platform for open science collaboration in machine learning, used to share datasets and results of machine learning experiments. In this paper we introduce *OpenML-Python*, a client API for Python, opening up the OpenML platform for a wide range of Python-based tools. It provides easy access to all datasets, tasks and experiments on OpenML from within Python. It also provides functionality to conduct machine learning experiments, upload the results to OpenML, and reproduce results which are stored on OpenML. Furthermore, it comes with a scikit-learn plugin and a plugin mechanism to easily integrate other machine learning libraries written in Python into the OpenML ecosystem. Source code and documentation is available at https://github.com/openml/openml-python/.

Keywords: Python, Collaborative Science, Meta-Learning, Reproducible Research

1. Introduction

OpenML is a collaborative online machine learning (ML) platform, meant for sharing and building on prior empirical machine learning research (Vanschoren et al., 2014).

It goes beyond open data repositories, such as UCI (Dua and Graff, 2017), PMLB (Olson et al., 2018), the 'datasets' submodules in scikit-learn (Pedregosa et al., 2011) and tensor-

©2019 Matthias Feurer, Jan N. van Rijn, Arlind Kadra, Pieter Gijsbers, Neeratyoy Mallik, Sahithya Ravi, Andreas Müller, Joaquin Vanschoren and Frank Hutter.

License: CC-BY 4.0, see https://creativecommons.org/licenses/by/4.0/.

flow (Abadi et al., 2016), and the closed-source data sharing platform at Kaggle.com, since OpenML also collects millions of shared experiments on these datasets, linked to the exact ML pipelines and hyperparameter settings, and includes comprehensive logging and uploading functionalities which can be accessed programmatically via a REST API. However, sharing ML experiments adds significant complexity to most people's workflows.

OpenML-Python is a seamless integration of OpenML into the popular Python ML ecosystem¹, that takes away this complexity by providing easy programmatic access to all OpenML data and automating the sharing of new experiments.² In this paper, we introduce OpenML-Python's core design, showcase its extensibility to new ML libraries, and give code examples for several common research tasks.

2. Use cases for the OpenML-Python API

OpenML-Python allows for easy dataset and experiment sharing by handling all communication with OpenML's REST API. In this section, we briefly describe how the package can be used in several common machine learning tasks and highlight recent uses.

Working with datasets. OpenML-Python can retrieve the thousands of datasets on OpenML (all of them, or specific subsets) in a unified format, retrieve meta-data describing them, and search through them with filters. Datasets are converted from OpenML's internal format into numpy, scipy or pandas data structures, which are standard for ML in Python. To facilitate contributions from the community, it allows people to upload new datasets in only two function calls, and to define new tasks on them (combinations of a dataset, train/test split and target attribute).

Publishing and retrieving results. Sharing empirical results allows anyone to search and download them in order to reproduce and reuse them in their own research. One goal of OpenML is to simplify the comparison of new algorithms and implementations to existing approaches by comparing to the results on OpenML. To this end we also provide an interface for integrating new machine learning libraries with OpenML and we have already integrated *scikit-learn*. OpenML-Python can then be used to set up and conduct machine learning experiments for a given *task* and *flow* (an ML pipeline including hyperparameters and random states), and publish reproducible results.

Use cases in published works. OpenML-Python has already been used to scale up studies with hundreds of consistently formatted datasets (Feurer et al., 2015; Fusi et al., 2018), supply large amounts of meta-data for meta-learning (Perrone et al., 2018), answer questions about algorithms such as hyperparameter importance (van Rijn and Hutter, 2018) and facilitate large-scale comparisons of algorithms (Strang et al., 2018).

3. High-level Design of OpenML-Python

The OpenML platform is organized around several entity types which describe different aspects of a machine learning study. It hosts *datasets*, *tasks* that define how models should be evaluated on them. *flows* that record the structure and other details of ML pipelines, and

^{1.} https://github.blog/2019-01-24-the-state-of-the-octoverse-machine-learning/

^{2.} Other clients already exist for R (Casalicchio et al., 2017) and Java (van Rijn, 2016).

Figure 1: Code for retrieving the predictive accuracy of an SVM classifier on the 'letter' dataset and creating a contour plot with the results.

runs that record the experiments evaluating specific flows on certain tasks. For instance, an experiment (run) shared on OpenML can show how a random forest (flow) performs on 'iris' (dataset) if evaluated with 10-fold cross-validation (task), and how to reproduce that result. In OpenML-Python, all these entities are represented by classes, each defined in their own submodule. This implements a natural mapping from OpenML concepts to Python objects. While OpenML is an online platform, we facilitate offline usage as well.


Plugins. To allow users to automatically run and share machine learning experiments with different libraries through the same OpenML-Python interface, we designed a plugin interface that standardizes the interaction between machine learning library code and OpenML-Python. We also created a plugin for *scikit-learn* (Pedregosa et al., 2011), as it is one of the most popular Python machine learning libraries. This plugin can be used for any library which follows the *scikit-learn* API (Buitinck et al., 2013).

A plugin's responsibility is to convert between the libraries' models and OpenML flows, interact with its training interface and format predictions. For example, the *scikit-learn* plugin can convert an *OpenMLFlow* to an Estimator (including hyperparameter settings), train models and produce predictions for a task, and create an *OpenMLRun* object to upload the predictions to the OpenML server. The plugin also handles advanced procedures, such as *scikit-learn*'s random search or grid search and uploading its traces (hyperparameters and scores of each model evaluated during search).

We are working on more plugins, and anyone can contribute their own using the scikit-learn plugin implementation as a reference.

4. Examples

We show two example uses of OpenML-Python to demonstrate its API's simplicity. First, we show how to retrieve results and evaluations from the OpenML server in Figure 1 (generating the plot on the right).



SVM hyperparameter contour plot generated by the code in Figure 1.

Figure 2: Training and evaluating a decision tree classifier from scikit-learn on each task of the OpenML-CC18 benchmark suite (Bischl et al., 2019).

Second, in Figure 2 we show how to conduct experiments on a benchmark suite (Bischl et al., 2019). Further examples, including how to create datasets and tasks and how OpenML-Python was used in previous publications, can be found in the online documentation.³

5. Project development

The project has been set up for development through community effort from different research groups, and has received contributions from numerous individuals. The package is developed publicly through Github which also provides an issue tracker for bug reports, feature requests and usage questions. To ensure a coherent and robust code base we use continuous integration for Windows and Linux as well as automated type and style checking. Documentation is also rendered on continuous integration servers and consists of a mix of tutorials, examples and API documentation.

For ease of use and stability, we use well-known and established third-party packages where needed. For instance, we build documentation using the popular $sphinx\ Python\ documentation\ generator^4$, use an extension to automatically compile examples into documentation and Jupyter notebooks⁵, and employ standard open-source packages for scientific computing such as numpy, scipy (Virtanen et al., 2019), and pandas (McKinney, 2010). The package is written in Python3 and open-sourced with a 3-Clause BSD License.³

6. Conclusion

OpenML-Python allows easy interaction with OpenML from within Python. It makes it easy for people to share and reuse the data, meta-data, and empirical results which are generated as part of an ML study. This allows for better reproducibility, simpler benchmarking and easier collaboration on ML projects. Our software is shipped with a scikit-learn plugin and has a plugin mechanism to easily integrate other ML libraries written in Python.

^{3.} We provide documentation and code examples on http://openml.github.io/openml-python and host the project on http://github.com/openml/openml-python.

Acknowledgments

MF, NM and FH acknowledge funding by the Robert Bosch GmbH. AK, JvR and FH acknowledge funding by the European Research Council (ERC) under the European Union's Horizon 2020 research and innovation programme under grant no. 716721. JV and PG acknowledge funding by the Data Driven Discovery of Models (D3M) program run by DARPA and the Air Force Research Laboratory. The authors also thank Bilge Celik, Victor Gal and everyone listed at https://github.com/openml/openml-python/graphs/contributors for their contributions.

References

- M. Abadi, A. Agarwal, P. Barham, E. Brevdo, Z. Chen, C. Citro, G. S. Corrado, A. Davis, J. Dean, M. Devin, et al. TensorFlow: Large-Scale Machine Learning on Heterogeneous Distributed Systems. arXiv:1603.04467 [cs.DC], 2016.
- B. Bischl, G. Casalicchio, M. Feurer, F. Hutter, M. Lang, R. G. Mantovani, J. N. van Rijn, and J. Vanschoren. OpenML Benchmarking Suites. arXiv:1708.03731v2 [cs.LG], 2019.
- L. Buitinck, G. Louppe, M. Blondel, F. Pedregosa, A. Müller, O. Grisel, V. Niculae, P. Prettenhofer, A. Gramfort, J. Grobler, et al. API design for machine learning software: experiences from the scikit-learn project. In ECML PKDD LML Workshop, 2013.
- G. Casalicchio, J. Bossek, M. Lang, D. Kirchhoff, P. Kerschke, B. Hofner, H. Seibold, J. Vanschoren, and B. Bischl. OpenML: An R package to connect to the machine learning platform OpenML. Computational Statistics, 32(3), 2017.
- D. Dua and C. Graff. UCI machine learning repository, 2017. URL http://archive.ics.uci.edu/ml.
- M. Feurer, A. Klein, K. Eggensperger, J. T. Springenberg, M. Blum, and F. Hutter. Efficient and Robust Automated Machine Learning. In *Proc. of NeurIPS'15*, 2015.
- N. Fusi, R. Sheth, and M. Elibol. Probabilistic Matrix Factorization for Automated Machine Learning. In *Proc. of NeurIPS'18*. 2018.
- W. McKinney. Data Structures for Statistical Computing in Python. In Proc. of SciPy, 2010.
- R. S. Olson, W. La Cava, Z. Mustahsan, A. Varik, and J. H. Moore. Data-driven Advice for Applying Machine Learning to Bioinformatics Problems. In *Proc. of PSB'18*, pages 192–203, 2018.
- F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, et al. Scikit-learn: Machine Learning in Python. *JMLR*, 12, 2011.
- V. Perrone, R. Jenatton, M. Seeger, and C. Archambeau. Scalable Hyperparameter Transfer Learning. In Proc. of NeurIPS'18. 2018.
- B. Strang, P. van der Putten, J. N. van Rijn, and F. Hutter. Don't Rule Out Simple Models Prematurely: A Large Scale Benchmark Comparing Linear and Non-linear Classifiers in OpenML. In Proc. of IDA XVII, 2018.
- J. N. van Rijn. Massively Collaborative Machine Learning. PhD thesis, Leiden University, 2016.
- J. N. van Rijn and F. Hutter. Hyperparameter Importance Across Datasets. In Proc. of KDD'18, 2018.
- J. Vanschoren, J. van Rijn, B. Bischl, and L. Torgo. OpenML: Networked science in machine learning. SIGKDD, 15(2):49–60, 2014.
- P. Virtanen, R. Gommers, T. E. Oliphant, M. Haberland, T. Reddy, D. Cournapeau, E. Burovski, P. Peterson, W. Weckesser, J. Bright, et al. SciPy 1.0-Fundamental Algorithms for Scientific Computing in Python. arXiv:1907.10121 [CS:MS], 2019.